

Lecture 3:

Backpropagation and Neural Networks

Dmitry Yashunin
IntelliVision

Recall from last time: Linear Classifier

Image



$$s = f(x, W) = Wx + b$$

Diagram illustrating the linear classifier equation $s = f(x, W) = Wx + b$ with dimensions:

- s (scores): 10×1 (green box)
- $f(x, W)$ (function): 10×3072 (red box)
- W (weights or parameters): 3072×1 (blue box)
- x (image pixels): 10×1 (pink box)
- b (bias): 10×1 (pink box)

s – scores

W – weights or
parameters

x – image pixels

b – bias

Array of **32x32x3** numbers
(3072 numbers total)


CIFAR-10

50,000 training images


10,000 testing images

10 classes


Recall from last time: Linear classifier interpretation



$$f(x, W) = Wx + b$$



Example trained weights of a linear classifier trained on CIFAR-10:



Recall from last time: Loss functions

Image



x_i - image

y_i - label, element of a set $\{0, 1, \dots\}$

scores $s = f(x_i, W) = [s_0, \dots, s_{y_i}, \dots]$

Loss over dataset:

$$L = \frac{1}{N} \sum_{i=1}^N L_i$$

Multiclass SVM (hinge) loss:

$$L_i = \sum_{i \neq y_i} \max(0, s_i - s_{y_i} + 1)$$

Cross-entropy (softmax) loss:

$$L_i = -\log \frac{e^{s_{y_i}}}{\sum_j e^{s_j}}$$

Recall from last time: Regularization

Softmax or SVM

Full loss

$$L = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

λ - regularization strength (hyperparameter)

How do we find the best W ?

L2 regularization


$$R(W) = \sum_k \sum_l W_{k,l}^2$$

L1 regularization

$$R(W) = \sum_k \sum_l |W_{k,l}|$$

Elastic net (L1 + L2)

$$R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$$



Optimization



Optimization



Strategy #1: A first very bad idea solution: Random search

```
# assume X_train is the data where each column is an example (e.g. 3073 x 50,000)
# assume Y_train are the labels (e.g. 1D array of 50,000)
# assume the function L evaluates the loss function

bestloss = float("inf") # Python assigns the highest possible float value
for num in xrange(1000):
    W = np.random.randn(10, 3073) * 0.0001 # generate random parameters
    loss = L(X_train, Y_train, W) # get the loss over the entire training set
    if loss < bestloss: # keep track of the best solution
        bestloss = loss
        bestW = W
    print 'in attempt %d the loss was %f, best %f' % (num, loss, bestloss)

# prints:
# in attempt 0 the loss was 9.401632, best 9.401632
# in attempt 1 the loss was 8.959668, best 8.959668
# in attempt 2 the loss was 9.044034, best 8.959668
# in attempt 3 the loss was 9.278948, best 8.959668
# in attempt 4 the loss was 8.857370, best 8.857370
# in attempt 5 the loss was 8.943151, best 8.857370
# in attempt 6 the loss was 8.605604, best 8.605604
# ... (truncated: continues for 1000 lines)
```


Lets see how well this works on the test set...

```
# Assume X_test is [3073 x 10000], Y_test [10000 x 1]  
scores = Wbest.dot(Xte_cols) # 10 x 10000, the class scores for all test examples  
# find the index with max score in each column (the predicted class)  
Yte_predict = np.argmax(scores, axis = 0)  
# and calculate accuracy (fraction of predictions that are correct)  
np.mean(Yte_predict == Yte)  
# returns 0.1555
```

15.5% accuracy! not bad!
(state of the art is $\approx 96\%$)

Strategy #2: Follow the slope



Strategy #2: Follow the slope

In 1-dimension, the derivative of a function:

$$\frac{df(x)}{dx} = \lim_{h \rightarrow 0} \frac{f(x+h) - f(x)}{h}$$

In multiple dimensions, the **gradient** is the vector of partial derivatives along each dimension

current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

gradient dL/dW:

[?,
?,
?,
?,
?,
?,
?,
?,
?,...]

current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

W + h (first dim):

[0.34 + **0.0001**,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25322

gradient dL/dW:

[?,
?,
?,
?,
?,
?,
?,
?,
?,...]

current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

W + h (first dim):

[0.34 + **0.0001**,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25322

gradient dL/dW:

[-2.5,
?,
?,

$$(1.25322 - 1.25347)/0.0001 = -2.5$$

$$\frac{dL(W)}{dW} = \lim_{h \rightarrow 0} \frac{L(W + h) - L(W)}{h}$$

∴,
?,...]

current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

W + h (second dim):

[0.34,
-1.11 + **0.0001**,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25322

gradient dL/dW:

[-2.5,
?,
?,
?,
?,
?,
?,
?,
?,...]

current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

W + h (second dim):

[0.34,
-1.11 + **0.0001**,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25353

gradient dL/dW:

[-2.5,
0.6,
?,
?,
..., ...]


$$(1.25353 - 1.25347) / 0.0001 = 0.6$$

$$\frac{dL(W)}{dW} = \lim_{h \rightarrow 0} \frac{L(W + h) - L(W)}{h}$$

current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

W + h (third dim):

[0.34,
-1.11,
0.78 + **0.0001**,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

gradient dL/dW:

[-2.5,
0.6,
?,
?,
?,
?,
?,
?,
?,...]

current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

W + h (third dim):

[0.34,
-1.11,
0.78 + **0.0001**,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

gradient dL/dW:

[-2.5,
0.6,
0,
?,
?


$$(1.25347 - 1.25347)/0.0001 = 0$$

$$\frac{dL(W)}{dW} = \lim_{h \rightarrow 0} \frac{L(W + h) - L(W)}{h}$$

Can we do better?

The loss is just a function of W :

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda \sum_k W_k^2$$

$$L_i = \sum_{i \neq y_i} \max(0, s_i - s_{y_i} + 1)$$

$$s = f(x, W) = Wx + b$$

want $\nabla_W L$

Can we do better?


The loss is just a function of W :

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda \sum_k W_k^2$$

$$L_i = \sum_{i \neq y_i} \max(0, s_i - s_{y_i} + 1)$$

$$s = f(x, W) = Wx + b$$

want $\nabla_W L$



Can we do better?

The loss is just a function of W :

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda \sum_k W_k^2$$

$$L_i = \sum_{i \neq y_i} \max(0, s_i - s_{y_i} + 1)$$

$$s = f(x, W) = Wx + b$$

want $\nabla_W L$

Calculus!



current W:

[0.34,
-1.11,
0.78,
0.12,
0.55,
2.81,
-3.1,
-1.5,
0.33,...]

loss 1.25347

$dL/dW = \dots$
(some function
data and W)

gradient dL/dW :

[-2.5,
0.6,
0,
0.2,
0.7,
-0.5,
1.1,
1.3,
-2.1,...]

Recap

- Numerical gradient: approximate, slow, easy to write
- Analytic gradient: exact, fast, error-prone

In practice: Always use analytic gradient, but check implementation with numerical gradient. This is called a **gradient check**.


Gradient Descent

```
# Vanilla Gradient Descent
```

```
while True:
```

```
    weights_grad = evaluate_gradient(loss_fun, data, weights)
```

```
    weights += - step_size * weights_grad # perform parameter update
```



Stochastic Gradient Descent (SGD)

$$L(W) = \frac{1}{N} \sum_{i=1}^N L_i(x_i, y_i, W) + \lambda R(W)$$

Full sum expensive when N is large!

$$\nabla_W L(W) = \frac{1}{N} \sum_{i=1}^N \nabla_W L_i(x_i, y_i, W) + \lambda \nabla_W R(W)$$

Approximate sum using a **minibatch** of examples
32 / 64 / 128 common


```
# Vanilla Minibatch Gradient Descent
```

```
while True:
```

```
    data_batch = sample_training_data(data, 256) # sample 256 examples
```

```
    weights_grad = evaluate_gradient(loss_fun, data_batch, weights)
```



```
    weights += - step_size * weights_grad # perform parameter update
```



Example of optimization progress while training a neural network.

(Loss over mini-batches goes down over time.)

The effects of step size (or “learning rate”)



Stochastic Gradient Descent (SGD)

$$L(W) = \frac{1}{N} \sum_{i=1}^N L_i(x_i, y_i, W) + \lambda R(W)$$

Full sum expensive when
N is large!

$$\nabla_W L(W) = \frac{1}{N} \sum_{i=1}^N \nabla_W L_i(x_i, y_i, W) + \lambda \nabla_W R(W)$$

Approximate sum using a
minibatch of examples
32 / 64 / 128 common

```
# Vanilla Minibatch Gradient Descent
```

```
while True:
```


```
    data_batch = sample_training_data(data, 256) # sample 256 examples
```

```
    weights_grad = evaluate_gradient(loss_fun, data_batch, weights)
```


```
    weights += - step_size * weights_grad # perform parameter update
```

we will look at more
fancy update formulas
(momentum, Adagrad,
RMSProp, Adam, ...)

The effects of
different
update form
formulas




Interactive Web Demo time....




<http://vision.stanford.edu/teaching/cs231n-demos/linear-classify/>

Computational graphs



Convolutional Network


AlexNet



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g. $x = -2$, $y = 5$, $z = -4$



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

A magenta arrow points from this box to the input z of the multiplication node in the computational graph above.

Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

3

Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial q}$$

Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

$$\frac{\partial f}{\partial y}$$

Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$


Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$





Chain rule:


$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$


$$\frac{\partial f}{\partial x}$$
















Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$


Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



$$\begin{array}{lcl}
 f(x) = e^x & \rightarrow & \frac{df}{dx} = e^x \\
 f_a(x) = ax & \rightarrow & \frac{df}{dx} = a
 \end{array}$$


$$\begin{array}{lcl}
 f(x) = \frac{1}{x} & \rightarrow & \frac{df}{dx} = -1/x^2 \\
 f_c(x) = c + x & \rightarrow & \frac{df}{dx} = 1
 \end{array}$$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$

$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$

$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$

$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$




$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$




$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

$$f(w, x) = \frac{1}{1 + e^{-(w_0 x_0 + w_1 x_1 + w_2)}}$$

$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad \text{sigmoid function}$$

$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$




$$f(w, x) = \frac{1}{1 + e^{-(w_0 x_0 + w_1 x_1 + w_2)}}$$

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$


sigmoid function

$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$



Patterns in backward flow


add gate: gradient distributor



Patterns in backward flow

add gate: gradient distributor


Q: What is a **max** gate?



Patterns in backward flow

add gate: gradient distributor

max gate: gradient router




Patterns in backward flow

add gate: gradient distributor

max gate: gradient router

Q: What is a **mul** gate?




Patterns in backward flow


add gate: gradient distributor

max gate: gradient router


mul gate: gradient switcher




Gradients in branches (shared variables)



Gradients for vectorized code



Vectorized operations




Vectorized operations

$$\frac{\partial L}{\partial x} = \boxed{\frac{\partial f}{\partial x}} \frac{\partial L}{\partial f}$$

Jacobian matrix

4096-d
output vector



4096-d
output vector


Q: what is the
size of the
Jacobian matrix?

Vectorized operations

$$\frac{\partial L}{\partial x} = \boxed{\frac{\partial f}{\partial x}} \frac{\partial L}{\partial f}$$

Jacobian matrix


4096-d
output vector



4096-d
output vector

Q: what is the
size of the
Jacobian matrix?
[4096 x 4096!]

Vectorized operations



Q: what is the size of the Jacobian matrix?
[4096 x 4096!]

in practice we process an entire minibatch (e.g. 100) of examples at one time:


i.e. Jacobian would technically be a [409,600 x 409,600] matrix

Vectorized operations

$$\frac{\partial L}{\partial x} = \boxed{\frac{\partial f}{\partial x}} \frac{\partial L}{\partial f}$$

Jacobian matrix

4096-d
output vector




4096-d
output vector

Q: what is the
size of the
Jacobian matrix?
[4096 x 4096!]


Q2: what does it
look like?

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$
$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$
$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$



$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$
$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial f}{\partial q_i} = 2q_i$$

$$\nabla_q f = 2q$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial f}{\partial q_i} = 2q_i$$

$$\nabla_q f = 2q$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial q_k}{\partial W_{i,j}} = \mathbf{1}_{k=i}x_j$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial q_k}{\partial W_{i,j}} = \mathbf{1}_{k=i}x_j$$

$$\begin{aligned} \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\ &= \sum_k (2q_k)(\mathbf{1}_{k=i}x_j) \\ &= 2q_i x_j \end{aligned}$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial q_k}{\partial W_{i,j}} = \mathbf{1}_{k=i} x_j$$

$$\begin{aligned} \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\ &= \sum_k (2q_k) (\mathbf{1}_{k=i} x_j) \\ &= 2q_i x_j \end{aligned}$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$



$$\nabla_W f = 2q \cdot x^T$$


$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial q_k}{\partial W_{i,j}} = \mathbf{1}_{k=i} x_j$$

$$\begin{aligned} \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\ &= \sum_k (2q_k) (\mathbf{1}_{k=i} x_j) \\ &= 2q_i x_j \end{aligned}$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$



$$\nabla_W f = 2q \cdot x^T$$

Always check: The gradient with respect to a variable should have the same shape as the variable


$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial q_k}{\partial W_{i,j}} = \mathbf{1}_{k=i}x_j$$

$$\begin{aligned} \frac{\partial f}{\partial W_{i,j}} &= \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial W_{i,j}} \\ &= \sum_k (2q_k)(\mathbf{1}_{k=i}x_j) \\ &= 2q_i x_j \end{aligned}$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$




$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial q_k}{\partial x_i} = W_{k,i}$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$



$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$


$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$

$$\frac{\partial q_k}{\partial x_i} = W_{k,i}$$

$$\frac{\partial f}{\partial x_i} = \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial x_i}$$

$$\frac{\partial f}{\partial x_i} = \sum_k 2q_k W_{k,i}$$

A vectorized example: $f(x, W) = ||W \cdot x||^2 = \sum_{i=1}^n (W \cdot x)_i^2$



$$\nabla_x f = 2W^T \cdot q$$

$$q = W \cdot x = \begin{pmatrix} W_{1,1}x_1 + \cdots + W_{1,n}x_n \\ \vdots \\ W_{n,1}x_1 + \cdots + W_{n,n}x_n \end{pmatrix}$$

$$f(q) = ||q||^2 = q_1^2 + \cdots + q_n^2$$


$$\frac{\partial q_k}{\partial x_i} = W_{k,i}$$

$$\frac{\partial f}{\partial x_i} = \sum_k \frac{\partial f}{\partial q_k} \frac{\partial q_k}{\partial x_i}$$

$$\frac{\partial f}{\partial x_i} = \sum_k 2q_k W_{k,i}$$


Modularized implementation: forward / backward API

Graph (or Net) object (*rough psuedo code*)



```
class ComputationalGraph(object):  
    #...  
    def forward(inputs):  
        # 1. [pass inputs to input gates...]  
        # 2. forward the computational graph:  
        for gate in self.graph.nodes_topologically_sorted():  
            gate.forward()  
        return loss # the final gate in the graph outputs the loss  
    def backward():  
        for gate in reversed(self.graph.nodes_topologically_sorted()):  
            gate.backward() # little piece of backprop (chain rule applied)  
        return inputs_gradients
```

Modularized implementation: forward / backward API



(x,y,z are scalars)

```
class MultiplyGate(object):  
    def forward(x,y):  
        z = x*y  
        return z  
    def backward(dz):  
        # dx = ... #todo  
        # dy = ... #todo  
        return [dx, dy]
```


$$\frac{\partial L}{\partial z}$$

An arrow points from this box to the `dz` parameter in the `backward` method of the `MultiplyGate` class.

$$\frac{\partial L}{\partial x}$$

An arrow points from this box to the `dx` element in the `return [dx, dy]` statement of the `backward` method of the `MultiplyGate` class.

Modularized implementation: forward / backward API




(x,y,z are scalars)

```
class MultiplyGate(object):  
    def forward(x,y):  
        z = x*y  
        self.x = x # must keep these around!  
        self.y = y  
        return z  
    def backward(dz):  
        dx = self.y * dz # [dz/dx * dL/dz]  
        dy = self.x * dz # [dz/dy * dL/dz]  
        return [dx, dy]
```

Example: Caffe layers


























Branch: **master** **caffe** / **src** / **caffe** / **layers** /

Create new fileUpload filesFind fileHistory

 **shelhamer** committed on **GitHub** Merge pull request **#4630** from **BiGene/load_hdf5_fix** **...**

Latest commit **e687a71** 21 days ago

..

 absval_layer.cpp	dismantle layer headers	a year ago
 absval_layer.cu	dismantle layer headers	a year ago
 accuracy_layer.cpp	dismantle layer headers	a year ago
 argmax_layer.cpp	dismantle layer headers	a year ago
 base_conv_layer.cpp	enable dilated deconvolution	a year ago
 base_data_layer.cpp	Using default from proto for prefetch	3 months ago
 base_data_layer.cu	Switched multi-GPU to NCCL	3 months ago
 batch_norm_layer.cpp	Add missing spaces besides equal signs in batch_norm_layer.cpp	4 months ago
 batch_norm_layer.cu	dismantle layer headers	a year ago
 batch_reindex_layer.cpp	dismantle layer headers	a year ago
 batch_reindex_layer.cu	dismantle layer headers	a year ago
 bias_layer.cpp	Remove incorrect cast of gemm int arg to Dtype in BiasLayer	a year ago
 bias_layer.cu	Separation and generalization of ChannelwiseAffineLayer into BiasLayer	a year ago
 bnll_layer.cpp	dismantle layer headers	a year ago
 bnll_layer.cu	dismantle layer headers	a year ago
 concat_layer.cpp	dismantle layer headers	a year ago
 concat_layer.cu	dismantle layer headers	a year ago
 contrastive_loss_layer.cpp	dismantle layer headers	a year ago
 contrastive_loss_layer.cu	dismantle layer headers	a year ago
 conv_layer.cpp	add support for 2D dilated convolution	a year ago
 conv_layer.cu	dismantle layer headers	a year ago
 crop_layer.cpp	remove redundant operations in Crop layer (#5138)	2 months ago
 crop_layer.cu	remove redundant operations in Crop layer (#5138)	2 months ago
 cudnn_conv_layer.cpp	dismantle layer headers	a year ago
 cudnn_conv_layer.cu	Add cuDNN v5 support, drop cuDNN v3 support	11 months ago

=



Caffe Sigmoid Layer

```
1 #include <cmath>
2 #include <vector>
3
4 #include "caffe/layers/sigmoid_layer.hpp"
5
6 namespace caffe {
7
8 template <typename Dtype>
9 inline Dtype sigmoid(Dtype x) {
10     return 1. / (1. + exp(-x));
11 }
12
13 template <typename Dtype>
14 void SigmoidLayer<Dtype>::Forward_cpu(const vector<Blob<Dtype>*>& bottom,
15     const vector<Blob<Dtype>*>& top) {
16     const Dtype* bottom_data = bottom[0]->cpu_data();
17     Dtype* top_data = top[0]->mutable_cpu_data();
18     const int count = bottom[0]->count();
19     for (int i = 0; i < count; ++i) {
20         top_data[i] = sigmoid(bottom_data[i]);
21     }
22 }
23
24 template <typename Dtype>
25 void SigmoidLayer<Dtype>::Backward_cpu(const vector<Blob<Dtype>*>& top,
26     const vector<bool>& propagate_down,
27     const vector<Blob<Dtype>*>& bottom) {
28     if (propagate_down[0]) {
29         const Dtype* top_data = top[0]->cpu_data();
30         const Dtype* top_diff = top[0]->cpu_diff();
31         Dtype* bottom_diff = bottom[0]->mutable_cpu_diff();
32         const int count = bottom[0]->count();
33         for (int i = 0; i < count; ++i) {
34             const Dtype sigmoid_x = top_data[i];
35             bottom_diff[i] = top_diff[i] * sigmoid_x * (1. - sigmoid_x);
36         }
37     }
38 }
39
40 #ifndef CPU_ONLY
41 STUB_GPU(SigmoidLayer);
42 #endif
43
44 INSTANTIATE_CLASS(SigmoidLayer);
45
46 } // namespace caffe
```

forward()

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$


backward()

$$(1 - \sigma(x)) \sigma(x) * \text{top_diff} \text{ (chain rule)}$$

Backpropagation summary

- neural nets will be very large: impractical to write down gradient formula by hand for all parameters
- **backpropagation** = recursive application of the chain rule along a computational graph to compute the gradients of all inputs/parameters/intermediates
- implementations maintain a graph structure, where the nodes implement the **forward()** / **backward()** API
- **forward**: compute result of an operation and save any intermediates needed for gradient computation in memory
- **backward**: apply the chain rule to compute the gradient of the loss function with respect to the inputs

Neural Networks



Neural networks: without the brain stuff

(**Before**) Linear score function: $f = Wx$

Neural networks: without the brain stuff


(Before) Linear score function: $f = Wx$

(Now) 2-layer Neural Network: $f = W_2 \max(0, W_1 x)$

Neural networks: without the brain stuff

(**Before**) Linear score function: $f = Wx$

(**Now**) 2-layer Neural Network: $f = W_2 \max(0, W_1 x)$




hidden layer

Neural networks: without the brain stuff

(**Before**) Linear score function: $f = Wx$

(**Now**) 2-layer Neural Network: $f = W_2 \max(0, W_1 x)$



Neural networks: without the brain stuff

(**Before**) Linear score function: $f = Wx$


(**Now**) 2-layer Neural Network: $f = W_2 \max(0, W_1 x)$
or we can go deeper


3-layer Neural Network $f = W_3 \max(0, W_2 \max(0, W_1 x))$


Full implementation of training a 2-layer Neural Network needs ~20 lines:



```
1  import numpy as np
2  from numpy.random import randn
3
4  N, D_in, H, D_out = 64, 1000, 100, 10
5  x, y = randn(N, D_in), randn(N, D_out)
6  w1, w2 = randn(D_in, H), randn(H, D_out)
7
8  for t in range(2000):
9      h = 1 / (1 + np.exp(-x.dot(w1)))
10     y_pred = h.dot(w2)
11     loss = np.square(y_pred - y).sum()
12     print(t, loss)
13
14     grad_y_pred = 2.0 * (y_pred - y)
15     grad_w2 = h.T.dot(grad_y_pred)
16     grad_h = grad_y_pred.dot(w2.T)
17     grad_w1 = x.T.dot(grad_h * h * (1 - h))
18
19     w1 -= 1e-4 * grad_w1
20     w2 -= 1e-4 * grad_w2
```


Biological neuron and artificial neuron












sigmoid activation function

$$\frac{1}{1 + e^{-x}}$$





```
class Neuron:
```

```
# ...
```

```
def neuron_tick(inputs):
```

```
    """ assume inputs and weights are 1-D numpy arrays and bias is a number """
```

```
    cell_body_sum = np.sum(inputs * self.weights) + self.bias
```

```
    firing_rate = 1.0 / (1.0 + math.exp(-cell_body_sum)) # sigmoid activation function
```

```
    return firing_rate
```

Be very careful with your brain analogies!


Biological Neurons:

- Many different types
- Dendrites can perform complex non-linear computations
- Synapses are not a single weight but a complex non-linear dynamical system
- Rate code may not be adequate

Activation functions


Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




tanh

$$\tanh(x)$$




ReLU

$$\max(0, x)$$



Leaky ReLU

$$\max(0.1x, x)$$




Maxout


$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

ELU


$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$



Neural networks: Architectures




“2-layer Neural Net”, or
“1-hidden-layer Neural Net”



“3-layer Neural Net”, or
“2-hidden-layer Neural Net”


“Fully-connected” layers

Example feed-forward computation of a neural network



```
# forward-pass of a 3-layer neural network:  
f = lambda x: 1.0/(1.0 + np.exp(-x)) # activation function (use sigmoid)  
x = np.random.randn(3, 1) # random input vector of three numbers (3x1)  
h1 = f(np.dot(W1, x) + b1) # calculate first hidden layer activations (4x1)  
h2 = f(np.dot(W2, h1) + b2) # calculate second hidden layer activations (4x1)  
out = np.dot(W3, h2) + b3 # output neuron (1x1)
```

Demo time



Setting the number of layers and their sizes

Setting regularization

<http://cs.stanford.edu/people/karpathy/convnetjs/demo/classify2d.html>

Summary

- we arrange neurons into fully-connected layers
- The abstraction of a **layer** has the nice property that it allows us to use efficient vectorized code (e.g. matrix multiplies)
- Neural networks are not really *neural*
- Next time: **Convolutional Neural Networks**