

Correction

Correction: Grabow et al. Triggering and Characterisation of Realistic Internal Short Circuits in Lithium-Ion Pouch Cells—A New Approach Using Precise Needle Penetration. *Batteries* 2023, 9, 496

Jens Grabow ^{1,*} , Jacob Klink ¹ , Nury Orazov ¹ , Ralf Bengler ¹ , Ines Hauer ²  and Hans-Peter Beck ³

¹ Research Center Energy Storage Technologies, Clausthal University of Technology, Am Stollen 19A, D-38640 Goslar, Germany

² Institute of Electrical Power Engineering and Electrical Energy Engineering, Clausthal University of Technology, Leibnizstraße 28, D-38678 Clausthal-Zellerfeld, Germany

³ Energy Research Centre Lower Saxony, Am Stollen 19A, D-38640 Goslar, Germany

* Correspondence: jens.grabow@tu-clausthal.de

The authors wish to make the following corrections to their paper [1]:

Error in Table

In the original publication, there was a mistake in Table 9, as published. The temperatures of $T - 9_{\max}^*$ were incorrect. The corrected Table 9 appears below. The authors state that the scientific conclusions are unaffected. This correction was approved by the Academic Editor. The original publication has also been updated.

Table 9. List of the key features of six needle penetrations with the experimental conditions: 100% SOC and a penetration depth ΔX of 100 μm .

Feature	Unit	100% SOC, Penetration Depth after First ISC = 100 μm					
		3.1	3.2	3.3	3.4	3.5	3.6
R_{\min} , ISC	Ω	0.201	0.192	0.012	0.011	0.009	0.007
I_{\max} , ISC	A	20.4	21.3	260.5	289.3	312.1	362.5
P_{\max} , ISC	W	83.6	87.2	812.1	870.9	909.7	971.5
t_{\max} , ISC	s	676	348	941	362	327	646
SOC _{max} , ISC	%	>99	>99	98.7	>98.4	98.5	96.0
$T - 9_{\max}^*$	$^{\circ}\text{C}$	165	193	540	555	556	607
ISC-Type	-	Ila	Ila	Ilb (TR)	Ilb (TR)	Ilb (TR)	Ilb (TR)
$t_{\text{charact. ISC}}$	s	2188	731	948	371	337	655
SOC _{charact. ISC}	%	84.7	89.7	98.0	96.1	96.0	93.5
m_{loss}	%	0	0.4	53.8	51.6	52.7	57.6

Reference

- Grabow, J.; Klink, J.; Orazov, N.; Bengler, R.; Hauer, I.; Beck, H.-P. Triggering and Characterisation of Realistic Internal Short Circuits in Lithium-Ion Pouch Cells—A New Approach Using Precise Needle Penetration. *Batteries* **2023**, *9*, 496. [[CrossRef](#)]

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.



Citation: Grabow, J.; Klink, J.; Orazov, N.; Bengler, R.; Hauer, I.; Beck, H.-P.

Correction: Grabow et al. Triggering and Characterisation of Realistic Internal Short Circuits in Lithium-Ion Pouch Cells—A New Approach Using Precise Needle Penetration. *Batteries*

2023, 9, 496. *Batteries* **2024**, *10*, 291.

<https://doi.org/10.3390/batteries10080291>

batteries10080291

Received: 25 July 2024

Accepted: 30 July 2024

Published: 19 August 2024



Copyright: © 2024 by the authors. Licensee MDPI, Basel, Switzerland.

This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).