

2) (10 pts) DSN (Sorting)

For this problem, fill in the blank to finish the stable (elements with the same values are kept in their original order) quicksort on a linked list. We are using the head of the linked list as a pivot. You can assume that the following linked list functions have all been implemented and take $O(1)$ operations.

Note: Each blank is worth one point and involves either making calls or filling in parameters to the functions whose prototypes and descriptions are given below.

```
typedef struct Node {  
    int value;  
    struct Node * next;  
} Node;
```

```
typedef struct List {  
    Node* front;  
    Node* back;  
} List;
```

```
void addToTail(List * list, Node * node); // Add to tail
```

```
// Returns a list that is the combination of 2 given lists.  
List * merge(List * front, List * back);
```

```
Node* getAndRemoveHead(List * list); // Removes and returns the head  
List* createEmptyList(); // Returns dynamically allocated empty List  
int isEmpty(List * list); // Returns 1 if empty and 0 otherwise
```

```
// Sort code on next page
```

```
List * sort(List * lst) {  
  
    if (_____ (lst)) return lst;  
  
    Node * pivot = getAndRemoveHead(lst);  
  
    List * first = _____ ();  
  
    List * last = _____ ();  
  
    List * middle = createEmptyList();  
  
    addToTail(middle, pivot);  
  
    while (!isEmpty(lst)) {  
  
        Node * cur = _____ (lst);  
  
        if (cur->value < pivot->value)  
            addToTail(_____, cur);  
        else if (cur->value == pivot->value)  
            addToTail(_____, cur);  
        else  
            addToTail(_____, cur);  
    }  
  
    first = sort(_____);  
  
    last = sort(_____);  
  
    first = merge(first, middle);  
    first = merge(first, last);  
    free(middle);  
    free(last);  
    free(lst);  
  
    return _____;  
}
```