

1. 查询用户注册手机是否存在

加密主Key:1126

key 的生成规则, 比如手机号码 13397186156 就是取手机的最后4位 $6+1 = 7$
 $1+1 = 2$ $5+2 = 7$ $6+6 = 12$ 就是 C (10-C 11-C 12-C 类推) 所以key 就是 727C 传入参数

http://113.57.133.83:1982/apps_android.php?
url={"method":"checkiphoneUserinfor","u_iphone":"13006147142","key":
"xxxxx"}

方法名: checkiphoneUserinfor

参数: u_iphone 手机号码 key 加密key

返回值:

成功: {"0"}

失败: {"1"}

2. 校验验证码

http://113.57.133.83:1982/apps_android.php?
url={"method":"checkphonemassage","u_iphone":"13006147142","Code":"1
1111"}

方法名: checkphonemassage

参数: u_iphone 手机号码 Code 短信验证码

返回值:

成功: {"0"}

失败: {"1"}

3. 注册接口

http://113.57.133.83:1982/apps_android.php?
url={"method":"resaveUserinfor","u_realname":"宋
玮","u_sex":"1","u_cbcid":"420107198208053714","u_emil":"songwei8283
@qq.com","u_name":"songwei8285","u_log_password":"123456","u_v_id":
"1","u_iphone":"13006147142"}

方法名: resaveUserinfor

参数: u_realname,真实姓名 u_sex:性别(0,1) u_cbcid,省份证号 u_emil 邮箱
u_name 用户名 u_log_password 密码 u_v_id 用户vip等级 注册默认1 u_iphone
手机

返回值:

成功: {"State":"0"}

失败: {"State":"error"}

用户名重复: {"State":"2"}

手机重复: {"State":"3"}

邮箱重复: {"State":"4"}

同一身份证号码不能重复注册3个账号: {"State":"5"}

4. 登陆

http://113.57.133.83:1982/apps_android.php?
url={"method":"LoginUserinfor","u_logname":"songwei","u_log_password":
"123456"}

方法名称: LoginUserinfor

参数: u_logname 登录用户名 u_log_password 密码

返回结果:

成功: {"userToken": "4f525238-88bf-42e4-b32d-96b1d914c820"}
(token需要客户端保存, 作为用户权限唯一的令牌, 在需要获取用户权限的接口调用中必须传给服务器接口)

失败:

{"State", "3"} 禁止登陆, 联系管理员

{"State", "4"} 用户以挂失

5. 获取用户基本信息

http://113.57.133.83:1982/apps_android.php?

url={"method": "ShowUserinfor", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427"}

方法名称: ShowUserinfor

参数: userToken 用户令牌

成功:

失败:

{"State": "1"}

6. 显示用户卡片

参数筛选条件: 商户名称, 卡号, 卡状态, 余额排序 (程序数组排序)

全部数据:

http://113.57.133.83:1982/apps_android.php?

url={"method": "ShowUtocard", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427"}

卡号筛选:

http://113.57.133.83:1982/apps_android.php?

url={"method": "ShowUtocard", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427"}

方法名称: ShowUtocard

可选筛选参数: "u_card": "AA00000000000001" 卡号筛选 "card_state": 0 卡号状态筛选 (是否冻结 0, 1) "b_jname": "荆楚甲鱼" 商户名称筛选

返回值:

成功:

```
{"showtable": [{"u_t_cid": 3, "userinfor": 16, "username": "宋伟", "uiphone": "13006147142", "u_card": "AA00000000000001", "b_prefilx": "AA000000", "b_jname": "荆楚甲鱼", "b_cording": "2.jpg", "card_state": 0, "card_balance": "691.26", "b_c_name": "武汉市", "@datatype": "java.util.UtocardV0"}, {"u_t_cid": 4, "userinfor": 16, "username": "宋伟", "uiphone": "13006147142", "u_card": "AA00000100000001", "b_prefilx": "AA000001", "b_jname": "武汉银讯", "b_cording": "1.jpg", "card_state": 0, "card_balance": "0.00", "b_c_name": "武汉市", "@datatype": "java.util.UtocardV0"}]}
```

7. 选择消费卡

http://113.57.133.83:1982/apps_android.php?

url={"method": "updateUserinfor", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427", "u_prefix": "String", "u_pre_num": "1"}

方法名称: updateUserinfor

参数: userToken 用户令牌 u_prefix 消费卡卡柄 u_pre_num 卡号

返回结果:

成功: {" State": "0"}

失败: {" State": "1"}

8. 消费记录

http://113.57.133.83:1982/apps_android.php?

url={"method": "ShowConsumption", "pre_r_id": "1", "u_iphone": "1300", "card": "aa300", "frist": "0", "pageNum": "0", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427", "con_state": "0", "con_nor": "12", "con_pos": "532", "b_no": "d2445", "scon_amount": "11.00", "mcon_amount": "15.00", "scon_tmd": "2014-1-2", "mcon_tmd": "2014-2-4"}

方法名称: ShowConsumption

可选筛选参数 商户名称, 消费时间 (区间, 范围), 卡号 [注意分页参数 frist, pageNum 如果不用分页全部传0,0]

返回结果:

失败: {" State": "0"}

成功: json 串

9. 充值记录

查找条件: 商户名称, 充值时间 (区间, 范围), 卡号, 充值方式, 结算状态

http://113.57.133.83:1982/apps_android.php?

url={"method": "ShowPreRecords", "b_id": "1", "u_iphone": "1300", "card": "aa300", "pre_nor": "AA1234", "samount": "200", "mamount": "300", "spre_r_tmd": "2014-1-1", "mpre_r_tmd": "2014-2-5", "frist": "0", "pageNum": "0", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427", "acc_r_tmd": "2014-02-02", "u_id": "11", "acc_state": "0"}

方法名称: ShowPreRecords

可选筛选参数 商户名称, 消费时间 (区间, 范围), 卡号 [注意分页参数 frist, pageNum 如果不用分页全部传0,0]

返回结果:

失败: {" State": "0"}

成功: json 串

10. 修改登陆和交易密码

http://113.57.133.83:1982/apps_android.php?

url={"method": "ResetUPwd", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427", "u_tran_password": "654321", "newu_tran_password": "654321"}

方法名称: ResetUPwd

参数: u_tran_password 交易密码

成功: {"State": "0"}

失败: {" State": "error"} 原始交易密码错误: {" State": "1"}

访问接口:

http://113.57.133.83:1982/apps_android.php?

url={"method": "ResetUPwd", "userToken": "693c077e-5ed2-4d37-9116-6dfac8d84427", "u_log_password": "654321", "newu_log_password": "654321"}

方法名称: ResetUPwd

参数: u_log_password 登录密码

成功: {"State":"0"}

失败: {"State":"error"} 原始登录密码错误: {"State":"1"}

11. 挂失

http://113.57.133.83:1982/apps_android.php?

url={"method":"updateloss","userToken":"693c077e-5ed2-4d37-9116-6dfac8d84427","u_realname":"宋玮","u_loss_state":"1","u_cbcid":"420107198208053713","u_loss_datetime":""}

方法名称: updateloss

参数: userToken 用户令牌 u_realname 用户名 u_loss_state 挂失状态 u_cbcid 省份证号 u_loss_datetime 填"" 空串

成功: {"State":"0"}

失败或填写信息有误: {"State":"error"} 验证信息不正确: {"State":"1"}

12. 一级分类

http://113.57.133.83:1982/apps_android.php?

url={"method":"showBtype"}

方法名称: showBtype

参数: 空 (二级分类这次需求不提供)

13. 统计用户是否有这商户的预付费卡

http://113.57.133.83:1982/apps_android.php?

url={"method":"countcard","b_id":"1","userToken":"693c077e-5ed2-4d37-9116-6dfac8d84427"}

方法名称: countcard

参数: b_id 商户id userToken 用户令牌

返回结果:

成功: {"State":"1"} 有一张卡 {"State":"0"} 没有该商户卡

失败: {"State":"error"}

开发人员: 宋玮, 其它说明: 因为要返回POS的个数, 因此在ResponseJSONController 填 加了count方法

14. 用户注册新卡

http://113.57.133.83:1982/apps_android.php?

url={"method":"Regcard","b_id":"1","userToken":"693c077e-5ed2-4d37-9116-6dfac8d84427"}

方法名称: Regcard

参数: b_id 需要注册卡的商户id userToken 用户令牌

返回结果:

成功: {"State":"0"} 注册成功 {"State":"1"} 有一张卡

失败: {"State":"error"}

开发人员: 宋玮, 其它说明: 因为要返回POS的个数。

15. 查询商户列表

查询条件: 一级分类\二级分类\省\市\区\热门分类\附近 (地图)\商圈\商户名称

http://113.57.133.83:1982/apps_android.php?
url={"method":"ShowBinfor","b_username":"String","b_no":"String","b_jname":"b_jname","b_prefix":"b_prefix","b_cordnum":"b_cordnum","b_id":"1","b_type":"1","b_2type":"1","b_htype":"1","b_province":"1","b_city":"1","b_district":"1","b_cbd":"1","u_vip":"1","b_crcle":"1","b_stat":"1","b_h_state":"1","b_t_state":"1","frist":"0","pageNum":"0"}

方法名称: ShowBinfor

筛选查询参数: 这里参数比较多就不一一列举了, 具体线上沟通

返回结果:

成功: {"showtable":[{"b_id":1,"b_username":"songwei","b_password":null,"b_loginphone":"13006147142","b_msgyzm":"aaaaaa","b_msgdatetime":"2014-06-01 00:00:00.0","b_name":"sw","b_jname":"s","b_cording":"ds","b_cordnum":"1","btype":"1","b2type":"2","bhtype":"2","bprovince":"1","bcity":"2","bdistrict":"2","bcbd":"2","bcrcle":"3","b_coordinate":"2","b_contacts":"12","b_stat":0,"b_h_state":null,"b_t_state":null,"b_sort":null,"b_details":null,"b_fraction":null,"b_vip":null,"b_z":null,"b_in":null,"b_c":null,"b_recharge":null,"b_prefix":null,"b_rate":null,"b_liq":1,"b_regdate":null,"b_ad":null,"b_img":null,"b_logo":null,"b_back":null,"b_agreement":null,"b_no":null,"b_man":null,"cord_num":null,"b_m_phone":null,"b_rechargem":null,"b_consumption":null,"b_re_num":null,"b_con_num":null}]}
失败: {"State":"1"}

16. 商户总数

http://113.57.133.83:1982/apps_android.php?
url={"method":"countbinfor","b_username":"String","b_no":"String","b_jname":"b_jname","b_prefix":"b_prefix","b_cordnum":"b_cordnum","b_id":"1","b_type":"1","b_2type":"1","b_htype":"1","b_province":"1","b_city":"1","b_district":"1","b_cbd":"1","u_vip":"1","b_crcle":"1","b_stat":"1","b_h_state":"1","b_t_state":"1"}

方法名称: countbinfor

筛选查询参数: 这里参数比较多就不一一列举了, 具体线上沟通

成功: {"State":"10"}

失败: {"State":"error"}

开发人员: 宋玮, 其它说明: 因为要返回个数, 因此在ResponseJSONController填 加了count方法