



GALAHAD

SILS

PACKAGE SPECIFICATION

GALAHAD Optimization Library version 2.2

1 SUMMARY

This package **solves a sparse symmetric system of linear equations**. Given a sparse symmetric matrix $\mathbf{A} = \{a_{ij}\}_{n \times n}$, and an n -vector \mathbf{b} or a matrix $\mathbf{B} = \{b_{ij}\}_{n \times r}$, this subroutine solves the system $\mathbf{Ax} = \mathbf{b}$ or the system $\mathbf{AX} = \mathbf{B}$. The matrix \mathbf{A} need not be definite. There is an option for iterative refinement.

The method used is a direct method based on a sparse variant of Gaussian elimination and is discussed further by Duff and Reid, *ACM Trans. Math. Software* **9** (1983), 302-325.

ATTRIBUTES — Versions: GALAHAD_SILS_single, GALAHAD_SILS_double. **Remark:** GALAHAD_SILS is a Fortran 90 encapsulation of the HSL Fortran 77 package MA27, that offers some additional facilities. The user interface is designed to be equivalent to the more recent HSL package HSL_MA57, so the two packages may be used interchangeably. **Uses:** GALAHAD_SMT, MA27. **Date:** April 2001. **Origin:** Interface by N. I. M. Gould, Rutherford Appleton Laboratory, documentation follows that of I.S. Duff and J.K. Reid, *ibid.* **Language:** Fortran 95 + TR 15581 or Fortran 2003.

2 HOW TO USE THE PACKAGE

2.1 Calling sequences

Access to the package requires a USE statement such as

Single precision version

```
USE GALAHAD_SILS_single
```

Double precision version

```
USE GALAHAD_SILS_double
```

If it is required to use both modules at the same time, the derived types SMT_TYPE, SILS_CONTROL, SILS_AINFO, SILS_FINFO, SILS_SINFO, and SILS_FACTORS, (Section 2.2) and the subroutines SILS_INITIALIZE, SILS_ANALYSE, SILS_FACTORIZE, SILS_SOLVE, SILS_FINALIZE, (Section 2.3) SILS_ENQUIRE, SILS_ALTER_D, and SILS_PART-SOLVE (Section 2.5) must be renamed on one of the USE statements.

There are five principal subroutines for user calls (see Section 2.5 for further features):

The subroutine SILS_INITIALIZE must be called to initialize the structure for the factors. It may also be called to set default values for the components of the control structure. If non-default values are wanted for any of the control components, the corresponding components should be altered after the call to SILS_INITIALIZE.

SILS_ANALYSE accepts the pattern of \mathbf{A} and chooses pivots for Gaussian elimination using a selection criterion to preserve sparsity. It subsequently constructs subsidiary information for actual factorization by SILS_FACTORIZE. The user may provide the pivot sequence, in which case only the necessary information for SILS_FACTORIZE will be generated.

SILS_FACTORIZE factorizes a matrix \mathbf{A} using the information from a previous call to SILS_ANALYSE. The actual pivot sequence used may differ from that of SILS_ANALYSE if \mathbf{A} is not definite.

SILS_SOLVE uses the factors generated by SILS_FACTORIZE to solve a system of equations with one ($\mathbf{Ax} = \mathbf{b}$) or several ($\mathbf{AX} = \mathbf{B}$) right-hand sides, or to improve a given solution or set of solutions by iterative refinement.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

`SILS_FINALIZE` reallocates the arrays held inside the structure for the factors to have size zero. It should be called when all the systems involving its matrix have been solved unless the structure is about to be used for the factors of another matrix.

2.2 The derived data types

Six derived data types are accessible from the package.

2.2.1 The derived data type for holding the matrix

The derived data type `SMT_TYPE` is used to hold the matrix **A**. The components of `SMT_TYPE` are:

- N** is a scalar variable of type default `INTEGER`, that holds the order n of the matrix **A**. **Restriction:** $N \geq 1$.
- NE** is a scalar variable of type default `INTEGER`, that holds the number of matrix entries. **Restriction:** $NE \geq 0$.
- VAL** is a rank-one allocatable array of type default `REAL` (double precision in `GALAHAD_SILS_double`), and dimension at least **NE**, that holds the values of the entries. Each pair of off-diagonal entries $a_{ij} = a_{ji}$ is represented as a single entry. Duplicated entries are summed.
- ROW** is a rank-one allocatable array of type default `INTEGER`, and dimension at least **NE**, that holds the row indices of the entries.
- COL** is a rank-one allocatable array of type default `INTEGER`, and dimension at least **NE**, that holds the column indices of the entries.

2.2.2 The derived data type for holding control parameters

The derived data type `SILS_CONTROL` is used to hold controlling data. Default values may be obtained by calling `SILS_initialize` (see Section 2.3.1). The components of `SILS_CONTROL` are:

- LP** is an `INTEGER` scalar used by the subroutines as the output stream for error messages. If it is negative, these messages will be suppressed. The default value is 6.
- WP** is an `INTEGER` scalar used by the subroutines as the output stream for warning messages. If it is negative, these messages will be suppressed. The default value is 6.
- MP** is an `INTEGER` scalar used by the subroutines as the output stream for diagnostic printing. If it is negative, these messages will be suppressed. The default value is 6.
- SP** is an `INTEGER` scalar used by the subroutines as the output stream for statistics. If it is negative, these messages will be suppressed. The default value is -1.
- LDIAG** is an `INTEGER` scalar used by the subroutines to control diagnostic printing. If **LDIAG** is less than 1, no messages will output. If the value is 1, only error messages will be printed. If the value is 2, then error and warning messages will be printed. If the value is 3, scalar data and a few entries of array data on entry and exit from each subroutine will be printed. If the value is greater than 3, all data will be printed on entry and exit. The default value is 2.
- LA** is an `INTEGER` scalar used by `SILS_FACTORIZE`. If $LA \geq \text{NRLNEC}$ (see Section 2.2.3), the real array that holds data for the factors is reallocated to have size **LA**. Otherwise, the array is not reallocated unless its size is less than **NRLNEC**, in which case it is reallocated with size **NRLTOT** (see Section 2.2.3). The default value is 0.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

LIW is an INTEGER scalar used by `SILS_FACTORIZE`. If $LIW \geq NIRNEC$ (see Section 2.2.3), the integer array that holds data for the factors is reallocated to have size `LIW`. Otherwise, the array is not reallocated unless its size is less than `NIRNEC`, in which case it is reallocated with size `NIRTOT` (see Section 2.2.3). The default value is 0.

MAXLA is an INTEGER scalar used by `SILS_FACTORIZE`. An error return occurs if the real array that holds data for the factors is too small and reallocating it to have size changed by the factor `MULTIPLIER` would make its size greater than `MAXLA`. The default value is `HUGE(0)`.

MAXLIW is an INTEGER scalar used by `SILS_FACTORIZE`. An error return occurs if the integer array that holds data for the factors is too small and reallocating it to have size changed by the factor `MULTIPLIER` would make its size greater than `MAXLIW`. The default value is `HUGE(0)`.

MULTIPLIER is a REAL (double precision in `GALAHAD_SILS_double`) scalar used by `SILS_FACTORIZE` when a real or integer array that holds data for the factors is too small. The array is reallocated with its size changed by the factor `MULTIPLIER`. The default value is 2.0.

REDUCE is a REAL (double precision in `GALAHAD_SILS_double`) scalar that reduces the size of previously allocated internal workspace arrays if they are larger than currently required by a factor of `REDUCE` or more. The default value is 2.0.

NEMIN is an INTEGER scalar used by `SILS_ANALYSE` for the minimum number of eliminations in a step that is automatically accepted. If two adjacent steps can be combined and each has fewer eliminations, they are combined. The default value is 1.

THRESH is an INTEGER scalar used by `SILS_ANALYSE` to identify dense rows during pivot selection. It is the percentage density for a row to be regarded as dense. The default value is 100.

PIVOTING is an INTEGER scalar that is used to control numerical pivoting by `SILS_FACTORIZE`. It must have one of the following values:

- 1 Numerical pivoting will be performed, with relative pivot tolerance given by the component `U`.
- 2 No pivoting will be performed and an error exit will occur immediately a sign change is detected among the pivots. This is suitable for cases when \mathbf{A} is thought to be definite and is likely to decrease the factorization time while still providing a stable decomposition.
- 3 No pivoting will be performed and an error exit will occur if a zero pivot is detected. This is likely to decrease the factorization time, but may be unstable if there is a sign change among the pivots.
- 4 No pivoting will be performed but the matrix will be altered if a non-positive pivot is encountered.

The default value is 1.

U is a REAL (double precision in `GALAHAD_SILS_double`) scalar that is used by `SILS_FACTORIZE` when the component `PIVOTING` has the value 1 to hold the relative pivot tolerance. The default value is 0.01. For problems requiring greater than average numerical care a higher value than the default would be advisable. Values greater than 0.5 are treated as 0.5 and less than 0.0 as 0.0.

TOLERANCE is a REAL (double precision in `GALAHAD_SILS_double`) scalar that is used by `SILS_FACTORIZE`. Any entry of modulus less than or equal to `TOLERANCE` is treated as zero. The default value is 0.0.

FACTORBLOCKING is an INTEGER scalar used by `SILS_FACTORIZE` to determine the block size used for the Level 3 BLAS. The default value is 16.

SOLVEBLOCKING is an INTEGER scalar used by `SILS_SOLVE` to determine the block size used for the Level 2 and Level 3 BLAS. The default value is 16.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

2.2.3 The derived data type for holding informational parameters from SILS_ANALYSE

The derived data type `SILS_AINFO` is used to hold parameters that give information about the progress of the `SILS_ANALYSE` subroutine. The components of `SILS_AINFO` are:

`FLAG` is an `INTEGER` scalar. The value zero indicates that the subroutine has performed successfully. For nonzero values, see Section 2.4.1.

`MORE` is an `INTEGER` scalar that provides further information in the case of an error, see Section 2.4.1.

`OOB` is an `INTEGER` scalar that is set to the number of entries with one or both indices out of range.

`DUP` is an `INTEGER` scalar that is set to the number of duplicate off-diagonal entries.

`STAT` is an `INTEGER` scalar. In the case of the failure of an `allocate` or `deallocate` statement, it is set to the `STAT` value.

`NSTEPS` is an `INTEGER` scalar that is set to the number of nodes in the assembly tree (number of major steps in the factorization).

`MAXFRT` is an `INTEGER` scalar that holds the largest front size.

`OPSA` is a `REAL` (double precision in `GALAHAD_SILS_double`) scalar that is set to the number of floating-point additions required by the assembly of frontal matrices if no pivoting is performed. Numerical pivoting may increase the number of operations.

`OPSE` is a `REAL` (double precision in `GALAHAD_SILS_double`) scalar that is set to the number of floating-point operations required by the factorization if no pivoting is performed. Numerical pivoting may increase the number of operations.

`NRLTOT` and `NIRTOT` are `INTEGER` scalars that give the total amount of real and integer words respectively required for a successful factorization without the need for data compression, provided no numerical pivoting is performed.

`NRLNEC` and `NIRNEC` are `INTEGER` scalars that give the total amount of real and integer words required respectively for successful factorization allowing data compression, provided no numerical pivoting is performed.

`NRLADU` and `NIRADU` are `INTEGER` scalars that give the number of real and integer words required respectively to hold the matrix factors if no numerical pivoting is performed.

`NCMPA` is an `INTEGER` scalar that holds the number of compresses of the internal data structure performed by `SILS_ANALYSE`.

2.2.4 The derived data type for holding informational parameters from SILS_FACTORIZE

The derived data type `SILS_FINFO` is used to hold parameters that give information about the progress of the `SILS_FACTORIZE` subroutine. The components of `SILS_FINFO` are:

`FLAG` is an `INTEGER` scalar. The value of zero indicates that the subroutine has performed successfully. For nonzero values, see Section 2.4.2.

`MORE` is an `INTEGER` scalar that provides further information in the case of an error, see Section 2.4.2.

`STAT` is an `INTEGER` scalar. In the case of the failure of an `allocate` or `deallocate` statement, it is set to the `STAT` value.

`MAXFRT` is an `INTEGER` scalar that holds the largest front size.

`OPSA` is a `REAL` (double precision in `GALAHAD_SILS_double`) scalar that is set to the number of floating-point additions performed during assembly.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

OPSE is a REAL (double precision in GALAHAD_SILS_double) scalar that is set to the number of floating-point operations performed during factorization.

OPSB is a REAL (double precision in GALAHAD_SILS_double) scalar that is set to the number of additional floating-point operations performed during factorization because of use of the BLAS.

NRLTOT and NIRTOT are INTEGER scalars that give the total amount of REAL (double precision in GALAHAD_SILS_double) and INTEGER words respectively required for a successful factorization without the need for data compression, provided the same pivots are used.

NRLNEC and NIRNEC are INTEGER scalars that give the amount of REAL (double precision in GALAHAD_SILS_double) and INTEGER words required respectively for successful factorization allowing data compression, provided the same pivots are used.

NEBDU is an INTEGER scalar that gives the total number of entries in the factorization.

NRLBDU and NIRBDU are INTEGER scalars that give the amount of real and integer words used respectively to hold the factorization.

NCMPBR and NCMPBI are INTEGER scalars that hold the number of compresses of the real and integer data structure respectively required by the factorization.

NTWO is an INTEGER scalar that holds the number of 2 by 2 pivots used during the factorization.

NEIG is an INTEGER scalar that holds the number of negative eigenvalues of **A**.

RANK is an INTEGER scalar that holds the rank of the original factorization.

DELAY is an INTEGER scalar that holds the number of pivots passed up the tree because of numerical pivoting considerations.

SIGNC is an INTEGER scalar that holds the number of sign changes of pivot when SILS_CONTROL%PIVOTING is set to 3.

MODSTEP is an INTEGER scalar that holds the pivot step at which matrix modification is first performed when SILS_CONTROL%PIVOTING is set to 4.

MAXCHANGE is a REAL (double precision in GALAHAD_SILS_double) scalar that is set to the value of the largest change made to a pivot when SILS_AINFO%MODSTEP is positive.

2.2.5 The derived data type for holding informational parameters from SILS_SOLVE

The derived data type SILS_SINFO is used to hold parameters that give information about the progress of the SILS_FACTORIZE subroutine. The components of SILS_SINFO are:

FLAG is an INTEGER scalar. The value of zero indicates that the subroutine has performed successfully. For nonzero values, see Section 2.4.3.

STAT is an INTEGER scalar. In the case of the failure of an allocate or deallocate statement, it is set to the STAT value.

2.2.6 The derived data type for holding factors of a matrix

The derived data type SILS_FACTORS is used to hold the factors and related data for a matrix. All components are private.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

2.3 Argument lists and calling sequences

We use square brackets [] to indicate OPTIONAL arguments.

2.3.1 The initialization subroutine

The initialization subroutine must be called for each structure used to hold the factors. It may also be called for a structure used to control the subroutines. Each argument is optional. A call with no arguments has no effect.

```
CALL SILS_INITIALIZE( [FACTORS][, CONTROL] )
```

FACTORS is optional, scalar, of INTENT(OUT) and of type SILS_FACTORS. On exit, its allocatable array components will have targets of length zero. Without such initialization, these components are undefined and other calls are likely to fail.

CONTROL is optional, scalar, of INTENT(OUT) and of type SILS_CONTROL. On exit, its components will have been given the default values specified in Section 2.2.2.

2.3.2 The sparsity pattern analysis subroutine

The sparsity pattern of **A** may be analysed as follows:

```
CALL SILS_ANALYSE( MATRIX, FACTORS, CONTROL, AINFO[, PERM] )
```

MATRIX is scalar, of INTENT(IN) and of type SMT_TYPE. The user must set the components N, NE, ROW, and COL, and they are not altered by the subroutine. **Restrictions:** $MATRIX\%N \geq 1$ and $MATRIX\%NE \geq 0$.

FACTORS is scalar, of INTENT(INOUT) and of type SILS_FACTORS. It must have been initialized by a call to SILS_INITIALIZE or have been used for a previous calculation. In the latter case, the previous data will be lost but the allocatable arrays will not be reallocated unless they are found to be too small.

CONTROL is scalar, of INTENT(IN) and of type SILS_CONTROL. Its components control the action, as explained in Section 2.2.2.

AINFO is scalar, of INTENT(OUT) and of type SILS_AINFO. Its components provide information about the execution, as explained in Section 2.2.3.

PERM is an optional rank-one default INTEGER array of INTENT(IN) and length N. If present, PERM(*i*), $i = 1, \dots, n$, should be set to the position of variable *i* in the pivotal sequence.

2.3.3 The numerical factorization subroutine

Once it has been analysed, the matrix **A** may be factorized as follows:

```
CALL SILS_FACTORIZE( MATRIX, FACTORS, CONTROL, FINFO )
```

MATRIX is scalar, of INTENT(IN) and of type SMT_TYPE. The components N and NE must be unaltered since the call to SILS_ANALYSE. The user must set the component VAL to hold the real values of the entries. None of the components are altered by the subroutine.

FACTORS is scalar, of INTENT(INOUT) and of type SILS_FACTORS. It must be unaltered since the call to SILS_ANALYSE or a subsequent call to SILS_FACTORIZE.

CONTROL is scalar, of INTENT(IN) and of type SILS_CONTROL. Its components control the action, as explained in Section 2.2.2.

FINFO is scalar, of INTENT(OUT) and of type SILS_FINFO. Its components provide information about the execution, as explained in Section 2.2.4.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

2.3.4 The solution subroutine

Given the factorization, a set of equations may be solved as follows:

```
CALL SILS_SOLVE( MATRIX, FACTORS, X, CONTROL, SINFO[, RHS] )
```

MATRIX is scalar, of `INTENT(IN)` and of type `SMT_TYPE`. It must be unaltered since the call to `SILS_FACTORIZE` and is not altered by the subroutine.

FACTORS is scalar, of `INTENT(IN)` and of type `SILS_FACTORS`. It must be unaltered since the call to `SILS_FACTORIZE` and is not altered by the subroutine.

X is an assumed-shape array with 1 or 2 dimensions, of `INTENT(INOUT)` and of type `REAL` (double precision in `GALAHAD_SILS_double`). If **RHS** is absent, **X** must be set by the user to the vector **b** or the matrix **B** and on return it holds the solution **x** or **X**. If **RHS** is present, **X** must be set by the user to an approximate solution and on return it holds an improved solution, obtained by one cycle of iterative refinement without any use of arithmetic with additional precision.

CONTROL is scalar, of `INTENT(IN)` and of type `SILS_CONTROL`. Its components control the action, as explained in Section 2.2.2.

SINFO is scalar, of `INTENT(OUT)` and of type `SILS_SINFO`. Its components provide information about the execution, as explained in Section 2.2.5.

RHS is an assumed-shape array of the same shape as **X**, optional, of `intent(in)`, and of type `REAL` (double precision in `GALAHAD_SILS_double`). If present, it must be set by the user to the vector **b** or the matrix **B**.

2.3.5 The termination subroutine

All previously allocated arrays are reallocated to have targets of length zero as follows:

```
CALL SILS_FINALIZE( FACTORS, CONTROL, INFO )
```

FACTORS is scalar, of `INTENT(INOUT)` and of type `SILS_FACTORS`. On exit, its allocatable array components will have been reallocated to have targets of length zero. Without such finalization, the storage occupied is unavailable for other purposes. In particular, this is very wasteful if the structure goes out of scope on return from a procedure.

CONTROL is scalar, of `INTENT(IN)` and of type `SILS_CONTROL`. Its components control the action, as explained in Section 2.2.2.

INFO is scalar, of `INTENT(OUT)` and of type `INTEGER`. On return, the value 0 indicates success. Any other value is the `STAT` value of an `ALLOCATE` or `DEALLOCATE` statement that has failed.

2.4 Warning and error messages

2.4.1 When analysing the sparsity pattern

A successful return from `SILS_ANALYSE` is indicated by `AINFO%FLAG` having the value zero. A negative value is associated with an error message which will be output on unit `CONTROL%LP`. Possible negative values are:

- 1 Value of `MATRIX%N` out of range. `MATRIX%N < 1`. `AINFO%MORE` is set to value of `MATRIX%N`.
- 2 Value of `MATRIX%NE` out of range. `MATRIX%NE < 0`. `AINFO%MORE` is set to value of `MATRIX%NE`.
- 3 Failure of an `allocate` or `deallocate` statement. `AINFO%STAT` is set to the `STAT` value.
- 9 The array `PERM` does not hold a permutation. `AINFO%MORE` holds first component at which error was detected.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

A positive flag value is associated with a warning message which will be output on unit AINFO%MP. Possible positive values are:

- 1 Index (in MATRIX%ROW or MATRIX%COL) out of range. Action taken by subroutine is to ignore any such entries and continue. AINFO%OOR is set to the number of such entries. Details of the first ten are printed on unit CONTROL%MP.
- 2 Duplicate indices. Action taken by subroutine is to keep the duplicates and then to sum corresponding reals when SILS_FACTORIZE is called. AINFO%DUP is set to the number of faulty entries. Details of the first ten are printed on unit CONTROL%MP.
- 3 Both out-of-range indices and duplicates exist.

2.4.2 When factorizing the matrix

A successful return from SILS_FACTORIZE is indicated by FINFO%FLAG having the value zero. A negative value is associated with an error message which will be output on unit CONTROL%LP. In this case, no factorization will have been calculated. Possible negative values are:

- 1 Value of MATRIX%N differs from the SILS_ANALYSE value. FINFO%MORE holds value of MATRIX%N.
- 2 Value of MATRIX%NE out of range. $MATRIX\%NE < 0$.
FINFO%MORE holds value of MATRIX%NE.
- 3 Failure of an allocate or deallocate statement. FINFO%STAT is set to the STAT value.
- 5 Zero pivot detected (CONTROL%PIVOTING has the value 2 or 3). FINFO%MORE is set to the pivot step at which this was detected.
- 6 A change of sign of pivots has been detected (CONTROL%PIVOTING has the value 2). FINFO%MORE is set to the pivot step at which this was detected.
- 7 The real array that holds data for the factors needs to be bigger than CONTROL%MAXLA.
- 8 The integer array that holds data for the factors needs to be bigger than CONTROL%MAXLIW.

A positive flag value is associated with a warning message which will be output on unit CONTROL%MP. In this case, a factorization will have been calculated.

- 4 Matrix is rank deficient. In this case, FINFO%RANK will be set to the rank of the original factorization, but the factorization is altered by changing all the zero pivots to one. This will enable the subsequent solution of consistent sets of equations.
- 5 Pivots have different signs when CONTROL%PIVOTING has the value 3. FINFO%NEIG is set to the number of negative eigenvalues. Details of the first ten are printed on unit CONTROL%MP. FINFO%MORE is set to the number of sign changes.

2.4.3 When solving a linear system

A successful return from SILS_SOLVE is indicated by FINFO%FLAG having the value zero. A negative value is associated with an error message which will be output on unit CONTROL%LP. In this case, no solution will have been found. Possible negative values are:

- 3 Failure of an allocate or deallocate statement. FINFO%STAT is set to the STAT value.

**All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html> .
For any commercial application, a separate license must be signed.**

2.5 Further features

In this section, we describe features for enquiring about and manipulating the parts of the factorization constructed. These features will not be needed by a user who wants simply to solve systems of equations with matrix **A**.

The algorithm produces an \mathbf{LDL}^T factorization of a permutation of **A**, where **L** is a unit lower triangular matrix and **D** is a block diagonal matrix with blocks of order 1 and 2. It is convenient to write this factorization in the form

$$\mathbf{A} = (\mathbf{PLP}^T)(\mathbf{PDP}^T)(\mathbf{PL}^T\mathbf{P}^T),$$

where **P** is a permutation matrix. The following subroutines are provided:

SILS_ENQUIRE returns **P** or **D** or both.

SILS_ALTER_D alters **D**. Note that this means that we no longer have a factorization of the given matrix **A**.

SILS_PART_SOLVE solves one of the systems of equations $\mathbf{PLP}^T\mathbf{x} = \mathbf{b}$, $\mathbf{PDP}^T\mathbf{x} = \mathbf{b}$, or $\mathbf{PL}^T\mathbf{P}^T\mathbf{x} = \mathbf{b}$, for one or more right-hand sides.

2.5.1 To return **P** or **D** or both

```
CALL SILS_ENQUIRE( FACTORS[, PERM][, PIVOTS][, D][, PERTURBATION] )
```

FACTORS is scalar, of **INTENT(IN)** and of type **SILS_FACTORS**. It must be unaltered since the call to **SILS_FACTORIZE** or a subsequent call to **SILS_ALTER_D**.

PERM is an optional rank-one default **INTEGER** array of **INTENT(OUT)** and length *N*. If present, **PERM** will be set to the pivot permutation selected by **SILS_ANALYSE**.

PIVOTS is an optional rank-one default **INTEGER** array of **INTENT(OUT)** and length *N*. If present, the index of pivot *i* will be placed in **PIVOTS**(*i*), *i* = 1, ..., *n*, with its sign negative if it is the index of a 2 x 2 block.

D is an optional rank-two default **REAL** (double precision in **GALAHAD_SILS_double**) array of **INTENT(OUT)** and shape (2, *N*). If present, the diagonal entries of \mathbf{D}^{-1} will be placed in **D**(1, *i*), *i* = 1, ..., *n* and the off-diagonal entries of \mathbf{D}^{-1} will be placed in **D**(2, *i*), *i* = 1, ..., *n* - 1.

PERTURBATION is an optional rank-one default **REAL** (double precision in **GALAHAD_SILS_double**) array of **INTENT(OUT)** and length *N*. If present, **PERTURBATION** will be set to a vector of diagonal perturbations chosen by **SILS_FACTORIZE**. This array can only be nonzero if **SILS_FACTORIZE** was last called with **CONTROL%PIVOTING** = 4.

2.5.2 To alter **D**

```
CALL SILS_ALTER_D( FACTORS, D, INFO )
```

FACTORS is scalar, of **INTENT(INOUT)** and of type **SILS_FACTORS**. It must be unaltered since the call to **SILS_FACTORIZE** or a subsequent call to **SILS_ALTER_D**.

D is an array of shape (2, *n*) of **INTENT(INOUT)** and of type **REAL** (double precision in **GALAHAD_SILS_double**). The diagonal entries of \mathbf{D}^{-1} will be altered to **D**(1, *i*), *i* = 1, ..., *n* and the off-diagonal entries of \mathbf{D}^{-1} will be altered to **D**(2, *i*), *i* = 1, ..., *n* - 1.

INFO is scalar, of **INTENT(OUT)** and of type **INTEGER**. On return, the value 0 indicates success and the value *i* > 0 indicates that **D**(2, *i*) is nonzero, but is not part of a block of order 2 of **D**.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

2.5.3 To perform a partial solution

```
CALL SILS_PART_SOLVE( FACTORS, CONTROL, PART, X, INFO )
```

FACTORS is scalar, of `INTENT(IN)` and of type `SILS_FACTORS`. It must be unaltered since the call to `SILS_FACTORIZE` or a subsequent call to `SILS_ALTER_D`.

CONTROL is scalar, of `INTENT(IN)` and of type `SILS_CONTROL`. Its components control the action, as explained in Section 2.2.2.

PART is scalar, of `INTENT(IN)` and of type `CHARACTER`. It must have one of the values

- L for solving $\mathbf{PLP}^T \mathbf{x} = \mathbf{b}$ or $\mathbf{PLP}^T \mathbf{X} = \mathbf{B}$,
- D for solving $\mathbf{PDP}^T \mathbf{x} = \mathbf{b}$ or $\mathbf{PDP}^T \mathbf{X} = \mathbf{B}$, or
- U for solving $\mathbf{PL}^T \mathbf{P}^T \mathbf{x} = \mathbf{b}$ or $\mathbf{PL}^T \mathbf{P}^T \mathbf{X} = \mathbf{B}$.

X is an assumed-shape array with 1 or 2 dimensions, of `intent(inout)`, and of type `REAL` (double precision in `GALAHAD_SILS_double`). It must be set by the user to the vector \mathbf{b} or the matrix \mathbf{B} and on return it holds the solution \mathbf{x} or \mathbf{X} .

INFO is scalar, of `INTENT(OUT)` and of type `INTEGER`. On return, the value 0 indicates success. Any other value is the `STAT` value of an `ALLOCATE` or `DEALLOCATE` statement that has failed.

3 GENERAL INFORMATION

Use of common: None, although unfortunately MA27 uses common.

Workspace: Provided automatically by the module.

Other routines called directly: MA27A/AD, MA27B/BD, MA27C/CD.

Other modules used directly: GALAHAD_SMT_single/double.

Input/output: Error, warning and diagnostic messages only. Error messages on unit `CONTROL%LP` and warning and diagnostic messages on unit `CONTROL%WP` and `CONTROL%MP`, respectively. These have default value 6, and printing of these messages is suppressed if the relevant unit number is set negative. These messages are also suppressed if `SILS_CONTROL%LDIAG` is less than 1.

Restrictions: `MATRIX%N` ≥ 1 , `MATRIX%NE` ≥ 0 .

Portability: ISO Fortran 95 + TR 15581 or Fortran 2003. The package is thread-safe.

4 METHOD

A version of sparse Gaussian elimination is used.

The `SILS_ANALYSE` entry chooses pivots from the diagonal using the minimum degree criterion employing a generalized element model of the elimination thus avoiding the need to store the filled-in pattern explicitly. The elimination is represented as an assembly tree with the order of elimination determined by a depth-first search of the tree.

The `SILS_FACTORIZE` entry factorizes the matrix by using the assembly and elimination ordering generated by `SILS_ANALYSE`. At each stage in the multifrontal approach, pivoting and elimination are performed on full submatrices and, when diagonal 1×1 pivots would be numerically unstable, 2×2 diagonal blocks are used. The operations on the full submatrices are performed using the Level 3 BLAS. `SILS_FACTORIZE` can thus be used to factor indefinite systems and will perform well on machines with caches or levels of memory hierarchy.

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

The SILS_SOLVE entry uses the factors from SILS_FACTORIZE to solve systems of equations either by loading the appropriate parts of the vectors into an array of the current front-size and using full matrix code employing the Level 2 and Level 3 BLAS or by indirect addressing at each stage, whichever performs better.

Reference: A fuller account of this method is given by Duff and Reid (AERE-R.10533, 1982) and Duff and Reid, ACM Trans. Math. Software **9** (1983), 302-325.

5 EXAMPLE OF USE

We illustrate the use of the package on the solution of the single set of equations

$$\begin{pmatrix} 2 & 3 & & & \\ 3 & & 4 & & 6 \\ & 4 & 1 & 5 & \\ & & 5 & & \\ 6 & & & & 1 \end{pmatrix} \mathbf{x} = \begin{pmatrix} 8 \\ 45 \\ 31 \\ 15 \\ 17 \end{pmatrix}$$

(Note that this example does not illustrate all the facilities). Then we may use the following code

```
PROGRAM MAIN
USE GALAHAD_SILS_DOUBLE
IMPLICIT NONE
INTEGER, PARAMETER :: wp = KIND( 1.0D+0 )
TYPE(SMT_TYPE) MATRIX
TYPE(SILS_CONTROL) CONTROL
TYPE(SILS_AINFO) AINFO
TYPE(SILS_FINFO) FINFO
TYPE(SILS_SINFO) SINFO
TYPE(SILS_FACTORS) FACTORS
REAL ( KIND = wp ), ALLOCATABLE, DIMENSION( : ) :: B, X
INTEGER I,INFO,N,NE
READ (5,*) N,NE ! Read matrix order and number of entries
MATRIX%N = N
MATRIX%NE = NE
! Allocate arrays of appropriate sizes
ALLOCATE(MATRIX%VAL(NE), MATRIX%ROW(NE), MATRIX%COL(NE))
ALLOCATE(B(N), X(N))
! Read matrix and right-hand side
READ (5,*) (MATRIX%ROW(I),MATRIX%COL(I),MATRIX%VAL(I),I=1,NE)
READ (5,*) B
CALL SILS_INITIALIZE(FACTORS,CONTROL) ! Initialize the structures
CALL SILS_ANALYSE(MATRIX,FACTORS,CONTROL,AINFO) ! Analyse
IF(AINFO%FLAG\bm0) THEN
WRITE(6, '(A,I2)') &
' Failure of SILS_ANALYSE with AINFO%FLAG=', AINFO%FLAG
STOP
END IF
CALL SILS_FACTORIZE(MATRIX,FACTORS,CONTROL,FINFO) ! Factorize
IF(FINFO%FLAG<0) THEN
WRITE(6, '(A,I2)') &
```

All use is subject to licence. See <http://galahad.rl.ac.uk/galahad-www/cou.html>.
For any commercial application, a separate license must be signed.

```

      ' Failure of SILS_FACTORIZE with FINFO%FLAG=', FINFO%FLAG
      STOP
    END IF
    X = B ! Solve without refinement
    CALL SILS_SOLVE(MATRIX,FACTORS,X,CONTROL,SINFO)
    IF(SINFO%FLAG==0)WRITE(6,'(A/, (3F20.16))') &
      ' Solution without refinement is',X
    CALL SILS_SOLVE(MATRIX,FACTORS,X,CONTROL,SINFO,B) ! Perform one refinement
    IF(SINFO%FLAG==0)WRITE(6,'(A/, (3F20.16))') &
      ' Solution after one refinement is',X
    END PROGRAM MAIN

```

with the following data

```

5 7
1 1 2.0
1 2 3.0
2 3 4.0
2 5 6.0
3 3 1.0
3 4 5.0
5 5 1.0
8. 45. 31. 15. 17.

```

This produces the following output:

```

Solution without refinement is
1.0000000000000000 1.9999999999999998 3.0000000000000000
4.0000000000000008 5.0000000000000017
Solution after one refinement is
1.0000000000000000 2.0000000000000000 3.0000000000000000
4.0000000000000000 5.0000000000000000

```