

PART NUMBER 446100-OSDP-WCW

UL Listed and Rated Type CMP; Plenum Composite Cable

■ 0275/0725 FT ● SMARTWIRE OSDP COMPOSITE CABLE E102194 CL2P (UL) 6C 18 + 8C 22 AWG 75 C CMP C (UL) RS-485 ROHS



SPECIFICATIONS

DESCRIPTION Elem1: 22/1P Conductor Shielded, Lo-Cap, Tinned Copper, RS-485, 120 Ohms;+
18-02 Conductor Non-Shielded, Bare Copper White Jacket;
Elem2: 18-04 Conductor Non-Shielded, Bare Copper White Jacket with Orange Stripe;
Elem3: 22-04 Conductor Non-Shielded, Bare Copper White Jacket with Red Stripe;
Elem4: 22-02 Conductor Non-Shielded, Bare Copper White Jacket with Green Stripe

Plenum Composite Cable, C(UL) US CMP, Overall White Jacket

CONDUCTOR Elem1: 22 AWG Strand Tinned Copper + 18 AWG Strand Bare Copper
Elem2: 18 AWG Strand Bare Copper
Elem3: 22 AWG 7 Strand Bare Copper
Elem4: 22 AWG 7 Strand Bare Copper

INSULATION .006 Wall Plenum Alloy

COLOR CODE Elem1: Green/White + Red/Black
Elem2: Black, Red, White, Green
Elem3: Black, Red, White, Green
Elem4: Black, Red

LAY LENGTH Elem1: 1.5" lay
Elem2: 5" lay
Elem3: 5" lay
Elem4: 5" lay

SHIELD Elem1: 22-02 Conductor, Aluminum Mylar; 18 AWG is Non-Shielded
Elem2, 3 & 4: Non-Shielded

DRAIN WIRE Elem1: Tape with Aluminum Mylar (Foil Out + #24 7/32 TC DRN)
Elem2, 3 & 4: N/A

JACKET COLOR Elem1: White Jacket
Elem2: White Jacket with Orange Stripe
Elem3: White Jacket with Red Stripe
Elem4: White Jacket with Green Stripe

Outer Jacket: White Jacket

MARKING Elem1: OSDP A B C D E 0 1 2 3 4 5 6 7 8 9;
Elem2: Lock Power A B C D E 0 1 2 3 4 5 6 7 8 9
Elem3: REX/SPARE A B C D E 0 1 2 3 4 5 6 7 8 9
Elem4: DOOR CONTACT A B C D E 0 1 2 3 4 5 6 7 8 9

Outer Jacket: Smartwire OSDP Composite Cable E143243 6C 18 AWG + 8C 22 AWG 75C
CMP (UL) RS-485 ROHS

OVERALL DIAMETER Elem1: O D: .306" Nom.
Elem2: O D: .172" Nom.
Elem3: O D: .131" Nom.
Elem4: O D: .114" Nom.
Outer Jacket: O D: .415" Nom.

JACKET Inner Jackets: All Elements: Wall Plenum Alloy.015";
Outer Jacket: Low-Smoke PVC .018"

CODES & LISTINGS NEC Article 800, UL Subject 444, Type CMP; (UL) RS-485 ROHS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

All specifications referenced are nominal measurements unless otherwise noted.