


PART NUMBER 415110-OSDP

UL Listed and Rated Type CMP Multi-Pair Shielded Plenum Cable

■ 0275/0725 FT ● ABCDE0123456789 OSDP 22AWG 75C CMP C(UL)US ROHS MADE IN THE USA



CABLE SPECIFICATIONS

DESCRIPTION	22 AWG, 2 Pairs Twisted, Tinned Copper Shielded with an Overall Plenum Rated PVC Jacket Communication, Instrumentation and Special Application Plenum Cable
CONDUCTOR	22 AWG (7 Strand) Tinned Copper
INSULATION	Foam FEP .016"
COLOR CODE	Black/Red, White/Green
LAY LENGTH	Pair Lay: 2" Left Hand Lay (6 twists per foot) Cable Lay: 3" Left Hand Lay (4 twists per foot)
SHIELD	Aluminum Mylar Foil
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Plenum-Rated Polyvinylchloride .015"
JACKET COLOR	White Jacket
MARKING	SMARTWIRE "OSDP" DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 E171202 22AWG 2PR SHIELDED 75C (UL) CL3P OR FPLP OR C(UL)US CMP FT6 "ROHS COMPLIANT" MADE IN THE USA
OVERALL DIAMETER	.230" Nom.
CABLE WEIGHT	25 Lbs/Mft.
CAPACITANCE	11 pF/Ft. Nom.
IMPEDANCE	120 Ohms Nom.
DC RESISTANCE	17.04 Ohms/Mft @ 20 C Maximum (Conductor)
TEMPERATURE RATING	0 C to 75 C
VOLTAGE RATING	300 Volts

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC (NFPA 70) Articles 800, 725, and 760; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.