

PART NUMBER 044000

UL Listed and Rated Type CMP Single Pair Shielded Plenum Cable

■ 0275/0725 FT ● TEMPERATURE CONTROL SYSTEM ZONE BUS/COMM LINE ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION	24 AWG 1 Pair Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP (UL)
CONDUCTOR	24 (7/32 Bare Copper)
INSULATION	FEP .022"
COLOR CODE	Black/White
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	White Jacket
MARKING	TEMPERATURE CONTROL SYSTEM AN BIN DIG IN / OUT A B C D E 0 1 2 3 4 5 6 7 8 9 24 AWG C(UL)US CMP (UL) ROHS MADE IN THE USA
OVERALL DIAMETER	.178" Nom.
CABLE WEIGHT	13 Lbs/Mft.
CAPACITANCE	12.5 pF/Ft. Nom.
IMPEDANCE	100 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP (UL), RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.