### LAB1

# **Entities and Attributes:**

### 1. Airport

- airport id (PK, INT)
- airport name (VARCHAR)
- country (VARCHAR)
- state (VARCHAR)
- city (VARCHAR)
- created\_at (TIMESTAMP)
- updated\_at (TIMESTAMP)

### 2. Airline

- airline id (PK, INT)
- airline code (VARCHAR)
- name (VARCHAR)
- country (VARCHAR)
- created\_at (TIMESTAMP)
- updated\_at (TIMESTAMP)

# 3. Flight

- flight\_id (PK, INT)
- departing\_gate (VARCHAR)
- arriving gate (VARCHAR)
- airline\_id (FK → Airline, INT)
- departure\_airport\_id (FK → Airport, INT)
- arrival\_airport\_id (FK → Airport, INT)
- scheduled\_departure\_time (TIMESTAMP)
- scheduled\_arrival\_time (TIMESTAMP)
- actual departure time (TIMESTAMP)
- actual\_arrival\_time (TIMESTAMP)
- created\_at (TIMESTAMP)
- updated\_at (TIMESTAMP)

### 4. Passenger

- passenger\_id (PK, INT)
- first name (VARCHAR)
- last\_name (VARCHAR)
- gender (VARCHAR)
- date\_of\_birth (DATE)
- country\_of\_citizenship (VARCHAR)
- country\_of\_residence (VARCHAR)
- passport\_number (VARCHAR, UNIQUE)
- created\_at (TIMESTAMP)
- updated at (TIMESTAMP)

### 5. Booking

- booking\_id (PK, INT)
- flight id (FK → Flight, INT)
- passenger\_id (FK → Passenger, INT)
- status (VARCHAR)
- booking\_platform (VARCHAR)
- ticket\_price (DECIMAL (10,2))
- created\_at (TIMESTAMP)
- updated\_at (TIMESTAMP)

## 6. BookingChange

- booking\_change\_id (PK, INT)
- booking\_id (FK → Booking, INT)
- change\_details (TEXT)
- created\_at (TIMESTAMP)
- updated\_at (TIMESTAMP)

# 7. BoardingPass

- boarding\_pass\_id (PK, INT)
- booking\_id (FK → Booking, INT)
- seat (VARCHAR)

- boarding time (TIMESTAMP)
- created\_at (TIMESTAMP)
- updated\_at (TIMESTAMP)

### 8. Baggage

- baggage id (PK, INT)
- booking id (FK → Booking, INT)
- weight\_kg (DECIMAL (5,2))
- created at (TIMESTAMP)
- updated\_at (TIMESTAMP)

## 9. BaggageCheck

- baggage\_check\_id (PK, INT)
- baggage id (FK → Baggage, INT)
- passenger\_id (FK → Passenger, INT)
- check\_results (VARCHAR)
- created at (TIMESTAMP)
- updated at (TIMESTAMP)

# 10. SecurityCheck

- security\_check\_id (PK, INT)
- passenger\_id (FK → Passenger, INT)
- check\_results (VARCHAR)
- created\_at (TIMESTAMP)
- updated at (TIMESTAMP)

# **Relationships:**

## 1. Airport – Flight

- $_{\circ}$  Airport.airport\_id  $\rightarrow$  Flight.departure\_airport\_id
- o Airport.airport\_id → Flight.arrival\_airport\_id
- o (1:N)

#### 2. Airline - Flight

- o Airline.airline id → Flight.airline id
- 。 **(1:N)**

## 3. Flight – Booking

- ∘ Flight.flight id → Booking.flight id
- o (1:N)

### 4. Passenger - Booking

- ∘ Passenger.passenger\_id → Booking.passenger\_id
- 。 **(1:N)**

# 5. **Booking – Booking Change**

- Booking.booking\_id → BookingChange.booking\_id
- o (1:N)

### 6. **Booking – BoardingPass**

- o (1:1)

## 7. Booking - Baggage

- Booking.booking id → Baggage.booking id
- 。 **(1:N)**

# 8. Baggage – BaggageCheck

- ₀ Baggage.baggage\_id → BaggageCheck.baggage\_id
- 。 **(1:N)**

## 9. Passenger – BaggageCheck

- ∘ Passenger.passenger\_id → BaggageCheck.passenger\_id
- o (1:N)

# 10. **Passenger – SecurityCheck**

- Passenger.passenger\_id → SecurityCheck.passenger\_id
- (1:N)

