

Ubuntu 26.04.1 LTS Ubuntu-Target tty1

Ubuntu-Target login: vboxuser

Password:

Welcome to Ubuntu 26.04.1 LTS (GNU/Linux 7.0.0-34-generic x86_64)

* Documentation: <https://docs.ubuntu.com>
* Management: <https://landscape.canonical.com>
* Support: <https://ubuntu.com/pro>

System information as of Thu Oct 1 11:47:30 AM UTC 2026

System load: 0.59	Memory usage: 13%	Processes: 103
Usage of /: 14.7% of 24.44GB	Swap usage: 0%	Users logged in: 0

* Canonical Workshop gives developers fast, composable, reproducible, and secure developer environments that are perfect for agentic workflows.

<https://ubuntu.com/workshop>

Expanded Security Maintenance for Applications is not enabled.

21 updates can be applied immediately.

To see these additional updates run: `apt list --upgradable`

Enable ESM Apps to receive additional future security updates.

See <https://ubuntu.com/esm> or run: `sudo pro status`

vboxuser@Ubuntu-Target:~\$ ip a

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP group default qlen 1000
    link/ether 08:00:27:35:13:d9 brd ff:ff:ff:ff:ff:ff
    altname enx0800273513d9
    inet 192.168.56.102/24 metric 100 brd 192.168.56.255 scope global dynamic enp0s3
        valid_lft 433sec preferred_lft 433sec
    inet6 fe80::a00:27ff:fe35:13d9/64 scope link proto kernel_ll
        valid_lft forever preferred_lft forever
```

vboxuser@Ubuntu-Target:~\$

Activate Windows
Go to Settings to activate Windows.



Home



File System



Trash

```
kali@kali: ~  
Session Actions Edit View Help  
(kali@kali)-[~]  
$ hydra -l vboxuser -P pass.txt 192.168.56.102 ssh  
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in  
military or secret service organizations, or for illegal purposes (this is n  
on-binding, these ** ignore laws and ethics anyway).  
  
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-10-01 07:  
49:36  
[WARNING] Many SSH configurations limit the number of parallel tasks, it is r  
ecomended to reduce the tasks: use -t 4  
[DATA] max 5 tasks per 1 server, overall 5 tasks, 5 login tries (l:1/p:5), ~1  
try per task  
[DATA] attacking ssh://192.168.56.102:22/  
[22][ssh] host: 192.168.56.102 login: vboxuser password: 123456  
1 of 1 target successfully completed, 1 valid password found  
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-10-01 07:  
49:41  
(kali@kali)-[~]  
$
```

Activate Windows
Go to Settings to activate Windows.

```
# "bantime.formula" used by default to calculate next value of ban time, default value below,
# the same ban time growing will be reached by multipliers 1, 2, 4, 8, 16, 32...
#bantime.formula = ban.Time * (1<<(ban.Count if ban.Count<20 else 20)) * banFactor
#
# more aggressive example of formula has the same values only for factor "2.0 / 2.885385" :
#bantime.formula = ban.Time * math.exp(float(ban.Count+1)*banFactor)/math.exp(1*banFactor)

# "bantime.multipliers" used to calculate next value of ban time instead of formula, corresponding
# previously ban count and given "bantime.factor" (for multipliers default is 1);
# following example grows ban time by 1, 2, 4, 8, 16 ... and if last ban count greater as multipliers count,
# always used last multiplier (64 in example), for factor '1' and original ban time 600 - 10.6 hours
#bantime.multipliers = 1 2 4 8 16 32 64
# following example can be used for small initial ban time (bantime=60) - it grows more aggressive at begin,
# for bantime=60 the multipliers are minutes and equal: 1 min, 5 min, 30 min, 1 hour, 5 hour, 12 hour, 1 day, 2 day
#bantime.multipliers = 1 5 30 60 300 720 1440 2880

# "bantime.overalljails" (if true) specifies the search of IP in the database will be executed
# cross over all jails, if false (default), only current jail of the ban IP will be searched
#bantime.overalljails = false

# -----

# "ignoreself" specifies whether the local resp. own IP addresses should be ignored
# (default is true). Fail2ban will not ban a host which matches such addresses.
#ignoreself = true

# "ignoreip" can be a list of IP addresses, CIDR masks or DNS hosts. Fail2ban
# will not ban a host which matches an address in this list. Several addresses
# can be defined using space (and/or comma) separator.
#ignoreip = 127.0.0.1/8 ::1

# External command that will take an tagged arguments to ignore, e.g. <ip>,
# and return true if the IP is to be ignored. False otherwise.
#
# ignorecommand = /path/to/command <ip>

vboxuser@Ubuntu-Target:~$ sudo systemctl restart fail2ban
vboxuser@Ubuntu-Target:~$ sudo fail2ban-client status sshd
Status for the jail: sshd
|- Filter
|   |- Currently failed: 0
|   |- Total failed:    0
|   - Journal matches:  _SYSTEMD_UNIT=ssh.service + _COMM=sshd
- Actions
  |- Currently banned: 0
  |- Total banned:    0
  - Banned IP list:
vboxuser@Ubuntu-Target:~$
```

GNU nano 8.7.1 /etc/passwd/jail.local

```
#  
# WARNING: heavily refactored in 0.9.0 release. Please review and  
#           customize settings for your setup.  
#  
# Changes:  in most of the cases you should not modify this  
#           file, but provide customizations in jail.local file,  
#           or separate .conf files under jail.d/ directory, e.g.:  
#  
# HOW TO ACTIVATE JAILS:  
#  
# YOU SHOULD NOT MODIFY THIS FILE.  
#  
# It will probably be overwritten or improved in a distribution update.  
#  
# Provide customizations in a jail.local file or a jail.d/customisation.local.  
# For example to change the default bantime for all jails and to enable the  
# ssh-iptables jail the following (uncommented) would appear in the .local file.  
# See man 5 jail.conf for details.  
#
```

```
# [DEFAULT]  
# bantime = 1h  
#
```

```
[sshd]
```

```
enabled = true  
port = ssh  
filter=sshd  
backend = systemd  
maxretry = 3  
findtime = 1m  
bantime = 10m  
# See jail.conf(5) man page for more information
```

```
# Comments: use '#' for comment lines and ';' (following a space) for inline comments
```

```
[INCLUDES]
```

```
#before = paths-distro.conf  
before = paths-debian.conf
```

```
# The DEFAULT allows a global definition of the options. They can be overridden  
# in each jail afterwards.
```

```
[DEFAULT]
```

[Read 997 lines]

```
^G Help  
^X Exit
```

```
^O Write Out  
^R Read File
```

```
^F Where Is  
^N Replace
```

```
^K Cut  
^U Paste
```

```
^T Execute  
^J Justify
```

```
^C Location  
^_ Go To Line
```

```
M-U Undo  
M-E Redo
```

```
M-A Set Mark  
M-6 Copy
```

```
M-] To Bracket  
^B Where Was
```

```
M-B Previous  
M-F Next
```

Activate Windows

Go to Settings to activate Windows.



Home



File System



Trash

```
kali@kali: ~  
Session Actions Edit View Help  
[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4  
[DATA] max 5 tasks per 1 server, overall 5 tasks, 5 login tries (l:1/p:5), ~1 try per task  
[DATA] attacking ssh://192.168.56.102:22/  
[22][ssh] host: 192.168.56.102 login: vboxuser password: 123456  
1 of 1 target successfully completed, 1 valid password found  
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-10-01 08:53:04  
  
(kali@kali)-[~]  
$ printf "wrong1\nwrong2\nwrong3\nwrong4\nwrong5\n" > fail_pass.txt  
  
(kali@kali)-[~]  
$ hydra -l vboxuser -P fail_pass.txt -t 1 192.168.56.102 ssh  
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these ** ignore laws and ethics anyway).  
  
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-10-01 08:55:33  
[DATA] max 1 task per 1 server, overall 1 task, 5 login tries (l:1/p:5), ~5 tries per task  
[DATA] attacking ssh://192.168.56.102:22/  
[ERROR] could not connect to ssh://192.168.56.102:22 - Connection refused  
  
(kali@kali)-[~]  
$
```

Activate Windows
Go to Settings to activate Windows.

```
# YOU SHOULD NOT MODIFY THIS FILE.
#
# It will probably be overwritten or improved in a distribution update.
#
# Provide customizations in a jail.local file or a jail.d/customisation.local.
# For example to change the default bantime for all jails and to enable the
# ssh-iptables jail the following (uncommented) would appear in the .local file.
# See man 5 jail.conf for details.
#
# [DEFAULT]
# bantime = 1h
#
[sshd]
enabled = true
port = ssh
filter=sshd
backend = systemd
maxretry = 3
findtime = 1m
bantime = 10m
# See jail.conf(5) man page for more information

# Comments: use '#' for comment lines and ';' (following a space) for inline comments

[INCLUDES]

#before = paths-distro.conf
before = paths-debian.conf

# The DEFAULT allows a global definition of the options. They can be overridden
# in each jail afterwards.

[DEFAULT]

vboxuser@Ubuntu-Target:~$ sudo systemctl restart fail2ban
vboxuser@Ubuntu-Target:~$ sudo fail2ban-client status sshd
Status for the jail: sshd
|- Filter
| |- Currently failed: 0
| |- Total failed: 4
| \- Journal matches: _SYSTEMD_UNIT=ssh.service + _COMM=sshd
- Actions
  |- Currently banned: 1
  |- Total banned: 1
  \- Banned IP list: 192.168.56.103
vboxuser@Ubuntu-Target:~$ _
```

Activate Windows
Go to Settings to activate Windows.

```
#
# YOU SHOULD NOT MODIFY THIS FILE.
#
# It will probably be overwritten or improved in a distribution update.
#
# Provide customizations in a jail.local file or a jail.d/customisation.local.
# For example to change the default bantime for all jails and to enable the
# ssh-iptables jail the following (uncommented) would appear in the .local file.
# See man 5 jail.conf for details.
#
# [DEFAULT]
# bantime = 1h
#
[sshd]
enabled = true
port = ssh
filter=sshd
backend = systemd
maxretry = 3
findtime = 1m
bantime = 10m
# See jail.conf(5) man page for more information

# Comments: use '#' for comment lines and ';' (following a space) for inline comments

[INCLUDES]

#before = paths-distro.conf
before = paths-debian.conf

# The DEFAULT allows a global definition of the options. They can be overridden
# in each jail afterwards.

[DEFAULT]

vboxuser@Ubuntu-Target:~$ sudo fail2ban-client status sshd
Status for the jail: sshd
|- Filter
| |- Currently failed: 0
| |- Total failed: 4
| \- Journal matches: _SYSTEMD_UNIT=ssh.service + _COMM=sshd
- Actions
  |- Currently banned: 1
  |- Total banned: 1
  \- Banned IP list: 192.168.56.103
vboxuser@Ubuntu-Target:~$
```

Activate Windows
Go to Settings to activate Windows.

GNU nano 8.7.1 /etc/ssh/sshd_config

#IgnoreRhosts yes

To disable tunneled clear text passwords, change to "no" here!

#PasswordAuthentication yes

#PermitEmptyPasswords no

Change to "yes" to enable keyboard-interactive authentication. Depending on

the system's configuration, this may involve passwords, challenge-response,

one-time passwords or some combination of these and other methods.

Beware issues with some PAM modules and threads.

KbdInteractiveAuthentication yes

Kerberos options

#KerberosAuthentication no

#KerberosOrLocalPasswd yes

#KerberosTicketCleanup yes

#KerberosGetAFSToken no

GSSAPI options

#GSSAPIAuthentication no

#GSSAPICleanupCredentials yes

#GSSAPIStrictAcceptorCheck yes

#GSSAPIKeyExchange no

Set this to 'yes' to enable PAM authentication, account processing,

and session processing. If this is enabled, PAM authentication will

be allowed through the KbdInteractiveAuthentication and

PasswordAuthentication. Depending on your PAM configuration,

PAM authentication via KbdInteractiveAuthentication may bypass

the setting of "PermitRootLogin prohibit-password".

If you just want the PAM account and session checks to run without

PAM authentication, then enable this but set PasswordAuthentication

and KbdInteractiveAuthentication to 'no'.

UsePAM yes

#AllowAgentForwarding yes

#AllowTcpForwarding yes

#GatewayPorts no

X11Forwarding yes

#X11DisplayOffset 10

#X11UseLocalhost yes

#PermitTTY yes

PrintMotd no

#PrintLastLog yes

#TCPKeepAlive yes

#PermitUserEnvironment no

^G Help

^O Write Out

^F Where Is

^K Cut

^T Execute

^C Location

M-U Undo

M-A Set Mark

M-I To Bracket

G-B Previous

^X Exit

^R Read File

^N Replace

^U Paste

^J Justify

^_ Go To Line

M-E Redo

M-G Copy

^B Where Was

M-F Next

Activate Windows

Go to Settings to activate Windows.

```
GNU nano 8.7.1 /etc/ssh/sshd_config
# the setting of "PermitRootLogin prohibit-password".
# If you just want the PAM account and session checks to run without
# PAM authentication, then enable this but set PasswordAuthentication
# and KbdInteractiveAuthentication to 'no'.
UsePAM yes

#AllowAgentForwarding yes
#AllowTcpForwarding yes
#GatewayPorts no
X11Forwarding yes
#X11DisplayOffset 10
#X11UseLocalhost yes
#PermitTTY yes
PrintMotd no
#PrintLastLog yes
#TCPKeepAlive yes
#PermitUserEnvironment no
#Compression delayed
#ClientAliveInterval 0
#ClientAliveCountMax 3
#UseDNS no
#PidFile /run/sshd.pid
#MaxStartups 10:30:100
#PermitTunnel no
#ChrootDirectory none
#VersionAddendum none

# no default banner path
#Banner none

# Allow client to pass locale and color environment variables
AcceptEnv LANG LC_* COLORTERM NO_COLOR

# override default of no subsystems
Subsystem          sftp          /usr/lib/openssh/sftp-server

# Example of overriding settings on a per-user basis
#Match User anoncvs
#      X11Forwarding no
#      AllowTcpForwarding no
#      PermitTTY no
#      ForceCommand cvs server
#KbdInteractiveAuthentication yes
PasswordAuthentication yes
UsePAM yes
```

^G Help
^X Exit

^O Write Out
^R Read File

^F Where Is
^N Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^_ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-G Copy

M-I To Bracket
M-B Where Was

M-B Previous
M-F Next

Activate Windows
Go to Settings to activate Windows.

```
# the setting of PermitRootLogin prohibit-password .
# If you just want the PAM account and session checks to run without
# PAM authentication, then enable this but set PasswordAuthentication
# and KbdInteractiveAuthentication to 'no'.
UsePAM yes
```

```
#AllowAgentForwarding yes
#AllowTcpForwarding yes
#GatewayPorts no
X11Forwarding yes
#X11DisplayOffset 10
#X11UseLocalhost yes
#PermitTTY yes
PrintMotd no
#PrintLastLog yes
#TCPKeepAlive yes
#PermitUserEnvironment no
#Compression delayed
#ClientAliveInterval 0
#ClientAliveCountMax 3
#UseDNS no
#PidFile /run/sshd.pid
#MaxStartups 10:30:100
#PermitTunnel no
#ChrootDirectory none
#VersionAddendum none
```

```
# no default banner path
#Banner none
```

```
# Allow client to pass locale and color environment variables
AcceptEnv LANG LC_* COLORTERM NO_COLOR
```

```
# override default of no subsystems
Subsystem sftp /usr/lib/openssh/sftp-server
```

```
# Example of overriding settings on a per-user basis
```

```
#Match User anoncvs
#    X11Forwarding no
#    AllowTcpForwarding no
#    PermitTTY no
#    ForceCommand cvs server
#KbdInteractiveAuthentication yes
PasswordAuthentication yes
UsePAM yes
```

```
vboxuser@Ubuntu-Target:~$ sudo systemctl restart ssh
```

```
vboxuser@Ubuntu-Target:~$ _
```

Activate Windows
Go to Settings to activate Windows.

Applications

Home

Trash

File System

```
kali@kali: ~  
Session Actions Edit View Help  
(kali@kali)-[~]  
$ ssh vboxuser@192.168.56.102  
(vboxuser@192.168.56.102) Password:  
(vboxuser@192.168.56.102) Verification code:  
(vboxuser@192.168.56.102) Password:  
(vboxuser@192.168.56.102) Verification code:  
(vboxuser@192.168.56.102) Password:  
(vboxuser@192.168.56.102) Verification code:  
Connection closed by 192.168.56.102 port 22  
(kali@kali)-[~]  
$
```

Activate Windows
Go to Settings to activate Windows.