

Ejercicio Time Series - Clase 2

Daniel Ferreira Zanchetta and Lais Silva Almeida Zanchetta

31/05/2020


```
#setwd("/Users/laisalmeida/Desktop/Master/Data Analytics/Aula 22 - 08-05/Time_Series_Datasets/")
setwd("C:/Users/Daniel/Documents/Certificados & Faculdade/UPC Master Big Data/Data Analytics/Time Series/Sesion 08/05/20/Time_Series_Datasets/")
#Reading and formatting the file
goods <- read.csv2(file = "INE_IPC.csv", sep = ";", header = TRUE, nrows = 13, skip = 6)
```

Exercise 1) Read the IPC data as you did in the last homework. Then compute the Inflation as $Inflation \leftarrow 100 * diff(IPC, lag=12) / lag(IPC, k=-12)$.

```
cols <- colnames(goods)
end_block_IPCindex <- min(grep(".1", cols, fixed = TRUE))-1
for ( i in 2:end_block_IPCindex){
  cols[i] <- paste0(cols[i], ".0")
}
cols[782] <- sub(cols[782], "X.1", "X.4")
```

IPC Index

```
end <- max(grep(".0", cols, fixed = TRUE))
cols.0 <- cols[end:2]
# IPC is only taking into consideration the "Indice geral" row
IPC <- as.numeric(
  t(read.csv2(file = "INE_IPC.csv", skip=7,
    dec = ".", header = FALSE,
    encoding = "UTF-8", row.names = 1,
    nrows=1)[1, (end-1):1])
)
year <- as.numeric(substr(cols.0, start=2, stop=5))
month <- as.numeric(substr(cols.0, start=7, stop=8))
tt <- year + month/12
IPC.ts <- ts(IPC, frequency = 12, start=c(year[1], month[1]))
plot(tt, IPC, type="l", main="IPC index", xlab="Time", lab=c(8, 5, 7))
abline(v=seq(2002, 2018, by=2), lty=2, col=8)
```



```
#Computing the inflation
Inflation <- 100*diff(IPC,lag=12)/lag(IPC,k=-12)


## Warning in 100 * diff(IPC, lag = 12)/lag(IPC, k = -12): comprimento do
objeto
## maior não é múltiplo do comprimento do objeto menor
```

Exercise 2) Join the two previous time series with `ts.union` and plot the resulting bivariate series.

```
Inflation.ts <- ts(Inflation, start=c(year[1], month[1]), frequency = 12)

tsunion <- ts.union(IPC.ts,Inflation.ts)
plot(tsunion,main="Union IPC and Inflation Time Series", yax.flip=TRUE)
abline(v=seq(2002,2018,by=2),lty=2,col=8)
```


Union IPC and Inflation Time Series



Exercise 3) Define `IPC.d1.d12` as the IPC series after having taken difference of orders 1 (regular difference) and 12 (seasonal difference). Define `Infl.d1` as the regular difference of Inflation. Check that both series are very similar.

```
IPCindexdiff12.ts <- diff(IPC.ts, lag=12)
IPC.d1.d12 <- diff(IPCindexdiff12.ts, lag=1)
Infl.d1 <- diff(Inflation.ts, lag = 1)

plot(ts.union(IPC.d1.d12, Infl.d1))
```



Exercise 4) Using the function window, cut the time series IPC in two parts, a training part until December 2016, and a test part from January 2017. Call them IPC.tr and IPC.te, respectively.

```
IPC.tr <- window(IPC.ts, start=c(year[1], month[1]), end = c(2016, 12))
IPC.te <- window(IPC.ts, start=c(2017, 1))
```

Exercise 5) Compute the regular and seasonal difference of IPC.tr and call the resulting series IPC.tr.d1.d12.


- a. Plot this series, as well as its ACF and its PACF.
- b. Do you think IPC.tr.d1.d12 is white noise?

Reply: At first glance they look like white noise, however we **do not** think it can be seen as white noise, because the ACF and PACF plots show correlations between the data.


```
IPCTrdiff12.ts <- ts(diff(IPC.tr, lag=12), frequency = 12,
start=c(year[1], month[1]))
IPC.tr.d1.d12 <- ts(diff(IPCTrdiff12.ts, lag=1), frequency = 12,
start=c(year[1], month[1]))

op<-par(mfrow=c(2,2))
acf(IPC.tr.d1.d12, main = "ACF")
pacf(IPC.tr.d1.d12, main = "PACF")
plot.ts(IPC.tr.d1.d12, type="l", main="IPC Regular and Seasonal
```

```
Differences", xlab="Time")
abline(v=seq(2002,2018,by=2),lty=2,col=8)
par(op)
```



3C Regular and Seasonal Differenc




Exercise 6) Use the functions `HoltWinters` (with the default parameters) and `predict.HoltWinters` to predict the next 15 values of `IPC.tr.d1.d12` (these are the forecasting of the values corresponding to the period from January 2017 to March 2018). Plot the forecasted object.

```
library(astsa)
IPC.HW <- HoltWinters(IPC.tr.d1.d12)
pred.HW <- predict(IPC.HW, n.ahead=15, prediction.interval = TRUE)

#library(ggplot2)
#library(forecast)
plot(IPC.HW, predicted.values = pred.HW)
```

Holt-Winters filtering




Exercise 7) Use the expression $X_t = X_{t-1} + X_{t-12} - X_{t-13} + a_t$ to compute the predictions for the IPC j steps ahead, $X_{T+j|T}$, $j = 1, \dots, 15$. Compare these predictions with the values of the test values in `IPC.te`. Take into account the following indications:

- You can use the predicted values for `IPC.tr.d1.d12` obtained before as a_{T+j} .
- Once you have computed $X_{T+j|T}$, you can use this value as an estimation of X_{T+j} when computing $X_{T+h|T}$ for $h > j$.

```
frcst.lag = IPC.tr[1:180]

#Para los intervalor de test
for (i in ((length(IPC.tr)+1):(length(IPC.tr)+length(IPC.te)))){
  #Xt = Xt-1 +Xt-12 -Xt-13 + at
  frcst.lag[i] <- frcst.lag[i-1]+frcst.lag[i-12]-frcst.lag[i-
13]+pred.HW[i-180]
}
frcst.lag.ts <- ts(frcst.lag, frequency = 12, start=c(year[1], month[1]))

plot(frcst.lag.ts)
lines(IPC.te,col="red")
```




Exercise 8) Use the functions `HoltWinters` (with the default parameters) and `predict.HoltWinters` to predict the next 15 values of `IPC.tr` (these are the forecasting of the values corresponding to the period from January 2017 to March 2018).

- a. Plot the forecasted object.

```
IPC.tr.HW <- HoltWinters(IPC.tr)
pred.IPC.tr.HW <- predict(IPC.tr.HW, n.ahead=15, prediction.interval=TRUE)

plot(IPC.tr.HW, predicted.values = pred.IPC.tr.HW)
```


Holt-Winters filtering



- b. Compare these predictions with the values of the test values in IPC.te.

```
plot(IPC.tr.HW, predicted.values = pred.IPC.tr.HW)  
lines(IPC.te,col="blue")
```

Holt-Winters filtering



- c. (Optional) Which forecasting method is preferable in this case, the one used here or that used in the previous exercise?

Reply: In our experience with both ways to calculate the forecast so far, we prefer the method used here.

Exercise 9) Based on the ACF and the PACF, propose at least two different ARMA models for IPC.tr.d1.d12.

- a. Estimate the ARMA models you propose. Plot the residuals of them and the residuals ACF and PACF.

```
#par(mfrow=c(1,2))
#acf(IPC.tr.d1.d12)
#pacf(IPC.tr.d1.d12)

#Model 1) ARMA(1,1)
library(forecast)

## Registered S3 method overwritten by 'quantmod':
##   method      from
##   as.zoo.data.frame zoo


##
## Attaching package: 'forecast'

## The following object is masked from 'package:astsa':
##
##   gas

arma.1.1.d1.d12.IPC <- Arima(IPC.tr.d1.d12,order=c(1,0,1))


plot(arma.1.1.d1.d12.IPC$residuals,main=paste("Var=",round(var(arma.1.1.d1.d12.IPC$residuals),4)))
```

Var= 0.1021




```
acf(arma.1.1.d1.d12.IPC$residuals)
```

Series arma.1.1.d1.d12.IPC\$residuals



```
pacf(arma.1.1.d1.d12.IPC$residuals)
```


Series arma.1.1.d1.d12.IPC\$residuals



```
#Model 2) ARMA(0,1)
library(forecast)
arma.1.d1.d12.IPC <- Arima(IPC.tr.d1.d12,order=c(0,0,1))


plot(arma.1.d1.d12.IPC$residuals,main=paste("Var=",round(var(arma.1.d1.d12.IPC$residuals),4)))
```

Var= 0.105




```
acf(arma.1.d1.d12.IPC$residuals)
```

Series arma.1.d1.d12.IPC\$residuals



```
pacf(arma.1.d1.d12.IPC$residuals)
```



- b. Which is the model suggested by auto.arima? Plot the residuals of them and the residuals ACF and PACF.


Reply: ARIMA(1,0,0)(0,0,1)[12] with zero mean

```
suggested.model <- auto.arima(IPC.tr.d1.d12)
print(suggested.model)

## Series: IPC.tr.d1.d12
## ARIMA(1,0,0)(0,0,1)[12] with zero mean
##
## Coefficients:
##          ar1          sma1
##      0.4134   -0.7176
## s.e.  0.0719    0.0665
##
## sigma^2 estimated as 0.06771:  log likelihood=-15.57
## AIC=37.13   AICc=37.28   BIC=46.49


plot(suggested.model$residuals, main=paste("Var=", round(var(suggested.model$residuals), 4)))
```

Var= 0.067




```
acf(suggested.model$residuals)
```

Series suggested.model\$residuals



```
pacf(suggested.model$residuals)
```



c. Which ARMA model do you chose finally for IPC.tr.d1.d12?

Reply: As per the results seen we would choose the model provided by auto.arima function. The values seem more adjusted, and even when comparing ACF and PACF, the lags are within the boundaries.

Exercise 10) Which is the model suggested by auto.arima for the time series IPC.tr? Plot the residuals of this model and the residuals ACF and PACF.


Reply: ARIMA(1,1,0)(0,1,1)[12]

```
IPC.tr.auto.arima <- auto.arima(IPC.tr)
print(IPC.tr.auto.arima)

## Series: IPC.tr
## ARIMA(1,1,0)(0,1,1)[12]
##
## Coefficients:
##          ar1      sma1
##      0.4134  -0.7175
## s.e.  0.0719   0.0665
##
## sigma^2 estimated as 0.06814: log likelihood=-15.57
## AIC=37.14  AICc=37.29  BIC=46.5


plot(IPC.tr.auto.arima$residuals,main=paste("Var=",round(var(IPC.tr.auto.arima$residuals),4)))
```

Var= 0.0625




```
acf(IPC.tr.auto.arima$residuals)
```

Series IPC.tr.auto.arima\$residuals




```
pacf(IPC.tr.auto.arima$residuals)
```

Exercise 11) Consider the ARMA model suggested and estimated by `auto.arima` for the time series `IPC.tr.d1.d12`. Use the function `forecast` from library `forecast` to predict the next 15 values of `IPC.tr.d1.d12` (these are the forecasting of the values corresponding to the period from January 2017 to March 2018). Plot the forecasted object using `plot` and `autoplot`.


```
library(forecast)
library(ggplot2)
frcst.suggested.model <- forecast(suggested.model,h=15)
autoplot(frcst.suggested.model)
```

Forecasts from ARIMA(1,0,0)(0,0,1)[12] with zero mea



```
plot(frcst.suggested.model)
```

Forecasts from ARIMA(1,0,0)(0,0,1)[12] with zero me




Exercise 12) Let X_t be the time series `IPC.tr`. Use the expression $X_t = X_{t-1} + X_{t-12} - X_{t-13}$ + at to compute the predictions for the IPC j steps ahead, $X_{T+j|T}$, $j = 1, \dots, 15$. Compare these predictions with the values of the test values in `IPC.te`. Take into account the following indications:

- You can use the predicted values for `IPC.tr.d1.d12` obtained from the previous ARMA model.

```
frcst.IPC.tr.arma = IPC.tr[1:180]

for (i in ((length(IPC.tr)+1):(length(IPC.tr)+length(IPC.te)))){
  frcst.IPC.tr.arma[i] <- frcst.IPC.tr.arma[i-1] + frcst.IPC.tr.arma[i-
12] - frcst.IPC.tr.arma[i-13] + frcst.suggested.model$mean[i-180]
}
frcst.lag.arma.ts <- ts(frcst.IPC.tr.arma, frequency = 12,
start=c(year[1], month[1]))

plot(frcst.lag.arma.ts)
lines(IPC.te,col="red")
```



- Once you have computed $X_{T+j|T}$, you can use this value as an estimation of X_{T+j} when computing $X_{T+h|T}$ for $h > j$.


```
###
h = length(frcst.IPC.tr.arma)+15
frcst.IPC.tr.arma.2 = frcst.lag.arma.ts[1:195]
```

```

for (i in ((length(frcst.IPC.tr.arma.2)+1):h)){
  frcst.IPC.tr.arma.2[i] <- frcst.IPC.tr.arma.2[i-1] +
frcst.IPC.tr.arma.2[i-12] - frcst.IPC.tr.arma.2[i-13]
}
frcst.lag.arma.ts.2 <- ts(frcst.IPC.tr.arma.2, frequency = 12,
start=c(year[1], month[1]))

plot(frcst.lag.arma.ts.2)
lines(IPC.te,col="red")

```




Exercise 13) Consider the ARIMA model suggested and estimated by auto.arima for the time series IPC.tr. Use the function forecast from library forecast to predict the next 15 values of IPC.tr (these are the forecasting of the values corresponding to the period from January 2017 to March 2018).

- a. Plot the forecasted object using plot and autoplot.


```

frcst.IPC.tr.auto.arima <- forecast(IPC.tr.auto.arima,h=15)
autoplot(frcst.IPC.tr.auto.arima)

```




```
plot(frcst.IPC.tr.auto.arima)
```



b. Compare these predictions with the values of the test values in IPC.te.

```
autoplot(frcst.IPC.tr.auto.arima) +
  autolayer(IPC.te, series="Real") +
  autolayer(frcst.IPC.tr.auto.arima$mean, series="Forecast")
```




- c. (Optional) Do they coincide the forecasting done here and that done in the previous exercise?

Reply: They coincide a lot. We've observed a minimum difference in the predicted values, which are totally irrelevant tough.

Exercise 14) Compare the predictions obtained by Holt-Winters and by the ARIMA model with the true values of IPC (IPC.te).

```
autoplot(IPC.tr) +
  autolayer(IPC.te, series="IPC Test Data") +
  autolayer(frcst.IPC.tr.auto.arima$mean, series="Forecast ARIMA") +
  autolayer(pred.IPC.tr.HW[,1], series = "Forecast Holt-Winters")
```



Reply: We thought it would be a good way to compare the two forecasts with the real test data by plotting it. At first glance, we may see that apparently the prediction by the Holt-Winters model gets closer to the IPC Test data.