





敬业钢铁有限公司 Jingye Iron and Steel Co.,Ltd.







中国认可 产品 PRODUCT CNAS C162-P

质量证明书 Mill Test Certificate

	1 WOAT	bloop	STATE						20117				102 15 PT 003				341						
	订货单位 Customer		敬业钢铁有限公司							产品名称 Commodity				钢筋混凝土用钢 : 热轧光圆钢筋 STEEL REINFORCED CONCRETE: HOT ROLLED RIBBED BARS									
-	收货单位 Consignee		敬业钢铁有限公司							装车作业单编号 Loading Job No.				LT2505251025			质保书编号 Certificate No.			250525W00003			
执行标准 Standard			GB 1499. 1-2024							签发日期 Date of Issue				2025/05/25			合同编号 Contract No.			NW250525003			
牌号 Grade			HPB300							车号 Truck No.				Terrain 1			发货日期 Date of Delivery			2025/05/25			
生产许可证编号 Permission No.			(冀) XK05-001-00001						交货状态 Delivery State				热轧 Hot rolled										
项	轧制批号	炉号	规格	件数	重量					容炼成分 it Analysis%						拉伸试验 x1 TENSILE TEST		R°m∕ R°el	R°el ∕Rel	弯曲 试验	反弯 试验		
次ITEM	LOT No.	HEAT No.	DIMENSION (mm)	PCS	Weight (t)	С	Si	Mn	Р	S	V	Cr	Nb	Ceq	屈服 RelY.S	抗拉 RmT.S	力 总 延 伸 Agt%	K CI	/ Ke1	W(3)11	W(3 <u>W</u>		
No.	OUP					- 2 X10	- 2 X10	- 2 X10	- 3 X10	- 3 X10	- 3 X10	- 3 X10	- 3 X10	- 2 X10	MPa	MPa	118 0 //	XULL			4		
001	X325050026004	25803011	Ф6	25	59.80	23	19	85	32	16	3	50	1	38	345	550	14. 6	1. 59	1.10	合格	合格		

合格 1.54 1.09 15.6 370 570 合格 1.55 1.10 360 15.0 合计 (TOTAL) 59.80

注释 NOTE

Y. S屈服强度=Yield Strength T. S抗拉强度=Tensile Strength 最大力总延伸Agt%=Total elongation at maximum force.

Rom/Roel=Tensile/yield strength ratio

R° e1/Re1=Yield Strength / Globle Standard's Yield Strength

弯曲试验=Bending Test 弯曲角度=Angle Of Bend 反弯试验=Rebend Test

备注

本产品N含量能保证,重量偏差、钢筋尺寸、表面质量、金相组织均符合标准规定。请用户按产品批号验收,如有质量异议请填写好质量异议函,并将实物妥善保管好,切勿动用。 THE N CONTENT OF THIS PRODUCT CAN BE GUARANTEED, AND THE WEIGHT DEVIATION, STEEL BAR SIZE, SURFACE QUALITY, AND METALLOGRAPHIC STRUCTURE ALL MEET THE STANDARD REQUIREMENTS. PLEASE HAVE THE USER INSPECT THE PRODUCT ACCORDING TO THE BATCH NUMBER. IF THERE ARE ANY QUALITY

OBJECTIONS, PLEASE FILL OUT THE QUALITY OBJECTION LETTER AND KEEP THE PHYSICAL ITEM PROPERLY. DO NOT USE IT.

计量质检部部长 General manager, department of product testing

曹建虎

CAO JIANHU

REMARK