



敬业钢铁有限公司  
Jingye Iron and Steel Co.,Ltd.  
质量证明书  
Mill Test Certificate



中国认可  
产品  
PRODUCT  
CNAS C162-P

|                           |                   |                            |                                                                         |                          |               |
|---------------------------|-------------------|----------------------------|-------------------------------------------------------------------------|--------------------------|---------------|
| 订货单位<br>Customer          | 敬业钢铁有限公司          | 产品名称<br>Commodity          | 钢筋混凝土用钢：热轧带肋钢筋<br>STEEL FOR REINFORCED CONCRETE: HOT ROLLED RIBBED BARS |                          |               |
| 收货单位<br>Consignee         | 敬业钢铁有限公司          | 装车作业单编号<br>Loading Job No. | LT251218035                                                             | 质保书编号<br>Certificate No. | 251218W002080 |
| 执行标准<br>Standard          | GB 1499.2-2024    | 签发日期<br>Date of Issue      | 2025/12/18                                                              | 合同编号<br>Contract No.     | NW2512180115  |
| 牌号<br>Grade               | HRB400E           | 车号<br>Truck No.            |                                                                         | 发货日期<br>Date of Delivery | 2025/12/18    |
| 生产许可证编号<br>Permission No. | (冀)XK05-001-00001 | 交货状态<br>Delivery State     | 热轧<br>Hot rolled                                                        |                          |               |

| 项次<br>ITEM<br>No. | 轧制批号<br>LOT No. | 炉号<br>HEAT<br>No. | 规格<br>DIMENSION<br>(mm) | 件数<br>PCS | 重量<br>Weight<br>(t) | 熔炼成分<br>Cast Analysis% |            |            |            |            |            |            |            |            | 拉伸试验 x1<br>TENSILE TEST |             | 最大<br>力总<br>延伸<br>Agt% | R°m/<br>R°e1 | R°e1<br>/Re1 | 弯曲<br>试验 | 反弯<br>试验 |
|-------------------|-----------------|-------------------|-------------------------|-----------|---------------------|------------------------|------------|------------|------------|------------|------------|------------|------------|------------|-------------------------|-------------|------------------------|--------------|--------------|----------|----------|
|                   |                 |                   |                         |           |                     | C                      | Si         | Mn         | P          | S          | V          | Cr         | Nb         | Ceq        | 屈服<br>ReLY.S            | 抗拉<br>RmT.S |                        |              |              |          |          |
|                   |                 |                   |                         |           |                     | - 2<br>X10             | - 2<br>X10 | - 2<br>X10 | - 3<br>X10 | - 3<br>X10 | - 3<br>X10 | - 3<br>X10 | - 3<br>X10 | - 2<br>X10 | MPa                     | MPa         |                        |              |              |          |          |
| 001               | X325120230028   | 25506035          | Φ8                      | 28        | 53.28               | 23                     | 26         | 137        | 28         | 21         | 23         | 57         | 1          | 47         | 440                     | 655         | 9.5                    | 1.50         | 1.09         | 合格       | 合格       |
|                   |                 |                   |                         |           |                     |                        |            |            |            |            |            |            |            |            | 450                     | 655         | 9.5                    | 1.48         | 1.10         | 合格       | 合格       |
|                   |                 |                   |                         |           |                     |                        |            |            |            |            |            |            |            |            | 430                     | 650         | 9.8                    | 1.44         | 1.11         | 合格       | 合格       |

|           |    |       |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|-----------|----|-------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 合计(TOTAL) | 28 | 53.28 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|-----------|----|-------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|

|            |                                                                                                                                                                        |  |  |  |  |  |  |  |  |  |                                                                                                                                       |  |  |  |  |  |  |  |  |  |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|--|--|--|---------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|--|--|--|
| 注释<br>NOTE | Y.S屈服强度=Yield Strength<br>T.S抗拉强度=Tensile Strength<br>最大力总延伸Agt%=Total elongation at maximum force.<br>R <sup>o</sup> m/R <sup>o</sup> e1=Tensile/yield strength ratio |  |  |  |  |  |  |  |  |  | R <sup>o</sup> e1/Re1=Yield Strength / Globe Standard's Yield Strength<br>弯曲试验=Bending Test<br>弯曲角度=Angle Of Bend<br>反弯试验=Rebend Test |  |  |  |  |  |  |  |  |  |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|--|--|--|---------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|--|--|--|

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                           |                                                                  |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|------------------------------------------------------------------|
| 备注<br>REMARK | 本产品N含量能保证，重量偏差、钢筋尺寸、表面质量、金相组织均符合标准规定。请用户按产品批号验收，如有质量异议请填写好质量异议函，并将实物妥善保管好，切勿动用。<br>THE N CONTENT OF THIS PRODUCT CAN BE GUARANTEED, AND THE WEIGHT DEVIATION, STEEL BAR SIZE, SURFACE QUALITY, AND METALLOGRAPHIC STRUCTURE ALL MEET THE STANDARD REQUIREMENTS. PLEASE HAVE THE USER INSPECT THE PRODUCT ACCORDING TO THE BATCH NUMBER. IF THERE ARE ANY QUALITY OBJECTIONS, PLEASE FILL OUT THE QUALITY OBJECTION LETTER AND KEEP THE PHYSICAL ITEM PROPERLY. DO NOT USE IT. | 曹建虎<br>CAO JIANHU                                         | <div>质量检验专用章<br/>Quality inspection dedicated seal<br/>(1)</div> |
|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 计量质检部部长<br>General manager, department of product testing |                                                                  |

