



系统编号: 0030705008 000010  
SYSTEM NO.  
合同编号:  
CONTRACT NO.  
订货单位:  
PRUCHASER  
收货单位:  
CONSIGNEE

质量证明书  
QUALITY CERTIFICATE

产品名称: 热轧光圆钢筋

PRODUCT: Hot rolled palin bars

质量记录编号: TG/CX-Q-03-04(101)  
TAB OF QUALIY  
生产许可证号: (冀)XK05-001-00013  
PROCESS LICENSE NO  
证明书号: Z2-202607100001305  
CERTIFICATE NO:  
车 号:  
VEHICLE(CARRIAGE)NO



| 牌号<br>GRADE(S)     | 标 准<br>STANDARD                                                                                                                                                                                                                                                                                                            |      |                           | 规 格<br>SIZE(S) |                                                           | 交货状态<br>DELIVERYCONDITION |                                                            |      | 总件数<br>TOTAL BUNDLE(S) |  |                        | 实际总重量<br>TOTAL ACTLIAL WEIGHT    |                          |                                                     |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|---------------------------|----------------|-----------------------------------------------------------|---------------------------|------------------------------------------------------------|------|------------------------|--|------------------------|----------------------------------|--------------------------|-----------------------------------------------------|
| HPB300             | GB 1499. 1-2024                                                                                                                                                                                                                                                                                                            |      |                           | Φ10mm          |                                                           | 热轧<br>HOT ROLLED          |                                                            |      | 27                     |  |                        | 57.75t                           |                          |                                                     |
| 批次号<br>ROLLING NO. | 化学成分（％）<br>CHEMICAL COMPOEITION                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  | 生产日期<br>DATE           | 件数<br>NUMBER                     | 实际重量（t）<br>MEASURED MASS | 重量偏差（％）<br>WEIGHT EVIATION                          |
|                    | C                                                                                                                                                                                                                                                                                                                          | Si   | Mn                        | P              | S                                                         | V                         | N                                                          | Cep  |                        |  |                        |                                  |                          |                                                     |
| 26107105BC0        | 0.24                                                                                                                                                                                                                                                                                                                       | 0.40 | 1.45                      | 0.021          | 0.026                                                     | 0.002                     | 合格                                                         | 0.49 |                        |  |                        | 2026-07-10                       |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
| 批次号<br>ROLLING NO. | 抗拉强度<br>T. S. (MPA) Rm                                                                                                                                                                                                                                                                                                     |      | 屈服强度<br>Y. S (MPa)<br>ReL |                | R <sup>o</sup> <sub>m</sub> /R <sup>o</sup> <sub>eL</sub> |                           | R <sup>o</sup> <sub>eL</sub> /R <sup>o</sup> <sub>eL</sub> |      | 断后伸长率<br>EL. (%)       |  | 最大力<br>总伸长率<br>Agt (%) | 180°弯曲实验<br>B. T.<br>弯曲压头直径 d=4d |                          | 反向弯曲<br>正向 90°，反向 20°<br>REBEND TEST<br>弯曲压头直径 d=5d |
| 26107105BC0        | 680,680                                                                                                                                                                                                                                                                                                                    |      | 460,455                   |                | 1.48, 1.51                                                |                           | 1.15, 1.13                                                 |      |                        |  | 11.8, 12.3             | 合格, 合格                           |                          | 合格                                                  |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
|                    |                                                                                                                                                                                                                                                                                                                            |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
| 注释 NOTE            | T. S.=TENSILE STRENGTH Y. S.=YIELD STRENGTH EL.=ELONGATION B. T.=BEND TEST                                                                                                                                                                                                                                                 |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        |                                  |                          |                                                     |
| 备注<br>REMARKS      | 1、无质量证明专用章无效。Effective with quality certificate stamping<br>2、兹证明本产品根据相应标准进行生产。We certify that the products have been produced according to relevant standard<br>3、N含量能保证；尺寸、表面合格。Nitrogen content complied with the standard; Dimension ,tolerances on dimensions and surface appearance are in accordance with standard. |      |                           |                |                                                           |                           |                                                            |      |                        |  |                        | 负责人：张春宇(2) 质量证明章<br>产品质量检验专用章    |                          |                                                     |

地址: 中国河北唐山市乐亭经济开发区  
ADD: Laoting Economic Development Zone Tanshan Hebei China  
URL: www.tangsteel.com.cn

销 售 电 话: +86 0315-2703265  
SALES TEL  
售后服务电话: +86 0315-27033722  
AFTER-SALES SERVICE TEL

打印人:  
PRINTER

打印日期: 2026-07-10  
PRINT DATE

发货日期: 2026-07-10  
DELIVERY DATE