


Intelligent Agents Using KQML and KIF

Individual Project



System Overview & Unit 6 Link

- ▶ Builds on the Unit 6 group design of autonomous data-retrieval agents.
- ▶ Guided by the **BDI model** of rational agency (Rao & Georgeff, 1995).
- ▶ Reflects current interest in **distributed, cooperative AI** (Xie et al., 2017).
- ▶ Emphasises **ethical AI** - transparency, fairness, accountability (Floridi & Cowls, 2019).
- ▶ Bridges theory and practice through a Python implementation of agent dialogue.



Architecture & Classes

- Object-oriented design using Python data classes
- Implements lightweight KQML message structure
- Modular, reusable, and testable agent components.

```
from dataclasses import dataclass, field
from typing import Optional, Dict
import time, uuid

def _now_iso() -> str:
    return time.strftime("%Y-%m-%dT%H:%M:%S", time.gmtime())

@dataclass
class KQMLMessage:
    """
    Why this design:
    - Implements a lightweight version of the KQML (Knowledge Query and Manipulation Language).
    - Demonstrates how agents communicate using performatives and parameters.
    - Designed for clarity and explanation rather than complexity.
    """
    performative: str
    sender: str
    receiver: str
    language: str = "KIF"
    ontology: str = "research-ops-1"
    content: str = ""
    in_reply_to: Optional[str] = None
    reply_with: str = field(default_factory=lambda: f"msg-{uuid.uuid4().hex[:8]}")
    timestamp: str = field(default_factory=_now_iso)
    params: Dict[str, str] = field(default_factory=dict)
```

Agent Communication (KQML + KIF)



- Implements structured agent dialogue via KQML performatives (*ask-one*, *reply*)
- Messages contain metadata for sender, receiver, and ontology context
- Logical content expressed in KIF ensures interpretability and reasoning consistency
- Promotes transparency and traceability in autonomous communication (Finin et al., 1994; Genesereth and Fikes, 1992)
- Supports ethical accountability through explainable message structure (Floridi and Cowls, 2019)

```
# Initialise system
bus = MessageBus()
ext = Extractor()
ret = Retriever()
bus.register(ext)
bus.register(ret)

# Happy path
print("=== HAPPY PATH ===")
ret.start_dialogue("nano")

# Error path (empty query)
print("\n=== ERROR PATH ===")
ret.start_dialogue("") # should produce an error
```

“Happy Path” Demonstration



- Demonstrates complete communication cycle between Retriever and Extractor.
- Valid data request processed and summarised as structured KIF output.
- Timestamped logs provide auditability and reproducibility
- Confirms successful task fulfilment and agent coordination (Jennings and Bussmann, 2003)
- Output illustrates system transparency and ethical clarity (Gal, 2022)

```
=== HAPPY PATH ===
SEND (ask-one
:sender Retriever
:receiver Extractor
:language KIF
:ontology research-ops-1
:reply-with msg-286bcf7d
:timestamp 2025-10-13T21:30:50
:content (findPapers "nano"))

RECV (ask-one
:sender Retriever
:receiver Extractor
:language KIF
:ontology research-ops-1
:reply-with msg-286bcf7d
:timestamp 2025-10-13T21:30:50
:content (findPapers "nano"))

RECV (reply
:sender Extractor
:receiver Retriever
:language KIF
:ontology research-ops-1
:reply-with msg-60031a63
:timestamp 2025-10-13T21:30:50
:in-reply-to msg-286bcf7d
:content ((Paper p1) (hasTitle p1 "Nanomaterials Survey") (hasDOI p1 "10.1234/nano.001") (hasSummary p1 "Overview of nanomaterial synt
hesis and properties.")))

RECV (reply
:sender Extractor
:receiver Retriever
:language KIF
:ontology research-ops-1
:reply-with msg-60031a63
:timestamp 2025-10-13T21:30:50
:in-reply-to msg-286bcf7d
:content ((Paper p1) (hasTitle p1 "Nanomaterials Survey") (hasDOI p1 "10.1234/nano.001") (hasSummary p1 "Overview of nanomaterial synt
hesis and properties.")))
```

Error Handling & Retry Logic



- Detects invalid or empty queries and returns structured error responses
- Prevents propagation of faulty requests across the network
- Logs each error with timestamps for traceability and recovery
- Implements retry mechanism for message resilience (Bellifemine et al., 2007)
- Meets ethical standard of explicability in AI system behaviour (Floridi and Cowls, 2019)

```
---- SUMMARY ----  
- Nanomaterials Survey [10.1234/nano.001]  
  Overview of nanomaterial synthesis and properties.
```

```
=== ERROR PATH ===  
SEND (ask-one  
  :sender Retriever  
  :receiver Extractor  
  :language KIF  
  :ontology research-ops-1  
  :reply-with msg-fecf2ee6  
  :timestamp 2025-10-13T21:30:50  
  :content (findPapers ""))
```

```
RECV (ask-one  
  :sender Retriever  
  :receiver Extractor  
  :language KIF  
  :ontology research-ops-1  
  :reply-with msg-fecf2ee6  
  :timestamp 2025-10-13T21:30:50  
  :content (findPapers ""))
```

```
RECV (error  
  :sender Extractor  
  :receiver Retriever  
  :language KIF  
  :ontology research-ops-1  
  :reply-with msg-aeb821c1  
  :timestamp 2025-10-13T21:30:50  
  :in-reply-to msg-fecf2ee6  
  :content (reason EmptyQuery))
```

```
RECV (error  
  :sender Extractor  
  :receiver Retriever  
  :language KIF  
  :ontology research-ops-1  
  :reply-with msg-aeb821c1  
  :timestamp 2025-10-13T21:30:50  
  :in-reply-to msg-fecf2ee6
```

Subscriptions & Reasoning



- Demonstrates *subscribe* performative for dynamic updates and ongoing monitoring
- Extractor sends *inform* messages autonomously when new data appears
- Introduces ranking and scoring of results to simulate relevance reasoning
- Embodies proactive and reactive agent traits (Wooldridge and Jennings, 1995)
- Enhances autonomy and adaptiveness within cooperative multi-agent systems (Nguyen et al., 2018)

```
class Retriever(Agent):
    """Search & Retrieval with pending request map and correlation checks."""
    def __init__(self, name="Retriever"):
        super().__init__(name)
        self.last_answers: List[str] = []
        self.pending: Dict[str, str] = {} # reply_with -> term

    def start_dialogue(self, term: str):
        ask = KQMLMessage(
            performative="ask-one", sender=self.name, receiver="Extractor",
            content=f'(findPapers "{term}")'
        )
        self.pending[ask.reply_with] = term
        self.send(ask)

    def subscribe_updates(self, term: str):
        sub = KQMLMessage(
            performative="subscribe", sender=self.name, receiver="Extractor",
            content=f'(findPapers "{term}")'
        )
        self.pending[sub.reply_with] = term
        self.send(sub)
```

Testing & Validation

- Automated tests executed using Python unittest framework
- Validates both successful communication and error recovery processes
- Confirms reliable message exchange under normal and fault conditions
- Reinforces system dependability and maintainability (Bellifemine et al., 2007)
- Transparent logging and reproducibility uphold ethical and technical standards (Floridi and Cows, 2019).

```
import unittest

class TestAgents(unittest.TestCase):
    def setUp(self):
        self.bus = MessageBus()
        self.ext = Extractor()
        self.ret = Retriever()
        self.bus.register(self.ext)
        self.bus.register(self.ret)

    def test_happy_path_returns_facts(self):
        self.ret.start_dialogue("nano")
        combined = " ".join(self.ret.last_answers)
        self.assertIn("hasDOI", combined)

    def test_error_on_empty_query(self):
        self.ret.start_dialogue("")
        self.assertTrue(any(ans.startswith("ERROR ") for ans in self.ret.last_answers))

suite = unittest.TestLoader().loadTestsFromTestCase(TestAgents)
unittest.TextTestRunner(verbosity=2).run(suite)

test_error_on_empty_query (__main__.TestAgents.test_error_on_empty_query) ... ok
test_happy_path_returns_facts (__main__.TestAgents.test_happy_path_returns_facts) ... ok

-----
Ran 2 tests in 0.012s

OK
```


Limitations & Future Work

- ▶ All design goals from Unit 6 successfully implemented in Python: data retrieval, processing, and structured KIF output.
- ▶ Agents demonstrated autonomy and cooperation via KQML performatives.
- ▶ Fault tolerance and retry logic improved robustness and reliability (Bellifemine et al., 2007).
- ▶ Communication remained interpretable, fulfilling ethical transparency standards (Floridi and Cowls, 2019).
- ▶ Code modularity and in-line documentation enhanced maintainability and scalability (Jennings and Bussmann, 2003).
- ▶ Minor limitations: static dataset and simplified ontology restrict external integration.



Conclusion & Ethical Reflection

- ▶ Developed a functional multi-agent system based on KQML and KIF protocols.
- ▶ Demonstrated autonomy, communication, and transparency.
- ▶ Fulfilled ethical design criteria through interpretability and accountability.
- ▶ Provides scalable foundation for responsible AI development.
- ▶ Future work: dynamic ontologies, API integration, and adaptive learning mechanisms.



References

References:

- Barba-Guamán, L., Luján-Mora, S. and López, V. (2017) *Belief-Desire-Intention model for reasoning procedure*, in *A BDI Agent Model for Behavioural Change Process in People with Chronic Disease*. ResearchGate. Available at: https://www.researchgate.net/figure/Belief-Desire-Intention-model-for-reasoning-procedure_fig1_313617511 (Accessed: 12 October 2025).
- Bellifemine, F., Caire, G. and Greenwood, D. (2007) *Developing Multi-Agent Systems with JADE*. Chichester: John Wiley & Sons. Available at: <https://onlinelibrary.wiley.com/doi/book/10.1002/9780470058411> (Accessed: 12 October 2025).
- da Costa, A.C.R., Lima, T., Feitosa, D. and Lima, R. (2020) *A Survey on Multi-Agent Systems: Concepts, Tools and Applications*. Engineering Applications of Artificial Intelligence, 90, p. 103509.
- Finin, T., Fritzon, R., McKay, D. and McEntire, R. (1994) KQML as an Agent Communication Language.' Proceedings of the 3rd International Conference on Information and Knowledge Management. Available at: <https://dl.acm.org/doi/10.1145/191246.191322> (Accessed: 12 October 2025).
- Floridi, L. and Cowls, J. (2019) *Translating Principles into Practices of Digital Ethics: Five Risks of Being Unethical*. Philosophy & Technology, 33(4), pp. 701-722. Available at: <https://link.springer.com/article/10.1007/s13347-019-00354-x> (Accessed: 12 October 2025).
- Gal, K. (2022) 'Multi-Agent Systems: Technical and Ethical Challenges.' Daedalus, 151(2), pp. 114-128. Available at: <https://direct.mit.edu/daed/article/151/2/114/110611> (Accessed: 12 October 2025).
- Genesereth, M.R. and Fikes, R.E. (1992) *Knowledge Interchange Format 3.0 Reference Manual*. Stanford University, Logic Group. Available at: <http://www-ksl.stanford.edu/knowledge-sharing/kif/> (Accessed: 12 October 2025).
- Gil, Y., Greenspan, R., Krause, J. and Schulz, S. (2020) *Toward Trustworthy AI: Best Practices for Explainability and Testing*. AI Magazine, 41(3), pp. 10-23.
- Jennings, N.R. (2001) *An Agent-Based Approach for Building Complex Software Systems*. Communications of the ACM, 44(4), pp. 35-41. Available at: <https://doi.org/10.1145/367211.367250> (Accessed: 12 October 2025).
- Jennings, N.R. and Bussmann, S. (2003) *Agent-Based Control Systems: Why Are They Suited to Engineering Complex Systems?* IEEE Control Systems Magazine, 23(3), pp. 61-74. Available at: <https://doi.org/10.1109/MCS.2003.1200249> (Accessed: 12 October 2025).
- Nguyen, D.T., Nguyen, T. and Nahavandi, S. (2018) *Deep Reinforcement Learning for Multiagent Systems: A Review of Challenges, Solutions, and Applications*. IEEE Access, 6, pp. 28520-28544. Available at: <https://ieeexplore.ieee.org/document/9043893> (Accessed: 12 October 2025).
- Rao, A.S. and Georgeff, M.P. (1995) *BDI Agents: From Theory to Practice*. Proceedings of the 1st International Conference on Multi-Agent Systems (ICMAS '95). Available at: <https://cdn.aaai.org/ICMAS/1995/ICMAS95-042.pdf> (Accessed: 12 October 2025).
- Shoham, Y. and Leyton-Brown, K. (2008) *Multiagent Systems: Algorithmic, Game-Theoretic, and Logical Foundations*. Cambridge: Cambridge University Press.
- Woodridge, M. and Jennings, N.R. (1995) *Intelligent Agents: Theory and Practice*. Knowledge Engineering Review, 10(2), pp. 115-152. Available at: https://www.cs.cmu.edu/~motionplanning/papers/sbp_papers/integrated1/woodridge_intelligent_agents.pdf (Accessed: 12 October 2025).
- Xie, J., Lui C.C.. (2017) *Multi-Agent Systems and Their Applications*. Artificial Intelligence Review, 47(3), pp. 1-33. Available at: https://www.researchgate.net/publication/318421603_Multi-agent_systems_and_their_applications (Accessed: 12 October 2025).