

# Ideal Abstraction for Depth-Bounded Processes

Thomas Wies   **Damien Zufferey**   Thomas A. Henzinger

IST Austria

October 11, 2011

# What are Depth-Bounded Processes (DBP) ?

As buzzwords: concurrent/distributed message-passing programs with process creation and mobility.  
(Warning restrictions may apply.)


For the programmers: some class of programs using the actor model (Erlang, Scala, Akka, ActorFoundry, ...)

For the theoreticians: a fragment of the  $\pi$ -calculus.


# Example: client-server communication pattern




# Example: client-server communication pattern




# Example: client-server communication pattern




# Example: client-server communication pattern



# Example: client-server communication pattern




# Example: client-server communication pattern






# Example: client-server communication pattern




# What kind of properties are we looking at ?

Safety properties, more precisely the control-state reachability problem (aka covering problem).



# What kind of properties are we looking at ?

Safety properties, more precisely the control-state reachability problem (aka covering problem).



# What kind of properties are we looking at ?

Safety properties, more precisely the control-state reachability problem (aka covering problem).

initial state




# What kind of properties are we looking at ?

Safety properties, more precisely the control-state reachability problem (aka covering problem).




# What kind of properties are we looking at ?

Safety properties, more precisely the control-state reachability problem (aka covering problem).




# What kind of properties are we looking at ?

Safety properties, more precisely the control-state reachability problem (aka covering problem).



# What kind of properties are we looking at ?


Safety properties, more precisely the control-state reachability problem (aka covering problem).





# What kind of properties are we looking at ?

Safety properties, more precisely the control-state reachability problem (aka covering problem).



A well-structured transition system (WSTS) is a transition system  $\langle S, \rightarrow, \leq \rangle$  such that:

- $\leq$  is a well-quasi-ordering (wqo),  
i.e. well-founded + no infinite antichain.
- compatibility of  $\leq$  w.r.t.  $\rightarrow$


$$\begin{array}{ccc} & & * \\ & t \longrightarrow & t' \\ \forall & \vee | & \vee | \quad \exists \\ & s \longrightarrow & s' \end{array}$$

For more detail see:


[Finkel and Schnoebelen, 2001, Abdulla et al., 1996]

# Depth-bounded systems: [Meyer, 2008]


System with a bound on the longest acyclic path.  
(Concretely: it is not possible to encode an infinite memory.)




# Backward algorithm for covering




# Backward algorithm for covering




# Backward algorithm for covering



# Backward algorithm for covering




# Forward algorithm for covering







# Forward algorithm for covering



# Forward algorithm for covering



# Forward algorithm for covering



# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]






# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]




# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]






# Adequate domain of limits

ADL: [Geeraerts et al., 2006]

Further developed in [Finkel and Goubault-Larrecq, 2009]

Applied to DBP in [Wies et al., 2010]

$$(\nu x)(Server(x) \mid !(\nu y)(Client(y, x) \mid !Messages(x, y)))$$



# When does acceleration work ? (flat systems)

Usually forward algorithms are based on acceleration. By acceleration we mean computing the result of executing a loop infinitely many time.

We can see this as computing the result of execution traces of length  $< \omega^2$ . Concretely, it means that the algorithm can saturate the covering set by executing only simple loops (see [Bardin et al., 2005]). This condition is known as flattability.





Figure: Example of a flat program

# DBP are intrinsically not flat.

initial configuration:



covering set:




How many steps are there between the initial configuration and the final configuration ?  
 $\omega^2$  steps

Hence, we need to consider nested loops if we want to compute the covering set.


# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.



# From acceleration to widening


Acceleration considers transitions. Widening only states.






# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.




# From acceleration to widening

Acceleration considers transitions. Widening only states.



# From acceleration to widening

Acceleration considers transitions. Widening only states.



- Concrete domain:  $D = \mathcal{P}(S)$
- Abstract domain:  $D_{\downarrow} = \{ \downarrow X \mid X \subseteq S \}$

The abstract domain can be further refined from the set of downward-closed set to the set of ideals (downward-closed and *directed*).

- Abstract domain 2:  $D_{Idl}$

An arbitrary downward-closed set can be represented as the finite union of ideals.



# Widening (1)

Goal: try to mimic acceleration (when possible), and force termination

A set-widening operator ( $\nabla$ ) for a poset  $X$  is partial function  $(\mathcal{P}(X) \rightarrow X)$  that satisfies:

**Covering** : for all  $Y \subseteq X$ ,  $y \in Y \Rightarrow y \leq \nabla(Y)$ ;

**Termination** : widening of any ascending chain stabilizes.

Reason of using a set-widening operator: we need the history.


Lifting a widening operators from  $Idl(S)$  to  $D_{Idl}$ : going from elements of the domain to finite powerset is non-trivial. We assume that the ordering is a *bqo*. Thus  $Idl(S)$  is also a *bqo*.

Given an ascending chain:  $C = \{L_i\}_{0 \leq i \leq n}$ ,  $C \subseteq D_{Idl}$  (history)


- $\nabla(\{L_0\}) = \{L_0\}$
- $\nabla(\{L_0, \dots, L_i\}) = \nabla(\{L_0, \dots, L_{i-1}\}) \sqcup \{\nabla_S(\mathcal{I}) \mid \mathcal{I} \text{ max ascending chain in } \nabla(\{L_0, \dots, L_{i-1}\})\}$

Why a *bqo* ? To avoid having an infinite antichain in  $Idl(S)$ .


# Set-widening for DBP (1)




# Set-widening for DBP (1)




# Set-widening for DBP (1)




# Set-widening for DBP (2)



# Set-widening for DBP (2)




# Set-widening for DBP (2)







# Set-widening for DBP (3)




# Set-widening for DBP (3)



# Set-widening for DBP (3)



# Set-widening for DBP (3)



# What about the precision ?

- Acceleration and widening seems like the *extreme* ends of some spectrum.
- Is there a class of nested loops for which we can compute exactly the result ?
- Can we get a good characterisation of the programs for which this kind of widening matches acceleration ?

- DBP is one of the largest fragment of the  $\pi$ -calculus for which interesting verification questions are still decidable.
- Not yet clear what is the right way of handling features such as process creation and mobility.
- WSTS approach gives decidability a result, now we are working on an efficient analysis.

Questions ?



Abdulla, P. A., Cerans, K., Jonsson, B. and Tsay, Y.-K. (1996).  
General Decidability Theorems for Infinite-State Systems.  
In *LICS* pp. 313–321,.



Bardin, S., Finkel, A., Leroux, J. and Schnoebelen, P. (2005).  
Flat Acceleration in Symbolic Model Checking.  
In *ATVA* pp. 474–488,.



Finkel, A. and Goubault-Larrecq, J. (2009).  
Forward Analysis for WSTS, Part I: Completions.  
In *STACS* vol. 09001, of *Dagstuhl Sem. Proc.* pp. 433–444,.



Finkel, A. and Schnoebelen, P. (2001).  
Well-structured transition systems everywhere!  
*Theor. Comput. Sci.* 256, 63–92.



Geeraerts, G., Raskin, J.-F. and Van Begin, L. (2006).  
Expand, Enlarge and Check: New algorithms for the coverability problem of WSTS.  
*J. Comput. Syst. Sci.* 72, 180–203.



Meyer, R. (2008).  
On Boundedness in Depth in the  $\pi$ -Calculus.  
In *IFIP TCS* vol. 273, of *IFIP* pp. 477–489, Springer.



Wies, T., Zufferey, D. and Henzinger, T. A. (2010).  
Forward Analysis of Depth-Bounded Processes.  
In *FoSSaCS 2010* vol. 4349, of *LNCS* pp. 94–108, Springer.