

Seaglider Piloting Checklist

Seaglider ID: _____ Pilot: _____ Date: _____

Source

Paraphrased from community Seaglider piloting checklists, updated for basestation3/vis workflows. See [Dive Cycle & Control Files](#) and [Trim & Flight Model](#) for the how.

Each piloting session

- ☐ Check glider `comm.log` entries and `cmdfile` state *did the last call status: latest the current complete? what directive is staged?*
- ☐ Review glider health: battery consumption and minimum voltage, internal pressure/vacuum, humidity, Iridium call quality
- ☐ Review the dive plots (vis or piloting tools): dive symmetry, vertical velocity, pitch/roll behavior
- ☐ Check the altimeter is finding the bottom and is sensibly tuned *(if in use)*
- ☐ Trim if needed; **log every `cmdfile` change** on the agreed team channel
- ☐ Confirm science sensors are producing data of expected quality; watch for anomalies
- ☐ Plot the latest surfacing positions; confirm the glider is tracking its waypoints
- ☐ Check ship-traffic and current forecasts along the track for upcoming risks
- ☐ Update the endurance estimate against *amp-hours consumed per day vs. remaining mission* plan
- ☐ Confirm mission objectives are being met; propose plan adjustments if not
- ☐ Fill in the dive/pilot log