

Introduction

This document provides the API test cases for the student and enrolment management module, based on the updated `student_route.py`. The endpoints are designed to handle the full lifecycle of student records and their official enrolment in courses, with functionality segregated by user roles.

The test cases are divided into three main sections:

1. **General Features:** Read-only access for 'Learning Advisors' and 'Managers'.
2. **Learning Advisor Features:** Full CRUD (Create, Read, Update, Delete) access for managing student and enrolment records.
3. **Teacher Features:** Read-only access to view students within a specific class.

Testing Environment

- **Tool:** Postman
- **Base URL:** `http://127.0.0.1:5000`
- **Prerequisites:**
 - The application is running, and the database is seeded.
 - A valid JWT for a **Learning Advisor** is stored as `{{laToken}}`.
 - A valid JWT for a **Manager** is stored as `{{managerToken}}`.
 - A valid JWT for a **Teacher** is stored as `{{teacherToken}}`.

General Features (Learning Advisor & Manager)

Feature: Get and Search Students

- **Feature ID:** STU-01
- **Endpoints:** `GET /student/`, `GET /student/search`

| Test Case ID | Description | Test Steps | Expected Result |
|----------------|--|---|---|
| STU-001-TC-001 | Get All Students (LA) | <ol style="list-style-type: none"> 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/. 3. Set Authorization header to Bearer {{laToken}}. 4. Send request. | ER: Status code is 200 OK . The response body is a JSON array of all student objects. |
| STU-001-TC-002 | Search for Student (Manager) | <ol style="list-style-type: none"> 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/search?id=STU001. 3. Set Authorization header to Bearer {{managerToken}}. 4. Send request. | ER: Status code is 200 OK . The response body contains the profile for student ST001. |
| STU-001-TC-003 | Unauthorised Access (Attempt by Teacher) | <ol style="list-style-type: none"> 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/. 3. Set Authorization header to Bearer {{teacherToken}}. 4. Send request. | ER: Status code is 403 Forbidden . The response body contains an access denied message. |

- **Results**

| Test Case ID | Result | Status | Notes |
|----------------|---------------|--------|-------|
| STU-001-TC-001 | Similar to ER | PASSED | N/A |
| STU-001-TC-002 | Similar to ER | PASSED | N/A |
| STU-001-TC-003 | Similar to ER | PASSED | N/A |

Feature: Get and Search Enrolments

- **Feature ID:** STU-002
- **Endpoints:** GET /student/enrolment/, GET /student/enrolment/search

| Test Case ID | Description | Test Steps | Expected Result |
|----------------|------------------------------|---|---|
| STU-002-TC-001 | Get All Enrolments (Manager) | 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/enrolment/. 3. Set Authorization header to Bearer {{managerToken}}. 4. Send request. | ER: Status code is 200 OK . The response body is a JSON array of all enrolment objects. |
| STU-002-TC-002 | Search for Enrolment (LA) | 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/enrolment/search?id=ER001. | ER: Status code is 200 OK . The response body contains the |

| | | | |
|--|--|--|--|
| | | 3. Set Authorization header to Bearer {{laToken}}. 4. Send request. | JSON object for the enrolment with the ID ER001. |
|--|--|--|--|

- **Result**

| Test Case ID | Result | Status | Notes |
|----------------|---------------|--------|-------|
| STU-002-TC-001 | Similar to ER | PASSED | N/A |
| STU-002-TC-002 | Similar to ER | PASSED | N/A |

Learning Advisor Features

Feature: Manage Student Records (CRUD)

- **Feature ID:** STU-003
- **Endpoints:** /student/learningadvisor/add, /update, /delete

| Test Case ID | Description | Test Steps | Expected Result |
|----------------|-----------------------------|--|--|
| STU-003-TC-001 | Successful Student Creation | 1. Set method to POST. 2. Set URL to {{baseUrl}}/student/learningadvisor/add. 3. Set Authorization header to Bearer {{laToken}}. 4. Set Body to raw JSON with valid, unique data for a new student. | ER: Status code is 201 Created . The response body contains |

| | | | |
|-----------------------|--|--|--|
| | | 5. Send request. | the new student object. |
| STU-003-TC-002 | Successful Student Update | <ol style="list-style-type: none"> 1. Set method to PUT. 2. Set URL to {{baseUrl}}/student/learningadvisor/update?id=STU001. 3. Set Authorization header to Bearer {{laToken}}. 4. Set Body to raw JSON: { "contact_info": "0900112233 - Uncle" }. 5. Send request. | ER: Status code is 200 OK . The response contains the message: Student updated successfully. |
| STU-003-TC-003 | Successful Student Deletion | <ol style="list-style-type: none"> 1. Set method to DELETE. 2. Set URL to {{baseUrl}}/student/learningadvisor/delete?id=STU002. 3. Set Authorization header to Bearer {{laToken}}. 4. Send request. | ER: Status code is 200 OK . The response contains the message: Student deleted successfully. |
| STU-003-TC-004 | Attempt to Add Student with Duplicate ID | <ol style="list-style-type: none"> 1. Set method to POST. 2. Set URL to {{baseUrl}}/student/learningadvisor/add. | ER: Status code is 400 Bad Request . The |

| | | | |
|--|--|--|--|
| | | 3. Set Authorization header to Bearer {{laToken}}. 4. Set Body to raw JSON with an id that already exists (e.g., STU001). 5. Send request. | response body contains an error message about a database constraint violation. |
|--|--|--|--|

- **Results**

| Test Case ID | Result | Status | Notes |
|----------------|---------------|--------|-------|
| STU-003-TC-001 | Similar to ER | PASSED | N/A |
| STU-003-TC-002 | Similar to ER | PASSED | N/A |
| STU-003-TC-003 | Similar to ER | PASSED | N/A |
| STU-003-TC-004 | Similar to ER | PASSED | N/A |

Feature: Manage Enrolment Records (CRUD)

- **Feature ID:** STU-004
- **Endpoints:** /student/enrolment/learningadvisor/add, /update, /delete

| Test Case ID | Description | Test Steps | Expected Result |
|--------------|-------------------------------|------------------------|---|
| STU-004- | Successful Enrolment Creation | 1. Set method to POST. | ER: Status code is 201 Created. |

| | | | |
|-----------------------|-------------------------------|---|--|
| TC-001 | | <ol style="list-style-type: none"> 2. Set URL to {{baseUrl}}/student/enrolment/learningadvisor/add. 3. Set Authorization header to Bearer {{laToken}}. 4. Set Body to raw JSON with valid data linking an existing student, contract, and course. 5. Send request. | <p>The response body contains the new enrolment object.</p> |
| STU-004-TC-002 | Successful Enrolment Update | <ol style="list-style-type: none"> 1. Set method to PUT. 2. Set URL to {{baseUrl}}/student/enrolment/learningadvisor/update?id=ER001. 3. Set Authorization header to Bearer {{laToken}}. 4. Set Body to raw JSON with a valid new enrolment_date. 5. Send request. | <p>ER: Status code is 200 OK. The response contains the message: Enrolment updated successfully.</p> |
| STU-004-TC-003 | Successful Enrolment Deletion | <ol style="list-style-type: none"> 1. Set method to DELETE. 2. Set URL to {{baseUrl}}/student/enrolment/learningadvisor/delete?id=ER002. 3. Set Authorization header to Bearer {{laToken}}. 4. Send request. | <p>ER: Status code is 200 OK. The response contains the message: Enrolment deleted</p> |

| | | | |
|-----------------------|--|---|---|
| | | | successfully. |
| STU-004-TC-004 | Attempt to Create Enrolment with Non-existent Contract | 1. Set method to POST. 2. Set URL to {{baseUrl}}/student/enrolment/learningadvisor/add. 3. Set Authorization header to Bearer {{laToken}}. 4. Set Body to raw JSON with a contract_id that does not exist. 5. Send request. | ER: Status code is 404 Not Found . The response body contains the message: Contract not found. |

- **Results:**

| Test Case ID | Result | Status | Notes |
|-----------------------|--------|--------|-------|
| STU-004-TC-001 | N/A | N/A | N/A |
| STU-004-TC-002 | N/A | N/A | N/A |
| STU-004-TC-003 | N/A | N/A | N/A |
| STU-004-TC-004 | N/A | N/A | N/A |

Teacher Features

Feature: Get Students by Class

- **Feature ID:** STU-005

- **Endpoint:** GET /student/teacher/

| Test Case ID | Description | Test Steps | Expected Result |
|----------------|----------------------------|---|---|
| STU-005-TC-001 | Successful Retrieval | <ol style="list-style-type: none"> 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/teacher/?id= <class_id>. (Use a valid class ID from the seed data). 3. Set Authorization header to Bearer {{teacherToken}}. 4. Send request. | ER: Status code is 200 OK . The response body is a JSON array of student profiles for all students enrolled in the specified class |
| STU-005-TC-002 | Missing Class ID Parameter | <ol style="list-style-type: none"> 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/teacher/. 3. Set Authorization header to Bearer {{teacherToken}}. 4. Send request. | ER: Status code is 404 Not Found . The response body contains the message: Missing |

| | | | |
|-----------------------|--|--|--|
| | | | class ID in query params |
| STU-005-TC-003 | Unauthorised Access (Attempt by Manager) | 1. Set method to GET. 2. Set URL to {{baseUrl}}/student/teacher/?id= <class_id>. 3. Set Authorization header to Bearer {{managerToken}}. 4. Send request. | ER: Status code is 403 Forbidden . The response body contains an access denied message. |

- **Results**

| Test Case ID | Result | Status | Notes |
|-----------------------|--------|--------|-------|
| STU-005-TC-001 | N/A | N/A | N/A |
| STU-005-TC-002 | N/A | N/A | N/A |
| STU-005-TC-003 | N/A | N/A | N/A |