Release Notes

Learn about what's new in the VMware Cloud Foundation™ (VCF) 9.1.x releases, the software components and versions included in the Bill of Materials (BOM), product support notes, resolved and known issues.

In This Chapter

- VMware Cloud Foundation 9.1 Release Notes
  - Upgrade Sequence to 9.1
  - What's New
  - Bill of Materials 9.1.0
  - Product Support Notes
  - Known Issues
  - Resolved Issues
- VMware Cloud Foundation 9.1.1.0 Release Notes
- Patch Releases 9.1.0.x
- Patch Releases 9.1.1.x
- Async Releases

VMware Cloud Foundation 9.1 Release Notes

Learn about what's new in the VMware Cloud Foundation (VCF) release, the software components and versions included in the Bill of Materials (BOM), product support notes, known and resolved issues.

VMware Cloud Foundation 9.1 | 12 MAY 2026
Check for additions and updates to these release notes.

This document contains the following sections:

- Upgrade Sequence to 9.1
- What's New
- Bill of Materials 9.1.0
- Product Support Notes
- Known Issues
- Resolved Issues

Internationalization

VMware Cloud Foundation 9.1 is available in the following languages:

- English
- Japanese
- Spanish
- French

Components of VMware Cloud Foundation 9.1 do not accept non-ASCII input.

Upgrade Sequence to 9.1

This document contains the following sections

- Important Upgrade Notes for VCF 9.1 and vSphere Foundation 9.1
  - Upgrading from VMware Cloud Foundation 5.2.x or 9.0.x to 9.1
  - Upgrading to vSphere Foundation 9.1
  - Upgrading vSphere 8 and Aria Operations 8 to 9.1

- Common Related Issues

Important Upgrade Notes for VCF 9.1 and vSphere Foundation 9.1

Upgrading your environment to version 9.1 requires a strict component upgrade sequence.

Follow the upgrade guidance based on your current environment:

Upgrading from VMware Cloud Foundation 5.2.x or 9.0.x to 9.1

For upgrading from VMware Cloud Foundation 5.2.x or 9.0.x to 9.1, see the following documentation:

- Upgrading from VMware Cloud Foundation 5.2.x to 9.1
- Upgrading from VMware Cloud Foundation 9.0.x to 9.1

Upgrading to vSphere Foundation 9.1

For upgrading from vSphere Foundation 5.2.x or 9.0.x to 9.1, see the following documentation:

- Upgrading to vSphere Foundation 9.1

Upgrading vSphere 8 and Aria Operations 8 to 9.1

As a first phase to upgrade your vSphere 8 and Aria Operations 8 virtual infrastructure to 9.1, follow the order of upgrade and deployment procedures as described:

- Upgrading vSphere 8 and Aria Operations 8 to 9.1

Common Related Issues

Incorrect upgrade sequence results in errors. See the most common scenarios described in the following documentation:

- vCenter known issues
- VCF Operations known issues
- Licenses could not be assigned to vCenter, license assignment failure on VCF 9.1

What's New

Following are the key features and capabilities of VMware Cloud Foundation 9.1:

- **Enhanced NVMe Memory Tiering.** Hypervisor tiers active pages to DRAM and cold pages to local NVMe, expanding effective memory capacity without additional DRAM and adding software-based mirroring and cost savings analysis.
- **Extended vSAN Deduplication, Compression.** Inline data reduction broadened across cluster types and workload profiles, lowering raw storage footprint per logical TB. Adding dedupe support for data-at-rest encryption, and improved compression.
- **vSphere Elastic Provisioning (Zero Touch).** Automatically bootstrap and configure ESX on bare metal servers using network-based imaging (UEFI, HTTP/S) with no manual intervention.
- **VCF Management Services.** VCF 9.1 adds a common runtime and set of components that unifies the architecture of lifecycle and operational capabilities: VCF management services. For more information, see Components in VCF and vSphere Foundation.
- **VKS and VM Fast-Deploy.** Significantly faster deployment and upgrading of VKS and VM clusters using linked clone technology, significantly improving operational agility and time to value.
- **Simplified Container-as-a-Service.** Self-service namespace provisioning with registry, ingress, quotas, and identity inherited from VCF constructs; simpler, faster way to provision a few containers without full K8s management.
- **Native Object Storage (Tech Preview).** Self-service S3 object storage for developers, with IT keeping the guardrail; deploy, scale, and manage object storage with the same workflows as block and file.
- **Live Patching for ESX for TPM-enabled hosts.** Patches applied to running kernel memory; VMs continue running with no maintenance window, covering up to 80% of patches.
- **Continuous Compliance Enforcement.** Advanced Cyber Compliance now supports continuous compliance remediation and unified security posture management for the VCF stack.

- **On-prem Ransomware Recovery.** Integrated cyber recovery to on-premises VCF isolated clean rooms.

What's New in VCF 9.1 by Component

See more information on What's New in VCF 9.1 listed within each component:

- vSphere
- vSAN
- NSX
- VCF Installer
- VCF Operations
- VCF Automation

vSphere

This document contains the following sections

- Compatibility
- ESX New Features
  - Installation
  - Storage
  - API
  - ESX Host Client
  - Snapshot Operations
  - Virtual Machine Management
  - I/O
  - Security
  - System Services
  - Memory Tiering
- vCenter New Features
  - vSphere Lifecycle Manager
  - vSphere Client
  - vCenter
  - Content Library
  - Storage
  - vSphere High Availability
  - API
  - Snapshots
  - Metrics
  - Distributed Resource Scheduler

Compatibility

Guest Operating System Compatibility for ESX

To determine which guest operating systems are compatible with ESX 9.1, see the Broadcom Compatibility Guide.

The following new major guest operating system releases are supported in this release:

- Ubuntu 26.04 LTS
- SUSE Linux Enterprise Server 16
- Debian 13.0
- FreeBSD 15.0
- Pardus 25.0
- CentOS Stream 10 (supported as Tech Preview)
- CentOS Stream 9 (supported as Tech Preview)

Support for the following guest operating system releases is deprecated or terminated in this release:

- RHEL 4.x: Terminated
- Oracle Linux 5.x: Terminated
- CentOS 4.x and 5.x: Terminated
- SUSE Linux Enterprise Server 10 SP4: Terminated
- SUSE Linux Enterprise Desktop 12: Terminated
- Debian 7.x: Terminated
- Flatcar Container Linux 3033 LTS: Terminated
- Asianux 3.x: Terminated
- Asianux 4.x: Deprecated

Windows Guest OS Pending Reboot Reporting with VMware Tools 13.1.0:

With VCF 9.1, VMware Tools 13.1.0 adds a vCenter UI and API restart status indicator that allows you to monitor and identify virtual machines with pending restarts after a VMware Tools upgrade. This status allows you to efficiently schedule the pending restarts. For more information, see Monitor the Guest Operating System Reboot Status.

ESX New Features

Installation

Zero Touch Provisioning (ZTP) for ESX installation:

VCF 9.1 introduces Zero Touch Provisioning (ZTP), using a secure UEFI and HTTPS-based network boot to provision ESX images on hosts at scale. ZTP simplifies and modernizes the way ESX hosts are installed and prepared for VCF consumption, avoiding the configuration of PXE infrastructure and the use of additional network services such as TFTP configurations. With VCF 9.1, you can boot multiple servers from a single HTTPS URL using a static network configuration on bare metal. ZTP serves as a forward-looking replacement for legacy Auto Deploy, which is deprecated in VCF 9.0. For more information, see Using Zero Touch Provisioning.

Storage

RDMA Observability Enhancement:

With VCF 9.1, you can use the `pktcap-uw --capture RDMASniffer` command for packet analysis and the `rdmaperf-uw` tool to validate network readiness for RDMA-based applications such as vSAN over RDMA or NVMe over RDMA. With the `RDMA Sniffer` capability for native packet capture and the built-in `rdmaperf` utility, you can troubleshoot RoCEv2 connections, verify end-to-end connectivity between nodes, and evaluate throughput and latency metrics directly within the ESX hypervisor.

API

Guest Customization APIs:

VCF 9.1 introduces updates to the Guest Customization APIs, focusing on network configuration flexibility and improved automation:

- For Powered-Off VMs:
  - IPv6-Only Support: You can explicitly deactivate IPv4 to configure IPv6-only networking in guest customization by both the UI and API. This capability avoids the need to maintain a parallel IPv4 configuration.
  - Partial Network Customization: You can customize network settings by providing only network-related fields to Guest Customization API. This capability streamlines operations by avoiding the need to supply the full customization profile when only network changes are required.
- Expanded Account Management:
  - Linux: Adds support for setting the root account password during customization.
  - Windows/Linux: Adds support for resetting root (Linux) and Administrator (Windows) passwords on existing VMs.
  - Script Execution: Enhanced support for executing customization scripts within Windows guest environments.
- For Powered-On VMs:
  - Live Network Customization: The Guest Customization API supports updating guest network settings for powered-on VMs. This capability facilitates real-time network changes without the need to power off the VM.

For more information, see Guest Operating System Customization.

ESX Host Client

Updated ESX Host Client:

VCF 9.1 provides improved experience in the ESX Host Client, similar to the vSphere Client, to manage compute, storage and networking at the single ESX host level. The updated ESX Host Client provides full feature parity with previous versions.

Snapshot Operations

Change Block Tracking (CBT) Enhancement:

VCF 9.1 adds an enhancement to CBT enablement that removes the unresponsiveness of VMs during snapshot operations. The overall operation for taking a snapshot is not reduced in time, but the VM unresponsiveness is resolved, as opposed to an undefined period of unresponsiveness for VMs with larger disks before the change.

Virtual Machine Management

Linked Clones of First Class Disk:

As of VCF 9.1, you can make linked clones of first class disk (FCD). You can use such clones for fast provisioning of container storage volumes in VMware Kubernetes Service (VKS). For more information, see Linked Clone First Class Disk.

I/O

Enhanced DirectPath for Operational Flexibility:

- **NVIDIA Mellanox ConnectX-7 and BlueField-3:** ESX 9.1 adds support for NVIDIA Mellanox ConnectX-7 and BlueField-3 with Enhanced DirectPath, delivering high performance for AI/HPC workloads in passthrough architectures. This enablement elevates raw performance but also operational flexibility for using vSphere vMotion, Storage vMotion, Live Patch, and Hot-Add/Remove virtual hardware.
- **AMD MI350:** ESX 9.1 adds support for the AMD MI350 GPU, with Enhanced DirectPath, advancing AI/HPC workloads in passthrough architectures to deliver high-performance speeds for faster training and inference. This enablement facilitates virtualization capabilities such as Live Patch, Storage vMotion, and Hot-Add/Remove virtual hardware, and enhances operational flexibility. Strategic partnerships with Hugging Face and participation in key open source consortiums (PyTorch, OPEA, UALink) ensures optimized performance and accelerate AI adoption.

Support for Intel NIC E825 for Xeon Gen 6 (Granite Rapids-D):

ESX 9.1 expands hardware compatibility by adding support for Intel NIC E825, which is integrated into the Intel Xeon Gen 6 (Granite Rapids-D) platform and functions as a LAN on Motherboard (LOM) NIC.

IOMMU Virtualization Support for AMD Hosts with DirectPath Devices:

ESX 9.1 introduces IOMMU virtualization support for AMD hosts with DirectPath devices to deliver significant performance gains and near-native hardware access for critical virtual machines while improving security and memory isolation.

Security

Quick Boot Support for ESX Hosts with Confidential VMs:

With ESX 9.1, Quick Boot supports ESX hosts running confidential VMs, bypassing the time-consuming full power cycle and firmware initialization required by a regular reboot. Quick Boot support speeds up maintenance operations and significantly reduces the upgrade time for the ESX server.

User-Level Monitor (ULM) for Enhanced Security:

VCF 9.1 introduces User-Level Monitor (ULM) as the default monitor for all virtual machines. ULM completely reimplements the virtual machine monitor (VMM) for ESX. The monitor is responsible for running your virtual machines and significantly reduces the amount of hypervisor code running in privileged mode in the ESX kernel, hence reducing the potential of guest escapes compromising the host.

General Availability for AMD Secure Encrypted Virtualization-Secure Nested Paging (SEV-SNP):

With ESX 9.1, AMD SEV-SNP for confidential VMs is general availability, after being introduced as a limited availability release with ESX 9.0. AMD SEV-SNP provides a hardware-based Trusted Execution Environment (TEE) for critical workloads, ensuring data integrity, confidentiality, and verifiable authenticity. The latest version of SEV-SNP adds memory integrity protections to prevent hypervisor-based attacks like data re-play and memory re-mapping. The latest SEV-SNP release also enables remote attestation to ensure the integrity of confidential VMs are not compromised. It is compatible with AMD EPYC Zen 3 (Milan) and later processors. For more information, see Securing Virtual Machines with AMD Secure Encrypted Virtualization-Secure Nested Paging.

General Availability for Intel Trusted Domain Extensions (TDX):

With ESX 9.1, Intel TDX for confidential VMs is general availability, after being introduced as a limited availability release with ESX 9.0. Intel TDX provides a hardware-based Trusted Execution Environment (TEE) for critical workloads, ensuring data integrity, confidentiality, and verifiable authenticity through attestation. It is compatible with Intel Xeon Gen 5 (Emerald Rapids) and later processors, see Securing Virtual Machines with Intel TDX. For more information, see Securing Virtual Machines with Intel TDX.

System Services

Improved Syslog Service Performance:

ESX 9.1 optimizes the syslog service, vmsyslogd, to handle a greater volume of logging messages for the TCP, SSL, and UDP protocols, ensuring more efficient and reliable logging in high-demand environments. This enhancement delivers improved performance and stability for system monitoring. For more information, see ESX Syslog Options.

Memory Tiering

Memory Tiering Configuration Enhancements:

- Simplified deployment: Memory Tiering configuration, including enablement and device selection, does not require a host reboot, reducing deployment time and the maintenance window, and resulting in cost savings.
- Support for all VM types: ESX 9.1 removes limitations for the types of VMs you can power on in memory tiered host, such as low-latency, security, and monster VMs.

Resiliency for Memory Tiering by Using Software RAID Mirroring:

ESX 9.1 improves resiliency for Memory Tiering by allowing for a mirrored device, without impacting performance. With the enablement, if a device fails, the secondary device performs memory tiering to ensure continued operations. With a second NVMe device using RAID1 mirroring, memory tiering cannot fail, regardless of NVMe device lifetime, reliability, and wear-out.

vCenter New Features

File integrity monitoring capability:

VCF 9.1 adds a File Integrity Monitoring (FIM) capability, aligned with NIST SP 800-115, which detects changes by malware or malicious actors to static files or binaries installed by vCenter. FIM is turned on by default and runs every four hours to detect malicious or unintentional changes or corruption of the installed files . You can get a FIM report by using API or stream FIM logs to VCF Operations by using the syslog service.

Pre-installed Logs Management Agent:

vCenter 9.1 comes with a pre-installed Logs management agent that pushes logs to VCF Operations and persists across upgrades. For more information, see Configure Log Insight Agent to Send Custom vCenter Logs to log management.

Upgrade of the vCenter Virtual Machine Hardware Version to vmx-17:

With VCF 9.1, vCenter VM hardware version is upgraded from vmx-10 to vmx-17. For more information, see Manually update the vCenter VM's hardware version in vCenter 9.1 and above if its updated from 9.0.

On-demand Pre-checks for RDU:

With vCenter 9.1, you can run on-demand pre-checks for RDU, similar to the regular vCenter patching pre-checks. For more information, see Perform Upgrade Prechecks.

Automating Download of Payloads for vCenter Reduced Downtime Upgrade (RDU):

With vCenter 9.1, you can download payloads automatically by using RDU as opposed to downloading an ISO image and mounting it for RDU workflow. For more information, see Download Updates from the Broadcom Online Repository.

vCenter Quick Patch:

With VCF 9.1, you can use the vCenter quick patches to upgrade vCenter with zero to 5 minutes of downtime. Quick patches carry security or critical bug fixes and cannot be used for major upgrades. Based on the services included in the patch payload, three groups of services are determined: zero, zero to 3 minutes, and 3 to 5 minutes of downtime. For more information, see the section vCenter Quick Patches.

vSphere Lifecycle Manager

Configure Global Remediation Settings for Clusters with vSphere Configuration Profiles Enabled:

With VCF 9.1, you can configure how ESX hosts and VMs behave before and during the remediation of a cluster that you manage with an image and has vSphere Configuration Profiles enabled. For more information, see Configure the Global Remediation Settings for Clusters That Have vSphere Configuration Profiles Enabled.

Integrity Verification of Customized and Exported ESX Images:

VCF 9.1 introduces validation of image integrity for customized ESX images. Large enterprises often customize ESX images that require a review and sign off by internal compliance teams before use. Such validation ensures that the image has not been modified and that administrators are consistently using the compliance-approved image. For more information, see Verifying Image Integrity with SHA-256.

Skip Reserved VIBs During Remediation:

Starting with VCF 9.1, vSphere Lifecycle Manager improves remediation efficiency by skipping the transfer of reserved VIBs that are not part of customized ESX images, saving bandwidth and reducing task duration.

vSphere Client

Memory Tiering Improvements:

With vCenter 9.1, the vSphere Client adds the following improvements for Memory Tiering:

- Memory pane:
  - Shows tier 1 stats at host and cluster level in a summary page with a memory card.
  - Streamlines the configuration at cluster level into a single flow that includes device selection.
  - Enhances monitoring by plotting graphs with tiering-specific metrics.
- Cluster workflows:
  - Memory Tiering cluster configuration allows for device selection and selection of Memory Tiering parameters.

Improved Interface for GPU Passthrough Devices:

With vCenter 9.1, the vSphere Client adds enumeration in human-readable form for GPU passthrough devices, simpler names in English, and filtering capabilities to enumerate the passthrough device list.

VPC Transit Gateway, Traceflow, and Live Traffic Analysis available from the vSphere Client:

With vCenter 9.1, you can configure an external connection for a Transit Gateway, use Traceflow to inspect the path of a packet, and get insight about tracing live traffic and bi-directional packet tracing by using Live Traffic Analysis (LTA) from the vSphere Client. To provide complete VPC configuration capabilities, vCenter 9.1 adds:

- integration with external connections, which can define VPC connectivity policy. The Transit Gateway can connect to a single centralized external connection or multiple distributed external connections.
- port mirroring (SPAN), which allows you to set up the range of inventory objects covered by the VPC network under the same Transit Gateway.
- Virtual Network Appliance Clusters (VNAC), which enable VPC connectivity services.
- IP management capabilities for IP allocation and DHCP setup.

For more information, see Managing Virtual Private Clouds in vCenter.

vSphere Client Usability Improvements:

- **VM tagging:** When you create, clone or deploy a VM from a template, you can assign tags to the VM as part of the workflow. Adding tags is a separate step in the **Create VM** wizard.
- **Virtual scrolling:** You can virtually scroll the grids of all managed objects, which prevents switching between pages to browse object lists with large number of entities.
- **Automatically adjustable columns in object lists**: The column width for long strings in object lists automatically adjusts to avoid text wrapping on multiple rows. You can switch to automatic adjustment and other options by using the settings menu at the top of the Inventory tree section.
- **CSV export of vCenter roles and permissions:** From the vSphere Client, you can export vCenter roles and permissions as a CSV file. The option is available for the global permission list and for the permission lists on inventory objects level such as vCenter instance, cluster, and ESX host.
- **Alphabetic order of all roles and permissions lists**, including configuration views.
- **Automatic propagation of user permissions:** User permissions set for a particular inventory object are automatically propagated to the object children by default.
- **Alphabetic order of object selection views:** In the OVF deployment wizard, objects are sorted alphabetically to simplify configuration.
- **900 rows limit per page:** In the consoles for tasks and events, you can increase the row limit to 900 from the default of 300.
- **Live refresh of the list of events.**

Event Tracking:

VCF 9.1 adds an **Event Tracking** page in the vSphere Client, which visualizes the full sequence of events when an ESX host fails and HA initiates recovery actions. The page provides a clear timeline that correlates ESX host failures, failover decisions, restarts, and recovery steps, all in one console. For more information, see Monitor and Analyze High Availability Events.

vCenter

Common objects identifiers between NSX and vCenter:

Starting with VCF 9.1, the maximum length of the `Folder` object name is increased from 80 to 255 chars for compatibility with NSX network management to enable common object identifiers between NSX and vCenter. In previous releases, NSX folder names could be too long for vCenter. For more information, see Folders in the Hierarchy.

Enhanced scalability in extra-large environments:

VCF 9.1 allows for up to 20% faster vCenter operations per minute. As a result, management tasks on virtual machines and ESX hosts, such as power on/off, run significantly faster.

Content Library

Convert Subscribed Content Library to Published Local Library:

With VCF 9.1, to avoid loss of content in case the original published local library is not available, you can convert a subscribed content library to a published local content library. For example, when you decommission a vCenter instance that hosts a published library serving subscribed libraries, the capability allows a subscribed library on another vCenter instance to convert to a published library, becoming the new content distributor and maintaining content availability.

Storage

VAAI-NAS support for Unmap with NFS v4.1:

VCF 9.1 supports space reclamation for VMs running on thin-provisioned NFS v4.1 datastores with VAAI-NAS Unmap. For more information, see vSphere Hardware Acceleration on NAS Devices.

Increased Host Scale for NFS Datastores:

VCF 9.1 supports up to 256 hosts per NFS v3 or NFS v4.1 datastore. This enhancement improves storage flexibility and allows for larger cluster configurations. For more information, see VMware Configuration Maximums.

Partner-supported NVMe stretch cluster solutions:

VCF 9.1 introduces NVMe dispersed namespaces which enable storage partners to validate and support NVMe-based stretch cluster solutions. For more information, see Requirements for VMware NVMe Storage.

iSCSI support for the iSNS service:

VCF 9.1 introduces automated discovery, configuration and management of iSCSI connections with the Internet Storage Name Service (iSNS) service. For more information, see Using iSNS with ESX iSCSI.

vSphere High Availability

Enhanced Failover Alarms:

VCF 9.1 introduces fully reworked logic for vSphere High Availability failover alarm that ensures accurate, stable, and reliable failover notifications. In previous releases, HA failover alarms might intermittently toggle on or off, leading to misleading signals about cluster health.

API

vCenter Support for OAuth 2.0 API Tokens:

With VCF 9.1, vCenter supports OAuth 2.0 API tokens, which help you manage API clients and emergency access clients to support secure automation. For more information, see Managing API Clients and Tokens.

Tech Preview of FIPS API:

VCF 9.1 launches a tech preview of an API that allows you to retrieve information about the FIPS cryptographic modules used by each VCF component, including version number, CMVP certificate, and CAVP certificate. For more information, see Using the FIPS API to Query FIPS Status of Components.

Query API for Efficient Data Access:

VCF 9.1 adds a new **Query API** as extension of the already existing **Search Index API** that delivers a fast, flexible, and scalable way to retrieve vSphere inventory data such as virtual machines and clusters.

The Query API enables:

- Server-side filtering based on user-defined criteria
- Efficient data access with pagination, property selection, and projections
- Lightweight, stateless queries without server-side state or client-side caching
- Entity counts and filtered results without retrieving full datasets

Designed for high-frequency automation use cases, the Query API simplifies data access.

Single, unified API endpoint for managing all vCenter instances in a vCenter group:

VCF 9.1 adds the vCenter group federated API (VGFA), a single, unified API endpoint for managing all vCenter instances in a vCenter group. VGFA allows you to view and manage inventory across multiple vCenter instances as if they were one, without changing any of the existing API integrations. VGFA becomes available with the configuration of VCF SSO in VCF Operations. After activation, you gain seamless access to a consolidated inventory and operations experience, consistent with the grouping capability under VCF Operations.

Utilization API:

VCF 9.1 adds Utilization API, which monitors vCenter capacity and usage metrics, including:

- The number of active connections compared to the maximum allowed connection limit.
- The endpoints through which these connections are established.
- The number of requests sent to vCenter services relative to the maximum request capacity supported by those services.

Building on this API, new alarms are available in the vSphere Client. These alarms are triggered when:

- Active connections exceed a configured threshold, and/or
- Service request volume surpasses the defined limit.

You can configure threshold values by using Advanced Settings.

Snapshots

Enhanced snapshot operational efficiency and reliability:

VCF 9.1 adds the following enhancements to snapshot operations:

- **Resumable Consolidation:** You can resume snapshot consolidation for powered-on VMs, eliminating the need to restart the process from scratch if canceled. For more information, see Consolidate Snapshots.
- **Disk Chain Integrity:** New safeguards detect disk chain mismatches. In the vSphere Client, you see respective alerts. The new safeguards block unsafe VM operations to prevent potential data corruption, while providing guided self-service steps to resolve the issue.
- **Capacity Planning Visibility:**
  With VCF 9.1, infrastructure admins can track the **Max Data to Consolidate** metric for better planning and resource estimation for snapshot consolidation tasks. The metric is available in the Snapshots tile under the VCF Operations diagnostics and in the VM `RuntimeInfo` file, under the parameter `consolidateWorkTotal`. For more information, see Virtual Machine Snapshots Health inVCF Operations Health and Diagnostics.

Metrics

vMotion Downtime Estimates with Enhanced DirectPath:

In vCenter 9.1, configuring a workload with an Enhanced DirectPath device provides you with increased visibility into the estimated downtime for a vSphere vMotion operation, enabling better workload planning and management.

GPU Power Metrics for Virtual Machines:

With vCenter 9.1, the **Advanced Performance** charts include **Power Capacity Usage - GPU** metrics for real-time insights into GPU power consumption at the workload level for virtual machines using NVIDIA GPUs.

Distributed Resource Scheduler

Intel QAT Offload for Encrypted vSphere vMotion Operations:

- CPU Efficiency: QAT offloads the majority of encryption cycles, reducing Source CPU utilization by nearly 67% and reducing Destination CPU utilization by nearly 22%.
- Predictability: With QAT, you see significantly lower variance in 'Total Migration Time' and 'Oracle Performance during vMotion' metrics as compared to the software-based encrypted vSphere vMotion that is sensitive to the microarchitectural interference, including cache pollution, memory bandwidth contention, and scheduler jitter.
- Workload Performance: The reduction in microarchitectural interference due to QAT offload correlates to an 14% increase in Oracle transaction throughput during the migration window.

vSphere Distributed Resource Scheduler (DRS) Enhancements:

- Optimized DRS VM selection logic to remediate CPU and memory contention faster, prioritizing the migration of high-impact VMs and bucketing VMs to ensure that migrations directly address the most constrained resources rather than defaulting to random, low-impact moves.
- Non-disruptive maintenance mode, which ensures that no workload disruptions occur during the host evacuation process. Instead, DRS notifies you why a VM cannot be evacuated when a forceful evacuation can result in performance degradation.
- Streaming vMotion Orchestrator:
  - Streaming vMotion Execution: Removes the requirement to wait for an entire batch of migrations to complete before starting the next to ensure that the migration pipeline remains at peak saturation, preventing a single slow migration from stalling the overall progress.
  - Adaptive Host-Pair Distribution (Progressive Pair-Sum): To prevent resource contention on key ESX hosts, a new adaptive algorithm prioritizes the selection of distinct source and destination host pairs. By intelligently spreading the migration load across all participating hosts in the cluster before loading any single host a second time, the scheduler ensures balanced network and CPU utilization, reducing the risk of delays and NIC saturation.
  - Dynamic Concurrency Control: You can move beyond the static cluster-wide limit of eight concurrent migrations. You can use new advanced configuration options to fine-tune vSphere vMotion concurrency based on specific hardware capabilities such as 25/100GbE networks and cluster size, enabling the system to scale throughput linearly with the number of available hosts.

vSAN

This document contains the following sections

- vSAN 9.1 New Features

vSAN 9.1 New Features

vSAN ESA Auto RAID 6:

In VCF 9.1, vSAN clusters use RAID-6 as the default RAID level. vSAN automatically configures RAID-6, removing the need for manual selection and ensuring superior data protection without impacting performance. For more information, see Selecting the Best RAID Configuration for a vSAN Storage Cluster.

Cyber Recovery vSAN Storage Clusters:

VCF 9.1 introduces a cyber recovery vSAN storage cluster that you can deploy through vCenter Quickstart. It optimizes recovery from a cyber event using VCF Protection and Recovery and provides alerts to ensure that the cyber recovery cluster is healthy and secure. For more information, see Deploy a vSAN ESA Storage Cluster for Cyber Recovery.

Seeding for vSAN Replication:

VCF 9.1 optimizes data transfer by using existing replicas to avoid full synchronization. When you create new replications, this seeding capability saves time and bandwidth by syncing only incremental changes. For more information, see Use vSAN Snapshots and Replication.

Tag Based VM Membership for vSAN Protection Groups:

VCF 9.1 simplifies administration by allowing you to define protection group membership using VM tags. This automation protects new workloads instantly based on their assigned metadata, without manual intervention. For more information, see Create a vSAN Protection Group.

Multiple Retention Schedules for vSAN Snapshots:

VCF 9.1 enhances retention management by allowing you to create daily, weekly, and monthly snapshot schedules. This flexibility supports long-term cyber recovery strategies and day-to-day operational recovery needs. For more information, see Create a vSAN Protection Group.

Cyber Recovery Using On-premises Clean Room:

VCF 9.1 introduces integrated cyber recovery workflows that use vSAN snapshots to recover from events. Baked-in recovery processes, combined with integrated Endpoint Detection and Response (EDR) and vDefend push-button network isolation, significantly reduce downtime during a security breach. For more information, see Using Cyber Recovery.

vSAN Replication from Any Source Site:

VCF 9.1 extends vSAN replication to support workloads running on any storage by using vSAN ESA as the target. You can now take advantage of vSAN replication capabilities such as dynamic protection groups, immutable snapshots, and an integrated vCenter User Interface across a broader set of workloads.

vSAN ESA Compression Enhancements:

VCF 9.1 improves vSAN ESA compression to deliver better storage efficiency. You can expect increased space savings compared to previous releases, helping reduce storage consumption without impacting performance. For more information, see Using Global Deduplication and Compression in a vSAN ESA Cluster.

vSAN ESA Global Deduplication:

VCF 9.1 introduces vSAN ESA Global Deduplication, a cluster-wide and post-processing setting with encryption support. Deduplication increases storage efficiency while providing data-at-rest security without reducing deduplication effectiveness. For more information, see Using Global Deduplication and Compression in a vSAN ESA Cluster.

RWX File Volume Support:

VCF 9.1 extends RWX file volume support to VM Service VMs and adds support for multiple clusters within a single vSphere Zone.

Fast Clone Volume Support:

VCF 9.1 introduces Fast Clone Volume support, adds snapshot and shared-disk capabilities for VM Service VMs, enables non-disruptive VM migration to Supervisor Clusters, and allows storage policy updates by reprovisioning volumes from snapshots.

CNS/CSI Scalability:

VCF 9.1 increases CNS/CSI scalability to 50,000 volumes per vCenter, supports shared-disk clustered workloads on Supervisor Clusters, and adds unified monitoring of Persistent Volume Claims through VCF Operations.

Improved vSAN File Services Performance for SMB Workloads:

VCF 9.1 improves vSAN File Services performance, delivering up to 2 times faster metadata operations optimized for SMB workloads. For more information, see vSAN File Service.

Clustered Applications Support on vSAN:

VCF 9.1 extends vSAN support for clustered applications and provides the capability to expand VMs with clustered disks without shutting down the clustered application, such as WSFC or Oracle RAC. This capability supports both Oracle RAC multi-writer and shared VMDK in Windows Server Failover Clusters. For more information, see Clustering Applications on vSAN.

vSAN Stretched Storage Across vCenter Instances:

VCF 9.1 adds flexibility by allowing vSAN stretched storage clusters to provide storage across vCenter boundaries. This includes sharing storage across workload domains within a VCF install or across multiple VCF deployments. For more information, see Mount Remote vSAN Datastores.

Shared vSAN Storage Cluster Support:

VCF 9.1 allows vSAN storage clusters to mount and use both vSAN OSA and vSAN ESA clusters. vSAN compute-only clusters can also mount vSAN OSA and vSAN storage clusters at the same time. For more information, see Sharing Remote vSAN Datastores.

End-to-End Encryption for Disaggregated vSAN:

VCF 9.1 enables end-to-end encryption support for vSAN by providing data-in transit encryption between client clusters and vSAN storage clusters. Combined with local data-in-transit and data-at-rest encryption, this capability fully protects disaggregated vSAN deployments.

Site Maintenance in a vSAN Stretched Cluster:

VCF 9.1 introduces support for placing a site in maintenance mode in a vSAN stretched cluster. vSAN automates promotion of the surviving data site and the witness sites during a site failure, enabling seamless data recovery. For more information, see Manage the Site Maintenance for a vSAN Stretched Cluster.

NSX

This document contains the following sections:

- Virtual Private Cloud (VPC) Networking
- Edge Platform
- Enhanced Data Path and Performance
- Platform Security
- VCF Integration
- Network Visibility
- Network Observability
- IP Address Management
- Load Balancer
- Operations
- VKS Multi-Interface Networking
- VCF Brownfield/Import
- Installation and Upgrade - LCM
- Routing

Virtual Private Cloud (VPC) Networking

AVI Integration: VPC and Distributed Transit Gateway (DTGW) with Distributed VLAN Connections

This release introduces support for AVI load balancers with VPCs and and Transit Gateways with distributed VLAN connection. For more information, see the Avi Load Balancer documentation.

Distributed VLAN connection support for Supervisor and VCF Automation

By integrating the Virtual Network Appliance (VNA), we've added the essential services needed to enable Distributed Transit Gateway for the Supervisor. This capability allows VCF Automation environments to connect to the data center using only a simple VLAN removing the need for more complex networking prerequisites.

Enhanced NSX UI experience around VPC and IPAM

Due to importance of VPC for VCF networking, the following enhancements have been made for improved NSX user experience:

- Extended VPC section with views per features (such as subnet and NAT) in addition to the view per VPC
- Full IP allocation and management workflow to ease IP management with IP allocation to services shortcuts (such as NAT and External IP). For more information, see Assign External IPs to a VPC.
- Re-organization of the Networking tabs to clearly delineate objects leveraged by VPC Networking (like Transit Gateway) versus objects that are part of Segment Networking (such as Tier-1s and segments)

Extend VPC and Transit Gateway consumption from vCenter

- Transit Gateway visible and fully configurable from vCenter
- Ability to extend Subnets to a VLAN in vCenter
- Full IPAM visibility and IP allocation mechanisms
- Extended Topology views and Traceflow available directly in vCenter for VPC VM
- DHCP server and DHCP relay options fully configurable from vCenter

Terraform extended coverage for Transit Gateway and VPCs

The Terraform Provider evolves in line with the new features added to VCF Networking by exposing new capabilities available on Transit Gateway (multiple TGW, advanced connectivity options., and so on) and VPC (improved IPAM, VLAN Extension, and so on). More details on NSX Terraform Page.

VPC Services: Load Balancer on Virtual Network Appliance

VPCs now support Load Balancer (LB) functionality through a solution deployed on top of a Virtual Networking Appliance (VNA). Layer 4 (L4) load balancing service is fully supported and runs within this dedicated VNA ensuring scalability, flexibility, and enhanced service isolation within your virtual network infrastructure.

VPC Services VPN support on Centralized Transit Gateway

IPSec VPN services support for VPC using centralized external connectivity - With VCF 9.1, IPSec VPN service is now supported for VPC using centralized external connectivity enabling secure and encrypted communication across diverse network environments. The release includes support for both Policy-Based and Route-Based (static route only) VPNs offering flexibility to meet various connectivity and security requirements.

For more information, see Enabling an IPSec VPN Service on a Centralized Transit Gateway.

1:N SNAT service support for VPC with external distributed connectivity

VCF 9.1 added support for 1:N SNAT when using the distributed Transit Gateway. This feature enables multiple internal VMs to share a single external IP address through Port Address Translation (PAT), optimizing public IP usage and simplifying outbound connectivity for workloads. For more information, see Register Add a NAT Rule for a VPC.

Introduction of Virtual Network Appliance in VCF 9.1

VCF 9.1 introduces the Virtual Network Appliance (VNA) which is designed to run and support network services within distributed VPC environments. This new appliance provides a flexible and scalable foundation for deploying advanced networking services. For more information, see Create a Virtual Network Appliance Cluster.

VLAN extension for VPC subnets

VPC VLAN extension provides capability to extend VPC subnets to an existing VLAN in the fabric. It enables on-boarding of VMs connected to DVPG to VPC subnets with a distributed VLAN extension. For more information, see Extending VPC Subnet to VLAN and Onboarding DVPG VMs to VPC Subnets.

Centralized Transit Gateway Advanced Connectivity Types

This feature delivers the following advanced connectivity options for Transit Gateways with a centralized external connectivity:

- Provision of multiple gateway external connections per Transit Gateway
- Deployment of multiple Transit Gateways within a single Project
- Configuration of independent choice high-availability modes and flexible edge node placements for a centralized Transit Gateway.
- Enablement of Proxy-ARP in Tier-0 for Transit Gateways and VPC subnets.

For more information, see Transit Gateways.

Multiple distributed Transit Gateways per Project

This release introduces support for multiple Transit Gateways with a Distributed VLAN Connection within the same project. For more information, see Transit Gateways.

Distributed Transit Gateway with EVPN VXLAN connectivity

This release introduces Distributed EVPN-VXLAN that enables direct workload integration with EVPN-VXLAN fabrics using BGP EVPN and VXLAN without centralized gateway appliances in the traffic path.

Forwarding is distributed closer to workloads and the BGP EVPN control-plane connectivity is provided by the VCF Route Controller peering with the fabric EVPN Border Gateways (BGWs)—delivering improved scale, performance, and simpler operational alignment across virtual and physical networks.

For more information, see External Connections.

Tenant networking support for services and multiple Transit Gateways

VCF Automation networking 9.1 allows a tenant to have:

- Distributed Connection to VLAN for both TGW and direct VLAN extension
- Multiple Transit Gateways with multiple connections
- Self Service NAT, VPN, Grouping, Firewalling (Stateful GFW and DFW requires vDefend Firewall License)
- Create subnets shared across Namespaces.

Support of native Infoblox integration with VPC

VCF networking IPAM can now optionally integrate with Infoblox to:

- Discover Infoblox Network Views, DNS Views, and Network Containers
- Use Infoblox Network Containers to create subnets and update VM IP/FQDN information

You can configure the feature in NSX: pairing with Infoblox, External IP Block to Infoblox Network Container mapping that can be discovered and used as VCF Automation External IP Block. For more information, see Register Infoblox NIOS DDI with NSX.

Ability to define Span for Transit Gateway and VPC

The span of VPCs can now be defined directly from vCenter or from NSX letting VPCs be restricted to specific clusters or have them span across all vCenter instances of the networking domain. For more information, see Add a Network Span.

New VPC Connectivity Policy

VPC communication can now be easily defined with a new feature, Connectivity Policy, that can group VPCs under the same Transit Gateway which are meant to communicate with each other. Different grouping options are available, such as communities of VPCs (for instance mapped to connected applications), isolated VPCs (for more restricted cases like DMZ and the like), and promiscuous VPCs that host services and are connected to all other VPCs. For more information, see Configure Connectivity Policies.

Edge Platform

New UI for Edge Node creation in NSX

VCF 9.1 is introducing a new, user-friendly, and simplified UI workflow for defining Edge Node and Edge Cluster configurations through NSX Manager. This enhancement streamlines setup and management that makes deployment

of edge infrastructure faster and more intuitive. For more information, see Create an NSX Edge Cluster and Add Edge Nodes.

Broadcom 574X/575X and Mellanox CX6 LX support for BM Edge datapath NIC

VCF 9.1 supports Broadcom 574X and 575X and Mellanox CX6 LX NICs for Datapath of BM Edge. For more information, see NSX Edge Bare Metal Requirements.

Edge Control Plane Prioritization

VCF 9.1 is introducing Control Plane Prioritization (CPP) on Edge Uplinks to ensure that all control plane packets are prioritized. This enhancement applies to both RX (receive) and TX (transmit) packets, providing greater reliability and stability for control plane operations. CPP is implemented for both the Bare Metal Edge (BME) and Edge VM deployments.

Edge VM VLAN and MTU health check

As part of the new UI for Edge node creation and new UI for edge cluster creation workflow, VLAN and MTU pre-check for the Edge node have been added. It validates that the VLAN and MTU configurations on the physical TOR switches have been properly configured to ensure successful deployment of VCF Networking Edges. For more information, see Create an NSX Edge Cluster and Add Edge Nodes.

Enhanced Data Path and Performance

FPO Hardware Steering for NVIDIA Accelerated NICs

This release introduces an asynchronous queue-based hardware steering engine to increase flow programming rates and scalability for UPTv2 and Enhanced DirectPath I/O. This capability is available on NVIDIA Accelerated NICs (ConnectX-6 DX, ConnectX-7, BlueField-2, BlueField-3).

Uniform Passthrough (UPT) for Accelerated NICs

Uniform Passthrough (UPT) enables near line-rate networking performance through the standard **VMXNET3** interface by offloading the data path to **NVIDIA ConnectX-7** or **BlueField-2, BlueField-3** (NIC mode) hardware. This technology removes the requirement for proprietary guest drivers and supports core features like **vMotion** making it ideal for high-performance general workloads that require operational flexibility and simplified image management.

- **Best Use Case:** High-performance general enterprise workloads that require a balance of speed and operational flexibility.
- **Key Benefit:** High-speed throughput without sacrificing vMotion or guest OS portability.

For more information, see Enhanced Network Offloads and Advanced NIC Passthrough.

Enhanced Direct Path I/O for Accelerated NICs

Enhanced direct path I/O (EDPIO) delivers the highest possible throughput and lowest latency by providing virtual machines with direct hardware access to NVIDIA ConnectX-6 DX, ConnectX-7, or BlueField-3 (NIC mode) adapters. This mode is specifically optimized for AI, machine learning, and distributed computing that offers support for **GPUDirect RDMA** to facilitate high-speed direct communication between GPUs across the network.

- **Best Use Case:** AI/ML training, large-scale distributed computing, and high-frequency trading environments.
- **Key Benefit:** Maximum hardware-level performance and advanced RDMA capabilities for compute-intensive applications.

Enhanced Data Path (EDP) Optimizations

EDP Standard features several deployment and performance enhancements:

- **Improved Deployment:** Utilizes an updated sequence to maintain data path up-time in multi-uplink environments during orchestrated maintenance.
- **Latency & Throughput:** Adds posted interrupt support for lower VMXNET3 latency, enhanced multicast Fast Path performance, and VMKAPI checksum offloading.
- **Expanded Feature Support:** Introduces SR-IOV for EDP Standard, RDMA parity with pkthandle, and LRO for Antrea-based deployments.
- **Platform Optimization:** Optimized for vSAN performance via multi-world VMKnics and AMD architectures through TLB optimizations.

GRE traffic scale for Cloud Service Providers (physical NIC and vNIC RSS Hashing)

GRE vNIC RSS hashing enhancements for Edge Node VM appliance improves the traffic scale. Inspection of the inner packet will distribute the traffic among multiple CPUs that increases the traffic performance.

Platform Security

Non-Disruptive Certificate renewal for VCF components that consume NSX services

With VCF 9.1, VCF components that use NSX services have adopted the standardized Non-Disruptive Certificate architecture that will allow them to maintain trust with NSX even when the NSX server certificates change.

RSA & SSH-ED algorithms support for NSX Backup and Restore

Experience better security and consistency as NSX Backup and Restore now support RSA and SSH-ED hostkey algorithms. For more information, see Configure Backups.

> **Note:**
>
> If you wish to use ssh-ed25519 hostkey algorithm, configure NSX Backups from the NSX Manager UI/API only.

New password to be different from the old password in case of the Reset Password operation in NSX

Starting with VCF 9.1, a user cannot provide the old password during the Reset Password operation of a local account. For information about resetting password, see Resetting User Passwords.

Make regular user accounts created by NSX internal accounts on ESXi

Starting with VCF 9.1, NSX no longer creates and uses the following regular users on ESX hosts for its own operations: mux_user, da-user, nsx-user, and lldpVim-user. Instead, it uses special accounts not visible to users.

NSX Transition to Ubuntu 24.04 and Chiseled Containers

All NSX appliances have been upgraded to Ubuntu 24.04 that leverages chiseled containers to minimize the attack surface, optimizes deployment efficiency, and simplifies patch management through a unified and enterprise-supported stack.

VCF Integration

Workflow to make domains VPC-ready

In VCF 9.1, you can configure vNetworking service (Tunnel EndPoint - TEP) even if it was not configured initially during creating or importing your VCF domain. You can also configure the default Transit Gateway as part of the default project.

Overlay service configuration in vCenter

In VCF 9.1, overlay Tunnel EndPoint (TEP) can now be configured directly from vCenter like other vmkernel NICs. This provides a central place to configure all the services running on ESX hosts.

UI support for Link Aggregation Control Protocol (LACP) on VCF workflows

VCF installer and VCF Operations offer the option to configure Link Aggregation Groups (LAG) with Link Aggregation Control Protocol (LACP) directly in the UI.

Sharing NSX Managers between Management and Workload Domains

VCF Management Domain can now share NSX Managers with other VCF workload domains. This reduces the resources to run NSX and the overhead for the NSX lifecycle.

Network Visibility

VDS IPFIX adopt ConnTrack module

Update IPFIX module (Netflow) in VDS to the ConnectionTrack-enabled module to improve performance and standardize on a single module for all IPFIX implementations (DFW IPFIX, Switch IPFIX, & VDS IPFIX). As a result, IPFIX for uplink port groups will not be supported. For more information, see Add a Switch IPFIX Profile.

Network Observability

Port mirroring policy API support

This feature enhances Policy API and UI to support Local SPAN as well RSPAN. Policy API only supported ERSPAN and Logical SPAN in prior releases. As a result, all SPAN types are configured centrally in one location. For more information, see Add a Port Mirroring Session.

IP Address Management

IP Address Management (IPAM) for Cloud Consumption

- **IPAM for Cloud Consumption**: The IPAM becomes more flexible and powerful by extending the IP Block. It now allows one IP Block to support up to 10 CIDRs, 10 IP ranges (from one previously), and to exclude specific IPs. This allows to populate CIDRs and IPs without disrupting VPC consumers. If an IP Block to go to the Internet is full, some new IPs can be added and consumers have nothing to change as it is the same IP block and same quota.
- **IP Address Management (IPAM) improved Provider Control:** It is now possible to share the IP Blocks to the tenant while limiting the visibility on the content of the IP Block. For instance, it allows the Provider to share an IP Block internet "Internet" to the Organization in VCF Automation with a quota of two IPs without exposing the Internet IPs generally owned by the Provider.
- **IPAM Allocation, Usage, and Visibility:** The IPAM offers enhanced IP allocation and IPAM management capabilities across the UIs consuming VPCs (VCF Automation, vCenter, and NSX)

For more information, see Add an NSX IP Address Block.

VPC Distributed DHCP Server enhancements

VCF 9.1 introduces automatic detection of static IP addresses that are now automatically excluded from the DHCP pool. This enhancement ensures seamless IP address management by preventing conflicts between statically assigned and dynamically allocated IPs, thus improving network stability and reducing manual configuration errors.

Load Balancer

Distributed Load Balancer decoupling from Distributed Firewall

The Distributed Load Balancer is now independently managed and decoupled from the Distributed Firewall (DFW). This separation provides greater flexibility allowing users to configure and operate load balancing services without dependency on DFW configurations. For more information, see Distributed Load Balancer.

Operations

SSH Login Banner Customization for NSX Appliances

An SSH Banner can now be configured on the NSX Manager and Edge appliances. Users will now see a configurable message from their administrator before logging into either of these appliances.

VKS Multi-Interface Networking

Provide Istio Service Mesh for VKS workloads

Istio Service Mesh is now available at a per-VKS cluster level for Supervisor based workloads. Key functionalities include:

- mTLS between container workloads within a single VKS cluster
- Both Sidecar and Istio Ambient (Sidecar-less) modes are available
- All Istio Security and Traffic Management APIs are available
- Both L4 and L7 routing are enabled (Waypoint Proxy included)

Dual-Network support for VKS cluster

This enables any VKS cluster to be deployed with a secondary network interface (vNIC) as well as Pods within the cluster to be deployed with secondary network interfaces when running Antrea CNI. Both VKS cluster nodes and secondary NICs of Pods are mapped to VLAN or overlay backed subnets in NSX VPC. This addresses a number of customer use cases such as traffic isolation from primary networks, multicast traffic to and from container workloads, direct access to physical systems such as NFS storage.

VCF Brownfield/Import

Out-of-band networking changes to not impact SDDC Manager

SDDC Manager now supports network configuration changes done directly in vCenter or NSX Manager to be synchronized in its database.

Bare Metal Edge support in VCF import

In VCF 9.1, existing non-VCF deployment with NSX Bare Metal edge nodes can now be imported in VCF.

Installation and Upgrade - LCM

VDS support for VCP Autobootstrap

VDS capabilities and enhancements to support the NSX - vSphere Config Profiles integration.

Move NSX Edge/SVM Upgrades to the End of Upgrade Sequence to Complete Aligning NSX Upgrade Process with vSphere

- Easier and faster upgrades - Consolidated maintenance windows for NSX and vSphere management plane and data plane.
- Latest VMX version on your NSX Edges as part of the upgrade process. No post upgrade manual intervention or extra reboot needed.

DPDK Upgrade to 24.11

Upgraded Data Plane Development Kit (DPDK) to version 24.11, bringing performance improvements, enhanced stability, and support for the latest hardware and features. This ensures better efficiency and future compatibility for high-performance networking workloads. For more information, see NSX Bare Metal Requirements.

Routing

Dynamic BGP Peering for Auto-Scaling applications

This feature provides dynamic BGP peering support on Tier-0 gateways and Tier-0 VRFs. With this feature, users can define a range of IP addresses that will be used to determine when a Tier-0 gateway should establish BGP peering with external routers. For more information, see Configure BGP.

Increased L3 Networking Scale

In this release, the configuration maximums for a number of aspects of VCF Networking (including L3 Networking scale) has been increased. For more information about limit increases, see the VMware Configuration Maximums tool.

VCF Installer

This document contains the following sections

- What's New in VCF Installer
- What's New in SDDC Manager

What's New in VCF Installer

Starting with VCF 9.1, the following configurations are supported for convergence and import operations:

- Existing VMware vCenter 8.0 Update 3a or later environment with NSX Manager 4.2 or later, without manual component upgrades.
- Existing VMware vCenter 8.0 Update 3a or later environment without NSX Manager, only by manually upgrading your vCenter instance to version 9.1.
- vCenter instances without ELM and with existing NSX Local Managers that are part of an NSX Federation configuration.
- If an existing VCF instance is configured to use dual-stack (IPv4 and IPv6) networking, existing vCenter environments that use dual-stack networking.

Default Component Deployment

Starting with VCF 9.1, VCF Installer deploys a default set of VCF management services components during new deployment. The components included are VCF services runtime, fleet lifecycle, identity broker, software depot, Salt RaaS, telemetry, and license server. This standardized deployment ensures that critical services are available from Day

0 without requiring additional configuration. For more information, see Deploy VCF Management Services and License Server as Part of Upgrade to 9.1.

UI Support for LACP Configuration

VCF 9.1 introduces native UI controls for configuring Link Aggregation Control Protocol (LACP) on vSphere Distributed Switches. You can now configure LACP directly during the deployment of management domains in VCF Installer. Previously an API-only capability, this feature also includes validation prechecks to ensure the physical network fabric is correctly configured for LAG prior to deployment.

Auto-Generated Passwords During Deployment

To improve security during deployment, VCF Installer now supports auto-generation of complex passwords for system-managed and break-glass accounts. These credentials can be retrieved post-deployment, reducing the risk associated with static or shared passwords during the initial configuration phase.

UI Support for Flexible Network Configuration for deployment of VCF Operations and VCF Automation

VCF Installer UI now supports the deployment of VCF Operations and VCF Automation on custom network configurations, including separate vSphere Distributed Switches (VDS), Distributed Virtual Port Groups (DVPGs), virtual private clouds, and NSX Segments. For more information, see Deploying VCF Operations and VCF Automation on Custom Networking.

Integrated Planning Workflow

VCF Installer now features an integrated planning workflow that allows you to define your deployment topology and component selection directly in the UI. Based on these inputs, VCF Installer generates a list of CPU, Memory, Storage, VLAN, and FQDN requirements which are then validated against the target infrastructure to ensure resource sufficiency prior to deployment. For more information, see Start a New VCF Fleet or a New VCF Instance Deployment by Using the VCF Installer Deployment Wizard.

What's New in SDDC Manager

Out of Band Operations

You can now perform the following tasks in vCenter without impacting SDDC Manager:

- Changes to vSphere Distributed Switch (add, remove, teaming policy, MTU, PNICs)
- Change primary datastore
- Changes to datastore
- Manual upgrade in vCenter

The following objects can be modified in NSX:

- Transport Zones
- Transport Node Profiles
- Uplink Profiles

Support for Dual Stack (IPv4 and IPv6) Networking

VCF 9.1 introduces native support for Dual Stack (IPv4/IPv6) networking for management and workload domains. For new deployments, you can configure management or workload domains with either IPv4 or Dual Stack networking. For existing environments, after you upgrade to VCF 9.1, you can configure SDDC Manager for Dual Stack networking, facilitating the deployment of new workload domains in Dual Stack mode. For more information, see Configure Dual-Stack Networking for SDDC Manager.

VCF Operations

This document contains the following sections

- VCF Operations UI Experience
- Build
  - Fleet lifecycle
  - Domain lifecycle management
  - Developer center

  - VCF Operations HCX
  - SDDC Manager Scale
- Manage
  - License management
  - Fleet management
  - Cost and capacity management
  - VCF Operations orchestrator
  - Workload Mobility
- Operate
  - Real-time metrics
  - Findings
  - Organizations
  - VCF health
  - Log management
  - VCF Operations for networks
  - Storage operations
  - Workload monitoring and observability
  - Notifications
- Protect
  - Security and compliance

VCF Operations UI Experience

VCF Operations now features an enhanced, intuitive experience structured around the functional pillars of VCF: Build, Manage, Operate, and Protect the private cloud. All capabilities are aligned with these operational pillars.

UI Support for LACP Configuration

VCF 9.1 introduces native UI controls for configuring Link Aggregation Control Protocol (LACP) on vSphere Distributed Switches. You can now configure LACP directly during the deployment of workload domains in VCF Operations. Previously an API-only capability, this feature also includes validation prechecks to ensure the physical network fabric is correctly configured for LAG prior to deployment.

Workload Domain without a vSphere Cluster

VCF 9.1 introduces a new workflow for creating a workload domain without a vSphere cluster. The workflow deploys and configures a vCenter instance and deploys and configures a new or joins an existing NSX Manager instance. You cannot patch or upgrade the components in the workload domain before adding a vSphere cluster. All workload domains that share an NSX Manager with a workload domain without a vSphere cluster cannot be patched or upgraded unless you add a vSphere cluster to the domain without a cluster. For more information, see Create a New Workload Domain without a vSphere Cluster Using VCF Operations.

Logging in to VCF Operations

While logging in to VCF Operations, use `https://<IP>` or FQDN.

Build

The **Build** capability provides the ability to deploy and manage the lifecycle of your private cloud. It orchestrates the complete platform lifecycle from the initial deployment, converging your existing infrastructure into the VCF private cloud, to the ongoing lifecycle management of your private cloud by providing the ability to patch and upgrade your infrastructure. Beyond deployment and lifecycle capabilities, this workspace acts as the central hub for managing software binaries using the software depot and running lifecycle updates to keep the platform current. It also enables extensibility by providing developers with access to APIs and SDKs through the developer center.

Fleet lifecycle

In VCF 9.1, the standalone VCF Operations Fleet Management Appliance no longer exists and is replaced by fleet lifecycle, a management component to streamline the lifecycle management of the VCF management components. The

inventory of the Fleet management appliance is fetched and leveraged by fleet lifecycle when the component is deployed. The remaining functionalities, such as service registry, user imported certificates, certificate signing requests, and so on are converged into VCF Operations 9.1.

The fleet lifecycle component provides a unified framework to install, upgrade, patch, backup, restore, and maintain the various management components that constitute the VCF environment:

- Identity broker
- VCF Operations
- VCF Operations for networks
- Real-time metrics
- Real-time metrics store
- Salt master
- Salt RaaS
- VCF Automation
- Telemetry
- SDDC lifecycle
- Software depot
- Log management
- Migration service engine
- VCF services runtime

For more information, see Deploy Log Management, Deploy VCF Operations for networks, Deploy Real-time metrics, Configure Backup Schedules for VCF Automation and VCF Management Services, In Place Restore of VCF Management Services Components, Performing Post Deployment Actions on Components, Scale up VCF Management Components.

Domain lifecycle management

Optimized NSX Manager and vCenter Maintenance Window

You can schedule an update scenario that reduces the required maintenance window downtime. The vCenter reduced downtime update (RDU) preparation stage is performed first and does not require downtime. Then, in the maintenance window, the NSX Manager nodes are updated followed by the vCenter instance switchover stage. For more information, see Perform an Optimized Upgrade of vCenter and NSX Manager.

NSX Edge Upgrades at the end of Domain Upgrade Sequence

NSX Edge clusters are now upgraded at the end of the domain upgrade process, following the upgrade of the management domain components and ESX clusters. This reordering aligns the NSX upgrade process with vSphere best practices, ensuring NSX Edges are upgraded on the hosts with the expected version. The NSX finalize process starts after the NSX Edge clusters are upgraded, streamlining the maintenance window and reducing manual intervention. For more information, see Upgrade the NSX Edge Cluster and Finalize NSX Upgrade.

Support for Imported Standalone Hosts and Single Host Clusters

Added support for the lifecycle management of standalone hosts and single host clusters.

Select Hosts during Cluster Upgrades

During a cluster upgrade, you can now select specific hosts rather than the entire cluster. If there are issues or errors with certain hosts, these hosts can be removed from the selection and skipped during the cluster upgrade. For more information, see Upgrade ESX to 9.1.

Improved Various Prechecks

Prechecks are now conducted using native VCF component capabilities rather than relying solely on SDDC Manager. This enhancement includes support for vCenter Reduced Downtime Upgrade (RDU) prechecks following upgrade configuration. Additionally, error and remediation messages have been updated, invalid or redundant prechecks have been removed, and precheck results can be exported to a CSV file for analysis. For more information, see Perform Upgrade Checks.

Component Versions

VCF centralizes version information and displays current and target versions for all supported components that are managed by VCF Operations on the Component Versions tab. For more information, see Lifecycle Management in VCF.

Developer center

Prometheus Support for Management Pack Builder

Prometheus support is now added to the Management Pack Builder in VCF Operations. You can create your own Management Pack using metrics from Prometheus Servers. This enables you to reuse your existing metrics and bring them into VCF Operations without writing new integrations using the SDK. For more information, see Designing a Management Pack Using Prometheus.

VCF Operations HCX

Support for VCF Operations HCX

Added support for the lifecycle management of VCF Operations HCX. For more information, see Deploy VCF Operations HCX and Import Existing VCF Operations HCX to a VCF Domain.

SDDC Manager Scale

Manage a maximum of 5000 hosts per VCF Instance

- Per Instance level number of hosts scale support has been increased by 2x from VCF 9.0.
- You can now perform streamlined management of DNS, NTP at scale.
- Parallelization of operations has been enhanced, allowing for 256 simultaneous cluster upgrades and concurrent workflows for domain creation and host commissioning.
- Revamped UI and API for brownfield imports and pre-checks to perform these operations in a scaled environment.

Manage

The **Manage** capability acts as the administrative control plane dedicated to maintaining fleet hygiene, governance, and resource efficiency. It streamlines complex operational tasks by unifying certificate lifecycle management, identity and access controls, and license entitlement into a centralized workflow. Along with fleet governance, it also provides financial and operational insights through capacity planning and cost metering tools, ensuring the environment is both efficient and cost-effective.

License management

Automatic License File Download in Connected Mode

If your VCF Operations is in connected mode, a new license file is now automatically downloaded to VCF Operations every 24 hours. This keeps your licenses updated and you do not need to manually request license updates. If you want to manually update licenses in connected mode, you can turn off this feature. For more information, see Change License Updates Mode.

Override License Support

You can now assign licenses directly to individual assets that consume license capacity, such as ESX hosts and vSAN clusters, if they are connected to a licensed vCenter instance. The licenses you assign directly to assets are called override licenses. To assign an override license to an asset, the override license must have enough available capacity and must be compatible with the license assigned to the vCenter instance. For example, you can assign a VCF license to a vCenter instance, and VCF Edge licenses to some of the ESX hosts in that vCenter instance. For more information about override licenses, see What is an Override License.

Aggregated License Usage for Hosts of Version 8.x and 9.x

License usage reporting is now unified for ESX hosts of versions 8.x and 9.x. The number of cores of ESX hosts of version 8.x is included in the version 9+ license usage. With the combined view in VCF Operations and the Business Services console, you can track your total license consumption. For more information, see License Usage Analytics.

VCF Operations License Server

Your licenses are now stored in a license server, instead of in VCF Operations. A license server is automatically installed during the installation of VCF Operations 9.1. For more information, see Registering VCF Operations with VCF Business Services Console.

Fleet management

Identity and Access Management

VCF introduces streamlined Identity and Access Management capabilities, enabling generic OIDC identity provider support, centralized VCF level role assignments, and OAuth 2.0 API tokens.

- **VCF Roles:** Create custom VCF roles by mapping to specific component permissions. VCF roles can be assigned to users and groups when you configure VCF SSO. For more information, see Managing VCF Roles.
- **SSO-Centric Management:** Manage the VCF SSO lifecycle at the identity broker level rather than from a VCF Instance for better operational granularity.
- **vCenter Role Sync and Remediation:** Provision vCenter custom roles across multiple vCenter instances and VCF Instances. VCF Operations automatically detects and remediates configuration drift. For more information, see Provisioning vCenter Custom Roles.
- **OAuth 2.0 API Tokens:** Help users with appropriate permissions to generate standard OAuth 2.0 tokens for VCF components. As an admin, you can also manage API clients and emergency access clients to support secure automation. For more information, see Managing API Clients and Tokens.
- **Migration from embedded to instance deployment of the identity broker:** Support for the migration of the identity broker from embedded mode to instance mode in VCF Operations. For more information, see Migration of Identity Broker (Embedded) to Identity Broker (Instance).
- **Migration from VMware Identity Manager to Identity Broker**: Support for script-based migration of data from VMware Identity Manager to identity broker. For more information, see Migrating VMware Identity Manager to Identity Broker.
- **IAM Settings**: Allow administrators to define global limits for token lifecycle and security settings, and to enable or disable entities such as the `all_users` group. For more information, see Identity and Access Management Settings.
- **Symantec Identity Security Platform.** Support for Symantec Identity Security Platform as an identity provider. For more information see, Configure Symantec Identity Security Platform as an Identity Provider.
- **Generic OIDC:** Supports any OpenID Connect (OIDC) compatible identity provider. For more information, see Configure an Identity Provider using Generic OIDC.

Certificate Management

VCF Operations introduces comprehensive certificate management capabilities. You can now manage certificates for VCF 5.2.x components in your environment, such as vCenter, NSX, and ESX hosts. In addition, you can now manage standalone vCenter and ESX host certificates from version 8.0 U3 and later. Key functionalities in this release:

- **User Interface:** VCF Operations UI now offers improved functionality and bulk certificate operations.
- **API support:** You can now use VCF Operations API for third-party integration and automation of certificate management for all VCF components.
- **Expanded scope:** You can now manage certificates for HCX and Advance Load Balancer.
- **Certificate expiry tracking:** You can now track intermediate certificate expiry for vCenter and ESX.

For more information, see Managing Certificates in VMware Cloud Foundation.

Password Management

VCF Operations expands password management capabilities. Key functionalities in this release:

- **Password Policy:** You can now manage account passwords across VCF components by using fleet or instance password policies. A password policy defines password length, password complexity, account lockout, password change interval, and password history.
- **Expanded Scope:** You can now manage account passwords for VCF 5.2.x components in your environment, such as vCenter, NSX, and ESX hosts. In addition, you can manage passwords for standalone vCenter and ESX hosts from version vSphere 8.0 U3 and later.
- **Simplified Management:** Password operations are now streamlined. Manual prechecks, previously required during VCF Operations password updates, are no longer necessary.

- **Enhanced Security:** VCF Operations 9.1 no longer stores break-glass account passwords, eliminating the need for password remediation.
- **Integration Ready:** VCF Operations 9.1 offers new APIs that allow you to integrate with third party tools, such as Enterprise Vault.

For more information, see Managing Passwords for VMware Cloud Foundation Components.

Configuration Management (Earlier Known as Configuration Drifts)

Configuration management configuration templates are now available for vSphere Configuration Profile (VCP) enabled clusters in VCF Operations. You can monitor, detect configuration drift, and schedule drift detection on ESX Clusters across your VCF Fleet. You can also identify, view, and download host and cluster drift information from VCF Operations. For more information, see Creating Configuration Management Templates for Clusters and Detecting Drifts and and Downloading Drift Reports for Clusters.

Centralized vCenter Tag Management from VCF Operations

VCF Operations offers the following features:

- You can assign tags on any object across vCenter instances in your VCF fleet from VCF Operations.
- You can view and manage all your vCenter tag assignments across the VCF fleet in a single pane of glass in VCF Operations.

For more information, see Tags and Categories Overview.

Fleet Settings

You can configure the following:

- Password Policies
  For more information, see Create a password Policy for VCF Components.
- IAM Settings
  For more information, see Identity and Access Management Settings.
- DNS and NTP Settings
  - VCF Operations now has a consolidated interface for DNS/NTP settings configurations.
  - DNS/NTP settings can be assigned at the fleet level.
  - The global settings ensure uniform and consistent DNS/NTP settings across all components in the management components hierarchy.
    For more information, see Managing External Infrastructure Services for VCF Components.

Cost and capacity management

Cost Driver Enhancements

- **Server Hardware Expense Management**. You can now use the intuitive spreadsheet like interface to update the server hardware cost drivers. You can also use the new fields and filters to manage multiple server hardware effortlessly.
- **Additional Cost Driver**. Additional Cost Drivers now extend beyond VMs to clusters, hosts, and datacenters. You have more options to capture your miscellaneous expenses. You can allocate costs using tags, performance metrics, or fixed amounts.
- **Customizable Cost Ratio.** You can take control of your cost distribution strategy and define custom cost ratios. This helps to determine how infrastructure cost is split between CPU and memory resources. You can also align the allocation models with your organization's unique consumption patterns.
- **VM Cost Visibility.** You can now filter costs within the Organization and Projects Showback dashboards by specific service types: Regular VMs, VKS, and DSM.
- **Reclamation Dashboard.** Use this dashboard for a detailed, centralized view of your cost savings achieved from reclaimed idle VMs, snapshots, orphaned disks, and powered-off resources.
- **Application Showback and Chargeback**. You can view the total running costs of your applications and tiers, as well as the corresponding charges for the same.

For more information, see Editing Server Hardware : Traditional, Editing Server Hardware: Hyper-Converged, Editing Additional Costs, and Cluster Cost Overview.

VKS Cost Management

VCF Operations now delivers comprehensive costing capabilities across your entire Kubernetes ecosystem, including nodes, clusters, vSphere namespaces, projects, and organizations. For more information, see Cost Overview.

Chargeback

- **Upfront Pricing:** VCF now delivers real-time pricing estimates when you deploy virtual machines and Kubernetes nodes in VCF Automation. For more information, see Configuring Provider Pricing Details.
- **Tenant Reports and Alerts:**
  - Immediate email notifications to tenants regarding capacity thresholds, pricing and other relevant information across organizations and regions.
  - Comprehensive reporting of infrastructure consumption, resource utilization, and cost breakdowns tailored by the providers for tenants and delivered directly to the tenant's email.

    For more information, see Creating Notification Rules for Tenant in VCF Operations.
- **Bill PDF Export and Emails:** Streamlined billing communication with automated PDF delivery that makes it easier for tenants to access, review, and manage their bills anytime and from anywhere. For more information, see Download and Publish Bills.
- **VKS Chargeback:** VCF Operations now offers powerful tools to implement transparent, granular chargeback models specifically for VMware Kubernetes Service (VKS) nodes in addition to the traditional VM pricing. For more information, see Configuring Provider Pricing Details.

Workload Optimization

- **Storage based eviction:**

  VMware Cloud Foundation now dynamically assesses your cluster stress and moves workloads across clusters. In addition to the existing Compute stress, Storage stress can now be configured as a criterion for eviction and placement of workloads in other clusters, using the Workload Automation policy.
- **Network port group support**:

  Virtual Machines are now placed across equivalent port groups for All Apps organizations.

For more information, see Optimizing Capacity in VCF Operations.

Capacity Enhancements

- **Enhanced Storage Capacity Visibility.** Improved visibility into storage usage across vSAN, VMFS, NFS, and vVol datastore types on clusters, hosts, and VMs.
- **Multiple Recommendations per VM.** Delivery of multiple, simultaneous recommendations, such as rightsizing and snapshot reclamation, for a single VM regardless of its state (idle, powered off, or oversized).
- **Automation Central Enhancements.** Inclusion of idle and powered-off VMs when scheduling automated jobs for snapshot deletion and rightsizing in Automation Central.
- **Orphaned Disks Deletion.** Identification and deletion of orphaned disks to optimize system hygiene and storage reclamation.
- **Exclusion Enhancements in Optimize.** Options to exclude VMs from rightsizing and reclamation recommendations based on property tags, VM age, and history, along with automatic exclusion of Broadcom appliances.
- **Scale Improvements for What-if Analysis.**Increased limits for What-if analysis scenarios to support up to 10,000 VMs and 200 TB of storage capacity.

For more information, see Optimizing Capacity in VCF Operations.

Improved Capacity Recommendations and Forecast

Updated capacity algorithms to improve the accuracy and explainability of forecasts and recommendations are available. The configuration process for managing conservative workloads is simplified. For more information, see Optimizing Capacity in VCF Operations.

VCF Operations orchestrator

Repository improvements for Python and PowerShell environments

You can now configure up to two repositories for your Python and PowerShell scripting environments. This allows you to achieve a more efficient separation between development and production code.

Improvements to the default error handler

Previously, the default error handler workflow element could only catch and handle errors in the main workflow elements of the workflow schema. With VCF 9.1, the default error handler can now also catch and handle errors in the default error handler element itself. Users can also reconfigure the number of re-entries that the default error handler can perform when it encounters an error. These improvements enhance the debugging and recovery functionality for workflow runs.

Configurable session timeout

Administrators can now configure the session timeout of the VCF Operations orchestrator UI in minutes. By configuring a custom session timeout, users and workflow developers can avoid losing unsaved changes because of a short timeout limit. This change is only applicable to external VCF Operations orchestrator instances. Session timeout for embedded VCF Operations orchestrator instances is managed by VCF Automation.

Workload Mobility

Feature Deprecation

PhotonOS Based Appliances

Support for self-managed PhotonOS appliances in VCF Operations HCX is deprecated as of version 9.1.0.

Rationale: The NSX Edge stack offers superior performance and eliminates the redundancy of maintaining two functionally equivalent network stacks. An automated migration workflow is introduced in HCX 9.1 to move PhotonOS appliances to the NSX Edge architecture.

Timeline: Target for full removal is VCF 10.0.0.

Expanded OS Support

The following operating systems are now supported for Guest OS customization and OS Assisted Migration (OSAM):

- Guest OS Customization / Bulk Migration now supports Windows Server 2022.
- OS Assisted Migration (OSAM) now supports Windows Server 2022, Windows Server 2025.

Security and Compliance

- FIPS 140-3 Certification: HCX is now FIPS 140-3 certified, meeting rigorous security standards.
- Non-Disruptive Certificate (NDC) Management: New HCX Manager REST APIs enable managing HCX certificates without disrupting client trust.
- Network Security: HCX ports are added to the Distributed Firewall (DFW) exclusion list. Standard IPsec traffic between enhanced IX and NE instances.

VCF Integration and Management

- Lifecycle Management (LCM): HCX Manager is now deployed, managed, and upgraded via VCF Operations. Manually deployed HCX Manager instances can be onboarded and managed from VCF Operations.
- VCF Operations HCX Management Pack: A new management pack is available for installation in VCF Operations, enabling critical services like password rotation for local users and certificate rotations, log bundle collection. Note: This pack is incompatible with the legacy vRealize Operations management pack for HCX.
- Identity and Access: Support for VCF Single Sign-On (SSO) and VCF Roles for unified authentication and authorization on the HCX Manager Web UI and API.

Migration and Interconnect Enhancements

- WAN Optimization: Re-introduction of an efficient WAN optimization functionality embedded directly within the HCX Interconnect service mesh configuration. This feature is exclusive to enhanced service meshes and is not available for OSAM and HAV migrations.
- Local Site Migrations: Support for appliance-less migrations within a single vCenter instance with HCX Assisted vMotion (HAV), enabling source and destination to be the same instance.
- Advanced Storage and Rules Support:
  - Support for non-default storage policies in Cold migrations.
  - Ability to select multiple destination datastores for a single virtual machine (VM), except for OS Assisted Migration (OSAM).

- VLAN Network Extensions: Support for extending VLAN networks to native Distributed Virtual Port Groups (DVPGs) at the destination.
- Enriched and refreshed Web UI.

Optimized Appliance Architecture

- Enhanced Architecture: A new, optimized enhanced architecture is introduced for HCX Interconnect (IX) and Network Extension (NE) appliances, providing superior performance.
- Default for New Service Meshes: Starting with version 9.1, all new service meshes are automatically created using the enhanced architecture. Existing appliances from previous versions will maintain their legacy architecture unless migrated via the Migrating Network Extensions workflow.

Operate

Designed as a comprehensive observability hub, the **Operate** capability delivers a single pane of glass for monitoring operational health and performance. It synthesizes critical information—including system metrics, logs, and network traffic flows—to enable proactive troubleshooting and rapid root-cause analysis across the entire infrastructure and VCF deployment. Additionally, it incorporates environmental analytics through sustainability scores, allowing organizations to align infrastructure performance with energy efficiency goals.

Real-time metrics

Real-Time Data

The Overview page displays real-time or historical data for critical performance indicators—including CPU usage, memory utilization, disk I/O, and network throughput—on the Overview page. You can configure the granularity of real-time metrics, which defaults to 20 seconds, to as low as 2 seconds for ESX metrics via policy-based configuration.

- **TopN Charts.** Identify top-ranked objects, such as VMs, hosts, or datastores, based on specific metrics like CPU or memory utilization.
- **Custom Query.** Use PromQL-based search queries to derive operational insights. You can also create and save dashboards based on these PromQL queries.
- **Flows.** Explore and analyze network flows by traffic, volume, session count, or flow count.
- **Actions.** Execute command-line tools—including ipconfig, nslookup, iptables, netstat, tcpdump, route, arp, and dig—directly from the Actions tab to identify and resolve network issues.
- **Notes.** Document your findings and insights directly in the Notes section during an investigation.
- **Troubleshooting Session Lifecycle.** Save your troubleshooting sessions as investigations to track their lifecycle.
- **Collaboration.** Share investigations with other users to improve collaboration.

For more information, see Real-time Data in the Workbench.

Findings

Log Assist enhancements

VCF Operations health and diagnostics 9.1 adds automatic log bundle generation for the following VCF components:

- Full support bundle for the VCF Operations cluster
- VCF management services
- Cloud proxies
- Log management
- Identity broker

Log Assist 9.1 also allows you to generate bundles for selected VCF Operations nodes, not only the cluster-level bundle option. For more information, see Use Log Assist to Accelerate Your Support Cases..

Public APIs for Findings

Starting with VCF Operations health and diagnostics 9.1, you can use a set of public APIs that allow you to integrate diagnostic findings into your internal reporting and monitoring workflows such as risk management or ticketing. The Findings API allows you to centralize monitoring of real-time findings or get data for trend analyses. For more information, see Diagnostics Public REST API.

vSphere High Availability metrics in VCF Operations health and diagnostics

VCF Operations health and diagnostics 9.1 adds vSphere High Availability metrics that help proactive identification of issues and preventive resolution from a single view that lists all high availability clusters with their operational state. For more information, see vSphere High Availability Health in VCF Operations Health and Diagnostics.

Organizations

Enhanced Monitoring of Organizations

This release introduces a capability to view details about Organizations that have been provisioned. The Organizations page provides details of workloads created using the following managed services:

- VMware Kubernetes Service
- Virtual Machine Service
- Data Services

VCF health

Monitor ESX health and operational state with VCF Health

With VCF Operations health and diagnostics 9.1, you can monitor all ESX hosts in your environment, diagnose all aspects of operation and performance, and proactively resolve issues. ESX Health under VCF Health summarizes the critical issues that impact availability and connectivity of ESX hosts, grouped in the following categories:

- Reachability
- Connectivity
- Services Hardware (Memory and SSD)
- Purple Diagnostic Screen failures (PSOD count, active partition or dump file config status, and free space)
- Utilization

For more information, see ESX Health in VCF Operations Health and Diagnostics.

Monitor vCenter health and operational state with VCF Health

In the vCenter health metrics, VCF Operations health and diagnostics 9.1 adds the following enhancements:

- Endpoint monitoring, replacing the ping reachable/unreachable check to the vSphere Client and APIs.
- Extends the list of vCenter services to 18 from 6.
- Adds the VM Operations Task ID parameter that allows a drill down to the backtrace of a particular task.
- Adds the Error Stack panel to analyze the logs in case of VM failure.
- Highlights VMs with fast-growing snapshot sizes and the biggest VMs in terms of snapshot size.

For more information, see vCenter Health in VCF Operations Health and Diagnostics.

Monitor NSX health and operational state

VCF Operations health and diagnostics 9.1 provides the key metrics for NSX building blocks that help you track points of failure to prevent overutilization and optimize performance in your system. NSX metrics in VCF Operations diagnostics covers all operational aspects of the underlying infrastructure and appliances. For more information, see NSX Health in VCF Operations Health and Diagnostics.

Monitor vSAN cluster health and performance

VCF Operations health and diagnostics 9.1 gives you a single pane of glass for any vSAN-related monitoring, issue detection, and troubleshooting tasks. Storage Operations is integrated with the Diagnostics capability to add value by combining health scores and metrics with the means of accessing vCenter instances from the same screen. With the combined capability, you can spot a negative health condition in the vSAN Health screen, follow up on the root cause and take guided remediation steps in the vCenter instance. For more information, see vSAN Health in VCF Operations Health and Diagnostics.

Log management

The following features have been added:

- **Unified Log Management.** Log management capabilities are integrated within VCF Operations, including log masking, filtering, forwarding, partitioning, and the import of archived logs. Centralized agent configuration for efficient management is available in VCF Operations.
- **Upgrade and Deployment Support.** Initial deployment of log components and upgrade paths from VCF Operations for Logs 8.18 and VCF Operations 9.0 to VCF Operations 9.1 is supported.
- **Centralized Log Configuration.** Viewing and configuration of log collection across all VCF components is possible in VCF Operations, eliminating the need for manual configuration on individual components.
- There is a standalone UI to access logs in cases where VCF Operations becomes unavailable. The log capabilities limited to read-only with no configuration view, add, update or delete. For more information, see Accessing Logs when the VCF Operations Console is Inaccessible.
- **Analyse Logs.** Log management features are natively integrated into VCF Operations console. To view and analyze logs, log into the VCF Operations UI and navigate to **Operate > Logs**.
  - VCF Operations supports searching and filtering log messages, performing analysis and visualizing search results, working with alert queries, and dynamic field extraction from log messages based on customized queries. Navigate to *VCF Operations* > *Operate* > *Logs* to view and analyse logs.
- **Log Control and Filtering.** Centralized options to manage log volume, including the ability to enable, disable, and filter logs to suit specific environments, such as production or non-production endpoints is supported.
- **Standardized Log Collection.** Log collection processes are standardized by utilizing the **Log Insight agent** for appliances and Fluentbit for Kubernetes environments.
- **Scalability.** You can increase the log management capacity by adjusting size and replicas. See VCF Operations > Log Management in Config Max. Use the VCF Operations Sizing Estimator for the Log Management deployment size. It is recommended to use total EPS (event per second) across all hosts from the existing Aria Operations for Logs UI as the baseline for the upgraded Log Management. In the Aria Operations for Logs UI, go to **System Monitor** > **Statistics.**
- **Health Overview.** The Log Management Health Overview dashboards are available to assist you in determining the appropriate course of action when a system alert is triggered. Available dashboards are:
  - Log Management Health Overview
  - Log Management Health Drilldown (disabled by default)

  For more information, see Log Management Health Overview Dashboard.

For more information, see Configuring and Analyzing Logs.

VCF Operations for networks

Infrastructure visibility to VCF admins

VCF Operations Health and Diagnostics provides infrastructure visibility to VCF admins. Infrastructure related critical issues around appliances and capabilities are captured in simple dashboards. You can resolve issues quickly with the right information. All NSX health issues related to appliances and capabilities are captured in the dashboard for each NSX instance. NSX edge and ESX host networking capacity monitoring is critical, as it can impact connectivity and performance of the applications hosted on the VCF infrastructure. The out-of-the-box dashboards provide detailed metrics of NSX edge and ESX host networking. For more information, see NSX Health in VCF Operations Health and Diagnostics.

> **Note:**
>
> Edge monitoring is only accessible from the Edge dashboards in VCF Operations. You cannot access edge monitoring from VCF Operations for networks.

Network Assessment and Value

The Network Assessment and Value feature helps users to evaluate their current network infrastructure and see the value of VCF networking capabilities. Users can benefit by utilizing VPC networks and achieve capital expenditure (CAPEX) and operational expenditure (OPEX) savings. This assessment focuses on deployments with only virtual networking (VDS). Existing VPC networking configurations are not taken into account in the assessment. For more information, see Network Assessment and Value Analysis.

Expanded IPFIX Functionality for VKS Clusters

This feature allows for the application of container IPFIX flows on VKS clusters deployed with Antrea to be exported to the VCF Operations for networks collector. Flows are activated on all VKS clusters after Antrea IPFIX is enabled on the vCenter data source. Flows are then parsed and aggregated to produce dashboards in VCF Operations. These dashboards focus on traffic patterns, such as pod-to-pod and pod-to-external traffic between clusters. For more information, see Using Antrea IPFIX for VKS Flows.

VPC Planning

The VPC planning feature provides users with guidance in transitioning from vSphere networking to VPC networking. After selecting a vCenter server and Distributed Switch (VDS). for analysis, users are presented with a table with information and subnets and the details required to create a VPC. The generated VPC design can be exported as a CSV file. For more information, see VPC Planning.

NSX Inventory Objects and Relationship

The following changes to the NSX inventory dashboard have been introduced:

- Enhancements to VPC support.
- The NSX transverse spec is now moved from the **Integrations** tab to the **Networks** tab.
- Legacy dashboards are deprecated which streamlines the main NSX inventory dashboard.

Expanded Migration Planning Functionality

The migration planning feature for VCF Operations for networks is enhanced to support the automatic generation of migration waves and groups. This functionality clusters workloads based on flow, latency and bandwidth data. The enhanced migration plan summary provides a centralized source of information on the latest status of the migration planning progress in VMware HCX and precise resource calculations for the destination site of the migrated workloads. These enhancements remove the guesswork from complex migrations allowing for the migration of workloads with greater confidence and less manual effort. For more information, see Create a Migration Plan and Export Migration Waves.

Storage operations

vSAN Storage Performance

Performance insights extend the existing reactive capabilities to proactively to monitor vSAN performance metrics against a set of predefined rules. If any deviations from regular performance patterns are detected, it generates actionable insights in VCF Operations, which include the plausible causes and the steps to remediate the issues. For more information, see Monitoring Storage Operations.

vSAN Diagnostics

VCF Operations can now expose detailed health findings and specifics from the vSAN Health Service, going beyond the overall health score. The vSAN Health Service analyzes the cluster's status to generate a health score (100 is best) and provides detailed health findings with remediation guidance in vCenter. This allows for better identification of problematic clusters and provides the ability to launch directly to the respective vCenter for detailed remediation steps.

vSAN Effective Capacity

vSAN Effective Capacity provides a clear and accurate view of usable storage capacity by way of abstracting the complexities of RAID policies and system overhead. It highlights data reduction from advanced efficiency features, such as deduplication and compression, and reflects efficiency gains from thin provisioning and snapshot savings. This reporting aligns with the storage industry and helps promote the benefit of major ESA features. For more information, see vSAN Cluster Summary Tab.

Workload monitoring and observability

Load Balancing for cloud proxies that are a part of HA enabled collector groups

You can now activate load balancing for all cloud proxies that are a part of HA enabled collector groups for both product managed and open source Telegraf agents. For more information, see Monitoring Application Services using Product Managed Telegraf and Monitoring Application Services and Operating Systems using Open Source Telegraf.

Monitoring Data Service Workloads with VCF Operations

VCF delivers a cloud-native Database-as-a-Service (DBaaS) experience through Data Services. As the unified platform for database provisioning and lifecycle management, Data Services now integrates with VCF Operations to provide out-of-the-box monitoring for these database workloads. For more information, see Monitoring Data Services in VCF Operations.

Notifications

The behavior of the `${SYMPTOMS}` placeholder in webhook notification payload templates has changed

In 9.1, the `${SYMPTOMS}` placeholder was redesigned from a plain string to a structured JSON object representing symptom sets, conditions, and related context. As a result, `${SYMPTOMS}` can no longer be embedded inline with other variables or text within the same JSON value.

For correct usage, place `${SYMPTOMS}` as a dedicated key-value pair: `"symptoms": "${SYMPTOMS}"`. Embedding the `${SYMPTOMS}` placeholder within a larger text string, such as `"description": "Alert description: ${ALERT_DEFINITION_DESCRIPTION} \n\nSymptoms: ${SYMPTOMS}"`, is no longer supported.

Protect

Serving as the platform's security command center, the **Protect** capability focuses on ensuring cyber resilience and rigorous regulatory adherence. It provides continuous, real-time assessment of the infrastructure's security posture by monitoring encryption readiness and critical security advisories. This defensive stance is reinforced by robust auditing and compliance validation against industry benchmarks.

Security and compliance

Confidential Computing

Confidential computing capabilities in Security Operations help you profile your datacenter hardware and discover hosts that are capable of running confidential VMs. Gain visibility into your confidential VM environment along with the potential opportunity to host confidential VMs on supported hardware. For more information, see Infrastructure Security.

Audit Records and Audit Trail

Investigate user actions across various VCF components using a centralized, time-sliced view which is available in VCF Operations. You can leverage aggregated action summaries to easily navigate your audit log data and quickly identify key events in your environment. For more information, see Audit Records and Audit Trails.

Security Posture Management

Assess the compliance of your VCF environment against the VCF Security Configuration Guide and PCI DSS v4.0.1 standards. Remediate non-compliant findings using a revamped experience that includes out-of-the-box assessment, remediation, and reporting capabilities. For more information, see Security Posture Management.

VCF Automation

This document contains the following sections

- Cloud Administration
  - Provider Management
  - Organization Management
- vSphere Supervisor

Cloud Administration

Provider Management

Migration Tool

In VCF Automation 9.1, you can use the Migration Tool to perform an in-place migration from VMware Cloud Director to VCF Automation. For more information, contact your Broadcom representative.

Support for vDefend Distributed Firewall and Gateway Firewall

VCF Automation 9.1 introduces vDefend Distributed Firewall and Gateway Firewall support directly within VCF Automation. Provider administrators can now delegate vDefend Firewall services to organization administrators to control their own vDefend Gateway for the Transit Gateway Firewall and Distributed Firewalls. In addition, out-of-the-box security profiles have been created to allow uniform vDefend Firewall security for new and existing VPCs along with role-based access control labeling for dynamic security groups. For more information, go to the official vDefend Firewall documentation.

Setting for default Private VPC and Private TGW IP Blocks

Starting with VCF Automation 9.1, providers can use the Provider Management UI to configure a default private VPC and private TGW IP blocks that are configured in the organization itself after the organization's regional networking is set up. These settings can also be overridden for each organization when its regional networking is provisioned.

Support for Avi Load Balancer

VCF Automation 9.1 introduces full self-service support for Avi Load Balancer. From the provider management portal, administrators can delegate load balancing creation and management rights to the All Apps organization, ensuring operational autonomy. Providers can set quotas (e.g., service engine limits, application limits) on organizations to manage resource consumption and capacity. Organizations can provision namespaces with Avi load-balancing and create allocations with necessary load-balancing components such as VIP, pool, health monitors, persistence profiles, and other features.

Avi Load Balancer is also supported for VM Apps organizations.

For more information, go to the official Avi Load Balancer for VMware Cloud Foundation 9.1 documentation.

Multiple External Connections (Formerly Provider Gateways)

VCF Automation 9.1 introduces expanded flexibility for outbound traffic by supporting multiple external connections per organization. Provider administrators can now use the Provider Management UI to configure multiple external connections and associate them with organizations. This way, organizations have multiple exit points for external communication. VCF Automation 9.1 supports both centralized connections (formerly called Provider Gateways), which are based on NSX Tier-0 or Tier-0 VRF, and distributed VLAN connections.

For more information, see Managing External Connections in the VCF Automation Provider Management UI.

Shared VLAN Extension Subnets

Starting with VCF Automation 9.1, provider administrators can use the Provider Management UI to configure a VLAN extension NSX subnet and share that subnet with one or multiple organizations to enable the workloads in those organizations to establish direct connectivity to devices on the VLAN.

For more information, see Managing VLAN Extension Subnets in VCF Automation.

External IP Blocks with Multiple CIDRs

In VCF Automation 9.1, IP spaces from earlier releases are renamed to external IP blocks. External IP blocks enable provider administrators to configure multiple CIDRs and to specify included or excluded custom IP ranges, inline with NSX. Leveraging the newly introduced integration between NSX and Infoblox External IPAM, providers can now tie an Infoblox network container to VCF Automation IP blocks. Also, providers can hide the entire content of an external IP block from the organizations that consume the IP block through an external connection.

For more information, see Managing IP Blocks in the VCF Automation Provider Management UI.

Fully Allocated and Multi-Supervisor Region Quota for Organizations

Starting with VCF Automation 9.1, provider administrators can grant organizations quota across multiple supervisors in any given region. In addition, providers can also share the capacity of the entire region across all available supervisors with multiple organizations to simplify quota management.

Organization Management

Change Namespace Allocation Limits

In VCF Automation 9.1, application teams can adapt to the changing resource needs of their applications by performing day 2 actions on namespaces like changing resource limits, VM classes, storage classes, and shared subnets.

Project Content Libraries

VCF Automation 9.1 supports the ability for project teams to maintain content libraries that are specific to their project. This capability gives project teams additional flexibility and removes their dependency on the organization administrator. Project content libraries can also span across multiple projects. See Create a Project Content Library in VCF Automation.

Canonical Content Libraries

In VCF Automation 9.1, organizations can now have subscribed content libraries for Canonical Ubuntu VM OS images. The Ubuntu LTS images are validated and supported by VCF. Organization administrators or advanced users can synchronize the Canonical subscribed content library to fetch new sets of images. See Subscribe to Ubuntu OS Images from a Canonical Content Library in VCF Automation.

Support for Shared NSX Subnets in Organizations

VCF Automation 9.1 allows organization administrators to configure organization-wide NSX subnets and share them with one or more namespaces within the organization.

NSX Transit Gateways Configurations in Organizations

In VCF Automation 9.1, organization administrators can create multiple NSX Transit Gateways and configure NAT, IPsec VPN, and vDefend Gateway Firewall on those gateways. See Create a Transit Gateway in VCF Automation.

vSphere Supervisor

For vSphere Supervisor What's New, see VMware vSphere Supervisor Release Notes.

VCF SDKs, APIs, and CLIs

This document contains the following sections

- VCF APIs
- VMware Cloud Foundation Java SDK
- VMware Cloud Foundation Python SDK
- VMware Cloud Foundation PowerCLI

VCF APIs

Real-Time Metrics APIs (VODAP)

The new Real-Time Metrics APIs deliver a modern, centralized observability platform for VMware Cloud Foundation.

Key Capabilities:

- **High-Granularity Visibility:** These Prometheus-compatible Edge APIs allow users to query real-time, high-granularity (up to 2-second) metrics across the unified SDDC stack, including ESX, vCenter, vSAN, and NSX.
- **Seamless Grafana Integration:** Native PromQL support enables the APIs to function as a direct data source for Grafana.
- **Simplified Configuration:** A single API call now accesses built-in collection profiles (Essentials, Standard, and Verbose), replacing the complex legacy configuration model. As part of this transition, the legacy vStats Tech-Preview APIs are deprecated.

For detailed information, see What's changed in Realtime Metrics API in the API Reference documentation.

Introduced the Utilization API, which monitors vCenter capacity and usage metrics.

Introduced the `Utilization` API, which monitors vCenter capacity and usage metrics, including:

- The number of active connections compared to the maximum allowed connection limit.
- The endpoints through which these connections are established.
- The number of requests sent to vCenter services relative to the maximum request capacity supported by those services.

Building on this API, new UI alarms have been added. These alarms are triggered when:

- Active connections exceed a configured threshold, and/or
- Service request volume surpasses the defined limit.

Threshold values are fully configurable through Advanced Settings.

The vCenter Group Federated API (VGFA) introduces a single unified API endpoint for managing all vCenter instances in a vCenter group.

It allows clients to view and manage inventory across multiple vCenter instances as if they were one—without changing existing API integrations.

VGFA can be enabled directly from the VCF Operations UI once SSO and vCenter group configuration are in place. After activation, users gain seamless access to a consolidated inventory and operations experience, consistent with Linked Mode in the UI.

This simplifies multi-vCenter automation, reduces integration complexity, and delivers a more streamlined management experience at scale.

Introduced a new Query API as extension of already existing Search Index API. that delivers a fast, flexible, and scalable way to retrieve vSphere inventory data such as virtual machines and clusters.

The Query API delivers a fast, flexible, and scalable way to retrieve vSphere inventory data such as virtual machines and clusters.

The Query API enables:

- Powerful server-side filtering based on user-defined criteria.
- Efficient data access with pagination, property selection, and projections.
- Lightweight, stateless queries without server-side state or client-side caching.
- Entity counts and filtered results without retrieving full datasets.

Designed for high-frequency automation use cases, the Query API simplifies data access. This capability is now available to customers and partners, improving performance, reliability, and ease of automation across vCenter environments.

VMware Cloud Foundation Java SDK

Extended component coverage for the VMware Cloud Foundation Java SDK

The list of new components supported in VCF 9.1 :

- VMware NSX
- VMware Cloud Foundation Operations
- Log Management
- VMware Cloud Foundation Operations for networks
- Fleet Lifecycle
- SDDC Lifecycle

Additionally, the VODAP OpenAPI specifications are now available.

Enhanced samples and API reference documentation

To accelerate your development, we have added a wide array of new samples to the VCF Java SDK. These samples cover:

- VCF Installer and vCenter
- NSX and VCF Operations
- SDDC Management workflows

The build system for the VMware Cloud Foundation Java SDK samples is changed from Gradle to Maven.

The code samples are shipped as separate .ZIP deliverable along with the VMware Cloud Foundation Java SDK.

VMware Cloud Foundation Python SDK

New components are now supported with VMware Cloud Foundation Python SDK

The list of new components supported in VCF 9.1 :

- VMware NSX

- VMware Cloud Foundation Operations
- Log Management
- VMware Cloud Foundation Operations for networks
- Fleet Lifecycle
- SDDC Lifecycle

Additionally, the VODAP OpenAPI specifications are now available.

Enhanced samples and API reference documentation

To accelerate your development, we have added a wide array of new samples to the VCF Python SDK. These samples cover:

- VCF Installer and vCenter
- NSX and VCF Operations
- SDDC Management workflows

The code samples are shipped as separate .ZIP deliverable along with the VMware Cloud Foundation Python SDK.

VMware Cloud Foundation PowerCLI

Introduction

VCF PowerCLI 9.1 introduces highly requested capabilities centered around high-performance storage, advanced networking, and critical security compliance. This release focuses on giving administrators more granular control over the SDDC stack while ensuring the underlying toolset remains modern and secure.

Core infrastructure and host management

The following list of top customer requests to improve host-level configuration and hardware optimization are addressed:

- CPU Topology Management: Support for Assigned at PowerOn, providing precise control over virtual machine CPU layouts.
- NVMe over TCP: Added support for enabling NVMe over TCP for VMkernel adapters, catering to high-performance storage requirements.
- Active Directory Integration: Enhanced host management by allowing hosts to join an AD domain via a proxy server.

vSAN enhancements

New cmdlets and methods are added to streamline storage reporting and remote datastore management:

- Effective Capacity Reporting: New cmdlet for better visibility into usable storage.
- vSAN Max: Support for client network enablement.
- Remote Datastore Management: Capability to add/remove remote datastores and cross vCenter remote datastores using both desired state and incremental methods.

Advanced VPC networking

The VPC module receives a massive expansion in 9.1, offering deeper integration for transit gateways and connectivity policies:

- DHCP & IP Management: Extended DHCP configurations for VPCs/Subnets and the ability to define IP Blocks for services or external IPs.
- Transit Gateway & Connectivity: New tools to manage Transit Gateway lifecycles and Connectivity Profiles to define how VPCs attach to gateways and IP blocks.
- Connectivity Policies: Introduced the ability to define logical VPC Groups with specific communication policies:
  - Community: Inter-VPC communication within the group.
  - Private: Isolation from other VPCs.
  - Promiscuous: Communication across all VPCs.
- Visibility: New support for retrieving VPC NAT configurations and viewing VPC-specific alarm information.

Image Builder and lifecycle security

To ensure compliance with the latest security standards and modern environments:

- Python 3.13 Support: The Image Builder module now officially supports Python 3.13, enabling customers with strict compliance rules to continue patching and updating safely.

  Important:

  Deprecation Notice: Support for Python 3.7 and 3.8 is now deprecated due to these versions reaching End of Life (EOL). While they remain functional in 9.1, support will be completely removed in the next release. We strongly recommend migrating to Python 3.9 or higher immediately.

What's New cmdlets

VCF PowerCLI 9.1 introduces the following new features, changes, and improvements:

- `VMware.VimAutomation.Storage` -
  - Added new cmdlet, `Get-VsanEffectiveCapacity`, to allow you to get `EffectiveCapacity` detailed metrics.
  - Added new parameter, `DeconvergedNetConfigEnabled`, to `Get-VsanClusterConfiguration` and `Set-VsanClusterConfiguration`. It allows you to activate and deactivate the vSAN Max Client Network (traffic separation or dedicated vmknic) in the vSAN cluster configuration.
  - Added new cmdlets, `New-VsanRemoteDatastore` and `Remove-VsanRemoteDatastore` and new parameter, `XVCDatastore -RemoteDatastore` to `Set-VsanClusterConfiguration` cmdlet. These allow you to add and remove remote datastore and cross vCenter remote datastore with desired state and incremental method.
- `VMware.ImageBuilder` -
  - Support for Python 3.7 and 3.8 is now deprecated due to these versions reaching End of Life (EOL). You must migrate to Python 3.9 or higher immediately.
  - Added support for Python 3.13 with `VMware.ImageBuilder`
- `VMware.VimAutomation.Vpc` -
  - `New-VpcServiceProfile`, `Set-VpcServiceProfile`, `Remove-VpcServiceProfile` - Added support for DHCP configurations.
  - `New-VpcIpBlock`, `Remove-VpcIpBlock`, new parameter in `Get-VpcIpBlock` - Allows to define the IP Block providing IPs for Subnets, Services or External IPs (Exposing VM on Private Networks).
  - In `New-NetworkAdapter`, `Set-NetworkAdapter`, `Get-NetworkAdapter` added new parameter - `AssignExternalIp` that allows you to assign external IPs to VM Network adapters on Private Networks.
  - `Get-VpcExternalConnection`, `New-VpcExternalConnection`, `Set-VpcExternalConnection`, and `Remove-VpcExternalConnection` - Allows you to manage External Connection providing connectivity between Transit Gateways and data center.
  - `Get-VpcVcCluster`, `Get-VpcSpan`, `New-VpcSpan`, `Set-VpcSpan`, and `Remove-VpcSpan` - Allows you to manage VPC span in a vCenter instance.
  - `Get-VpcEdgeCluster`, `Get-VpcServiceCluster`, `Get-VpcTransitGateway`, `New-VpcTransitGateway`, `Set-VpcTransitGateway`, and `Remove-VpcTransitGateway` - Allows you to manage Transit Gateway create, edit and delete to connect VPCs together and to outside.
  - `New-VpcConnectivityProfile`, `Set-VpcConnectivityProfile`, and `Remove-VpcConnectivityProfile` - Defines to which transit gateway the VPC connects and which IP blocks the VPC uses (external and private).
  - `Get-VpcNat`, `Get-VpcNatRules`, and `Get-VpcNatRulesStatistic` - Allows you to retrieve VPC NAT configurations.
  - `New-VpcGroup`, `Set-VpcGroup`, `Remove-VpcGroup`, and `Get-VpcGroup` - Allows you to define groups of VPCs, to logically group VPCs together in order to define connectivity policies.
  - `New-VpcConnectivityPolicy`, `Set-VpcConnectivityPolicy`, `Remove-VpcConnectivityPolicy`, and `Get-VpcConnectivityPolicy` - Allows you to define connectivity policies between VPCs connected to the same transit gateway. A VPC can belongs up to one group associated to a policy which can be :
    - community - communication between VPCs of the same community.
    - private - no communication with other private or community VPCs.
    - promiscuous - communication with all VPCs including private and any community.
  - `Get-VpcAlarm` - Shows alarm information about a VPC.
- `VMware.VimAutomation.Core` -
  - Adding support for VMK services in `New-VMHostNetworkAdapter` and `Set-VMHostNetworkAdapter`.

  - Adding support for `CoresPerNumaNode` for `New-VM` and `Set-VM` cmdlets. Updating `CoresPerSocket` support for `New-VM` and `Set-VM` cmdlets.
  - Added a `VcfOAuthSecurityContext` parameter to the following cmdlets: `Connect-VIServer`, `Connect-NsxServer`, and `Connect-VcfOpsServer`. Added a `VcfApiToken` parameter to the following cmdlets: `Connect-VIServer` and `Connect-NsxServer`.
    This change adds a new authentication mode for VCF components integrated with VCF SSO. Users can authenticate either by instantiating a `VcfOAuthSecurityContext` for a specific VCF SSO instance or just by an API token. In the latter case the VCF SSO is discovered automatically by VCF PowerCLI.
  - Added a `Proxy` parameter to `Set-VMHostAuthentication` - Added a new parameter for joining an ESX server to an Active Directory by using its vCenter as a proxy server.
  - Added the following parameters to `New-Cluster`: `Components` and `RemovedComponents`. Added support for specifying components excluded from a vSphere Lifecycle Manager image for clusters.
- `VMware.Vcf.Sso` -
  - `New-VcfOAuthSecurityContext` - Allows you to create a Single Sign-On connection using a VCF API token that can then be used to authenticate to other VCF components.
- `VMware.Vcf.SddcManager` -
  - `Remove-SddcCluster`, `Remove-SddcDomain`, `Remove-SddcHost`, and `Get-SddcTask` - Added commands for removal of SDDC workload domains, clusters and hosts, reporting and waiting on server task in the SDDC manager.

Changelog for VCF 9.1

This document provides a consolidated summary of all changes made to the API layer across various VCF components. It highlights newly introduced APIs, removed APIs, deprecated APIs, updated APIs, and structural modifications.

For in-depth information on each change, click the hyperlink associated with the corresponding API specification. This will take you to a dedicated page on the Broadcom Developer Portal with comprehensive details about the specific modifications.

vSphere

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
Virtual Infrastructure JSON API	48	0	0	
vSphere Automation API	101	28	28	

NSX

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
NSX Autonomous Edge API	9	0	1	
NSX Global Policy API	58	3	0	
NSX Manager API	31	11	17	
NSX Policy API	264	6	9	

VCF Operations

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
Log Management API	23	0	136	
VCF Operations API	134	0	0	

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
VCF Operations Orchestrator API	7	0	1	
VCF Operations for Networks API	5	22	1	

SDDC Manager

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
SDDC Manager API	48	21	0	

VMware Identity Broker

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
VMware Identity Broker - vCenter Server API	9	0	0	

VCF Installer

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
VCF Installer API	5	0	0	

Protection and Recovery

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
Data Protection Appliance Configuration API	0	0	0	
VMware Live Site Recovery API	0	0	0	
VMware Live Site Recovery Configuration API	0	0	0	
vSAN Data Protection API	17	0	0	
vSphere Replication API	0	0	0	

LCM

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
NEW VCF Fleet LCM Service APIs	51	0	0	
NEW VCF SDDC LCM Service APIs	26	0	0	

Org Management - All Apps Org

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
All Apps Org - Access Control	77	0	32	
All Apps Org - Aggregator	4	0	28	
All Apps Org - Approvals	4	0	28	
All Apps Org - Blueprint	6	0	0	
All Apps Org - Catalog	4	0	0	
All Apps Org - Custom Forms	0	7	0	
All Apps Org - Custom Resource Types And Actions	4	2	0	
NEW All Apps Org - Event Broker Service API	7	0	0	
All Apps Org - Instances	4	0	0	
All Apps Org - Orchestrator Gateway	0	0	0	
All Apps Org - Policy	4	0	0	
All Apps Org - Projects	1	0	0	

Org Management - VM Apps Org

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
VM Apps Org - ABX	0	1	0	
NEW VM Apps Org - Access Control	85	0	0	
VM Apps Org - Approval	0	0	68	
VM Apps Org - Blueprint	0	0	0	
VM Apps Org - Catalog	0	0	0	
VM Apps Org - Content Gateway	0	0	7	
VM Apps Org - Custom Forms	0	2	0	
VM Apps Org - Deployment	0	0	0	
VM Apps Org - DeploymentMetric	0	0	68	
NEW VM Apps Org - Event Broker Service API	7	0	0	
VM Apps Org - Onboarding	0	0	1	
VM Apps Org - Orchestrator Gateway	0	0	0	
VM Apps Org - Policies	0	0	0	
VM Apps Org - Project	0	0	0	
VM Apps Org - Provisioning Service	5	0	0	

Private AI Services

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
VMware Private AI Service API	18	0	0	

Provider Infrastructure APIs

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
Provider Infrastructure APIs	230	0	369	

Realtime Metrics

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
NEW Realtime Metrics API	4	0	0	

VMware Data Service Manager

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS	
VMware Data Services Manager REST API	1	0	0	

Changelog for NSX NSX Autonomous Edge API

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	9	247	0	1
Structures	6	11	0	0

Total changes: 308

Operation Changes

New Operations

VERB	PATH
POST	/node/file-store?action=retrieve_matching_host_key_algorithm
GET	/node/fips/modules
GET	/node/fips/modules?component_name=nsx-edge
GET	/node/fips/modules?component_name=nsx-global-manager
GET	/node/fips/modules?component_name=nsx-manager
DELETE	/node/services/ssh?action=clear_banner

VERB	PATH
POST	/node/services/syslog/exporters?action=delete_all_non_vcf_ops_managed_exporters
POST	/vpn/l2vpn/sessions
PUT	/vpn/l2vpn/sessions/{l2vpn-session-id}

Updated Operations

GET /high-availability/nodes/{node-id}/status

- Response added with Status Code `504`

DELETE /high-availability/nodes/{node-id}

- Response added with Status Code `504`

POST /high-availability?action=dissolve_and_make_primary

- Response added with Status Code `504`

GET /high-availability

- Response added with Status Code `504`

POST /node/aaa/auth-policy?action=reset-all

- Response added with Status Code `504`

POST /node/aaa/auth-policy?action=reset-auth-policies

- Response added with Status Code `504`

POST /node/aaa/auth-policy?action=reset-pwd-complexity

- Response added with Status Code `504`

GET /node/aaa/auth-policy

- Response added with Status Code `504`

PUT /node/aaa/auth-policy

- Response added with Status Code `504`

GET /node/api-certificate

- Response added with Status Code `504`

POST /node/api-certificate

- Response added with Status Code `504`

DELETE /node/core-dumps/{file-name}

- Response added with Status Code `504`

GET /node/core-dumps

- Response added with Status Code `504`

GET /node/diagnosis/inconsistency

- Response added with Status Code `504`

GET /node/diagnosis

- Response added with Status Code `504`

GET /node/file-store/{file-name}/data

- Response added with Status Code `504`

PUT /node/file-store/{file-name}/data

- Response added with Status Code `504`

GET /node/file-store/{file-name}/thumbprint

- Response added with Status Code `504`

DELETE /node/file-store/{file-name}

- Response added with Status Code `504`

GET /node/file-store/{file-name}

- Response added with Status Code `504`

POST /node/file-store/{file-name}

- Response added with Status Code `504`

POST /node/file-store?action=retrieve_ssh_fingerprint

- Response added with Status Code `504`

GET /node/file-store

- Response added with Status Code `504`

PUT /node/grub/{grub-username}

- Response added with Status Code `504`

GET /node/grub

- Response added with Status Code `504`

PUT /node/grub

- Response added with Status Code `504`

GET /node/hardening-policy/mandatory-access-control/report

- Response added with Status Code `504`

GET /node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

PUT /node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

GET /node/logical-routers/diagnosis

- Response added with Status Code `504`

GET /node/logical-routers/{logical-router-id}/diagnosis

- Response added with Status Code `504`

GET /node/logs/{log-name}/data

- Response added with Status Code `504`

GET /node/logs/{log-name}

- Response added with Status Code `504`

GET /node/logs

- Response added with Status Code `504`

GET /node/maintenance-mode

- Response added with Status Code `504`

PUT /node/maintenance-mode

- Response added with Status Code `504`

GET /node/motd

- Response added with Status Code `504`

GET /node/network/interfaces/{interface-id}/stats

- Response added with Status Code `504`

GET /node/network/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /node/network/interfaces/{interface-id}

- Response added with Status Code `504`

GET /node/network/interfaces

- Response added with Status Code `504`

GET /node/network/name-servers

- Response added with Status Code `504`

PUT /node/network/name-servers

- Response added with Status Code `504`

DELETE /node/network/routes/{route-id}

- Response added with Status Code `504`

GET /node/network/routes/{route-id}

- Response added with Status Code `504`

GET /node/network/routes

- Response added with Status Code `504`

POST /node/network/routes

- Response added with Status Code `504`

GET /node/network/search-domains

- Response added with Status Code `504`

PUT /node/network/search-domains

- Response added with Status Code `504`

GET /node/network

- Response added with Status Code `504`

GET /node/processes/{process-id}

- Response added with Status Code `504`

GET /node/processes

- Response added with Status Code `504`

GET /node/services/dataplane/cpu-stats

- Response added with Status Code `504`

PUT /node/services/dataplane/ctrl-prio

- Response added with Status Code `504`

GET /node/services/dataplane/flow-cache

- Response added with Status Code `504`

PUT /node/services/dataplane/flow-cache

- Response added with Status Code `504`

GET /node/services/dataplane/flow-mon

- Response added with Status Code `504`

PUT /node/services/dataplane/flow-mon

- Response added with Status Code `504`

GET /node/services/dataplane/geneve-cbit

- Response added with Status Code `504`

PUT /node/services/dataplane/geneve-cbit

- Response added with Status Code `504`

PUT /node/services/dataplane/intr-mode

- Response added with Status Code `504`

GET /node/services/dataplane/l2vpn-pmtu

- Response added with Status Code `504`

PUT /node/services/dataplane/l2vpn-pmtu

- Response added with Status Code `504`

GET /node/services/dataplane/physical-ports/{physical-port}/stats

- Response added with Status Code `504`

GET /node/services/dataplane/physical-ports/{physical-port}/xstats

- Response added with Status Code `504`

GET /node/services/dataplane/pmtu-learning

- Response added with Status Code `504`

PUT /node/services/dataplane/pmtu-learning

- Response added with Status Code `504`

PUT /node/services/dataplane/qat-enable

- Response added with Status Code `504`

GET /node/services/dataplane/qat-status

- Response added with Status Code `504`

GET /node/services/dataplane/queue-num-per-port-per-core

- Response added with Status Code `504`

PUT /node/services/dataplane/queue-num-per-port-per-core

- Response added with Status Code `504`

GET /node/services/dataplane/ring-size

- Response added with Status Code `504`

PUT /node/services/dataplane/rx-ring-size

- Response added with Status Code `504`

GET /node/services/dataplane/status

- Response added with Status Code `504`

PUT /node/services/dataplane/tx-ring-size

- Response added with Status Code `504`

GET /node/services/dataplane/upt-mode

- Response added with Status Code `504`

POST /node/services/dataplane?action=restart

- Response added with Status Code `504`

POST /node/services/dataplane?action=start

- Response added with Status Code `504`

POST /node/services/dataplane?action=stop

- Response added with Status Code `504`

GET /node/services/dataplane

- Response added with Status Code `504`

PUT /node/services/dataplane

- Response added with Status Code `504`

GET /node/services/docker/status

- Response added with Status Code `504`

GET /node/services/docker

- Response added with Status Code `504`

GET /node/services/ipsecvpn/status

- Response added with Status Code `504`

GET /node/services/ipsecvpn

- Response added with Status Code `504`

PUT /node/services/ipsecvpn

- Response added with Status Code `504`

GET /node/services/liagent/status

- Response added with Status Code `504`

POST /node/services/liagent?action=restart

- Response added with Status Code `504`

POST /node/services/liagent?action=start

- Response added with Status Code `504`

POST /node/services/liagent?action=stop

- Response added with Status Code `504`

GET /node/services/liagent

- Response added with Status Code `504`

GET /node/services/local-controller/status

- Response added with Status Code `504`

POST /node/services/local-controller?action=restart

- Response added with Status Code `504`

POST /node/services/local-controller?action=start

- Response added with Status Code `504`

POST /node/services/local-controller?action=stop

- Response added with Status Code `504`

GET /node/services/local-controller

- Response added with Status Code `504`

PUT /node/services/local-controller

- Response added with Status Code `504`

GET /node/services/nestdb/status

- Response added with Status Code `504`

POST /node/services/nestdb?action=restart

- Response added with Status Code `504`

POST /node/services/nestdb?action=start

- Response added with Status Code `504`

POST /node/services/nestdb?action=stop

- Response added with Status Code `504`

GET /node/services/nestdb

- Response added with Status Code `504`

GET /node/services/node-mgmt/loglevel

- Response added with Status Code `504`

PUT /node/services/node-mgmt/loglevel

- Response added with Status Code `504`

GET /node/services/node-mgmt/status

- Response added with Status Code `504`

POST /node/services/node-mgmt?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

GET /node/services/node-mgmt

- Response added with Status Code `504`

GET /node/services/nsx-platform-client/status

- Response added with Status Code `504`

POST /node/services/nsx-platform-client?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

POST /node/services/nsx-platform-client?action=start

- Parameter added: `force`
- Response added with Status Code `504`

POST /node/services/nsx-platform-client?action=stop

- Parameter added: `force`
- Response added with Status Code `504`

GET /node/services/nsx-platform-client

- Response added with Status Code `504`

GET /node/services/nsx-upgrade-agent/status

- Response added with Status Code `504`

POST /node/services/nsx-upgrade-agent?action=restart

- Response added with Status Code `504`

POST /node/services/nsx-upgrade-agent?action=start

- Response added with Status Code `504`

POST /node/services/nsx-upgrade-agent?action=stop

- Response added with Status Code `504`

GET /node/services/nsx-upgrade-agent

- Response added with Status Code `504`

GET /node/services/ntp/status

- Response added with Status Code `504`

POST /node/services/ntp?action=restart

- Response added with Status Code `504`

POST /node/services/ntp?action=start

- Response added with Status Code `504`

POST /node/services/ntp?action=stop

- Response added with Status Code `504`

GET /node/services/ntp

- Response added with Status Code `504`

PUT /node/services/ntp

- Response added with Status Code `504`

GET /node/services/replica-agent/client/status

- Response added with Status Code `504`

GET /node/services/replica-agent/status

- Response added with Status Code `504`

POST /node/services/replica-agent?action=restart

- Response added with Status Code `504`

POST /node/services/replica-agent?action=start

- Response added with Status Code `504`

POST /node/services/replica-agent?action=stop

- Response added with Status Code `504`

GET /node/services/replica-agent

- Response added with Status Code `504`

GET /node/services/router-config/status

- Response added with Status Code `504`

GET /node/services/router-config

- Response added with Status Code `504`

GET /node/services/router/status

- Response added with Status Code `504`

GET /node/services/router

- Response added with Status Code `504`

GET /node/services/snmp/status

- Response added with Status Code `504`

GET /node/services/snmp/v3-engine-id

- Response added with Status Code `504`

PUT /node/services/snmp/v3-engine-id

- Response added with Status Code `504`

POST /node/services/snmp?action=restart

- Response added with Status Code `504`

POST /node/services/snmp?action=start

- Response added with Status Code `504`

POST /node/services/snmp?action=stop

- Response added with Status Code `504`

GET /node/services/snmp

- Response added with Status Code `504`

PUT /node/services/snmp

- Response added with Status Code `504`

POST /node/services/ssh/notify_mpa?action=restart

- Response added with Status Code `504`

POST /node/services/ssh/notify_mpa?action=start

- Response added with Status Code `504`

POST /node/services/ssh/notify_mpa?action=stop

- Response added with Status Code `504`

GET /node/services/ssh/status

- Response added with Status Code `504`

POST /node/services/ssh?action=remove_host_fingerprint

- Response added with Status Code `504`

POST /node/services/ssh?action=restart

- Response added with Status Code `504`

POST /node/services/ssh?action=start

- Response added with Status Code `504`

POST /node/services/ssh?action=stop

- Response added with Status Code `504`

GET /node/services/ssh

- Response added with Status Code `504`

PUT /node/services/ssh

- Response added with Status Code `504`

DELETE /node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `409`
- Response added with Status Code `504`

GET /node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `504`

POST /node/services/syslog/exporters?action=verify

- Response added with Status Code `504`

DELETE /node/services/syslog/exporters

- Response added with Status Code `409`
- Response added with Status Code `504`

GET /node/services/syslog/exporters

- Response added with Status Code `504`

POST /node/services/syslog/exporters

- Response added with Status Code `504`

GET /node/services/syslog/status

- Response added with Status Code `504`

POST /node/services/syslog?action=restart

- Response added with Status Code `504`

POST /node/services/syslog?action=start

- Response added with Status Code `504`

POST /node/services/syslog?action=stop

- Response added with Status Code `504`

GET /node/services/syslog

- Response added with Status Code `504`

GET /node/services

- Response added with Status Code `504`

POST /node/status?action=clear_bootup_error

- Response added with Status Code `504`

GET /node/status

- Response added with Status Code `504`

GET /node/support-bundle

- Response added with Status Code `504`

GET /node/tasks/{task-id}/response

- Response added with Status Code `504`

POST /node/tasks/{task-id}?action=cancel

- Response added with Status Code `504`

DELETE /node/tasks/{task-id}

- Response added with Status Code `504`

GET /node/tasks/{task-id}

- Response added with Status Code `504`

GET /node/tasks

- Response added with Status Code `504`

POST /node/upgrade/performtask

- Response added with Status Code `504`

GET /node/upgrade/progress-status

- Response added with Status Code `504`

GET /node/upgrade/status-summary

- Response added with Status Code `504`

GET /node/upgrade

- Response added with Status Code `504`

POST /node/users/{userid}/ssh-keys?action=add_ssh_key

- Response added with Status Code `504`

POST /node/users/{userid}/ssh-keys?action=remove_ssh_key

- Response added with Status Code `504`

GET /node/users/{userid}/ssh-keys

- Response added with Status Code `504`

POST /node/users/{userid}?action=reset_password

- Response added with Status Code `504`

DELETE /node/users/{userid}

- Response added with Status Code `504`

GET /node/users/{userid}

- Response added with Status Code `504`

PUT /node/users/{userid}

- Response added with Status Code `504`

GET /node/users

- Property changed `operationId` from `ListNodeUsersTrue` to `ListNodeUsers`
- Response added with Status Code `504`

GET /node/version

- Response added with Status Code `504`

POST /node?action=restart

- Response added with Status Code `504`

POST /node?action=set_coredump_config

- Response added with Status Code `504`

POST /node?action=set_system_time

- Response added with Status Code `504`

POST /node?action=shutdown

- Response added with Status Code `504`

GET /node

- Response added with Status Code `504`

PUT /node

- Response added with Status Code `504`

GET /ports/{logical-router-port-id}/statistics

- Response added with Status Code `504`

DELETE /ports/{port-id}

- Response added with Status Code `504`

GET /ports/{port-id}

- Response added with Status Code `504`

PUT /ports/{port-id}

- Response added with Status Code `504`

GET /ports

- Response added with Status Code `504`

POST /ports

- Response added with Status Code `504`

GET /routing/forwarding-table

- Response added with Status Code `504`

DELETE /routing/static-routes/{static-route-id}

- Response added with Status Code `504`

GET /routing/static-routes/{static-route-id}

- Response added with Status Code `504`

PUT /routing/static-routes/{static-route-id}

- Response added with Status Code `504`

GET /routing/static-routes

- Response added with Status Code `504`

POST /routing/static-routes

- Response added with Status Code `504`

DELETE /trust-management/certificates/{cert-id}

- Response added with Status Code `504`

GET /trust-management/certificates/{cert-id}

- Response added with Status Code `504`

PUT /trust-management/certificates/{cert-id}

- Response added with Status Code `504`

GET /trust-management/certificates

- Response added with Status Code `504`

POST /trust-management/certificates

- Response added with Status Code `504`

DELETE /trust-management/crls/{crl-id}

- Response added with Status Code `504`

GET /trust-management/crls/{crl-id}

- Response added with Status Code `504`

PUT /trust-management/crls/{crl-id}

- Response added with Status Code `504`

GET /trust-management/crls

- Response added with Status Code `504`

POST /trust-management/crls

- Response added with Status Code `504`

DELETE /vpn/ipsec/dpd-profiles/{ipsec-vpn-dpd-profile-id}

- Response added with Status Code `504`

GET /vpn/ipsec/dpd-profiles/{ipsec-vpn-dpd-profile-id}

- Response added with Status Code `504`

PUT /vpn/ipsec/dpd-profiles/{ipsec-vpn-dpd-profile-id}

- Response added with Status Code `504`

GET /vpn/ipsec/dpd-profiles

- Response added with Status Code `504`

POST /vpn/ipsec/dpd-profiles

- Response added with Status Code `504`

DELETE /vpn/ipsec/ike-profiles/{ipsec-vpn-ike-profile-id}

- Response added with Status Code `504`

GET /vpn/ipsec/ike-profiles/{ipsec-vpn-ike-profile-id}

- Response added with Status Code `504`

PUT /vpn/ipsec/ike-profiles/{ipsec-vpn-ike-profile-id}

- Response added with Status Code `504`

GET /vpn/ipsec/ike-profiles

- Response added with Status Code `504`

POST /vpn/ipsec/ike-profiles

- Response added with Status Code `504`

DELETE /vpn/ipsec/multi-path-groups/{ipsec-multi-path-group-id}

- Response added with Status Code `504`

GET /vpn/ipsec/multi-path-groups/{ipsec-multi-path-group-id}

- Response added with Status Code `504`

PUT /vpn/ipsec/multi-path-groups/{ipsec-multi-path-group-id}

- Response added with Status Code `504`

GET /vpn/ipsec/multi-path-groups

- Response added with Status Code `504`

POST /vpn/ipsec/multi-path-groups

- Response added with Status Code `504`

GET /vpn/ipsec/service

- Response added with Status Code `504`

PUT /vpn/ipsec/service

- Response added with Status Code `504`

GET /vpn/ipsec/sessions/{ipsec-vpn-session-id}?action=show-sensitive-data

- Response added with Status Code `504`

DELETE /vpn/ipsec/sessions/{ipsec-vpn-session-id}

- Response added with Status Code `504`

GET /vpn/ipsec/sessions/{ipsec-vpn-session-id}

- Response added with Status Code `504`

PUT /vpn/ipsec/sessions/{ipsec-vpn-session-id}

- Response added with Status Code `504`

GET /vpn/ipsec/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /vpn/ipsec/sessions

- Response added with Status Code `504`

POST /vpn/ipsec/sessions

- Response added with Status Code `504`

DELETE /vpn/ipsec/tunnel-profiles/{ipsec-vpn-tunnel-profile-id}

- Response added with Status Code `504`

GET /vpn/ipsec/tunnel-profiles/{ipsec-vpn-tunnel-profile-id}

- Response added with Status Code `504`

PUT /vpn/ipsec/tunnel-profiles/{ipsec-vpn-tunnel-profile-id}

- Response added with Status Code `504`

GET /vpn/ipsec/tunnel-profiles

- Response added with Status Code `504`

POST /vpn/ipsec/tunnel-profiles

- Response added with Status Code `504`

GET /vpn/l2vpn/sessions/{l2vpn-session-id}/statistics

- Response added with Status Code `504`

PUT /vpn/l2vpn/sessions/{l2vpn-session-id}?action=update_with_peer_code

- Response added with Status Code `504`

DELETE /vpn/l2vpn/sessions/{l2vpn-session-id}

- Response added with Status Code `504`

GET /vpn/l2vpn/sessions/{l2vpn-session-id}

- Response added with Status Code `504`

POST /vpn/l2vpn/sessions?action=create_with_peer_code

- Response added with Status Code `504`

GET /vpn/l2vpn/sessions

- Response added with Status Code `504`

Deprecated Operations

No changes.

Deleted Operations

VERB	PATH
GET	/node/users?internal=true

Data Structure Changes

New Structures

Structure Name
EdgeNodeServiceLoggingLevelProperties
EdgeNodeServiceReadonlyLoggingLevelProperties
HostKeyProperties
NodeFIPsModuleProperties
RetrieveMatchingHostKeyAlgorithmProperties
TunnelEncapsulation

Updated Structures

CpuStats

- New Property: `idle_pollrounds`
- New Property: `busy_pollrounds`

EdgeNodeServiceLoggingProperties

- Updated Property: `service_properties` From `` to `object`

EdgeNodeServiceLoggingReadOnlyProperties

- Updated Property: `service_properties` From `` to `object`

IPSecVPNSession

- New Property: `peer_certificate`
- New Property: `multipath`
- New Property: `encryptionless`

L2Extension

- New Property: `local_gw_mac`
- New Property: `mon`
- New Property: `filter_spcl_garp`
- New Property: `remote_gw_mac`
- New Property: `logical_switch_port_id`
- New Property: `arp_resolver_mac`
- New Property: `l2_rewrite`
- New Property: `stitch_mac`
- New Property: `gateway_ip`
- New Property: `arp_resolver`

L2VPNSession

- New Property: `encryptionless`
- New Property: `tcp_mss_clamping`
- New Property: `tcp_mss_value`
- New Property: `tunnel_encapsulation`
- New Property: `description`
- New Property: `display_name`

ListResult

- New Property: `cursor`

NodeSyslogExporterProperties

- New Property: `enabled`

PhysicalPortStats

- New Property: `rx_drop_no_match`

SshServiceProperties

- New Property: `banner`
- New Property: `host_keys`
- New Property: `protocol_version`

TransportTunnel

- New Property: `peer_id`
- New Property: `multipath`
- New Property: `connection_initiation_mode`
- New Property: `peer_certificate`
- New Property: `trust_ca_ids`
- New Property: `certificate_id`
- New Property: `local_vti_ip`
- New Property: `trust_crl_ids`
- New Property: `psk`

Deprecated Structures

No changes.

Deleted Structures

No changes.

Changelog for NSX NSX Global Policy API

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	58	948	3	0
Structures	128	61	0	2

Total changes: 1274

Operation Changes

New Operations

VERB	PATH
GET	/global-infra/categories/{category-id}/tags/{tag-id}/attachments
PATCH	/global-infra/categories/{category-id}/tags/{tag-id}/attachments
DELETE	/global-infra/categories/{category-id}/tags/{tag-id}/attachments
GET	/global-infra/domains/{domain-id}/groups/{group-id}/members/vpcs
POST	/global-infra/firewall-identity-stores-org-units
POST	/global-infra/firewall-identity-stores/{firewall-identity-store-id}
POST	/global-infra/identity-firewall-stores/action/delta-sync
POST	/global-infra/identity-firewall-stores/action/full-sync
POST	/global-infra/identity-firewall-stores/action/stop-sync
POST	/global-infra/identity-firewall-stores/ldap-servers/action/connectivity-check
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-els-server-mappings
PUT	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-els-server-mappings/{site-mapping-id}
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-els-server-mappings/{site-mapping-id}
DELETE	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-els-server-mappings/{site-mapping-id}
PATCH	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-els-server-mappings/{site-mapping-id}
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-ldap-server-mappings
DELETE	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-ldap-server-mappings/{site-mapping-id}
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-ldap-server-mappings/{site-mapping-id}

VERB	PATH
PUT	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-ldap-server-mappings/{site-mapping-id}
PATCH	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-ldap-server-mappings/{site-mapping-id}
PUT	/global-infra/settings/advanced-security-configuration
PATCH	/global-infra/settings/advanced-security-configuration
GET	/global-infra/settings/advanced-security-configuration
PATCH	/global-infra/settings/firewall/idfw/global-config-setting
PUT	/global-infra/settings/firewall/idfw/global-config-setting
GET	/global-infra/settings/firewall/idfw/global-config-setting
GET	/global-infra/settings/firewall/security/exclude-list/members-count
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}
POST	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures
POST	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures-diff
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/export
POST	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/upload-custom-signatures
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/{sig-id}
GET	/global-infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs
DELETE	/global-infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}
PATCH	/global-infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}
PUT	/global-infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}
GET	/global-infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}
GET	/global-infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}/signatures/{sig-id}
GET	/global-infra/settings/firewall/security/intrusion-services/signatures/vtis-bundle-status

VERB	PATH
GET	/global-infra/settings/security/cluster-configs/{cluster-external-id}
POST	/global-infra/settings/security/host-configuration-report
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/nat/statistics
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors/{neighbor-id}/advertised-routes
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors/{neighbor-id}/routes
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/summary
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/tunnels/statistics
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/remote-tep-connectivity/bgp/summary
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/remote-tep-connectivity/status
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}/spans
POST	/licenses/action/async-query
GET	/licenses/action/async-query/status
GET	/system-config/auto-reject-ip-options-gateway-firewall
PATCH	/system-config/auto-reject-ip-options-gateway-firewall

Updated Operations

GET /aaa/features-with-properties

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources/{ldap-identity-source-id}/search

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources/{ldap-identity-source-id}?action=probe

- Response added with Status Code `504`

DELETE /aaa/ldap-identity-sources/{ldap-identity-source-id}

- Response added with Status Code `504`

GET /aaa/ldap-identity-sources/{ldap-identity-source-id}

- Response added with Status Code `504`

PUT /aaa/ldap-identity-sources/{ldap-identity-source-id}

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources?action=fetch_certificate

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources?action=probe_identity_source

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources?action=probe_ldap_server

- Response added with Status Code `504`

GET /aaa/ldap-identity-sources

- Response added with Status Code `504`

POST /aaa/registration-token/delete

- Response added with Status Code `504`

POST /aaa/registration-token/retrieve

- Response added with Status Code `504`

DELETE /aaa/registration-token/{token}

- Response added with Status Code `504`

GET /aaa/registration-token/{token}

- Response added with Status Code `504`

POST /aaa/registration-token

- Response added with Status Code `504`

DELETE /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

GET /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

PUT /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

POST /aaa/role-bindings?action=delete_stale_bindings

- Response added with Status Code `504`

GET /aaa/role-bindings

- Response added with Status Code `504`

POST /aaa/role-bindings

- Response added with Status Code `504`

GET /aaa/roles-with-feature-permissions

- Response added with Status Code `504`

PUT /aaa/roles/{role}/role-assignment-permission-config

- Response added with Status Code `504`

POST /aaa/roles/{role}?action=clone

- Response added with Status Code `504`

DELETE /aaa/roles/{role}

- Response added with Status Code `504`

GET /aaa/roles/{role}

- Response added with Status Code `504`

PUT /aaa/roles/{role}

- Response added with Status Code `504`

POST /aaa/roles?action=validate

- Response added with Status Code `504`

GET /aaa/roles

- Response added with Status Code `504`

GET /aaa/user-info

- Response added with Status Code `504`

GET /aaa/vidm/groups

- Response added with Status Code `504`

POST /aaa/vidm/search

- Response added with Status Code `504`

GET /aaa/vidm/users

- Response added with Status Code `504`

POST /api/session/create

- Response added with Status Code `504`

POST /api/session/destroy

- Response added with Status Code `504`

POST /batch

- Response added with Status Code `504`

GET /cluster/api-service

- Response added with Status Code `504`

PUT /cluster/api-service

- Response added with Status Code `504`

GET /cluster/backups/config

- Response added with Status Code `504`

PUT /cluster/backups/config

- Response added with Status Code `504`

GET /cluster/backups/history

- Response added with Status Code `504`

GET /cluster/backups/overview

- Response added with Status Code `504`

GET /cluster/backups/status

- Response added with Status Code `504`

POST /cluster/backups?action=retrieve_ssh_fingerprint

- Response added with Status Code `504`

POST /cluster/node?action=repo_sync

- Response added with Status Code `504`

GET /cluster/nodes/deployments/{node-id}/status

- Response added with Status Code `504`

POST /cluster/nodes/deployments/{node-id}?action=delete

- Response added with Status Code `504`

GET /cluster/nodes/deployments/{node-id}

- Response added with Status Code `504`

GET /cluster/nodes/deployments

- Response added with Status Code `504`

POST /cluster/nodes/deployments

- Response added with Status Code `504`

GET /cluster/nodes/{node-id}/repo_sync/status

- Response added with Status Code `504`

POST /cluster/restore/action/retry_with_updated_config

- Response added with Status Code `504`

GET /cluster/restore/backuptimestamps

- Response added with Status Code `504`

GET /cluster/restore/instruction-resources

- Response added with Status Code `504`

POST /cluster/restore?action=advance

- Response added with Status Code `504`

POST /cluster/restore?action=cancel

- Response added with Status Code `504`

POST /cluster/restore?action=retry

- Response added with Status Code `504`

POST /cluster/restore?action=start

- Response added with Status Code `504`

POST /cluster/restore?action=suspend

- Response added with Status Code `504`

POST /cluster?action=backup_to_remote

- Response added with Status Code `504`

POST /cluster?action=summarize_inventory_to_remote

- Response added with Status Code `504`

GET /compliance/status

- Response added with Status Code `504`

GET /configs/management

- Response added with Status Code `504`

PUT /configs/management

- Response added with Status Code `504`

GET /error-resolver/{error_id}

- Response added with Status Code `504`

POST /error-resolver?action=resolve_error

- Response added with Status Code `504`

GET /error-resolver

- Response added with Status Code `504`

POST /eula/accept

- Response added with Status Code `504`

GET /eula/acceptance

- Response added with Status Code `504`

GET /eula/content

- Response added with Status Code `504`

GET /fine-tuning/resources

- Response added with Status Code `504`

DELETE /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

GET /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

PUT /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

GET /global-infra/bfd-profiles

- Response added with Status Code `504`

GET /global-infra/bms-group-associations

- Response added with Status Code `504`

GET /global-infra/bmsi-group-associations

- Response added with Status Code `504`

GET /global-infra/cabundles/{cabundle-id}/pem-file

- Response added with Status Code `504`

DELETE /global-infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

GET /global-infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

PATCH /global-infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

POST /global-infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

PUT /global-infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

GET /global-infra/cabundles

- Parameter added: `fmt`
- Response added with Status Code `504`

DELETE /global-infra/certificates/{certificate-id}

- Response added with Status Code `504`

GET /global-infra/certificates/{certificate-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

PATCH /global-infra/certificates/{certificate-id}

- Response added with Status Code `504`

PUT /global-infra/certificates/{certificate-id}

- Response added with Status Code `504`

GET /global-infra/certificates

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /global-infra/cloud-native-service-group-associations

- Response added with Status Code `504`

GET /global-infra/config

- Response added with Status Code `504`

GET /global-infra/constraint-global-config

- Response added with Status Code `504`

PATCH /global-infra/constraint-global-config

- Response added with Status Code `504`

PUT /global-infra/constraint-global-config

- Response added with Status Code `504`

GET /global-infra/constraints/{constraint-id}

- Response added with Status Code `504`

GET /global-infra/constraints

- Response added with Status Code `504`

GET /global-infra/context-profiles/attribute-types

- Response added with Status Code `504`

GET /global-infra/context-profiles/attributes

- Response added with Status Code `504`

GET /global-infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /global-infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

POST /global-infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /global-infra/context-profiles/custom-attributes

- Response added with Status Code `504`

POST /global-infra/context-profiles/custom-attributes

- Response added with Status Code `504`

DELETE /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PUT /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /global-infra/context-profiles

- Parameter added: `has_unsupported_app_ids`
- Response added with Status Code `504`

POST /global-infra/crls/{crl-id}?action=import

- Response added with Status Code `504`

POST /global-infra/crls/{crl-id}?action=upload

- Response added with Status Code `504`

DELETE /global-infra/crls/{crl-id}

- Response added with Status Code `504`

GET /global-infra/crls/{crl-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

PATCH /global-infra/crls/{crl-id}

- Response added with Status Code `504`

PUT /global-infra/crls/{crl-id}

- Response added with Status Code `504`

GET /global-infra/crls

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /global-infra/csrs/{csr-id}/pem-file

- Response added with Status Code `504`

POST /global-infra/csrs/{csr-id}?action=create

- Response added with Status Code `504`

POST /global-infra/csrs/{csr-id}?action=import

- Response added with Status Code `504`

POST /global-infra/csrs/{csr-id}?action=self_sign

- Response added with Status Code `504`

POST /global-infra/csrs/{csr-id}?action=upload

- Response added with Status Code `504`

DELETE /global-infra/csrs/{csr-id}

- Response added with Status Code `504`

GET /global-infra/csrs/{csr-id}

- Response added with Status Code `504`

POST /global-infra/csrs?action=self_sign

- Response added with Status Code `504`

GET /global-infra/csrs

- Response added with Status Code `504`

DELETE /global-infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

GET /global-infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

PATCH /global-infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

PUT /global-infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

GET /global-infra/dhcp-relay-configs

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/leases

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/state

- Response added with Status Code `504`

POST /global-infra/dhcp-server-configs/{config-id}/stats?action=reset

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/stats

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/status

- Response added with Status Code `504`

DELETE /global-infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

PATCH /global-infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

PUT /global-infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs

- Response added with Status Code `504`

DELETE /global-infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

GET /global-infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

PATCH /global-infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

PUT /global-infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

GET /global-infra/dns-forwarder-zones

- Response added with Status Code `504`

DELETE /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PUT /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/dns-security-profiles

- Response added with Status Code `504`

GET /global-infra/domains/firewall-flood-protection-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/domains/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/domain-deployment-maps

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/statistics

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/member-types

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/bms

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/bmsi

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/cloud-native-service-instances

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/dvpg

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/dvports

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/ip-addresses

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/ip-groups

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/logical-ports

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/logical-switches

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/pods

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/segment-ports

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/segments

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/vifs

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/virtual-machines

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/tags

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/statistics

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/statistics

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/statistics

- Response added with Status Code `504`

POST /global-infra/domains/{domain-id}/security-policies/{security-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies

- Response added with Status Code `504`

DELETE /global-infra/domains/{domain-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}

- Response added with Status Code `504`

PATCH /global-infra/domains/{domain-id}

- Response added with Status Code `504`

PUT /global-infra/domains/{domain-id}

- Response added with Status Code `504`

GET /global-infra/domains

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}/aggregated

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}/aggregated_with_pagination

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}/complete

- Response added with Status Code `504`

POST /global-infra/drafts/{draft-id}?action=publish

- Response added with Status Code `504`

DELETE /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

PATCH /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

PUT /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /global-infra/drafts

- Response added with Status Code `504`

PATCH /global-infra/evpn-tenant-configs/{config-id}

- Response added with Status Code `504`

PUT /global-infra/evpn-tenant-configs/{config-id}

- Response added with Status Code `504`

GET /global-infra/federation-config

- Response added with Status Code `504`

POST /global-infra/firewall-identity-store-event-log-servers/status

- Response added with Status Code `504`

POST /global-infra/firewall-identity-store-ldap-server

- Response added with Status Code `504`

GET /global-infra/firewall-identity-stores/{firewall-identity-store-id}/org-units

- Response added with Status Code `504`

GET /global-infra/firewall-identity-stores/{firewall-identity-store-id}/sync-stats

- Response added with Status Code `504`

GET /global-infra/firewall-ip-reputation-feed/download/status

- Response added with Status Code `504`

GET /global-infra/firewall-ip-reputation-feed

- Response added with Status Code `504`

POST /global-infra/firewall-ip-reputation-feed

- Response added with Status Code `504`

DELETE /global-infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

GET /global-infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

PATCH /global-infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

PUT /global-infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

GET /global-infra/firewall-schedulers

- Response added with Status Code `504`

DELETE /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PUT /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /global-infra/firewall-session-timer-profiles

- Response added with Status Code `504`

GET /global-infra/firewall/policies

- Response added with Status Code `504`

GET /global-infra/firewall/rules

- Response added with Status Code `504`

GET /global-infra/flood-protection-profiles/{flood-protection-profile-id}/bindings

- Response added with Status Code `504`

DELETE /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PUT /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /global-infra/flood-protection-profiles

- Response added with Status Code `504`

GET /global-infra/full-sync-states/{full-sync-id}

- Response added with Status Code `504`

GET /global-infra/full-sync-states

- Response added with Status Code `504`

DELETE /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/gateway-qos-profiles

- Response added with Status Code `504`

GET /global-infra/geo-ip/setting

- Response added with Status Code `504`

PATCH /global-infra/geo-ip/setting

- Response added with Status Code `504`

PUT /global-infra/geo-ip/setting

- Response added with Status Code `504`

GET /global-infra/global-manager-config?action=show-sensitive-data

- Response added with Status Code `504`

PATCH /global-infra/global-manager-config

- Response added with Status Code `504`

PUT /global-infra/global-manager-config

- Response added with Status Code `504`

DELETE /global-infra/global-managers/{global-manager-id}

- Response added with Status Code `504`

GET /global-infra/global-managers/{global-manager-id}

- Response added with Status Code `504`

PATCH /global-infra/global-managers/{global-manager-id}

- Response added with Status Code `504`

PUT /global-infra/global-managers/{global-manager-id}

- Response added with Status Code `504`

GET /global-infra/global-managers

- Response added with Status Code `504`

GET /global-infra/group-associations

- Response added with Status Code `504`

GET /global-infra/group-service-associations

- Response added with Status Code `504`

GET /global-infra/health

- Response added with Status Code `504`

DELETE /global-infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

PATCH /global-infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

PUT /global-infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

DELETE /global-infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

PATCH /global-infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

PUT /global-infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers

- Response added with Status Code `504`

DELETE /global-infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

PATCH /global-infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

PUT /global-infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores

- Response added with Status Code `504`

POST /global-infra/import-k8s-np-to-dfw

- Response added with Status Code `504`

GET /global-infra/ip-address-group-associations

- Response added with Status Code `504`

DELETE /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PUT /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/ip-discovery-profiles

- Response added with Status Code `504`

GET /global-infra/ip-reputation-exclusion-list

- Response added with Status Code `504`

DELETE /global-infra/ip-reputation-site-mappings/{mapping-id}

- Response added with Status Code `504`

GET /global-infra/ip-reputation-site-mappings/{mapping-id}

- Response added with Status Code `504`

PATCH /global-infra/ip-reputation-site-mappings/{mapping-id}

- Response added with Status Code `504`

PUT /global-infra/ip-reputation-site-mappings/{mapping-id}

- Response added with Status Code `504`

GET /global-infra/ip-reputation-site-mappings

- Response added with Status Code `504`

DELETE /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PUT /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-dad-profiles

- Response added with Status Code `504`

DELETE /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PUT /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-ndra-profiles

- Response added with Status Code `504`

GET /global-infra/labels/{label-id}

- Response added with Status Code `504`

GET /global-infra/labels

- Response added with Status Code `504`

DELETE /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PUT /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/mac-discovery-profiles

- Response added with Status Code `504`

GET /global-infra/metadata-proxies/{metadata-proxy-id}/statistics

- Response added with Status Code `504`

GET /global-infra/metadata-proxies/{metadata-proxy-id}/status

- Response added with Status Code `504`

POST /global-infra/onboarding-check-compatibility

- Response added with Status Code `504`

GET /global-infra/opstats

- Response added with Status Code `504`

GET /global-infra/overridden-resources

- Response added with Status Code `504`

GET /global-infra/performance

- Response added with Status Code `504`

GET /global-infra/pod-group-associations

- Response added with Status Code `504`

DELETE /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/qos-profiles

- Response added with Status Code `504`

GET /global-infra/realized-state/alarms

- Response added with Status Code `504`

GET /global-infra/realized-state/realized-entities

- Response added with Status Code `504`

POST /global-infra/realized-state/realized-entity?action=refresh

- Response added with Status Code `504`

GET /global-infra/realized-state/status

- Response added with Status Code `504`

GET /global-infra/security-global-config

- Response added with Status Code `504`

PUT /global-infra/security-global-config

- Response added with Status Code `504`

DELETE /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PUT /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /global-infra/segment-security-profiles

- Response added with Status Code `504`

GET /global-infra/segments/state

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-table

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/inter-site-forwarder/site-span-info

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/inter-site-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/inter-site-forwarder/status

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/tep-table

- Response added with Status Code `504`

POST /global-infra/segments/{segment-id}?action=delete_dhcp_leases

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/state

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /global-infra/segments

- Response added with Status Code `504`

DELETE /global-infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

GET /global-infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

PATCH /global-infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

PUT /global-infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

GET /global-infra/services/{service-id}/service-entries

- Response added with Status Code `504`

DELETE /global-infra/services/{service-id}

- Response added with Status Code `504`

GET /global-infra/services/{service-id}

- Response added with Status Code `504`

PATCH /global-infra/services/{service-id}

- Response added with Status Code `504`

PUT /global-infra/services/{service-id}

- Response added with Status Code `504`

GET /global-infra/services

- Response added with Status Code `504`

GET /global-infra/session-timer-profiles/{session-timer-profile-id}/bindings

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps/{cpu-mem-thresholds-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/cpu-mem-thresholds-profiles

- Response added with Status Code `504`

POST /global-infra/settings/firewall/export?action=cancel

- Response added with Status Code `504`

GET /global-infra/settings/firewall/export?action=download

- Response added with Status Code `504`

GET /global-infra/settings/firewall/export

- Response added with Status Code `504`

POST /global-infra/settings/firewall/export

- Response added with Status Code `504`

GET /global-infra/settings/firewall/gateway/dependent-services

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/group-vm-details

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/system-stats

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/user-session-data

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/vm-stats/{vm-id}

- Response added with Status Code `504`

POST /global-infra/settings/firewall/import?action=cancel

- Response added with Status Code `504`

GET /global-infra/settings/firewall/import

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/dependent-services

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/exclude-list?action=filter

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/exclude-list?system_owned=true

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/exclude-list

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/security/exclude-list

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/security/exclude-list

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/global-intrusion-services

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/security/global-intrusion-services

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/security/global-intrusion-services

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/affected-ips

- Parameter added: `context`
- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/affected-users

- Parameter added: `context`
- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/affected-vms

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/cluster-configs/{cluster-config-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/cluster-configs

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/security/intrusion-services/gsm/global-signatures/{signature-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/gsm/global-signatures/{signature-id}

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/security/intrusion-services/gsm/global-signatures/{signature-id}

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/security/intrusion-services/gsm/global-signatures/{signature-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/gsm/global-signatures

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/ids-events

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/ids-summary

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/pcaps/export

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/pcaps/{file-name}/download

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/security/intrusion-services/pcaps/{id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/pcaps

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/profiles/{profile-id}/effective-signatures

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/profiles

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}/signatures

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/signature-versions

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/signature-versions

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/signatures/airgapped-auto-update-errors

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/signatures/status

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/signatures?action=update_signatures

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/security/intrusion-services/site-version-mappings/{mapping-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/site-version-mappings/{mapping-id}

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/security/intrusion-services/site-version-mappings/{mapping-id}

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/security/intrusion-services/site-version-mappings/{mapping-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/site-version-mappings

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/site-version-mappings

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/stats?action=reset

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/security

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/security

- Response added with Status Code `504`

POST /global-infra/settings/firewall/stats?action=reset

- Response added with Status Code `504`

GET /global-infra/site-cleanup-pending

- Response added with Status Code `504`

GET /global-infra/sites/listener_certificate

- Response added with Status Code `504`

GET /global-infra/sites/settings/firewall/security

- Response added with Status Code `504`

DELETE /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

PUT /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles

- Response added with Status Code `504`

POST /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}?action=full-sync

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/allocation/status

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{edge-node-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/status

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones

- Response added with Status Code `504`

POST /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}?action=reload

- Response added with Status Code `504`

DELETE /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

PATCH /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

PUT /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/onboarding/feature-summary

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/onboarding/invalid-config-details

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/onboarding/preferences

- Response added with Status Code `504`

PUT /global-infra/sites/{site-id}/onboarding/preferences

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/onboarding/status

- Response added with Status Code `504`

POST /global-infra/sites/{site-id}/onboarding?action=check_conflict

- Response added with Status Code `504`

POST /global-infra/sites/{site-id}/onboarding?action=start_onboarding

- Response added with Status Code `504`

DELETE /global-infra/sites/{site-id}/security-setting

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/security-setting

- Response added with Status Code `504`

PATCH /global-infra/sites/{site-id}/security-setting

- Response added with Status Code `504`

PUT /global-infra/sites/{site-id}/security-setting

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/settings/firewall/security

- Response added with Status Code `504`

PATCH /global-infra/sites/{site-id}/settings/firewall/security

- Response added with Status Code `504`

PUT /global-infra/sites/{site-id}/settings/firewall/security

- Response added with Status Code `504`

DELETE /global-infra/sites/{site-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}

- Response added with Status Code `504`

PATCH /global-infra/sites/{site-id}

- Response added with Status Code `504`

PUT /global-infra/sites/{site-id}

- Response added with Status Code `504`

GET /global-infra/sites

- Response added with Status Code `504`

GET /global-infra/span

- Response added with Status Code `504`

DELETE /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PUT /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /global-infra/spoofguard-profiles

- Response added with Status Code `504`

GET /global-infra/tags/effective-resources

- Response added with Status Code `504`

GET /global-infra/tags/tag-operations/{operation-id}/status

- Response added with Status Code `504`

GET /global-infra/tags/tag-operations/{operation-id}

- Response added with Status Code `504`

PUT /global-infra/tags/tag-operations/{operation-id}

- Response added with Status Code `504`

GET /global-infra/tags

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/arp-proxies?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/arp-proxies

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/community-lists

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/nslookup

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/status

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

POST /global-infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/forwarding-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/forwarding-table

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/gateway-firewall

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/inter-vrf-routing/{inter-vrf-routing-id}/advertised-networks

- Response added with Status Code `504`

POST /global-infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/arp-proxies

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/status

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/advertised-routes?format=csv

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/advertised-routes

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/routes?format=csv

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/routes

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{interface-group-id}/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/dad-state

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/gateway-firewall

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/number-of-routes

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/prefix-lists

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/route-maps

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/routing-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/routing-table

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/state

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

POST /global-infra/tier-0s?action=site_failover

- Response added with Status Code `504`

GET /global-infra/tier-0s

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/advertised-networks/csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/advertised-networks

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/arp-proxies?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/arp-proxies

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/nslookup

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/status

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

POST /global-infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/forwarding-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/forwarding-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/gateway-firewall

- Response added with Status Code `504`

POST /global-infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/arp-proxies

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{interface-group-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/dad-state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/gateway-firewall

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/inter-site-forwarder/status

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/bep-statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/bep-status

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/inter-site-forwarder/site-span-info

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/inter-site-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/inter-site-forwarder/status

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}?force=true

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/state

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/static-routes

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

POST /global-infra/tier-1s/{tier1-id}/segments/{segment-id}?action=delete_dhcp_leases

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s

- Response added with Status Code `504`

GET /global-infra/traceflows/{traceflow-id}/observations

- Response added with Status Code `504`

GET /global-infra/traceflows/{traceflow-id}/status

- Response added with Status Code `504`

DELETE /global-infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /global-infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

PATCH /global-infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

POST /global-infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

PUT /global-infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /global-infra/traceflows

- Response added with Status Code `504`

GET /global-infra/transport-zone-profiles/{tz-profile-id}

- Response added with Status Code `504`

GET /global-infra/transport-zone-profiles

- Response added with Status Code `504`

GET /global-infra/upgrade-summary

- Response added with Status Code `504`

GET /global-infra/virtual-machine-group-associations

- Response added with Status Code `504`

GET /global-infra/virtual-network-interface-group-associations

- Response added with Status Code `504`

DELETE /global-infra/vm-tag-replication-policies/{id}

- Response added with Status Code `504`

GET /global-infra/vm-tag-replication-policies/{id}

- Response added with Status Code `504`

PATCH /global-infra/vm-tag-replication-policies/{id}

- Response added with Status Code `504`

PUT /global-infra/vm-tag-replication-policies/{id}

- Response added with Status Code `504`

GET /global-infra/vm-tag-replication-policies

- Response added with Status Code `504`

GET /global-infra

- Response added with Status Code `504`

PATCH /global-infra

- Response added with Status Code `504`

PUT /global-infra

- Response added with Status Code `504`

GET /gm-operational-state

- Response added with Status Code `504`

GET /licenses/security-usage?format=csv

- Response added with Status Code `504`

GET /licenses/security-usage

- Response added with Status Code `504`

POST /licenses/vcf-licenses

- Response added with Status Code `504`

GET /licenses/vcf/action/async/status

- Response added with Status Code `504`

POST /licenses/vcf/action/async

- Parameter added: `only_sync_unlicensed_vc`
- Response added with Status Code `504`

POST /licenses/vcf/action/sync

- Response added with Status Code `504`

GET /malware-prevention/compute-collection/{compute-collection-id}/status

- Response added with Status Code `504`

POST /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment/action/change-appliance

- Response added with Status Code `504`

DELETE /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

GET /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

POST /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

GET /malware-prevention/ovf-spec

- Response added with Status Code `504`

GET /malware-prevention/teaser/regions

- Response added with Status Code `504`

POST /malware-prevention/teaser/registration_url

- Response added with Status Code `504`

GET /malware-prevention/teaser/status

- Response added with Status Code `504`

GET /malware-prevention/transport-node/{transport-node-id}/status

- Response added with Status Code `504`

GET /management-plane-health

- Response added with Status Code `504`

GET /observability/flow-details

- Response added with Status Code `504`

GET /search/dsl

- Response added with Status Code `504`

GET /search/query

- Response added with Status Code `504`

POST /security/sensor-registration-token

- Response added with Status Code `504`

GET /system-config/auto-enable-gateway-firewall

- Response added with Status Code `504`

PATCH /system-config/auto-enable-gateway-firewall

- Response added with Status Code `504`

GET /system-config/nsx-partial-patch-config

- Response added with Status Code `504`

PATCH /system-config/nsx-partial-patch-config

- Response added with Status Code `504`

DELETE /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

PUT /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}/widgetconfigurations

- Response added with Status Code `504`

POST /ui-views/{view-id}/widgetconfigurations

- Response added with Status Code `504`

DELETE /ui-views/{view-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}

- Response added with Status Code `504`

PUT /ui-views/{view-id}

- Response added with Status Code `504`

GET /ui-views

- Response added with Status Code `504`

POST /ui-views

- Response added with Status Code `504`

GET /upgrade/version-whitelist/{component_type}

- Response added with Status Code `504`

PUT /upgrade/version-whitelist/{component_type}

- Response added with Status Code `504`

GET /upgrade/version-whitelist

- Response added with Status Code `504`

DELETE /watermark

- Response added with Status Code `504`

GET /watermark

- Response added with Status Code `504`

POST /watermark

- Response added with Status Code `504`

PUT /watermark

- Response added with Status Code `504`

Deprecated Operations

VERB	PATH
POST	/global-infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers/{ldap-server-id}
GET	/global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/inter-site/bgp-summary
GET	/global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/inter-site/status

Deleted Operations

No changes.

Data Structure Changes

New Structures

Structure Name
AffectedProductDetail
AtpSecurityConfig
AtpSettings
AutoRejectIPOptionsGatewayFirewallConfig
BaseSpan
BfdConfigParameters
BgpNeighbor
BgpNeighborAddressFamily
BgpNeighborRouteDetails
BgpTroubleshootConfig
BridgeConnection
CentralizedConfig
ChildBridgeConnection
ChildCentralizedConfig
ChildClusterSecurityConfiguration
ChildConnectivityPolicy
ChildDistributedVxlanConnection
ChildDynamicIpAddressReservation
ChildNetworkSpan
ChildPolicyBaseHostSwitchProfile
ChildRouteAdvertisement

Structure Name
ChildRouteController
ChildRouteControllerBgpNeighborConfig
ChildRouteControllerBgpRoutingConfig
ChildRouteControllerBgpTroubleshootConfig
ChildRouteControllerInterface
ChildSecurityPolicyContainerCluster
ChildSecurityProfileAttachment
ChildSecurityStrategy
ChildSiteToElsServerMapping
ChildSiteToLdapServerMapping
ChildTransitGatewaySecurityFeatures
ChildTransportNodeMonitoringProfileBindingMap
ChildVirtualNetworkApplianceCluster
ClusterBasedSpan
ClusterInfo
ClusterSecurityConfiguration
ClusterSecurityFeature
ClusterStatusErrorDetails
ConnectivityPolicy
CustomSignatureModification
CustomSignatureValidationPayload
DistributedVxlanConnection
DynamicIpAddressReservation
EastWestFirewall
FirewallExcludeListMembersCount
FirewallExcludeListMembersCountListResult
GatewayFailoverRequestParameters
GlobalIdentityFirewallConfiguration
GmImportSpec
GmImportStatus
HostConfigCsvRecord
HostConfigReportInCsv
HostConfigReportRequest
IdentityFirewallStoreSyncObject
IdentityFirewallStoreSyncRequest
IdsCustomSignature
IdsCustomSignatureListResult
IdsCustomSignatureVersion
IdsCustomSignatureVersionListResult
IdsCustomSignaturesDiff

Structure Name
IdsIncludedSignature
IdsRawSignatures
IdsThresholdConfigListResult
IdsValidationError
NatCounters
NatStatisticsPerPolicyEdgeNode
NatStatisticsPerTransportNode
NetworkSpan
NodeInterSiteStatistics
OverriddenSignature
PeerNodeStatus
PolicyBaseHostSwitchProfile
PolicyEdgeClusterMemberInterSiteBgpSummary
PolicyEdgeClusterMemberRemoteTunnelConnectivityStatus
PolicyEdgeClusterRemoteTunnelBgpSummary
PolicyEdgeClusterRemoteTunnelConnectivityStatus
PolicyEdgeNodeBgpNeighborAdvertisedRoutes
PolicyEdgeNodeBgpNeighborRouteDetailList
PolicyEdgeNodeBgpNeighborsListResult
PolicyEdgeNodeRemoteTepStatistics
PolicyIdsEventInnerFlowData
PolicyTraceflowConnectivityPolicyInfo
PolicyTraceflowObservationForwarded
PolicyTraceflowObservationReceived
ProviderAdvertiseOutBoundNetworks
ProviderNatConfig
RemoteTunnelStatistics
RemoteTunnelStatisticsPerSite
RouteAdvertisement
RouteController
RouteControllerBgpNeighborConfig
RouteControllerBgpRoutingConfig
RouteControllerInterface
RouteControllerInterfaceAddress
RuleTemplate
SecurityPolicyContainerCluster
SecurityProfileAttachment
SecurityStrategy
ServiceGatewayCounterPolicyStats
SiteToElsServerMapping

Structure Name
SiteToElsServerMappingListResult
SiteToLdapServerMapping
SiteToLdapServerMappingListResult
SpanListForTz
SpanReference
TagAttachment
TagAttachmentResponse
TestIdentityFirewallStoreLdapServerConnectivityRequest
ThirdPartyIPAMInfo
Tier0TGWAttachmentInterfaceState
TraceflowVlanExtensionBasicInfo
TraceflowVlanExtensionResultInfo
TransitGatewayAttachmentInterfaceState
TransitGatewayAttachmentInterfaceStateListResult
TransitGatewayRouteAdvertisementRule
TransitGatewaySecurityFeature
TransitGatewaySecurityFeatures
TransportNodeMonitoringProfileBindingMap
ValidationNote
VirtualNetworkApplianceCluster
VirtualNetworkApplianceClusterAdvancedConfiguration
VirtualNetworkApplianceClusterMember
VlanAvailability
VodapGlobalCollector
VpcDeploymentScope
VtisBundleInfo
ZoneBasedSpan

Updated Structures

BgpNeighborConfig

- Updated Property: `neighbor_address` From `ip` to `address-or-cidr-block`

BgpNeighborRouteDetailsCsvRecord

- New Property: `rd`
- New Property: `esi`
- New Property: `rmac_len`
- New Property: `rmac`
- New Property: `evpn_route_type`
- New Property: `eth_tag`

DataCounter

- New Property: `unknown_unicast`

DfwFirewallConfiguration

- New Property: `enforce_duplicate_sequence_number_check`

DirectoryLdapServer

- New Property: `path`

DistributedVlanConnection

- New Property: `associated_ip_block_paths`
- New Property: `restricted_availability`
- New Property: `subnet_extension_connection`

FileTransferProtocol

- New Property: `host_key_algorithm`

GatewayConnection

- New Property: `inbound_remote_networks`
- New Property: `nat_config`
- New Property: `advertise_outbound_networks`

GlobalCollectorConfig

- New Property: `collector_fqdn`

GlobalConfig

- New Property: `tgw_transit_subnet_prefix_length`
- New Property: `tgw_transit_subnet_blocks`

GlobalIdsSettings

- New Property: `enable_custom_signatures`

IdentityFirewallAdStore

- New Property: `event_log_scraper_enabled`

IdsGlobalEventConfig

- New Property: `enable_test_signatures`

IdsProfile

- New Property: `included_signatures`

IdsSignature

- New Property: `affected_products`

IdsSignatureStatus

- New Property: `is_user_uploaded`

IdsSignatureVersion

- New Property: `version_name`

IdsSiteVersionMapping

- New Property: `custom_signature_version_paths`

InfraSecurityConfig

- New Property: `ndcpp_enabled`

InterSitePortCounters

- New Property: `policy_dropped_packets`

IpAddressBlock

- New Property: `excluded_ips`

- New Property: `used_size`
- New Property: `cidrs`
- New Property: `total_size`
- New Property: `third_party_ipam`
- New Property: `usage_percentage`
- New Property: `subnet_exclusive`
- New Property: `ranges`

IpAddressPoolBlockSubnet

- New Property: `allocated_cidr`

LogicalRouterPortCounters

- New Property: `policy_dropped_packets`

NsxTDnsAnswer

- New Property: `answers`

NsxTDnsQueryAnswer

- New Property: `raw_string`

OpsGlobalConfig

- New Property: `vna_dscp_value`

PolicyAlarmResource

- New Property: `intent_paths`
- New Property: `severity`

PolicyBgpNeighborStatus

- New Property: `remote_site_path`
- New Property: `is_dynamic`
- New Property: `neighbor_path`

PolicyEdgeClusterMemberStatus

- New Property: `management_ips`
- New Property: `storage_state`
- New Property: `display_name`
- New Property: `failure_reason`
- New Property: `read_latency`
- New Property: `write_latency`
- New Property: `peer_node_status`
- New Property: `vtep_state`

PolicyEdgeClusterStatus

- New Property: `error_details`

PolicyIdsEventFlowData

- New Property: `flow_destination_ip`
- New Property: `target_vm_uuid`
- New Property: `attacker_vm_uuid`
- New Property: `flow_dest_vm_uuid`
- New Property: `target`
- New Property: `attacker`
- New Property: `flow_source_ip`
- New Property: `flow_source_vm_uuid`

- New Property: `flow_source_port`
- New Property: `inner_flow_details`
- New Property: `flow_destination_port`

PolicyTraceflowObservationDroppedLogical

- New Property: `dst_connectivity_policy`
- New Property: `src_connectivity_policy`
- New Property: `next_vpc_path`

PolicyTraceflowObservationForwardedLogical

- New Property: `dst_connectivity_policy`
- New Property: `src_connectivity_policy`

PolicyTransportZone

- New Property: `transport_zone_type`
- Deleted Property: `forwarding_mode`

PortMirroringProfile

- New Property: `preserve_original_vlan`
- New Property: `source_vlan_ids`
- New Property: `destination_pnics`
- New Property: `encapsulation_vlan_id`

Project

- New Property: `vpc_deployment_scope`
- New Property: `id_suffix`

RouteDetails

- New Property: `eth_tag`
- New Property: `rd`
- New Property: `evpn_route_type`
- New Property: `rmac`
- New Property: `rmac_len`
- New Property: `esi`

SharedResource

- New Property: `with_permission`

Tier0

- New Property: `tgw_transit_subnets`

Tier0GatewayState

- New Property: `tgw_attached_interfaces`

TraceflowObservationDelivered

- New Property: `uplink_name`

TraceflowObservationDropped

- New Property: `src_connectivity_policy_internal_id`
- New Property: `dst_connectivity_policy_internal_id`

TraceflowObservationDroppedLogical

- New Property: `next_vpc_id`

TraceflowObservationForwarded

- New Property: `lport_id`
- New Property: `lport_name`

TraceflowObservationForwardedLogical

- New Property: `dst_connectivity_policy_internal_id`
- New Property: `vlan_extension_result_info`
- New Property: `src_connectivity_policy_internal_id`
- New Property: `lr_forward_type`

TraceflowObservationReceived

- New Property: `lport_id`
- New Property: `lport_name`

TraceflowObservationReceivedLogical

- New Property: `vlan_extension_basic_info`

TransitGateway

- New Property: `span`
- New Property: `external_ip_signaling_mode`

TransitGatewayAttachment

- New Property: `route_advertisement_rules`
- New Property: `urpf_mode`

TransitGatewayAttachmentStatistics

- New Property: `last_update_timestamp`

TransitGatewayNatRule

- New Property: `scope`

TransitGatewayState

- New Property: `network_stack`

VpcAttachment

- New Property: `preferred_default_snat_ip`

VpcNatConfig

- New Property: `auto_snat_ip_block`

VpcSecurityProfile

- New Property: `east_west_firewall`

VpcServiceProfile

- New Property: `service_subnet_cidrs`

VpcSubnet

- New Property: `vlan_connection`

VpcTransitGatewayStatusResult

- New Property: `span`

VrniGlobalCollector

- New Property: `collector_fqdn`

VrniStreamingGlobalCollector

- New Property: `collector_fqdn`

WaveFrontGlobalCollector

- New Property: `collector_fqdn`

Deprecated Structures

No changes.

Deleted Structures

Structure Name
ChildVpcSubnetBridgeProfile
VpcSubnetBridgeProfile

Changelog for NSX NSX Manager API
These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	31	1388	11	17
Structures	32	53	0	2

Total changes: 1606

Operation Changes

New Operations

VERB	PATH
POST	/administration/network-diagnosis/host-resolution-test
POST	/administration/network-diagnosis/ping-reachability-test
POST	/cluster/{cluster-node-id}/node/file-store?action=retrieve_matching_host_key_algorithm
GET	/cluster/{cluster-node-id}/node/fips/modules
GET	/cluster/{cluster-node-id}/node/fips/modules?component_name=nsx-edge
GET	/cluster/{cluster-node-id}/node/fips/modules?component_name=nsx-global-manager
GET	/cluster/{cluster-node-id}/node/fips/modules?component_name=nsx-manager
DELETE	/cluster/{cluster-node-id}/node/services/ssh?action=clear_banner
POST	/cluster/{cluster-node-id}/node/services/syslog/exporters?action=delete_all_non_vcf_ops_managed_exporters
GET	/fabric/zones
GET	/fabric/zones/{zone-ext-id}
POST	/licenses/action/async-query
GET	/licenses/action/async-query/status

VERB	PATH
GET	/licenses/license/action/query-token
POST	/node/file-store?action=retrieve_matching_host_key_algorithm
GET	/node/fips/modules
GET	/node/fips/modules?component_name=nsx-edge
GET	/node/fips/modules?component_name=nsx-global-manager
GET	/node/fips/modules?component_name=nsx-manager
DELETE	/node/services/ssh?action=clear_banner
POST	/node/services/syslog/exporters?action=delete_all_non_vcf_ops_managed_exporters
GET	/systemhealth-extended/virtual-network-appliance-cluster
GET	/systemhealth-extended/virtual-network-appliance-nodes
POST	/transport-nodes/{transport-node-id}/node/file-store?action=retrieve_matching_host_key_algorithm
GET	/transport-nodes/{transport-node-id}/node/fips/modules
GET	/transport-nodes/{transport-node-id}/node/fips/modules?component_name=nsx-edge
GET	/transport-nodes/{transport-node-id}/node/fips/modules?component_name=nsx-global-manager
GET	/transport-nodes/{transport-node-id}/node/fips/modules?component_name=nsx-manager
DELETE	/transport-nodes/{transport-node-id}/node/services/ssh?action=clear_banner
POST	/transport-nodes/{transport-node-id}/node/services/syslog/exporters?action=delete_all_non_vcf_ops_managed_exporters
POST	/upgrade/pre-upgrade-checks/edge/planned-maintenance

Updated Operations

GET /aaa/features-with-properties

- Response added with Status Code `504`

POST /aaa/registration-token/delete

- Response added with Status Code `504`

POST /aaa/registration-token/retrieve

- Response added with Status Code `504`

DELETE /aaa/registration-token/{token}

- Response added with Status Code `504`

GET /aaa/registration-token/{token}

- Response added with Status Code `504`

POST /aaa/registration-token

- Response added with Status Code `504`

DELETE /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

GET /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

PUT /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

POST /aaa/role-bindings?action=delete_stale_bindings

- Response added with Status Code `504`

GET /aaa/role-bindings

- Response added with Status Code `504`

POST /aaa/role-bindings

- Response added with Status Code `504`

GET /aaa/roles-with-feature-permissions

- Response added with Status Code `504`

PUT /aaa/roles/{role}/role-assignment-permission-config

- Response added with Status Code `504`

POST /aaa/roles/{role}?action=clone

- Response added with Status Code `504`

DELETE /aaa/roles/{role}

- Response added with Status Code `504`

GET /aaa/roles/{role}

- Response added with Status Code `504`

PUT /aaa/roles/{role}

- Response added with Status Code `504`

POST /aaa/roles?action=validate

- Response added with Status Code `504`

GET /aaa/roles

- Response added with Status Code `504`

GET /aaa/user-info

- Response added with Status Code `504`

GET /aaa/vidm/groups

- Response added with Status Code `504`

POST /aaa/vidm/search

- Response added with Status Code `504`

GET /aaa/vidm/users

- Response added with Status Code `504`

POST /administration/audit-logs

- Response added with Status Code `504`

GET /administration/support-bundles/config

- Response added with Status Code `504`

PUT /administration/support-bundles/config

- Response added with Status Code `504`

GET /administration/support-bundles/dynamic-content-filters

- Response added with Status Code `504`

POST /administration/support-bundles?action=collect

- Response added with Status Code `504`

POST /administration/support-bundles?action=delete_async_response

- Response added with Status Code `504`

POST /alarms/{alarm-id}?action=set_status

- Response added with Status Code `504`

GET /alarms/{alarm-id}

- Response added with Status Code `504`

POST /alarms?action=set_status

- Response added with Status Code `504`

GET /alarms

- Response added with Status Code `504`

POST /api/session/create

- Response added with Status Code `504`

POST /api/session/destroy

- Response added with Status Code `504`

GET /automatic-health-check-toggle

- Response added with Status Code `504`

PUT /automatic-health-check-toggle

- Response added with Status Code `504`

GET /automatic-health-checks/transport-zones/{transport-zone-id}

- Response added with Status Code `504`

GET /automatic-health-checks

- Response added with Status Code `504`

POST /batch

- Response added with Status Code `504`

GET /capacity/threshold

- Response added with Status Code `504`

PUT /capacity/threshold

- Response added with Status Code `504`

GET /capacity/usage

- Response added with Status Code `504`

GET /certificate-management/certificate-bundle

- Response added with Status Code `504`

DELETE /cluster-profiles/{cluster-profile-id}

- Response added with Status Code `504`

GET /cluster-profiles/{cluster-profile-id}

- Response added with Status Code `504`

PUT /cluster-profiles/{cluster-profile-id}

- Response added with Status Code `504`

GET /cluster-profiles

- Response added with Status Code `504`

POST /cluster-profiles

- Response added with Status Code `504`

POST /cluster/api-certificate?action=clear_cluster_certificate

- Response added with Status Code `504`

POST /cluster/api-certificate?action=set_cluster_certificate

- Response added with Status Code `504`

GET /cluster/api-certificate

- Response added with Status Code `504`

GET /cluster/api-service

- Response added with Status Code `504`

PUT /cluster/api-service

- Response added with Status Code `504`

POST /cluster/api-virtual-ip?action=clear_virtual_ip6

- Response added with Status Code `504`

POST /cluster/api-virtual-ip?action=clear_virtual_ip

- Response added with Status Code `504`

POST /cluster/api-virtual-ip?action=set_virtual_ip

- Response added with Status Code `504`

GET /cluster/api-virtual-ip

- Response added with Status Code `504`

GET /cluster/backups/config

- Response added with Status Code `504`

PUT /cluster/backups/config

- Response added with Status Code `504`

GET /cluster/backups/history

- Response added with Status Code `504`

GET /cluster/backups/overview

- Response added with Status Code `504`

GET /cluster/backups/status

- Response added with Status Code `504`

GET /cluster/backups/ui_frames

- Response added with Status Code `504`

POST /cluster/backups?action=retrieve_ssh_fingerprint

- Response added with Status Code `504`

POST /cluster/node?action=repo_sync

- Response added with Status Code `504`

GET /cluster/nodes/deployments/{node-id}/status

- Response added with Status Code `504`

POST /cluster/nodes/deployments/{node-id}?action=delete

- Response added with Status Code `504`

GET /cluster/nodes/deployments/{node-id}

- Response added with Status Code `504`

GET /cluster/nodes/deployments

- Response added with Status Code `504`

POST /cluster/nodes/deployments

- Response added with Status Code `504`

GET /cluster/nodes/status

- Response added with Status Code `504`

GET /cluster/nodes/{node-id}/network/interfaces/{interface-id}/stats

- Response added with Status Code `504`

GET /cluster/nodes/{node-id}/network/interfaces/{interface-id}

- Response added with Status Code `504`

GET /cluster/nodes/{node-id}/network/interfaces

- Response added with Status Code `504`

GET /cluster/nodes/{node-id}/repo_sync/status

- Response added with Status Code `504`

GET /cluster/nodes/{node-id}/status

- Response added with Status Code `504`

DELETE /cluster/nodes/{node-id}

- Response added with Status Code `504`

GET /cluster/nodes/{node-id}

- Response added with Status Code `504`

GET /cluster/nodes

- Response added with Status Code `504`

POST /cluster/nodes

- Response added with Status Code `504`

POST /cluster/restore/action/retry_with_updated_config

- Response added with Status Code `504`

GET /cluster/restore/backuptimestamps

- Response added with Status Code `504`

GET /cluster/restore/config

- Response added with Status Code `504`

PUT /cluster/restore/config

- Response added with Status Code `504`

GET /cluster/restore/instruction-resources

- Response added with Status Code `504`

GET /cluster/restore/status

- Response added with Status Code `504`

POST /cluster/restore?action=advance

- Response added with Status Code `504`

POST /cluster/restore?action=cancel

- Response added with Status Code `504`

POST /cluster/restore?action=retry

- Response added with Status Code `504`

POST /cluster/restore?action=start

- Response added with Status Code `504`

POST /cluster/restore?action=suspend

- Response added with Status Code `504`

GET /cluster/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/aaa/auth-policy?action=reset-all

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/aaa/auth-policy?action=reset-auth-policies

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/aaa/auth-policy?action=reset-pwd-complexity

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/aaa/auth-policy

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/aaa/auth-policy

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/aaa/providers/vidm/status

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/aaa/providers/vidm

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/aaa/providers/vidm

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/central-config

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/central-config

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/core-dumps/{file-name}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/core-dumps

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/file-store/{file-name}/thumbprint

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/file-store/{file-name}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/file-store/{file-name}

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/file-store/{file-name}

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/file-store?action=retrieve_ssh_fingerprint

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/file-store

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/grub/{grub-username}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/grub

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/grub

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/hardening-policy/mandatory-access-control/report

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/intelligence/form-factors

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/logs/{log-name}/data

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/logs/{log-name}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/logs

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/management-plane

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/management-plane

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/management-plane

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/mode

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/motd

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/mpa-config

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/mpa-config

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/mpa-config

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/network/interfaces/link-local

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/interfaces/link-local

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/network/interfaces/link-local

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/interfaces/{interface-id}/stats

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/network/interfaces/{interface-id}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/interfaces

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/name-servers

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/network/name-servers

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/network/routes/{route-id}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/routes/{route-id}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/routes

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/network/routes

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network/search-domains

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/network/search-domains

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/network

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/processes/{process-id}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/processes

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/applianceproxy/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/applianceproxy?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/applianceproxy?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/applianceproxy?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/applianceproxy

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/async_replicator/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/async_replicator?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/async_replicator?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/async_replicator?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/async_replicator

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/async_replicator

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/auth/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/auth?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/auth?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/auth?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/auth

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/auth

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/cluster_manager/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/cluster_manager?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/cluster_manager?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/cluster_manager?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/cluster_manager

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/cm-inventory/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/cm-inventory?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/cm-inventory?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/cm-inventory?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/cm-inventory

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/controller/controller-certificate

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/controller/profiler

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/controller/profiler

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/controller/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/controller?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/controller?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/controller?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/controller

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore/corfu_cert_expiry_check?action=disable

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore/corfu_cert_expiry_check?action=enable

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/datastore/corfu_cert_expiry_check

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/datastore/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/datastore

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/datastore_nonconfig/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore_nonconfig?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore_nonconfig?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/datastore_nonconfig?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/datastore_nonconfig

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/http/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/http?action=apply_certificate

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/http?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/http?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/http?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/http

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/http

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/idps-reporting/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/idps-reporting?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/idps-reporting?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/idps-reporting?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/idps-reporting

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/install-upgrade/status

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/install-upgrade/uc-state

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/install-upgrade?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/install-upgrade?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/install-upgrade?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/install-upgrade

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/install-upgrade

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/liagent/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/liagent?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/liagent?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/liagent?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/liagent

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/manager/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/manager?action=reset-manager-logging-levels

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/manager?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/manager?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/manager?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/manager

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/manager

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/messaging-manager/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/messaging-manager?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/messaging-manager?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/messaging-manager?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/messaging-manager

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/migration-coordinator/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/migration-coordinator?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/migration-coordinator?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/migration-coordinator?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/migration-coordinator

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/monitoring/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/monitoring?action=reset-monitoring-logging-levels

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/monitoring?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/monitoring?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/monitoring?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/monitoring

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/monitoring

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/node-mgmt/loglevel

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/node-mgmt/loglevel

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/node-mgmt/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/node-mgmt?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/node-mgmt

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/node-stats/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/node-stats?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/node-stats?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/node-stats?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/node-stats

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/nsx-message-bus/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-message-bus?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-message-bus?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-message-bus?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/nsx-message-bus

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/nsx-platform-client/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-platform-client?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-platform-client?action=start

- Parameter added: `force`
- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-platform-client?action=stop

- Parameter added: `force`
- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/nsx-platform-client

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/nsx-upgrade-agent/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-upgrade-agent?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-upgrade-agent?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/nsx-upgrade-agent?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/nsx-upgrade-agent

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/ntp/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ntp?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ntp?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ntp?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/ntp

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/ntp

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/policy/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/policy?action=reset-manager-logging-levels

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/policy?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/policy?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/policy?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/policy

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/policy

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/search/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/search?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/search?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/search?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/search

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/sha/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/sha?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/sha?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/sha?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/sha

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/site_manager/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/site_manager?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/site_manager?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/site_manager?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/site_manager

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/snmp/status

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/snmp/v3-engine-id

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/snmp/v3-engine-id

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/snmp?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/snmp?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/snmp?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/snmp

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/snmp

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ssh/notify_mpa?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ssh/notify_mpa?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ssh/notify_mpa?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/ssh/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ssh?action=remove_host_fingerprint

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ssh?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ssh?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ssh?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/ssh

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/ssh

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `504`
- Response added with Status Code `409`

GET /cluster/{cluster-node-id}/node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/syslog/exporters?action=verify

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/services/syslog/exporters

- Response added with Status Code `504`
- Response added with Status Code `409`

GET /cluster/{cluster-node-id}/node/services/syslog/exporters

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/syslog/exporters

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/syslog/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/syslog?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/syslog?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/syslog?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/syslog

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/telemetry/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/telemetry?action=reset-telemetry-logging-levels

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/telemetry?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/telemetry?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/telemetry?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/telemetry

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/services/telemetry

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/ui-service/status

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ui-service?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ui-service?action=start

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/services/ui-service?action=stop

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services/ui-service

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/services

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/status?action=clear_bootup_error

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/status

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/tasks/{task-id}/response

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/tasks/{task-id}?action=cancel

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/tasks/{task-id}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/tasks/{task-id}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/tasks

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/upgrade/performtask

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/upgrade/progress-status

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/upgrade/status-summary

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/upgrade/uc

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/upgrade

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users/{userid}/ssh-keys?action=add_ssh_key

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users/{userid}/ssh-keys?action=remove_ssh_key

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/users/{userid}/ssh-keys

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users/{userid}?action=activate

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users/{userid}?action=deactivate

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users/{userid}?action=reset_password

- Response added with Status Code `504`

DELETE /cluster/{cluster-node-id}/node/users/{userid}

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/users/{userid}

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node/users/{userid}

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users?action=create_audit_user

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users?action=create_service_user

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users?action=create_user

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node/users?action=reset_own_password

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/users

- Property changed `operationId` from `ClusterClusterNodeIdNodeListNodeUsersTrue` to `ClusterClusterNodeIdNodeListNodeUsers`
- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node/version

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node?action=restart

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node?action=set_coredump_config

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node?action=set_system_time

- Response added with Status Code `504`

POST /cluster/{cluster-node-id}/node?action=shutdown

- Response added with Status Code `504`

GET /cluster/{cluster-node-id}/node

- Response added with Status Code `504`

PUT /cluster/{cluster-node-id}/node

- Response added with Status Code `504`

POST /cluster/{node-id}?action=remove_node

- Response added with Status Code `504`

GET /cluster/{node-id}

- Response added with Status Code `504`

POST /cluster?action=backup_to_remote

- Response added with Status Code `504`

POST /cluster?action=join_cluster

- Response added with Status Code `504`

POST /cluster?action=summarize_inventory_to_remote

- Response added with Status Code `504`

GET /cluster

- Response added with Status Code `504`

GET /configs/central-config/logging-servers

- Response added with Status Code `504`

PUT /configs/central-config/node-config-profiles/{node-config-profile-id}

- Response added with Status Code `504`

GET /configs/central-config/node-config-profiles/{profile-id}

- Response added with Status Code `504`

GET /configs/central-config/node-config-profiles

- Response added with Status Code `504`

GET /configs/inventory

- Response added with Status Code `504`

GET /configs/management

- Response added with Status Code `504`

PUT /configs/management

- Response added with Status Code `504`

POST /configs/node/mode

- Response added with Status Code `504`

GET /edge-clusters/{edge-cluster-id}/allocation-status

- Response added with Status Code `504`

GET /edge-clusters/{edge-cluster-id}/inter-site/status

- Response added with Status Code `504`

GET /edge-clusters/{edge-cluster-id}/state

- Response added with Status Code `504`

GET /edge-clusters/{edge-cluster-id}/status

- Response added with Status Code `504`

POST /edge-clusters/{edge-cluster-id}?action=relocate_and_remove

- Response added with Status Code `504`

POST /edge-clusters/{edge-cluster-id}?action=replace_transport_node

- Response added with Status Code `504`

DELETE /edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

GET /edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

PUT /edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

GET /edge-clusters

- Parameter added: `include_vna_clusters`
- Response added with Status Code `504`

POST /edge-clusters

- Response added with Status Code `504`

GET /error-resolver/{error_id}

- Response added with Status Code `504`

POST /error-resolver?action=resolve_error

- Response added with Status Code `504`

GET /error-resolver

- Response added with Status Code `504`

POST /eula/accept

- Response added with Status Code `504`

GET /eula/acceptance

- Response added with Status Code `504`

GET /eula/content

- Response added with Status Code `504`

POST /events/{event-id}?action=set_default

- Response added with Status Code `504`

GET /events/{event-id}

- Response added with Status Code `504`

PUT /events/{event-id}

- Response added with Status Code `504`

GET /events

- Response added with Status Code `504`

GET /fabric/baremetal-server-interfaces

- Response added with Status Code `504`

GET /fabric/baremetal-servers

- Response added with Status Code `504`

GET /fabric/cloud-native-service-instances/{external-id}

- Response added with Status Code `504`

GET /fabric/cloud-native-service-instances

- Response added with Status Code `504`

GET /fabric/compute-collections/{cc-ext-id}/member-status

- Response added with Status Code `504`

GET /fabric/compute-collections/{cc-ext-id}/network/physical-interfaces

- Response added with Status Code `504`

GET /fabric/compute-collections/{cc-ext-id}

- Response added with Status Code `504`

POST /fabric/compute-collections/{cc-ext-id}

- Response added with Status Code `504`

GET /fabric/compute-collections

- Parameter added: `datacenter_external_id`
- Response added with Status Code `504`

GET /fabric/compute-managers/thumbprint-hashing-algorithm

- Response added with Status Code `504`

PUT /fabric/compute-managers/thumbprint-hashing-algorithm

- Response added with Status Code `504`

GET /fabric/compute-managers/{compute-manager-id}/state

- Response added with Status Code `504`

GET /fabric/compute-managers/{compute-manager-id}/status

- Response added with Status Code `504`

DELETE /fabric/compute-managers/{compute-manager-id}

- Response added with Status Code `504`

GET /fabric/compute-managers/{compute-manager-id}

- Response added with Status Code `504`

PUT /fabric/compute-managers/{compute-manager-id}

- Response added with Status Code `504`

GET /fabric/compute-managers

- Response added with Status Code `504`

POST /fabric/compute-managers

- Response added with Status Code `504`

GET /fabric/container-application-instances/{container-application-instance-id}

- Response added with Status Code `504`

GET /fabric/container-application-instances

- Response added with Status Code `504`

GET /fabric/container-applications/{container-application-id}

- Response added with Status Code `504`

GET /fabric/container-applications

- Response added with Status Code `504`

GET /fabric/container-cluster-nodes/{container-cluster-node-id}

- Response added with Status Code `504`

GET /fabric/container-cluster-nodes

- Response added with Status Code `504`

GET /fabric/container-clusters/{container-cluster-id}

- Response added with Status Code `504`

GET /fabric/container-clusters

- Response added with Status Code `504`

GET /fabric/container-egress/{egress-id}

- Response added with Status Code `504`

GET /fabric/container-egresses

- Response added with Status Code `504`

GET /fabric/container-gateway/{gateway-id}

- Response added with Status Code `504`

GET /fabric/container-gateways

- Response added with Status Code `504`

GET /fabric/container-ingress-policies/{ingress-policy-id}

- Response added with Status Code `504`

GET /fabric/container-ingress-policies

- Response added with Status Code `504`

GET /fabric/container-ip-pool/{ip-pool-id}

- Response added with Status Code `504`

GET /fabric/container-ip-pools

- Response added with Status Code `504`

GET /fabric/container-network-policies/{network-policy-id}

- Response added with Status Code `504`

GET /fabric/container-network-policies

- Response added with Status Code `504`

GET /fabric/container-projects/{container-project-id}

- Response added with Status Code `504`

GET /fabric/container-projects

- Response added with Status Code `504`

POST /fabric/discovered-nodes/{node-ext-id}?action=create_transport_node

- Response added with Status Code `504`

POST /fabric/discovered-nodes/{node-ext-id}?action=reapply_cluster_config

- Response added with Status Code `504`

GET /fabric/discovered-nodes/{node-ext-id}

- Response added with Status Code `504`

GET /fabric/discovered-nodes

- Response added with Status Code `504`

GET /fabric/ostypes

- Response added with Status Code `504`

POST /fabric/scope-associations?action=add

- Response added with Status Code `504`

POST /fabric/scope-associations?action=delete

- Response added with Status Code `504`

GET /fabric/scope-associations

- Response added with Status Code `504`

GET /fabric/vifs

- Response added with Status Code `504`

GET /fabric/virtual-machines/tools-info

- Response added with Status Code `504`

POST /fabric/virtual-machines?action=add_tags

- Response added with Status Code `504`

POST /fabric/virtual-machines?action=remove_tags

- Response added with Status Code `504`

POST /fabric/virtual-machines?action=update_tags

- Response added with Status Code `504`

GET /fabric/virtual-machines

- Response added with Status Code `504`

GET /fabric/virtual-switches

- Response added with Status Code `504`

DELETE /failure-domains/{failure-domain-id}

- Response added with Status Code `504`

GET /failure-domains/{failure-domain-id}

- Response added with Status Code `504`

PUT /failure-domains/{failure-domain-id}

- Response added with Status Code `504`

GET /failure-domains

- Response added with Status Code `504`

POST /failure-domains

- Response added with Status Code `504`

DELETE /host-switch-profiles/{host-switch-profile-id}

- Response added with Status Code `504`

GET /host-switch-profiles/{host-switch-profile-id}

- Response added with Status Code `504`

PUT /host-switch-profiles/{host-switch-profile-id}

- Response added with Status Code `504`

GET /host-switch-profiles

- Response added with Status Code `504`

POST /host-switch-profiles

- Response added with Status Code `504`

POST /hpm/features/{feature-stack-name}?action=reset_collection_frequency

- Response added with Status Code `504`

GET /hpm/features/{feature-stack-name}

- Response added with Status Code `504`

PUT /hpm/features/{feature-stack-name}

- Response added with Status Code `504`

GET /hpm/features

- Response added with Status Code `504`

GET /hpm/global-config

- Response added with Status Code `504`

PUT /hpm/global-config

- Response added with Status Code `504`

DELETE /latency-profiles/{latency-profile-id}

- Response added with Status Code `504`

GET /latency-profiles/{latency-profile-id}

- Response added with Status Code `504`

PUT /latency-profiles/{latency-profile-id}

- Response added with Status Code `504`

GET /latency-profiles

- Response added with Status Code `504`

POST /latency-profiles

- Response added with Status Code `504`

GET /license

- Response added with Status Code `504`

PUT /license

- Response added with Status Code `504`

GET /licenses/licenses-usage?format=csv

- Response added with Status Code `504`

GET /licenses/licenses-usage

- Response added with Status Code `504`

GET /licenses/security-usage?format=csv

- Response added with Status Code `504`

GET /licenses/security-usage

- Response added with Status Code `504`

POST /licenses/vcf-licenses

- Response added with Status Code `504`

GET /licenses/vcf/action/async/status

- Response added with Status Code `504`

POST /licenses/vcf/action/async

- Parameter added: `only_sync_unlicensed_vc`
- Response added with Status Code `504`

POST /licenses/vcf/action/sync

- Response added with Status Code `504`

DELETE /licenses/{license-key}

- Response added with Status Code `504`

GET /licenses/{license-key}

- Response added with Status Code `504`

GET /licenses

- Response added with Status Code `504`

GET /logical-switches/{logical-switch-id}/inter-site-forwarder/site-span-info

- Response added with Status Code `504`

GET /logical-switches/{logical-switch-id}/inter-site-forwarder/statistics

- Response added with Status Code `504`

GET /logical-switches/{logical-switch-id}/inter-site-forwarder/status

- Response added with Status Code `504`

GET /malware-prevention/compute-collection/{compute-collection-id}/status

- Response added with Status Code `504`

POST /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment/action/change-appliance

- Response added with Status Code `504`

DELETE /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

GET /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

POST /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

GET /malware-prevention/ovf-spec

- Response added with Status Code `504`

GET /malware-prevention/teaser/regions

- Response added with Status Code `504`

POST /malware-prevention/teaser/registration_url

- Response added with Status Code `504`

GET /malware-prevention/teaser/status

- Response added with Status Code `504`

GET /malware-prevention/transport-node/{transport-node-id}/status

- Response added with Status Code `504`

GET /management-plane-health

- Response added with Status Code `504`

DELETE /manual-health-checks/{manual-health-check-id}

- Response added with Status Code `504`

GET /manual-health-checks/{manual-health-check-id}

- Response added with Status Code `504`

GET /manual-health-checks

- Response added with Status Code `504`

POST /manual-health-checks

- Response added with Status Code `504`

PUT /migration/overlay-adoption/vcenters/{vcenter-id}/add_to_migration_scope

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/assessment/assessment-units/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/assessment/messages/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/inventory/dvpg/virtual-machines/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/inventory/dvpgs/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/inventory/segment-to-dvpgs-mapping/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/inventory/segment/virtual-machines/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/action/continue

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/action/reset

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/action/rollback

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/action/start

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/feedbacks/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/spec/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflow/vm-group/vm-aggregate-info-list/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflows/dvpg-aggregate-info-list/search

- Response added with Status Code `504`

GET /migration/overlay-adoption/vcenters/{vcenter-id}/workflows/dvpg-migration-info

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflows/dvpg-segment-pair/search

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters/{vcenter-id}/workflows/specs/dvpg-segment-pair/search

- Response added with Status Code `504`

GET /migration/overlay-adoption/vcenters

- Response added with Status Code `504`

POST /migration/overlay-adoption/vcenters

- Response added with Status Code `504`

GET /migration/overlay-adoption/workflows/vc-workflow-timestamp-list

- Response added with Status Code `504`

POST /node/aaa/auth-policy?action=reset-all

- Response added with Status Code `504`

POST /node/aaa/auth-policy?action=reset-auth-policies

- Response added with Status Code `504`

POST /node/aaa/auth-policy?action=reset-pwd-complexity

- Response added with Status Code `504`

GET /node/aaa/auth-policy

- Response added with Status Code `504`

PUT /node/aaa/auth-policy

- Response added with Status Code `504`

GET /node/aaa/providers/vidm/status

- Response added with Status Code `504`

GET /node/aaa/providers/vidm

- Response added with Status Code `504`

PUT /node/aaa/providers/vidm

- Response added with Status Code `504`

GET /node/central-config

- Response added with Status Code `504`

PUT /node/central-config

- Response added with Status Code `504`

DELETE /node/core-dumps/{file-name}

- Response added with Status Code `504`

GET /node/core-dumps

- Response added with Status Code `504`

GET /node/file-store/{file-name}/data

- Response added with Status Code `504`

PUT /node/file-store/{file-name}/data

- Response added with Status Code `504`

GET /node/file-store/{file-name}/thumbprint

- Response added with Status Code `504`

DELETE /node/file-store/{file-name}

- Response added with Status Code `504`

GET /node/file-store/{file-name}

- Response added with Status Code `504`

POST /node/file-store/{file-name}

- Response added with Status Code `504`

POST /node/file-store?action=retrieve_ssh_fingerprint

- Response added with Status Code `504`

GET /node/file-store

- Response added with Status Code `504`

PUT /node/grub/{grub-username}

- Response added with Status Code `504`

GET /node/grub

- Response added with Status Code `504`

PUT /node/grub

- Response added with Status Code `504`

GET /node/hardening-policy/mandatory-access-control/report

- Response added with Status Code `504`

GET /node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

PUT /node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

GET /node/intelligence/form-factors

- Response added with Status Code `504`

GET /node/logs/{log-name}/data

- Response added with Status Code `504`

GET /node/logs/{log-name}

- Response added with Status Code `504`

GET /node/logs

- Response added with Status Code `504`

DELETE /node/management-plane

- Response added with Status Code `504`

GET /node/management-plane

- Response added with Status Code `504`

PUT /node/management-plane

- Response added with Status Code `504`

GET /node/mode

- Response added with Status Code `504`

GET /node/motd

- Response added with Status Code `504`

DELETE /node/mpa-config

- Response added with Status Code `504`

GET /node/mpa-config

- Response added with Status Code `504`

PUT /node/mpa-config

- Response added with Status Code `504`

DELETE /node/network/interfaces/link-local

- Response added with Status Code `504`

GET /node/network/interfaces/link-local

- Response added with Status Code `504`

POST /node/network/interfaces/link-local

- Response added with Status Code `504`

GET /node/network/interfaces/{interface-id}/stats

- Response added with Status Code `504`

GET /node/network/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /node/network/interfaces/{interface-id}

- Response added with Status Code `504`

GET /node/network/interfaces

- Response added with Status Code `504`

GET /node/network/name-servers

- Response added with Status Code `504`

PUT /node/network/name-servers

- Response added with Status Code `504`

DELETE /node/network/routes/{route-id}

- Response added with Status Code `504`

GET /node/network/routes/{route-id}

- Response added with Status Code `504`

GET /node/network/routes

- Response added with Status Code `504`

POST /node/network/routes

- Response added with Status Code `504`

GET /node/network/search-domains

- Response added with Status Code `504`

PUT /node/network/search-domains

- Response added with Status Code `504`

GET /node/network

- Response added with Status Code `504`

GET /node/processes/{process-id}

- Response added with Status Code `504`

GET /node/processes

- Response added with Status Code `504`

GET /node/services/applianceproxy/status

- Response added with Status Code `504`

POST /node/services/applianceproxy?action=restart

- Response added with Status Code `504`

POST /node/services/applianceproxy?action=start

- Response added with Status Code `504`

POST /node/services/applianceproxy?action=stop

- Response added with Status Code `504`

GET /node/services/applianceproxy

- Response added with Status Code `504`

GET /node/services/async_replicator/status

- Response added with Status Code `504`

POST /node/services/async_replicator?action=restart

- Response added with Status Code `504`

POST /node/services/async_replicator?action=start

- Response added with Status Code `504`

POST /node/services/async_replicator?action=stop

- Response added with Status Code `504`

GET /node/services/async_replicator

- Response added with Status Code `504`

PUT /node/services/async_replicator

- Response added with Status Code `504`

GET /node/services/auth/status

- Response added with Status Code `504`

POST /node/services/auth?action=restart

- Response added with Status Code `504`

POST /node/services/auth?action=start

- Response added with Status Code `504`

POST /node/services/auth?action=stop

- Response added with Status Code `504`

GET /node/services/auth

- Response added with Status Code `504`

PUT /node/services/auth

- Response added with Status Code `504`

GET /node/services/cluster_manager/status

- Response added with Status Code `504`

POST /node/services/cluster_manager?action=restart

- Response added with Status Code `504`

POST /node/services/cluster_manager?action=start

- Response added with Status Code `504`

POST /node/services/cluster_manager?action=stop

- Response added with Status Code `504`

GET /node/services/cluster_manager

- Response added with Status Code `504`

GET /node/services/cm-inventory/status

- Response added with Status Code `504`

POST /node/services/cm-inventory?action=restart

- Response added with Status Code `504`

POST /node/services/cm-inventory?action=start

- Response added with Status Code `504`

POST /node/services/cm-inventory?action=stop

- Response added with Status Code `504`

GET /node/services/cm-inventory

- Response added with Status Code `504`

GET /node/services/controller/controller-certificate

- Response added with Status Code `504`

GET /node/services/controller/profiler

- Response added with Status Code `504`

PUT /node/services/controller/profiler

- Response added with Status Code `504`

GET /node/services/controller/status

- Response added with Status Code `504`

POST /node/services/controller?action=restart

- Response added with Status Code `504`

POST /node/services/controller?action=start

- Response added with Status Code `504`

POST /node/services/controller?action=stop

- Response added with Status Code `504`

GET /node/services/controller

- Response added with Status Code `504`

POST /node/services/datastore/corfu_cert_expiry_check?action=disable

- Response added with Status Code `504`

POST /node/services/datastore/corfu_cert_expiry_check?action=enable

- Response added with Status Code `504`

GET /node/services/datastore/corfu_cert_expiry_check

- Response added with Status Code `504`

GET /node/services/datastore/status

- Response added with Status Code `504`

POST /node/services/datastore?action=restart

- Response added with Status Code `504`

POST /node/services/datastore?action=start

- Response added with Status Code `504`

POST /node/services/datastore?action=stop

- Response added with Status Code `504`

GET /node/services/datastore

- Response added with Status Code `504`

GET /node/services/datastore_nonconfig/status

- Response added with Status Code `504`

POST /node/services/datastore_nonconfig?action=restart

- Response added with Status Code `504`

POST /node/services/datastore_nonconfig?action=start

- Response added with Status Code `504`

POST /node/services/datastore_nonconfig?action=stop

- Response added with Status Code `504`

GET /node/services/datastore_nonconfig

- Response added with Status Code `504`

GET /node/services/http/status

- Response added with Status Code `504`

POST /node/services/http?action=apply_certificate

- Response added with Status Code `504`

POST /node/services/http?action=restart

- Response added with Status Code `504`

POST /node/services/http?action=start

- Response added with Status Code `504`

POST /node/services/http?action=stop

- Response added with Status Code `504`

GET /node/services/http

- Response added with Status Code `504`

PUT /node/services/http

- Response added with Status Code `504`

GET /node/services/idps-reporting/status

- Response added with Status Code `504`

POST /node/services/idps-reporting?action=restart

- Response added with Status Code `504`

POST /node/services/idps-reporting?action=start

- Response added with Status Code `504`

POST /node/services/idps-reporting?action=stop

- Response added with Status Code `504`

GET /node/services/idps-reporting

- Response added with Status Code `504`

GET /node/services/install-upgrade/status

- Response added with Status Code `504`

PUT /node/services/install-upgrade/uc-state

- Response added with Status Code `504`

POST /node/services/install-upgrade?action=restart

- Response added with Status Code `504`

POST /node/services/install-upgrade?action=start

- Response added with Status Code `504`

POST /node/services/install-upgrade?action=stop

- Response added with Status Code `504`

GET /node/services/install-upgrade

- Response added with Status Code `504`

PUT /node/services/install-upgrade

- Response added with Status Code `504`

GET /node/services/liagent/status

- Response added with Status Code `504`

POST /node/services/liagent?action=restart

- Response added with Status Code `504`

POST /node/services/liagent?action=start

- Response added with Status Code `504`

POST /node/services/liagent?action=stop

- Response added with Status Code `504`

GET /node/services/liagent

- Response added with Status Code `504`

GET /node/services/manager/status

- Response added with Status Code `504`

POST /node/services/manager?action=reset-manager-logging-levels

- Response added with Status Code `504`

POST /node/services/manager?action=restart

- Response added with Status Code `504`

POST /node/services/manager?action=start

- Response added with Status Code `504`

POST /node/services/manager?action=stop

- Response added with Status Code `504`

GET /node/services/manager

- Response added with Status Code `504`

PUT /node/services/manager

- Response added with Status Code `504`

GET /node/services/messaging-manager/status

- Response added with Status Code `504`

POST /node/services/messaging-manager?action=restart

- Response added with Status Code `504`

POST /node/services/messaging-manager?action=start

- Response added with Status Code `504`

POST /node/services/messaging-manager?action=stop

- Response added with Status Code `504`

GET /node/services/messaging-manager

- Response added with Status Code `504`

GET /node/services/migration-coordinator/status

- Response added with Status Code `504`

POST /node/services/migration-coordinator?action=restart

- Response added with Status Code `504`

POST /node/services/migration-coordinator?action=start

- Response added with Status Code `504`

POST /node/services/migration-coordinator?action=stop

- Response added with Status Code `504`

GET /node/services/migration-coordinator

- Response added with Status Code `504`

GET /node/services/monitoring/status

- Response added with Status Code `504`

POST /node/services/monitoring?action=reset-monitoring-logging-levels

- Response added with Status Code `504`

POST /node/services/monitoring?action=restart

- Response added with Status Code `504`

POST /node/services/monitoring?action=start

- Response added with Status Code `504`

POST /node/services/monitoring?action=stop

- Response added with Status Code `504`

GET /node/services/monitoring

- Response added with Status Code `504`

PUT /node/services/monitoring

- Response added with Status Code `504`

GET /node/services/node-mgmt/loglevel

- Response added with Status Code `504`

PUT /node/services/node-mgmt/loglevel

- Response added with Status Code `504`

GET /node/services/node-mgmt/status

- Response added with Status Code `504`

POST /node/services/node-mgmt?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

GET /node/services/node-mgmt

- Response added with Status Code `504`

GET /node/services/node-stats/status

- Response added with Status Code `504`

POST /node/services/node-stats?action=restart

- Response added with Status Code `504`

POST /node/services/node-stats?action=start

- Response added with Status Code `504`

POST /node/services/node-stats?action=stop

- Response added with Status Code `504`

GET /node/services/node-stats

- Response added with Status Code `504`

GET /node/services/nsx-message-bus/status

- Response added with Status Code `504`

POST /node/services/nsx-message-bus?action=restart

- Response added with Status Code `504`

POST /node/services/nsx-message-bus?action=start

- Response added with Status Code `504`

POST /node/services/nsx-message-bus?action=stop

- Response added with Status Code `504`

GET /node/services/nsx-message-bus

- Response added with Status Code `504`

GET /node/services/nsx-platform-client/status

- Response added with Status Code `504`

POST /node/services/nsx-platform-client?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

POST /node/services/nsx-platform-client?action=start

- Parameter added: `force`
- Response added with Status Code `504`

POST /node/services/nsx-platform-client?action=stop

- Parameter added: `force`
- Response added with Status Code `504`

GET /node/services/nsx-platform-client

- Response added with Status Code `504`

GET /node/services/nsx-upgrade-agent/status

- Response added with Status Code `504`

POST /node/services/nsx-upgrade-agent?action=restart

- Response added with Status Code `504`

POST /node/services/nsx-upgrade-agent?action=start

- Response added with Status Code `504`

POST /node/services/nsx-upgrade-agent?action=stop

- Response added with Status Code `504`

GET /node/services/nsx-upgrade-agent

- Response added with Status Code `504`

GET /node/services/ntp/status

- Response added with Status Code `504`

POST /node/services/ntp?action=restart

- Response added with Status Code `504`

POST /node/services/ntp?action=start

- Response added with Status Code `504`

POST /node/services/ntp?action=stop

- Response added with Status Code `504`

GET /node/services/ntp

- Response added with Status Code `504`

PUT /node/services/ntp

- Response added with Status Code `504`

GET /node/services/policy/status

- Response added with Status Code `504`

POST /node/services/policy?action=reset-manager-logging-levels

- Response added with Status Code `504`

POST /node/services/policy?action=restart

- Response added with Status Code `504`

POST /node/services/policy?action=start

- Response added with Status Code `504`

POST /node/services/policy?action=stop

- Response added with Status Code `504`

GET /node/services/policy

- Response added with Status Code `504`

PUT /node/services/policy

- Response added with Status Code `504`

GET /node/services/search/status

- Response added with Status Code `504`

POST /node/services/search?action=restart

- Response added with Status Code `504`

POST /node/services/search?action=start

- Response added with Status Code `504`

POST /node/services/search?action=stop

- Response added with Status Code `504`

GET /node/services/search

- Response added with Status Code `504`

GET /node/services/sha/status

- Response added with Status Code `504`

POST /node/services/sha?action=restart

- Response added with Status Code `504`

POST /node/services/sha?action=start

- Response added with Status Code `504`

POST /node/services/sha?action=stop

- Response added with Status Code `504`

GET /node/services/sha

- Response added with Status Code `504`

GET /node/services/site_manager/status

- Response added with Status Code `504`

POST /node/services/site_manager?action=restart

- Response added with Status Code `504`

POST /node/services/site_manager?action=start

- Response added with Status Code `504`

POST /node/services/site_manager?action=stop

- Response added with Status Code `504`

GET /node/services/site_manager

- Response added with Status Code `504`

GET /node/services/snmp/status

- Response added with Status Code `504`

GET /node/services/snmp/v3-engine-id

- Response added with Status Code `504`

PUT /node/services/snmp/v3-engine-id

- Response added with Status Code `504`

POST /node/services/snmp?action=restart

- Response added with Status Code `504`

POST /node/services/snmp?action=start

- Response added with Status Code `504`

POST /node/services/snmp?action=stop

- Response added with Status Code `504`

GET /node/services/snmp

- Response added with Status Code `504`

PUT /node/services/snmp

- Response added with Status Code `504`

POST /node/services/ssh/notify_mpa?action=restart

- Response added with Status Code `504`

POST /node/services/ssh/notify_mpa?action=start

- Response added with Status Code `504`

POST /node/services/ssh/notify_mpa?action=stop

- Response added with Status Code `504`

GET /node/services/ssh/status

- Response added with Status Code `504`

POST /node/services/ssh?action=remove_host_fingerprint

- Response added with Status Code `504`

POST /node/services/ssh?action=restart

- Response added with Status Code `504`

POST /node/services/ssh?action=start

- Response added with Status Code `504`

POST /node/services/ssh?action=stop

- Response added with Status Code `504`

GET /node/services/ssh

- Response added with Status Code `504`

PUT /node/services/ssh

- Response added with Status Code `504`

DELETE /node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `504`

- Response added with Status Code `409`

GET /node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `504`

POST /node/services/syslog/exporters?action=verify

- Response added with Status Code `504`

DELETE /node/services/syslog/exporters

- Response added with Status Code `504`
- Response added with Status Code `409`

GET /node/services/syslog/exporters

- Response added with Status Code `504`

POST /node/services/syslog/exporters

- Response added with Status Code `504`

GET /node/services/syslog/status

- Response added with Status Code `504`

POST /node/services/syslog?action=restart

- Response added with Status Code `504`

POST /node/services/syslog?action=start

- Response added with Status Code `504`

POST /node/services/syslog?action=stop

- Response added with Status Code `504`

GET /node/services/syslog

- Response added with Status Code `504`

GET /node/services/telemetry/status

- Response added with Status Code `504`

POST /node/services/telemetry?action=reset-telemetry-logging-levels

- Response added with Status Code `504`

POST /node/services/telemetry?action=restart

- Response added with Status Code `504`

POST /node/services/telemetry?action=start

- Response added with Status Code `504`

POST /node/services/telemetry?action=stop

- Response added with Status Code `504`

GET /node/services/telemetry

- Response added with Status Code `504`

PUT /node/services/telemetry

- Response added with Status Code `504`

GET /node/services/ui-service/status

- Response added with Status Code `504`

POST /node/services/ui-service?action=restart

- Response added with Status Code `504`

POST /node/services/ui-service?action=start

- Response added with Status Code `504`

POST /node/services/ui-service?action=stop

- Response added with Status Code `504`

GET /node/services/ui-service

- Response added with Status Code `504`

GET /node/services

- Response added with Status Code `504`

POST /node/status?action=clear_bootup_error

- Response added with Status Code `504`

GET /node/status

- Response added with Status Code `504`

GET /node/support-bundle

- Response added with Status Code `504`

GET /node/tasks/{task-id}/response

- Response added with Status Code `504`

POST /node/tasks/{task-id}?action=cancel

- Response added with Status Code `504`

DELETE /node/tasks/{task-id}

- Response added with Status Code `504`

GET /node/tasks/{task-id}

- Response added with Status Code `504`

GET /node/tasks

- Response added with Status Code `504`

POST /node/upgrade/performtask

- Response added with Status Code `504`

GET /node/upgrade/progress-status

- Response added with Status Code `504`

GET /node/upgrade/status-summary

- Response added with Status Code `504`

POST /node/upgrade/uc

- Response added with Status Code `504`

GET /node/upgrade

- Response added with Status Code `504`

POST /node/users/{userid}/ssh-keys?action=add_ssh_key

- Response added with Status Code `504`

POST /node/users/{userid}/ssh-keys?action=remove_ssh_key

- Response added with Status Code `504`

GET /node/users/{userid}/ssh-keys

- Response added with Status Code `504`

POST /node/users/{userid}?action=activate

- Response added with Status Code `504`

POST /node/users/{userid}?action=deactivate

- Response added with Status Code `504`

POST /node/users/{userid}?action=reset_password

- Response added with Status Code `504`

DELETE /node/users/{userid}

- Response added with Status Code `504`

GET /node/users/{userid}

- Response added with Status Code `504`

PUT /node/users/{userid}

- Response added with Status Code `504`

POST /node/users?action=create_audit_user

- Response added with Status Code `504`

POST /node/users?action=create_service_user

- Response added with Status Code `504`

POST /node/users?action=create_user

- Response added with Status Code `504`

POST /node/users?action=reset_own_password

- Response added with Status Code `504`

GET /node/users

- Property changed `operationId` from `NodeListNodeUsersTrue` to `NodeListNodeUsers`
- Response added with Status Code `504`

GET /node/version

- Response added with Status Code `504`

POST /node?action=restart

- Response added with Status Code `504`

POST /node?action=set_coredump_config

- Response added with Status Code `504`

POST /node?action=set_system_time

- Response added with Status Code `504`

POST /node?action=shutdown

- Response added with Status Code `504`

GET /node

- Response added with Status Code `504`

PUT /node

- Response added with Status Code `504`

POST /notification-watchers/{watcher-id}/notifications?action=add_uri_filters

- Response added with Status Code `504`

POST /notification-watchers/{watcher-id}/notifications?action=delete_uri_filters

- Response added with Status Code `504`

GET /notification-watchers/{watcher-id}/notifications

- Response added with Status Code `504`

PUT /notification-watchers/{watcher-id}/notifications

- Response added with Status Code `504`

DELETE /notification-watchers/{watcher-id}

- Response added with Status Code `504`

GET /notification-watchers/{watcher-id}

- Response added with Status Code `504`

PUT /notification-watchers/{watcher-id}

- Response added with Status Code `504`

GET /notification-watchers

- Response added with Status Code `504`

POST /notification-watchers

- Response added with Status Code `504`

GET /pktcap/session/{session-id}/capturefile

- Response added with Status Code `504`

POST /pktcap/session/{session-id}?action=delete

- Response added with Status Code `504`

POST /pktcap/session/{session-id}?action=restart

- Response added with Status Code `504`

POST /pktcap/session/{session-id}?action=terminate

- Response added with Status Code `504`

GET /pktcap/session/{session-id}

- Response added with Status Code `504`

POST /pktcap/session

- Response added with Status Code `504`

POST /pktcap/sessions?action=delete

- Response added with Status Code `504`

GET /pktcap/sessions

- Response added with Status Code `504`

GET /pools/ip-pools/{pool-id}/allocations

- Response added with Status Code `504`

GET /pools/ip-pools/{pool-id}

- Response added with Status Code `504`

GET /pools/ip-pools

- Response added with Status Code `504`

GET /pools/mac-pools/{pool-id}

- Response added with Status Code `504`

GET /pools/mac-pools

- Response added with Status Code `504`

DELETE /pools/vni-pools/{pool-id}

- Response added with Status Code `504`

GET /pools/vni-pools/{pool-id}

- Response added with Status Code `504`

PUT /pools/vni-pools/{pool-id}

- Response added with Status Code `504`

GET /pools/vni-pools

- Response added with Status Code `504`

POST /pools/vni-pools

- Response added with Status Code `504`

GET /pools/vtep-label-pools/{pool-id}

- Response added with Status Code `504`

GET /pools/vtep-label-pools

- Response added with Status Code `504`

GET /proxy/config

- Response added with Status Code `504`

PUT /proxy/config

- Response added with Status Code `504`

GET /realization-state-barrier/config

- Response added with Status Code `504`

PUT /realization-state-barrier/config

- Response added with Status Code `504`

POST /realization-state-barrier/current?action=increment

- Response added with Status Code `504`

GET /realization-state-barrier/current

- Response added with Status Code `504`

GET /repository/bundles/ovf-deploy-info

- Response added with Status Code `504`

GET /repository/bundles/upload-allowed

- Response added with Status Code `504`

GET /repository/bundles/{bundle-id}/upload-status

- Response added with Status Code `504`

POST /repository/bundles/{bundle-id}?action=cancel_upload

- Response added with Status Code `504`

POST /repository/bundles?action=upload

- Response added with Status Code `504`

GET /repository/bundles

- Response added with Status Code `504`

POST /repository/bundles

- Response added with Status Code `504`

GET /reverse-proxy/node/health

- Response added with Status Code `504`

GET /search/dsl

- Response added with Status Code `504`

GET /search/query

- Response added with Status Code `504`

GET /search/reconcile/status

- Response added with Status Code `504`

POST /search/reconcile

- Response added with Status Code `504`

POST /security/sensor-registration-token

- Response added with Status Code `504`

DELETE /serviceinsertion/service-attachments/{service-attachment-id}

- Response added with Status Code `504`

GET /serviceinsertion/service-attachments/{service-attachment-id}

- Response added with Status Code `504`

PUT /serviceinsertion/service-attachments/{service-attachment-id}

- Response added with Status Code `504`

GET /serviceinsertion/service-attachments

- Response added with Status Code `504`

POST /serviceinsertion/service-attachments

- Response added with Status Code `504`

GET /serviceinsertion/service-chains/{service-chain-id}/service-paths

- Response added with Status Code `504`

DELETE /serviceinsertion/service-chains/{service-chain-id}

- Response added with Status Code `504`

GET /serviceinsertion/service-chains/{service-chain-id}

- Response added with Status Code `504`

GET /serviceinsertion/service-chains

- Response added with Status Code `504`

POST /serviceinsertion/service-chains

- Response added with Status Code `504`

GET /serviceinsertion/service-instances

- Response added with Status Code `504`

DELETE /serviceinsertion/service-managers/{service-manager-id}

- Response added with Status Code `504`

GET /serviceinsertion/service-managers/{service-manager-id}

- Response added with Status Code `504`

PUT /serviceinsertion/service-managers/{service-manager-id}

- Response added with Status Code `504`

GET /serviceinsertion/service-managers

- Response added with Status Code `504`

POST /serviceinsertion/service-managers

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-deployments/{service-deployment-id}/state

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-deployments/{service-deployment-id}/status

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-deployments/{service-deployment-id}?action=upgrade

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}/service-deployments/{service-deployment-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-deployments/{service-deployment-id}

- Response added with Status Code `504`

PUT /serviceinsertion/services/{service-id}/service-deployments/{service-deployment-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-deployments

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-deployments

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/group-associations

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-endpoints/{instance-endpoint-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-endpoints/{instance-endpoint-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-endpoints

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-endpoints

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-runtimes/{instance-runtime-id}/interfaces/{interface_index}/statistics

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-runtimes/{instance-runtime-id}/interfaces/{interface_index}/status

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-runtimes/{instance-runtime-id}

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-runtimes?action=delete

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-runtimes?action=deploy

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-runtimes?action=upgrade

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/instance-runtimes

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/state

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}/status

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

PUT /serviceinsertion/services/{service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-instances

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-instances

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-profiles/{service-profile-id}/nsgroups

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-profiles/{service-profile-id}/service-chain-mappings

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}/service-profiles/{service-profile-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-profiles/{service-profile-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/service-profiles

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/service-profiles

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}/solution-configs/{solution-config-id}/extended-solution-config

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/solution-configs/{solution-config-id}/extended-solution-config

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/solution-configs/{solution-config-id}/extended-solution-config

- Response added with Status Code `504`

PUT /serviceinsertion/services/{service-id}/solution-configs/{solution-config-id}/extended-solution-config

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}/solution-configs/{solution-config-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/solution-configs/{solution-config-id}

- Response added with Status Code `504`

PUT /serviceinsertion/services/{service-id}/solution-configs/{solution-config-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/solution-configs

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/solution-configs

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}/vendor-templates/{vendor-template-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/vendor-templates/{vendor-template-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}/vendor-templates

- Response added with Status Code `504`

POST /serviceinsertion/services/{service-id}/vendor-templates

- Response added with Status Code `504`

DELETE /serviceinsertion/services/{service-id}

- Response added with Status Code `504`

GET /serviceinsertion/services/{service-id}

- Response added with Status Code `504`

PUT /serviceinsertion/services/{service-id}

- Response added with Status Code `504`

GET /serviceinsertion/services

- Response added with Status Code `504`

POST /serviceinsertion/services

- Response added with Status Code `504`

GET /serviceinsertion/source-entities

- Response added with Status Code `504`

GET /sites/compatibility/remote

- Response added with Status Code `504`

GET /sites/compatibility

- Response added with Status Code `504`

GET /sites/self

- Response added with Status Code `504`

GET /sites/status

- Response added with Status Code `504`

GET /sites/switchover-status

- Response added with Status Code `504`

GET /sites?version=3.0.2

- Response added with Status Code `504`

GET /sites?version=3.1.0

- Response added with Status Code `504`

GET /sites?version=latest

- Response added with Status Code `504`

GET /sites

- Response added with Status Code `504`

GET /systemhealth-extended/edge-cluster

- Response added with Status Code `504`

GET /systemhealth-extended/edge-transport-nodes

- Response added with Status Code `504`

GET /systemhealth-extended/host-transport-nodes

- Response added with Status Code `504`

GET /systemhealth-extended/management-cluster

- Response added with Status Code `504`

GET /systemhealth-extended/management-nodes/{node-id}/services/{service-name}

- Response added with Status Code `504`

GET /systemhealth-extended/management-nodes

- Response added with Status Code `504`

GET /systemhealth-extended/metadata

- Response added with Status Code `504`

GET /systemhealth/appliances/latency/status

- Response added with Status Code `504`

GET /systemhealth/appliances/process/status

- Response added with Status Code `504`

GET /systemhealth/appliances/{appliance-id}/latency/status

- Response added with Status Code `504`

GET /systemhealth/appliances/{appliance-id}/process/status

- Response added with Status Code `504`

GET /systemhealth/container-cluster/ncp/status

- Response added with Status Code `504`

POST /systemhealth/container-cluster/ncp/status

- Response added with Status Code `504`

DELETE /systemhealth/container-cluster/{cluster-id}/ncp/status

- Response added with Status Code `504`

GET /systemhealth/container-cluster/{cluster-id}/ncp/status

- Response added with Status Code `504`

GET /systemhealth/plugins/status/{node-id}

- Response added with Status Code `504`

POST /systemhealth/plugins/{plugin-id}/files/{file-name}/data

- Response added with Status Code `504`

DELETE /systemhealth/plugins/{plugin-id}

- Response added with Status Code `504`

GET /systemhealth/plugins/{plugin-id}

- Response added with Status Code `504`

GET /systemhealth/plugins

- Response added with Status Code `504`

POST /systemhealth/plugins

- Response added with Status Code `504`

DELETE /systemhealth/profiles/{profile-id}

- Response added with Status Code `504`

GET /systemhealth/profiles/{profile-id}

- Response added with Status Code `504`

PUT /systemhealth/profiles/{profile-id}

- Response added with Status Code `504`

GET /systemhealth/profiles

- Response added with Status Code `504`

POST /systemhealth/profiles

- Response added with Status Code `504`

GET /systemhealth/transport-nodes/{node-id}/container/agent/status

- Response added with Status Code `504`

GET /systemhealth/transport-nodes/{node-id}/container/hyperbus/status

- Response added with Status Code `504`

GET /tasks/{task-id}/response

- Response added with Status Code `504`

GET /tasks/{task-id}

- Response added with Status Code `504`

GET /tasks

- Response added with Status Code `504`

GET /telemetry/agreement

- Response added with Status Code `504`

PUT /telemetry/agreement

- Response added with Status Code `504`

GET /telemetry/config

- Response added with Status Code `504`

PUT /telemetry/config

- Response added with Status Code `504`

GET /transport-node-collections/{transport-node-collection-id}/state

- Response added with Status Code `504`

POST /transport-node-collections/{transport-node-collection-id}?action=retry_profile_realization

- Response added with Status Code `504`

DELETE /transport-node-collections/{transport-node-collection-id}

- Response added with Status Code `504`

GET /transport-node-collections/{transport-node-collection-id}

- Response added with Status Code `504`

PUT /transport-node-collections/{transport-node-collection-id}

- Response added with Status Code `504`

GET /transport-node-collections

- Response added with Status Code `504`

POST /transport-node-collections

- Response added with Status Code `504`

DELETE /transport-node-profiles/{transport-node-profile-id}

- Response added with Status Code `504`

GET /transport-node-profiles/{transport-node-profile-id}

- Response added with Status Code `504`

PUT /transport-node-profiles/{transport-node-profile-id}

- Response added with Status Code `504`

GET /transport-node-profiles

- Response added with Status Code `504`

POST /transport-node-profiles

- Response added with Status Code `504`

GET /transport-nodes/state

- Parameter added: `node_types`
- Response added with Status Code `504`

GET /transport-nodes/status

- Response added with Status Code `504`

POST /transport-nodes/{edge-node-id}/action/clean-stale-entries

- Response added with Status Code `504`

GET /transport-nodes/{edge-node-id}/inter-site/bgp/neighbors/{neighbor-id}/advertised-routes

- Response added with Status Code `504`

GET /transport-nodes/{edge-node-id}/inter-site/bgp/neighbors/{neighbor-id}/routes

- Response added with Status Code `504`

GET /transport-nodes/{edge-node-id}/inter-site/bgp/neighbors

- Response added with Status Code `504`

GET /transport-nodes/{edge-node-id}/inter-site/bgp/summary

- Response added with Status Code `504`

GET /transport-nodes/{edge-node-id}/inter-site/statistics

- Response added with Status Code `504`

GET /transport-nodes/{node-id}/modules

- Response added with Status Code `504`

GET /transport-nodes/{node-id}/pnic-bond-status

- Response added with Status Code `504`

GET /transport-nodes/{node-id}/remote-transport-node-status

- Response added with Status Code `504`

GET /transport-nodes/{node-id}/statistics/nat-rules

- Response added with Status Code `504`

GET /transport-nodes/{node-id}/status

- Response added with Status Code `504`

GET /transport-nodes/{node-id}/tunnels/{tunnel-name}

- Response added with Status Code `504`

GET /transport-nodes/{node-id}/tunnels

- Response added with Status Code `504`

POST /transport-nodes/{node-id}?action=addOrUpdatePlacementReferences

- Response added with Status Code `504`

POST /transport-nodes/{node-id}?action=redeploy

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/capabilities

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/network/interfaces/{interface-id}/stats

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/network/interfaces/{interface-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/network/interfaces

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/aaa/auth-policy?action=reset-all

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/aaa/auth-policy?action=reset-auth-policies

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/aaa/auth-policy?action=reset-pwd-complexity

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/aaa/auth-policy

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/aaa/auth-policy

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/certificate

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/configuration

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}/node/core-dumps/{file-name}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/core-dumps

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/diagnosis/inconsistency

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/diagnosis

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/file-store/{file-name}/thumbprint

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}/node/file-store/{file-name}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/file-store/{file-name}

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/file-store/{file-name}

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/file-store?action=retrieve_ssh_fingerprint

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/file-store

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/flows/interfaces/{iface-uuid}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/flows/logical-routers/{uuid}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/flows

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/grub/{grub-username}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/grub

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/grub

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/hardening-policy/mandatory-access-control/report

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/hardening-policy/mandatory-access-control

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/logical-routers/diagnosis

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/logical-routers/{logical-router-id}/diagnosis

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/logs/{log-name}/data

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/logs/{log-name}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/logs

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/maintenance-mode

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/maintenance-mode

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/motd

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network/interfaces/{interface-id}/stats

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/network/interfaces/{interface-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network/interfaces

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network/name-servers

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/network/name-servers

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}/node/network/routes/{route-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network/routes/{route-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network/routes

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/network/routes

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network/search-domains

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/network/search-domains

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/network

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/processes/{process-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/processes

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/cpu-stats

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/ctrl-prio

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/flow-cache

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/flow-cache

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/flow-mon

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/flow-mon

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/fw-conns

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/fw-stats

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/geneve-cbit

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/geneve-cbit

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/intr-mode

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/l2vpn-pmtu

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/l2vpn-pmtu

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/physical-ports/{physical-port}/stats

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/physical-ports/{physical-port}/xstats

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/pmtu-learning

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/pmtu-learning

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/qat-enable

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/qat-status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/queue-num-per-port-per-core

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/queue-num-per-port-per-core

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/ring-size

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/rx-ring-size

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/status

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane/tx-ring-size

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane/upt-mode

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/dataplane?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/dataplane?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/dataplane?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dataplane

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dataplane

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dhcp/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dhcp

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/dhcp

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dispatcher/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/dispatcher?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/dispatcher?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/dispatcher?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/dispatcher

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/docker/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/docker

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/ipsecvpn/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/ipsecvpn

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/ipsecvpn

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/liagent/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/liagent?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/liagent?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/liagent?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/liagent

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/local-controller/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/local-controller?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/local-controller?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/local-controller?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/local-controller

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/local-controller

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/metadata-proxy/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/metadata-proxy

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nestdb/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nestdb?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nestdb?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nestdb?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nestdb

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/node-mgmt/loglevel

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/node-mgmt/loglevel

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/node-mgmt/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/node-mgmt?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/node-mgmt

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-control-plane-agent/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-control-plane-agent?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-control-plane-agent?action=start

- Parameter added: `force`
- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-control-plane-agent?action=stop

- Parameter added: `force`
- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-control-plane-agent

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-opsagent/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-opsagent?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-opsagent?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-opsagent?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-opsagent

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-platform-client/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-platform-client?action=restart

- Parameter added: `force`
- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-platform-client?action=start

- Parameter added: `force`
- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-platform-client?action=stop

- Parameter added: `force`
- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-platform-client

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-upgrade-agent/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-upgrade-agent?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-upgrade-agent?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/nsx-upgrade-agent?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/nsx-upgrade-agent

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/ntp/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ntp?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ntp?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ntp?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/ntp

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/ntp

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/router-config/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/router-config

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/router/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/router

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/security-hub/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/security-hub

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/snmp/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/snmp/v3-engine-id

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/snmp/v3-engine-id

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/snmp?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/snmp?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/snmp?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/snmp

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/snmp

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ssh/notify_mpa?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ssh/notify_mpa?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ssh/notify_mpa?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/ssh/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ssh?action=remove_host_fingerprint

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ssh?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ssh?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/ssh?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/ssh

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/ssh

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}/node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `504`
- Response added with Status Code `409`

GET /transport-nodes/{transport-node-id}/node/services/syslog/exporters/{exporter-name}

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/syslog/exporters?action=verify

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}/node/services/syslog/exporters

- Response added with Status Code `504`
- Response added with Status Code `409`

GET /transport-nodes/{transport-node-id}/node/services/syslog/exporters

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/syslog/exporters

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/syslog/status

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/syslog?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/syslog?action=start

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/services/syslog?action=stop

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/syslog

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/vpn/ipsec/deterministic-esp-rss/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services/vpn/ipsec/deterministic-esp-rss

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/services/vpn/ipsec/deterministic-esp-rss

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/services

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/status?action=clear_bootup_error

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/status

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/tasks/{task-id}/response

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/tasks/{task-id}?action=cancel

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}/node/tasks/{task-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/tasks/{task-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/tasks

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/users/{userid}/ssh-keys?action=add_ssh_key

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/users/{userid}/ssh-keys?action=remove_ssh_key

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/users/{userid}/ssh-keys

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node/users/{userid}?action=reset_password

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}/node/users/{userid}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/users/{userid}

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node/users/{userid}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/users

- Property changed `operationId` from `TransportNodesTransportNodeIdNodeListNodeUsersTrue` to `TransportNodesTransportNodeIdNodeListNodeUsers`
- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node/version

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node?action=restart

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node?action=set_coredump_config

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node?action=set_system_time

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}/node?action=shutdown

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/node

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}/node

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}/state

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}?action=disable_flow_cache

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}?action=enable_flow_cache

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}?action=restart_inventory_sync

- Response added with Status Code `504`

POST /transport-nodes/{transport-node-id}?action=restore_cluster_config

- Response added with Status Code `504`

DELETE /transport-nodes/{transport-node-id}

- Response added with Status Code `504`

GET /transport-nodes/{transport-node-id}

- Response added with Status Code `504`

PUT /transport-nodes/{transport-node-id}

- Response added with Status Code `504`

POST /transport-nodes/{transportnode-id}?action=resync_host_config

- Response added with Status Code `504`

POST /transport-nodes/{transportnode-id}

- Response added with Status Code `504`

POST /transport-nodes?action=clean_stale_entries

- Response added with Status Code `504`

GET /transport-nodes

- Response added with Status Code `504`

POST /transport-nodes

- Response added with Status Code `504`

GET /transport-zones/status

- Parameter added: `include_system_owned`
- Response added with Status Code `504`

GET /transport-zones/transport-node-status-report-json

- Response added with Status Code `504`

GET /transport-zones/transport-node-status-report

- Response added with Status Code `504`

GET /transport-zones/transport-node-status

- Parameter added: `node_type`
- Response added with Status Code `504`

GET /transport-zones/{zone-id}/status

- Response added with Status Code `504`

GET /transport-zones/{zone-id}/summary

- Response added with Status Code `504`

GET /transport-zones/{zone-id}/transport-node-status-report-json

- Response added with Status Code `504`

GET /transport-zones/{zone-id}/transport-node-status-report

- Response added with Status Code `504`

GET /transport-zones/{zone-id}/transport-node-status

- Parameter added: `node_type`
- Response added with Status Code `504`

DELETE /transport-zones/{zone-id}

- Response added with Status Code `504`

GET /transport-zones/{zone-id}

- Response added with Status Code `504`

PUT /transport-zones/{zone-id}

- Response added with Status Code `504`

GET /transport-zones

- Response added with Status Code `504`

POST /transport-zones

- Response added with Status Code `504`

DELETE /transportzone-profiles/{transportzone-profile-id}

- Response added with Status Code `504`

GET /transportzone-profiles/{transportzone-profile-id}

- Response added with Status Code `504`

PUT /transportzone-profiles/{transportzone-profile-id}

- Response added with Status Code `504`

GET /transportzone-profiles

- Response added with Status Code `504`

POST /transportzone-profiles

- Response added with Status Code `504`

GET /trust-management/certificate-profile/{service-type}

- Response added with Status Code `504`

GET /trust-management/certificate-profiles

- Response added with Status Code `504`

POST /trust-management/certificates/action/batch-replace

- Response added with Status Code `504`

POST /trust-management/certificates/action/renew-appliance-certificates

- Response added with Status Code `504`

POST /trust-management/certificates/action/replace-host-certificate/{host-id}

- Response added with Status Code `504`

DELETE /trust-management/certificates/batch-results

- Response added with Status Code `504`

GET /trust-management/certificates/batch-results

- Response added with Status Code `504`

POST /trust-management/certificates/{alias}?action=import_trusted_ca

- Response added with Status Code `504`

POST /trust-management/certificates/{cert-id}?action=apply_certificate

- Response added with Status Code `504`

GET /trust-management/certificates/{cert-id}?action=validate

- Response added with Status Code `504`

DELETE /trust-management/certificates/{cert-id}

- Response added with Status Code `504`

GET /trust-management/certificates/{cert-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

POST /trust-management/certificates?action=fetch_peer_certificate_chain

- Response added with Status Code `504`

POST /trust-management/certificates?action=import

- Response added with Status Code `504`

POST /trust-management/certificates?action=set_appliance_proxy_certificate_for_inter_site_communication

- Response added with Status Code `504`

POST /trust-management/certificates?action=set_pi_certificate_for_federation

- Response added with Status Code `504`

GET /trust-management/certificates

- Parameter added: `fmt`
- Response added with Status Code `504`

POST /trust-management/crl-distribution-points/pem-file

- Response added with Status Code `504`

GET /trust-management/crl-distribution-points/{crl-distribution-point-id}/status

- Response added with Status Code `504`

DELETE /trust-management/crl-distribution-points/{crl-distribution-point-id}

- Response added with Status Code `504`

GET /trust-management/crl-distribution-points/{crl-distribution-point-id}

- Response added with Status Code `504`

PUT /trust-management/crl-distribution-points/{crl-distribution-point-id}

- Response added with Status Code `504`

GET /trust-management/crl-distribution-points

- Response added with Status Code `504`

POST /trust-management/crl-distribution-points

- Response added with Status Code `504`

DELETE /trust-management/crls/{crl-id}

- Response added with Status Code `504`

GET /trust-management/crls/{crl-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

PUT /trust-management/crls/{crl-id}

- Response added with Status Code `504`

POST /trust-management/crls?action=import

- Response added with Status Code `504`

GET /trust-management/crls

- Parameter added: `fmt`
- Response added with Status Code `504`

POST /trust-management/csrs-extended

- Response added with Status Code `504`

GET /trust-management/csrs/{csr-id}/pem-file

- Response added with Status Code `504`

POST /trust-management/csrs/{csr-id}?action=import

- Response added with Status Code `504`

POST /trust-management/csrs/{csr-id}?action=self_sign

- Response added with Status Code `504`

DELETE /trust-management/csrs/{csr-id}

- Response added with Status Code `504`

GET /trust-management/csrs/{csr-id}

- Response added with Status Code `504`

POST /trust-management/csrs?action=self_sign

- Response added with Status Code `504`

GET /trust-management/csrs

- Response added with Status Code `504`

POST /trust-management/csrs

- Response added with Status Code `504`

POST /trust-management/oidc-uris/action/configure-vidb-oidc-endpoint

- Response added with Status Code `504`

POST /trust-management/oidc-uris/action/configure-ws1b-oidc-endpoint

- Response added with Status Code `504`

POST /trust-management/oidc-uris/action/remove-ws1b-oidc-endpoint

- Response added with Status Code `504`

POST /trust-management/oidc-uris/action/test-vidb-oidc-endpoint-connection

- Response added with Status Code `504`

GET /trust-management/oidc-uris/{id}/health

- Response added with Status Code `504`

POST /trust-management/oidc-uris/{id}/search

- Response added with Status Code `504`

GET /trust-management/oidc-uris/{id}/user-or-group-exists

- Response added with Status Code `504`

POST /trust-management/oidc-uris/{id}?action=refresh

- Response added with Status Code `504`

GET /trust-management/oidc-uris/{id}

- Response added with Status Code `504`

PUT /trust-management/oidc-uris/{id}

- Response added with Status Code `504`

POST /trust-management/oidc-uris?action=update_thumbprint

- Response added with Status Code `504`

GET /trust-management/oidc-uris

- Response added with Status Code `504`

POST /trust-management/oidc-uris

- Response added with Status Code `504`

POST /trust-management/principal-identities/with-certificate

- Response added with Status Code `504`

DELETE /trust-management/principal-identities/{principal-identity-id}

- Response added with Status Code `504`

GET /trust-management/principal-identities/{principal-identity-id}

- Response added with Status Code `504`

POST /trust-management/principal-identities?action=update_certificate

- Response added with Status Code `504`

GET /trust-management/principal-identities

- Response added with Status Code `504`

POST /trust-management/principal-identities

- Response added with Status Code `504`

GET /trust-management/stale-certificates

- Response added with Status Code `504`

DELETE /trust-management/token-principal-identities/{principal-identity-id}

- Response added with Status Code `504`

GET /trust-management/token-principal-identities/{principal-identity-id}

- Response added with Status Code `504`

GET /trust-management/token-principal-identities

- Response added with Status Code `504`

POST /trust-management/token-principal-identities

- Response added with Status Code `504`

GET /trust-management

- Parameter added: `for_certificate_generation`
- Response added with Status Code `504`

DELETE /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

PUT /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}/widgetconfigurations

- Response added with Status Code `504`

POST /ui-views/{view-id}/widgetconfigurations

- Response added with Status Code `504`

DELETE /ui-views/{view-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}

- Response added with Status Code `504`

PUT /ui-views/{view-id}

- Response added with Status Code `504`

GET /ui-views

- Response added with Status Code `504`

POST /ui-views

- Response added with Status Code `504`

GET /upgrade/available-releases

- Response added with Status Code `504`

GET /upgrade/banners

- Response added with Status Code `504`

GET /upgrade/bundles/{bundle-id}/status

- Response added with Status Code `504`

GET /upgrade/bundles/{bundle-id}/upload-status

- Response added with Status Code `504`

POST /upgrade/bundles/{bundle-id}?action=cancel_upload

- Response added with Status Code `504`

GET /upgrade/bundles/{bundle-id}

- Response added with Status Code `504`

POST /upgrade/bundles?action=upload

- Response added with Status Code `504`

POST /upgrade/bundles

- Response added with Status Code `504`

GET /upgrade/consistency-report

- Response added with Status Code `504`

POST /upgrade/eula/accept

- Response added with Status Code `504`

GET /upgrade/eula/acceptance

- Response added with Status Code `504`

GET /upgrade/eula/content

- Response added with Status Code `504`

POST /upgrade/filter/upgrade-unit-groups

- Response added with Status Code `504`

POST /upgrade/filter/upgrade-units

- Response added with Status Code `504`

GET /upgrade/filterGroups

- Response added with Status Code `504`

GET /upgrade/filterUnits

- Response added with Status Code `504`

GET /upgrade/functional-state

- Response added with Status Code `504`

GET /upgrade/history

- Response added with Status Code `504`

GET /upgrade/nodes-summary

- Response added with Status Code `504`

GET /upgrade/nodes

- Response added with Status Code `504`

GET /upgrade/plan/{component_type}/settings

- Response added with Status Code `504`

PUT /upgrade/plan/{component_type}/settings

- Response added with Status Code `504`

POST /upgrade/plan?action=continue

- Response added with Status Code `504`

POST /upgrade/plan?action=pause

- Response added with Status Code `504`

POST /upgrade/plan?action=reset

- Response added with Status Code `504`

POST /upgrade/plan?action=stage-upgrade

- Response added with Status Code `504`

POST /upgrade/plan?action=start

- Response added with Status Code `504`

POST /upgrade/plan?action=upgrade

- Response added with Status Code `504`

POST /upgrade/plan?action=upgrade_selected_units

- Response added with Status Code `504`

GET /upgrade/pre-upgrade-checks/edge-failover-readiness/config

- Response added with Status Code `504`

PUT /upgrade/pre-upgrade-checks/edge-failover-readiness/config

- Response added with Status Code `504`

GET /upgrade/pre-upgrade-checks/failures

- Response added with Status Code `504`

POST /upgrade/pre-upgrade-checks/host/planned-maintenance

- Response added with Status Code `504`

GET /upgrade/pre-upgrade-checks/success

- Response added with Status Code `504`

POST /upgrade/pre-upgrade-checks/{pre-upgrade-check-id}?action=acknowledge

- Response added with Status Code `504`

POST /upgrade/pre-upgrade-checks/{pre-upgrade-check-id}?action=resolve

- Response added with Status Code `504`

GET /upgrade/pre-upgrade-checks?format=csv

- Response added with Status Code `504`

GET /upgrade/status-summary

- Response added with Status Code `504`

GET /upgrade/summary

- Response added with Status Code `504`

GET /upgrade/uc-bundle-metadata

- Response added with Status Code `504`

GET /upgrade/uc-upgrade-metadata

- Response added with Status Code `504`

GET /upgrade/uc-upgrade-status

- Response added with Status Code `504`

GET /upgrade/ui/preferences

- Response added with Status Code `504`

GET /upgrade/upgrade-checks-info

- Response added with Status Code `504`

GET /upgrade/upgrade-unit-groups-status

- Response added with Status Code `504`

GET /upgrade/upgrade-unit-groups/aggregate-info

- Response added with Status Code `504`

GET /upgrade/upgrade-unit-groups/{group-id}/status

- Response added with Status Code `504`

POST /upgrade/upgrade-unit-groups/{group-id}/upgrade-unit/{upgrade-unit-id}?action=reorder

- Response added with Status Code `504`

POST /upgrade/upgrade-unit-groups/{group-id}?action=add_upgrade_units

- Response added with Status Code `504`

POST /upgrade/upgrade-unit-groups/{group-id}?action=reorder

- Response added with Status Code `504`

DELETE /upgrade/upgrade-unit-groups/{group-id}

- Response added with Status Code `504`

GET /upgrade/upgrade-unit-groups/{group-id}

- Response added with Status Code `504`

PUT /upgrade/upgrade-unit-groups/{group-id}

- Response added with Status Code `504`

GET /upgrade/upgrade-unit-groups

- Response added with Status Code `504`

POST /upgrade/upgrade-unit-groups

- Response added with Status Code `504`

GET /upgrade/upgrade-units-stats

- Response added with Status Code `504`

GET /upgrade/upgrade-units/aggregate-info

- Response added with Status Code `504`

GET /upgrade/upgrade-units/{upgrade-unit-id}

- Response added with Status Code `504`

GET /upgrade/upgrade-units

- Response added with Status Code `504`

GET /upgrade/version-whitelist/{component_type}

- Response added with Status Code `504`

PUT /upgrade/version-whitelist/{component_type}

- Response added with Status Code `504`

GET /upgrade/version-whitelist

- Response added with Status Code `504`

POST /upgrade/{component-type}?action=execute_post_upgrade_checks

- Response added with Status Code `504`

POST /upgrade?action=abort_pre_upgrade_checks

- Response added with Status Code `504`

POST /upgrade?action=execute_pre_upgrade_checks

- Parameter added: `run_only_implicit_pre_checks`
- Parameter added: `run_only_on_enabled_groups`
- Response added with Status Code `504`

POST /upgrade?action=rollback

- Response added with Status Code `504`

POST /upgrade?action=upgrade_uc

- Response added with Status Code `504`

POST /vpn/ipsec/sessions/{sessionid}/statistics?action=reset

- Response added with Status Code `504`

DELETE /watermark

- Response added with Status Code `504`

GET /watermark

- Response added with Status Code `504`

POST /watermark

- Response added with Status Code `504`

PUT /watermark

- Response added with Status Code `504`

Deprecated Operations

VERB	PATH
GET	/global-configs
GET	/global-configs/{config-type}
PUT	/global-configs/{config-type}
PUT	/global-configs/{config-type}?action=resync_config
POST	/licenses
POST	/licenses?action=delete
GET	/lldp/fabric-nodes/{fabric-node-id}/interfaces
GET	/lldp/fabric-nodes/{fabric-node-id}/interfaces/{interface-name}
GET	/lldp/transport-nodes/{node-id}/interfaces
GET	/lldp/transport-nodes/{node-id}/interfaces/{interface-name}
POST	/transport-nodes/{transport-node-id}?action=refresh_node_configuration&resource_type=EdgeNode

Deleted Operations

VERB	PATH
GET	/cluster/{cluster-node-id}/node/users?internal=true
GET	/metric/node/{node-id}/plugin/{plugin-id}
DELETE	/metric/node/{node-id}/plugin/{plugin-id}/data
GET	/metric/node/{node-id}/plugin/{plugin-id}/data
GET	/metric/nodes/plugin/{plugin-id}/data
POST	/mirror-sessions
GET	/mirror-sessions
DELETE	/mirror-sessions/{mirror-session-id}
PUT	/mirror-sessions/{mirror-session-id}
GET	/mirror-sessions/{mirror-session-id}
GET	/mirror-sessions/{mirror-session-id}/mirror-stack-status
POST	/mirror-sessions/{mirror-session-id}?action=verify

VERB	PATH
DELETE	/monitor/node/{node-id}/data
GET	/monitor/node/{node-id}/status
DELETE	/monitor/node/{node-id}/status
GET	/node/users?internal=true
GET	/transport-nodes/{transport-node-id}/node/users?internal=true

Data Structure Changes

New Structures

Structure Name
BootBankVolumeInfo
CryptoEntity
DnsProperties
EdgeNodeServiceLoggingLevelProperties
EdgeNodeServiceReadonlyLoggingLevelProperties
GrpcInfo
HealthCheckClusterScopeFilter
HostKeyProperties
HostResolutionRequest
HostResolutionResponse
LicenseTokenInfo
LicenseTokenInfoListResult
NodeFIPsModuleProperties
NodesPluginQueryParameters
PingReachabilityRequest
PingReachabilityResult
PingReachabilityStatistics
PluginQueryParameters
PolicyTraceflowConnectivityPolicyInfo
PolicyTraceflowObservationForwarded
PolicyTraceflowObservationReceived
PreUpgradeEdgeHealthCheckRequest
RetrieveMatchingHostKeyAlgorithmProperties
SnmpCommunity
SnmpV2Target
SnmpV3Target
StatisticsRoundTripTime
TraceflowVlanExtensionBasicInfo

Structure Name
TraceflowVlanExtensionResultInfo
TransportNodeCollectionSpanAssociations
Zone
ZoneListResult

Updated Structures

AphInfo

- New Property: `ipv6_address`

BgpNeighborRouteDetailsCsvRecord

- New Property: `evpn_route_type`
- New Property: `rd`
- New Property: `rmac_len`
- New Property: `esi`
- New Property: `eth_tag`
- New Property: `rmac`

BgpNeighborStatus

- New Property: `bgp_neighbor_id`
- New Property: `dynamic_bgp_neighbor`

CentralNodeConfigProfile

- New Property: `dns`

ComputeCollection

- New Property: `datacenter_external_id`

CpuStats

- New Property: `busy_pollrounds`
- New Property: `idle_pollrounds`

DataCounter

- New Property: `unknown_unicast`

DirectoryAdDomain

- New Property: `event_log_scraper_enabled`
- New Property: `path`

DirectoryLdapServer

- New Property: `path`

DiscoveredNode

- New Property: `boot_bank_volume_details`

EdgeNodeServiceLoggingProperties

- Updated Property: `service_properties` From `` to `object`

EdgeNodeServiceLoggingReadOnlyProperties

- Updated Property: `service_properties` From `` to `object`

Endpoint

- New Property: `net_stack_instance_key`

FederationConfiguration

- New Property: `is_saas`

FederationSite

- New Property: `export_type`
- New Property: `grpc_info`
- New Property: `is_grpc_capable`

FileTransferProtocol

- New Property: `host_key_algorithm`

HealthCheckResultPerTransportNode

- New Property: `result_status`

HealthCheckResultPerUplink

- New Property: `vlan_allowed`
- New Property: `mtu_allowed`

HostSwitchState

- New Property: `vtepless`
- New Property: `nsx_configured_uplinks`

IPsecVPNIKESessionSummary

- New Property: `negotiating_sessions`

InterSitePortCounters

- New Property: `policy_dropped_packets`

LocalSiteConfiguration

- New Property: `is_saas`

LogicalRouterPortCounters

- New Property: `policy_dropped_packets`

ManualHealthCheck

- New Property: `cluster_scope_filter`

NodeSyslogExporterProperties

- New Property: `enabled`

OidcEndPoint

- Deleted Property: `csp_config`

PhysicalPortStats

- New Property: `rx_drop_no_match`

PolicyTraceflowObservationDroppedLogical

- New Property: `src_connectivity_policy`
- New Property: `dst_connectivity_policy`
- New Property: `next_vpc_path`

PolicyTraceflowObservationForwardedLogical

- New Property: `src_connectivity_policy`
- New Property: `dst_connectivity_policy`

RemoteTunnelEndpoint

- New Property: `net_stack_instance_key`

RemoteTunnelStatisticsPerSite

- New Property: `remote_site_path`

RouteDetails

- New Property: `evpn_route_type`
- New Property: `esi`
- New Property: `rmac`
- New Property: `eth_tag`
- New Property: `rd`
- New Property: `rmac_len`

SecurityGlobalConfig

- New Property: `ndcpp_enabled`

SiteCompatibilityInfo

- New Property: `site_version_full`
- New Property: `export_type`

SnmpServiceProperties

- New Property: `v3_targets`
- New Property: `v2_targets`
- Updated Property: `communities` From `array` to `SnmpCommunity`

SnmpV3User

- New Property: `security_level`
- New Property: `access`

SshServiceProperties

- New Property: `host_keys`
- New Property: `protocol_version`
- New Property: `banner`

StandardHostSwitch

- New Property: `perf_nic_offload`

SyslogExporter

- New Property: `facilities`

TraceflowObservationDelivered

- New Property: `uplink_name`

TraceflowObservationDropped

- New Property: `dst_connectivity_policy_internal_id`
- New Property: `src_connectivity_policy_internal_id`

TraceflowObservationDroppedLogical

- New Property: `next_vpc_id`

TraceflowObservationForwarded

- New Property: `lport_id`
- New Property: `lport_name`

TraceflowObservationForwardedLogical

- New Property: `src_connectivity_policy_internal_id`

- New Property: `lr_forward_type`
- New Property: `vlan_extension_result_info`
- New Property: `dst_connectivity_policy_internal_id`

TraceflowObservationReceived

- New Property: `lport_name`
- New Property: `lport_id`

TraceflowObservationReceivedLogical

- New Property: `vlan_extension_basic_info`

TransportNodeCollection

- New Property: `network_span_paths`

TransportNodeCollectionState

- New Property: `span_associations`

TransportNodeDeploymentProgressState

- New Property: `current_step`

TransportNodeState

- New Property: `network_span_path`

TransportZone

- Deleted Property: `forwarding_mode`

TrustManagementData

- New Property: `approved_ec_curves`
- New Property: `supported_signature_algorithms`

TunnelProperties

- New Property: `remote_node_path`

Deprecated Structures

No changes.

Deleted Structures

Structure Name
CspConfig
PublicCloudGatewayNode

Changelog for NSX NSX Policy API
These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	264	3459	6	9
Structures	232	97	0	1

Total changes: 4186

Operation Changes

New Operations

VERB	PATH
GET	/alb/controller-info/info
GET	/alb/controller-info/info/{controller-id}
DELETE	/alb/controller-info/info/{controller-id}
PUT	/alb/controller-info/info/{controller-id}
POST	/alb/controller-nodes/cloud
POST	/alb/controller-nodes/pki-profile
POST	/alb/controller-nodes/user
PUT	/alb/controller-nodes/user
DELETE	/alb/controller-nodes/user/{username}
POST	/alb/controller-nodes/vcenterserver
DELETE	/alb/controller-nodes/vcenterserver/{vcenter-server-name}
GET	/global-infra/domains/{domain-id}/groups/{group-id}/members/vpcs
POST	/global-infra/firewall-identity-store-event-log-servers/status
POST	/global-infra/firewall-identity-store-ldap-server
POST	/global-infra/firewall-identity-stores/{firewall-identity-store-id}
GET	/global-infra/firewall-identity-stores/{firewall-identity-store-id}/groups
GET	/global-infra/firewall-identity-stores/{firewall-identity-store-id}/org-units
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/groups/{group-id}/children
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/groups/{group-id}/parent-groups
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-els-server-mappings
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-els-server-mappings/{site-mapping-id}
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-ldap-server-mappings
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/site-to-ldap-server-mappings/{site-mapping-id}
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/users

VERB	PATH
GET	/global-infra/identity-firewall-stores/{identity-firewall-store-id}/users/{user-id}/parent-groups
GET	/global-infra/settings/firewall/security/exclude-list/members-count
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures
GET	/global-infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/{sig-id}
GET	/global-infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs
GET	/global-infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/nat/statistics
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors/{neighbor-id}/advertised-routes
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors/{neighbor-id}/routes
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/summary
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/tunnels/statistics
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/remote-tep-connectivity/bgp/summary
GET	/global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/remote-tep-connectivity/status
DELETE	/infra/categories/{category-id}/tags/{tag-id}/attachments
GET	/infra/categories/{category-id}/tags/{tag-id}/attachments
PATCH	/infra/categories/{category-id}/tags/{tag-id}/attachments
GET	/infra/distributed-vxlan-connections
PATCH	/infra/distributed-vxlan-connections/{distributed-vxlan-connection-id}
GET	/infra/distributed-vxlan-connections/{distributed-vxlan-connection-id}
DELETE	/infra/distributed-vxlan-connections/{distributed-vxlan-connection-id}
PUT	/infra/distributed-vxlan-connections/{distributed-vxlan-connection-id}
GET	/infra/domains/{domain-id}/groups/{group-id}/members/vpcs

VERB	PATH
POST	/infra/gateways/action/reallocate
POST	/infra/identity-firewall-stores/action/delta-sync
POST	/infra/identity-firewall-stores/action/full-sync
POST	/infra/identity-firewall-stores/action/stop-sync
POST	/infra/identity-firewall-stores/ldap-servers/action/connectivity-check
GET	/infra/ip-blocks/allocation-state
GET	/infra/ip-blocks/usage
GET	/infra/ip-blocks/{ip-block-id}/allocation-state
GET	/infra/ip-blocks/{ip-block-id}/available-subnets
GET	/infra/network-spans
GET	/infra/network-spans/{span-id}
PUT	/infra/network-spans/{span-id}
PATCH	/infra/network-spans/{span-id}
DELETE	/infra/network-spans/{span-id}
GET	/infra/network-spans/{span-id}/members
GET	/infra/route-controllers
GET	/infra/route-controllers/{route-controller-id}/bgp/neighbors/status
GET	/infra/route-controllers/{route-controller-id}/bgp/neighbors/{neighbor-id}/advertised-routes
GET	/infra/route-controllers/{route-controller-id}/bgp/neighbors/{neighbor-id}/advertised-routes/download
GET	/infra/route-controllers/{route-controller-id}/bgp/neighbors/{neighbor-id}/routes
GET	/infra/route-controllers/{route-controller-id}/bgp/neighbors/{neighbor-id}/routes/download
GET	/infra/route-controllers/{route-controller-id}/forwarding-table
GET	/infra/route-controllers/{route-controller-id}/forwarding-table/download
GET	/infra/route-controllers/{route-controller-id}/interfaces/{interface-id}/statistics
GET	/infra/route-controllers/{route-controller-id}/interfaces/{interface-id}/statistics/summary
GET	/infra/route-controllers/{route-controller-id}/routing-table

VERB	PATH
GET	/infra/route-controllers/{route-controller-id}/routing-table/download
GET	/infra/route-controllers/{route-controller-id}/state
DELETE	/infra/route-controllers/{router-controller-id}
GET	/infra/route-controllers/{router-controller-id}
PUT	/infra/route-controllers/{router-controller-id}
PATCH	/infra/route-controllers/{router-controller-id}
GET	/infra/route-controllers/{router-controller-id}/bgp
PATCH	/infra/route-controllers/{router-controller-id}/bgp
DELETE	/infra/route-controllers/{router-controller-id}/bgp
PUT	/infra/route-controllers/{router-controller-id}/bgp
GET	/infra/route-controllers/{router-controller-id}/bgp/neighbors
PATCH	/infra/route-controllers/{router-controller-id}/bgp/neighbors/{neighbor-id}
DELETE	/infra/route-controllers/{router-controller-id}/bgp/neighbors/{neighbor-id}
GET	/infra/route-controllers/{router-controller-id}/bgp/neighbors/{neighbor-id}
PUT	/infra/route-controllers/{router-controller-id}/bgp/neighbors/{neighbor-id}
GET	/infra/route-controllers/{router-controller-id}/bgp/troubleshoot
PUT	/infra/route-controllers/{router-controller-id}/bgp/troubleshoot
PATCH	/infra/route-controllers/{router-controller-id}/bgp/troubleshoot
DELETE	/infra/route-controllers/{router-controller-id}/bgp/troubleshoot
GET	/infra/route-controllers/{router-controller-id}/interfaces
PUT	/infra/route-controllers/{router-controller-id}/interfaces/{interface-id}
GET	/infra/route-controllers/{router-controller-id}/interfaces/{interface-id}
DELETE	/infra/route-controllers/{router-controller-id}/interfaces/{interface-id}
PATCH	/infra/route-controllers/{router-controller-id}/interfaces/{interface-id}
PATCH	/infra/settings/advanced-security-configuration
PUT	/infra/settings/advanced-security-configuration

VERB	PATH
GET	/infra/settings/advanced-security-configuration
GET	/infra/settings/firewall/security/exclude-list/members-count
GET	/infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}/signatures/{sig-id}
GET	/infra/settings/firewall/security/intrusion-services/signatures/vtis-bundle-status
GET	/infra/settings/scrx/cluster-configs
PATCH	/infra/settings/scrx/cluster-configs/{cluster-id}
PUT	/infra/settings/scrx/cluster-configs/{cluster-id}
GET	/infra/settings/scrx/cluster-configs/{cluster-id}
GET	/infra/settings/scrx/default-scrxsize
GET	/infra/settings/security/cluster-configs
GET	/infra/settings/security/cluster-configs/{cluster-external-id}
PUT	/infra/settings/security/cluster-configs/{cluster-external-id}
PATCH	/infra/settings/security/cluster-configs/{cluster-external-id}
POST	/infra/settings/security/host-configuration-report
POST	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-transport-nodes/{edge-transport-node-id}/action/sync-edge-configuration
GET	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-transport-nodes/{node-id}/lldp/interfaces
GET	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-transport-nodes/{node-id}/lldp/interfaces/{interface-name}
GET	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-transport-nodes/{node-id}/tunnels
GET	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-transport-nodes/{node-id}/tunnels/{tunnel-name}
GET	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps
PUT	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
PATCH	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
GET	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
DELETE	/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/nat/statistics

VERB	PATH
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors/{neighbor-id}/advertised-routes
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/neighbors/{neighbor-id}/routes
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/bgp/summary
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{policy-edge-node-id}/remote-tep-connectivity/tunnels/statistics
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/remote-tep-connectivity/bgp/summary
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/remote-tep-connectivity/status
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{node-id}/nat/statistics
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}/spans
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters
PUT	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}
PATCH	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}
DELETE	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/allocation/status
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/state
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/status
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}
PUT	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}
PATCH	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}
DELETE	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}
POST	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}/action/enter-maintenance-mode

VERB	PATH
POST	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}/action/evacuate
POST	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}/action/exit-maintenance-mode
POST	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}/action/redeploy
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/virtual-network-appliance-clusters/{virtual-network-appliance-cluster-id}/virtual-network-appliances/{virtual-network-appliance-id}/state
GET	/infra/ssp/registration
GET	/infra/ssp/registration/{cluster-id}
GET	/infra/third-party-ipam-providers
PUT	/infra/third-party-ipam-providers/{provider-instance-id}
PATCH	/infra/third-party-ipam-providers/{provider-instance-id}
DELETE	/infra/third-party-ipam-providers/{provider-instance-id}
GET	/infra/third-party-ipam-providers/{provider-instance-id}
GET	/infra/third-party-ipam-providers/{provider-instance-id}/connection-status
POST	/infra/third-party-ipam-providers/{provider-instance-id}/dns-records-sync
POST	/infra/third-party-ipam-providers/{provider-instance-id}/ip-cidrs
GET	/infra/third-party-ipam-providers/{provider-instance-id}/version
GET	/infra/third-party-ipam-providers/{provider-instance-id}/views
POST	/infra/tier-0s/{tier-0-id}/actions/failover
POST	/infra/tier-1s/{tier-1-id}/actions/failover
GET	/infra/zones/{zone-id}/members
POST	/licenses/action/async-query
GET	/licenses/action/async-query/status
DELETE	/orgs/{org-id}/projects/{project-id}/infra/categories/{category-id}/tags/{tag-id}/attachments
PATCH	/orgs/{org-id}/projects/{project-id}/infra/categories/{category-id}/tags/{tag-id}/attachments
GET	/orgs/{org-id}/projects/{project-id}/infra/categories/{category-id}/tags/{tag-id}/attachments
GET	/orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/vpcs

VERB	PATH
POST	/orgs/{org-id}/projects/{project-id}/infra/gateways/action/reallocate
GET	/orgs/{org-id}/projects/{project-id}/infra/ip-blocks/allocation-state
GET	/orgs/{org-id}/projects/{project-id}/infra/ip-blocks/usage
GET	/orgs/{org-id}/projects/{project-id}/infra/ip-blocks/{ip-block-id}/allocation-state
PUT	/orgs/{org-id}/projects/{project-id}/infra/settings/advanced-security-configuration
PATCH	/orgs/{org-id}/projects/{project-id}/infra/settings/advanced-security-configuration
GET	/orgs/{org-id}/projects/{project-id}/infra/settings/advanced-security-configuration
GET	/orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}/signatures/{sig-id}
GET	/orgs/{org-id}/projects/{project-id}/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps
DELETE	/orgs/{org-id}/projects/{project-id}/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
PATCH	/orgs/{org-id}/projects/{project-id}/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
PUT	/orgs/{org-id}/projects/{project-id}/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
GET	/orgs/{org-id}/projects/{project-id}/infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{host-transport-node-id}/transport-node-monitoring-profile-binding-maps/{binding-map-id}
POST	/orgs/{org-id}/projects/{project-id}/infra/third-party-ipam-providers/{provider-instance-id}/dns-records-sync
POST	/orgs/{org-id}/projects/{project-id}/infra/tier-0s/{tier-0-id}/actions/failover
POST	/orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/actions/failover
GET	/orgs/{org-id}/projects/{project-id}/security-profile-attachments
PUT	/orgs/{org-id}/projects/{project-id}/security-profile-attachments/{security-profile-attachment-id}
GET	/orgs/{org-id}/projects/{project-id}/security-profile-attachments/{security-profile-attachment-id}
PATCH	/orgs/{org-id}/projects/{project-id}/security-profile-attachments/{security-profile-attachment-id}
GET	/orgs/{org-id}/projects/{project-id}/security-strategies
GET	/orgs/{org-id}/projects/{project-id}/security-strategies/{security-strategy-id}
GET	/orgs/{org-id}/projects/{project-id}/state
POST	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/actions/failover
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{attachment-id}/state/interfaces

VERB	PATH
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{attachment-id}/state/interfaces/{interface-id}/statistics
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/centralized-configs
PATCH	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/centralized-configs/{centralized-config-id}
PUT	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/centralized-configs/{centralized-config-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/centralized-configs/{centralized-config-id}
DELETE	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/centralized-configs/{centralized-config-id}
POST	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/connected-vpcs
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/connectivity-policies
PUT	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/connectivity-policies/{connectivity-policy-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/connectivity-policies/{connectivity-policy-id}
DELETE	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/connectivity-policies/{connectivity-policy-id}
PATCH	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/connectivity-policies/{connectivity-policy-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services
PUT	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}
DELETE	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}
PATCH	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/local-endpoints
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/local-endpoints/{local-endpoint-id}
PUT	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/local-endpoints/{local-endpoint-id}
PATCH	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/local-endpoints/{local-endpoint-id}
DELETE	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/local-endpoints/{local-endpoint-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/sessions
DELETE	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/sessions/{session-id}

VERB	PATH
PUT	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/sessions/{session-id}
PATCH	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/sessions/{session-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/sessions/{session-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/sessions/{session-id}/peer-config
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{ipsec-vpn-service-id}/sessions/{session-id}?action=show_sensitive_data
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics
POST	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/ipsec-vpn-services/{service-id}/summary
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/security-config
PUT	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/security-config
PATCH	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/security-config
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/static-routes
DELETE	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/static-routes/{route-id}
PUT	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/static-routes/{route-id}
PATCH	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/static-routes/{route-id}
GET	/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/static-routes/{route-id}
POST	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/actions/failover
PATCH	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/categories/{category-id}/tags/{tag-id}/attachments
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/categories/{category-id}/tags/{tag-id}/attachments
DELETE	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/categories/{category-id}/tags/{tag-id}/attachments
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-blocks/allocation-state
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-blocks/usage
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-connections
PUT	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-connections/{bridge-connection-id}

VERB	PATH
DELETE	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-connections/{bridge-connection-id}
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-connections/{bridge-connection-id}
PATCH	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-connections/{bridge-connection-id}
PATCH	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profile
PUT	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profile
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profile
DELETE	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profile
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dynamic-ip-reservations
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dynamic-ip-reservations/{dynamic-ip-reservation-id}
PATCH	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dynamic-ip-reservations/{dynamic-ip-reservation-id}
PUT	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dynamic-ip-reservations/{dynamic-ip-reservation-id}
DELETE	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dynamic-ip-reservations/{dynamic-ip-reservation-id}
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/state
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/state/dhcp-server-managed-ports
PATCH	/system-config/auto-reject-ip-options-gateway-firewall
GET	/system-config/auto-reject-ip-options-gateway-firewall

Updated Operations

GET /aaa/features-with-properties

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources/{ldap-identity-source-id}/search

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources/{ldap-identity-source-id}?action=probe

- Response added with Status Code `504`

DELETE /aaa/ldap-identity-sources/{ldap-identity-source-id}

- Response added with Status Code `504`

GET /aaa/ldap-identity-sources/{ldap-identity-source-id}

- Response added with Status Code `504`

PUT /aaa/ldap-identity-sources/{ldap-identity-source-id}

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources?action=fetch_certificate

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources?action=probe_identity_source

- Response added with Status Code `504`

POST /aaa/ldap-identity-sources?action=probe_ldap_server

- Response added with Status Code `504`

GET /aaa/ldap-identity-sources

- Response added with Status Code `504`

DELETE /aaa/object-permissions

- Response added with Status Code `504`

GET /aaa/object-permissions

- Response added with Status Code `504`

PATCH /aaa/object-permissions

- Response added with Status Code `504`

POST /aaa/registration-token/delete

- Response added with Status Code `504`

POST /aaa/registration-token/retrieve

- Response added with Status Code `504`

DELETE /aaa/registration-token/{token}

- Response added with Status Code `504`

GET /aaa/registration-token/{token}

- Response added with Status Code `504`

POST /aaa/registration-token

- Response added with Status Code `504`

DELETE /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

GET /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

PUT /aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

POST /aaa/role-bindings?action=delete_stale_bindings

- Response added with Status Code `504`

GET /aaa/role-bindings

- Response added with Status Code `504`

POST /aaa/role-bindings

- Response added with Status Code `504`

GET /aaa/roles-with-feature-permissions

- Response added with Status Code `504`

PUT /aaa/roles/{role}/role-assignment-permission-config

- Response added with Status Code `504`

POST /aaa/roles/{role}?action=clone

- Response added with Status Code `504`

DELETE /aaa/roles/{role}

- Response added with Status Code `504`

GET /aaa/roles/{role}

- Response added with Status Code `504`

PUT /aaa/roles/{role}

- Response added with Status Code `504`

POST /aaa/roles?action=validate

- Response added with Status Code `504`

GET /aaa/roles

- Response added with Status Code `504`

GET /aaa/user-info

- Response added with Status Code `504`

GET /aaa/vidm/groups

- Response added with Status Code `504`

POST /aaa/vidm/search

- Response added with Status Code `504`

GET /aaa/vidm/users

- Response added with Status Code `504`

POST /alb/controller-nodes/certificate/csr

- Response added with Status Code `504`

POST /alb/controller-nodes/certificate/install

- Response added with Status Code `504`

PUT /alb/controller-nodes/check-password

- Response added with Status Code `504`

GET /alb/controller-nodes/cluster

- Response added with Status Code `504`

PUT /alb/controller-nodes/cluster

- Response added with Status Code `504`

DELETE /alb/controller-nodes/clusterconfig

- Response added with Status Code `504`

GET /alb/controller-nodes/clusterconfig

- Response added with Status Code `504`

POST /alb/controller-nodes/clusterconfig

- Response added with Status Code `504`

GET /alb/controller-nodes/deployments/{node-id}/status

- Response added with Status Code `504`

POST /alb/controller-nodes/deployments/{node-id}?action=delete

- Response added with Status Code `504`

GET /alb/controller-nodes/deployments/{node-id}

- Response added with Status Code `504`

PUT /alb/controller-nodes/deployments/{node-id}

- Response added with Status Code `504`

GET /alb/controller-nodes/deployments

- Response added with Status Code `504`

POST /alb/controller-nodes/deployments

- Response added with Status Code `504`

GET /alb/controller-nodes/form-factors

- Response added with Status Code `504`

PUT /alb/controller-nodes/system-configuration

- Response added with Status Code `504`

DELETE /alb/controller-nodes/user-credential/{username}

- Response added with Status Code `504`

POST /alb/controller-nodes/user-credential

- Response added with Status Code `504`

PUT /alb/controller-nodes/user-credential

- Response added with Status Code `504`

POST /api/session/create

- Response added with Status Code `504`

POST /api/session/destroy

- Response added with Status Code `504`

POST /batch

- Response added with Status Code `504`

GET /cluster/api-service

- Response added with Status Code `504`

PUT /cluster/api-service

- Response added with Status Code `504`

GET /cluster/backups/config

- Response added with Status Code `504`

PUT /cluster/backups/config

- Response added with Status Code `504`

GET /cluster/backups/history

- Response added with Status Code `504`

GET /cluster/backups/overview

- Response added with Status Code `504`

GET /cluster/backups/status

- Response added with Status Code `504`

POST /cluster/backups?action=retrieve_ssh_fingerprint

- Response added with Status Code `504`

POST /cluster/restore/action/retry_with_updated_config

- Response added with Status Code `504`

GET /cluster/restore/backuptimestamps

- Response added with Status Code `504`

GET /cluster/restore/config

- Response added with Status Code `504`

PUT /cluster/restore/config

- Response added with Status Code `504`

GET /cluster/restore/instruction-resources

- Response added with Status Code `504`

POST /cluster/restore?action=advance

- Response added with Status Code `504`

POST /cluster/restore?action=cancel

- Response added with Status Code `504`

POST /cluster/restore?action=retry

- Response added with Status Code `504`

POST /cluster/restore?action=start

- Response added with Status Code `504`

POST /cluster/restore?action=suspend

- Response added with Status Code `504`

POST /cluster?action=backup_to_remote

- Response added with Status Code `504`

POST /cluster?action=summarize_inventory_to_remote

- Response added with Status Code `504`

GET /compliance/status

- Response added with Status Code `504`

GET /configs/management

- Response added with Status Code `504`

PUT /configs/management

- Response added with Status Code `504`

DELETE /enforcement-points/{enforcement-point-id}/service-definitions/{service-definition-id}

- Response added with Status Code `504`

GET /enforcement-points/{enforcement-point-id}/service-definitions/{service-definition-id}

- Response added with Status Code `504`

PUT /enforcement-points/{enforcement-point-id}/service-definitions/{service-definition-id}

- Response added with Status Code `504`

GET /enforcement-points/{enforcement-point-id}/service-definitions

- Response added with Status Code `504`

POST /enforcement-points/{enforcement-point-id}/service-definitions

- Response added with Status Code `504`

GET /error-resolver/{error_id}

- Response added with Status Code `504`

POST /error-resolver?action=resolve_error

- Response added with Status Code `504`

GET /error-resolver

- Response added with Status Code `504`

POST /eula/accept

- Response added with Status Code `504`

GET /eula/acceptance

- Response added with Status Code `504`

GET /eula/content

- Response added with Status Code `504`

GET /fine-tuning/resources

- Response added with Status Code `504`

DELETE /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

GET /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

PUT /global-infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

GET /global-infra/bfd-profiles

- Response added with Status Code `504`

GET /global-infra/bms-group-associations

- Response added with Status Code `504`

GET /global-infra/bmsi-group-associations

- Response added with Status Code `504`

GET /global-infra/certificates/{certificate-id}

- Parameter added: `fmt`

- Response added with Status Code `504`

GET /global-infra/certificates

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /global-infra/cloud-native-service-group-associations

- Response added with Status Code `504`

GET /global-infra/constraint-global-config

- Response added with Status Code `504`

PATCH /global-infra/constraint-global-config

- Response added with Status Code `504`

PUT /global-infra/constraint-global-config

- Response added with Status Code `504`

GET /global-infra/constraints/{constraint-id}

- Response added with Status Code `504`

GET /global-infra/constraints

- Response added with Status Code `504`

GET /global-infra/context-profiles/attributes

- Response added with Status Code `504`

GET /global-infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /global-infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

POST /global-infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /global-infra/context-profiles/custom-attributes

- Response added with Status Code `504`

POST /global-infra/context-profiles/custom-attributes

- Response added with Status Code `504`

DELETE /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PUT /global-infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /global-infra/context-profiles

- Parameter added: `has_unsupported_app_ids`

- Response added with Status Code `504`

GET /global-infra/crls/{crl-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /global-infra/crls

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /global-infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

GET /global-infra/dhcp-relay-configs

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/leases

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/state

- Response added with Status Code `504`

POST /global-infra/dhcp-server-configs/{config-id}/stats?action=reset

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/stats

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{config-id}/status

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

GET /global-infra/dhcp-server-configs

- Response added with Status Code `504`

GET /global-infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

GET /global-infra/dns-forwarder-zones

- Response added with Status Code `504`

DELETE /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PUT /global-infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/dns-security-profiles

- Response added with Status Code `504`

GET /global-infra/domains/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/domain-deployment-maps

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/gateway-policies

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/member-types

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/bms

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/bmsi

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/cloud-native-service-instances

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/consolidated-effective-ip-addresses

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/dvpg

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/dvports

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/ip-addresses

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/ip-groups

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/logical-ports

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/logical-switches

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/pods

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/segment-ports

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/segments

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/vifs

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/members/virtual-machines

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}/tags

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/groups

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-gateway-policies

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/intrusion-service-policies

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/rules

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}/statistics

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}/security-policies

- Response added with Status Code `504`

GET /global-infra/domains/{domain-id}

- Response added with Status Code `504`

GET /global-infra/domains

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}/aggregated

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}/aggregated_with_pagination

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}/complete

- Response added with Status Code `504`

POST /global-infra/drafts/{draft-id}?action=publish

- Response added with Status Code `504`

DELETE /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

PATCH /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

PUT /global-infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /global-infra/drafts

- Response added with Status Code `504`

GET /global-infra/federation-config

- Response added with Status Code `504`

GET /global-infra/firewall-identity-stores/{firewall-identity-store-id}/sync-stats

- Response added with Status Code `504`

GET /global-infra/firewall-ip-reputation-feed

- Response added with Status Code `504`

POST /global-infra/firewall-ip-reputation-feed

- Response added with Status Code `504`

GET /global-infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

GET /global-infra/firewall-schedulers

- Response added with Status Code `504`

DELETE /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PUT /global-infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /global-infra/firewall-session-timer-profiles

- Response added with Status Code `504`

GET /global-infra/firewall/policies

- Response added with Status Code `504`

GET /global-infra/firewall/rules

- Response added with Status Code `504`

GET /global-infra/flood-protection-profiles/{flood-protection-profile-id}/bindings

- Response added with Status Code `504`

DELETE /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PUT /global-infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /global-infra/flood-protection-profiles

- Response added with Status Code `504`

GET /global-infra/full-sync-states/{full-sync-id}

- Response added with Status Code `504`

GET /global-infra/full-sync-states

- Response added with Status Code `504`

DELETE /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /global-infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/gateway-qos-profiles

- Response added with Status Code `504`

GET /global-infra/global-manager-config?action=show-sensitive-data

- Response added with Status Code `504`

GET /global-infra/global-managers/{global-manager-id}

- Response added with Status Code `504`

GET /global-infra/global-managers

- Response added with Status Code `504`

GET /global-infra/group-associations

- Response added with Status Code `504`

GET /global-infra/group-service-associations

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

GET /global-infra/identity-firewall-stores

- Response added with Status Code `504`

GET /global-infra/ip-address-group-associations

- Response added with Status Code `504`

DELETE /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PUT /global-infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/ip-discovery-profiles

- Response added with Status Code `504`

GET /global-infra/ip-reputation-site-mappings/{mapping-id}

- Response added with Status Code `504`

GET /global-infra/ip-reputation-site-mappings

- Response added with Status Code `504`

DELETE /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PUT /global-infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-dad-profiles

- Response added with Status Code `504`

DELETE /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PUT /global-infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /global-infra/ipv6-ndra-profiles

- Response added with Status Code `504`

GET /global-infra/labels/{label-id}

- Response added with Status Code `504`

GET /global-infra/labels

- Response added with Status Code `504`

DELETE /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PUT /global-infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /global-infra/mac-discovery-profiles

- Response added with Status Code `504`

GET /global-infra/metadata-proxies/{metadata-proxy-id}/statistics

- Response added with Status Code `504`

GET /global-infra/metadata-proxies/{metadata-proxy-id}/status

- Response added with Status Code `504`

GET /global-infra/pod-group-associations

- Response added with Status Code `504`

DELETE /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /global-infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /global-infra/qos-profiles

- Response added with Status Code `504`

GET /global-infra/realized-state/realized-entities

- Response added with Status Code `504`

POST /global-infra/realized-state/realized-entity?action=refresh

- Response added with Status Code `504`

GET /global-infra/realized-state/status

- Response added with Status Code `504`

GET /global-infra/security-global-config

- Response added with Status Code `504`

PUT /global-infra/security-global-config

- Response added with Status Code `504`

DELETE /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PUT /global-infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /global-infra/segment-security-profiles

- Response added with Status Code `504`

GET /global-infra/segments/state

- Response added with Status Code `504`

DELETE /global-infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/arp-table

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/inter-site-forwarder/site-span-info

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/inter-site-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/inter-site-forwarder/status

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

DELETE /global-infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PATCH /global-infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PUT /global-infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/ports

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}/tep-table

- Response added with Status Code `504`

GET /global-infra/segments/{segment-id}

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/state

- Response added with Status Code `504`

GET /global-infra/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /global-infra/segments

- Response added with Status Code `504`

GET /global-infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

GET /global-infra/services/{service-id}/service-entries

- Response added with Status Code `504`

GET /global-infra/services/{service-id}

- Response added with Status Code `504`

GET /global-infra/services

- Response added with Status Code `504`

GET /global-infra/session-timer-profiles/{session-timer-profile-id}/bindings

- Response added with Status Code `504`

GET /global-infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

PUT /global-infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/cpu-mem-thresholds-profiles

- Response added with Status Code `504`

POST /global-infra/settings/firewall/export?action=cancel

- Response added with Status Code `504`

GET /global-infra/settings/firewall/export?action=download

- Response added with Status Code `504`

GET /global-infra/settings/firewall/export

- Response added with Status Code `504`

POST /global-infra/settings/firewall/export

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/group-vm-details

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/system-stats

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/user-session-data

- Response added with Status Code `504`

GET /global-infra/settings/firewall/idfw/vm-stats/{vm-id}

- Response added with Status Code `504`

POST /global-infra/settings/firewall/import?action=cancel

- Response added with Status Code `504`

GET /global-infra/settings/firewall/import

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/exclude-list?action=filter

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/exclude-list?system_owned=true

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/exclude-list

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/gsm/global-signatures/{signature-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/gsm/global-signatures

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/pcaps/export

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/pcaps/{file-name}/download

- Response added with Status Code `504`

DELETE /global-infra/settings/firewall/security/intrusion-services/pcaps/{id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/pcaps

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/profiles/{profile-id}/effective-signatures

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/profiles

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}/signatures

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/site-version-mappings/{mapping-id}

- Response added with Status Code `504`

GET /global-infra/settings/firewall/security/intrusion-services/site-version-mappings

- Response added with Status Code `504`

POST /global-infra/settings/firewall/security/intrusion-services/stats?action=reset

- Response added with Status Code `504`

POST /global-infra/settings/firewall/stats?action=reset

- Response added with Status Code `504`

GET /global-infra/sha/dynamic-plugins/{plugin-id}

- Response added with Status Code `504`

GET /global-infra/sha/dynamic-plugins

- Response added with Status Code `504`

GET /global-infra/sha/plugin-profiles/{sha-profile-id}

- Response added with Status Code `504`

GET /global-infra/sha/plugin-profiles

- Response added with Status Code `504`

GET /global-infra/sha/plugin-status/{node-id}

- Response added with Status Code `504`

GET /global-infra/sha/pre-defined-plugins/{plugin-id}

- Response added with Status Code `504`

GET /global-infra/sha/pre-defined-plugins

- Response added with Status Code `504`

GET /global-infra/sites/listener_certificate

- Response added with Status Code `504`

GET /global-infra/sites/settings/firewall/security

- Response added with Status Code `504`

DELETE /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

PUT /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/allocation/status

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{edge-node-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/status

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/enforcement-points

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/security-setting

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}/settings/firewall/security

- Response added with Status Code `504`

GET /global-infra/sites/{site-id}

- Response added with Status Code `504`

GET /global-infra/sites

- Response added with Status Code `504`

GET /global-infra/span

- Response added with Status Code `504`

DELETE /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PATCH /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PUT /global-infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /global-infra/spoofguard-profiles

- Response added with Status Code `504`

GET /global-infra/tags/effective-resources

- Response added with Status Code `504`

GET /global-infra/tags

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/arp-proxies?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/arp-proxies

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/community-lists

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/nslookup

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder/status

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

POST /global-infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/forwarding-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/forwarding-table

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/gateway-firewall

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/groups/{group-id}/members/ip-addresses

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/groups/{group-id}/members/virtual-machines

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/groups/{group-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/groups

- Response added with Status Code `504`

POST /global-infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/arp-proxies

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/status

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/advertised-routes?format=csv

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/advertised-routes

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/routes?format=csv

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/routes

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/troubleshoot

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/troubleshoot

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/troubleshoot

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{interface-group-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/dad-state

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

DELETE /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/gateway-firewall

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/locale-services

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/nat

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/number-of-routes

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/prefix-lists

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/route-maps

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/routing-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/routing-table

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/state

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/troubleshoot

- Response added with Status Code `504`

PATCH /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/troubleshoot

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/troubleshoot

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes/bfd-peers

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

PUT /global-infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/static-routes

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}/tier-1-interface/statistics

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-0s

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/advertised-networks/csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/advertised-networks

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/arp-proxies?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/arp-proxies

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/nslookup

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder/status

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

POST /global-infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/forwarding-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/forwarding-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/gateway-firewall

- Response added with Status Code `504`

POST /global-infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/arp-proxies

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{interface-group-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/dad-state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/gateway-firewall

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/inter-site-forwarder/status

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/locale-services

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/nat

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/bep-statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/bep-status

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/inter-site-forwarder/site-span-info

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/inter-site-forwarder/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/inter-site-forwarder/status

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

DELETE /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PATCH /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PUT /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/segments

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/state

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/static-routes

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table?format=csv

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/statistics/summary

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}/tier-0-interface/statistics

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /global-infra/tier-1s

- Response added with Status Code `504`

DELETE /global-infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /global-infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /global-infra/traceflows

- Response added with Status Code `504`

GET /global-infra/transport-zone-profiles/{tz-profile-id}

- Response added with Status Code `504`

GET /global-infra/transport-zone-profiles

- Response added with Status Code `504`

GET /global-infra/virtual-machine-group-associations

- Response added with Status Code `504`

GET /global-infra/virtual-network-interface-group-associations

- Response added with Status Code `504`

GET /global-infra/vm-tag-replication-policies/{id}

- Response added with Status Code `504`

GET /global-infra/vm-tag-replication-policies

- Response added with Status Code `504`

GET /global-infra

- Response added with Status Code `504`

PATCH /global-infra

- Response added with Status Code `504`

PUT /infra/alb-auth-token

- Response added with Status Code `504`

DELETE /infra/alb-onboarding-workflow/{managed-by}

- Response added with Status Code `504`

PUT /infra/alb-onboarding-workflow

- Response added with Status Code `504`

GET /infra/antrea/traceflows/{traceflow-id}/observations

- Response added with Status Code `504`

GET /infra/antrea/traceflows/{traceflow-id}/status

- Response added with Status Code `504`

DELETE /infra/antrea/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /infra/antrea/traceflows/{traceflow-id}

- Response added with Status Code `504`

PATCH /infra/antrea/traceflows/{traceflow-id}

- Response added with Status Code `504`

POST /infra/antrea/traceflows/{traceflow-id}

- Response added with Status Code `504`

PUT /infra/antrea/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /infra/antrea/traceflows

- Response added with Status Code `504`

GET /infra/auto-health-check-toggle

- Response added with Status Code `504`

PUT /infra/auto-health-check-toggle

- Response added with Status Code `504`

GET /infra/auto-health-checks

- Response added with Status Code `504`

POST /infra/baremetal-server-interfaces/tags

- Response added with Status Code `504`

POST /infra/baremetal-servers/tags

- Response added with Status Code `504`

DELETE /infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

GET /infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

PATCH /infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

PUT /infra/bfd-profiles/{bfd-profile-id}

- Response added with Status Code `504`

GET /infra/bfd-profiles

- Response added with Status Code `504`

GET /infra/bms-group-associations

- Response added with Status Code `504`

GET /infra/bmsi-group-associations

- Response added with Status Code `504`

GET /infra/cabundles/{cabundle-id}/pem-file

- Response added with Status Code `504`

DELETE /infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

GET /infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

PATCH /infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

POST /infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

PUT /infra/cabundles/{cabundle-id}

- Response added with Status Code `504`

GET /infra/cabundles

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /infra/capacity/dashboard/usage

- Response added with Status Code `504`

GET /infra/capacity/threshold

- Response added with Status Code `504`

PATCH /infra/capacity/threshold

- Response added with Status Code `504`

PUT /infra/capacity/threshold

- Response added with Status Code `504`

GET /infra/capacity/usage

- Response added with Status Code `504`

DELETE /infra/certificates/{certificate-id}

- Response added with Status Code `504`

GET /infra/certificates/{certificate-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

PATCH /infra/certificates/{certificate-id}

- Response added with Status Code `504`

PUT /infra/certificates/{certificate-id}

- Response added with Status Code `504`

GET /infra/certificates

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /infra/cloud-native-service-group-associations

- Response added with Status Code `504`

GET /infra/connectivity-global-config

- Response added with Status Code `504`

PATCH /infra/connectivity-global-config

- Response added with Status Code `504`

PUT /infra/connectivity-global-config

- Response added with Status Code `504`

GET /infra/constraint-global-config

- Response added with Status Code `504`

PATCH /infra/constraint-global-config

- Response added with Status Code `504`

PUT /infra/constraint-global-config

- Response added with Status Code `504`

DELETE /infra/constraints/{constraint-id}

- Response added with Status Code `504`

GET /infra/constraints/{constraint-id}

- Response added with Status Code `504`

PATCH /infra/constraints/{constraint-id}

- Response added with Status Code `504`

PUT /infra/constraints/{constraint-id}

- Response added with Status Code `504`

GET /infra/constraints

- Response added with Status Code `504`

GET /infra/context-profiles/attribute-types

- Response added with Status Code `504`

GET /infra/context-profiles/attributes

- Response added with Status Code `504`

GET /infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

POST /infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /infra/context-profiles/custom-attributes

- Response added with Status Code `504`

POST /infra/context-profiles/custom-attributes

- Response added with Status Code `504`

DELETE /infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PATCH /infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PUT /infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /infra/context-profiles

- Parameter added: `has_unsupported_app_ids`
- Response added with Status Code `504`

POST /infra/crls/{crl-id}?action=import

- Response added with Status Code `504`

POST /infra/crls/{crl-id}?action=upload

- Response added with Status Code `504`

DELETE /infra/crls/{crl-id}

- Response added with Status Code `504`

GET /infra/crls/{crl-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

PATCH /infra/crls/{crl-id}

- Response added with Status Code `504`

PUT /infra/crls/{crl-id}

- Response added with Status Code `504`

GET /infra/crls

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /infra/csrs/{csr-id}/pem-file

- Response added with Status Code `504`

POST /infra/csrs/{csr-id}?action=create

- Response added with Status Code `504`

POST /infra/csrs/{csr-id}?action=import

- Response added with Status Code `504`

POST /infra/csrs/{csr-id}?action=self_sign

- Response added with Status Code `504`

POST /infra/csrs/{csr-id}?action=upload

- Response added with Status Code `504`

DELETE /infra/csrs/{csr-id}

- Response added with Status Code `504`

GET /infra/csrs/{csr-id}

- Response added with Status Code `504`

POST /infra/csrs?action=self_sign

- Response added with Status Code `504`

GET /infra/csrs

- Response added with Status Code `504`

DELETE /infra/deployment-zones/{deployment-zone-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

GET /infra/deployment-zones/{deployment-zone-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

PATCH /infra/deployment-zones/{deployment-zone-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

PUT /infra/deployment-zones/{deployment-zone-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

GET /infra/deployment-zones/{deployment-zone-id}/enforcement-points

- Response added with Status Code `504`

GET /infra/deployment-zones/{deployment-zone-id}

- Response added with Status Code `504`

GET /infra/deployment-zones

- Response added with Status Code `504`

DELETE /infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

GET /infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

PATCH /infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

PUT /infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

GET /infra/dhcp-relay-configs

- Response added with Status Code `504`

GET /infra/dhcp-server-configs/{config-id}/leases

- Response added with Status Code `504`

GET /infra/dhcp-server-configs/{config-id}/state

- Response added with Status Code `504`

POST /infra/dhcp-server-configs/{config-id}/stats?action=reset

- Response added with Status Code `504`

GET /infra/dhcp-server-configs/{config-id}/stats

- Response added with Status Code `504`

GET /infra/dhcp-server-configs/{config-id}/status

- Response added with Status Code `504`

DELETE /infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

GET /infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

PATCH /infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

PUT /infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

GET /infra/dhcp-server-configs

- Response added with Status Code `504`

DELETE /infra/distributed-vlan-connections/{distributed-vlan-connection-id}

- Response added with Status Code `504`

GET /infra/distributed-vlan-connections/{distributed-vlan-connection-id}

- Response added with Status Code `504`

PATCH /infra/distributed-vlan-connections/{distributed-vlan-connection-id}

- Response added with Status Code `504`

PUT /infra/distributed-vlan-connections/{distributed-vlan-connection-id}

- Response added with Status Code `504`

GET /infra/distributed-vlan-connections

- Response added with Status Code `504`

DELETE /infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

GET /infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

PATCH /infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

PUT /infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

GET /infra/dns-forwarder-zones

- Response added with Status Code `504`

DELETE /infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PUT /infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/dns-security-profiles

- Response added with Status Code `504`

GET /infra/domains/endpoint-policies

- Response added with Status Code `504`

GET /infra/domains/firewall-flood-protection-profile-binding-maps

- Response added with Status Code `504`

GET /infra/domains/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

GET /infra/domains/redirection-policies

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/rules

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}/statistics

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/bridge-policies/{bridge-firewall-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/bridge-policies

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/communication-maps/{communication-map-id}/communication-entries/{communication-entry-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/communication-maps/{communication-map-id}/communication-entries/{communication-entry-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/communication-maps/{communication-map-id}/communication-entries/{communication-entry-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/communication-maps/{communication-map-id}/communication-entries/{communication-entry-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/communication-maps/{communication-map-id}/communication-entries/{communication-entry-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/communication-maps/{communication-map-id}/communication-entries

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/communication-maps/{communication-map-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/communication-maps/{communication-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/communication-maps/{communication-map-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/communication-maps/{communication-map-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/communication-maps/{communication-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/communication-maps

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/domain-deployment-maps/{domain-deployment-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/domain-deployment-maps

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}/endpoint-rules/{endpoint-rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}/endpoint-rules/{endpoint-rule-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}/endpoint-rules/{endpoint-rule-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}/endpoint-rules/{endpoint-rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}/endpoint-rules

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/endpoint-policies/{endpoint-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/statistics

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/gateway-policies

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/associated-kubernetes-clusters

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/group-monitoring-profile-binding-maps/{group-monitoring-profile-binding-map-id}/mirror-stack-status

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/group-monitoring-profile-binding-maps/{group-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/group-monitoring-profile-binding-maps/{group-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/group-monitoring-profile-binding-maps/{group-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/groups/{group-id}/group-monitoring-profile-binding-maps/{group-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/group-monitoring-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/member-types

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/antrea-egresses

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/antrea-ip-pools

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/bms

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/bmsi

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/cloud-native-service-instances

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/dvpg

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/dvports

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/identity-groups

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/ip-addresses

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/ip-groups

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/kubernetes-gateways

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/kubernetes-ingresses

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/kubernetes-node-ips

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/kubernetes-node-pod-cidrs

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/kubernetes-services

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/logical-ports

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/logical-switches

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/pods

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/segment-ports

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/segments

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/transport-nodes

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/vifs

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/members/virtual-machines

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}/port-mirroring-instances/{port-mirroring-instance-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/port-mirroring-instances/{port-mirroring-instance-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}/port-mirroring-instances/{port-mirroring-instance-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/groups/{group-id}/port-mirroring-instances/{port-mirroring-instance-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/port-mirroring-instances

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/statistics/virtual-machines

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}/tags

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/groups

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/rules

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}/statistics

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/intrusion-service-gateway-policies/{policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-gateway-policies

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/statistics

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/intrusion-service-policies

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}/rules

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/redirection-policies/{redirection-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/redirection-policies

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/security-policies/{security-policy-id}/container-cluster-span/{antrea-cluster-1}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies/{security-policy-id}/container-cluster-span/{antrea-cluster-1}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/security-policies/{security-policy-id}/container-cluster-span/{container-cluster-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/security-policies/{security-policy-id}/container-cluster-span/{container-cluster-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies/{security-policy-id}/container-cluster-span

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies/{security-policy-id}/rules

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies/{security-policy-id}/statistics

- Response added with Status Code `504`

POST /infra/domains/{domain-id}/security-policies/{security-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}/security-policies

- Response added with Status Code `504`

DELETE /infra/domains/{domain-id}

- Response added with Status Code `504`

GET /infra/domains/{domain-id}

- Response added with Status Code `504`

PATCH /infra/domains/{domain-id}

- Response added with Status Code `504`

PUT /infra/domains/{domain-id}

- Response added with Status Code `504`

GET /infra/domains

- Response added with Status Code `504`

GET /infra/drafts/{draft-id}/aggregated

- Response added with Status Code `504`

GET /infra/drafts/{draft-id}/aggregated_with_pagination

- Response added with Status Code `504`

GET /infra/drafts/{draft-id}/complete

- Response added with Status Code `504`

POST /infra/drafts/{draft-id}?action=publish

- Response added with Status Code `504`

DELETE /infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /infra/drafts/{draft-id}

- Response added with Status Code `504`

PATCH /infra/drafts/{draft-id}

- Response added with Status Code `504`

PUT /infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /infra/drafts

- Response added with Status Code `504`

DELETE /infra/evpn-tenant-configs/{config-id}

- Response added with Status Code `504`

GET /infra/evpn-tenant-configs/{config-id}

- Response added with Status Code `504`

PATCH /infra/evpn-tenant-configs/{config-id}

- Response added with Status Code `504`

PUT /infra/evpn-tenant-configs/{config-id}

- Response added with Status Code `504`

GET /infra/evpn-tenant-configs

- Response added with Status Code `504`

GET /infra/features/detailed-view

- Response added with Status Code `504`

GET /infra/features

- Response added with Status Code `504`

GET /infra/federation-config

- Response added with Status Code `504`

POST /infra/firewall-identity-store-event-log-servers/status

- Response added with Status Code `504`

POST /infra/firewall-identity-store-ldap-server

- Response added with Status Code `504`

POST /infra/firewall-identity-store-size

- Response added with Status Code `504`

POST /infra/firewall-identity-stores-org-units

- Response added with Status Code `504`

DELETE /infra/firewall-identity-stores/{firewall-identity-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

PATCH /infra/firewall-identity-stores/{firewall-identity-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

PUT /infra/firewall-identity-stores/{firewall-identity-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}/groups/{group-id}/member-groups

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}/groups

- Response added with Status Code `504`

DELETE /infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

PATCH /infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

PUT /infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}/org-units

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}/sync-stats

- Response added with Status Code `504`

DELETE /infra/firewall-identity-stores/{firewall-identity-store-id}

- Response added with Status Code `504`

GET /infra/firewall-identity-stores/{firewall-identity-store-id}

- Response added with Status Code `504`

PATCH /infra/firewall-identity-stores/{firewall-identity-store-id}

- Response added with Status Code `504`

PUT /infra/firewall-identity-stores/{firewall-identity-store-id}

- Response added with Status Code `504`

GET /infra/firewall-identity-stores

- Response added with Status Code `504`

GET /infra/firewall-ip-reputation-feed

- Response added with Status Code `504`

POST /infra/firewall-ip-reputation-feed

- Response added with Status Code `504`

DELETE /infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

GET /infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

PATCH /infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

PUT /infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

GET /infra/firewall-schedulers

- Response added with Status Code `504`

DELETE /infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PATCH /infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PUT /infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /infra/firewall-session-timer-profiles

- Response added with Status Code `504`

GET /infra/firewall/policies

- Response added with Status Code `504`

GET /infra/firewall/rules

- Response added with Status Code `504`

GET /infra/flood-protection-profiles/{flood-protection-profile-id}/bindings

- Response added with Status Code `504`

DELETE /infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PATCH /infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PUT /infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /infra/flood-protection-profiles

- Response added with Status Code `504`

POST /infra/full-sync-action

- Response added with Status Code `504`

GET /infra/full-sync-states/{full-sync-id}

- Response added with Status Code `504`

GET /infra/full-sync-states

- Response added with Status Code `504`

DELETE /infra/gateway-connections/{gateway-connection-id}

- Response added with Status Code `504`

GET /infra/gateway-connections/{gateway-connection-id}

- Response added with Status Code `504`

PATCH /infra/gateway-connections/{gateway-connection-id}

- Response added with Status Code `504`

PUT /infra/gateway-connections/{gateway-connection-id}

- Response added with Status Code `504`

GET /infra/gateway-connections

- Response added with Status Code `504`

DELETE /infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /infra/gateway-qos-profiles

- Response added with Status Code `504`

GET /infra/geo-ip/blocked-events

- Response added with Status Code `504`

GET /infra/geo-ip/bundle

- Response added with Status Code `504`

POST /infra/geo-ip/bundle

- Response added with Status Code `504`

GET /infra/geo-ip/look-up

- Response added with Status Code `504`

GET /infra/geo-ip/setting

- Response added with Status Code `504`

PATCH /infra/geo-ip/setting

- Response added with Status Code `504`

PUT /infra/geo-ip/setting

- Response added with Status Code `504`

GET /infra/global-config

- Response added with Status Code `504`

PATCH /infra/global-config

- Response added with Status Code `504`

PUT /infra/global-config

- Response added with Status Code `504`

GET /infra/group-associations

- Response added with Status Code `504`

GET /infra/group-service-associations

- Response added with Status Code `504`

DELETE /infra/host-switch-profiles/{host-switch-profile-id}

- Response added with Status Code `504`

GET /infra/host-switch-profiles/{host-switch-profile-id}

- Response added with Status Code `504`

PATCH /infra/host-switch-profiles/{host-switch-profile-id}

- Response added with Status Code `504`

PUT /infra/host-switch-profiles/{host-switch-profile-id}

- Response added with Status Code `504`

GET /infra/host-switch-profiles

- Response added with Status Code `504`

GET /infra/host-transport-node-profiles/{host-transport-node-profile-id}

- Response added with Status Code `504`

DELETE /infra/host-transport-node-profiles/{transport-node-profile-id}

- Response added with Status Code `504`

PUT /infra/host-transport-node-profiles/{transport-node-profile-id}

- Parameter added: `update_vcp_config`
- Response added with Status Code `504`

GET /infra/host-transport-node-profiles

- Response added with Status Code `504`

DELETE /infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

PATCH /infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

PUT /infra/identity-firewall-stores/{identity-firewall-store-id}/event-log-servers/{event-log-server-id}

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}/groups/{group-id}/children

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}/groups/{group-id}/parent-groups

- Response added with Status Code `504`

DELETE /infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

PATCH /infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

PUT /infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers/{ldap-server-id}

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}/ldap-servers

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}/users/{user-id}/parent-groups

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}/users

- Response added with Status Code `504`

DELETE /infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

GET /infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

PATCH /infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

PUT /infra/identity-firewall-stores/{identity-firewall-store-id}

- Response added with Status Code `504`

GET /infra/identity-firewall-stores

- Response added with Status Code `504`

GET /infra/identity-group-associations

- Response added with Status Code `504`

DELETE /infra/igmp-profiles/{igmp-profile-id}

- Response added with Status Code `504`

GET /infra/igmp-profiles/{igmp-profile-id}

- Response added with Status Code `504`

PATCH /infra/igmp-profiles/{igmp-profile-id}

- Response added with Status Code `504`

PUT /infra/igmp-profiles/{igmp-profile-id}

- Response added with Status Code `504`

GET /infra/igmp-profiles

- Response added with Status Code `504`

POST /infra/import-k8s-np-to-dfw

- Response added with Status Code `504`

GET /infra/ip-address-group-associations

- Response added with Status Code `504`

GET /infra/ip-blocks/state

- Response added with Status Code `504`

GET /infra/ip-blocks/{ip-block-id}/usage

- Response added with Status Code `504`

DELETE /infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

GET /infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

PATCH /infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

PUT /infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

GET /infra/ip-blocks

- Response added with Status Code `504`

DELETE /infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PATCH /infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PUT /infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /infra/ip-discovery-profiles

- Response added with Status Code `504`

DELETE /infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

GET /infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

PATCH /infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

PUT /infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

GET /infra/ip-pools/{ip-pool-id}/ip-allocations

- Response added with Status Code `504`

DELETE /infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

GET /infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

PATCH /infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

PUT /infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

GET /infra/ip-pools/{ip-pool-id}/ip-subnets

- Response added with Status Code `504`

DELETE /infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

GET /infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

PATCH /infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

PUT /infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

GET /infra/ip-pools

- Response added with Status Code `504`

GET /infra/ip-reputation-exclusion-list

- Response added with Status Code `504`

DELETE /infra/ipfix-dfw-collector-profiles/{ipfix-dfw-collector-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-dfw-collector-profiles/{ipfix-dfw-collector-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipfix-dfw-collector-profiles/{ipfix-dfw-collector-profile-id}

- Response added with Status Code `504`

PUT /infra/ipfix-dfw-collector-profiles/{ipfix-dfw-collector-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-dfw-collector-profiles

- Response added with Status Code `504`

DELETE /infra/ipfix-dfw-profiles/{ipfix-dfw-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-dfw-profiles/{ipfix-dfw-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipfix-dfw-profiles/{ipfix-dfw-profile-id}

- Response added with Status Code `504`

PUT /infra/ipfix-dfw-profiles/{ipfix-dfw-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-dfw-profiles

- Response added with Status Code `504`

DELETE /infra/ipfix-l2-collector-profiles/{ipfix-l2-collector-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-l2-collector-profiles/{ipfix-l2-collector-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipfix-l2-collector-profiles/{ipfix-l2-collector-profile-id}

- Response added with Status Code `504`

PUT /infra/ipfix-l2-collector-profiles/{ipfix-l2-collector-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-l2-collector-profiles

- Response added with Status Code `504`

DELETE /infra/ipfix-l2-profiles/{ipfix-l2-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-l2-profiles/{ipfix-l2-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipfix-l2-profiles/{ipfix-l2-profile-id}

- Response added with Status Code `504`

PUT /infra/ipfix-l2-profiles/{ipfix-l2-profile-id}

- Response added with Status Code `504`

GET /infra/ipfix-l2-profiles

- Response added with Status Code `504`

DELETE /infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

GET /infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

PUT /infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

GET /infra/ipsec-vpn-dpd-profiles

- Response added with Status Code `504`

DELETE /infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

GET /infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

PUT /infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

GET /infra/ipsec-vpn-ike-profiles

- Response added with Status Code `504`

DELETE /infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

GET /infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

PUT /infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

GET /infra/ipsec-vpn-tunnel-profiles

- Response added with Status Code `504`

DELETE /infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PUT /infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /infra/ipv6-dad-profiles

- Response added with Status Code `504`

DELETE /infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PATCH /infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PUT /infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /infra/ipv6-ndra-profiles

- Response added with Status Code `504`

GET /infra/l7-access-profiles/attributes

- Response added with Status Code `504`

DELETE /infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

GET /infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

PATCH /infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

PUT /infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

GET /infra/l7-access-profiles/{l7-access-profile-id}/entries

- Response added with Status Code `504`

DELETE /infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

GET /infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

PATCH /infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

PUT /infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

GET /infra/l7-access-profiles

- Parameter added: `has_unsupported_app_ids`
- Response added with Status Code `504`

DELETE /infra/labels/{label-id}

- Response added with Status Code `504`

GET /infra/labels/{label-id}

- Response added with Status Code `504`

PATCH /infra/labels/{label-id}

- Response added with Status Code `504`

PUT /infra/labels/{label-id}

- Response added with Status Code `504`

GET /infra/labels

- Response added with Status Code `504`

DELETE /infra/latency-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/latency-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /infra/latency-profiles/{profile-id}

- Response added with Status Code `504`

PUT /infra/latency-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/latency-profiles

- Response added with Status Code `504`

DELETE /infra/lb-app-profiles/{lb-app-profile-id}

- Response added with Status Code `504`

GET /infra/lb-app-profiles/{lb-app-profile-id}

- Response added with Status Code `504`

PATCH /infra/lb-app-profiles/{lb-app-profile-id}

- Response added with Status Code `504`

PUT /infra/lb-app-profiles/{lb-app-profile-id}

- Response added with Status Code `504`

GET /infra/lb-app-profiles

- Response added with Status Code `504`

DELETE /infra/lb-client-ssl-profiles/{lb-client-ssl-profile-id}

- Response added with Status Code `504`

GET /infra/lb-client-ssl-profiles/{lb-client-ssl-profile-id}

- Response added with Status Code `504`

PATCH /infra/lb-client-ssl-profiles/{lb-client-ssl-profile-id}

- Response added with Status Code `504`

PUT /infra/lb-client-ssl-profiles/{lb-client-ssl-profile-id}

- Response added with Status Code `504`

GET /infra/lb-client-ssl-profiles

- Response added with Status Code `504`

DELETE /infra/lb-monitor-profiles/{lb-monitor-profile-id}

- Response added with Status Code `504`

GET /infra/lb-monitor-profiles/{lb-monitor-profile-id}

- Response added with Status Code `504`

PATCH /infra/lb-monitor-profiles/{lb-monitor-profile-id}

- Response added with Status Code `504`

PUT /infra/lb-monitor-profiles/{lb-monitor-profile-id}

- Response added with Status Code `504`

GET /infra/lb-monitor-profiles

- Response added with Status Code `504`

GET /infra/lb-node-usage-summary

- Parameter added: `node_type`
- Response added with Status Code `504`

GET /infra/lb-node-usage

- Response added with Status Code `504`

DELETE /infra/lb-persistence-profiles/{lb-persistence-profile-id}

- Response added with Status Code `504`

GET /infra/lb-persistence-profiles/{lb-persistence-profile-id}

- Response added with Status Code `504`

PATCH /infra/lb-persistence-profiles/{lb-persistence-profile-id}

- Response added with Status Code `504`

PUT /infra/lb-persistence-profiles/{lb-persistence-profile-id}

- Response added with Status Code `504`

GET /infra/lb-persistence-profiles

- Response added with Status Code `504`

DELETE /infra/lb-pools/{lb-pool-id}

- Response added with Status Code `504`

GET /infra/lb-pools/{lb-pool-id}

- Response added with Status Code `504`

PATCH /infra/lb-pools/{lb-pool-id}

- Response added with Status Code `504`

PUT /infra/lb-pools/{lb-pool-id}

- Response added with Status Code `504`

GET /infra/lb-pools

- Response added with Status Code `504`

DELETE /infra/lb-server-ssl-profiles/{lb-server-ssl-profile-id}

- Response added with Status Code `504`

GET /infra/lb-server-ssl-profiles/{lb-server-ssl-profile-id}

- Response added with Status Code `504`

PATCH /infra/lb-server-ssl-profiles/{lb-server-ssl-profile-id}

- Response added with Status Code `504`

PUT /infra/lb-server-ssl-profiles/{lb-server-ssl-profile-id}

- Response added with Status Code `504`

GET /infra/lb-server-ssl-profiles

- Response added with Status Code `504`

GET /infra/lb-service-usage-summary

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/debug-info

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/detailed-status

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/lb-pools/{lb-pool-id}/detailed-status

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/lb-pools/{lb-pool-id}/statistics

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/lb-virtual-servers/{lb-virtual-server-id}/detailed-status

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/lb-virtual-servers/{lb-virtual-server-id}/statistics

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/service-usage

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}/statistics

- Response added with Status Code `504`

DELETE /infra/lb-services/{lb-service-id}

- Response added with Status Code `504`

GET /infra/lb-services/{lb-service-id}

- Response added with Status Code `504`

PATCH /infra/lb-services/{lb-service-id}

- Response added with Status Code `504`

PUT /infra/lb-services/{lb-service-id}

- Response added with Status Code `504`

GET /infra/lb-services

- Response added with Status Code `504`

GET /infra/lb-ssl-ciphers-and-protocols

- Response added with Status Code `504`

DELETE /infra/lb-virtual-servers/{lb-virtual-server-id}

- Response added with Status Code `504`

GET /infra/lb-virtual-servers/{lb-virtual-server-id}

- Response added with Status Code `504`

PATCH /infra/lb-virtual-servers/{lb-virtual-server-id}

- Response added with Status Code `504`

PUT /infra/lb-virtual-servers/{lb-virtual-server-id}

- Response added with Status Code `504`

GET /infra/lb-virtual-servers

- Response added with Status Code `504`

GET /infra/limits/state

- Response added with Status Code `504`

GET /infra/limits/{limit-id}/state

- Response added with Status Code `504`

DELETE /infra/limits/{limit-id}

- Response added with Status Code `504`

GET /infra/limits/{limit-id}

- Response added with Status Code `504`

PATCH /infra/limits/{limit-id}

- Response added with Status Code `504`

PUT /infra/limits/{limit-id}

- Response added with Status Code `504`

GET /infra/limits

- Response added with Status Code `504`

GET /infra/livetraces/statuses

- Response added with Status Code `504`

GET /infra/livetraces/{livetrace-id}/forward/capturefile

- Response added with Status Code `504`

GET /infra/livetraces/{livetrace-id}/result

- Response added with Status Code `504`

GET /infra/livetraces/{livetrace-id}/reverse/capturefile

- Response added with Status Code `504`

GET /infra/livetraces/{livetrace-id}/status

- Response added with Status Code `504`

DELETE /infra/livetraces/{livetrace-id}

- Response added with Status Code `504`

GET /infra/livetraces/{livetrace-id}

- Response added with Status Code `504`

PATCH /infra/livetraces/{livetrace-id}

- Response added with Status Code `504`

POST /infra/livetraces/{livetrace-id}

- Response added with Status Code `504`

PUT /infra/livetraces/{livetrace-id}

- Response added with Status Code `504`

GET /infra/livetraces

- Response added with Status Code `504`

DELETE /infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PATCH /infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PUT /infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /infra/mac-discovery-profiles

- Response added with Status Code `504`

GET /infra/manager-ip-pools/{manager-ip-pool-id}

- Response added with Status Code `504`

GET /infra/manager-ip-pools

- Response added with Status Code `504`

GET /infra/manual-health-checks/{manual-health-check-id}/result

- Response added with Status Code `504`

DELETE /infra/manual-health-checks/{manual-health-check-id}

- Response added with Status Code `504`

GET /infra/manual-health-checks/{manual-health-check-id}

- Response added with Status Code `504`

POST /infra/manual-health-checks/{manual-health-check-id}

- Response added with Status Code `504`

GET /infra/manual-health-checks

- Response added with Status Code `504`

GET /infra/metadata-proxies/{metadata-proxy-id}/statistics

- Response added with Status Code `504`

GET /infra/metadata-proxies/{metadata-proxy-id}/status

- Response added with Status Code `504`

DELETE /infra/metadata-proxies/{metadata-proxy-id}

- Response added with Status Code `504`

GET /infra/metadata-proxies/{metadata-proxy-id}

- Response added with Status Code `504`

PATCH /infra/metadata-proxies/{metadata-proxy-id}

- Response added with Status Code `504`

PUT /infra/metadata-proxies/{metadata-proxy-id}

- Response added with Status Code `504`

GET /infra/metadata-proxies

- Response added with Status Code `504`

POST /infra/napp/common-agent/host-config?action=reset

- Response added with Status Code `504`

GET /infra/napp/common-agent/host-config

- Response added with Status Code `504`

PATCH /infra/napp/common-agent/host-config

- Response added with Status Code `504`

GET /infra/ops-global-config

- Response added with Status Code `504`

PATCH /infra/ops-global-config

- Response added with Status Code `504`

PUT /infra/ops-global-config

- Response added with Status Code `504`

GET /infra/partner-services/{service-name}

- Response added with Status Code `504`

GET /infra/partner-services

- Response added with Status Code `504`

DELETE /infra/pim-profiles/{pim-profile-id}

- Response added with Status Code `504`

GET /infra/pim-profiles/{pim-profile-id}

- Response added with Status Code `504`

PATCH /infra/pim-profiles/{pim-profile-id}

- Response added with Status Code `504`

PUT /infra/pim-profiles/{pim-profile-id}

- Response added with Status Code `504`

GET /infra/pim-profiles

- Response added with Status Code `504`

GET /infra/pktcap/session/{session-id}/CapturedFile

- Response added with Status Code `504`

DELETE /infra/pktcap/session/{session-id}

- Response added with Status Code `504`

GET /infra/pktcap/session/{session-id}

- Response added with Status Code `504`

POST /infra/pktcap/session/{session-id}

- Response added with Status Code `504`

POST /infra/pktcap/session

- Response added with Status Code `504`

DELETE /infra/pktcap/sessions

- Response added with Status Code `504`

GET /infra/pktcap/sessions

- Response added with Status Code `504`

GET /infra/pod-group-associations

- Response added with Status Code `504`

DELETE /infra/port-mirroring-profiles/{port-mirroring-profile-id}

- Response added with Status Code `504`

GET /infra/port-mirroring-profiles/{port-mirroring-profile-id}

- Response added with Status Code `504`

PATCH /infra/port-mirroring-profiles/{port-mirroring-profile-id}

- Response added with Status Code `504`

PUT /infra/port-mirroring-profiles/{port-mirroring-profile-id}

- Response added with Status Code `504`

GET /infra/port-mirroring-profiles

- Response added with Status Code `504`

DELETE /infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /infra/qos-profiles

- Response added with Status Code `504`

DELETE /infra/reactions/{reaction-id}

- Response added with Status Code `504`

GET /infra/reactions/{reaction-id}

- Response added with Status Code `504`

PATCH /infra/reactions/{reaction-id}

- Response added with Status Code `504`

PUT /infra/reactions/{reaction-id}

- Response added with Status Code `504`

GET /infra/reactions

- Response added with Status Code `504`

DELETE /infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

GET /infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

PATCH /infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

PUT /infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

GET /infra/real-time-eth-profiles

- Response added with Status Code `504`

GET /infra/realized-state/alarms

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/firewalls/firewall-sections/{firewall-section-id}

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/firewalls/firewall-sections

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/groups/nsgroups/{nsgroup-name}

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/groups/nsgroups

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/groups/securitygroups/{securitygroup-name}

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/groups/securitygroups

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/ip-sets/ip-sets-nsxt/{ip-set-name}

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/ip-sets/ip-sets-nsxt

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/mac-sets/mac-sets-nsxt/{mac-set-name}

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/mac-sets/mac-sets-nsxt

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/services/nsservices/{nsservice-name}

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/services/nsservices

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/vifs

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/virtual-machines/{virtual-machine-id}/details

- Response added with Status Code `504`

POST /infra/realized-state/enforcement-points/{enforcement-point-name}/virtual-machines?action=update_tags

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}/virtual-machines

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points/{enforcement-point-name}

- Response added with Status Code `504`

GET /infra/realized-state/enforcement-points

- Response added with Status Code `504`

GET /infra/realized-state/realized-entities

- Response added with Status Code `504`

POST /infra/realized-state/realized-entity?action=refresh

- Response added with Status Code `504`

GET /infra/realized-state/realized-entity

- Response added with Status Code `504`

GET /infra/realized-state/status

- Response added with Status Code `504`

GET /infra/realized-state/system-excluded-virtual-machines

- Response added with Status Code `504`

GET /infra/realized-state/system-virtual-machines

- Response added with Status Code `504`

GET /infra/realized-state/unassociated-virtual-machines

- Response added with Status Code `504`

POST /infra/realized-state/virtual-machines/{virtual-machine-id}/tags

- Response added with Status Code `504`

GET /infra/realized-state/virtual-machines

- Response added with Status Code `504`

DELETE /infra/routing-config/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

GET /infra/routing-config/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

PATCH /infra/routing-config/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

PUT /infra/routing-config/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

GET /infra/routing-config/prefix-lists

- Response added with Status Code `504`

DELETE /infra/routing-config/project-route-filters/{route-filter-id}

- Response added with Status Code `504`

GET /infra/routing-config/project-route-filters/{route-filter-id}

- Response added with Status Code `504`

PATCH /infra/routing-config/project-route-filters/{route-filter-id}

- Response added with Status Code `504`

PUT /infra/routing-config/project-route-filters/{route-filter-id}

- Response added with Status Code `504`

GET /infra/routing-config/project-route-filters

- Response added with Status Code `504`

GET /infra/sandboxed-resources

- Response added with Status Code `504`

GET /infra/security-global-config

- Response added with Status Code `504`

PUT /infra/security-global-config

- Response added with Status Code `504`

DELETE /infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PATCH /infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PUT /infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /infra/segment-security-profiles

- Response added with Status Code `504`

DELETE /infra/segments/service-segments/{service-segment-id}

- Response added with Status Code `504`

GET /infra/segments/service-segments/{service-segment-id}

- Response added with Status Code `504`

PATCH /infra/segments/service-segments/{service-segment-id}

- Response added with Status Code `504`

PUT /infra/segments/service-segments/{service-segment-id}

- Response added with Status Code `504`

GET /infra/segments/service-segments

- Response added with Status Code `504`

GET /infra/segments/state

- Response added with Status Code `504`

DELETE /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}/mirror-stack-status

- Response added with Status Code `504`

DELETE /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-monitoring-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}/mirror-stack-status

- Response added with Status Code `504`

DELETE /infra/segments/{infra-segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{infra-segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{infra-segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{infra-segment-id}/segment-monitoring-profile-binding-maps

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/arp-table

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/bep-statistics

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/bep-status

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/ports

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/security-config

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/security-config

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/security-config

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-connection-binding-maps

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /infra/segments/{segment-id}/tep-table

- Response added with Status Code `504`

POST /infra/segments/{segment-id}?action=delete_dhcp_leases

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

DELETE /infra/segments/{segment-id}

- Response added with Status Code `504`

GET /infra/segments/{segment-id}

- Response added with Status Code `504`

PATCH /infra/segments/{segment-id}

- Response added with Status Code `504`

PUT /infra/segments/{segment-id}

- Response added with Status Code `504`

GET /infra/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /infra/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /infra/segments/{segments-id}/state

- Response added with Status Code `504`

GET /infra/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /infra/segments

- Response added with Status Code `504`

GET /infra/service-chains/{service-chain-id}/service-paths

- Response added with Status Code `504`

DELETE /infra/service-chains/{service-chain-id}

- Response added with Status Code `504`

GET /infra/service-chains/{service-chain-id}

- Response added with Status Code `504`

PATCH /infra/service-chains/{service-chain-id}

- Response added with Status Code `504`

PUT /infra/service-chains/{service-chain-id}

- Response added with Status Code `504`

GET /infra/service-chains

- Response added with Status Code `504`

GET /infra/service-references/{service-reference-id}/service-profiles/{service-profile-id}/group-associations

- Response added with Status Code `504`

GET /infra/service-references/{service-reference-id}/service-profiles/{service-profile-id}/service-chain-mappings

- Response added with Status Code `504`

DELETE /infra/service-references/{service-reference-id}/service-profiles/{service-profile-id}

- Response added with Status Code `504`

GET /infra/service-references/{service-reference-id}/service-profiles/{service-profile-id}

- Response added with Status Code `504`

PATCH /infra/service-references/{service-reference-id}/service-profiles/{service-profile-id}

- Response added with Status Code `504`

PUT /infra/service-references/{service-reference-id}/service-profiles/{service-profile-id}

- Response added with Status Code `504`

GET /infra/service-references/{service-reference-id}/service-profiles

- Response added with Status Code `504`

DELETE /infra/service-references/{service-reference-id}

- Response added with Status Code `504`

GET /infra/service-references/{service-reference-id}

- Response added with Status Code `504`

PATCH /infra/service-references/{service-reference-id}

- Response added with Status Code `504`

PUT /infra/service-references/{service-reference-id}

- Response added with Status Code `504`

GET /infra/service-references

- Response added with Status Code `504`

DELETE /infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

GET /infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

PATCH /infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

PUT /infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

GET /infra/services/{service-id}/service-entries

- Response added with Status Code `504`

DELETE /infra/services/{service-id}

- Response added with Status Code `504`

GET /infra/services/{service-id}

- Response added with Status Code `504`

PATCH /infra/services/{service-id}

- Response added with Status Code `504`

PUT /infra/services/{service-id}

- Response added with Status Code `504`

GET /infra/services

- Response added with Status Code `504`

GET /infra/session-timer-profiles/{session-timer-profile-id}/bindings

- Response added with Status Code `504`

DELETE /infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps/{cpu-mem-thresholds-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps/{cpu-mem-thresholds-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps/{cpu-mem-thresholds-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps/{cpu-mem-thresholds-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/cpu-mem-thresholds-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/cpu-mem-thresholds-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/cpu-mem-thresholds-profiles

- Response added with Status Code `504`

POST /infra/settings/firewall/export?action=cancel

- Response added with Status Code `504`

GET /infra/settings/firewall/export?action=download

- Response added with Status Code `504`

GET /infra/settings/firewall/export

- Response added with Status Code `504`

POST /infra/settings/firewall/export

- Response added with Status Code `504`

GET /infra/settings/firewall/gateway/dependent-services

- Response added with Status Code `504`

DELETE /infra/settings/firewall/idfw/cluster/{cluster-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/cluster/{cluster-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/idfw/cluster/{cluster-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/idfw/cluster/{cluster-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/cluster

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/compute-collections/status

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/compute-collections/{compute-collection-id}/status

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/compute-collections/{compute-collection-id}/transport-nodes/status

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/group-vm-details

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/standalone-host-switch-setting

- Response added with Status Code `504`

PATCH /infra/settings/firewall/idfw/standalone-host-switch-setting

- Response added with Status Code `504`

PUT /infra/settings/firewall/idfw/standalone-host-switch-setting

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/system-stats

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/transport-nodes/{transport-node-id}/vms/status

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/user-session-data

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/user-stats/{user-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/idfw/vm-stats/{vm-id}

- Response added with Status Code `504`

POST /infra/settings/firewall/import?action=cancel

- Response added with Status Code `504`

GET /infra/settings/firewall/import

- Response added with Status Code `504`

GET /infra/settings/firewall/security/dependent-services

- Response added with Status Code `504`

POST /infra/settings/firewall/security/exclude-list?action=filter

- Response added with Status Code `504`

GET /infra/settings/firewall/security/exclude-list?system_owned=true

- Response added with Status Code `504`

GET /infra/settings/firewall/security/exclude-list

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/exclude-list

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/exclude-list

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/affected-ips

- Parameter added: `context`
- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/affected-users

- Parameter added: `context`
- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/affected-vms

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/cluster-configs/{cluster-config-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/intrusion-services/cluster-configs/{cluster-config-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/intrusion-services/cluster-configs/{cluster-config-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/cluster-configs

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures-diff

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/export

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/upload-custom-signatures

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/{sig-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/settings

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/settings

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/settings

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/custom-signature-versions

- Response added with Status Code `504`

DELETE /infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs/{signature-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/global-signatures/threshold-configs

- Response added with Status Code `504`

DELETE /infra/settings/firewall/security/intrusion-services/global-signatures/{signature-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/global-signatures/{signature-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/intrusion-services/global-signatures/{signature-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/intrusion-services/global-signatures/{signature-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/global-signatures

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/gsm/global-signatures

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/ids-events

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/ids-standalone-host-config

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/intrusion-services/ids-standalone-host-config

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/intrusion-services/ids-standalone-host-config

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/ids-summary

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/pcaps/export

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/pcaps/{file-name}/download

- Response added with Status Code `504`

DELETE /infra/settings/firewall/security/intrusion-services/pcaps/{id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/pcaps

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/profiles/{profile-id}/effective-signatures

- Response added with Status Code `504`

DELETE /infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/profiles

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}/signatures

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/signature-versions/{version-id}

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/signature-versions?action=make_active_version

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/signature-versions

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services/signatures/status

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/signatures?action=update_signatures

- Response added with Status Code `504`

POST /infra/settings/firewall/security/intrusion-services/stats?action=reset

- Response added with Status Code `504`

GET /infra/settings/firewall/security/intrusion-services

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/intrusion-services

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/intrusion-services

- Response added with Status Code `504`

DELETE /infra/settings/firewall/security/malware-prevention-service/profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/malware-prevention-service/profiles/{profile-id}

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security/malware-prevention-service/profiles/{profile-id}

- Response added with Status Code `504`

PUT /infra/settings/firewall/security/malware-prevention-service/profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/settings/firewall/security/malware-prevention-service/profiles

- Response added with Status Code `504`

GET /infra/settings/firewall/security/malware-prevention-service/signatures

- Response added with Status Code `504`

GET /infra/settings/firewall/security

- Response added with Status Code `504`

PATCH /infra/settings/firewall/security

- Response added with Status Code `504`

PUT /infra/settings/firewall/security

- Response added with Status Code `504`

POST /infra/settings/firewall/stats?action=reset

- Response added with Status Code `504`

GET /infra/settings/service-insertion/security/exclude-list?system_owned=true

- Response added with Status Code `504`

GET /infra/settings/service-insertion/security/exclude-list

- Response added with Status Code `504`

PATCH /infra/settings/service-insertion/security/exclude-list

- Response added with Status Code `504`

PUT /infra/settings/service-insertion/security/exclude-list

- Response added with Status Code `504`

GET /infra/settings/service-insertion/security/status

- Response added with Status Code `504`

PATCH /infra/settings/service-insertion/security/status

- Response added with Status Code `504`

PUT /infra/settings/service-insertion/security/status

- Response added with Status Code `504`

GET /infra/sha/appliances/latency/status

- Response added with Status Code `504`

GET /infra/sha/appliances/process/status

- Response added with Status Code `504`

GET /infra/sha/appliances/{appliance-id}/latency/status

- Response added with Status Code `504`

GET /infra/sha/appliances/{appliance-id}/process/status

- Response added with Status Code `504`

POST /infra/sha/dynamic-plugins/{plugin-id}/files/{file-name}

- Response added with Status Code `504`

DELETE /infra/sha/dynamic-plugins/{plugin-id}

- Response added with Status Code `504`

GET /infra/sha/dynamic-plugins/{plugin-id}

- Response added with Status Code `504`

PATCH /infra/sha/dynamic-plugins/{plugin-id}

- Response added with Status Code `504`

PUT /infra/sha/dynamic-plugins/{plugin-id}

- Response added with Status Code `504`

GET /infra/sha/dynamic-plugins

- Response added with Status Code `504`

POST /infra/sha/dynamic-runbook-instances/{instance-id}/file/action/remedy

- Response added with Status Code `504`

DELETE /infra/sha/dynamic-runbook-instances/{instance-id}/file

- Response added with Status Code `504`

POST /infra/sha/dynamic-runbook-instances/{instance-id}/file

- Response added with Status Code `504`

GET /infra/sha/dynamic-runbook-instances/{instance-id}/state

- Response added with Status Code `504`

DELETE /infra/sha/dynamic-runbook-instances/{instance-id}

- Response added with Status Code `504`

GET /infra/sha/dynamic-runbook-instances/{instance-id}

- Response added with Status Code `504`

PATCH /infra/sha/dynamic-runbook-instances/{instance-id}

- Response added with Status Code `504`

POST /infra/sha/dynamic-runbook-instances/{instance-id}

- Response added with Status Code `504`

GET /infra/sha/dynamic-runbook-instances

- Response added with Status Code `504`

GET /infra/sha/dynamic-runbooks/{runbook-id}/help

- Response added with Status Code `504`

GET /infra/sha/dynamic-runbooks/{runbook-id}

- Response added with Status Code `504`

GET /infra/sha/dynamic-runbooks

- Response added with Status Code `504`

GET /infra/sha/monitors-status

- Response added with Status Code `504`

DELETE /infra/sha/monitors/{monitor-id}/profiles/{monitor-profile-id}

- Response added with Status Code `504`

GET /infra/sha/monitors/{monitor-id}/profiles/{monitor-profile-id}

- Response added with Status Code `504`

PATCH /infra/sha/monitors/{monitor-id}/profiles/{monitor-profile-id}

- Response added with Status Code `504`

PUT /infra/sha/monitors/{monitor-id}/profiles/{monitor-profile-id}

- Response added with Status Code `504`

GET /infra/sha/monitors/{monitor-id}/profiles

- Response added with Status Code `504`

GET /infra/sha/monitors/{monitor-id}/status

- Response added with Status Code `504`

GET /infra/sha/monitors/{monitor-id}

- Response added with Status Code `504`

GET /infra/sha/monitors

- Response added with Status Code `504`

DELETE /infra/sha/plugin-profiles/{sha-profile-id}

- Response added with Status Code `504`

GET /infra/sha/plugin-profiles/{sha-profile-id}

- Response added with Status Code `504`

PATCH /infra/sha/plugin-profiles/{sha-profile-id}

- Response added with Status Code `504`

PUT /infra/sha/plugin-profiles/{sha-profile-id}

- Response added with Status Code `504`

GET /infra/sha/plugin-profiles

- Response added with Status Code `504`

GET /infra/sha/plugin-status/{node-id}

- Response added with Status Code `504`

GET /infra/sha/pre-defined-plugins/{plugin-id}

- Response added with Status Code `504`

GET /infra/sha/pre-defined-plugins

- Response added with Status Code `504`

GET /infra/sha/pre-defined-runbooks/{runbook-id}/help

- Response added with Status Code `504`

GET /infra/sha/pre-defined-runbooks/{runbook-id}

- Response added with Status Code `504`

GET /infra/sha/pre-defined-runbooks

- Response added with Status Code `504`

GET /infra/sha/runbook-artifacts/{request-id}/artifact

- Response added with Status Code `504`

DELETE /infra/sha/runbook-artifacts/{request-id}

- Response added with Status Code `504`

GET /infra/sha/runbook-artifacts/{request-id}

- Response added with Status Code `504`

PATCH /infra/sha/runbook-artifacts/{request-id}

- Response added with Status Code `504`

PUT /infra/sha/runbook-artifacts/{request-id}

- Response added with Status Code `504`

GET /infra/sha/runbook-artifacts

- Response added with Status Code `504`

GET /infra/sha/runbook-invocations/{invocation-id}/artifact

- Response added with Status Code `504`

GET /infra/sha/runbook-invocations/{invocation-id}/report

- Response added with Status Code `504`

DELETE /infra/sha/runbook-invocations/{invocation-id}

- Response added with Status Code `504`

GET /infra/sha/runbook-invocations/{invocation-id}

- Response added with Status Code `504`

POST /infra/sha/runbook-invocations/{invocation-id}

- Response added with Status Code `504`

GET /infra/sha/runbook-invocations

- Response added with Status Code `504`

DELETE /infra/sha/runbook-settings/{runbook-setting-id}

- Response added with Status Code `504`

GET /infra/sha/runbook-settings/{runbook-setting-id}

- Response added with Status Code `504`

PATCH /infra/sha/runbook-settings/{runbook-setting-id}

- Response added with Status Code `504`

PUT /infra/sha/runbook-settings/{runbook-setting-id}

- Response added with Status Code `504`

GET /infra/sha/runbook-settings

- Response added with Status Code `504`

DELETE /infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

GET /infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

PATCH /infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

PUT /infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

GET /infra/shares/{share-id}/resources

- Response added with Status Code `504`

DELETE /infra/shares/{share-id}

- Response added with Status Code `504`

GET /infra/shares/{share-id}

- Response added with Status Code `504`

PATCH /infra/shares/{share-id}

- Response added with Status Code `504`

PUT /infra/shares/{share-id}

- Response added with Status Code `504`

GET /infra/shares

- Response added with Status Code `504`

GET /infra/site/offboarding-status

- Response added with Status Code `504`

GET /infra/sites/agents/intelligence/maintenance

- Response added with Status Code `504`

PUT /infra/sites/agents/intelligence/maintenance

- Response added with Status Code `504`

GET /infra/sites/agents/metrics

- Response added with Status Code `504`

PUT /infra/sites/agents/metrics

- Response added with Status Code `504`

GET /infra/sites/listener_certificate

- Response added with Status Code `504`

GET /infra/sites/napp/registration/{cluster-id}

- Response added with Status Code `504`

GET /infra/sites/napp/registration

- Response added with Status Code `504`

GET /infra/sites/settings/firewall/security

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/container-cluster-ncpstatus

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/container-cluster-ncpstatus

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/container-cluster/{cluster-id}/ncpstatus

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/container-cluster/{cluster-id}/ncpstatus

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles/{profile-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-bridge-profiles

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/fqdn-analysis-config

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/fqdn-analysis-config

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/fqdn-analysis-config

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/fqdn-analysis-config

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/url-categorization-configs/{url-categorization-config-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/url-categorization-configs/{url-categorization-config-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/url-categorization-configs/{url-categorization-config-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-clusters/{edge-cluster-id}/url-categorization-configs/{url-categorization-config-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-transport-nodes/troubleshoot/datapath

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/edge-transport-nodes/troubleshoot/datapath

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes-aggstatus

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes-status

- Parameter added: `node_type`
- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/hyperbus-status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/lldp/interfaces/{interface-name}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/lldp/interfaces

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/node-agent-status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/pnic-bond-status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/remote-transport-node-status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/tunnels/{tunnel-name}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/host-transport-nodes/{node-id}/tunnels

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/transport-node-status-report-json

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/transport-node-status-report

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/transport-zones-aggstatus

- Parameter added: `include_system_owned`
- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/transport-zones/{zone-id}/status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/transport-zones/{zone-id}/transport-node-status-report-json

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/transport-zones/{zone-id}/transport-node-status-report

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}/transport-zones/{zone-id}/transport-node-status

- Parameter added: `node_type`
- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcement-point-id}?action=full-sync

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/bm-ccpn-status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/bm-ccpn/{cluster-control-plane-id}/status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes-heartbeat-config

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes-status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes/{cluster-control-plane-id}/heartbeat-config

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes/{cluster-control-plane-id}/heartbeat-config

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes/{cluster-control-plane-id}/heartbeat-config

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes/{cluster-control-plane-id}/status

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes/{cluster-control-plane-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes/{cluster-control-plane-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes/{cluster-control-plane-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/cluster-control-planes

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-cluster-high-availability-profiles/{edge-cluster-high-availability-profile-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-cluster-high-availability-profiles/{edge-cluster-high-availability-profile-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-cluster-high-availability-profiles/{edge-cluster-high-availability-profile-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-cluster-high-availability-profiles/{edge-cluster-high-availability-profile-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-cluster-high-availability-profiles

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/action/relocate-and-remove-edge-transport-node

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/action/replace-edge-transport-node

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/allocation/status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes/{edge-node-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/edge-nodes

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/state

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}/status

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters/{edge-cluster-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-clusters

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/state

- Parameter added: `node_types`
- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/status

- Parameter added: `node_type`
- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}/action/enter-maintenance-mode

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}/action/exit-maintenance-mode

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}/action/redeploy

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}/network/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}/network/interfaces

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}/state

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}/status

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}

- Parameter added: `force`
- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes/{edge-transport-node-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/edge-transport-nodes

- Parameter added: `node_types`
- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/failure-domains/{failure-domain-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/failure-domains/{failure-domain-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/failure-domains/{failure-domain-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/failure-domains/{failure-domain-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/failure-domains

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/state

- Parameter added: `node_types`
- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}/discovered-vifs

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}/modules

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}/state

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}/statistics/debug

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}/statistics/monitor

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}/vteps/actions/status

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}/vteps/actions

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}?action=restore_cluster_config

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}?action=resync_host_config

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/{host-transport-node-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/sub-clusters/{subcluster-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/sub-clusters/{subcluster-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/sub-clusters/{subcluster-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/sub-clusters/{subcluster-id}

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/sub-clusters?action=move

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/sub-clusters

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collection-id}/state

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collection-id}?action=install_for_microseg

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collection-id}?action=remove_nsx

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collection-id}?action=retry_profile_realization

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collection-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collection-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collection-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections/{transport-node-collections-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-node-collections

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones/{transport-zone-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/transport-zones

- Response added with Status Code `504`

POST /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}?action=reload

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}/enforcement-points

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/kubeconfig

- Response added with Status Code `504`

POST /infra/sites/{site-id}/napp/deployment/kubeconfig

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/kubernetes-tools

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/platform/checks/execution/required

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/platform/checks/status

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/napp/deployment/platform/checks

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/platform/form-factors

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/platform/status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/platform/versions

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/platform

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/napp/deployment/platform

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/napp/deployment/registry/reset

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/registry

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/napp/deployment/registry

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/storage-classes

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/tools/upload/status/{bundle-id}

- Response added with Status Code `504`

POST /infra/sites/{site-id}/napp/deployment/tools/upload

- Response added with Status Code `504`

POST /infra/sites/{site-id}/napp/deployment/tools/upload_from_remote_server

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/upgrade-coordinator/checks/status

- Response added with Status Code `504`

PUT /infra/sites/{site-id}/napp/deployment/upgrade-coordinator/checks

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/upgrade-coordinator/status

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/upgrade-coordinator/versions

- Response added with Status Code `504`

GET /infra/sites/{site-id}/napp/deployment/upgrade-coordinator

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}/napp/deployment/upgrade-coordinator

- Response added with Status Code `504`

GET /infra/sites/{site-id}/settings/firewall/security

- Response added with Status Code `504`

DELETE /infra/sites/{site-id}

- Response added with Status Code `504`

GET /infra/sites/{site-id}

- Response added with Status Code `504`

PATCH /infra/sites/{site-id}

- Response added with Status Code `504`

PUT /infra/sites/{site-id}

- Response added with Status Code `504`

GET /infra/sites

- Response added with Status Code `504`

GET /infra/span

- Response added with Status Code `504`

DELETE /infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PATCH /infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PUT /infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /infra/spoofguard-profiles

- Response added with Status Code `504`

DELETE /infra/static-mime-contents/{static-mime-content-id}

- Response added with Status Code `504`

GET /infra/static-mime-contents/{static-mime-content-id}

- Response added with Status Code `504`

PATCH /infra/static-mime-contents/{static-mime-content-id}

- Response added with Status Code `504`

PUT /infra/static-mime-contents/{static-mime-content-id}

- Response added with Status Code `504`

GET /infra/static-mime-contents

- Response added with Status Code `504`

GET /infra/tags/effective-resources

- Response added with Status Code `504`

GET /infra/tags/tag-operations/{operation-id}/status

- Response added with Status Code `504`

GET /infra/tags/tag-operations/{operation-id}

- Response added with Status Code `504`

PUT /infra/tags/tag-operations/{operation-id}

- Response added with Status Code `504`

GET /infra/tags

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/arp-proxies?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/arp-proxies

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/community-lists/{community-list-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/community-lists

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/dns-forwarder/nslookup

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/dns-forwarder/statistics

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/dns-forwarder/status

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

POST /infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/dns-forwarder

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/evpn

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/evpn

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/evpn

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/forwarding-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/forwarding-table

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/gateway-firewall

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/groups/{group-id}/members/ip-addresses

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/groups/{group-id}/members/virtual-machines

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/groups/{group-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/groups/{group-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/groups/{group-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/groups/{group-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/groups

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/inter-vrf-routing/{inter-vrf-routing-id}/advertised-networks?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/inter-vrf-routing/{inter-vrf-routing-id}/advertised-networks

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/inter-vrf-routing/{inter-vrf-routing-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/inter-vrf-routing/{inter-vrf-routing-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/inter-vrf-routing/{inter-vrf-routing-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/inter-vrf-routing/{inter-vrf-routing-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/inter-vrf-routing

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/local-endpoints

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}?action=show_sensitive_data

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/sessions

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/ipsec-vpn-services

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}/remote-mac

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}?action=create_with_peer_code

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/l2vpn-services

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/arp-proxies

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/status

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/advertised-routes?format=csv

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/advertised-routes

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/routes?format=csv

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}/routes

- Parameter added: `neighbor_address`
- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors/{neighbor-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/neighbors

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/troubleshoot

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/troubleshoot

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp/troubleshoot

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/bgp

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/byod-service-instances

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{interface-group-id}/statistics

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups/{label-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interface-groups

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/dad-state

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics/summary

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/interfaces

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}?action=show_sensitive_data

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context/l2vpns/{l2vpn-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context/l2vpns/{l2vpn-id}/statistics

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context/l2vpns/{l2vpn-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context/l2vpns/{l2vpn-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context/l2vpns/{l2vpn-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context/l2vpns/{l2vpn-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context/l2vpns

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-context

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/remote-mac

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}?action=create_with_peer_code

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l2vpn-services

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpn-context

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns/{l3vpn-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns/{l3vpn-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns/{l3vpn-id}?action=show_sensitive_data

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns/{l3vpn-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns/{l3vpn-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns/{l3vpn-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns/{l3vpn-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/l3vpns

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/areas/{area-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/areas/{area-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/areas/{area-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/areas/{area-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/areas

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/database?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/database

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/neighbors

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/routes?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf/routes

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ospf

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}?action=reauth

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-instances

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/service-interfaces

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps/{tier-0-deployment-map-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/tier-0-deployment-maps

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/evpn-tunnel-endpoints/{tunnel-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/evpn-tunnel-endpoints/{tunnel-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/evpn-tunnel-endpoints/{tunnel-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/evpn-tunnel-endpoints/{tunnel-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/evpn-tunnel-endpoints

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/gateway-firewall

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/forwarding?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/forwarding

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/igmp-memberships?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/igmp-memberships

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/pim-rp-mappings?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/pim-rp-mappings

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/routes?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast/routes

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/multicast

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels/{tunnel-id}/statistics/summary

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels/{tunnel-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels/{tunnel-id}/status

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels/{tunnel-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels/{tunnel-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels/{tunnel-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels/{tunnel-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services/{locale-svc-id}/tunnels

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/locale-services

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/nat/statistics

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/nat

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/number-of-routes

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/prefix-lists/{prefix-list-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/prefix-lists

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/route-maps/{route-map-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/route-maps

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/routing-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/routing-table

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/security-config

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/state

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/troubleshoot

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/troubleshoot

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/troubleshoot

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers/{bfd-peer-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/static-routes/bfd-peers

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/static-routes

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/tier-1-interface/arp-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/tier-1-interface/arp-table

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/tier-1-interface/statistics/summary

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}/tier-1-interface/statistics

- Response added with Status Code `504`

POST /infra/tier-0s/{tier-0-id}?action=reprocess

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier-0-id}

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier0-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier0-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

DELETE /infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-0s/{tier0-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

POST /infra/tier-0s?action=site_failover

- Response added with Status Code `504`

GET /infra/tier-0s

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/advertised-networks/csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/advertised-networks

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/arp-proxies?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/arp-proxies

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/dns-forwarder/nslookup

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/dns-forwarder/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/dns-forwarder/status

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

POST /infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/forwarding-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/forwarding-table

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/gateway-firewall

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}?action=show_sensitive_data

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/ipsec-vpn-services

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/remote-mac

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}?action=create_with_peer_code

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/arp-proxies

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints/{service-instance-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}/service-instance-endpoints

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/byod-service-instances

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints/{virtual-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/endpoints/virtual-endpoints

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{interface-group-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/dad-state

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics/summary

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/local-endpoints

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}?action=show_sensitive_data

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/remote-mac

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}?action=create_with_peer_code

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}/sessions

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/l2vpn-services

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}/statistics

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-instances/{service-instance-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-instances

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/gateway-firewall

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/multicast/forwarding?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/multicast/forwarding

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/multicast/igmp-memberships?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/multicast/igmp-memberships

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/multicast

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/multicast

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/multicast

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/locale-services

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/nat/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/nat

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/state

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/bep-statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/bep-status

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}/mirror-stack-status

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-monitoring-profile-binding-maps/{port-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-monitoring-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/security-config

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/security-config

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/security-config

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}/mirror-stack-status

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-monitoring-profile-binding-maps/{segment-monitoring-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-monitoring-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}?force=true

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segments-id}/state

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/segments

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/state

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/static-routes

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table?format=csv

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/tier-0-interface/statistics/summary

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/tier-0-interface/statistics

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/tls-inspection-state/fqdns/{fqdn-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/tls-inspection-state/fqdns

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}/tls-inspection-state

- Response added with Status Code `504`

POST /infra/tier-1s/{tier-1-id}?action=reprocess

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

POST /infra/tier-1s/{tier1-id}/segments/{segment-id}?action=delete_dhcp_leases

- Response added with Status Code `504`

DELETE /infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /infra/tier-1s

- Response added with Status Code `504`

DELETE /infra/tls-inspection-action-profiles/{action-profile-id}

- Response added with Status Code `504`

GET /infra/tls-inspection-action-profiles/{action-profile-id}

- Response added with Status Code `504`

PATCH /infra/tls-inspection-action-profiles/{action-profile-id}

- Response added with Status Code `504`

PUT /infra/tls-inspection-action-profiles/{action-profile-id}

- Response added with Status Code `504`

GET /infra/tls-inspection-action-profiles

- Response added with Status Code `504`

DELETE /infra/tls-inspection-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/tls-inspection-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /infra/tls-inspection-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /infra/tls-inspection-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /infra/tls-inspection-policies/{policy-id}/rules

- Response added with Status Code `504`

DELETE /infra/tls-inspection-policies/{policy-id}

- Response added with Status Code `504`

GET /infra/tls-inspection-policies/{policy-id}

- Response added with Status Code `504`

PATCH /infra/tls-inspection-policies/{policy-id}

- Response added with Status Code `504`

PUT /infra/tls-inspection-policies/{policy-id}

- Response added with Status Code `504`

GET /infra/tls-inspection-policies

- Response added with Status Code `504`

GET /infra/traceflows/{traceflow-id}/observations

- Response added with Status Code `504`

GET /infra/traceflows/{traceflow-id}/status

- Response added with Status Code `504`

DELETE /infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

PATCH /infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

POST /infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

PUT /infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /infra/traceflows

- Response added with Status Code `504`

DELETE /infra/transport-zone-profiles/{tz-profile-id}

- Response added with Status Code `504`

GET /infra/transport-zone-profiles/{tz-profile-id}

- Response added with Status Code `504`

PATCH /infra/transport-zone-profiles/{tz-profile-id}

- Response added with Status Code `504`

PUT /infra/transport-zone-profiles/{tz-profile-id}

- Response added with Status Code `504`

GET /infra/transport-zone-profiles

- Response added with Status Code `504`

GET /infra/url-categories

- Response added with Status Code `504`

GET /infra/url-reputation-severities

- Response added with Status Code `504`

GET /infra/virtual-machine-group-associations

- Response added with Status Code `504`

GET /infra/virtual-network-interface-group-associations

- Response added with Status Code `504`

DELETE /infra/vni-pools/{vni-pool-id}

- Response added with Status Code `504`

GET /infra/vni-pools/{vni-pool-id}

- Response added with Status Code `504`

PATCH /infra/vni-pools/{vni-pool-id}

- Response added with Status Code `504`

PUT /infra/vni-pools/{vni-pool-id}

- Response added with Status Code `504`

GET /infra/vni-pools

- Response added with Status Code `504`

GET /infra

- Response added with Status Code `504`

PATCH /infra

- Response added with Status Code `504`

PUT /infra

- Response added with Status Code `504`

POST /licenses/vcf-licenses

- Response added with Status Code `504`

GET /licenses/vcf/action/async/status

- Response added with Status Code `504`

POST /licenses/vcf/action/async

- Parameter added: `only_sync_unlicensed_vc`
- Response added with Status Code `504`

POST /licenses/vcf/action/sync

- Response added with Status Code `504`

GET /malware-prevention/compute-collection/{compute-collection-id}/status

- Response added with Status Code `504`

POST /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment/action/change-appliance

- Response added with Status Code `504`

DELETE /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

GET /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

POST /malware-prevention/compute-collection/{compute-collection-id}/svm-deployment

- Response added with Status Code `504`

GET /malware-prevention/ovf-spec

- Response added with Status Code `504`

GET /malware-prevention/teaser/regions

- Response added with Status Code `504`

POST /malware-prevention/teaser/registration_url

- Response added with Status Code `504`

GET /malware-prevention/teaser/status

- Response added with Status Code `504`

GET /malware-prevention/transport-node/{transport-node-id}/status

- Response added with Status Code `504`

GET /management-plane-health

- Response added with Status Code `504`

GET /observability/flow-details

- Response added with Status Code `504`

GET /org-root

- Response added with Status Code `504`

PATCH /org-root

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/aaa/role-bindings

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/aaa/role-bindings

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/aaa/roles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/aaa/user-info

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/baremetal-server-interfaces/tags

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/baremetal-servers/tags

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/bms-group-associations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/bmsi-group-associations

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/certificates/{certificate-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/certificates/{certificate-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/certificates/{certificate-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/certificates/{certificate-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/certificates

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/connectivity-global-config

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/connectivity-global-config

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/connectivity-global-config

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/constraint-global-config

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/constraint-global-config

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/constraint-global-config

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/constraints/{constraint-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/constraints/{constraint-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/constraints/{constraint-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/constraints/{constraint-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/constraints

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/context-profiles/attributes

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/context-profiles/custom-attributes/default

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/context-profiles/custom-attributes

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/context-profiles/custom-attributes

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/context-profiles/{context-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/context-profiles

- Parameter added: `has_unsupported_app_ids`
- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/crls/{crl-id}?action=import

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/crls/{crl-id}?action=upload

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/crls/{crl-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/crls/{crl-id}

- Parameter added: `fmt`
- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/crls/{crl-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/crls/{crl-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/crls

- Parameter added: `fmt`
- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/csrs/{csr-id}/pem-file

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/csrs/{csr-id}?action=create

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/csrs/{csr-id}?action=import

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/csrs/{csr-id}?action=self_sign

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/csrs/{csr-id}?action=upload

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/csrs/{csr-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/csrs/{csr-id}

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/csrs?action=self_sign

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/csrs

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/dhcp-relay-configs/{dhcp-relay-config-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-relay-configs

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{config-id}/leases

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{config-id}/state

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{config-id}/stats?action=reset

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{config-id}/stats

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{config-id}/status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs/{dhcp-server-config-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dhcp-server-configs

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/dns-forwarder-zones/{dns-forwarder-zone-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dns-forwarder-zones

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/dns-security-profiles/{profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/dns-security-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/firewall-flood-protection-profile-binding-maps

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/gateway-policies

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps/{discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps/{dns-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/dns-security-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/external-id-expressions/{expression-id}

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps/{firewall-flood-protection-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-flood-protection-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps/{firewall-session-timer-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/firewall-session-timer-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/ip-address-expressions/{expression-id}

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/mac-address-expressions/{expression-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/member-types

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/ip-addresses

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/ip-groups

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/logical-ports

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/logical-switches

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/pods

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/segment-ports

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/segments

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/vifs

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/members/virtual-machines

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/path-expressions/{expression-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/statistics/virtual-machines

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}/tags

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups/{group-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/groups

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{ids-policy-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}/rules

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies/{policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/intrusion-service-policies

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}/security-policies

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains/{domain-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/domains

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}/aggregated

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}/aggregated_with_pagination

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}/complete

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}?action=publish

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/drafts/{draft-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/drafts

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/firewall-schedulers/{firewall-scheduler-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/firewall-schedulers

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/firewall-session-timer-profiles/{firewall-session-timer-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/firewall-session-timer-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/firewall/policies

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/firewall/rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/flood-protection-profiles/{flood-protection-profile-id}/bindings

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/flood-protection-profiles/{flood-protection-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/flood-protection-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/gateway-qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/gateway-qos-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/geo-ip/blocked-events

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/geo-ip/look-up

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/global-config

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/global-config

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/global-config

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/group-associations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/group-service-associations

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/import-k8s-np-to-dfw

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-address-group-associations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-blocks/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-blocks/{ip-block-id}/usage

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ip-blocks/{ip-block-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-blocks

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ip-discovery-profiles/{ip-discovery-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-discovery-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-allocations

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-subnets/{ip-subnet-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}/ip-subnets

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ip-pools

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-dpd-profiles/{dpd-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-dpd-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-ike-profiles/{ike-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-ike-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-tunnel-profiles/{tunnel-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipsec-vpn-tunnel-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ipv6-dad-profiles/{dad-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipv6-dad-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ipv6-ndra-profiles/{ndra-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ipv6-ndra-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/attributes

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}/entries/{l7-access-entry-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}/entries

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles/{l7-access-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/l7-access-profiles

- Parameter added: `has_unsupported_app_ids`
- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/labels/{label-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/labels/{label-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/labels

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/limits/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/limits/{limit-id}/state

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/limits/{limit-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/limits/{limit-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/limits/{limit-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/limits/{limit-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/limits

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/mac-discovery-profiles/{mac-discovery-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/mac-discovery-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/ops-global-config

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/ops-global-config

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/ops-global-config

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/qos-profiles/{qos-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/qos-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/real-time-eth-profiles/{real-time-eth-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/real-time-eth-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/realized-state/realized-entities

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/realized-state/realized-entity?action=refresh

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/realized-state/status

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/realized-state/virtual-machines/{virtual-machine-id}/tags

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/realized-state/virtual-machines

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segment-security-profiles/{segment-security-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segment-security-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/state

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/ports/{infra-port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{infra-segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/arp-table

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps/{port-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-real-time-eth-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/ports

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-connection-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps/{segment-real-time-eth-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-real-time-eth-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}/tep-table

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}?action=delete_dhcp_leases

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}?force=true

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/segments/{segment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segments-id}/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/segments

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}/service-entries/{service-entry-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}/service-entries

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/services/{service-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/services

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/session-timer-profiles/{session-timer-profile-id}/bindings

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/export?action=cancel

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/export?action=download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/export

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/export

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/import?action=cancel

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/import

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/affected-ips

- Parameter added: `context`
- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/affected-users

- Parameter added: `context`
- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/affected-vms

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures-diff

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/export

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures/{sig-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}/custom-signatures

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/custom-signature-versions/{version-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/custom-signature-versions

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/ids-events

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/ids-summary

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/pcaps/export

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/pcaps/{file-name}/download

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/pcaps/{id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/pcaps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/profiles/{profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security/intrusion-services/profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/settings/firewall/security

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}/resources/{shared-resource-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}/resources

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/shares/{share-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/shares

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/sites/agents/intelligence/maintenance

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/sites/agents/intelligence/maintenance

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/sites/agents/metrics

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/sites/agents/metrics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/span

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/spoofguard-profiles/{spoofguard-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/spoofguard-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tags/effective-resources

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tags/tag-operations/{operation-id}/status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tags/tag-operations/{operation-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tags/tag-operations/{operation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tags

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-0s/{tier-0-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-0s/{tier-0-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-0s/{tier-0-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/advertised-networks/csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/advertised-networks

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/arp-proxies?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/arp-proxies

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder/failed-queries

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder/nslookup

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder/status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/dns-forwarder

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/forwarding-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/forwarding-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/gateway-firewall

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints/{local-endpoint-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/local-endpoints

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}?action=show_sensitive_data

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/sessions

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services/{service-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/ipsec-vpn-services

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/remote-mac

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}?action=create_with_peer_code

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/arp-proxies

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{group-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups/{interface-group-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interface-groups

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-proxy

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/arp-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/dad-state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics/summary

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/interfaces/{interface-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/detailed-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/sessions/{session-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/ipsec-vpn-services/{service-id}/summary

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces/{interface-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-service-id}/service-interfaces

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/gateway-firewall

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces/{interface-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}/interfaces

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services/{locale-services-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/locale-services

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/nat

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/security-config

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-proxy

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/arp-table

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/dhcp-static-bindings/{binding-id}/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/effective-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-arp-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-dad-state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics/summary

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/gateway-interface-statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/mac-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/effective-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps/{port-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps/{port-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps/{port-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/port-security-profile-binding-maps

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}/state

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports/{port-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/ports

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-connection-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps/{segment-discovery-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-discovery-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps/{segment-qos-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-qos-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps/{segment-security-profile-binding-map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/segment-security-profile-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/static-arp

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}/tep-table

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}?force=true

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segments-id}/ports/{port-id}/status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segments-id}/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments/{segments-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/segments

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/state

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/static-routes

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table?format=csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/tier-0-interface/arp-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/tier-0-interface/statistics/summary

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/tier-0-interface/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}?action=reprocess

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/flood-protection-profile-bindings/{flood-protection-profile-binding-id}

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/locale-services/{locale-services-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/segments/{segment-id}?action=delete_dhcp_leases

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier1-id}/session-timer-profile-bindings/{session-timer-profile-binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/traceflows/{traceflow-id}/observations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/traceflows/{traceflow-id}/status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/infra/traceflows/{traceflow-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/traceflows

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/virtual-machine-group-associations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra/virtual-network-interface-group-associations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/infra

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/infra

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/ip-address-allocations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/lb-node-capacity-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/limits/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/quota-stats

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/shared-with-me

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/transit-gateways/{tgw-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{tgw-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/transit-gateways/{tgw-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/transit-gateways/{tgw-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{tgw-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{tgw-id}/nat/{nat-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{tgw-id}/nat

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/arp-proxies/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/arp-proxies

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{attachment-id}/statistics

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{attachment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{attachment-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{attachment-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{attachment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{external-attachment-id}/advertised-networks/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments/{external-attachment-id}/advertised-networks

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/attachments

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/forwarding-table/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/forwarding-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/nat/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/realization-failures

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/routing-table/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/routing-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}/status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/transit-gateways

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vc-folder-status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpc-connectivity-profiles/{vpc-connectivity-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpc-connectivity-profiles/{vpc-connectivity-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpc-connectivity-profiles/{vpc-connectivity-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpc-connectivity-profiles/{vpc-connectivity-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpc-connectivity-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpc-security-profiles/{vpc-security-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpc-security-profiles/{vpc-security-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpc-security-profiles/{vpc-security-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpc-security-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpc-service-profiles/{vpc-service-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpc-service-profiles/{vpc-service-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpc-service-profiles/{vpc-service-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpc-service-profiles/{vpc-service-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpc-service-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/aaa/role-bindings/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/aaa/role-bindings

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/aaa/role-bindings

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/aaa/roles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/aaa/user-info

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/advertised-networks/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/advertised-networks

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/arp-proxies/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/arp-proxies

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/attachments/{vpc-attachment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/attachments/{vpc-attachment-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/attachments/{vpc-attachment-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/attachments/{vpc-attachment-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/attachments

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/dns-forwarder-statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/forwarding-table/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/forwarding-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies/{gateway-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/gateway-policies

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/group-associations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}/member-types

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}/members/ip-addresses

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}/members/subnet-ports

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}/members/subnets

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}/members/vifs

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}/members/virtual-machines

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups/{group-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/groups

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-address-allocations/{ip-address-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-address-allocations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-address-group-associations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/ip-address-usage

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/limits/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/{nat-id}/nat-rules/{nat-rule-id}/statistics

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/{nat-id}/nat-rules/{nat-rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/{nat-id}/nat-rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat/{nat-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/nat

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/quota-stats

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/realization-failures

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/realization-failures

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/rules/{rule-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/rules/{rule-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/rules/{rule-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/rules

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}/statistics

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}?action=revise

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies/{security-policy-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/security-policies

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/shared-with-me

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/state

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/static-routes/{route-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/static-routes/{route-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/static-routes/{route-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/static-routes

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/statistics/summary

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/realization-failures

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/actions/release-dhcp-server-leases

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/arp-proxy/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/arp-proxy

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/arp-table/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/arp-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dhcp-server-config/stats

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dhcp-server-config/status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dhcp-static-binding-configs/{binding-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/dhcp-static-binding-configs

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ip-pools/{ip-pool-id}/ip-allocations/{ip-allocation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ip-pools/{ip-pool-id}/ip-allocations

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ip-pools/{ip-pool-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ip-pools

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/mac-table/download

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/mac-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}/mac-table/csv

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}/mac-table

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}/state

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}/status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports/{port-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/ports

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/state/dhcp-server-leases

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/subnet-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/subnet-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/subnet-connection-binding-maps/{map-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/subnet-connection-binding-maps/{map-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/subnet-connection-binding-maps

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/tags/effective-resources

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/tags/vpc-tag-operations/{operation-id}/status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/tags/vpc-tag-operations/{operation-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/tags/vpc-tag-operations/{operation-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/tags

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vc-folder-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/virtual-machine-group-associations

- Response added with Status Code `504`

POST /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/virtual-machines/{virtual-machine-id}/tags

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/virtual-machines

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/virtual-network-interface-group-associations

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-app-profiles/{vpc-lb-app-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-app-profiles/{vpc-lb-app-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-app-profiles/{vpc-lb-app-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-app-profiles/{vpc-lb-app-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-app-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-client-ssl-profiles/{vpc-lb-client-ssl-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-client-ssl-profiles/{vpc-lb-client-ssl-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-client-ssl-profiles/{vpc-lb-client-ssl-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-client-ssl-profiles/{vpc-lb-client-ssl-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-client-ssl-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-monitor-profiles/{vpc-lb-monitor-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-monitor-profiles/{vpc-lb-monitor-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-monitor-profiles/{vpc-lb-monitor-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-monitor-profiles/{vpc-lb-monitor-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-monitor-profiles

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-node-capacity-status

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-persistence-profiles/{vpc-lb-persistence-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-persistence-profiles/{vpc-lb-persistence-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-persistence-profiles/{vpc-lb-persistence-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-persistence-profiles/{vpc-lb-persistence-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-persistence-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-pools/{vpc-lb-pool-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-pools/{vpc-lb-pool-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-pools/{vpc-lb-pool-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-pools/{vpc-lb-pool-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-pools

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-server-ssl-profiles/{vpc-lb-server-ssl-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-server-ssl-profiles/{vpc-lb-server-ssl-profile-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-server-ssl-profiles/{vpc-lb-server-ssl-profile-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-server-ssl-profiles/{vpc-lb-server-ssl-profile-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-server-ssl-profiles

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-virtual-servers/{vpc-lb-virtual-server-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-virtual-servers/{vpc-lb-virtual-server-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-virtual-servers/{vpc-lb-virtual-server-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-virtual-servers/{vpc-lb-virtual-server-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lb-virtual-servers

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}/detailed-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}/usage

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}/vpc-lb-pools/{vpc-lb-pool-id}/detailed-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}/vpc-lb-pools/{vpc-lb-pool-id}/statistics

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}/vpc-lb-virtual-servers/{vpc-lb-virtual-server-id}/detailed-status

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}/vpc-lb-virtual-servers/{vpc-lb-virtual-server-id}/statistics

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs/{vpc-lb-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/vpc-lbs

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}/vpcs

- Response added with Status Code `504`

DELETE /orgs/{org-id}/projects/{project-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects/{project-id}

- Response added with Status Code `504`

PATCH /orgs/{org-id}/projects/{project-id}

- Response added with Status Code `504`

PUT /orgs/{org-id}/projects/{project-id}

- Response added with Status Code `504`

GET /orgs/{org-id}/projects

- Response added with Status Code `504`

GET /orgs/{org-id}/shared-with-me

- Response added with Status Code `504`

GET /orgs/{org-id}

- Response added with Status Code `504`

GET /orgs

- Response added with Status Code `504`

GET /search/dsl

- Response added with Status Code `504`

GET /search/query

- Response added with Status Code `504`

GET /search/reconcile/status

- Response added with Status Code `504`

POST /search/reconcile

- Response added with Status Code `504`

POST /security/sensor-registration-token

- Response added with Status Code `504`

GET /system-config/auto-enable-gateway-firewall

- Response added with Status Code `504`

PATCH /system-config/auto-enable-gateway-firewall

- Response added with Status Code `504`

GET /system-config/nsx-partial-patch-config

- Response added with Status Code `504`

PATCH /system-config/nsx-partial-patch-config

- Response added with Status Code `504`

POST /system/input/login-logout-events

- Response added with Status Code `504`

GET /tasks/{task-id}/response

- Response added with Status Code `504`

GET /tasks/{task-id}

- Response added with Status Code `504`

GET /tasks

- Response added with Status Code `504`

DELETE /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

PUT /ui-views/{view-id}/widgetconfigurations/{widgetconfiguration-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}/widgetconfigurations

- Response added with Status Code `504`

POST /ui-views/{view-id}/widgetconfigurations

- Response added with Status Code `504`

DELETE /ui-views/{view-id}

- Response added with Status Code `504`

GET /ui-views/{view-id}

- Response added with Status Code `504`

PUT /ui-views/{view-id}

- Response added with Status Code `504`

GET /ui-views

- Response added with Status Code `504`

POST /ui-views

- Response added with Status Code `504`

GET /upgrade/version-whitelist/{component_type}

- Response added with Status Code `504`

PUT /upgrade/version-whitelist/{component_type}

- Response added with Status Code `504`

GET /upgrade/version-whitelist

- Response added with Status Code `504`

DELETE /watermark

- Response added with Status Code `504`

GET /watermark

- Response added with Status Code `504`

POST /watermark

- Response added with Status Code `504`

PUT /watermark

- Response added with Status Code `504`

Deprecated Operations

VERB	PATH
POST	/global-infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers/{ldap-server-id}
GET	/global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/inter-site/bgp-summary
GET	/global-infra/tier-0s/{tier-0-id}/locale-services/{locale-services-id}/inter-site/status
POST	/infra/firewall-identity-stores/{firewall-identity-store-id}
POST	/infra/firewall-identity-stores/{firewall-identity-store-id}/ldap-servers/{ldap-server-id}
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/gateway-interface-statistics/summary

Deleted Operations

VERB	PATH
GET	/infra/settings/firewall/security/exclude-list/global
PUT	/infra/settings/firewall/security/exclude-list/global
PATCH	/infra/settings/firewall/security/exclude-list/global
PUT	/orgs/{org-id}/projects/{project-id}/infra/labels/{label-id}
PATCH	/orgs/{org-id}/projects/{project-id}/infra/labels/{label-id}
DELETE	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profiles
GET	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profiles
PUT	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profiles
PATCH	/orgs/{org-id}/projects/{project-id}/vpcs/{vpc-id}/subnets/{subnet-id}/bridge-profiles

Data Structure Changes

New Structures

Structure Name
ALBControllerCloudCreationRequest
ALBControllerPKIProfileCACert
ALBControllerPKIProfileRequest
ALBControllerPKIProfileResponse
ALBControllerUser
ALBControllerVcenterServerCreationRequest
AffectedProductDetail
AlbControllerInfo
AlbControllerInfoList
AllocationDetails
AtpSecurityConfig
AtpSettings
AutoRejectIPOptionsGatewayFirewallConfig
BaseNetworkAppliance
BaseNetworkApplianceState
BaseSpan
BfdConfigParameters
BgpNeighbor
BgpNeighborAddressFamily
BgpNeighborRouteDetails
BridgeConnection
BridgeConnectionListResult
CentralizedConfig
CentralizedConfigListResult
ChildBaseNetworkAppliance
ChildBridgeConnection
ChildCentralizedConfig
ChildClusterSecurityConfiguration
ChildConnectivityPolicy
ChildDistributedVxlanConnection
ChildDynamicIpAddressReservation
ChildNetworkSpan
ChildPolicyBaseHostSwitchProfile
ChildPolicyHighPerformanceHostSwitchProfile
ChildPolicyHostTransportNodeProfile
ChildPolicyUplinkHostSwitchProfile
ChildPolicyVtepHAHostSwitchProfile
ChildRouteAdvertisement

Structure Name
ChildRouteController
ChildRouteControllerBgpNeighborConfig
ChildRouteControllerBgpRoutingConfig
ChildRouteControllerBgpTroubleshootConfig
ChildRouteControllerInterface
ChildSecurityPolicyContainerCluster
ChildSecurityProfileAttachment
ChildSecurityStrategy
ChildSiteToElsServerMapping
ChildSiteToLdapServerMapping
ChildTransitGatewaySecurityFeatures
ChildTransportNodeMonitoringProfileBindingMap
ChildVirtualNetworkApplianceCluster
CidrInfo
CidrInfoListResult
CidrUsageDetails
ClusterBasedSpan
ClusterInfo
ClusterSecurityConfiguration
ClusterSecurityConfigurationListResult
ClusterSecurityFeature
ClusterStatusErrorDetails
ConnectedVpc
ConnectedVpcListRequestBody
ConnectedVpcListResult
ConnectivityPolicy
ConnectivityPolicyListResult
DistributedVxlanConnection
DistributedVxlanConnectionListResult
DynamicIpAddressReservation
DynamicIpAddressReservationListResult
EastWestFirewall
FirewallExcludeListMembersCount
FirewallExcludeListMembersCountListResult
GatewayFailoverRequestParameters
GatewayReallocationRequestParameters
GlobalIdentityFirewallConfiguration
GmImportSpec
GmImportStatus
HealthCheckClusterScopeFilter

Structure Name
HostConfigCsvRecord
HostConfigReportInCsv
HostConfigReportRequest
HostScrxDebugStats
HostScrxMonitorStats
IdentityFirewallStoreSyncObject
IdentityFirewallStoreSyncRequest
IdsIncludedSignature
InfobloxIPAMProvider
IpAddressBlockAllocationState
IpAddressBlockAllocationStateForCidr
IpAddressBlockAllocationStateList
IpAddressBlockAvailableSubnetsCount
IpAddressBlockCidrUsedByDetails
IpAddressBlockUsageList
IpamThirdPartyProvider
IpamThirdPartyProviderCommonParams
IpamThirdPartyProviderConnectionInfo
IpamThirdPartyProviderFilterParams
IpamThirdPartyProviderListResult
IpamThirdPartyProviderPaginationParams
IpamThirdPartyProviderVersion
IpamThirdPartyProviderViews
LBVirtualNetworkApplianceCapacity
LBVirtualNetworkApplianceUsage
ListDhcpManagedPortAllocations
ManagedObjectOwnershipRequestParameters
NatCounters
NatStatisticsPerPolicyEdgeNode
NatStatisticsPerTransportNode
NetworkApplianceState
NetworkSpan
NetworkSpanListResult
NodeInterSiteStatistics
PeerNodeStatus
PeerVirtualNetworkApplianceStatus
PolicyEdgeClusterMemberConfigurationState
PolicyEdgeClusterMemberInterSiteBgpSummary
PolicyEdgeClusterMemberRemoteTunnelConnectivityStatus
PolicyEdgeClusterRemoteTunnelBgpSummary

Structure Name
PolicyEdgeClusterRemoteTunnelConnectivityStatus
PolicyEdgeNodeBgpNeighborAdvertisedRoutes
PolicyEdgeNodeBgpNeighborRouteDetailList
PolicyEdgeNodeBgpNeighborsListResult
PolicyEdgeNodeRemoteTepStatistics
PolicyIdsEventInnerFlowData
PolicyTraceflowConnectivityPolicyInfo
PolicyTraceflowObservationForwarded
PolicyTraceflowObservationReceived
ProjectState
ProviderAdvertiseOutBoundNetworks
ProviderNatConfig
RangeUsageDetails
RemoteTunnelStatistics
RemoteTunnelStatisticsPerSite
RouteAdvertisement
RouteController
RouteControllerBgpNeighborConfig
RouteControllerBgpNeighborConfigListResult
RouteControllerBgpNeighborRoutes
RouteControllerBgpNeighborRoutesListResult
RouteControllerBgpNeighborStatus
RouteControllerBgpNeighborsStatusListResult
RouteControllerBgpRoutingConfig
RouteControllerInterface
RouteControllerInterfaceAddress
RouteControllerInterfaceListResult
RouteControllerInterfaceStatistics
RouteControllerInterfaceStatisticsPerNode
RouteControllerInterfaceStatisticsSummary
RouteControllerListResult
RouteControllerRoutingTable
RouteControllerRoutingTableListResult
RouteControllerState
RouteControllerStateNodeStatus
RuleTemplate
ScrxClusterConfig
ScrxClusterConfigListResult
ScrxDebugStats
ScrxMonitorStats

Structure Name
ScrxSizeInfo
SecurityProfileAttachment
SecurityProfileAttachmentListResult
SecurityStrategy
SecurityStrategyListResult
ServiceGatewayCounterPolicyStats
ShaEdgeVodap20secMonitorConfig
ShaEdgeVodap5minMonitorConfig
ShaEdgeVodapAdvancedMetricsMonitorConfig
ShaEsxDatapathMonitorConfig
ShaEsxTnMetricsMonitorConfig
ShaEsxTnPnicMetricsMonitorConfig
ShaEsxTnTopologyMetricsMonitorConfig
ShaEsxTnVmknicMetricsMonitorConfig
ShaEsxTnVnicMetricsMonitorConfig
ShaVodapAlarmMonitorConfig
SiteToElsServerMapping
SiteToElsServerMappingListResult
SiteToLdapServerMapping
SiteToLdapServerMappingListResult
SpanListForTz
SpanMember
SpanMembersListResult
SpanReference
SspRegistration
SspRegistrationList
TagAttachment
TagAttachmentResponse
TestIdentityFirewallStoreLdapServerConnectivityRequest
ThirdPartyIPAMInfo
ThirdPartySyncStatusForDns
Tier0TGWAttachmentInterfaceState
TraceflowVlanExtensionBasicInfo
TraceflowVlanExtensionResultInfo
TransitGatewayAttachmentInterfaceState
TransitGatewayAttachmentInterfaceStateListResult
TransitGatewayRouteAdvertisementRule
TransitGatewaySecurityFeature
TransitGatewaySecurityFeatures
TransportNodeCollectionSpanAssociations

Structure Name
TransportNodeMonitoringProfileBindingMap
TransportNodeMonitoringProfileBindingMapListResult
ViewInfo
VirtualNetworkAppliance
VirtualNetworkApplianceCluster
VirtualNetworkApplianceClusterAdvancedConfiguration
VirtualNetworkApplianceClusterAllocationStatus
VirtualNetworkApplianceClusterListResult
VirtualNetworkApplianceClusterMember
VirtualNetworkApplianceClusterMemberAllocationStatus
VirtualNetworkApplianceClusterMemberPublishState
VirtualNetworkApplianceClusterMemberState
VirtualNetworkApplianceClusterMemberStatus
VirtualNetworkApplianceClusterPublishState
VirtualNetworkApplianceClusterState
VirtualNetworkApplianceClusterStatus
VirtualNetworkApplianceConfigurationState
VirtualNetworkApplianceConfigurationStateElement
VirtualNetworkApplianceCredential
VirtualNetworkApplianceDeploymentConfig
VirtualNetworkApplianceListResult
VirtualNetworkApplianceManagementInterface
VirtualNetworkApplianceState
VlanAvailability
VlanExtensionAggregatedDataCounter
VlanExtensionDataCounter
VlanExtensionStatistics
VodapGlobalCollector
VpcDeploymentScope
VpcServiceInstanceStatus
VpcSubnetConfigurationState
VpcSubnetVlanExtensionStatus
VtisBundleInfo
ZoneBasedSpan

Updated Structures

ALBControllerUserCredential

- New Property: `name`

ALBControllerUserCredentialResponse

- New Property: `name`

BgpNeighborConfig

- Updated Property: `neighbor_address` From `ip` to `address-or-cidr-block`

BgpNeighborRouteDetailsCsvRecord

- New Property: `rd`
- New Property: `evpn_route_type`
- New Property: `rmac_len`
- New Property: `esi`
- New Property: `eth_tag`
- New Property: `rmac`

DataCounter

- New Property: `unknown_unicast`

DatapathPacketDrops

- New Property: `firewall_scrx_packet_drops`

DfwFirewallConfiguration

- New Property: `enforce_duplicate_sequence_number_check`

DirectoryAdDomain

- New Property: `event_log_scraper_enabled`
- New Property: `path`

DirectoryLdapServer

- New Property: `path`

DistributedVlanConnection

- New Property: `subnet_extension_connection`
- New Property: `associated_ip_block_paths`
- New Property: `restricted_availability`

Endpoint

- New Property: `net_stack_instance_key`

FileTransferProtocol

- New Property: `host_key_algorithm`

GatewayConnection

- New Property: `nat_config`
- New Property: `advertise_outbound_networks`
- New Property: `inbound_remote_networks`

GlobalCollectorConfig

- New Property: `collector_fqdn`

GlobalConfig

- New Property: `tgw_transit_subnet_blocks`
- New Property: `tgw_transit_subnet_prefix_length`

GlobalIdsSettings

- New Property: `enable_custom_signatures`

HealthCheckResultPerUplink

- New Property: `vlan_allowed`
- New Property: `mtu_allowed`

HostSwitchState

- New Property: `nsx_configured_uplinks`
- New Property: `vtepless`

HostTransportNodeCollection

- New Property: `network_span_paths`

IPsecVPNIKESessionSummary

- New Property: `negotiating_sessions`

IdentityFirewallAdStore

- New Property: `event_log_scraper_enabled`

IdsGlobalEventConfig

- New Property: `enable_test_signatures`

IdsProfile

- New Property: `included_signatures`

IdsSignature

- New Property: `affected_products`

IdsSignatureStatus

- New Property: `is_user_uploaded`

IdsSignatureVersion

- New Property: `version_name`

IdsSiteVersionMapping

- New Property: `custom_signature_version_paths`

InfraSecurityConfig

- New Property: `ndcpp_enabled`

InterSitePortCounters

- New Property: `policy_dropped_packets`

IpAddressBlock

- New Property: `excluded_ips`
- New Property: `third_party_ipam`
- New Property: `used_size`
- New Property: `subnet_exclusive`
- New Property: `ranges`
- New Property: `total_size`
- New Property: `cidrs`
- New Property: `usage_percentage`

IpAddressBlockUsage

- New Property: `display_name`
- New Property: `intent_path`
- New Property: `visibility`
- New Property: `address_type`
- New Property: `overall_ips_count`
- New Property: `description`
- New Property: `range_usage`

- New Property: `cidr_usage`

IpAddressPoolBlockSubnet

- New Property: `allocated_cidr`

LogicalRouterPortCounters

- New Property: `policy_dropped_packets`

NappRegistration

- New Property: `is_disconnected`

NsxTDnsAnswer

- New Property: `answers`

NsxTDnsQueryAnswer

- New Property: `raw_string`

ObservabilityCounterDebugQueryResult

- New Property: `scrx_stats`

ObservabilityCounterMonitorQueryResult

- New Property: `scrx_stats`

OpsGlobalConfig

- New Property: `vna_dscp_value`

PolicyAlarmResource

- New Property: `intent_paths`
- New Property: `severity`

PolicyBgpNeighborStatus

- New Property: `is_dynamic`
- New Property: `neighbor_path`
- New Property: `remote_site_path`

PolicyEdgeClusterMemberState

- New Property: `configuration_state`

PolicyEdgeClusterMemberStatus

- New Property: `failure_reason`
- New Property: `peer_node_status`
- New Property: `display_name`
- New Property: `management_ips`
- New Property: `write_latency`
- New Property: `storage_state`
- New Property: `read_latency`
- New Property: `vtep_state`

PolicyEdgeClusterState

- New Property: `consolidated_status`

PolicyEdgeClusterStatus

- New Property: `error_details`

PolicyEdgeHighAvailabilityProfile

- New Property: `vip_max_hold_timer`

PolicyHostTransportNodeProfile

- New Property: `vcp_managed`

PolicyIdsEventFlowData

- New Property: `attacker`
- New Property: `flow_dest_vm_uuid`
- New Property: `target_vm_uuid`
- New Property: `flow_source_port`
- New Property: `inner_flow_details`
- New Property: `flow_destination_port`
- New Property: `attacker_vm_uuid`
- New Property: `flow_destination_ip`
- New Property: `flow_source_ip`
- New Property: `target`
- New Property: `flow_source_vm_uuid`

PolicyManualHealthCheck

- New Property: `cluster_scope_filter`

PolicyTraceflowObservationDroppedLogical

- New Property: `next_vpc_path`
- New Property: `src_connectivity_policy`
- New Property: `dst_connectivity_policy`

PolicyTraceflowObservationForwardedLogical

- New Property: `src_connectivity_policy`
- New Property: `dst_connectivity_policy`

PolicyTransportZone

- New Property: `transport_zone_type`
- Deleted Property: `forwarding_mode`

PortMirroringProfile

- New Property: `destination_pnics`
- New Property: `source_vlan_ids`
- New Property: `encapsulation_vlan_id`
- New Property: `preserve_original_vlan`

Project

- New Property: `id_suffix`
- New Property: `vpc_deployment_scope`

RemoteTunnelEndpoint

- New Property: `net_stack_instance_key`

RouteDetails

- New Property: `eth_tag`
- New Property: `evpn_route_type`
- New Property: `rd`
- New Property: `esi`
- New Property: `rmac`
- New Property: `rmac_len`

ShaMonitorExportedMetricDetail

- New Property: `destinations`
- New Property: `metric_key`

SharedResource

- New Property: `with_permission`

StandardHostSwitch

- New Property: `perf_nic_offload`

SubnetStatistics

- New Property: `vlan_extension`

Tier0

- New Property: `tgw_transit_subnets`

Tier0GatewayState

- New Property: `tgw_attached_interfaces`

TraceflowObservationDelivered

- New Property: `uplink_name`

TraceflowObservationDropped

- New Property: `dst_connectivity_policy_internal_id`
- New Property: `src_connectivity_policy_internal_id`

TraceflowObservationDroppedLogical

- New Property: `next_vpc_id`

TraceflowObservationForwarded

- New Property: `lport_name`
- New Property: `lport_id`

TraceflowObservationForwardedLogical

- New Property: `src_connectivity_policy_internal_id`
- New Property: `lr_forward_type`
- New Property: `vlan_extension_result_info`
- New Property: `dst_connectivity_policy_internal_id`

TraceflowObservationReceived

- New Property: `lport_name`
- New Property: `lport_id`

TraceflowObservationReceivedLogical

- New Property: `vlan_extension_basic_info`

TransitGateway

- New Property: `span`
- New Property: `external_ip_signaling_mode`

TransitGatewayAttachment

- New Property: `urpf_mode`
- New Property: `route_advertisement_rules`

TransitGatewayAttachmentStatistics

- New Property: `last_update_timestamp`

TransitGatewayNatRule

- New Property: `scope`

TransitGatewayState

- New Property: `network_stack`

TransportNodeCollectionState

- New Property: `span_associations`

TransportNodeDeploymentProgressState

- New Property: `current_step`

TransportNodeHealthCheckResult

- New Property: `transport_node_name`
- New Property: `result_status`

TransportNodeState

- New Property: `network_span_path`

TunnelProperties

- New Property: `remote_node_path`

VDSFolderState

- New Property: `folder_display_name`

VmApplianceState

- New Property: `allow_ssh_root_login`

VmPlacementState

- New Property: `form_factor`

VpcAttachment

- New Property: `preferred_default_snat_ip`

VpcIpAddressBlock

- New Property: `cidrs`
- New Property: `ranges`
- New Property: `excluded_ips`

VpcNatConfig

- New Property: `auto_snat_ip_block`

VpcSecurityProfile

- New Property: `east_west_firewall`

VpcServiceProfile

- New Property: `service_subnet_cidrs`

VpcState

- New Property: `network_stack`

VpcStateNodeStatus

- New Property: `service_instance_status`

VpcStatus

- New Property: `span`

VpcSubnet

- New Property: `vlan_connection`

VpcSubnetStatus

- New Property: `vlan_extension`

VpcSubnetStatusListResult

- New Property: `span`

VpcTransitGatewayStatusResult

- New Property: `span`

VrniGlobalCollector

- New Property: `collector_fqdn`

VrniStreamingGlobalCollector

- New Property: `collector_fqdn`

WaveFrontGlobalCollector

- New Property: `collector_fqdn`

Deprecated Structures

No changes.

Deleted Structures

Structure Name
ChildVpcSubnetBridgeProfile

Changelog for VCF PowerCLI 9.1

Overview

This document outlines all changes made to the VCF PowerCLI modules and cmdlets across various VCF components. The current page provides a summarized view of these changes, which include newly introduced commands, deleted commands, deprecated commands and updated commands. For detailed information on each change, click the hyperlink associated with each Module. This will redirect you to a dedicated page containing comprehensive details about the specific modifications.

VMware vSphere And vSAN

MODULE	NEW COMMANDS	DEPRECATED COMMANDS	DELETED COMMANDS	UPDATED COMMANDS	TYPES CHANGES
VMware.VimAutomation.Vpc	33	0	0	2	22
VMware.ImageBuilder	0	0	0	3	0
VMware.VimAutomation.Core	0	0	0	8	5
VMware.VimAutomation.Storage	3	0	0	1	2
NEW VMware.Vcf.Sso	1	0	0	0	1

VCF SDDC Manager

MODULE	NEW COMMANDS	DEPRECATED COMMANDS	DELETED COMMANDS
VMware.Vcf.SddcManager	4	0	0

Changelog for VCF PowerCLI VMware.VimAutomation.Vpc

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Commands	33	2	0	0
Structures	19	3	0	0

Total changes: 57

Commands Changes

New Commands

Command Name	
Get-VpcAlarm	
Get-VpcConnectivityPolicy	
Get-VpcEdgeCluster	
Get-VpcExternalConnection	
Get-VpcGroup	
Get-VpcNatRule	
Get-VpcNatRuleStatistics	
Get-VpcServiceCluster	
Get-VpcSpan	
Get-VpcTransitGateway	
Get-VpcVcCluster	
New-VpcConnectivityPolicy	
New-VpcConnectivityProfile	
New-VpcExternalConnection	
New-VpcGroup	
New-VpcIpBlock	
New-VpcSpan	
New-VpcTransitGateway	
Remove-VpcConnectivityPolicy	
Remove-VpcConnectivityProfile	
Remove-VpcExternalConnection	
Remove-VpcGroup	
Remove-VpcIpBlock	
Remove-VpcSpan	
Remove-VpcTransitGateway	

Command Name	
Set-VpcConnectivityPolicy	
Set-VpcConnectivityProfile	
Set-VpcExternalConnection	
Set-VpcGroup	
Set-VpcIpBlock	
Set-VpcServiceProfile	
Set-VpcSpan	
Set-VpcTransitGateway	

Updated Commands

Set-Vpc

- Added parameter 'ConnectivityProfile'
- Added parameter 'ConnectivityPolicy'

New-Vpc

- Added parameter 'ConnectivityProfile'
- Added parameter 'ConnectivityPolicy'

Deprecated Commands

No changes.

Deleted Commands

No changes.

Type Changes

New Types

Structure Name	
VMware.VimAutomation.Vpc.Types.V1.VpcAlarm	
VMware.VimAutomation.Vpc.Types.V1.ConnectivityPolicyType	
VMware.VimAutomation.Vpc.Types.V1.Span	
VMware.VimAutomation.Vpc.Types.V1.FirewallMatch	
VMware.VimAutomation.Vpc.Types.V1.TransitGateway	
VMware.VimAutomation.Vpc.Types.V1.ConnectivityPolicy	
VMware.VimAutomation.Vpc.Types.V1.ExternalConnectionType	
VMware.VimAutomation.Vpc.Types.V1.NatRule	
VMware.VimAutomation.Vpc.Types.V1.NatRuleAction	
VMware.VimAutomation.Vpc.Types.V1.NatType	
VMware.VimAutomation.Vpc.Types.V1.GroupType	
VMware.VimAutomation.Vpc.Types.V1.ExternalConnection	
VMware.VimAutomation.Vpc.Types.V1.MonitoringSeverity	
VMware.VimAutomation.Vpc.Types.V1.Group	
VMware.VimAutomation.Vpc.Types.V1.NatRuleStatistics	
VMware.VimAutomation.Vpc.Types.V1.ServiceCluster	

Structure Name	
VMware.VimAutomation.Vpc.Types.V1.EdgeCluster	
VMware.VimAutomation.Vpc.Types.V1.MonitoringStatus	
VMware.VimAutomation.Vpc.Types.V1.VcCluster	

Updated Types

VMware.VimAutomation.Vpc.Types.V1.ConnectivityProfile

- Added property 'EdgeCluster'
- Added property 'ServiceCluster'
- Added property 'TransitGateway'
- Added property 'ProfileId'
- Added property 'Path'
- Added property 'Name'
- Added property 'Id'

VMware.VimAutomation.Vpc.Types.V1.ServiceProfile

- Added property 'ProfileId'
- Added property 'Id'
- Added property 'Name'

VMware.VimAutomation.Vpc.Types.V1.IpBlock

- 'Type' changed from System.String to System.String[] for property Cidr
- Added property 'SubnetExclusive'
- Added property 'IpRange'
- Added property 'ReservedIp'
- Added property 'IpBlockId'
- Added property 'Id'
- Added property 'Name'

Deleted Types

No changes.

Changelog for VCF PowerCLI VMware.ImageBuilder
These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Commands	0	3	0	0
Structures	0	0	0	0

Total changes: 3

Commands Changes

New Commands

No changes.

Updated Commands

New-IsoImage

- Added parameter 'SkipReservedVibsCaching'

New-OfflineBundle

- Added parameter 'SkipReservedVibsCaching'

New-PxeImage

- Added parameter 'SkipReservedVibsCaching'

Deprecated Commands

No changes.

Deleted Commands

No changes.

Type Changes

New Types

No changes.

Updated Types

No changes

Deleted Types

No changes.

Changelog for VCF PowerCLI VMware.VimAutomation.Core
These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Commands	0	8	0	0
Structures	0	5	0	0

Total changes: 13

Commands Changes

New Commands

No changes.

Updated Commands

New-VM

- Type changed from System.Int32 to System.Int32[] for parameter CoresPerSocket
- Added parameter 'CoresPerNumaNode'

Set-VMHostAuthentication

- Added parameter 'ProxyVcenterIPAddress'

New-NetworkAdapter

- Added parameter 'ExternalIp'

Set-VM

- Type changed from System.Int32 to System.Int32[] for parameter CoresPerSocket
- Added parameter 'AssignCoresPerNumaNodeAtPowerOn'
- Added parameter 'AssignCoresPerSocketAtPowerOn'
- Added parameter 'CoresPerNumaNode'

New-VMHostNetworkAdapter

- Added parameter 'VSphereBackupNfcEnabled'
- Added parameter 'VsanWitnessEnabled'
- Added parameter 'VsanStorgeClusterClientEnabled'
- Added parameter 'VSphereReplicationEnabled'
- Added parameter 'VSphereReplicationNfcEnabled'
- Added parameter 'NVMeTcpEnabled'
- Added parameter 'ProvisioningEnabled'
- Added parameter 'NVMeRdmaEnabled'

Set-NetworkAdapter

- Added parameter 'ExternalIp'

Set-VMHostNetworkAdapter

- Added parameter 'VsanWitnessEnabled'
- Added parameter 'VsanStorgeClusterClientEnabled'
- Added parameter 'NVMeTcpEnabled'
- Added parameter 'NVMeRdmaEnabled'

Connect-VIServer

- Added parameter 'VcfApiToken'
- Added parameter 'VcfOAuthSecurityContext'

Deprecated Commands

No changes.

Deleted Commands

No changes.

Type Changes

New Types

No changes.

Updated Types

VMware.VimAutomation.ViCore.Types.V1.VM.Snapshot

- Added property 'SizeOnDiskGB'
- Added property 'SizeOnDiskMB'

VMware.VimAutomation.ViCore.Types.V1.Inventory.VirtualMachine

- Updated 'IsNullable' from 'false' to 'true' for property 'CoresPerSocket'
- Added property 'AssignCoresPerSocketAtPowerOn'
- Added property 'CoresPerNumaNode'

- Added property 'AssignCoresPerNumaNodeAtPowerOn'

VMware.VimAutomation.ViCore.Types.V1.Vpc.Vpc

- Added property 'Span'
- Added property 'ConnectivityPolicyPath'
- Added property 'ConnectivityPolicy'
- Added property 'ConnectivityProfilePath'
- Added property 'Alarm'

VMware.VimAutomation.ViCore.Types.V1.Vpc.Subnet

- Added property 'Span'
- Added property 'Alarm'

VMware.VimAutomation.ViCore.Types.V1.Vpc.Project

- Added property 'Span'

Deleted Types

No changes.

Changelog for VCF PowerCLI VMware.VimAutomation.Storage
These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Commands	3	1	0	0
Structures	1	1	0	0

Total changes: 6

Commands Changes

New Commands

Command Name	
Add-VsanRemoteDatastore	
Get-VsanEffectiveCapacity	
Remove-VsanRemoteDatastore	

Updated Commands

Set-VsanClusterConfiguration

- Added parameter 'XVCDatastores'
- Added parameter 'RemoteDatastores'
- Added parameter 'DeconvergedNetConfigEnabled'

Deprecated Commands

No changes.

Deleted Commands

No changes.

Type Changes

New Types

Structure Name	
VMware.VimAutomation.Storage.Types.V1.Vsan.VsanEffectiveCapacity	

Updated Types

VMware.VimAutomation.Storage.Types.V1.Vsan.VsanClusterConfiguration

- Added property 'DeconvergedNetConfigEnabled'

Deleted Types

No changes.

Changelog for VCF PowerCLI VMware.Vcf.Sso

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Commands	1	0	0	0
Structures	1	0	0	0

Total changes: 2

Commands Changes

New Commands

Command Name	
New-VcfOAuthSecurityContext	

Updated Commands

No changes

Deprecated Commands

No changes.

Deleted Commands

No changes.

Type Changes

New Types

Structure Name	
VMware.Vcf.Sso.Types.VcfOAuthSecurityContext	

Updated Types

No changes

Deleted Types

No changes.

Changelog for VCF PowerCLI VMware.Vcf.SddcManager
These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Commands	4	0	0	0
Structures	3	0	0	0

Total changes: 7

Commands Changes

New Commands

Command Name	
Get-SddcTask	
Remove-SddcCluster	
Remove-SddcDomain	
Remove-SddcHost	

Updated Commands

No changes

Deprecated Commands

No changes.

Deleted Commands

No changes.

Type Changes

New Types

Structure Name	
VMware.Vcf.SddcManager.Api.Model.FullTaskStatus	
VMware.Vcf.SddcManager.Api.Model.ResolutionStatus	
VMware.Vcf.SddcManager.Types.Task	

Updated Types

No changes

Deleted Types

No changes.

Bill of Materials 9.1.0

This document contains the following sections

- Introduction
- Upgrade Sequence for VCF 9.1 and vSphere Foundation 9.1
- Bill of Materials (BOM)
- Dependencies

Introduction

VMware Cloud Foundation 9.1 | 12 MAY 2026

Upgrade Sequence for VCF 9.1 and vSphere Foundation 9.1

IMPORTANT: Upgrading your environment to version 9.1 requires a strict component upgrade sequence. See Upgrade Sequence to 9.1.

Bill of Materials (BOM)

VMware Cloud Foundation (VCF) is comprised of the following components listed in the Bill of Materials (BOM) table. The components in the BOM are interoperable and compatible. You can select which components to apply in your deployment based on the impact to your environment and operational costs. The Broadcom Support Portal allows you to download the appropriate set of bits based on your entitlement.

VMware Cloud Foundation Component	VMware vSphere Foundation Component	Version	Build Number
VCF Installer/ SDDC Manager	Yes (VCF Installer only)	9.1.0.0	25371088
ESX	Yes	9.1.0.0	25370933
vCenter	Yes	9.1.0.0	25370922
vSAN ESA Witness	Yes	9.1.0.0	25370927
vSAN File Services	Yes	9.1.0.0	25370922
vSAN OSA Witness	Yes	9.1.0.0	25370925
NSX	-	9.1.0.0	25318225
VCF Operations	Yes	9.1.0.0	25346025
Cloud proxy	Yes	9.1.0.0	25346033
License server	Yes	9.1.0.0	25346031
VCF Operations for networks	-	9.1.0.0	25318550
VCF Operations HCX	-	9.1.0.0	25318520
VCF Operations orchestrator	Yes	9.1.0.0	25346069
VCF Automation	-	9.1.0.0	25370929
Supervisor	Yes	9.1.0.0	25370922
VKS Standard Packages	Yes	3.6.0+20260211	N/A
vSphere Kubernetes releases	Yes	1.34.2+vmware.2-vkr.2	N/A
VMware vSphere Kubernetes Service	Yes	3.6.1+v1.35	N/A
Fleet lifecycle	Yes	9.1.0.0	25371109
Identity broker	-	9.1.0.0	25368698
Log management	Yes	9.1.0.0	25346055
Real-time metrics	-	9.1.0.0	25346020
Real-time metrics store	-	9.1.0.0	25346020
Salt RaaS	-	9.1.0.0	25346036
Salt master	-	9.1.0.0	25346036
SDDC lifecycle	Yes	9.1.0.0	25371107
Software depot	Yes	9.1.0.0	25371105
Telemetry	Yes	9.1.0.0	25181946
VCF services runtime	Yes	9.1.0.0	25370367
VCF download tool	Yes	9.1.0.0	25371089

VMware Cloud Foundation Component	VMware vSphere Foundation Component	Version	Build Number
VMware Remote Console	Yes	13.1.0.0	25236164
VMware Tools	Yes	13.1.0.0	25294452
VCF Consumption CLI	Yes	9.1.0.0	25296329
VCF Consumption CLI Plugins & Database	Yes	9.1.0.0	25305443

Supervisor Services

VMware Cloud Foundation Component	VMware vSphere Foundation Component	Version	Build Number
Harbor (Supervisor)	Yes	9.1.0.0	25220498
Argo CD Supervisor Service	Yes	9.1.0.0	25100889
CA cluster issuer Supervisor service	Yes	9.1.0.0	25317155
Contour Supervisor Service	Yes	9.1.0.0	25276585
External DNS Supervisor Service	Yes	9.1.0.0	25276584
Supervisor Management Proxy	Yes	9.1.0.0	25317170

VCF Services

VMware Cloud Foundation Component	Included in VCF SKU	Version	Build Number
Secret Store Service	Yes	9.1.0.0	25367485
Migration service engine	Yes	9.1.0.0	25370929
VKS Cluster Management	Yes	9.1.0.0	25370929
Configuration Service	Yes	9.1.0.0	25303350
DSM Data Services	Add-on	9.1.0.0	25367580
Encryption Management	Yes	9.1.0.0	25370929
Metrics Aggregator Package	Yes	9.1.0.0	25317134
Protection and Recovery	Add-on	9.1.0.0	25369307
Harbor	Yes	9.1.0.0	25370929

The following VMware Cloud Foundation add-ons are interoperable with the components from the VCF BOM above:

VMware Cloud Foundation Add-on	VMware vSphere Foundation	Version	Build Number
Deep learning VM	-	9.1.0.0	N/A (see Dependencies)
VMware Data Services Manager	-	9.1.0.0	25367580
Protection and Recovery	Yes	9.1.0.0	25367487

Dependencies

- The Product Interoperability Matrix provides the upgrade order dependencies.
- The functionality of VMware Private AI Foundation with NVIDIA is delivered as a combination of components. Some are bundled within the VCF software bits, while others are delivered separately.
  The following components are a part of the VCF software:
  - Guided deployment workflow in the vSphere Client
  - AI catalog items in VCF Automation
  The following components are delivered separately from VCF 9.1:

  - VMware Deep Learning VM 9.1 Build 25217931
    For more information about VMware Deep Learning VM image releases, see the VMware Deep Learning VM Release Notes.
  - Private AI Services 2.0.89
    For more information about Private AI Services releases, see the VMware Private AI Services Release Notes.
- Third-party products from the VCF ecosystem maintain their existing dependencies at the component level. For example, OEM driver add-ons, ESX device drivers, and UI plugins.
- VCF versioning is not applicable to any component with external dependency for the version, such as the Kubernetes version.
- Clusters that don't have active VMware Supervisor are supported, but do not support key capabilities of VCF, such as VCF Automation workflows.

Product Support Notes

This document contains the following sections

- Introduction
- VCF-level
- ESX
  - Deprecation Notes
  - Other Notes
- vCenter
  - Deprecation Notes
  - End of Support Notes
  - Other Notes
- vSAN
- NSX
  - Deprecation Notes
  - End of Support Notes
- VCF Installer
  - End of Support Notes
- VCF Operations
  - Deprecation Notes
  - End of Support Notes
  - Other Notes
- VCF Automation
- VCF APIs
  - Deprecation Notes
  - End of Support Notes
  - Other Notes
- VMware Cloud Foundation Java SDK
  - Compatibility Notes
- VMware Cloud Foundation Python SDK
  - Compatibility Notes
- VMware Cloud Foundation PowerCLI
  - Deprecation Notes

Introduction

See key product support notes for VMware Cloud Foundation 9.1 listed within each component:

VCF-level

Deprecation of SHA1-based cryptographic algorithms:

Usage and dependencies on SHA1-based cryptographic algorithms are deprecated and will be removed in a future VCF release.

ESX

Deprecation Notes

ESX System Storage Deprecations:

Starting with VCF 9.1, support is deprecated and will be removed in the next major release for the following:

- USB and SD boot devices
- ESX without a persistent system storage device for OSDATA partition
- ESX with system storage device of less than 32 GB
- APIs for reconfiguring the system storage locations

Deprecation of suspend-to-RAM option during ESX upgrades:

Support for the suspend-to-RAM option during ESX upgrades is deprecated and will be removed in a future VCF release. You can use suspend-resume or vSphere vMotion in maintenance mode as a less complicated and state-preserving alternative.

Deprecation of Marvell/Aquantia (Atlantic) NIC devices and drivers:

VCF 9.1 deprecates Marvell/Aquantia (Atlantic) NIC drivers for VMware ESX that enable 10GbE networking for USB-based and PCIe devices commonly used in home labs. Support for the Marvell/Aquantia (Atlantic) NIC devices and drivers will be removed in a future VCF release.

Deprecation of AMD Solarflare 8000 and X2 series Ethernet adapters:

With VCF 9.1, AMD Solarflare 8000 and X2 series Ethernet adapters are deprecated and support will be removed in a future VCF release.

Marvell E3 and E4 Drivers Deprecation:

Support for Marvell's Converged Network Adapters (CNAs) FastLinQ 57800/57810/57811 series and FastLinQ 41000/45000 series is deprecated in VCF 9.1 and will be be discontinued in a future major release**.**

Cisco Virtual Interface Card (VIC) 1200 and 1300 Series Deprecation:

Support for Cisco Virtual Interface Card (VIC) 1200 and 1300 series devices is deprecated in VCF 9.1 and will be discontinued in a future major release due to lack of support for Enhanced Data Path (EDP).

Other Notes

Expiration of Microsoft 2011 Secure Boot Certificates:

Microsoft UEFI and KEK CA 2011 certificates, which affect the Secure Boot capability for ESX hosts and Linux guests, expire in June 2026, while the Windows Production PCA 2011 certificate, which affects the Secure Boot capability for Windows guests, expires in October 2026. The expiration of the 2011 certificates only prevents Microsoft from creating new signatures with them; it does not invalidate existing signatures created prior to the expiration. Therefore, any version of ESX that can Secure Boot on a host machine before the expiration can still do so afterward, unless you actively remove the expired certificate from the machine's firmware, which is not generally recommended.

ESX 9.1 is multiply signed by:

- Microsoft UEFI CA 2011 certificate
- Microsoft UEFI CA 2023 certificates, including certain components that require the Microsoft Option ROM UEFI CA certificate
- VMware Secure Boot Signing certificate

Therefore, host Secure Boot of ESX 9.1 generally is not affected by the 2011 certificates expiration. The 2011 certificates expiration has more complex effects on virtual machines running Windows and Linux guests. For more details, see KB article 423893.

Deprecated use of First Class Disk in NFS v.3 datastores shared by more than 128 ESX hosts:

The use of First Class Disk (FCD), also known as an Improved Virtual Disk (IVD), in NFS v.3 datastores that are shared by more than 128 ESX hosts, is not supported.

vCenter

Deprecation Notes

Deprecation of Internet Protocol Flow Information Export (IPFIX):

With VCF 9.1, the following options are deprecated and will be removed in a future major release:

- Using IPFIX on a VMware vSphere Distributed Switch (VDS) Uplink Port Group.
- Use the `LagIpfixConfig` class, which defines the IPFIX configuration of the Link Aggregation Control Protocol (LACP) group. `LagIpfixConfig` is in the VMware Storage Policy API.
- Set Override port policies for IPFIX on a VDS to enable monitoring on uplink port groups. If IPFIX is already active on uplink port groups or LACP ports, vCenter upgrade is blocked. You see an error message to remove the IPFIX configurations before proceeding with the upgrade.

End of Support Notes

Blocking port 514:

Starting with vCenter 9.1, the unencrypted port 514 (UDP/TCP) is blocked for use and any syslog data transfers to vCenter by port 514 are no longer supported. You can use port 1514, which supports secure, TLS-encrypted connections, for all syslog traffic to vCenter. If you are using the `syslog.ext.port` option for scripted CLI installations, you must switch to using the `syslog.ext.tls.port` option.

Removal of vSphere Cluster Services:

Starting with vCenter 9.1, vSphere Cluster Services (vCLS) is deactivated by default and you cannot re-activate the capability. All remaining APIs and configurations are not supported and will be removed in the next major release.

Other Notes

Extended vCenter API that sets the global policy for local accounts:

VCF 9.1 extends the vCenter API that sets the global policy for local accounts, (`PUT /api/appliance/local-accounts/global-policy`) to change existing user configurations, along with its current functionality to configure password expiration for new users. If you need to set the configuration of a certain user as different from the global policy, you can create an exception by using another local accounts API (`PATCH /api/appliance/local-accounts/{username}`).

vSAN

None

NSX

Deprecation Notes

Deprecation announcement for “LagIpfixConfig” and “overwrite port policy Netflow”

VDS IPFIX will be backed with NSX Connection Track based IPFIX data path to export TCP connection information. However, the Connection Track based IPFIX does not support uplink port due to performance constraints. As IPFIX will not be supported on the uplink port group, the dependent “LagIpfixConfig” and “overwrite port policy Netflow” will not be supported.

End of Support Notes

Removal of Logical MP API for port mirroring

Logical MP API for port mirroring is no longer supported.

VCF Installer

End of Support Notes

Removal of all vSphere Cluster Services functionality from VCF Installer UI and SDDC Manager UI

In VCF 9.0, vSphere Cluster Services (vCLS) is decoupled from Distributed Resource Scheduler (DRS) and vSphere High Availability (HA). In VCF 9.1, all vCLS functionalities available in SDDC Manager UI and VCF Installer UI are removed. vCLS will be deprecated in a future release.

VCF Operations

Deprecation Notes

Compliance feature is now deprecated and replaced by Security Posture Management

Security Posture Management offers enhanced assessment and remediation capabilities for VCF. For more information, see Security Posture Management.

Deprecation announcement for the support of PhotonOS-based appliances in VCF Operations HCX

A new stack based on NSX Edge is being introduced that has a better performance than the PhotonOS stack. Therefore, the PhotonOS-based appliances in VCF Operations HCX is being deprecated.

Deprecation of the legacy cluster expansion method in VCF Operations 9.1

In VCF Operations, the legacy method for expanding an existing cluster via the newly deployed node is deprecated in VCF 9.1.

Deprecation of Microsoft Azure and Amazon Web Services as data sources in VCF Operations for networks

Azure and AWS data sources are now deprecated.

Deprecation of bundled OpenSSL in VCF Operations for logs Agent

The VCF Operations for logs Agent fails to function on host systems that do not have OpenSSL version 3 or higher installed. Starting with VCF Operations for logs Agent 9.1.0, the OpenSSL library is no longer bundled within the agent package. Instead, the agent has transitioned to using the system's default OpenSSL library to handle cryptographic operations. To ensure the agent functions correctly, you must either update their host system to a version that includes OpenSSL 3 or higher or continue utilizing an older version of the agent that includes the bundled library.

End of Support Notes

Removal of vCenter Assessment report feature

The vCenter Assessment report is removed from VCF Operations for networks.

End of General Support for VCF Operations for logs (previously known as VMware Aria Operation Logs) Content Packs

Starting with VCF 9.1 , you will not be able to use VMware Aria Operation for logs (VCF Operations for logs (previously VMware Aria Operation Logs) content packs in VCF Operations. For all 3rd party content packs, you must convert your content packs into management packs. These converted management packs can then be used in VCF Operations. For more details, see Converting Content Packs to Management Packs.

Effective with the VCF 9.1 release, direct vCenter authentication for VCF Operations has been removed

The list of vCenter instances is no longer available on the VCF Operations login screen, and API authentication using vCenter user credentials is no longer supported.

The Network Share plugin has been removed starting from version 9.1

During an upgrade to VCF 9.1 or later, any existing Network Share plugin, its configurations, and related data are automatically removed. This is because beginning with VCF 9.1, FIPS compliance is enabled by default and cannot be disabled. The Network Share plugin relies on components that are not compatible with FIPS requirements and is therefore no longer supported. As an alternative, use the Standard Email plugin to deliver generated reports as email attachments to specified recipients instead of copying them to a network share.

VCF Operations Configuration Drifts functionality has now been incorporated into the new VCF Operations Fleet Configuration Management service

Standalone Management Pack Builder Appliance

The standalone Management Pack Builder appliance is no longer supported or actively maintained. To ensure continued updates and technical support, please transition to the in-product Management Pack Builder introduced in VCF Operations 9.0.

Other Notes

Support for Windows log agent

VCF 9.1 adds Fluent Bit as a supported version for Windows to collect Windows Event Logs, including System and Security logs. Download the supported Fluent Bit MSI file from here.

Support for open source Telegraf agents:

VCF 9.1 adds support for the installation of open source Telegraf agents for configurations required for VCF Operations cloud proxies. Support extends to the initial configuration, which provides a consistent flow of metrics to endpoints with no common failure patterns observed on VCF Operations. For queries on agent operations beyond this scope, use the Telegraf open source community. For more information, see Monitoring Application Services and Operating Systems using Open Source Telegraf and Open Source Telegraf Troubleshooting.

Important Upgrade Guidance for VCF Operations

- **Customers planning to upgrade to VCF Operations 9.0.x:**
  Do not upgrade to VCF Operations 8.18.6. Instead, upgrade directly to VCF Operations 9.0.x.
- **Customers who have already upgraded to VCF Operations 8.18.6:**
  To continue the upgrade path to the 9.x stream, you must wait for a subsequent release, such as VCF 9.1 or VCF Operations 9.0.3, or a later version.

VCF Automation

None

VCF APIs

Deprecation Notes

VCF Operations for Networks API

This API surface experienced the most significant deprecations within the Operations component, and clients relying on usage data or proxy secrets should be updated.

- **Deprecated Operations (22):** A total of 22 operations have been marked as deprecated and should be migrated to replacement routes before future removal.

For detailed information, see What's changed in VCF Operations for Networks API in the API Reference documentation.

SDDC Manager APIs

- Deprecated Operations
  - **Deprecated Operations (21):** A total of 21 operations have been marked as deprecated.
  - **Affected Areas:** Deprecations primarily affect edge cluster operations (list, create, update, and validation APIs), enabling domain overlays, system DNS and NTP configurations, and upgrade precheck operations.
  - **Impact:** Operators should follow replacement guidance and plan migrations off these endpoints before they are removed in a later release.

For detailed information, see What's changed in SDDC Manager API in the API Reference documentation.

vSphere Automation API

This surface contains the most significant updates in the vSphere component. Scripts and integrations relying on Hybrid Linked Mode (HVC) must be updated to supported workflows.

- **Deprecated Operations (28) & Schemas (30):** A broad set of namespace management operations, cluster upgrades, and appliance health endpoints have been deprecated and should be migrated to replacements before future removal.

For detailed information, see What's changed in vSphere Automation API in the API Reference documentation.

Virtual Infrastructure (VI) JSON API

The VI JSON API surface is primarily additive in this release, with no deleted operations or deleted schemas.

- **Deprecated Schemas (4):** Four event and configuration schemas are deprecated and should not be used in new workflows: `DrsRuleComplianceEvent`, `VMwareDvsLagIpfixConfig`, `VsanHostIpConfig`, and `VsanHostIpConfigEx`.

For detailed information, see What's changed in Virtual Infrastructure JSON API in the API Reference documentation.

End of Support Notes

Virtual Infrastructure (VI) JSON API

The VI JSON API surface is primarily additive in this release, with no deleted operations or deleted schemas.

- **Deleted Operations & Schemas:** 0 operations and 0 schemas were removed.

For detailed information, see What's changed in Virtual Infrastructure JSON API in the API Reference documentation.

vSphere Automation API

This surface contains the most significant removals in the vSphere component. Scripts and integrations relying on Hybrid Linked Mode (HVC) must be updated to supported workflows.

- **Deleted Operations (9):** Removed REST operations focused entirely on Hybrid Linked Mode (HVC) links and HVC management administrators. This includes **GET**, **POST**, **PUT**, and **DELETE** paths for listing, creating, retrieving, setting, and removing HVC links and administrators.
- **Deleted Schemas (9):** Removed payload and response models related to the deleted HVC link APIs. Key removals include **Vapi Metadata SourceType**, **Vcenter Hvc Links CreateSpec**, and **Vcenter Hvc Links Info**.

For detailed information, see What's changed in vSphere Automation API in the API Reference documentation.

SDDC Manager APIs

- Deleted Operations & Schemas
  - **Deleted Operations:** 0 operations were removed in this release.
  - **Deleted Schemas (2):** The **PartnerExtensionSpec** and **VcfOperationsFleetManagementSpec** structures were removed. Clients and shared models should drop imports of these deleted types to align with parallel removals in the VCF Installer surface.

For detailed information, see What's changed in SDDC Manager API in the API Reference documentation.

VCF Operations for Networks API

This API surface experienced the most significant removals within the Operations component, and clients relying on usage data or proxy secrets should be updated.

- **Deleted Operations (1):** Removed the **GET Get Migration Wave** operation.
- **Deleted Structures (13):** Removed schemas related to CSP management, customer usage reporting, licensing enforcement, metadata types, and proxy secret requests. Specific removed structures include **CspManagementResponse**, **CustomerUsageData**, **LicenseUsageEnforcement**, **ProxySecret**, and **ProxyUrl**, among others.

NSX Manager API

A total of 17 operations have been removed from the NSX Manager API. These removals primarily affect the following functional areas:

- **System Health Agent (SHA) Metrics and Monitoring:** Removed operations related to plugin- and host-level SHA metric management. This includes endpoints for retrieving real-time metrics, reading monitor status, and deleting metric data by Host ID.
- **Port Mirroring:** Removed operations for managing port mirroring (SPAN) sessions. This includes endpoints for creating, verifying, updating, deleting, and retrieving mirror stack status.
- **Node User Enumeration:** Removed operations associated with listing local node users across clusters, transport nodes, and individual management nodes.

vStats related APIs which were in TechPreview state are removed in VCF 9.1

In VCF 9.1, the vStats APIs (previously in Tech Preview) are removed. You can use the new Real Time Metrics API. For more information about the Real Time Metrics API, refer to the *Real-time metrics* section in VCF Operations What's New.

NSX Policy API

A total of 9 operations have been removed from the NSX Policy API, affecting the following resource groups:

- **VPC Subnet Bridge Profiles:** Removed the complete lifecycle operations (`GET`, `PUT`, `PATCH`, and `DELETE`) for VPC Subnet Bridge Profiles.
- **PMaaS Firewall Exclude Lists:** Removed the `GET`, `PUT`, and `PATCH` operations used to manage PMaaS firewall exclude lists.
- **Infrastructure Policy Labels:** Removed the `PUT` (Create/Replace) and `PATCH` (Update) operations for Infrastructure Policy Labels within Organization and Project multi-tenancy contexts.

NSX Autonomous Edge API

A single operation has been removed from the NSX Autonomous Edge API:

- **Edge Node User Enumeration:** Removed the `GET` operation used to list local node users directly on Autonomous Edges.

Provider Infrastructure APIs

This API surface experienced the most significant deprecation in the 9.1 release and should be treated as a top migration priority.

- **Deleted Operations (369):** Broad removals (including 154 `GET`, 56 `Update`, 43 `Create`, and 42 `Query` operations) covering provider- and tenant-scoped areas. Affected resources include app templates, EULAs, catalogs, org/VDC storage and compute, access-control grants, SDDC and Kubernetes resources, quota policies, and virtual machine snapshots.
- **Deleted Structures (101):** Widespread removal of request/response and projection schemas. Key removals include `AppTemplate`, `Catalog`, `OrgVdc`, `ProviderVdc`, `QuotaPolicy`, `Sddc`, `StoragePolicy`, `KubernetesNamespace`, and 81 other named schema types.

VM Apps Org APIs

Removals in the VM Apps functional area primarily affect approvals, metadata retrieval, and content gateways.

- **Approvals & Deployment Metric:** 68 `GET` operations were removed from both the Approval and Deployment Metric APIs. These were read helpers for cloud accounts, approval-policy actions, approver roles, and supporting metadata like regions, tags, flavors, and OS/owner types. Both APIs also removed the `DataElement` and `PageDataElement` structures.
- **Content Gateway:** 7 operations and 15 structures were removed, directly impacting domain enumeration, service account modifications, and service credential generation.
- **ABX:** Removed 6 structures related to Action and run-related projections (e.g., `ActionCountById`, `ActionProjection`, `PageActionRunProjection`).
- **Custom Forms:** Removed 3 structures: `FormExtValueResponseObject`, `Link`, and `SortObject`.
- **Onboarding:** Removed 1 operation (`GET Handle Get_9`) and 1 structure (`About`).
- **Orchestrator Gateway & Project:** Both APIs removed the `SortObject` structure.

All Apps Org APIs

Removals in the All Apps functional area largely mirror the VM Apps area, heavily targeting access control, aggregators, and approvals.

- **Access Control:** 32 operations were removed (mostly `GET` requests). These removals affect org content libraries and items, namespaces, org settings, preferences, regions, zones, VM/storage class queries, and WebMKS ticket creation.
- **Aggregator & Approvals:** 28 `GET` operations were removed from each API. Removals include endpoints for fetching actions for approval policies, supported approver roles, blueprints, catalogs, and tag keys/values. Both APIs also removed the `DataElement` and `PageDataElement` structures.
- **Custom Forms:** Removed 2 structures: `FormExtValueResponseObject` and `Link`.
- **Custom Resource Types, Orchestrator Gateway, & Projects:** These three APIs each saw the removal of the `SortObject` structure.

VCF Operations Orchestrator API

Changes to this API are minor but include one operational removal and one relaxed contract.

- **Deleted Operations (1):** Removed the `POST Add Actions To Package` operation. Workflows that posted additional actions to a package via this route must be reworked or removed.

For detailed information, see What's changed in VCF Operations Orchestrator API in the API Reference documentation.

VCF Installer APIs

- Deleted Operations & Schemas
  - **Deleted Schemas (2):** The `PartnerExtensionSpec` and `VcfOperationsFleetManagementSpec` structures were removed. Clients should be regenerated, and any stored specifications or tools that reference these types (such as fields nested in SDDC or bundle models) must be updated.

For detailed information, see What's changed in VCF Installer API in the API Reference documentation.

Other Notes

VCF Operations Orchestrator API

Changes to this API are minor but include one relaxed contract.

- **Updated Operations (1):** For the `GET /forms` operation, the `conditions` query parameter has been changed from required to optional (`true` to `false`).

For detailed information, see What's changed in VCF Operations Orchestrator API in the API Reference documentation.

VCF Operations API

No operations or structures were deleted or deprecated in the VCF Operations API. However, there are two contract updates that clients must accommodate.

- **Test Alert Plugin Update:** The `POST /suite-api/api/alertplugins/{pluginId}/test` operation now includes a newly added **receiverAddress** request parameter. Test-alert workflows must be updated to supply this address.
- **Get Relationships Update:** For the `GET /suite-api/api/resources/{id}/relationships` operation, the `relationshipType` query parameter is no longer required.

For detailed information, see What's changed in VCF Operations API in the API Reference documentation.

SDDC Manager APIs

Updated Operations & Schemas

- Updated Operations (20):Several REST operations received contract changes that require clients to be refreshed. Key themes include:
  - **Pagination:** Query parameters for `pageNumber` and `pageSize` were added to list operations, such as `GET /v1/alb-clusters(Get Avi LB Clusters)` and other `list-styleGETrequests`.

  - **Async Validation:** An `optionaluseAsyncValidation` parameter was added to several `POST` operations, including those for validating cluster creation specs, vSAN remote datastore specs, and vSAN remote datastore mount specs.
  - **Responses & Parameters:** Various status codes were added or removed (e.g., new 202, 403, or 500 responses, and removed 200 responses on some paths). Additionally, query adjustments were made for `managedObjectReferenceIdonGet Clusters (GET /v1/clusters)`.
  - **Updated Schemas (53):**53 schemas were updated in this release.

For detailed information, see What's changed in SDDC Manager APIin the API Reference documentation.

VCF Installer APIs

- Updated Operations & Schemas
  - **Updated Operations (1):** A contract change was made to the `GET /v1/sddcs/validations/{id}` (Get SDDC spec validation) operation. The previously documented 501 HTTP response has been removed. Clients and tests that expected this 501 response should be revisited and aligned with the updated contract.
  - **Updated Schemas (20):** 20 schemas were updated. Clients should refresh their models and revalidate any JSON mapped to installer types.

For detailed information, see What's changed in VCF Installer API in the API Reference documentation.

vSphere Automation API

Updated Operations (3): Three operations received contract changes requiring client updates:

- `GET /api/vcenter/compute/policies/tag-usage`: Added `policy_namesandcapabilities` query parameters.
- `POST /api/vcenter/namespace-management/networks/nsx/projects/project/vpc-connectivity-profiles/profile_action=check-compatibility`: Added `filter` and `zones` query parameters; a 400 response is now explicitly documented.
- `GET /api/vcenter/namespace-management/software/supervisors/versions`: Added `filter` and `zones` query parameters; a 400 response is now explicitly documented.

For detailed information, see What's changed in vSphere Automation API in the API Reference documentation.

Virtual Infrastructure (VI) JSON API

The VI JSON API surface is primarily additive in this release.

- **Updated Schemas (119):**Property-level changes (fields added, removed, or altered) were made to 119 schemas. Generated models must be refreshed and persisted JSON revalidated against the new types.

For detailed information, see What's changed in Virtual Infrastructure JSON API in the API Reference documentation.

VMware Cloud Foundation Java SDK

Compatibility Notes

The SDK is compatible with the following Java LTS versions: 11, 17, 21, 25. It is strongly recommended to use one of those versions when integrating the SDK into custom applications and when running the samples.

VMware Cloud Foundation Python SDK

Compatibility Notes

All modules of the VCF SDK for Python are compatible and verified with the supported versions of Python at the time of their release. Once a Python version reaches EOL (End-Of-Life), it no longer receives security patches. VCF SDK releases which happen after this moment will not provide compatibility guarantees for the EOL-ed Python version. As generally good practice and for best security posture, it is recommended to use the VCF SDK with an actively maintained version of Python and keeping your environment on the latest patch provided by the Python Software Foundation (PSF).

For VCF release 9.1.0.0, the supported Python versions are 3.10, 3.11, 3.12, 3.13, and 3.14.

VMware Cloud Foundation PowerCLI

Deprecation Notes

Support for Python 3.7 and 3.8:

Starting with VCF 9.,1, support for Python 3.7 and 3.8 is deprecated due to these versions reaching End of Life (EOL). While they remain functional in 9.1, support will be completely removed in the next release. We strongly recommend migrating to Python 3.9 or higher immediately.

Known Issues

See known issues for VCF components in version 9.1:

- vSphere
- vSAN
- NSX
- VCF Installer
- VCF Operations
- VCF Automation
- VCF SDKs, APIs, and CLIs

vSphere

This document contains the following sections

- ESX Known Issues:
  - Memory Tiering Issues
  - Miscellaneous Issues
  - vSphere vMotion Issues
  - Drivers
  - Networking Issues
- vCenter Known Issues:
  - vSphere Client and vCenter Issues
  - Upgrade Issues
  - Miscellaneous Issues
  - Auto Deploy Issues
  - API Issues

ESX Known Issues:

Memory Tiering Issues

In rare cases, during migration or upgrade some virtual machines in clusters with Memory Tiering and DRS might fail to power on

In clusters with Memory Tiering, if Tier-0 (physical DRAM) VMs occupy a significant portion of the DRAM, in rare cases, DRS might fail to place additional VMs correctly during migration or upgrade tasks. Consequently, such VMs might fail to power on after the respective operation.

Workaround: Avoid placing non-tiered (DRAM-only) VMs that occupy a significant portion of the DRAM on memory-tiered hosts.

In the vSphere Client, you see an alarm that a NVMe Memory Tiering device is not healthy

In an ESX host with Memory Tiering and a single NVMe device, if the NVMe device fails and the VM on which the device resides migrates out of the host, the ESX host might also fail. In the vSphere Client, you see an alarm `<ESX host> NVMe Memory Tiering device is not healthy` suggesting that you need to replace the device.

Workaround: Place the ESX host in maintenance mode, replace the NVME device, and use the command `esxcli memtier config set -d <new_device>` to set the Memory Tiering configuration.

You see an alarm for failed vSphere HA failover for some virtual machines in clusters with Memory Tiering

If Tier 0, physical DRAM, resources are insufficient on any ESX host in a cluster with Memory Tiering to satisfy the requirement of VMs with memory reservation to power on, you might see the alarm `vSphere HA virtual machine failover failed` in the **Summary** tab of the vSphere Client. As a result, you might see some VMs, either with memory reservation or not, in a powered off state. vSphere HA might report the alarm even if the overall memory resources in the cluster are sufficient. You might also see the alarm `vSphere HA stopped trying to restart this VM because the maximum VM restart count was reached` for such VMs with failed failover. The issue occurs only in clusters in which some virtual machines use only Tier 0 memory, such as Low Latency VMs, Prealloc VMs, and Fault Tolerant VMs.

Workaround**:** If a virtual machine failover fails in a cluster with Memory Tiering, provide sufficient DRAM resources. You can either add hosts for additional DRAM capacity or reduce current usage, powering off some VMs consuming DRAM for example. Sufficient DRAM resources allow VMs with memory reservation on all ESX hosts to power on. vSphere HA might have stopped trying to restart such VMs and you must manually power them on.

Miscellaneous Issues

ESX host might fail with a purple diagnostic screen due to a rare memory overcommitment scenario

In a rare memory overcommitment scenario, where an ESX host transiently enters a low memory condition and an invalid machine page number (MPN) is accessed during a swap-out operation, the host might fail with a purple diagnostic screen with an error such as `ASSERT bora/vmkernel/mem/swap.c:1201`. The issue occurs only in a combination of the following conditions:

1. Low Memory State: The ESX host is in a low memory state, defined as typically having less than 2% free ESX consumed memory.
2. Encrypted VMs: The issue only affects encrypted VMs.
3. Trigger Event: An encrypted VM is powered on, or an operation like vSphere vMotion migration, VM-resume, or Fast Suspend and Resume (FSR) is executed on the encrypted VM while the host is in the low memory state.

Workaround: When you power on encrypted VMs or plan operations such as migration, FSR, or VM-resume on encrypted VMs make sure that the ESX host is not in a low memory state that might lead to memory overcommitment.

ESX virtual host IP address unexpectedly changes during VM suspend, resume, or snapshot revert operations

In some environments, nested ESX hosts using DHCP-based IP configuration might experience unexpected IP address changes during VM suspend, resume, or snapshot revert operations. The issue occurs when NTP time synchronization introduces a significant time drift, causing the DHCP lease renewal to fail before lease expiration. As a result, the DHCP lease expires and the IP address is released and reassigned, leading to a temporary loss of connectivity .

Workaround: Use a stable NTP server and configure longer DHCP lease duration and renewal timers to ensure sufficient margin for successful lease renewal during transient network events.

You cannot turn on the disk LED by using the command 'esxcli storage core device set -d naa.xxx --led-state error' on lsi_mr3, lsi_msgpt3, lsi_msgpt35, and bcm_mpi3 controllers

The `ERROR LED` operation is not supported for the lsuv2-lsiv2-drivers-plugin. When you use the command `esxcli storage core device set -d naa.xxx --led-state error` on lsi_mr3, lsi_msgpt3, lsi_msgpt35, and bcm_mpi3 controllers, you get an error such as:

```
Not supported':[root@xxx:~] esxcli storage core device set -d naa.xxx --led-state error
Unable to set LED state for device naa.xxx: Not supported!
```

This issue does not impact turn on/off LED operations from the vSphere Client.

Workaround: You can turn on the LED from the vSphere Client or use the following `LOCATOR LED` command:

```
[root@xxx:~] esxcli storage core device set -d naa.xxx --led-state locator --led-duration
100
```

Intel Xeon 6 processors utilizing QAT accelerators might see increased boot times on ESX 9.1

On Intel Xeon 6 processors systems using QAT devices, in some cases, the boot time for ESX hosts might increase.

Workaround: None. This issue will be fixed in a future patch release.

vSphere vMotion Issues

You cannot migrate an NVIDIA Enhanced DirectPath I/O device from one distributed virtual switch to another if the switches have a different number of uplinks

NVIDIA firmware does not support vSphere vMotion operations between configurations that use different uplink settings. As a result, you cannot migrate an Enhanced DirectPath I/O device from one switch to another if the switches have a different number of uplinks. The issue affects only Enhanced DirectPath I/O devices backed by NVIDIA's BlueField-3 and ConnectX-7.

Workaround: None

Drivers

In rare cases, an ESX host might fail with a blue screen due to a IOMMU fault or traffic connection timeout

In a setup of two ESX hosts connected by a Cisco N9K switch, the target node in an RDMA Write operation might trigger an IOMMU fault or a traffic connection timeout. As a result, the target host fails with a blue screen and an error such as `PTE not set to allow Write`. The issue occurs only under specific conditions:

1. RDMA write operations use DMA-based memory regions (DMA MR)
2. The network QoS of the switch are not properly configured

Workaround: None.

To prevent the issue, follow these best practices:

1. Use a supported N9K switch model with up-to-date firmware.
2. Properly configure QoS for RoCE on the N9K switch, following the Cisco configuration guides.
3. Avoid using DMA MR–based RDMA write operations. The Cisco nenic driver supports only NVMe over RoCEv2, which uses FRMR for RDMA write operations.

Networking Issues

Loss of network traffic for VMs connected with Virtual Functions (VF) from NVIDIA ConnectX-7 four ports adapter

Due to a hardware limitation of NVIDIA ConnectX-7 four port cards preventing support for hardware LAG, VF configured in LAG might experience traffic loss. In the `vmkernel.log`, you see error messages such as:

```
2026-03-10T02:21:57.741Z -ALERT vmkalert - [esx@4413] cpu0:1001391606) <NMLX_ERR> 0000:46:00.0:
nmlx5_CoreCreateLag:56 command failed, status bad parameter(0x3), syndrome 0xf460ff
2026-03-10T02:21:57.741Z -ALERT vmkalert - [esx@4413] cpu0:1001391606) <NMLX_ERR> nmlx5_core: 0000:46:00.0:
nmlx5_CoreCreateLag:59 - Create LAG command fails with error: Failure
2026-03-10T02:21:57.741Z -ALERT vmkalert - [esx@4413] cpu0:1001391606) <NMLX_ERR> nmlx5_core: 0000:46:00.0:
nmlx5_en_LagInit:237 - Unable to create lag: Failure
```

Only LAGs with matching number of ports are supported, for example for a four-port Host Channel Adapters (HCA), only a four-port LAG is supported.

Workaround: None.

Mounts on an NFS v4.1 server fail with a NFS4ERR_CLID_INUSE error

Each NFS v4.1 client instance is represented by a client ID and each NFS v4.1 server instance is identified by a server owner which is a combination of server major and server minor and uniquely identifies a server in a cluster. When NFS v4.1 client mounts a share, it creates a session per server owner and associates the TCP connection with the session. Each session is associated with a client ID provided by the NFS v4.1 server. The server keeps the state of the authentication mechanism for the existing client and the session and rejects any new security mechanism for the existing client. A change in vmknic binding or nConnect, or mounting a new datastore from same NFS v4.1 server with a different security flavor might lead to the creation of additional connections with a different security flavor. As a result, such operations might fail with an `NFS4ERR_CLID_INUSE` error.

Workaround: Use the same security mechanism and vmknic binding with which a cluster was created for all connection and mounting requests. For more details, see KB 370714.

vCenter Known Issues:

vSphere Client and vCenter Issues

Lost password sync between vCenter and SDDC Manager

In a VCF environment, you can change the local user password `administrator@vsphere.local` either under **Administration > Users and Groups** in the vSphere Client or by using the vCenter API. However, when you change the `administrator@vsphere.local` password of a vCenter instance, the password sync with the SDDC Manager and VCF Operations might be lost. As a result, you see status `Disconnected` for the vCenter instance in the vCenter grid under **Security > Password Management** in the SDDC Manager interface.

Workaround: In the vCenter grid under **Security > Password Management** in the SDDC Manager interface, select the vCenter account and click **Remediate Password**.

vSphere Client shows an error that the vCenter instance is not connected to a license server

During an upgrade to vCenter 9.1, in the vSphere Client you might see a banner with the following error:

```
One or more vCenter instances are not connected to a license server. To avoid service interruption, verify that the vCenter instance is connected to a license server.
```

The banner triggers when the connected VCF Operations is not yet upgraded to 9.1 and the license server is not yet deployed. This behavior is expected.

Workaround: To upgrade to version 9.1, strictly follow the upgrade order of components as documented in the 9.1 product documentation:

- Upgrading to VMware Cloud Foundation 9.1
- Upgrading to vSphere Foundation 9.1
- Upgrading vSphere 8 and Aria Operations 8 to 9.1

The vpxd service might fail with an error "Memory exceeds hard limit. Panic"

In rare cases, on very large virtual machines, the vpxd service might fail with an out-of-memory condition after around 3 days of uptime. As a result, some running operations in the vCenter instance might fail. The service recovers automatically and vCenter resumes normal operations.

Workaround: None

In very rare cases, you might see a false positive alarm "License assignment failed for this host"

Due to a difference in the license entitlement formats in VCF 9.0 and VCF 9.1 and later, after an upgrade to vCenter 9.1, in the vSphere Client you might see the alarm `License assignment failed for this host`. This is a false positive alarm, because a license is provided but not auto-acknowledged upon successful licensing. The alarm does not indicate a broken workload or function.

Workaround: Confirm that the host is licensed and acknowledge the alarm.

Some files, including the OVA image, remain staged on the source vCenter even when an CLI upgrade fails

The CLI installer does not support a user-initiated cancel operation during an upgrade and cancellation occurs only when the upgrade fails. When an upgrade fails, some staged files, including the OVA image, on the source vCenter are preserved by design, because:

1. When an upgrade fails, you usually resolve the issue and retry.
2. During the retry, the OVA file, which might weight 9 GB for example, is transferred to the source vCenter, which is time consuming.

Keeping the OVA file staged saves significant load time.

If you use a different ISO, the existing OVA is deleted.

Workaround: If you need to reclaim disk space after a failed upgrade that will not be retried, you can manually delete the staged files from the source vCenter from the location: `/storage/lifecycle/vlcm/`

Virtual machine templates might fail to sync when vCenter instances are linked by using vCenter grouping in VCF Operations

With VCF 9.1, you link vCenter instances in vCenter Groups under **Operate > Administration > Configurations > vCenter Linking** in VCF Operations, instead of using the vCenter Enhanced Linked Mode (ELM), which is deprecated. After you create a vCenter group, if you create a content library on one of the vCenter instances, add a VM template, and try to create a new subscription, the VM template sync might fail. In the vSphere Client, you might see either of the following errors:

- `A general system error occurred: Failed to publish library <source library> to subscribed library <target library> on vCenter Server XYZ. Reason: The operation failed due to Permission to perform this operation was denied.`
- `Permission to perform this operation was denied: You do not hold privileges... VM template sync works if the vCenter instances are linked in ELM.`

Workaround: For all linked vCenter instances, run the following commands:

1. To retrieve the machine id: `/usr/lib/vmware-vmafd/bin/vmafd-cli get-machine-id --server-name localhost`
   Output example: eac8395e-f676-4358-a8aa-79e3668ddfa7
2. To add content library user: `/usr/lib/vmware-vmafd/bin/dir-cli group modify --name vSphereClientSolutionUsers --add content-library-user-<machine-id> --login <vCenter Server SSO administrator login id>`
   For example: `/usr/lib/vmware-vmafd/bin/dir-cli group modify --name vSphereClientSolutionUsers --add content-library-user-eac8395e-f676-4358-a8aa-79e3668ddfa7 --login administrator@vsphere.local`
   Enter password for administrator@vsphere.local:
   Output example: Account [content-library-user-eac8395e-f676-4358-a8aa-79e3668ddfa7] added to group [vSphereClientSolutionUsers]Group member [content-library-user-eac8395e-f676-4358-a8aa-79e3668ddfa7] added successfully

You do not see linked vCenter instances in the vSphere Client after removing them from a vCenter group in VCF Operations

When you remove vCenter instances from an existing vCenter group in VCF Operations, you might not see such instances in the vSphere Client after you add them to a new group.

Workaround: Log in to SSH as root and run the command `service-control --restart vsphere-ui`.

You cannot select options to preserve MAC-addresses and include extra configuration when cloning a VM template

In the vSphere Client, when you right-click a virtual machine template and select **Clone to Library**, you do not see an option to select the following parameters:

- Preserve MAC-addresses on network adapters
- Include extra configuration

Workaround: You can set either option by using API or the vSphere Client:

1. API: Use backend API https://developer.broadcom.com/xapis/vsphere-automation-api/latest/api/vcenter/ovf/library-item/post/ with the export flags in the CreateSpec https://developer.broadcom.com/xapis/vsphere-automation-api/latest/data-structures/Vcenter%20Ovf%20LibraryItem%20CreateSpec/
   For example:

```
curl --location 'https://<vCenter IP>/api/vcenter/ovf/library-item' \
--header 'Content-Type: application/json' \
--header 'Cookie: vmware-api-session-id=xxxxx' \
--data '{
    "source": {
        "type": "VirtualMachine",
```

```
            "id": "vm-xxxxx"
        },
        "target": {
            "library_id": "xxxxx"
        },
        "create_spec": {
            "name":"<your_spec>",
            "flags" : ["EXTRA_CONFIG", "PRESERVE_MAC"]
        }
    }
```

Get the export flags with this command:

```
curl --location 'https://<vCenter IP>/api/vcenter/ovf/export-flag' \
--header 'Cookie: vmware-api-session-id=xxxxx' \
--data ''

[
    {
        "description": {
            "args": [],
            "default_message": "Preserve MAC-addresses on network adapters.",
            "id": "com.vmware.ovfs.ovfs-main.ovfs.export_flag_preserve_mac"
        },
        "option": "PRESERVE_MAC"
    },
    {
        "description": {
            "args": [],
            "default_message": "Include extra configuration.",
            "id": "com.vmware.ovfs.ovfs-main.ovfs.export_flag_extraconfig"
        },
        "option": "EXTRA_CONFIG"
    }
]
```

2. vSphere Client:
   a. Right click on a VM template and select **Convert to Virtual Machine**. You see a new VM created.
   b. Right-click the new VM and click **Clone > Clone as Template to Library**.
   c. In the **Clone as Template to Library** modal, select OVF as **Template type**.

Opening vCenter tasks in a new tab in the vSphere Client takes long

When the vSphere Client runs on a low-resource virtual machine, such as a Windows jumpbox, opening a vCenter task in a new tab might take long, sometimes more than three minutes. This issue is more likely to occur during periods of high activity, such as vCenter processing more than 5,000 parallel operations per hour. In such cases, the **vCenter Task Console** also responds with a significant delay.

Workaround: Run the vSphere Client on a machine with higher resource availability to ensure responsive performance.

In the vSphere Client, you see tasks with name OvfManager.deployVm.label under Recent Tasks

In the vSphere Client, when deploying a virtual machine by using vCenter OVFS API, in **Recent Tasks** you see tasks with name `OvfManager.deployVm.label` and the **Initiator** column shows an incorrect user name. The task name should read **Deploy OVF template** and the initiator should show the actual user name logged into the vCenter Client.

Workaround: None

After breaking Enhanced Link Mode (ELM), linking to some vCenter instances in VCF Operations fails

In a 9.x environment, after breaking ELM and setting up VCF Operations, linking to some vCenter instances might fail with the message `An error has occurred. Please retry the linking process after some time.` The issue occurs because breaking ELM removes the service accounts associated with an already used token which sometimes

makes such tokens stale and no longer valid, causing vCenter API calls to fail. To confirm the issue, SSH into the affected vCenter instance and check the following log file: `/var/log/vmware/vapi/endpoint/endpoint.log`. Look for the error: `Request is invalid: ns0:InvalidRequest: 'ActAs' token is invalid!`

Workaround: To restore connectivity to vCenter API calls:

1. SSH into the affected vCenter instance.
2. Use the command `service-control --restart <service name>` to restart the following services:
   – vmware-vapi-endpoint
   – vmware-vpxd
3. In VCF Operations, remove the affected vCenter instance from vCenter linking.
4. Re-add the vCenter instance. Confirm that vCenter linking status shows as **Active**.

Pods on VKS 3.6.0 might run out of memory during scaling

During scaling of a VCF 9.1 environment, some pods on VKS 3.6.0 might run out of memory.

Workaround: Upgrade to VKS 3.6.1.

The generation of the vCenter support bundle intermittently fails with the error ActionException("Error in creating tar file: %s" % self.getFilePath()).

Due to a rare race condition between read and write tasks, tar creation during the generation of the vCenter support bundle might fail with an error such as `unexpected end of data`. In the backtrace, you see logs similar to:

```
INFO:vmware.appliance.supportbundle.supportbundle_helper:Task : Support Bundle task failed.
ERROR:vmware.appliance.supportbundle.supportbundle_helper:Failed : 874 CRITICAL vmtar.py:341
[tarVmtar] /storage/log/vmware/vpxd-svcs/authz-ldapdump.ldif
^[[31mException^[[0m "unexpected end of data"
ERROR vc-support:34 /usr/bin/vc-support encountered an exception: Error in creating tar file: /storage/log/vc-
support.tgz
Traceback (most recent call last):
  File "/usr/bin/vc-support", line 29, in <module>
    sys.exit(main(sys.argv[1:]))
             ^^^^^^^^^^^^^^^^^^
  File "/usr/lib/vmware/site-packages/supportbundle/cli/vcsupport.py", line 60, in main
    run(options)
  File "/usr/lib/vmware/site-packages/supportbundle/main.py", line 644, in run
    tarObj.close()
  File "/usr/lib/vmware/site-packages/supportbundle/vmtar.py", line 670, in close
    raise ActionException("Error in creating tar file: %s" % self.getFilePath())
supportbundle.action.ActionException: Error in creating tar file: /storage/log/vc-
vcenter-1.vrack.vsphere.local-2025-03-11--15.37-466918.tgz
```

Workaround: None. The vCenter support bundle generation succeeds on retry.

You cannot log in to the vSphere Client with Google Chrome after generating a VMCA certificate with key size larger than 15 KB

Due to a limit on the maximum size of a TLS/SSL certificate chain that Google Chrome and other Chromium-based browsers can process, you might not be able to log in to the vSphere Client after generating a VMCA certificate with a key size larger than 15 KB.

Workaround: None

Upgrade Issues

A reset of the vSphere Lifecycle Manager database might cause data loss in the Supervisor

If the vSphere Lifecycle Manager database in your environment is reset before upgrading vCenter from versions 8.0 Update 3 and later or 9.0.x to 9.1.0 or 9.1.1, the upgrade might cause data loss in the Supervisor. To avoid data loss, before a vCenter upgrade, you must first check your environment and take mitigation steps, if necessary.

Workaround: See Broadcom knowledge base article 455737 for instructions how to check if your environment is affected and for mitigation steps.

vCenter upgrade to 9.1 might fail with a pre-check error for NetFlow enabled on distributed portgroups

When upgrading vCenter Server to version 9.1, the upgrade pre-check might fail with an error in the vSphere Client such as:

```
Some uplink distributed portgroup(s) on the source vCenter Server have NetFlow enabled.
Make sure NetFlow is disabled and NetFlow Override port policies is disabled in the
following uplink distributed portgroup(s) list.
```

Using Internet Protocol Flow Information Export (IPFIX) on a vSphere Distributed Switch (VDS) uplink port group is deprecated in VCF 9.1.

This error typically occurs in environments managed by VCF Operations for networks, formerly vRealize Network Insight (vRNI), which automatically re-enables NetFlow on VDS.

Workaround: See Broadcom knowledge base article 441813.

In VCF Operations, you see completed status under Configuration Upgrades for all ESX hosts even though some upgrades are still in progress

If a vCenter instance has both standalone ESX hosts and clusters, in VCF Operations under **Build > Lifecycle > <workload> > Configuration Upgrades**, you might see a confirmation that the upgrade has completed. At the same time, under **Tasks**, you might see that some upgrades have completed, for standalone ESX hosts for example, while cluster upgrades are still running. The issue occurs because after the upgrade of standalone hosts completes, the bundles API might consider the task complete on bundle level and not track tasks on the individual resource level.

Workaround: Monitor the running tasks to ensure that all upgrades complete.

After an in-place upgrade to vCenter 9.1, you see two disks backing /storage/dblog and /storage/lifecycle

A change in the Write-Ahead Log (WAL) usage in PostgreSQL can cause the `/storage/dblog` partition to reach 100% capacity during certain scenarios such as long-running uptime, which might affect vCenter availability or database operations. To avoid such issues, the `/storage/dblog` partition size is doubled across all deployment sizes in vCenter 9.1. For example, from 25 GB to 50 GB on large deployments. When you perform an in-place upgrade from vCenter 9.0 to 9.1 and later, the former `/storage/vtsdblog` storage is repurposed and its capacity is added to `/storage/dblog`, so the dblog partition is effectively doubled. As a result of this repurposing, you see two disks backing `/storage/dblog` and two disks backing `/storage/lifecycle` after the update. This is expected and does not require any action.

Workaround: None. When you update from vCenter 9.0 to any 9.1 release, the upgrade automatically repurposes `/storage/vtsdblog` and adds it to `/storage/dblog`. No additional action is required.

If you use the vCenter GUI installer, update to vCenter 9.1 from an earlier 9.x version fails

If you try to upgrade a vCenter instance from version 9.x to 9.1 by using the vCenter GUI installer, you see the following error message: `Source version is 9.0.0 and the installer version is 9.0. Supported version for upgrade is 8.0.`.

Workaround: Use the vCenter GUI installer only for upgrades of vCenter from 8.x to 9.0 and later. Use the Virtual Appliance Management Interface (VAMI) for updates between versions of VCF 9.0, for example vCenter 9.0 to vCenter 9.0.x or vCenter 9.1.

Miscellaneous Issues

OpenLDAP login to vCenter fails after upgrade to VCF 9.1 due to a missing attribute

vCenter requires the `serviceAccount` attribute for OpenLDAP providers and if such is missing, OpenLDAP login fail after an upgrade to VCF 9.1.

Workaround: Remove and readd the identity source on the vCenter instance.

If ESX hosts of a 9.1 vCenter run versions earlier than 8.0 Update 2, some hardware compatibility checks fail

When running hardware compatibility checks on a vCenter of version 9.1 with ESX hosts on versions earlier than 8.0 Update 2, in the vSphere Client, you might see the following errors:

1. vSphere Lifecycle Manager Hardware Compatibility check on cluster level: `There was a problem connecting to the hosts in the cluster.`

2. Discover and Plan (D&P) Hardware Compatibility check on host level: `There is a problem connecting to the host 'host-XX'. Make sure that the vCenter Server Appliance has network connectivity to the ESXi host.`
3. Cluster Remediation: If the option **Prevent remediation if hardware compatibility issues are found** is active, remediation fails to proceed on vSAN clusters due to the failed vSphere Lifecycle Manager Hardware Compatibility check.

Workaround: Manually verify hardware compatibility according to the Broadcom Compatibility Guide and considering if your cluster is a vSAN cluster. After the verification, you can uncheck **Prevent remediation if hardware compatibility issues are found** and proceed with the remediation.

During RDU upgrade, you see an error "Unable to connect to the given vCenter or ESXi [] on its SDK endpoint"

In the **Source Location** step of the **Target VM deployment** wizard in the vSphere Client during RDU upgrade, you see an error such as `Unable to connect to the given vCenter or ESXi [] on its SDK endpoint`. This error usually occurs because of incorrect username, password, or user certificate prompts.

Workaround: Check the username and the password, and retry.

Revert snapshot operation fails with the error 'The operation is not allowed in the current state.'

If a virtual machine has a chain of snapshots, which contains snapshots of both the VM and Improved Virtual Disks (IVD), also known as First Class Disks (FCD), reverting to a VM snapshot is not supported. If you try such an operation, in the logs you see a message such as:

```
The virtual machine cannot be reverted when crossing an Improved-Virtual-Disk snapshot.
```

or an error such as:

```
The operation is not allowed in the current state.
```

Workaround: None. The operation is not supported.

Auto Deploy Issues

Booting stateful ESX hosts on a vSphere Configuration Profile (VCP) cluster fails with error "Error copying / downloading file"

When you use Auto Deploy to provision ESX hosts in a VCP cluster at scale, if you do not provide a ready configuration, booting hosts fails with the message `Error copying / downloading file`.

Workaround: Before you start using Auto Deploy with VCP, you must have a ready configuration, either in a `.json` file or imported from a reference host. The best practice is to:

- Create a VCP cluster.
- Manually configure the desired settings on an existing ESX host that you select as a reference host.
- Import the reference host configuration to create a draft, make changes, precheck, and apply it.

Successful provisioning of hosts in VCP clusters requires a valid, non-empty desired configuration document. If the cluster configuration lacks networking details, Auto Deploy rules might fail, because hosts cannot come online. Always validate the configuration before you create Auto Deploy rules and attempt to provision hosts.

API Issues

Deploying an OVF by using vAPI on ESX hosts of version earlier than 9.0 fails

The vAPI for deploying an OVF, https://developer.broadcom.com/xapis/vsphere-automation-api/latest/api/vcenter/ovfs__action=deploy__vmw-task=true/post/, is only supported for ESX 9.0 and later releases. If an ESX host of version earlier than 9.0 is a target of OVF deployment by this API, the deployment fails with an `vmodl.fault.InvalidRequest` error.

Workaround: Use an ESX host of version 9.0 and later for OVF deployment by vAPI.

vSAN

This document contains the following sections

- vSAN Known Issues

vSAN Known Issues

Data component utilization is greater than 95% on vSAN ESA disk partitions, preventing creation of new pod VMs

vSAN ESA limits the maximum number of components per disk to 3000 (for hosts with more than 64GB memory and disk sizes greater than 1TB).

With only two disks per-host, the component limit is approximately 6000 components, which is reached before disk capacity is used up.

Workaround:

For full component capacity, use hosts with at least 9 disks per-host (IMK 9 disks are supported per-host)

Deduplication store UUID not displayed in Virtual Objects view

When you enable global deduplication on a vSAN ESA cluster, the Deduplication store appears in the Virtual Objects view but does not display its UUID or placement details. The UUID exists in the system and can be verified through command-line tools, but it is not visible in the vSphere Client UI.

Workaround:

To view the Deduplication store UUID, use the ESXi command line:

esxcli vsan dedup dedupstore get

This command displays the backend UUID and other Deduplication store details that are not shown in the vSphere Client interface.

vSAN ESA with VMware VSS (Volume Shadow Copy Service) quiesced snapshots are inconsistent

If you are using vSAN ESA with VMware VSS (Volume Shadow Copy Service) to quiesce your snapshots, from either VMware's own or 3rd-party data protection tools that use VADP, the virtual disks on the running VM might become inconsistent.

Specifically, guest files that are deleted only from the snapshot during VSS quiescing may get zeroed out in the running VM. Observed at-risk guest files include edb.log transaction logs and DataStore.edb, both from the Windows Update service.

If those files are affected and the Windows Update service restarts for any reason, the problem may manifest as the following record in the Window Event log:

wuaueng.dll (288) SUS20ClientDataStore: Unable to read the header of logfile C:\Windows\SoftwareDistribution \DataStore\Logs\edb.log. Error -501.

Manually restarting the Windows Update service by running this command "net start wuauserv" should regenerate the inconsistent files and fix the problem.

Workaround

To prevent this inconsistency from happening for Windows Update and other VSS-quiesced services, disable trim/unmap support for individual VSS-protected VMs. Trim/unmap for the VM can be re-enabled when a future patch is released that fixes this issue. If you see this issue before being able to disable trim/unmap, you can restore the affected VM from a recent snapshot (including the VSSs napshot that triggered that problem).

Stretching a vSAN cluster using the SDDC Manager API fails with the error "Failed to validate IP address pool"

When you attempt to stretch a vSAN cluster using a JSON specification that includes DHCP IP assignment for host TEPs and provides a network spec in the input spec, then the stretch cluster workflow fails at during the "Validate IP Address Availability for Edge Overlay (TEP) IP Assignment" action.

Workaround: See KB 399582.

NFS server leaks memory when clients mount shares using UDP protocol

Using UDP to mount NFS shares causes memory leaks, resulting in FSVM reboot.

Workaround: NFS clients must use TCP protocol to mount NFS shares.

Auto-downloading the OVF file is disabled during vSAN File Service enablement or upgrade

With the VCF product unified releases, the auto-downloading of the OVF file in vSAN File Service enablement or upgrade is disabled in the user interface of vCenter instances.

Manually download and install the vSAN File Service OVF file on the vCenter. See Broadcom knowledge base article 390237.

Performance impact when listing directories with many files

Listing files in a directory with many files takes more time.

Workaround: None

You cannot use the option "Install on a new vSAN cluster containing the target host" when deploying a vCenter instance

Due to a known technical limitation, you cannot use the option **Install on a new vSAN cluster containing the target host** when deploying a vCenter instance by using the GUI installer. If you use this option, the deployment fails with the error `VMware vSAN Health service failed firstboot` on the step **Install - Stage 2: vCenter Server setup is in progress**.

Workaround: Do not use the option **Install on a new vSAN cluster containing the target host** when deploying vCenter. You can activate vSAN from the vSphere Client after the vCenter deployment completes.

Mounting remote datastores from vSAN stretched clusters with unsupported vSAN versions is allowed

Missing guardrails allow mounting remote datastores from vSAN stretched clusters running unsupported vSAN versions, leading to undesired behavior.

Workaround: None.

Host might get PSOD error after adding a new host into a compute client cluster

vSAN VCenter Management Service gets restarted when a compute client cluster has mounted a vSAN ESA or vSAN storage cluster from a remote vCenter. The newly added host might get PSOD error when there is an I/O activity triggered on the host.

Workaround: Perform one of the following:

- Before adding a new host, mount a new vSAN ESA or vSAN storage cluster to the client cluster.
- Move the host into maintenance mode and then add the new host. Use the script "fixhostmount.py" to remediate the host.

NSX

This document contains the following sections

- Document Revision History
- NSX Known Issues

Document Revision History

Revision Date	Edition	Changes
May 12, 2026	1	Initial edition.
September 1, 2026	2	Added known issue 3737540.
October 8, 2026	3	Added known issue 3738267.

NSX Known Issues

On a transit gateway and tier-0 gateway, users can see the stale advertised prefix from a deleted VPC static route for AVI. The prefix used in deleted AVI VPC static route is reused for a different service like NAT, but the traffic doesn't work for the new service.

User traffic can be affected for a new service like NAT when a deleted VPC static route for AVIs public IP/prefix is reused in the new service.

Workaround: Call the following API on NSX Manager to remove the duplicate route:

```
POST /policy/api/v1/orgs/<orgId>/projects/<projectId>/vpcs/<vpcId>/force-resync
```

For more information, see Broadcom knowledge base article 445154.

When a load-based teaming policy is configured, a teaming failover is triggered when the load is increased. Datapath outage happens for VNICs and(or) VMKNICs that were migrated.

Outage of existing and new connections.

Workaround: Move to "Route based on originating virtual port" Teaming policy.

Workload VMs experience packet drops when co-located on the same ESX host as the edge node. The issue persists when all the following three conditions are met: i) the Edge Uplink Profile transport VLAN is unset or set to 0. ii) The Edge VTEP fastpath (fp-ethx) interface is connected to a non-trunk Distributed Virtual Port Group (DVPG). iii) Both the Edge VTEP and management/VLAN Host Switch interfaces are connected to VLAN-tagged DVPGs.

Customers using the specific configuration described above will experience datapath traffic interruptions due to packet drops for workload VMs residing on the same host as the edge node.

Workaround:

Refer the following KB article to address this issue:

https://knowledge.broadcom.com/external/article/445209/packet-drops-are-seen-when-edge-connecte.html

BFD Tunnel sessions are not coming up with Intel E810C NIC.

Customers using the Intel E810C NIC on their Bare Metal Edge nodes will be impacted. The tunnels fail to establish due to the incorrect VLAN handling that renders the overlay network non-functional for those segments. There is no graceful recovery from this issue.

Workaround:

Use the ice_comms-1.3.24.0.pkg package. Use the following steps to change the ice package:

1. cd /lib/firmware/intel/ice/ddp
2. Download ice_comms-1.3.24.0.pkg
3. sudo ln -sf ice-1.3.24.0.pkg ice.pkg
4. Check that link inside the container has also changed by running the following command:
   docker exec -it service_datapath ll /usr/lib/firmware/intel/ice/ddp

Changing the Span field value unexpectedly resets the External Connection field when specific Connectivity Types are selected.

When a user modifies the Span field, any previously entered or selected data in the External Connection field is automatically cleared. This behavior occurs specifically when the Connectivity Type is set to Centralized, Distributed, or VXLAN.

Workaround:

- From UI: Ensure that the Span field value is finalized before entering any information into the External Connection field.
- From API: Use Update TGW API to update Span value.PUT: /policy/api/v1/orgs/{org-id}/projects/{project-id}/transit-gateways/{transit-gateway-id}

Warning message is missing when tier-0 does not have "Transit Gateway Static advertisement" configured after an NSX 4.2 upgrade.

Users configuring a gateway connection and centralized Transit Gateway have no indication that the associated tier-0 is missing TGW_STATIC route redistribution, which leads to a silent routing misconfiguration after NSX 4.2 upgrades.

Workaround:

None.

IP Block statistics page shows CIDR allocated to a subnet and VM IPs connected to that subnet as two allocations.

Customers see VM IP addresses listed twice in the allocation details, once as part of the subnet CIDR allocation and again as individual VM IPs. This double-counting leads to inconsistency between the overall usage statistics and the detailed IP/CIDR listings.

Workaround:

No available workaround.

When a tier-1 gateway's edge cluster is changed from one edge cluster to another (cross-cluster reallocation), the VLAN conflict validation is ineffective. This allows segments with the same VLAN ID , Transport Zone, and the uplink teaming policy from different tier-1 gateways to land on the same edge node causing edge Datapath Configuration Failure.

Edge datapath configuration failure blocks all new configuration pushes to the affected edge node potentially impacting traffic for workloads routed through tier-1 gateways on that edge.

Workaround:

Before changing a tier-1 gateway's edge cluster, manually verify that no segments connected to the tier-1 (through service interfaces) have the same VLAN ID, Transport Zone, and the uplink teaming policy as segments already hosted on the target edge cluster's edge nodes. If a conflict exists, move the conflicting tier-1 to a different edge cluster that does not have overlapping VLAN segments on its edge nodes.

VCF Installer

This document contains the following sections

- VCF Installer Known Issues
- SDDC Manager Known Issues
- VCF Download Tool

VCF Installer Known Issues

When converging to VCF or vSphere Foundation, the operation fails during VCF management services deployment phase

When converging to VCF or vSphere Foundation, if the existing vCenter instance was upgraded from version 8.x to 9.0 or 9.1, then the VCF management services deployment task might fail to bootstrap VCF services runtime and return the following error message: `Failed to bootstrap VCF services runtime.` The VCF Installer and SDDC Manager logs show the following error message: `Bootstrap failed during stage INIT0001 - Validating configuration: INGRESS_PLATFORM_FQDN XXX could not be resolved via nameserver(s): 127.0.0.1.`

Workaround: Perform one of the following tasks.

- Before starting the convergence process, perform the following tasks.

1. SSH to the vCenter instance.
2. Change to `su`.
3. Open the `/etc/resolv.conf` file.
4. Check for more than one line that contains `nameserver 127.0.0.1` and remove the duplicate lines.
5. Open the `/etc/systemd/network/10-eth0.network` file.
6. If `DNS=127.0.0.1` or a similar `127.0.0.1` combination is present in the file, delete the `127.0.0.1` entry.
7. Restart the `systemd-networkd` service by running the `systemctl restart systemd-networkd` command.

- After a convergence to VCF has failed, perform the following tasks.

1. SSH to SDDC Manager component and switch to the root user.
2. Check for more than one line that contains `nameserver 127.0.0.1` and remove the duplicate lines.

3. Save the file and retry the failed VCF convergence.

- After a convergence to vSphere Foundation has failed, perform the following tasks.

1. SSH to the vCenter instance.
2. Check for more than one line that contains `nameserver 127.0.0.1` and remove the duplicate lines.
3. Save the file and retry the failed vSphere Foundation convergence.

When specific component FQDNs contain upper case characters, VCF deployment fails

If the following FQDNs contain upper case characters, VCF deployment fails:

- Fleet components FQDN
- Instance components FQDN
- Identity broker FQDN
- VCF services runtime FQDN
- VCF Automation FQDN
- VCF services runtime FQDN of the VCF Automation cluster

Workaround: Start the VCF deployment with lower case FQDNs for the listed components.

NFS Datastore Configuration validation fails for ESX hosts with a single physical network interface card (pNIC)

When deploying VCF 9.1 on ESX hosts with a single pNIC, the **NFS Datastore Configuration** validation step fails with the following error message: `Failed to validate NFS configuration. NFS datastore mount failed on host esx01.raipole.io: An error occurred during host configuration.`

This validation failure prevents the deployment from proceeding even when NFS connectivity is actually functioning correctly. The issue occurs because the validation check expects multiple physical NICs for redundancy.

Workaround: This is expected behavior and the configuration is unsupported. To proceed with the deployment, use 2 or more pNICs.

Fleet lifecycle service produces workflow inconsistencies due to transient database connectivity issues

- Symptom 1: After a VCF deployment workflow completes successfully, certain component deployment tasks or monitoring sub-tasks may remain displayed in an **In Progress** state in the VCF user interface, even though the deployment has finished and the components are fully operational. This is a display issue only and does not indicate any functional problems with the deployed infrastructure or services.
- Symptom 2: During a VCF deployment a component installation is triggered more than once. The subsequent execution of the installation step fails because the component is already installed.
- Symptom 3: One or more steps within a VCF lifecycle task display no progress updates for more than two hours, indicating the task is failed or stuck.

Workaround for symptoms 1 and 2: None. If the overall VCF deployment is reported as successful and the deployed component is accessible and operational, ignore the task statuses. Alternatively, to verify that the deployment completed successfully, perform the following tasks.

1. Verify the overall deployment status and if marked as successful, the deployment is complete.
2. Manually log into the deployed component's management interface.
3. Verify that all services are running and operational.

Workaround for symptom 3: To determine whether a task is stuck and which service to restart, see Broadcom knowledge base article 435569.

Converging a vCenter instance that is already connected to a SDDC Manager, destroys existing Fleet components

When converging existing infrastructure to a VCF Instance, if you select a vCenter instance that is already managed by SDDC Manager, the new deployment destroys the fleet components of the first VCF Instance. During VCF management services bootstrap, the second SDDC Manager deletes the shared vCenter folder used by the first VCF deployment, resulting in the destruction of the primary VCF management services cluster and workers. The second VCF deployment fails too.

Important:

A warning message is displayed during the deployment workflow indicating that an existing SDDC Manager extension is found on the vCenter instance. This warning does not prevent the deployment from proceeding.

Workaround: None. Redeploy the VCF Instance or restore it from backup.

During deferred components deployment, error messages appear in Depot settings and binary management

After deploying VCF, converting VCF Installer to SDDC Manager, and attempting to deploy deferred components (VCF Operations and VCF Automation), the **Depot settings and binary management** page displays error messages, such as: `This API is no longer supported from VCF 9.1" along with depot connection errors.`

Workaround: Disregard the error messages. The **Binary Management** section functions correctly and allows you to download required binaries and complete the deferred component deployment workflow.

Converging or importing an existing vCenter instance fails during validation with an error indicating that the NSX-T Manager install image cannot be found for the required NSX version

When converging or importing an existing vCenter instance that is not connected to NSX, SDDC Manager automatically deploys a new NSX Manager. The system selects the latest compatible NSX version based on your vCenter version and VCF release. If the install image (bundle) for the selected NSX version is not available in the SDDC Manager depot, the validation phase fails with an error message indicating which NSX version's install image is required.

Workaround: Download the NSX install image and retry the operation.

1. To identify the required NSX version, review the error message.
2. Download the required NSX-T Manager install image.
3. Retry the convergence or import operation.

Converging an existing vCenter instance with a non-compliant root password, fails

When converging an existing vCenter instance 8.0 Update 3 by using VCF Installer, the vCenter root user property is mandatory in VCF Installer and the password must be between 15 and 20 characters now, even when the root password is allowed to be between 8 and 20 characters in vCenter 8.0 Update 3.

Workaround: Change the vCenter root password. The password must be between 15 and 20 characters inclusive, have at least 1 lower case letter, 1 upper case letter, 1 digit, and 1 special character, be made only of ASCII characters, and have no white space.

SDDC Manager Known Issues

Initiating SDDC Manager upgrade pre-checks from the instance in Lifecycle tab in VCF Operations or from the Available Upgrades tab in SDDC Manager Lifecycle Management UI fails with a `Triggering SDDC Manager upgrade bundle failed`

When you initiate upgrade pre-checks for SDDC Manager in VCF Operations (**Build > Lifecycle > VCF Instances > instance > SDDC Manager Upgrades** tab) or SDDC Manager UI (**Lifecycle Management > SDDC Manager > Available Upgrades** tab), the operation fails with a `Triggering SDDC Manager upgrade bundle failed. A problem has occurred on the server. Please retry or contact the service provider and provide the reference token` error.

Workaround: Initiate the upgrade pre-checks either from the **Build > Lifecycle > VCF Instances > instance > domain > Upgrades** tab in the VCF Operations UI or the **Inventory > Workload Domains > domain > Upgrades** tab in the SDDC Manager UI.

When converting a Virtual Volume (vVol) primary datastore to vSAN HCI, the add host operation fails when validating L3 network data if the operation is performed before the client cluster is converted to vSAN HCI.

When converting a primary datastore from vVol to vSAN, the add host to the server cluster operation fails if it is performed before the client cluster is converted to vSAN. Both the client and the server clusters must use the same storage architecture.

Workaround: None.

Deleting a vSphere cluster in SDDC Manager fails with error: `Error occurred while generating input for remove workload for NSX Environment in NSX environment.`

If ESX hosts are NSX prepared out of band with some transport node profiles configured without an uplink profile, SDDC Manager cannot delete the vSphere cluster.

Workaround: Reconfigure all transport node profiles with an uplink profile and restart the delete workflow in SDDC Manager.

After SDDC Manager reboots during an upgrade to version 9.1, SDDC Manager core services fail to start automatically

After the reboot operation of SDDC Manager during upgrade to version 9.1, the core services fail to start, which results in prolonged service downtime and the user interface is also not accessible.

Workaround: Perform the following tasks.

1. Log in to the virtual machine of SDDC Manager by using SSH, obtain root permissions and run the following command:
   ```
   for s in domainmanager operationsmanager lcm commonsvcs sddc-manager-ui-app; do echo "--- $s ---"; systemctl status $s | grep -E "Active:|Loaded:"; done
   ```
2. In the command output, verify that the status for `domainmanager`, `operationsmanager`, `lcm`, and `commonsvcs` is inactive.
3. Reboot the appliance by running the `reboot` command.

When management domain upgrade process is incomplete, VCF Operations user interface displays incorrect upgrade status for the workload domain

When the management domain has pending upgrades, workload domains with fully completed upgrades to the target Bill of Materials (BOM), might display **AVAILABLE** instead of **UP TO DATE** upgrade status. Fleet lifecycle incorrectly calculates the upgrade availability, which results in displaying incorrect values in the user interface. The actual upgrade operations through the user interface and API endpoints function correctly and are not affected by the display issue.

Workaround: Perform one for the following tasks.

- Complete the management domain upgrade to remove all pending bundles. Once the management domain completes all pending upgrades, workload domains report upgrade status correctly.
- In the workload domain, verify that the NSX, vCenter, and ESX component versions match the target BOM versions. If these versions match the target BOM, treat the **AVAILABLE** upgrade status as a false-positive.

When attempting an upgrade of SDDC Manager in an isolated workload domain configuration, the process might fail

During SDDC Manager upgrade in a VCF 9.1 environment where vCenter instances of management and workload domains are not linked and have dedicated Single Sign-On, when attempting to establish an SSH connection to a management vCenter instance, the upgrade process might fail with the following error message: `Failed to SSH into VCenter using root credentials` even when credentials are correct and SSH access is properly configured.

Workaround: Perform the following tasks.

1. Log in to the SDDC Manager appliance.
2. Edit the `/opt/vmware/vcf/lcm/lcm-app/conf/application-prod.properties` file and add or modify the following parameter: `lcm.vcenter.ssh.precheck=false`
3. Restart all SDDC Manager services by using the following command: `sh /opt/vmware/vcf/operationsmanager/scripts/cli/sddcmanager_restart_services.sh`
4. Retry the SDDC Manager upgrade.

SDDC Manager deployment with single uplink DVS configuration and NFS datastore fails

Using a single physical network adapter (pNIC) configuration for the distributed virtual switch (DVS) in combination with an NFS datastore for SDDC Manager deployment is not supported and the operations fails.

Workaround: None.

When performing pre-checks or an upgrade of selected ESX hosts, Hardware Compatibility List (HCL) checks are performed on all hosts in the cluster

When performing pre-checks or upgrading selected ESX hosts in straddle state deployments, where SDDC Manager is at version 9.1 and vCenter and ESXi are at version 9.0 or earlier, the HCL checks run on all hosts in the cluster, instead of only on the selected hosts. Only the selected hosts are upgraded.

Workaround: None.

SDDC Manager does not reflect completed NSX dataplane upgrade status

After a successful NSX upgrade, SDDC Manager's inventory and lifecycle management cache might not reflect the updated NSX-T dataplane version due to timeout or synchronization issues.

Workaround: The automatic version synchronization process resolves the discrepancy within 24 hours.

Alternatively, perform the following tasks to manually trigger version synchronization and update SDDC Manager inventory immediately.

1. Confirm the NSX upgrade completed successfully on NSX Manager.
2. In the `/etc/vmware/vcf/operationsmanager/application-prod.properties` configuration file, set the `check.lcm.isVersionSyncRequired` flag to `false`.
3. In SDDC Manager API, trigger version synchronization by executing a POST request to `/v1/resources/version-syncs` with `resourceType` set to `SYSTEM`.
4. Wait approximately 5 minutes for the lifecycle management inventory refresh cycle to complete.
   Optionally, trigger a manual lifecycle management inventory cache refresh using `POST /lcm/inventory/refresh`.
5. Verify the bundle status reflects the correct NSX-T dataplane version by querying `GET /v1/bundles/domains/{domain-id}` and checking the `nsx_t_dataplane` entity status.

On environments with enabled Persistent Memory (PMem), SoS health check shows Cluster vSAN Status and Cluster Disk Status as RED.

In environments with Persistent Memory (PMem) enabled, the SoS health check can incorrectly report a `RED` status for `Cluster vSAN Status` and `Cluster Disk Status`. This is a reporting issue specific to Persistent Memory (PMem) enabled storage and can result in false health states during SoS storage health checks. Note that Persistent Memory and all the associated features are deprecated and are not supported starting with VCF 9.0.

Workaround: None.

In the VCF Operations UI, log bundle generate, download, and delete operations are not available for VCF Operations and VCF Operations for networks

In the VCF Operations user interface, the options to generate, download, or delete logs are not available for VCF Operations and VCF Operations for networks.

Workaround: Perform the following tasks.

- To generate a support bundle for VCF Operations, see Create a VCF Operations Support Bundle.
- To generate a support bundle for VCF Operations for networks, see Create a VCF Operations for networks Support Bundle.

VCF Download Tool

VCF Download Tool displays incorrect .net URL after executing the generate --software-depot-id command

The output of the `generate --software-depot-id` command contains a typographical error in the hardcoded string, pointing to an incorrect domain instead of the public Broadcom domain. As a result, you cannot reach the direct access page displayed by **Use this link to register**, such as:

```
$./bin/vcf-download-tool configuration get --software-depot-id
*********Welcome to VCF Download Tool***********
Version: 9.1.0.0.25172051 Use this link to register https://vcf.broadcom.net/vcf/clm/download-manager/
register?serviceId=######-####-####-####-######.
Alternatively login at https://vcf.broadcom.com, select Software depot Registration and use this Software
 depot ID: ######-####-####-####-######
```

Workaround: See Broadcom knowledge base article 441033.

When Internet access is routed through a proxy server, the `vcf-download-tool esx metadata` and `vcf-download-tool esx download` commands fail to authenticate

When network access to the Internet requires a proxy server, the `esx metadata` and `esx download` commands fail and return an authentication error. The VCF Download Tool does not apply the configured proxy settings to the OAuth token request it sends to the Broadcom authentication endpoint. As a result, the tool attempts to reach the authentication server directly, bypassing the proxy, and the request fails in environments where direct Internet access is not available.

Workaround: Download ESX binaries manually from the Broadcom Support Portal, then import them to software depot or VCF Installer by using the `vcf-download-tool esx import` command. For more information, see Broadcom knowledge base article 442226.

VCF Operations

This document contains the following sections

- Deployment and Upgrade
- Licensing
- Build
  - Lifecycle
- Operate
  - vCenter adapter
  - Log Management
  - Workbench
  - Real-time metrics
  - Application monitoring
  - Audit Records
  - VCF Operations for networks
  - Developer Center
  - Workload Mobility
- Manage
  - Fleet Management
  - VCF Operations orchestrator

Deployment and Upgrade

During upgrade from 9.0 to 9.1, after deployment of VCF management services, the remaining management components do not appear in the VCF Operations inventory

During VCF upgrade from 9.0 to 9.1, after successful upgrade of VCF Operations and SDDC Manager and deployment of VCF management services, the remaining existing management components are not migrated to the fleet lifecycle component and do not appear in the VCF Operations inventory. No error messages or banners indicate that the import failed. This issue occurs if a proxy server with SSL termination is configured in VCF Operations. The proxy server prevents VCF Operations from communicating with the fleet lifecycle component.

Workaround: Follow the guidance for option 2 from Broadcom knowledge base article 441858.

Upgrading VCF Identity Broker in appliance mode from 9.0.x to 9.1 fails during validation

After upgrade of VCF Operations and SDDC Manager to 9.1, upgrading VCF Identity Broker 9.0.x in appliance mode to identity broker 9.1 fails during the validation phase. With VCF 9.1, VCF Identity Broker transitions to being hosted by VCF management services. As a result, to successfully upgrade to identity broker 9.1, VCF Identity Broker 9.0.x and VCF management services must be deployed on the same network and on the same datastore. This issue occurs because one of the following conditions is met:

- VCF Identity Broker in appliance mode is deployed on an NSX overlay segment. You cannot deploy VCF management services on an NSX overlay segment.

- VCF Identity Broker in appliance mode is deployed on a different network than VCF management services.
- VCF Identity Broker in appliance mode is deployed on a different datastore than VCF management services.

Workaround: See Broadcom Knowledge Base Article 444734.

Upgrade from VCF 9.0.x to VCF 9.1 fails during the `Deploy VCF Management Components` task

During upgrade from VCF 9.0.x to 9.1, the task `Deploy VCF Management Components` fails at the `Import VCF Operations in Fleet Lifecycle` step. The task fails due to invalid certificates, stale data in VCF Operations 9.1 (for example, incorrect credentials), or connectivity issues for components previously managed by the VCF Operations fleet lifecycle appliance.

Workaround: See Broadcom Knowledge Base Article 441858.

Upgrade from VCF Operations 9.0.1 or 9.0.2 to VCF Operations 9.1 fails at step 9 of 14: `Applied Operating System Update`

The upgrade to VCF Operations 9.1 might fail at step 9 of 14 with the following error message: `Failed resource key=pak_manager.action_failed, resource args=[run master postgres db upgrade].`

Workaround: See Broadcom knowledge base article 440200.

The Binary Management tab in VCF Operations lists the 9.1 VCF version option, but no 9.1 binaries appear as available for download

This is expected behavior at this point, because the upgrade to version 9.1 starts with upgrading your VCF Operations to version 9.1 by using a PAK file.

Workaround: To upgrade VCF to version 9.1, strictly follow the upgrade order of components as documented in the 9.1 product documentation: Upgrading to VMware Cloud Foundation 9.1.

After a VCF Operations upgrade from 9.0 to 9.1, VCF Automation, VCF Identity Broker, VCF Operations for networks, or VCF Operations for logs might not appear in the VCF Operations UI

If VCF Automation, VCF Identity Broker, VCF Operations for networks, or VCF Operations for logs are deleted and then imported in VCF Operations 9.0 prior to upgrading to VCF 9.1, these components do not appear in the inventory of VCF Operations 9.1.

Workaround: See Broadcom Knowledge Base Article 441858.

When incorrect input is provided, vSAN Stretched Cluster expansion fails

vSAN Stretched Cluster expansion fails at step **Add ESX Host(s) to vSphere Distributed Switch** with the following error message: `No available vmnic found on the host.`

Workaround: Perform the tasks in kB 427183.

The Broadcom Support Portal link for cloud proxy download in the VCF Operations UI redirects to an incorrect version (8.18) instead of the intended VCF 9.1

In the VCF Operations UI, the Broadcom Support Portal link used for downloading the cloud proxy OVA incorrectly redirects users to version 8.18 instead of the expected 9.1 release. This could lead to deployment of an unsupported cloud proxy version and potential compatibility issues.

Workaround: Manually navigate to the Broadcom Support Portal and download the correct cloud proxy OVA version (9.1) by selecting it explicitly from the available versions list.

Licensing

After you upgrade a vCenter instance to version 9.1.0.0300, the vCenter instance does not appear on the Licensing page in VCF Operations

After you upgrade a vCenter instance from version 9.0.x to version 9.1.0.0300, the vCenter instance does not appear in the VCF Operations UI under **Manage** > **Licensing**, so you cannot assign a license to the vCenter instance. In the vSphere Client, no licenses are displayed on the **Administration** page. There is no banner to indicate that there are unlicensed assets.

A stale or orphaned vSphere+ subscription license in the vCenter LDAP database prevents the vCenter instance from appearing in the VCF Operations UI.

Identify the stale vSphere+ license and manually delete the license from the vCenter LDAP database. For more details, see Broadcom knowledge base article 455886.

The license server does not work properly and after the appliance boots, in the console you see a black screen

The license server uses the `172.16.0.0/12` and `172.17.0.0/16` IP address ranges for internal communications. If you deploy the license server on the `172.16.0.0/12` network or configure the license server to use a gateway that advertises a routable path of `172.17.0.0/16`, a network conflict occurs. As a result, you see only a black screen in the license server console after booting.

Workaround: See Broadcom knowledge base article 441526.

This issue is resolved starting with version 9.1.0.0200.

Build

Lifecycle

Pre-check functionality is not supported for upgrades of Log Management 9.x to 9.1

In the VCF Operations UI, the option to trigger a pre-check on the log management component might appear available for the 9.0 to 9.1 upgrade path. Fleet lifecycle does not support pre-check for log management when upgrading from version 9.0 to 9.1.

Workaround: If pre-check is initiated, the task will result in a failure. You can safely ignore the pre-check task failure and proceed with the upgrade.

Operate

vCenter adapter

vCenter data collection fails following an upgrade to VCF Operations 9.1

If a vCenter integration was originally configured using an IP address or FQDN that included trailing slashes or sub-paths (for example, `vcenter.example.com/, vcenter.example.com/ui`), the collection mechanism in VCF 9.1 fails to initialize. The new version requires a clean IP or FQDN without any trailing slashes or URL paths.

Workaround: Prior to upgrading to VCF 9.1, review all existing vCenter integration settings. Verify that the **vCenter** field contains only the IP address or FQDN, and remove all trailing slashes or trailing URL paths.

Log Management

vCenter and ESX events or tasks show "Update parameter values" errors approximately every two minutes when there is an HCX Migration Agent (MA) host in the vCenter

vCenter and ESX events/tasks display false positive errors such as "Update option values" and "A general system error occurred" when there is an HCX Migration Agent (MA) host in the vCenter. This occurs because the log management component attempts to configure ESX hosts, specifically enabling audit logs by default. But ESX HCX Migration Agent (MA) hosts do not support this option. This does not affect the actual log collection process.

Workaround: To stop the frequent error messages, you can disable audit log collection for the corresponding vCenter, though this will affect all ESX hosts managed by that vCenter.

1. Navigate to the Log Collection configuration page in the VCF Operations UI.
2. Edit the corresponding vCenter.
3. In the ESX section at the bottom of the page, uncheck the **Audit** checkbox and save the configuration.
4. The new configuration may take up to five minutes to apply, after which attempts to configure audit logs will be suspended.

Log Collection Delay after Updating Adapter Hostnames from IP to FQDNSymptom

After updating the hostname configuration from an IP address to a Fully Qualified Domain Name (FQDN) for NSX, vCenter, Supervisor, or HCX adapter instances, it can take up to one hour for log collection to resume. Hostname

configuration changes in adapter instance settings are synchronized to the Log Management component every hour. Consequently, when these hostnames are updated from an IP to an FQDN, log collection may not start working until the next scheduled synchronization occurs.

Workaround: To immediately trigger log collection after a hostname update, manually disable and then re-enable log collection from the adapter instance configuration page.

VM Log Tagging Discrepancy after vCenter Re-integration

VM logs retain an outdated {{vmw_vr_ops_id }}tag after a vCenter is deleted and subsequently added back to VCF Operations. These logs fail to be correctly indexed or viewed via the Inventory page under the new vCenter object. When a vCenter is removed and then added back to the same VCF Operations instance, the mapping mechanism on associated VM logs continues to use the previous vmw_vr_ops_id. VCF Operations does not automatically update these logs with the new identifier while an active agent continues to stream logs during the transition.

Workaround: Manually restart the Log Processor nodes to clear cached metadata and force a refresh of the ID mappings. Use the following command:

```
kubectl rollout restart sts/log-processor -n ops-logs
```

SSO login to the VCF Operations for logs 9.0 UI fails after upgrading VCF Identity Broker to version 9.1

When VCF Identity Broker is upgraded to version 9.1, you cannot perform an SSO login to the VCF Operations for logs 9.0 user interface. This issue occurs because identity broker 9.1 transitions to a VCF services runtime instance that hosts VCF management services, which uses the Server Name Indication (SNI) TLS extension to identify the correct service certificate. When running in FIPS mode, the TLS stack utilized by VCF Operations for logs 9.0.x fails to send the required SNI extension. Consequently, the gateway returns a default, untrusted certificate to the appliance, causing the SSO authentication to fail. This issue specifically affects FIPS-enabled deployments, while non-FIPS deployments remain unaffected.

Workaround: You can bypass by logging into the VCF Operations for logs 9.0 UI using a local, non-SSO account. Full SSO functionality is completely restored after VCF Operations for logs is upgraded to version 9.1, as authentication is then handled through VCF Operations and the updated UI.

VCF Operations for Logs Agent version 9.0.x fails to auto-upgrade to newer versions

VCF Operations for Logs Agent version 9.0.x is unable to perform automatic upgrades to newer versions. This issue is caused by changes in the versioning scheme and the deprecation of SysV init systems.

Workaround: Manually install a newer version of the Log Management Agent.

A "Log Store Health Warning" alert appears for healthy single-node clusters

Single-node Log Store clusters are not recommended for production because they create a single point of failure. If you use this configuration, the cluster health status remains "Yellow" in the VCF Operations administrative alert section. This occurs because replica shards cannot be assigned to the same node as their primary shards. The system interprets this as an availability issue and triggers a "Log Store Health Warning" on the dashboard.

Workaround: You can safely ignore this warning if you are intentionally running a single-node cluster.

Log forwarder SSL connections enforce strict certificate validation

Log forwarder fails to establish SSL connections and logs are not forwarded to configured destinations. SSL handshake errors regarding hostname verification are displayed. If you are upgrading from earlier versions, you may experience connection failures if existing log forwarder destinations use certificates that lack Subject Alternative Name (SAN) entries, even if the certificates contain valid Common Name (CN) fields. Starting in version 9.1, the log forwarder enforces strict hostname verification during the SSL handshake. Connections fail if the destination's certificate lacks a valid SAN entry matching the hostname, as the system no longer falls back to the Common Name (CN) for verification.

Always occurs when using SSL-enabled log forwarders with certificates that lack SAN fields after upgrading to version 9.1.

Workaround: Regenerate or update certificates for all log forwarder destinations to include valid SAN entries that match the destination hostname or IP address. If using self-signed certificates, ensure the SAN field is populated during certificate generation.

Data transfer from legacy clusters initiates for archived buckets only

When initiating data transfer from legacy clusters, data from all archived buckets is copied to the target cluster, potentially overlapping with the specified time interval. Only the most recent write buckets are active (non-archived) and data is not migrated from these active buckets. You can verify bucket states on the legacy cluster using the command: `/usr/lib/loginsight/application/sbin/bucket-index show`.

Workaround: None

Log Analysis page displays empty or partial results without error messages

The Log Analysis page in VCF Operations may display partial or empty results. Related alerts and dashboards are also affected. If the backend experiences exceptions (such as CorruptIndexException or CircuitBreakingException), VCF Operations handles these silently without displaying an error message to the user, making it unclear that the results are incomplete.

Workaround: A fix has been introduced for CircuitBreakingException; however, there is currently no workaround for other index-related exceptions.

Log collection should only be enabled in one VCF Operations instance for vCenter, NSX or other VCF components

Enabling log collection for vCenter, NSX or other VCF component in a new VCF Operations instance overrides the existing configuration of other instances. Log collection should only be enabled in one VCF Operations instance for vCenter, NSX or other VCF components. Enabling it across multiple instances results in undefined behavior where only one instance receives logs at a time.

Workaround: None

VCF Operations for Logs UI displays an HTTP 500 Internal Server Error when pods are shut down

The user interface displays an "HTTP 500 Internal Server Error" when the `ops-logs` service pods are scaled to zero or shut down. When all `ops-logs` pods are removed (during maintenance or shutdown), the Envoy Gateway returns an HTTP 500 error instead of the expected HTTP 503 (Service Unavailable). Envoy Gateway proactively detects the lack of healthy endpoints and programs a direct 500 response. If at least one pod exists (even if terminating), the gateway correctly returns 503.

Workaround: None. This is cosmetic and does not indicate a functional failure. The service will resume normal operation once pods are scaled back up.

Workbench

Real-Time Analysis displays "No data" for supported object types when core components are not upgraded to 9.1

During an upgrade from VCF 9.0 to 9.1, the Real Time Analysis tab in the Workbench may incorrectly display "No data" for supported object types. This occurs in brownfield scenarios where management components have been upgraded, but core components remain at a previous version. The Real Time Analysis tab does not currently provide a compatibility warning or notification to indicate that core components require an upgrade to display metrics.

Workaround: None. This is a transient state during the upgrade process. Ensure all core components are upgraded to version 9.1 to restore Real Time Analysis data visibility.

Real-time metrics

Real-time metrics data ingestion fails and data gaps appear in charts when the ClickHouse database reaches disk capacity

When the ClickHouse storage becomes full, the system is unable to process or store incoming real-time metrics, resulting in data loss. This occurs when the ingestion volume exceeds the provisioned disk space for the Real-time metrics component.

Workaround: Increase the storage size for the Real-time metrics component by navigating to **Build > Lifecycle > Real-time Metrics > Increase Storage Size**.

High ingestion loads cause real-time metrics pods to restart, resulting in intermittent data gaps in metric charts

During periods of significantly high data ingestion, real-time metrics pods may encounter instability and restart unexpectedly. This behavior leads to temporary data loss or "holes" in metric charts for the duration of the restart period.

Workaround: None.

Real-time metrics charts do not load when real-time metric data collection is not started

Real-time metrics charts fail to load in VCF Operations when a vCenter or NSX-T adapter instance under the VCF adapter has never been started since configuration. This happens because the real-time metric data collection is not started. This results in an ERROR status for the real-time metric adapter and prevents real-time metrics charts from loading.

Workaround: Manually start all instances of vCenter and NSX-T adapters under the VCF Adapter. The Real-time metrics adapter will sync and return to a healthy status within 48 hours of enabling collection for all domains.

Real-time metrics data collection fails after a vCenter upgrade

Data collection fails if the real-time metrics component was deployed before upgrading vCenter to version 9.1. If vCenter is upgraded after the real-time metrics component is already deployed, the system fails to enable data collection post-upgrade.

Workaround: From the real-time metrics Day-2 actions menu, stop the service and then start the service to resume collection.

Application monitoring

User Account Control (UAC) agent installation fails with *IndexError: list index out of range* when running *uaf-bootstrap-launcher.bat*

When running `uaf-bootstrap-launcher.bat` during the UAC agent installation flow, the installation fails with the following traceback:

```
File "C:\\VMware\\UCP\\downloads\\config-utils.py", line 1387, in <module>
u = UafBootstrap(sys.argv[2], sys.argv[3], sys.argv[5], sys.argv[6],
 run_dependent_action=run_dependent_action)
IndexError: list index out of range
```

The status for content upgrades of product-managed Telegraf agents may intermittently show as failed following the upgrade of VCF Operations and cloud proxies

After upgrading VCF Operations and Cloud Proxies from 8.18.6 or 9.0.2 to 9.1.0.0, the content upgrade operation on product-managed Telegraf agents may intermittently report a "Content Upgrade Failed" status in the UI. The actual agent content upgrade on the endpoint completes successfully; however, a post-upgrade step ("maintain-agent-status") can time out due to an asynchronous Salt Minion service restart, causing the overall operation to be marked as failed. This is more frequently observed on application monitoring HA-enabled collector groups with multiple monitored VMs.

Workaround: Retry the content upgrade on the affected agents. The Telegraf agent content on the endpoint is already upgraded to the target version; only the status in the UI is incorrect.

Audit Records

Audit record counts might not match the left navigation filters

In high-volume environments with large numbers of audit records (auditIDs) within a specific time period, the underlying query engine (Log Management) may encounter limitations when returning large aggregation totals. As a result, certain audit record counts may be excluded from the Category or Object Type filters.

- To address this, **No Object** and **No Category Type** fields have been added to the user interface to display missing data counts.
- These fields are for display purposes only and are disabled for selection in queries.
- The system enforces a cap of 50 aggregations for audit records. Consequently, the **Category** and **Object Type** filters will only display the top 50 audit record counts.
- The line chart on the **Audit Trail** page does not dynamically update when a filter is changed due to a UI framework restriction. To improve clarity, the chart title has been updated to **Total Records Timeline by Result**.

Workaround: Deselecting **VMSP** can provide more accurate count displays.

VCF Operations for networks

Antrea flows for the VKS 1.35.0+ clusters are not visible in VCF Operations for networks.

VKS 1.35.0+ clusters are not being discovered by VCF Operations for networks. Consequently, users cannot see these clusters and the Antrea flows associated with them in VCF Operations for networks. These flows are also missing from the Operate > Flows section in the VCF Operations.

Workaround: None

Existing VCF Operations for networks collector nodes are not imported or managed by fleet lifecycle

In VCF 9.1, fleet lifecycle does not import existing VCF Operations for networks collector nodes. As a result, these nodes do not appear in the fleet lifecycle inventory and cannot be managed for lifecycle tasks through VCF Operations.

Workaround: Day-N actions and management tasks for VCF Operations for networks collectors can be performed by following VCF Operations for networks guidance. For detailed, step-by-step instructions about performing these actions, see Network Inventory.

Support Bundle generation for VCF Operations and VCF Operations for networks is not available in Fleet Lifecycle

The ability to generate and download support bundles for VCF Operations and VCF Operations for networks components is not available directly within the fleet lifecycle interface in VCF 9.1. Support bundle generation and download for VCF Operations and VCF Operations for networks components is not integrated into fleet lifecycle for VCF 9.1.

Workaround: To collect support bundles, users must log in to the respective native product console for generation and download. Refer to the product-specific documentation for instructions:

- For VCF Operations, please see Create a Support Bunde in VCF Operations.
- For VCF Operations for networks, please see Create a Support Bundle in VCF Operations for Networks.

Developer Center

The PowerCLI card on the APIs & SDKs page under Developer Center displays an outdated install command, directing users to install the legacy VMware.PowerCLI 13.3 module instead of the current VCF.PowerCLI 9.x

On the APIs & SDKs page (Build > Developer Center > APIs & SDKs), the PowerCLI card instructs users to install PowerCLI by running "Install-Module -Name VMware.PowerCLI". This installs VMware PowerCLI 13.3, which only supports vSphere 8 and earlier versions. The current module has been renamed to VCF.PowerCLI starting with version 9.x, which supports both legacy versions and VCF 9.0 and later versions. The legacy module does not support VCF Operations and lacks a smooth transition path to VCF 9.0.

Workaround: Users can manually install the correct module by visiting https://developer.broadcom.com/powercli to download and install VCF.PowerCLI 9.x instead of following the command shown on the PowerCLI card.

Workload Mobility

The PowerCLI module for HCX Manager (VMware.VimAutomation.Hcx) included in all versions of VCF.PowerCLI is not compatible with VMware Operations HCX version 9.

The PowerCLI module for HCX Manager (VMware.VimAutomation.Hcx) included in all versions of VCF.PowerCLI is compatible with HCX version 4.11 and no later.

Editing a default service mesh fails with error "instance.computeProfiles does not meet minimum length of 2"

Edit operation fails with above error, the default service mesh disappears and a banner with error remains on the page.

Workaround: None

Multicast traffic on extended network in trunk mode fails to reach the other side.

Multicast traffic across an overlay to overlay extended network in trunk mode does not work.

Workaround:

Switch the bridge mode from trunk (multiple extensions per vNIC) to single extension per vNIC.

Option-1:

1. Create a new service mesh SM2 with overlay to overlay container pair in trunk mode.

2. Update SM2's bridge mode from "trunk-bridge" to "single-bridge"

3. Transition the affected network from SM1 to SM2.

Option 2:

1. Un-extend all the extensions from SM1 with overlay to overlay container pair in trunk mode

2. Update SM1's bridge mode from "trunk-bridge" to "single-bridge" for appliances having overlay to overlay network container pair

3. Extend all the networks back on SM1.

For an existing appliance pair, the bridge mode can be changed by running the following command at respective HCX managers:/opt/vmware/bin/interconnectDebugUtils.sh modifyBridgeMode <local-appliance-id> single.

Redeploying the HCX Edge appliance with the local=true flag results in the tunnel going down.

Redeploying the HCX Edge appliance with the local=true flag results in the tunnel going down.

Perform the redeploy via API by explicitly setting the local=false parameter to ensure proper state synchronization, or use the HCX Manager UI which, by default, maintains symmetry by redeploying both the local and remote peer appliances simultaneously.

Downtime of in-service redeployment of an edge based NE mesh took more than 10 sec.

The downtime during in-service redeployment of an edge-based NE mesh is higher ranging from a few seconds to a minute.

No workaround.

Force power off is not allowed from API when bulk migration is in progress.

Unable to modify the "Force Power Off" setting for an active migration if migration was initiated without a defined switchover schedule.

Temporarily assign a switchover schedule to the migration to force a value update.

HCX Assisted vMotion (HAV) migration failed with ENS enabled.

HAV migration failure occurs due to ENS Mode Mismatch between the configured source and the target network entities.

Set the advanced vCenter Server parameter config.vpxd.network.allowVmotionBetweenENSModes to true to permit vMotion operations between networks with different ENS modes. https://knowledge.broadcom.com/external/article/395576/manual-vmotion-fails-with-the-destinatio.html.

Manage

Fleet Management

Batch precheck of upgrade plan for all VCF management components fails with the validation error `VCF_LCM_FLEET_UPGRADE_400_COMPONENT_NOT_NEEDED_USER_INPUT_SPEC_PROVIDED`

This issue occurs when a component's user input specification remains configured after the component has already been upgraded to its target version. If you then click **Run Prechecks (ALL)**, or use **Select All** on the **VCF Management** > **Upgrade** page without selecting individual components, the precheck runs against the full upgrade plan. Because the plan includes a user input spec for a component that no longer requires one, the validation fails and returns the error above.

Workaround: Do not use the **Run Prechecks (ALL)** option. Instead, select the checkbox for each component you want to precheck individually, and then run the prechecks.

Deletion of an existing folder causes Day-N actions that provision new VCF services runtime nodes to fail

If you use the vCenter UI to move VCF services runtime or VCF Automation VMs from a folder or resource pool to another folder or resource pool after deployment, then delete the old folder or resource pool, any day-N operations that trigger VCF services runtime node rollouts will fail.

Workaround: Before deleting the old folder or resource pool, update deployment values in the VCF services runtime package to reference the new folder or resource pool to which VMs are being moved. This action triggers a rollout of the VCF service runtime nodes and will create new VMs in the newly specified resource pool or folder.

VCF SSO role assignment fails with an 'Internal server' error and VCF Operations login fails with a 'No user permissions' error

The VMware Infrastructure Management adapter fails to fetch role details from the VCF Operations API platform that is later updated in the identity broker. This results in a 'SocketException: Connection reset' error that temporarily prevents role-based access control and SSO logins in VCF 9.1. The system automatically recovers within one hour when the scheduled RoleSync job (running on a 1-hour interval) re-establishes connectivity and syncs role data.

Workaround: Restart the VMware Infrastructure Management adapter instance using the command: `service collector restart`.

Certificate and password management operations fail when a VCF component's TLS certificate is missing the IP/FQDN in its SAN entries while configuring a VCF component in VCF Operations

Certificate and password management operations fail when a VCF component's TLS certificate is missing the IP/FQDN in its SAN entries while configuring a VCF component in VCF Operations. This is because of a `HostNameVerification` failure during the TLS handshake.

Workaround: Edit the configuration of the VCF component in VCF Operations and set the hostname to the same IP or DNS name that appears in the VCF component TLS certificate's SAN (the value the certificate is actually issued for). After the integration `hostname` matches what the certificate presents, certificate and password management operations should not fail with the TLS handshake failure.

In VCF Operations, certificates for a standalone vCenter may not appear if the vCenter TLS certificate does not include a Subject Alternative Name (SAN) that matches the `hostname` you used when adding the vCenter integration.

When you add the vCenter adapter, you can use either an IP address or a DNS name (FQDN). If the vCenter certificate does not have a SAN entry that is used to add the vCenter adapter in VCF Operations, the standalone vCenter certificates are not collected. This is because of `HostNameVerification` failure when connecting to the vCenter to collect certificates. This validation is enforced by the vCenter SDK and cannot be bypassed.

Workaround: Edit the vCenter integration in VCF Operations and set the hostname to the same IP or DNS name that appears in the vCenter TLS certificate's SAN (the value the certificate is actually issued for). After the integration `hostname` matches what the certificate presents, standalone vCenter certificates should be collected as expected.

NSX certificates are not visible under the management domain

If a shared NSX manager is used to create a workload domain, the NSX certificates only appear in that newly created workload domain, and never in the management domain.

Workaround: Use the workload domain for NSX certificate rotation.

VCF Operations certificate and password management can be performed on Mobility Agent vSphere hosts for HCX migrations, however, this is an unintended visibility issue, as these entities should be excluded from the ESX list

VCF Operations certificate and password management pages currently list Mobility Agent vSphere hosts for HCX migrations (details) for the certificate and password management operations. The lifecycle of these hosts are controlled by VCF Operations HCX Manager in the Interconnect workflow. In VCF 9.1 they are erroneously listed under the VCF components list as ESX.

Workaround: Identify the Mobility Agent vSphere Hosts for HCX Migrations by noting the management IP address of all the HCX-WAN-IX appliance type under the VCF Operations HCX Interconnect page. Ignore these hosts when performing certificate or password management in VCF Operations.

VCF Operations orchestrator

Workflow variables missing from the field configuration dropdown in the Form Designer

When configuring field properties in the Form Designer, for example, mapping action inputs on the Values tab, the dropdown menu for selecting a field does not display the correct workflow variables. Under the Variables section of the dropdown, default request variables like `Catalog item reference`, `Tenant reference`, and `Provider binding` are incorrectly displayed.

Workaround: When configuring a VCF Operations orchestrator action input, change the input source type from `Field` to `Constant` and manually enter the required value instead of attempting to bind it dynamically to a workflow variable.

The Save button is disabled after clicking Rebuild on the Action page

On the Action page, clicking the Rebuild button while there are unsaved changes causes the Save button to become permanently disabled.

Workaround: Save your changes before rebuilding the environment.

System dashboard shows only one node for clustered VCF Operations orchestrator instances

When you configure a VCF Operations orchestrator cluster with VCF SSO, you can see only one node on the system dashboard in VCF Operations orchestrator.

Workaround: No workaround.

Scheduled workflow runs fail if a user has more than one role in VCF Automation

Scheduled workflows and long-running workflows fail if they are requested by a user who has more than one assigned role in VCF Automation.

Workaround: No workaround.

Local VCF Operations orchestrator roles are sometimes ignored if VCF Operations orchestrator is configured with VCF SSO

VCF Operations orchestrator fails to parse the correct organization during login for users using VCF SSO configured with UPN. Login works for VCF SSO configured with sAMAccountName. As a result, local roles assigned in VCF Operations orchestrator are ignored during login.

Workaround: Assign VCF Operations orchestrator global roles to VCF SSO users.

vCenter instance reported as unusable in the VCF Operations orchestrator plug-in for vCenter

If the connection to a vCenter instance is interrupted, the vCenter instance might be reported as unusable in the VCF Operations orchestrator inventory and you cannot run workflow against it.

Workaround: Update the vCenter instance registration in the VCF Operations orchestrator plug-in for vCenter.

The context.getToken() function breaks after token refresh in Python runtimes

In Python environments, the `context.getToken()` function does not work when VCF Operations orchestrator uses VCF Automation as an authentication provider.

Workaround: No workaround.

The vracli network command cannot change IP address

The `vracli network` command cannot change the IP address of a VCF Operations orchestrator instance.

Workaround: To work around this issue, see Broadcom knowledge base article 429962.

VCF Automation

This document contains the following sections

- Provider Management
- Organization Management
- Upgrade
- vSphere Supervisor

Provider Management

The following known issues impact the functionality included in the VCF Automation 9.1 Provider Management UI.

Namespace creation might fail due to an image synchronization timeout when a content library contains many VM images

When a project-scoped content library contains a large number of VM images, the image registry might take longer than the default 15-minute timeout to synchronize. This delay causes the namespace creation to fail.

Workaround: Increase the maximum number of readiness check attempts to 60 by running a script on the VCF Automation host.

1. Back up the VCF Automation appliance.
2. Set the kubeconfig environment variable to point to the VCF Automation cluster.
   ```
   export KUBECONFIG=vcfa.kubeconfig
   ```
3. Run the following command to apply the workaround script.
   ```
   base64 -d <<<
    "IyEvYmluL2Jhc2gKCklTU1VFPSJWQ0ZJWC04MjYzIgpDT05GSUdfS0VZPSJ2Y2ZhLmNvbnRlbnRMaWJyYXJ5Lm5hbWVzcGFjZS5hdHRhY2gucmVhZ
    | bash
   ```
4. Access the cell management tool and verify that the timeout value is `60`.
   ```
   kubectl -n prelude exec tenant-manager-0 -- bash
   /opt/vmware/vcloud-director/bin/cell-management-tool
   manage-config -l vcfa.contentLibrary.namespace.attach.readiness.check.max.attempts
   ```

Imported users and groups cannot log in to the VCF interface

Users and groups successfully imported into VCF Automation cannot log in to the VCF interface, even though they appear in the Access Control list. This problem occurs when there is a format mismatch between the identity provider (IDP) attribute mappings and the credentials that the user enters. If the IDP returns an attribute, such as an email address or UPN, in a format that does not exactly match the login string or group name, the authentication handshake fails.

Workaround: There is no workaround available in the VCF Automation user interface. You must correct the attribute mappings in your IDP configuration so that the returned attributes exactly match the user credentials and group names.

Region quota updates fail when a content library is in a Partially Ready state

When a backing vCenter content library is deleted directly in vCenter, VCF Automation retains a dangling reference to that library. This state causes the content library to appear as `Partially Ready` in the Organization UI and prevents successful updates to the region quota for the organization. Region quota updates fail with an error:

```
[ ba0b8208-a919-4f5c-a7d9-74039d44834b ] One or more exceptions have occurred
 - com.vmware.ssdc.util.LMException: NotFound (com.vmware.vapi.std.errors.not_found) => {
    messages = [LocalizableMessage (com.vmware.vapi.std.localizable_message) =>

{     id = com.vmware.vdcs.cls-main.library_not_found,     defaultMessage = Library 8132d356-
b880-498c-885f-90ac585bcc36 not found.,     args = [8132d356-b880-498c-885f-90ac585bcc36],     params =
 <null>,     localized = <null> }
],
```

Workaround: Delete the affected content library from the Organization UI. After you remove the dangling reference, region quota updates proceed successfully.

Bring Your Own Key (BYOK) operations time out and fail

If you remove a vCenter instance from VCF Automation without first deleting its associated key providers, the system retains the key providers in a failed state. This accumulation of failed key providers causes resource contention and blocks communication. As a result, BYOK operations, such as registering a key provider, generating an encryption key, or publishing a key provider to a tenant, fail with a timeout error.

Workaround: To recover the encryption manager, you must manually delete the failed Custom Resources (CRs) and Runtime Defined Entities (RDEs) associated with the removed vCenter instance.

1. Access the VCF Management Services cluster.
2. Identify and delete the following encryption management CRs for the failed key provider registration:
   - `SystemKeyProvider`

- `KeyProvider`
- `OrgKeyProvider`

3. Identify and delete the following encryption management RDE instances for the failed key provider registration:
   - `KeyProvider`
   - `KeyProviderStatus`
   - `OrgKeyProvider`
   - `EncryptionClass` (if any exist)
   - `EncryptionClassStatus` (if any exist)

High API load on VCF Automation during data collection

In large-scale environments, VCF Operations might overwhelm VCF Automation with frequent API calls. By default, the system attempts to fetch entity information every 5 minutes. In high-density configurations, the API requests can overlap and potentially destabilize the environment.

Workaround: To reduce the VCF Automation load in large-scale environments, manually adjust the collection intervals and thread pool settings.

1. Use the VCF Operations UI to set the collection interval to 40 minutes and the Advanced Metrics Collection Interval to 240 minutes.
2. Modify the adapter configuration.
   a. Log in to the VCF Operations node.
   b. Edit the `/usr/lib/vmware-vcops/user/plugins/inbound/automation_adapter/conf/automation.properties` file.
   c. Update the thread pool and timeout properties as follows:

```
RESOURCE_COLLECT_THREAD_POOL_SIZE=5
RELATIONSHIP_COLLECT_THREAD_POOL_SIZE=5
METRICS_COLLECT_THREAD_POOL_SIZE=10
RESOURCE_COLLECTION_TIMEOUT_IN_MS=3600000
RELATIONSHIP_COLLECTION_TIMEOUT_IN_MS=3600000
METRIC_COLLECTION_TIMEOUT_IN_MS=3600000
```

3. To apply the changes, restart the adapter instance collection.

Deleting the last region changes the provider scope to false for the vCenter instance in VCF Automation

After deleting all regions in VCF Automation, the `provider_scoped` flag is set to `false`. Reconnecting a vCenter instance after the change in flag status causes inventory data to be deleted.

Workaround:

After deleting the last region in VCF Automation associated with the specific vCenter instance, perform the following workaround, before attempting to create a new region on the same instance:

1. Navigate to **Connections** and unregister the vCenter instance.
2. Refresh the VCF Instance.

After the refresh, the vCenter instance is registered again with the `provider_scoped` flag set to `true`.

Deactivating the Provider Outbound NAT setting does not remove the NAT IP block reference in the database

When you deactivate the **Provider Outbound NAT** setting as a Day-2 operation, the corresponding NAT IP block does not get removed from the external connection in the database. As a result, you cannot delete the IP block.

Workaround: Create a dummy IP block and configure the external connection to use it for the Provider Outbound NAT. Alternatively, you can delete and re-create the external connection.

Deactivating the Provider Outbound NAT setting fails to trigger a cleanup of the NAT IP block from the advertised IP blocks in NSX Manager

When you deactivate the **Provider Outbound NAT** setting as a Day-2 operation, NSX Manager continues to advertise the NAT IP blocks that you used to configure the provider outbound NAT.

Workaround: Remove manually the IP block from the list of advertised IP blocks for the gateway connection

Centralized connections configured with provider outbound NAT require an external IP block

When you create a centralized connection for shared services and you select the **Provider Outbound NAT** checkbox, the outbound NAT IP block of the centralized connection is automatically added to the advertised IP blocks of the gateway connection, so specifying an external IP block should not be required. However, to successfully finish your task, you must select an external IP block.

Workaround: None.

Avi load balancer instance deployed via SDDC manager is automatically registerd to VCF Automation at next discovery interval

The default synchronization interval at which VCF Automation discovers objects is 24 hours. As a result, any Avi load balancer instance that is deployed during that interval is not discovered until the next synchronization run.

Workaround: In the VCF Automation Provider UI, manually refresh your account from the **VCF Instances** page.

Organization Management

The following known issues impact the functionality included in the VCF Automation organization UI.

Logged-in user unable to view any pages in a VM Apps organization

When a user with the Organization Owner role tries to log in to a VM Apps organization, they receive the error `Sorry, it looks like you don't have any invitations to VMware Cloud Services. At this time, product availability is limited to invitation only`**.** The user is not able to view any pages when logged-in.

Workaround: In addition to the Organization Owner role, assign the Assembler Administrator, Service Broker Administrator, or Orchestrator Administrator role to the user.

Blueprint deployment fails with the Counter Exhausted error

By default, when a new custom naming has a template with `${##}`, this indicates that the maximum digits that the naming template can have is 99. If a VM reaches the 99 digit limit, the next request fails with the error `Counter Exhausted`.

When the custom naming needs a counter appended at the end of the template, for example, `myvm-${##}`, it generates a counter that is incremented each time a new number is needed. Once the max limit is reached, the deployment fails with the error `Counter Exhausted`. Names are in the range from `myvm-01` to `myvm-99`.

Workaround: Increase the template counter size.

1. In the existing custom name template, delete the specific resource template, for example, the `Machine` template.

   Important:

   Do not delete the entire custom name template.
2. Create a new resource template for the specific resource with a larger counter size. For example, change `myvm-${##}` to `myvm-${###}` so you get a maximum of 999 counters.
3. Set the starting counter to 99. By setting the starting counter to 99, the next counter starts from 100 onwards so that existing VMs with counters from 01-99 can maintain the same name, avoiding conflicting counters.

Captured blueprint custom scripts contain \r characters

When uploading batch scripts (`.bat`, `.sh`) through the guest OS configuration forms in captured blueprints, Windows line endings (`\r\n`) are preserved and sent to the blueprint API. This causes an issue where the `\r` character is added to the script content, potentially breaking script execution on Unix-based systems.

Workaround: Remove the Windows `\r` character from the script before uploading it.

Approval request emails not sent to approvers

In approval policies, if the approval is assigned to a project administrator which is an AD group, group members do not get an email notifying them that they must approve a request. This issue only impacts the email notifications. Users can still log in to VCF Automation and approve the request.

Workaround: Instead of adding an AD group as an approver, add individual users one by one.

Creating a Canonical content library fails with an OVF validation error

This issue is caused by the addition of an SBOM in Ubuntu OS images. The following files are present in both the OVA and the manifest (`.mf`) file but are not actually downloaded because they are not referenced by the OVF:

- `ubuntu-resolute-26.04-cloudimg.manifest`
- `ubuntu-resolute-26.04-cloudimg.sbom.spdx`
- `ubuntu-resolute-26.04-cloudimg.filelist`

Because these files are missing in the OVF, the checksum validation fails with the error `Validation failed for the OVF file you provided: Invalid file: [...]` and the Canonical content library cannot be created.

No workaround.

Selecting a namespace class and region before selecting a project causes a 404 error when creating a namespace

When creating a namespace, if the user selects a namespace class and a region but does not select a project, VCF Automation fails with a 404 error message. The user cannot proceed with namespace creation or zone selection as the zone list is empty due to the 404 error. Selecting a project at this point does not resolve the issue.

Workaround: Clear the namespace class and region selection, select a project, and then reselect the namespace class and/or region.

Upfront pricing is not supported for vSphere Supervisor version 9.0.x

Upfront pricing is only supported for VCF Automation 9.1 when integrated with vCenter 9.1 and VCF Operations 9.1. Trying to fetch upfront pricing for deployments in a region on a vSphere Supervisor 9.0.x fails with an internal server error.

Workaround: Upgrade vSphere Supervisor to version 9.1.

IP Allocations UI fails with a 504 Timeout error in scaled organizations with over 500 IP blocks

In the VCF Automation organization UI, users cannot access the IP Allocations page to view or release IP block allocation states. This issue specifically affects scaled organizations that contain more than 500 IP blocks within a single region. When attempting to load the page, the request eventually fails and displays a timeout error message.

This issue is caused by a combination of UI data-fetching behavior and pagination limitations within the underlying NSX API. To render the IP Allocations page, the UI attempts to fetch the allocation states for all IP blocks in a region simultaneously. However, the maximum page size supported by the NSX IPBlockAllocationState API is 10 items per request.

In a scaled environment with more than 500 IP blocks, the backend service must execute 50 or more consecutive API calls to fulfill the single UI request. If the cumulative response time for these calls exceeds one minute, the API gateway drops the connection, resulting in a 504 Gateway timeout.

Workaround: To bypass the timeout and successfully view or release IP allocations, the organization administrator can use the VCF Automation CLI to manage the resources directly through the Kubernetes API.

1. Log in to the VCF Automation CLI and configure your kubectl context to access the organization.
2. List all IP blocks for the organization by running the following command.

   ```
   kubectl --context=cci get ipblocks -A
   ```

   Example output:

   ```
   NAME                            REGION    CIDRS           VISIBILITY   STATUS     AGE
   :ext-ip-blk1                    region1   10.10.1.0/24    External     Realized   112m
   :ext-ip-blk2                    region1   20.20.1.0/24    External     Realized   111m
   default-region1-172_30_0_0_16   region1   172.30.0.0/16   Private      Realized   109m
   default-tgw-region1             region1   172.31.0.0/16   Private      Realized   109m
   ip-block-gbrg                   region1   182.31.0.0/16   Private      Realized   104m
   vpc-x6b3-11_0_0_0_20            region1   11.0.0.0/20     Private      Realized   61s
   ```

3. View the allocation states for a specific IP block. Identify the target IP block from the previous step and use the `get` command to inspect its details. (Example: Viewing IPBlock :ext-ip-blk1)

   ```
   kubectl --context=cci get ipblockallocationstates :ext-ip-blk1 -o yaml
   ```

   Example Output:

```
  allocationStates:
  - cidr: 10.10.1.2/32
    ipAddressAllocationName: ip-allocation-gdhq
  - cidr: 10.10.1.0/32
    consumerVPCName: default-region1
    usedBy:
    - kind: VPCNATRule
      name: default-region1:default-default-region1-172_30_0_0_16
      usedFor: VPCNAT
    vpcIPAddressAllocationName: default-region1:_DEFAULT--SNAT_TRANSLATED
  - cidr: 10.10.1.3/32
    vpcIPAddressAllocationName: vpc-x6b3:ip-allocation-lm6g
  - cidr: 10.10.1.1/32
    consumerVPCName: vpc-x6b3
    usedBy:
    - kind: VPCNATRule
      name: vpc-x6b3:default-vpc-x6b3-11_0_0_0_20
      usedFor: VPCNAT
    vpcIPAddressAllocationName: vpc-x6b3:_DEFAULT--SNAT_TRANSLATED
  apiVersion: vpc.nsx.vmware.com/v1alpha1
  kind: IPBlockAllocationState
  metadata:
    creationTimestamp: null
    name: :ext-ip-blk1
  regionName: region1
  visibility: External
```

4. If you need to release a specific IP allocation that is no longer in use, delete the corresponding resource using the exact name identified in Step 3.
   a. To delete a standard IP Address Allocation, run the following command.

      ```
      kubectl --context=cci delete ipaddressallocations ip-allocation-gdhq
      ```

      Expected Output:

      ```
      ipaddressallocation.vpc.nsx.vmware.com "ip-allocation-gdhq" deleted
      ```

   b. To delete a VPC IP Address Allocation, run the following command.

      ```
      kubectl --context=cci delete vpcipaddressallocations vpc-x6b3:ip-allocation-lm6g
      ```

      Expected Output:

      ```
      vpcipaddressallocation.vpc.nsx.vmware.com "vpc-x6b3:ip-allocation-lm6g" deleted
      ```

The Bills page doesn't renew the authorization token

The Bills page on the Administer tab stops working or shows authorization session errors after the user has been on the page for more than five minutes. This is caused by a short-lived iframe URL token. When the token is not renewed, subsequent actions on the Bills page run with an expired token and fail until the user leaves or reloads the page.

Workaround: Navigate away from the Bills page and then open Bills again so a new token is fetched and a fresh URL is loaded.

Namespaces cannot have more than 1,000 shared subnets

When creating or updating a namespace, you cannot assign more than 1,000 shared subnets to the namespace.

No workaround.

The Edit button for namespaces is visible to project administrators even though they do not have the permissions to perform the action

Project administrators see an active **Edit** button on the namespace page in the VCF Automation organization UI, even though they cannot actually edit the namespace.

No workaround.

Lists for VM classes and storage classes on a namespace class only display the first 128 entries

When viewing or editing a namespace class in the VCF Automation organization UI, the interface retrieves available VM classes and storage classes using a default page size limit. In large-scale environments where the total number of classes across all associated regions exceeds 128, the list is truncated. Affected users are unable to view or assign classes that fall outside the initial 128 returned items, even though those classes are valid and present in the underlying system. This issue occurs in any organization where the combined total of VM classes or storage classes across all regions exceeds 128.

Workaround: If you need to assign a class that does not appear in the truncated list, use one of the following methods:

- Search by name. Use the Add dialog to query and add individual VM classes or storage classes by their specific name.
- Wildcard selection. Use the wildcard * selection, where supported, to include all available classes regardless of the display limit.
- API update. Use the VCF Automation APIs to update the namespace class directly. This bypasses the UI display limit and ensures all intended classes are associated correctly.

File upload fails or is canceled when the user navigates away from the content library page

After submitting the upload form for a VM image (tenant) or a content library item (provider content library), the user is brought to the content library list page. If the user then navigates to another part of the application while the upload is still in progress, the system cancels all in-flight network requests including the upload. A warning is displayed advising the user to stay on the page until the upload is complete, which disappears once the upload finishes.

Workaround: Stay on the content library upload page for the entire duration of the upload without navigating away.

The SubnetConnectionBindingMap resource is not captured during namespace capture

When capturing a namespace as a blueprint, the `SubnetConnectionBindingMap` resource is not captured.

Workaround: After the namespace capture is complete, add the following resource to the blueprint manually.

```
subnetConnBindingMap_binding-vlan-1701:
    type: CCI.Supervisor.Resource
    dependsOn:
    - <subnet_1>
    - <subnet_2>
    properties:
      context: ${resource["Namespace"].id}
      manifest:
        apiVersion: crd.nsx.vmware.com/v1alpha1
        kind: SubnetConnectionBindingMap
        metadata:
          name: <name>
        spec:
          subnetName: <subnetName>
          targetSubnetName: <targetSubnetName>
          vlanTrafficTag: <trafficTag>
```

When capturing a namespace as a blueprint, the Publish to catalog option might not be enabled due to warnings related to guest customization

When capturing a namespace as a blueprint, if any of the virtual machines are customized, users see a warning message that the guest customization will be removed in the generated blueprint. In VCF Automation 9.1, if any warnings are present, then the **Publish to catalog** option is not enabled in the UI.

Workaround: Even though the **Publish to catalog** option is not enabled, user can still generate the blueprint. Once the blueprint is generated, go to the blueprint, verify it, and manually publish it to catalog. See Publish a Blueprint to the Catalog in VCF Automation.

During namespace capture, users might see a warning message about a missing mandatory infrastructure policy

When a namespace is created, mandatory infrastructure policies are automatically applied. When capturing a namespace as a blueprint, however, VCF Automation incorrectly checks for mandatory infrastructure policies and displays a warning message that the policies are missing.

Workaround: Dismiss the warning message. The namespace capture will succeed and users can successfully go on to deploy the generated blueprint.

VPC LoadBalancer setting is missing from captured blueprints

When a namespace is captured into a blueprint, the load balancer property of the associated dedicated VPC is not preserved. This occurs because the blueprint VPC resource schema does not support the load balancer attribute. Resources deployed from such blueprints, like VMs, fail to receive expected external IP addresses which might lead to connectivity issues.

Workaround: The organization administrator must perform the following procedure.

1. After the VPC is created in the VCF Automation organization UI, navigate to **Manage & Govern** > **VPC**.
2. Toggle on the load balancer setting.

When capturing a blueprint into a project content library, items cannot be renamed in the organization UI

When capturing a namespace as a blueprint in a project content library, the captured images have auto-generated names that cannot be changed using the VCF Automation UI.

No workaround.

Creating a project content library fails with an internal server error in mixed tenancy mode

After upgrading from VMware Aria Automation 8.x, vCenter cloud accounts are imported as connections in a VCF Automation VM Apps organization. These connections can be used to create regions assigned to All Apps organizations so an All Apps organization can have region quota in a supervisor that is managed by the vCenter cloud account used in the VM Apps organization as a result of the upgrade. However, the connection is not automatically updated to use the service credentials with the necessary permissions because this is managed in the VM Apps organization. As a result, users in All Apps organizations cannot create project content libraries that are associated with that region.

Workaround: Add the user account used by the vCenter connection endpoint to the **SupervisorProviderAdministrators** group in vCenter, which manages the respective supervisor/region, to give users the ability to create project content libraries in that particular region.

Project level content library creation fails because of incompatible vCenter and vSphere Supervisor versions

Project content libraries require that both vCenter and the underlying vSphere Supervisor are at version VCF 9.1. Attempts to create a project content library on a Supervisor that is not upgraded to version 9.1 fail.

Workaround: Upgrade vCenter and vSphere Supervisor to version 9.1.

Updating the name or description of an item in a project content library fails with a timeout error

When you update the name or description of an item in a project content library, the update times out after around 25 minutes and fails. The item ends up in a `FAILED` state.

Workaround: After the update times out and fails, refresh the content library to recover the item.

Users cannot change the storage classes referenced by a project content library

When editing a project content library, users cannot change the storage class used by any of the regions that the content library is associated with.

No workaround.

In a VM Apps organization, switching VCF cloud account from service managed credentials fails with a certificate error

In a VM Apps organization, if you create a VCF cloud account using VCF service-managed credentials, when you switch to username/password instead, both vCenter and NSX passes credential validation, but saving the cloud account fails with `Failed to Validate Certificate`.

Workaround: Follow the procedure described in Broadcom knowledge base article 318756.

Information about persistent volumes does not show in the Organization UI when you create a backup with a CSI snapshot and Data Mover is deactivated

When you use **VKS Cluster Management** to create a backup using CSI snapshots and Data Mover is not activated, the information about persistent volumes fails to appear in the **VKS Cluster Management** backup UI. The reason for the issue is that the data protection server relies on the `csi-volumesnapshotcontents.json.gz` file, which is the is the output of Velero 1.16.x. The file is removed in Velero 1.17.x, which is the Velero version that VCF 9.1 uses. Creating backups with a CSI snapshot when Data Mover is activated does not trigger the issue. The processes of backup and restore are not affected.

Workaround: View information about persistent volumes in the `volumeinfo.json.gz` file in the storage.

Installing an add-on to a VKS cluster fails due to using a common name

When you install an add-on to a VKS cluster, you might see an error that the `AddonInstall` name already exists. The issue is that you have an add-on with an identical name installed on another VKS cluster.

Workaround: When you install an add-on, use a unique name. For example, you can add a prefix or a suffix to the add-on name, or you can include the cluster name or any distinguishing string to the add-on name.

VKS add-on images might not be pulled from the software depot via regional Harbor

If you have a deployment that has software depot fully configured and a Supervisor with multiple VKS clusters running, during add-on installation on VKS clusters, the add-on images must be pulled from the software depot by using the regional Harbor. However, sometimes, even though the software depot and the regional Harbor appear to be healthy and accessible in VCF Automation, the add-on images might still be pulled from the legacy public artifactory endpoint: `projects.packages.broadcom.com`, which is not the expected behavior.

The issue is caused by a reconciliation issue on VKS clusters and the `ClusterDomainResolutionEntry` custom resource by VKS. The issue is often triggered by the following sequence:

1. Some VKS clusters are unhealthy.

Some VKS clusters are unhealthy, for example due to NSX connectivity issues. Such unhealthy clusters cannot be reached to clean up related resources.

2. Some deletions remain in progress and cannot proceed.

A `ClusterDomainResolutionEntry` enters a deletion state when a Supervisor is removed from a region. The deletion of the `ClusterDomainResolutionEntry` becomes stuck, because of the unhealthy VKS clusters.

3. Fallback to public registry.

Even if you later the add the Superivor back to the region, because the `ClusterDomainResolutionEntry` is stuck in deletion, VKS cannot find a valid `ClusterDomainResolutionEntry` resource. As a result, VKS stops using the regional Harbor-based repository and reverts to the default legacy public repository - `projects.packages.broadcom.com`.

Workaround: Perform the following steps:

1. Remediate the unhealthy clusters.
   a. Identify and resolve the underlying connectivity or NSX issues causing VKS clusters to be `NotReady`.
   b. If you cannot recover and remediate a cluster, delete it and re-create it with the correct networkig/VPC configurations.
2. Clear stuck custom resources.
   a. Verify that any `ClusterDomainResolutionEntry` that is stuck in deletion is successfully cleared after cluster connectivity is restored.
   b. Wait until a new `ClusterDomainResolutionEntry` resource for the regional Harbor is created on the Supervisor.
3. Restart the kapp-controller by running the following command in the affected clusters:
   `kubectl -n tkg-system rollout restart deployment kapp-controller`
   Restarting the kapp-controller pod in the affected VKS clusters clears the internal cache and forces VKS clusters to use the correct regional Harbor repository for add-ons.

Upgrade

Custom forms with drop-down fields populated with VCF Operations orchestrator actions fail validation

After upgrading from VCF Automation 9.0.2 to VCF Automation 9.1, submitting custom forms that contain a drop-down field with a value list populated by VCF Operations orchestrator actions fails to validate. For VCF Operations orchestrator actions that return Properties objects in a key:value pair format, the backend validation compares the submitted values against an expected value list that contains null values. In VCF Automation 9.0, action results used the format `[\{"id": "<key>", "name": "<value>"}]`. In VCF Automation 9.1, however, the format changed to `[\{"key": "<key>", "value": "<value>"}]` so the validation fails when a user submits a form with incorrectly formatted data.

Workaround: For more information, see Broadcom knowledge base article 445540.

Upgrade to VCF Automation 9.1 fails during the `Perform Component Upgrade` stage

VCF Automation upgrade from 8.18.x or 9.x to 9.1 fails during the **Perform Component Upgrade** stage with error `Internal error occurred. Failed to attach disk [<Disk_Name>] <Disk_Path>.vmdk to node <VCFA_Node>. Please retry the operation or contact support if the issue persists.`

See Broadcom knowledge base article 448730.

Restore operation fails because of a resource reconciliation error

When attempting to restore VCF Automation from a backup, the user receives a resource reconciliation error with the error code `LCMVMSP10011`.

Workaround: Retry the restore operation.

After upgrading vCenter to 9.1, project content library creation fails with an internal server error for new organizations

After upgrading vCenter to version 9.1, service accounts in VCF Automation are not rotated immediately but 24 hours after the upgrade. As a result, when you create a project content library in an organization that has quota in a region associated with that vCenter, the content library ends up in a `Partially Created` state and is not attached to a namespace.

Workaround: After upgrading vCenter to version 9.1, you must enable service account rotation for the VCF instance that has the upgraded vCenter instance. In the VCF Automation Provider Management Portal, navigate to **Administration** > **VCF Instances**, click the vertical ellipsis next to the name of the target VCF instance, and select **Rotate Service Account**.

vSphere Supervisor

For vSphere Supervisor Known Issues, see VMware vSphere Supervisor Release Notes.

VCF SDKs, APIs, and CLIs

This document contains the following sections

- VCF APIs
- VMware Cloud Foundation Python SDK

VCF APIs

vStats related APIs which were in TechPreview state are removed in VCF 9.1

In VCF 9.1, the vStats APIs (previously in Tech Preview) are removed.

The API usage with the client bindings throws `NotSupported` error.

You can use the new Real Time Metrics API. For more information about the Real Time Metrics API, refer to the *Real-time metrics* section in VCF Operations What's New.

NSX Unsupported APIs

The NSX API operations that are not using *application/json* content type for their requests and/or responses are currently excluded from the VCF SDKs.

The unsupported APIs can be accessed over REST directly using a raw HTTP client.

VCF Operations unsupported APIs

List of VCF Operations APIs that are not supported in VCF SDKs:

- `/api/applications/clientCertificate/{collectorId}.post`
- `/api/applications/clientCertificate/{collectorIpOrGroupName}.get`
- `/api/applications/subscribe.put`
- `/api/applications/unsubscribe.put`
- `/api/certificate.get`
- `/api/certificate.post`
- `/api/chargeback/bills/{id}/download.get`
- `/api/chargeback/reports/{id}/download.get`
- `/api/compliance/benchmarks/{benchmarkKey}/assessments/export.post`
- `/api/compliance/benchmarks/{benchmarkKey}/remediations/export.get`
- `/api/configurations/files.get`
- `/api/content/backup/result.get`
- `/api/content/operations/export/zip.get`
- `/api/content/operations/import.post`
- `/api/content/restore.post`
- `/api/policies/export.get`
- `/api/policies/import.post`
- `/api/reports/{id}/download.get`

Direct REST APIs (HTTP) can be used in the automation workflows instead of SDK client bindings for the unsupported APIs.

Log Management unsupported APIs

List of Log Management APIs that are not supported in VCF SDKs:

- `/api/v2/agent/groups.get`
- `/api/v2/agent/secrets.get`
- `/api/v2/events.post`
- `/api/v2/events/ingest/{agentId}.post`
- `/api/v2/fields/extractedFields.post`

Direct REST APIs (HTTP) can be used in the automation workflows instead of SDK client bindings for the unsupported APIs.

VCF Operations for Networks unsupported APIs

List of VCF Operations for networks APIs that are not supported in VCF SDKs:

- `/flows/tcp-incomplete/csv-export.post`
- `/data-sources/common-device/dspack.put`
- `/data-sources/bulk/add.post`
- `/data-sources/generic-switches/{id}/data.put`
- `/groups/discovered-applications/custom-config/fbad/{id}/file/download.get`
- `/groups/discovered-applications/custom-config/fbad/fileErrors/csv.get`
- `/groups/discovered-applications/custom-config/fbad/file/upload.post`
- `/micro-seg/recommended-rules/nsx.post`

Direct REST APIs (HTTP) can be used in the automation workflows instead of SDK client bindings for the unsupported APIs.

VCF Operations Fleet Management unsupported APIs

List of VCF Operations Fleet Management APIs that are not supported in VCF SDKs:

- `/v1/components/{componentId}/support-bundles/{supportBundleId}.get`

Direct REST APIs (HTTP) can be used in the automation workflows instead of SDK client bindings for the unsupported APIs.

SDDC Manager unsupported APIs

List of SDDC Manager APIs that are not supported in VCF SDKs:

- `/v1/components/{componentId}/support-bundles/{supportBundleId}.get`

Direct REST APIs (HTTP) can be used in the automation workflows instead of SDK client bindings for the unsupported APIs.

VMware Cloud Foundation Python SDK
VCF Python SDK no longer supports Python 3.9 and earlier

Using unsupported python versions might result in unwarranted issues.

Always refer the latest compatibility notice of VCF Python SDK before your deployments.

Resolved Issues

See resolved issues for VCF components in version 9.1:

- vSphere
- vSAN
- VCF Installer
- NSX
- VCF Operations
- VCF Automation
- VCF SDKs, APIs, and CLIs

vSphere

This document contains the following sections

- ESX Resolved Issues:
  - Networking Issues
- vCenter Resolved Issues
  - vCenter and vSphere Client Issues
  - Networking Issues
  - vSphere Lifecycle Manager Issues

ESX Resolved Issues:

Networking Issues
After reloading the bnxtroce driver several times, network traffic might intermittently stop

If for some reason the bnxtroce driver unloads and reloads several times in a sequence, the driver might start dropping unknown unicast traffic. As a result, the network traffic might intermittently stop. The issue occurs due to a rare race condition in modifying tagged unicast traffic to unknown unicast address when Promiscuous Mode is active.

vCenter Resolved Issues

vCenter and vSphere Client Issues
You see Service Accounts and Solution Users under Configuration > Users and Groups in the vSphere Client

In VCF 9.0, instead of only accounts with which individuals are signing in, you can also see **Service Accounts and Solution Users** under **Configuration > Users and Groups** in the vSphere Client.

This issue is resolved in this release. With VCF 9.1, you see only the accounts with which individuals are signing in under **Configuration > Users and Groups** in the vSphere Client. The full list of the service accounts and solution users

is internal to vCenter and you can retrieve it by using the dir-cli command line tool. For more information, see dir-cli Command Reference.

Under the Available updates tab in the Virtual Appliance Management Interface (VAMI), values in the Type column might not display correctly

When you click on **Available updates** in the VAMI, if the update is of type **Bug Fix and Security**, in the **Type** column you see `vami.manage.update.type.Bug Fix and Security` instead of **Bug Fix and Security**.

Remediation operations run in a single batch in large environments might fail due to ScanTask timeout

In large environments, when remediation operations run in a single batch, you might see intermittent timeout errors during the host scanning phase. In the vSphere Client, you see errors such as:

```
An internal error occurred while fetching the compliance result from the host XXXXXX.
```

```
Failed to get task result for task(XXXXXX) on host(host-XXXX) : Dynamic exception type:
VumVapi::Lib::VapiClient::wait_error std::exception::what: Operation timed out.
```

The issue occurs not because any task fails, but because the status request waits in the queue longer than the 30-second threshold.

The Storage Policy Service (SPS) status might show unhealthy when adding hundreds of ESX hosts with active IOFilters (VASA Providers) to the inventory

When a large number of ESX hosts with active IOFilters are added to the vCenter inventory in quick succession, and the vCenter instance handles a large number of certificates in the Storage Monitoring Service (SMS) or TRUSTED_ROOT trust stores, the SPS status might show as unhealthy. The SPS generates core dumps with the `OutOfMemoryError` exception, such as:

```
Exception: java.lang.OutOfMemoryError thrown from the UncaughtExceptionHandler in thread
"Catalina-utility-3" Mar 02, 2025 3:10:23 PM org.apache.catalina.core.StandardServer
startPeriodicLifecycleEvent SEVERE: Error sending periodic event
java.util.concurrent.ExecutionException: java.lang.OutOfMemoryError: Java
heap space  at java.base/java.util.concurrent.FutureTask.report(Unknown
Source)  at java.base/java.util.concurrent.FutureTask.get(Unknown Source)  at
org.apache.catalina.core.StandardServer.startPeriodicLifecycleEvent(StandardServer.java:889)
 at java.base/java.util.concurrent.Executors$RunnableAdapter.call(Unknown Source)  at
java.base/java.util.concurrent.FutureTask.runAndReset(Unknown Source)  at java.base/
java.util.concurrent.ScheduledThreadPoolExecutor$ScheduledFutureTask.run(Unknown
Source)  at java.base/java.util.concurrent.ThreadPoolExecutor.runWorker(Unknown Source)
 at java.base/java.util.concurrent.ThreadPoolExecutor$Worker.run(Unknown Source)  at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:63)  at
java.base/java.lang.Thread.run(Unknown Source) Caused by: java.lang.OutOfMemoryError: Java
heap space
```

With read-only access, you cannot extract an image from an ESX host

In the vSphere Client, if you hold only read-only access on an ESX host, you cannot extract the current image on the host to create a new image in the **Image** step of the **Add Host** wizard. If you try to extract a new image and select the **Extract the image on the host** option, click **Next**, and accept either the host certificate or thumbprint, you see the error **Image not available**, and the **Extract Image** button instead of the expected host image information.

Networking Issues

The DirectPathProfile (DPP) identifier for a DirectPath device differs across power cycles of a virtual machine configured with the device

Three properties are considered to determine the DPP identifier for a DirectPath device with `DynamicBackingInfo`: `device name`, `allowed devices list`, and `assignedId`. The `device name` and `allowed devices list` properties persist over power cycles of a VM, but the `assignedId` is generated dynamically during the VM power-on. As a result, you cannot use the spec from a DPP in the config spec of a different VM, because the `assignedId` differs upon restart and the DPP computed for the other VM does not match the original, even if all other properties are the same. This issue affects only accelerator devices using `DynamicBackingInfo`. It does not affect vGPU devices, vendor device groups, or DVX devices.

vSphere Lifecycle Manager Issues

Creating a vSphere Lifecycle Manager image might fail even when the corresponding depots are imported

In rare cases, when multiple offline and online depots are imported into the vSphere Lifecycle Manager, the metadata of one depot might overwrite the metadata of a previously imported depot and effectively remove the older depot. As a result, when you try to create a desired image based on the deleted depot, during draft validation, the task fails. In the logs, you see an error that depends on the depot that is missing, for example: `Software Solution com.vmware.vsphere-wcp with version 9.0.1.31.6.0-24913416 cannot be found in depot`. This issue is more likely to occur in VCF environments where the depots imported in the vSphere Lifecycle Manager come from multiple sources.

vSAN

This document contains the following sections

- vSAN

vSAN

vSAN host crash (PSOD) caused by malformed network packets

Previously, in some enviroments vSAN hosts could crash with a Purple Screen of Death (PSOD) when receiving malformed or corrupt network packets. The crash occurred in the vSAN Cluster Monitoring, Membership, and Directory Service (CMMDS) layer, which is responsible for maintaining cluster state and membership across all hosts in a vSAN cluster.

This has been fixed. vSAN has enhanced the verification of vSAN CMMDS traffic by doing full-payload checksum verification. This ensures the integrity CMMDS traffic by detecting data corruption or tampering during transmission, which improves resiliency amd avoids potential PSOD situations.

VCF Installer

This document contains the following sections

- VCF Installer resolved issues

VCF Installer resolved issues

After upgrading the SDDC Manager appliance from 5.2.2 to 9.0.2, you see a 502 gateway error

The Plan Upgrade wizard displays the NSX appliance build number, rather than the NSX component build number

The Plan Upgrade UI displays the NSX Manager appliance build in the **Current Build** or the **Target Build** cells instead of the NSX component build number. The displayed build number can then differ before and after the upgrade. This is a cosmetic issue only, it does not affect the upgrade process.

During deployment in an air-gapped environment, SDDC Manager cannot download the VMware Cloud Foundation compatibility file

In an environment without connectivity to the Internet, SDDC Manager cannot download the compatibility file from `vvs.broadcom.com`. As a result, during the deployment process, the following error appears.

```
An error occurred when validating VMware Cloud Foundation compatibility: File with Compatibility Matrix
 Content for Compatibility controller VMWARE_COMPAT is not found. Please refer to error message above and
 contact support for more details.
```

Pre-checks and validations take longer than expected when running VCF Installer and SDDC Manager workflows in large environments

In VCF 9.0.1, cluster pre-checks perform additional lookups per ESX host through vCenter. In large environments, the cluster pre-checks scale per host, which may add significant time for an operation to complete. Affected workflows are add/remove ESX host from cluster, stretch cluster, add / expand / shrink / remove NSX Edge cluster, upgrade readiness pre-check, converge and synchronize existing virtual infrastructure, and import an existing vCenter.

If ESX hosts are unreachable during a decommission operation, SDDC Manager does not release VMKNIC IP addresses to the associated network pool

During a host decommission workflow, if the associated ESXi hosts are not reachable during the VMKNIC clean-up phase, SDDC Manager does not fail the workflow and removes the ESX hosts from the inventory. The VMKNIC IP addresses associated with the ESX hosts are not returned to the free list in the network pool.

VCF Operations does not display available vSphere Lifecycle Manager images when importing an image from a vCenter

After you create a vSphere Lifecycle Manager image in vCenter and you attempt to import the image in VCF Operations, the **Import Image** dialog box does not display the existing image. This happens because SDDC Manager cannot retrieve the vCenter image repository.

Validation fails with the following error message: **`The uplinks [uplink2, uplink1] used in the NSX teaming specification are not part of the uplinks defined [<uplink2-custom>, <uplink1-custom>] in the input specification for the Distributed Virtual Switch <vds-name>`**

If you edit the uplink names when configuring the vSphere Distributed Switch, those custom names are not applied to the NSX traffic settings, leading to the validation error.

VCF Operations appliance deployment fails if the password contains "?"

When you deploy a new VCF fleet and specify a password containing a "?" for the VCF Operations appliance or the VCF Operations collector appliance, the VCF Installer validation does not report an issue, but the deployment fails.

Retrying a failed deployment fails

When you deploy the VCF Installer appliance on one of the ESX hosts that will be used for the management domain and the deployment of a new VCF fleet or VCF Instance fails, retrying the deployment may fail if you are using vSAN storage. This issue occurs because the VCF Installer does not clean up the vSAN datastore that gets created on the ESX host during the initial failed deployment. The domain manager log files will contain an error similar to `The cache disk/s [<vsan-disk-id>] is/are in an invalid state.`.

Required hosts information for a vSAN OSA datastore does not reflect the deployment model

When you deploy a new VCF fleet or a new VCF Instance and choose vSAN OSA storage, the "Required hosts" information displayed in the deployment wizard may be misleading if you chose the high availability deployment model. For example, if you specify "1" for the "Failures to Tolerate" (FTT), the deployment wizard says that three ESX hosts are required, when high availability requires a minimum of four ESX hosts.

VMware Cloud Foundation deployment fails if the SDDC Manager FQDN includes uppercase letters

Deploying a new VCF fleet or VCF Instance fails when deploying SDDC Manager if the SDDC Manager FQDN includes uppercase letters. The logs show an error related to `CS_APPLIANCE_CERT_ALIAS_LOWERCASE`.

VCF Installer deployment fails when configuring the vSphere cluster

When you deploy VMware Cloud Foundation or VMware vSphere Foundation using the VCF Installer, the deployment can fail if you specify IP segments that are already in use by other components.

Validation fails in the VCF Installer if any of the vSphere Distributed Switch names include a space or special character

If you include a space or special character in the name of any vSphere Distributed Switch (vDS), deployment fails at **vSAN Network Connectivity** and the error message `A problem has occurred on the server. Please retry or contact the service provider and provide the reference token.` is displayed.

The VCF Installer UI validations incorrectly allow duplicate FQDN inputs that differ only by letter case

The UI validation for FQDNs incorrectly treats certain entries as unique. For example, Example.com and example.com are considered distinct. The final validation, which uses the validation API, correctly identifies the FQDNs as duplicates, but the user must go back and and manually fix the issue.

When you deploy VCF Operations with High Availability, anti-affinity rule is not configured

The anti-affinity rule ensures that all virtual machines associated with it are placed on separate hosts at all times, ensuring high availability of the VCF Operations cluster. Without the anti-affinity rule, the VCF Operations nodes could end up on a single host, which could lead to all VCF Operations nodes going down if that host fails.

VCF Installer displays incorrect evaluation period

When you deploy a new VCF fleet and you select the option to configure custom networking for VCF Operations and VCF Automation, the VCF Installer reports that you must apply a VCF license within the 60-day evaluation period. The actual evaluation period is 90 days.

VCF Installer validation error `vCenter Server root password must be at least 15 characters`

When you use the VCF Installer to deploy a VCF instance or VCF Fleet using an existing vCenter, you will get a validation error if the vCenter root password is too short. This can happen if the vCenter was upgraded to 9.0 from a previous version that accepted shorter passwords.

Deploying a new VCF fleet or VCF Instance with an existing vCenter and a new NSX Manager fails

If the existing vCenter has a large number of hosts or clusters, the import task may fail during NSX transport node creation. The domain manager log shows the following error message: `exceeded request rate of 100 per second`.

VCF Installer does not support IPv4/IPv6 dual-stack networking

Validation fails in the VCF Installer if you have dual-stack networking configured on your ESX hosts.

NSX

This document contains the following sections

- Resolved Issues

Resolved Issues

Route Advertisement Rules containing overlapping subnets are not working as expected.

Order of route advertisement rules is not maintained.

NSX Edge logs spammed with log: Query to /var/run/vmware/edge/dpd.ctl failed with lrouter with the UUID or vrfid does not exist.

Edge log errors triggering alarms in custom vRNI monitoring. There is no functionality impact.

VRF remains in the 'InProgress' state during deletion.

VRF deletion is hanging indefinitely in the customer's UI.

Bare Metal edges with over 4 NICs run out of memory.

Bare Metal edges run out of memory.

Stale ComputeManager ID references in internal tables might prevent realization of subnets folders/DVPGs.

DVPG may not get created/updated for certain subnets due to NullPointerException on accessing the stale ComputeManagerId reference.

Unable to delete Segments from the UI.

Customer is not able to delete these segments. These segments remain as stale and displayed under the listing of segments.

Log-ins to NSX Manager are intermittently failing with the following error: Failed to use SAMAccountName, attempting UserPrincipleName: Invalid credentials.

Unable to log in to NSX Manager.

Post upgrade, proton startup is taking a very long time. The upgrade is unable to progress and fails.

NSX manager upgrade failed on start_manager. Proton startup during an upgrade takes a very long time.

The API to get the cluster certificate is not returning the right certificate.

Compute Manager fails to create its connection with vCenter because it has the wrong cluster certificate.

Rare BGP flaps when the TCP source port is reused for the same source and destination IPs on another VRF.

Unexpected flap for correctly configured BGP session.

After PUB upload, the stage operation fails with NullPointerException.

No impact. Users can stage the upgrade bits post MUB upload and UC upgrade.

Not all vNIC might receive multicast traffic even if the multicast address and ICMP SNOOP are enabled.

Applications that depend on multicast functionality might break.

VMs intermittently lose their IP addresses from NSX security group membership that causes firewall rules to temporarily stop applying to affected VMs.

VMs experience intermittent network connectivity loss when their IP address is temporarily removed from NSX Group effective members. Distributed Firewall rules that rely on dynamic group membership may stop matching the affected VM's traffic during these periods. The issue is intermittent and can affect multiple VMs in production environments.

After replacing the vCenter root CA certificate with a certificate that lacks a Common Name (CN), the "Update Compute Manager" operation fails because NSX cannot properly identify the root certificate without the CN field.

Compute Manager connectivity remains down, preventing NSX from managing vCenter resources.

Stats for vusb0 interface is throwing an error.

If an ESX node has vusb0 interface, vROP and VRNI are reporting issues with vusb0 stats interface API that cannot be resolved.

Intents are not going through realization. The realization status gets stuck in IN_PROGRESS when customers try to create/update/delete tier-1.

None of the network services work.

During host transport nodes upgrade in a scale setup, multiple VMs can face connectivity issues.

For more information, see KB article 413006.

NSX firewall rule drops packets.

Logical-port IP is not realized and it is not present as an effective member in the NSGroup that is being used by the impacted firewall rule. As a result, the impacted firewall rule drops packets.

When a NAT Rule is deleted by Policy Provider from Corfu during an upgrade because of the data migration, an issue with CCP's UFO full sync might occur and CCP might not propagate this NAT Rule deletion to the data plane.

The stale NAT Rule in the data plane cannot be changed or interacted with. As a result, customers are not able to change the behavior.

Stateless cache enabled ESX host profile does not create a log directory under /scratch.

A host that auto-deploys with the stateless cache enabled host profile causes /var (ramdisk) to be full.

User observes a false alarm.

User observes a false alarm, remote_logging_server_error, and the false alarm keeps going on and off even if logs can be redirected to the remote logging-server as expected.

SNMP service crashed in edge node and generated core dump file in some race condition.

SNMP created a core dump and stops working when it loads TCP endpoints for v4 and v6 from the kernel.

Enlarged capacity or updated expiry VCF license with that same allocationId as the previously applied VCF license fails to sync with NSX.

Changes, such as expiry date and license capacity, in the vCenter's VCF license do not get reflected in the connected NSX.

Load balancer status is shown incorrect.

When a load balancer instance is enabled -> disabled -> detached -> attached again, then the status of the load balancer instance is shown as unknown.

Failure to configure the application profile of a load balancer.

If a tier-1 with an attached load balancer has no tier-0 and no tier-1 interface, the application profile of the load balancer cannot be configured.

After an upgrade, the perf configuration of the load balancer is lost.

The performance of the load balancer degrades after an upgrade.

Load balancer (LB) configuration cannot be loaded into LB nginx as char "" is configured in the request header body of the LB HTTP monitor.

The new LB configuration cannot be loaded. After the LB docker restarts with this configuration, LB cannot work and the LB status is unkown.

High disk usage occurs in/var/log partition of edge node.

This issue is caused by the failed rotation of load balancer debug files. As a result, many of these .tar.gz debug files persist in the /var/log partition.

NSX Manager reports incorrect load balancer (LB) status.

NSX Manager reports that the load balancer virtual service is down, even though the virtual service is capable of handling traffic. The issue is observed when multiple monitors are configured in the same LB pool.

Users can delete default load-balancing persistence profiles through the API.

In case the default LB persistence profile is deleted, users would have to manually create custom LB persistence profiles.

Nginx process can crash on NSX Edge when using L7 drop rule in load balancer configuration.

This issue is caused by an nginx coredump that occurs when using the drop rule in an L7 virtual server of the load balancer, resulting in L7 traffic disruption.

The nginx coredump is found after the source IP persistence feature of the Load Balancer (LB) is deactivated.

The LB traffic is impacted.

NSX Load Balancer status is marked as unknown because the UDP monitor is not configured correctly and LB is not running properly on the edge.

If the LB is configured with the incorrect UDP monitor in the beginning, the LB on edge cannot provide service and the LB status is unknown.

If the LB is configured properly in the beginning and the incorrect LB monitor is configured later, the reconfiguration cannot take effect anymore.

VCF Operations

This document contains the following sections

- Security Fixes
- Build
  - Lifecycle
- Operate
  - VCF Health
  - Log Management
  - Network Operations
  - Integrations
  - Inventory
  - Application Monitoring

  - Cost
  - Reports and Views
  - Metrics
  - Others
- Manage
  - Fleet Management
  - VCF Operations orchestrator

Security Fixes

- This release resolves CVE-2026-41722 and CVE-2026-41723. For more information about these vulnerabilities and their impact on VMware products, please see VMSA-2026-0004.
- For a list of fixed CVEs, see VCF_Ops_9.1_Fixed_CVEs.

Build

Lifecycle

Unable to download logs from VCF Operations

After upgrading the SDDC management stack, generated support bundles do not download using the VCF Operations post-deployment "Download Support Bundle" action.

Resource API calls are returning `resourceHealth=GREY` and `resourceHealthValue=-1`

The API call to GET resources by relationship type returns mismatched `resourceHealth` and `resourceHealthValue` field values. This mismatch impacts the VMware Aria Operations health monitoring value in VMware Aria Suite Lifecycle.

Operate

VCF Health

In VCF Health metrics, you see vCenter Archive Disk usage flagged as Critical, even though it is designed to operate above the 85% utilization threshold

By design, the **vCenter Archive Disk** metric keeps an utilization rate above 85%, which is the threshold for **Critical** status in **VCF Health**. As a result, in **VCF Health** you often see the **vCenter Archive Disk** metric above the **Critical** threshold, which is a false positive.

In VCF 9.1, the **vCenter Archive Disk** metric is removed from the count of **Critical** issues.

Log Management

The Log Analysis widget in public shared dashboards fails to load and displays a "Cannot retrieve logs" error.

When accessing a public shared dashboard, the Log Analysis widget may fail to display data and instead show a **Cannot retrieve logs** error message. This issue prevented users from viewing critical log metrics in shared environments.

Inaccurate status messages are displayed in the Log Data migration UI when a migration fails due to insufficient storage space.

When a log data migration fails because the destination nodes have reached storage capacity, specifically within the `/storage/core` partition, the user interface incorrectly displays the task as both "Completed" and "Pending 0%."

Configuring Log Forwarding using the Raw Protocol prevents the Preview and Create functions from operating.

When configuring Log Forwarding in the VCF Operations UI, selecting the **Raw Protocol** forwarding method caused the **Preview** and **Create** functionalities to become unresponsive. This issue occurred specifically when switching the input type from Syslog to Raw, preventing the successful establishment of new log forwarding destinations.

Network Operations

NSX-T latency metric profiles (BFD, Transport Zone, and Latency) accumulate redundant and duplicate entries in the collector database and in NSX-T due to DIDs/UUIDs appended to profile IDs.

The profile generation logic for NSX-T latency metrics appends unique system identifiers (DIDs/UUIDs) to profile IDs, causing the system to generate a high volume of redundant and superfluous profiles. This behavior increases internal state management overhead and degrades overall system efficiency over time. Database clutter accumulates as duplicate profile entries persist without resolution.

The NSX health widget incorrectly displays "no data available" on the Network Operations page

When navigating to the Network Operations page, the NSX health widget may display a `no data available` message. However, the underlying data is still being collected and is accessible. Clicking **View Details** under the widget successfully opens the detailed view displaying all expected metrics.

Custom-named VCF Operations for networks instances do not automatically update to the default "VCF OPS NI" name after upgrading to version 9.x.

Previously, if a VCF Operations for networks adapter was configured with a custom name in a pre-9.0 release, the custom name persisted after upgrading to version 9.x. The upgrade process has been corrected to automatically rename any existing VCF Operations for networks instances to the default "VCF OPS NI" name for consistency across the managed infrastructure.

The NSX health widget incorrectly displays "no data available" on the Network Operations page

While navigating to the Network Operations page, the **NSX health** widget may show a 'no data available' message. However, the underlying data is still being collected and is accessible; clicking "view details" under the widget successfully opens the detailed view displaying all expected metrics.

Integrations

Auto-discovery for VCF components may fail if a new CA certificate relevant to the VCF endpoint, is manually imported into VCF Operations

CA certificates imported via the VCF Operations Control Panel's Trusted Certificates section are not being sent to the VCF adapter. This can potentially cause new service accounts creation to fail for VCF instance sub-components.

Data-grid filters for vMotion reporting incorrectly display options derived from all vCenter instances rather than the specifically selected instance

In VCF 9.0, vMotion reporting is scoped to a specific vCenter instance within a VCF instance. While the data-grid correctly renders vMotion events for the selected vCenter instance, the associated filter options are incorrectly constructed using vMotion data from all vCenter instances across the fleet. This issue is fixed in VCF 9.1.

Inconsistent formatting of Knowledge Base (KB) article links within vCenter Management Pack recommendations.

Previously, references to Knowledge Base (KB) articles in the vCenter Management Pack recommendations displayed varying text formats. This issue has been resolved. All KB article references have now been standardized to follow a uniform format (for example, "See Broadcom KB 1000258").

The "Account Monitoring Notification" message updated with instructions on starting data collection.

The "Account Monitoring Notification" dialog box only stated that data collection does not start automatically. The message text has been updated to provide administrators with explicit instructions on how to manually start data collection.

Data collection for the VMware Infrastructure Health adapter may require multiple cycles (3–4) in large scale environments

The data collection process for the VMware Infrastructure Health adapter was delayed when ESX hosts in the vCenter environment became unresponsive or disconnected.

vCenter pricing in VCF Operations does not allow you to add a new tag if it uses an existing tag category as an existing tag with a new tag value, resulting in an error that prevents configuration completion

vCenter pricing enforces a unique tag category in the user interface for **Recurring**, **One-time**, and **Rate factor** tags, which prevents defining multiple distinct tag values under the same category. Administrators who need several values within one category for differentiated pricing cannot complete that model through vCenter pricing in the VCF Operations UI.

The vSAN Cloud account status remains in a "Stopped" state after configuring a VMware Cloud Foundation (VCF) Cloud account.

When configuring accounts in a specific sequence, the vSAN account may fail to initialize data collection automatically. This issue occurs when an administrator first creates a vCenter account using a vCenter instance from a VCF domain, starts data collection, and subsequently creates a VCF account with the "Enable Domain Monitoring on Creation" setting configured to "True". As a result of this sequence, while all VCF domains are successfully configured and started, the associated vSAN account defaults to a "Stopped" state, preventing immediate data collection and monitoring of the storage layer.

ESX Virtual Machine Network Interface Card (VMNIC) status was not accurately reflected in VCF Operations.

In certain cases, when a Virtual Machine Network Interface Card (VMNIC) went down, VCF Operations did not update its status accordingly and continued to display stale data. This resulted in an incorrect representation of the VMNIC state compared to vCenter. Due to this inconsistency, users were not able to reliably determine the actual VMNIC status, impacting monitoring and day-2 operations.

The actions from VCF Operations to vCenter fail to execute

This issue occurs because Distributed Resource Scheduler (DRS) tasks are not currently whitelisted during the collector's initialization phase. While the controller successfully starts adapter instances, the subsequent DRS configuration tasks are blocked, preventing the necessary communication between VCF Operations and vCenter. Whitelisting the DRS task ensures that adapter instances are correctly synchronized and operational during the startup sequence.

Administrators are subsequently unable to rename the vCenter adapter instance within the VCF adapter hierarchy.

Upon configuring the VCF adapter in VCF Operations, existing vCenter, vSAN, and NSX adapters automatically nest within the VCF adapter hierarchy. Following this integration, administrators are unable to rename the vCenter adapter.

Users are unable to edit or change the configuration of a VMware Cloud Foundation (VCF) cloud account when it is in a stopped state.

When a VCF cloud account is in a stopped state, configuration edits fails and returns the message "SDDC configuration is not available as adapter instance is not ready." This blocks administrative tasks such as vCenter Server license management, unless data collection is active, forcing users to start data collection, manage the integration, and then stop it again. This issue is resolved. Administrators can now modify VCF cloud account configurations in a stopped state, ensuring consistent operational behavior across all cloud account types.

Inventory

The error dialog box that opens when you use the Actions drop-down in the VCF Operations inventory UI uses an incorrect graphic and inconsistent style

If you encounter an error when using a functionality from the **Actions** drop-down menu in the VCF Operations inventory UI on both the VCF Instance and the VCF domain levels, the error message dialog box displays a graphic and is inconsistent with the remaining VCF Operations UI error messages.

Application Monitoring

After upgrading VMware Tools to 13.0.5 version, the Service Discovery adapter may stop collecting data

After upgrading VM Tools to version 13.0.5, you may encounter an issue where the credential-less mode fails to collect data from VMs.

Cost

Links in the Cost Optimization dashboard redirect incorrectly.

The link to the VCF Operations Forrester Total Economic Impact (TEI) documentation has been updated in the Cost Optimization dashboard in VCF Operations.

Administrators are unable to match the inventory count of virtual machines to the "Windows Server 2016 or later" license item within the License Cost Driver.

When an administrator lists virtual machines by Guest OS to determine the total count of systems running Windows Server 2016 or later, the resulting inventory count does not match the total displayed for the "Windows Server 2016 or later" license item in the License Cost Driver. Virtual machines running the Windows Server 2022 Guest OS are incorrectly categorized and counted under the "Other OS" classification during cost calculations. This discrepancy prevents accurate license cost attribution and reconciliation for newer Windows Server operating systems.

The Power and Cooling monthly cost calculated within the Facilities cost driver lacks accuracy because it relies on a fixed reference value for host energy consumption rather than actual utilization metrics.

There is an hourly energy consumption metric coming from vCenter adapter. It can be utilized for cost calculations. Currently a fixed monthly energy consumption is utilized for hosts. Using the actual host energy consumption will be more accurate for calculating cost.

Multiple Additional Cost configurations applied to the same Entity Selection object yield an incorrect "Monthly Additional Cost" host metric.

When multiple Additional Cost configurations are assigned to the same Entity Selection object (vCenter/ Datacenter/ Cluster Compute Resource/ Host System), the system incorrectly selects a single configuration to calculate the "Monthly Additional Cost" host metric. To ensure accurate financial modeling and cost calculation, the system must aggregate all applicable configurations assigned to the object rather than applying only one.

Reports and Views

The Report Templates page contains an obsolete 'Change report font' menu option

The report font customization feature has been deprecated and dropped from the product. However, the menu on the Report Templates page still displays this option.

The Virtual Machine Utilization Summary view displays an incorrect number of vCPUs

In the out-of-the-box **Virtual Machine Utilization Summary** view, the vCPU count might not match the actual number of vCPUs assigned to the virtual machine in vCenter. This occurs because the view incorrectly uses the "`Configuration|Hardware|Number of virtual sockets` property instead of the `Configuration|Hardware|Number of virtual CPUs` property to calculate the value.

Report generation stops working with new reports remaining stuck in the "In queue" status

During report generation, the system may encounter timeouts while attempting to load and render certain report pages. When this occurs, an issue in handling these timeouts causes the internal report generation service to become permanently blocked. Consequently, all subsequent report requests are unable to process, remaining stuck in the "In queue" status and eventually failing.

Metrics

VCF Operations UI displays deprecated metrics from older releases, metric from End of Life products (such as VMware Configuration Manager), and inaccurate network metrics.

In previous releases, VCF Operations retained certain metrics from End of Life products, like VMware Configuration Manager (VCM), as well as some legacy network metrics. To ensure accurate system monitoring and prevent misleading data, VCF Operations has now permanently deleted the obsolete metrics. Additionally, specific legacy network metrics have been officially marked as deprecated and will be completely removed in a future release.

Others

Tenant-scoped alerts are missing from the triggered alerts list when no filters are applied.

When viewing the triggered alerts list without any active filters, alerts scoped specifically for tenants fail to appear in the default view. To see these alerts, users were previously required to manually set the "For Tenants" filter field to "Yes." The alert filtering mechanism has been updated to ensure tenant-scoped alerts are included in the comprehensive triggered alerts list by default.

Fixed broken URLs in the VCF Operations UI.

Navigation from the Metrics tab to the Summary tab after selecting an object from Global Search

A user is on the **Metrics** tab of the **Inventory** page viewing a specific object and one or more metrics have been added to the metric chart area on the right of the page for this particular object. When the user opens **Global Search**, selects the **Object** category, and selects another object from the suggestions, the user is shown the **Summary** tab of the new object, when they were expecting to remain on the **Metrics** tab so they could add more metrics to the chart area.

The Custom Groups page displays "No Results Found" after a group deletion.

After deleting a custom group, the Custom Groups page incorrectly displays "No Results Found" even if other groups exist. Refreshing the browser resolves the issue and displays the remaining custom groups.

The browser's back button navigation does not work correctly after viewing generated reports

While navigating to the Report Templates page under Dashboards & Reports and clicking on a "Generated reports" link, subsequent use of the browser's back button fails to function as expected. Users may experience incorrect navigation behavior and be unable to return to their previous screens using the browser's built-in back controls.

Inability to navigate to the Custom Groups page directly from the "Push Categories to vCenter Instances" dialog box when existing groups are present

The link to create or manage Custom Groups was only visible within the "Push Categories" workflow when no groups had been defined. This required users to manually exit the Push Categories dialog box and navigate through the main panel to reach the Custom Groups page. A permanent "Add Custom Group" link, has been added to ensure a seamless navigation path regardless of whether existing groups are displayed.

The link configured in the Scoreboard widget opens in a new window

The link configured in the Scoreboard widget opens in a new window instead of navigating within the existing page.

The term 'Sustainability' has been updated to 'Green Score' across the product interface

To align with updated terminology guidelines, all references to **Sustainability** in the user interface have been replaced with **Green Score**. This includes updates to menu items and metric grouping names. This is a terminology update only and does not impact the underlying functionality or calculation of the metrics.

In large-scale VCF Operations instances, the "Appliances Health & Management" section on the VCF Overview page takes longer than expected to load.

When navigating to the **Operate> Home> VCF Overview** page in large-scale environments with more than 4,000 ESX hosts, there might be a delay of over a minute while the widgets in the "Appliances Health & Management" section load. This delay is caused by the time required to calculate and retrieve health and configuration data for the connected multi-cloud appliances. With this fix, the load time for these widgets has been reduced to less than 10 seconds.

In the metric chart, the 'Anomalies' option displays all active symptoms for the selected object, rather than filtering them by the specific metric key

In VCF Operations, when viewing a metric chart, the 'Anomalies' overlay incorrectly displayed all active symptoms for the selected object instead of filtering them by the chosen metric.

Manage

Fleet Management

Adding LDAP/AD users or groups in identity broker (group or user provisioning) fails; the UI displays the following error: `Over 1000 group/user DNs are available`. Search can hang or display an error when the directory under the base DN is very large, for example, over 1000 matching groups or users

With a large LDAP/AD tree, default substring search can return too many matches and hit the 1000-result limit, causing lookup to fail. The backend now supports an optional prefix search: type `^` only as the first character (for example, `^finance`) for a narrower, indexed-style match. How quickly results return still depends on your LDAP directory and its configuration, but prefix search usually returns a smaller, more focused set of matches than a broad substring search.

Configuration Template validation fails with a missing property error when only a subset of nested options is selected.

Within the Fleet Management > Configuration Management > Create Configuration Template workflow, administrators can select a subset of nested configuration keys using the UI checkboxes. However, back-end validation enforces certain child

properties as mandatory once a parent branch is selected (for example, requiring min_length under a password policy). This mismatch between the UI presentation of optional fields and the strict validation requirements causes template validation to fail, preventing the successful creation of the configuration template.

When attempting to use a functionality not available in VCF versions older than 9.0 in VCF Operations 9.0 UI, the view that opens does not provide a link to the relevant documentation.

When attempting to use a functionality not available in VCF versions older than 9.0 in VCF Operations 9.0 UI, such as Certificates, Passwords, Configuration Drifts, Lifecycle, and Tasks under **Fleet Management**, the view that opens does not provide a link to the relevant documentation.

User accounts with usernames that contain the exclamation mark character (!) are unable to authenticate or be provisioned when using Microsoft Entra ID for Single Sign-On (SSO) with vCenter or VCF 9.0

Authentication failures occur because the identity broker utilizes a strict validation pattern for SCIM user provisioning that does not include the exclamation mark as a permitted symbol. This issue prevents users with the exclamation mark character (!) from successfully logging into vCenter via Entra ID federation.

With Photon FIPS mode enabled, replacing the VCF Operations certificate with a certificate that is missing the serverAuth attribute in its Extended Key Usage (EKU) causes the UI to become unresponsive

When replacing the VCF Operations certificate, the validation workflow does not check whether the `serverAuth` attribute is available in the new certificate's Extended Key Usage (EKU). With FIPS mode enabled on the appliance, the cryptographic library explicitly requires that any certificate used for a server acting as a TLS endpoint must contain the `serverAuth` value in its EKU. As a result, applying this invalid certificate causes the VCF Operations UI to become unresponsive.

Show ESX Hosts toggle switch may not be visible depending on screen size

The **Show ESX Hosts** toggle switch in the VCF Operations certificate management UI is not floating and, depending on the screen size, may not be visible.

The management vCenter name appears with the prefix vRSLCM_VCF_VC Adapter Instance instead of a clear, human-readable name in vCenter Linking.

After upgrading VCF Operations, the vCenter Linking UI labels the management vCenter using an internal adapter instance name, making it hard to recognize. This display issue is isolated to the vCenter Linking workflow and does not impact underlying product functionality or vCenter operations beyond how the instance is identified in that specific view.

VCF Operations UI shows incorrect password expiration for VCF fleet level component accounts

VCF Operations UI does not show the correct password expiration for VCF fleet level component accounts, even when there is a set password expiry.

VCF Operations orchestrator

Readiness probe failure for services

Node-level issues can cause periodic unresponsiveness that triggers Apache Ignite cluster failures across all Ignite-based services on that node.

VCF Operations orchestrator restarts due to OutOfMemory errors

In some cases with relatively large vSphere environments, VCF Operations orchestrator stops working due to an `OutOfMemory` error. When logs are set to debug mode, you see error messages like `com.vmware.o11n.plugin.vsphere.pc.CacheUpdate - Update received with version: 0.1`. For more information, see Broadcom knowledge base article KB 432637.

Scheduled workflow runs fail to start when authenticated with vSphere SSO

Scheduled workflow runs fail with an error `Unable to convert token with id ##############################` visible in the logs. This issue is observed when VCF Operations orchestrator is configured with vSphere SSO as an authentication provider. For more information, see Broadcom knowledge base article 418596.

Issues with environments as part of a package

This release introduces fixes to various issues with environments as part of a package.

Carriage return character is replaced when passed as a workflow input through the API

When running a workflow using a script and passing the `"\r"` character as part of a string input, the character is then replaced to `"\n"` in the actual workflow run.

Workfow runs fail when using JSON.stringify()

When using `JSON.stringify()` on objects that are not Javascript-defined, the workflow run fails.

Refresh token values not applied if VCF Automation or VCF SSO are used for authentication

If an external VCF Operations orchestrator instance is authenticated with either VCF Automation or VCF SSO, the values set for the refresh token are not applied as configured. For example, you can configure a token duration for 300 seconds and then continue to use VCF Operations orchestrator even after this limit is exceeded.

VCF Operations orchestrator not detecting usage or dependencies for workflows or actions

The usage and dependency detection sometimes misses references to VCF Operations orchestrator workflows or actions in scripts in case of multi-line references.

V**CF Operations orchestrator page content is not updated after switching between VCF Operations orchestrator instances**

After switching between VCF Operations orchestrator instances, page content is not updated, unless you refresh your browser.

The VCF Operations orchestrator workflow run is interrupted when the VCF Automation browser session expires.

When performing workflow runs in the embedded VCF Operations orchestrator instance in VCF Automation, expiration of the browser session stops the workflow run. As a result, the workflow run usually fails with an access denied error.

The VCF Operations orchestrator API allows you to create configuration elements with same attribute name multiple times

Updating a configuration element with the **PUT /configurations/{id}** operation allows you to set multiple attributes with the same name. Performing the same action in the UI is not possible.

The Create a Supervisor Namespace example workflow fails

The example workflow **Create a Supervisor Namespace** fails even if the namespace is created successfully. This is caused by the missing `infrastructure.cci.vmware.com/id` annotation.

Error with the display prompt for external VCF Operations orchestrator certificate

When an external VCF Operations orchestrator with a self-signed certificate is added to a VCF Automation organization and the user goes to the **Orchestrate** tab, the VCF Operations orchestrator UI is not loaded and a spinner is shown until it times out. This is caused by the certificate not being accepted by the browser. The user still has to accept the certificate, but the message is fixed.

Bad request when deleting configuration properties in VCF Operations orchestrator

After deleting properties from System Settings -> Configuration Properties, you receive an "A problem occurred while saving properties. ..." error. The selected properties are still deleted from the server.

VCF Automation

This document contains the following sections

- Provider Management
- Organization Management
- Upgrade

Provider Management

When an organization is disabled, all currently logged-in users retain their sessions for up to 5 minutes

Because of the system's in-memory caching, the existing user sessions are not immediately stopped when an organization is deactivated. The sessions might be active for up to five minutes after the fact. After this time elapses, users see an error message "`Server Error: Error: 401 - OK`" or "`401 UNAUTHORIZED`".

Cannot create or delete organization in VCF Automation Provider Management

There are two scenarios for this issue. The first is a scenario where the organization creation process does not complete and the creation task is left in the running state. This scenario can happen in a situation the organization creation or deletion process is started in the VCF Automation Provider Management Portal when the Event Broker service is down or being restarted.

In the second scenario the organization creation or deletion process is marked as failed. This is cause by the Event Broker service failing to trigger the events associated with the creation or deletion of a organization. In such as case, you receive an error message similar to `Org creation/deletion task failed. Event processing failed with error :.`

Organization Management

The Utilization metrics UI breaks or hides critical controls when the underlying API returns a 400 Bad Request error{}

When attempting to view utilization metrics, a failure in the metrics API prevents users from switching between the **Project** and **Namespace** pages in the VCF Automation organization UI and can cause the entire interface to crash or malfunction. This happens when the API fails to return data, resulting in a lack of graceful error handling and the loss of visible organizational statistics.

Kubernetes JSON objects exposing the `Status` field

Using Kubernetes JSON objects exposes the `Status` field which might cause security issues. This issue is mitigated by replacing the Kubernetes custom object with a separate JSON object that does not expose the `Status` field.

VCF Automation experiences outage caused by a PostgreSQL issue

This issue is caused by the S3 WAL object store not having enough space to store 24 hours worth of WAL files. To resolve this issue, the storage size is now increased.

Installing a VKS package fails because of duplicate package name

Installing a VKS package to a cluster fails, if the package name is not unique for the Supervisor Namespace. For example, if you want to install a package called `cert-manager` on a VKS cluster that resides in Supervisor Namespace `ns01`, but another cluster that resides in that same Supervisor namespace has an installed add-on called identically, `cert-manager`, the installation fails with an error.

This issue is resolved in this release.

Upgrade

VCF SDKs, APIs, and CLIs

This document contains the following sections

- VMware Cloud Foundation PowerCLI

VMware Cloud Foundation PowerCLI

In VCF PowerCLI 9.0 and earlier, Get-VDPort does not display vDS information correctly

In environments with multiple vSphere Distributed Switches (vDS), when querying multiple Distributed Switches simultaneously using the `-VDSwitch` parameter of the `Get-VDPort` cmdlet, the cmdlet fails to return the complete list of ports or displayed incorrect uplink information.

If you use VCF PowerCLI 9.0 and earlier, upgrade to VCF PowerCLI 9.1.

If you are using an affected version of PowerCLI, you can avoid this issue by querying each Distributed Switch individually and joining the results.

Instead of running: `Get-VDPort -VDSwitch VDS-A, VDS-B -Uplink`, use a `foreach` loop to process each switch independently:

```
$mySwitches = Get-VDSwitch -Name "MS01-vmkernel01-vds", "MS01-nsxm01-cvds"
$allPorts = foreach ($vds in $mySwitches) {
    Get-VDPort -VDSwitch $vds -Uplink
}
$allPorts | Format-Table -AutoSize
```

Alternatively, you can join the results manually:

```
(Get-VDPort -VDSwitch SwitchA -Uplink) + (Get-VDPort -VDSwitch SwitchB -Uplink) | ft -a
```

When creating a new cluster using the parameter `RemovedComponent` and passing the component display name, the operation may fail with invalid image error.

In VCF PowerCLI 9.0, using the `-RemovedComponent` parameter with `New-Cluster` or `Set-Cluster` cmdlets may fail with an "*Image is invalid*" error if you pass for the argument the display name of the component instead of the short name of the component.

Upgrade to VCF PowerCLI 9.1.

If you are using an affected version of VCF PowerCLI, you can avoid this issue by passing the short name of the component instead of the display name.

In VCF PowerCLI 9.1, the `New-Cluster` and `Set-Cluster` cmdlets are updated with an on-demand resolution logic. The cmdlets now accept the user-friendly display names for the `-RemovedComponent` parameter and automatically resolve them to the required internal identifiers.

Client side validations are missing for the newly added cmdlet New-VsanIsciVipConfig

VCF PowerCLI 9.0 - vSAN Mesh became broken and critical VMs inaccessible

When using the `-MountRemoteDatastore` parameter to add a new remote datastore, PowerCLI fails to retrieve the existing remote datastore configuration.

In production environments, this can lead to:

- All Paths Down (APD) states on client hosts.
- Virtual Machine inaccessibility for VMs residing on remote mesh storage.
- Broken vSAN Mesh connectivity following automation tasks.

A similar defect exists in the `-UnmountRemoteDatastore` parameter, which may unmount all remote datastores rather than only the one specified.

The issue is fixed in VCF PowerCLI 9.1.

In VCF PowerCLI 9.0 and earlier, to safely mount a remote datastore without losing existing connections, users must manually append the new datastore to the current list in the command.

Usage Example:

```
$clu = Get-Cluster "Client-Cluster"
$config = Get-VsanClusterConfiguration -Cluster $clu
$newDatastore = Get-Datastore "New-Remote-DS"

# Correctly append the new datastore to the existing list
Set-VsanClusterConfiguration -Configuration $config -MountRemoteDatastore ($config.RemoteDatastore +
 $newDatastore)
```

Recommendations:

- Avoid using `-UnmountRemoteDatastore` until a patch is applied, unless the intention is to remove all remote storage.
- Verify the remote datastore list using `Get-VsanClusterConfiguration` immediately after running any mesh-related automation.

In VCF PowerCLI 9.0, attempting to enable vSAN Express Storage Architecture (ESA) on an existing cluster using the Set-Cluster cmdlet may fail with the following error: *Set-Cluster: The operation is not allowed in the current state*.

The issue was introduced due to an interoperability conflict with vSAN Max compatibility logic. While disabling vSAN ESA via `Set-Cluster` remains functional, enabling it on an already established cluster via this specific cmdlet is restricted in the affected version.

If using VCF PowerCLI 9.0 or earlier, you must upgrade to VCF PowerCLI 9.1 to restore full functionality to the `Set-Cluster` cmdlet.

If you still use VCF PowerCLI 9.0 or earlier, select one of the following workarounds:

- Manually enable vSAN ESA through the vSphere Client user interface.
- Enable vSAN ESA during the initial cluster creation using the `New-Cluster` cmdlet:

```
New-Cluster -Name "MyCluster" -Location "DataCenter" -VsanEnabled -VsanEsaEnabled
```

VMware Cloud Foundation 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Getting to 9.1.1

Introduction

Maintenance releases provide bug and security fixes, hardware enablement changes, such as support for servers, CPUs, devices, driver updates, guest OS support, and backward-compatible new features. They are limited in scope to minimize the operational impact. You can pick and choose which components to apply based on the impact on your environment and operational costs. For example, if you run into a critical issue with vCenter, you do not need to apply a patch to ESX that is irrelevant to your environment. Maintenance releases are synchronized among VCF components with a new Bill Of Materials.

VMware Cloud Foundation 9.1.1.0 | 03 SEP 2026 Check for additions and updates to these release notes.

What's New

VCF 9.1.1.0 is a maintenance release that comes with an updated Bill of Materials (BoM). The features it delivers are mostly focused on improving the supportability of the product.

See the list of updates in the release per component:

- vCenter
- ESX
- vSAN
- NSX
- VCF Installer
- VCF Operations
- VCF Automation

Getting to 9.1.1

9.1.1 is a maintenance release of VMware Cloud Foundation 9.1 and vSphere Foundation 9.1 that comes with an updated Bill of Materials (BOM).

You can get to 9.1.1 by following the respective guidance based on the desired operation. You can also use the VCF Upgrade Planning Tool to navigate you during the process of getting to 9.1.1.

Use the latest available binaries for components when you deploy, upgrade, or patch.

Operation	Description
You deploy a new VCF or vSphere Foundation environment at version 9.1.1.	You can use VCF Installer 9.1.1 to deploy a new VCF fleet or instance directly at version 9.1.1. See Deploying a New VCF or vSphere Foundation Platform.
You converge your existing virtual infrastructure to a VCF or a vSphere Foundation deployment at version 9.1.1.	You can converge your existing virtual infrastructure to a VCF or a vSphere Foundation environment directly at version 9.1.1. See Converging Existing Virtual Infrastructure to a VCF or a vSphere Foundation Platform.
You upgrade an existing VCF deployment at version 5.2.x or 9.0.x to version 9.1.1.	If your current version is released before VCF 9.1.1, you can upgrade directly to VCF 9.1.1. You start by first upgrading to VCF Operations 9.1.1. For the full upgrade sequence, see Upgrading Your VCF Management Domain to VMware Cloud Foundation 9.1.
You patch an existing VCF or vSphere Foundation deployment at version 9.1.0.x to version 9.1.1.	If your current version is VCF 9.1.0.x, you can patch to VCF 9.1.1.x. See Lifecycle Management of VCF Components. DO NOT use the Upgrade All button in VCF Operations UI, before you first comply with all of the VCF 9.1.1 specific patching dependencies between VCF components: 1. You begin applying the 9.1.1 maintenance release in your 9.1.0.x environment by patching the VCF management services fleet lifecycle component to 9.1.1 before any other VCF component. 2. After the fleet lifecycle component is at version 9.1.1, you must comply only with the following dependencies: a. VCF Operations must not be patched in parallel with other components. Before you patch VCF Operations, ensure that no other lifecycle operations in the environment are in progress. Do not start other lifecycle operations until the VCF Operations patch process completes. b. Before you patch ESX hosts from 9.1.0.x to 9.1.1.0, you must first patch the VCF Operations instance and the license servers connected to it. c. Before you patch an identity broker instance from 9.1.0.x to 9.1.1, you must first patch the respective VCF management services runtime that hosts the identity broker instance. d. Before you patch Salt RaaS from 9.1.0.x to 9.1.1, you must first patch the respective VCF management services runtime that hosts the Salt RaaS instance. e. Before you patch the migration service engine component from 9.1.0.x to 9.1.1, you must first patch VCF Automation. f. If you have a Data Services Manager instance integrated with VCF Automation, before you patch VCF Automation to 9.1.1, see Upgrading your Data Services Manager in a VCF Environment. g. When you patch a software depot instance, patching other components is blocked because the patch binaries are unavailable until the patch process for the software depot completes.

Bill of Materials 9.1.1

This document contains the following sections

- Bill of Materials (BOM)
- Dependencies

Bill of Materials (BOM)

VMware Cloud Foundation (VCF) is comprised of the following components listed in the Bill of Materials (BOM) table. The components in the BOM are interoperable and compatible. You can select which components to apply in your deployment based on the impact to your environment and operational costs. The Broadcom Support Portal allows you to download the appropriate set of bits based on your entitlement.

VMware Cloud Foundation Component	vSphere Foundation Component	Version	Build Number
VCF Installer/ SDDC Manager	Yes (VCF Installer only)	9.1.1.0	25713928
ESX	Yes	9.1.1.0	25714478
vCenter	Yes	9.1.1.0	25712839
vSAN ESA Witness	Yes	9.1.1.0	25714474
vSAN File Services	Yes	9.1.1.0	25714478
vSAN OSA Witness	Yes	9.1.1.0	25714473
NSX	-	9.1.1.0	25691509
VCF Operations	Yes	9.1.1.0	25679751
Cloud proxy	Yes	9.1.1.0	25679891
License server	Yes	9.1.1.0	25679819
VCF Operations for networks	-	9.1.1.0	25682214
VCF Operations HCX	-	9.1.1.0	25690219
VCF Operations orchestrator	Yes	9.1.1.0	25679883
VCF Automation	-	9.1.1.0	25714559
Supervisor	Yes	9.1.1.0	25714555
VKS Add-ons (former VKS Standard Packages)	Yes	3.7.0+20260618	25497365
vSphere Kubernetes releases	Yes	1.34.2+vmware.2-vkr.2	N/A
Fleet lifecycle	Yes	9.1.1.0	25713934
Identity broker	-	9.1.1.0	25679886
Log management	Yes	9.1.1.0	25679624
Real-time metrics	-	9.1.1.0	25679622
Real-time metrics store	-	9.1.1.0	25714471
Salt RaaS	-	9.1.1.0	25679895
Salt master	-	9.1.1.0	25679895
SDDC lifecycle	Yes	9.1.1.0	25713940
Software depot	Yes	9.1.1.0	25713941
Telemetry	Yes	9.1.1.0	25671600
VCF services runtime	Yes	9.1.1.0	25714471
VCF download tool	Yes	9.1.1.0	25713929
VMware Remote Console	Yes	13.1.1	25665422
VMware Tools	Yes	13.1.5.0	25677323
VCF Consumption CLI	Yes	9.1.1.0	25662425
VCF Consumption CLI Plugins & Database	Yes	9.1.1.0	25665404
Deep Learning VM	-	9.1.1.0	25664150
Private AI Services	-	3.0.0	25675446

Supervisor Services

VMware Cloud Foundation Component	vSphere Foundation Component	Version	Build Number
VMware vSphere Kubernetes Service	Yes	3.7.0+v1.36	N/A
Harbor (Supervisor service)	Yes	2.15.2+vmware.1-vks.1	25639075
CA Cluster issuer (Supervisor service)	Yes	9.1.1.0	25662423
Contour (Supervisor service)	Yes	1.33.5	25639301
External DNS (Supervisor service)	Yes	0.21.0+vmware.2-vks.1	25639209
ArgoCD (Supervisor service)	-	1.2.0	25642124
VKSM Auto-attach	-	9.1.1.0	25714559
Supervisor Management Proxy	Yes	9.1.1.0	25665478
VMware vSphere Supervisor LCI	Yes	9.1.2	25714560

VCF Services

VMware Cloud Foundation Component	Included in VCF SKU	Version	Build Number
Migration service engine (VCF service)	Yes	9.1.1.0	25714559
Migration Service (VCF service)	Yes	9.1.1.0	25714559
ArgoCD (VCF service)	Yes	1.2.0	25642124
Configuration Service (VCF service)	Yes	9.1.1.0	25670523
Data Services (VCF service)	Add-on	9.1.1.0	25651575
Encryption Management (VCF service)	Yes	9.1.1.0	25714559
Metrics Aggregator (VCF service)	Yes	9.1.1.0	25665407
Protection and Recovery (VCF service)	Add-on	9.1.1.0	25691510
Harbor (VCF service)	Yes	9.1.1.0	25714559
Secret Store (VCF service)	Yes	9.1.1.0	25710217

The following VMware Cloud Foundation add-ons are interoperable with the components from the VCF BOM above:

VMware Cloud Foundation Add-on	VMware vSphere Foundation Component	Version	Build Number
VMware Data Services Manager	-	9.1.1.0	25651575
Protection and Recovery	Yes	9.1.1.0	25691510

Dependencies

- The Product Interoperability Matrix provides the upgrade order dependencies.
- The functionality of VMware Private AI Foundation with NVIDIA is delivered as a combination of components. The following components are now all part of the VCF software:
  - Guided deployment workflow in the vSphere Client
  - AI catalog items in VCF Automation
  - VMware Deep Learning VM 9.1.1.0

For more information about VMware Deep Learning VM image releases, see the VMware Deep Learning VM Release Notes.

  - Private AI Services 3.0

    For more information about Private AI Services releases, see the VMware Private AI Services Release Notes.
- Third-party products from the VCF ecosystem maintain their existing dependencies at the component level. For example, OEM driver add-ons, ESX device drivers, and UI plugins.
- VCF versioning is not applicable to any component with external dependency for the version, such as the Kubernetes version.
- Clusters that don't have active VMware Supervisor are supported, but do not support key capabilities of VCF, such as VCF Automation workflows.

vCenter 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Product Support Notes
- Build Details
  - VMware vCenter 9.1.1.0
- Applying the Patch
- Resolved Issues
  - Storage Issues
  - Auto Deploy Issues
  - vCenter and vSphere Client Issues
  - Miscellaneous Issues
  - Upgrade Issues
  - Backup and Restore
- Known Issues
  - Migration Issues
  - API/CLI Issues
  - Upgrade Issues
  - vCenter and vSphere Client Issues

Introduction

VMware vCenter 9.1.1.0 | 03 SEP 2026 | Build 25712839
Check for additions and updates to these release notes.

What's New

- **Automated Secure Boot Platform Key (PK) Remediation:** To address Microsoft 2011 Secure Boot certificate expirations, as detailed in Broadcom knowledge base article 423893, VCF 9.1.1.0 introduces three new capabilities to simplify Platform Key (PK) remediation:
  - **vCenter Alarm:** Proactively warns administrators when Secure Boot-enabled, powered-on virtual machines have an out-of-date NULL PK. This per-VM alarm is triggered once vCenter and the ESX host are upgraded to 9.1.1.0.
  - **Silent PK Update in ESX:** Automatically updates the out-of-date NULL PK on Secure Boot-enabled virtual machines that have no virtual Trusted Platform Module (vTPM) during a guest reboot.
  - **Capsule PK Update:** Enables a secure mechanism to safely update the out-of-date NULL PK on Secure Boot-enabled, vTPM-enabled Windows virtual machines during a guest reboot without interrupting TPM-based applications. The Capsule PK update driver triggering the PK update is available starting in VMware Tools 13.1.5 for supported Windows versions, except Windows Server 2016, Windows 10 64-bit 22H2, and 1809, which will be supported in a future VMware Tools release. For the Capsule PK update, the July 2026 Windows Cumulative Update or later is required. You must install this cumulative update before installing or upgrading VMware Tools to

version 13.1.5 to allow the installation of the PK update driver, except for Windows Server 2025, Windows 11 25H2, and 24H2.

- **VM-VM anti-affinity and affinity rules through compute policies:**
  You can use compute policies to create VM-VM anti-affinity rules that distribute VMs across separate hosts for resiliency, and VM-VM affinity rules that collocate VMs on the same host for low latency. This functionality applies to traditional virtual machines and to virtual machines created through VM Service. In the VM spec file, you can configure the strictness of a rule as either required (hard) or preferred (soft) during initial VM placement. However, only the preferred setting is supported during runtime. For more information, see vSphere Compute Policies.
- Photon RPMs are upgraded to the latest versions for improved security.

Distributed Resource Scheduler (DRS) and High Availability (HA) support for Memory Tiering:

With VCF 9.1.1, Memory Tiering supports DRS and HA. In clusters with Memory Tiering activated, vSphere HA admission control tracks DRAM as an independent resource alongside total memory to make sure that the cluster retains sufficient DRAM capacity for virtual machines restart after a host failure. This capability prevents failover operations from silently failing due to insufficient DRAM. For more information, see Memory Tiering and HA Admission Control.

Product Support Notes

Removal of the lstool script:

The `ls_update_certs.py` script is removed, because it is only supported on vCenter 6.x and 7.x versions. You can use the Lookup Service Doctor (lsdoctor) tool instead, as described in Broadcom knowledge base article 320837.

vCenter enforces MethodActions alarms to run on behalf of the user who configures the alarm:

With VCF 9.1.1, new vCenter alarms configured with the `MethodAction` object can only be executed on behalf of existing users with current, valid permissions. Alarms configured by users who have been deleted or had their privileges revoked are blocked and a `com.vmware.vc.AlarmMethodActionBlockedEvent` event is posted on the target object. You can control the enforcement behavior by using the Advanced Setting `vpxd.alarm.methodActionMode` in vCenter and selecting a mode, such as `vpxd.alarm.methodActionMode = flexible | strict | legacy`:

- flexible (default): Enforces user identity and privilege checks for new alarms. Existing alarms continue to fire without disruption.
- strict: All `MethodActions` require valid user credentials and privilege checks. Blocked actions post a `com.vmware.vc.AlarmMethodActionBlockedEvent` event.
- legacy: Actions run impersonating the vpxd service account. If a `MethodAction` is blocked in strict mode, a `com.vmware.vc.AlarmMethodActionBlockedEvent` event is posted on the target object. Re-save the alarm to register fresh credentials.

Build Details

VMware vCenter 9.1.1.0

Build Details

Download Filename:	VMware-vCenter-Server-Appliance-9.1.1.0.25712839-patch-FP.iso
Build:	25712839
Download Size:	7717 MB
SHA256 checksum:	d281358465b5cb770d15ccfad5be528e840988986123f401a5039666f0fecbc1
Quick Patch	No
CVEs	N/A

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement.

For download instructions, see Download Broadcom products and software.

For more information on using the vCenter shells, see Broadcom knowledge base article 2100508.

For information about deploying, converging, upgrading or patching your environment to 9.1.1, see Getting to 9.1.1.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, see Upgrading the vCenter Appliance.

Resolved Issues

Storage Issues

You cannot clone a virtual machine with Raw Device Mappings (RDM) disk to a VM with thin flat disk

When you clone a VM with an RDM disk and select the thin provisioning option, the resulting disk is always converted to a thick flat disk.

Auto Deploy Issues

Deploying a stateful ESX host by using Auto Deploy fails with "Certificate path is missing for host with id"

Due to a timing conflict between the configuration of distributed virtual switches (DVS) and the Auto Deploy notification code, deploying a stateful ESX host by using Auto Deploy with a Host Profile configured to add the host to a DVS might fail. In the vSphere Client, you see an error such as `Certificate path is missing for host with id`.

vCenter and vSphere Client Issues

Generating a hardware compatibility report in the vSphere Client fails with an error for the Internet connection

In the vSphere Client, when you generate a host hardware compatibility report, the task might fail with an error such as `Check vCenter Server Appliance internet connection to the VMware Verification Service at 'vvs.esp.vmware.com' and 'auth.esp.vmware.com'`. The issue occurs when the hardware compatibility check requires online search or the **Sync Compatibility Data** operation in the vSphere Lifecycle Manager cannot complete.

You see an error that a VCF license cannot be assigned to a vCenter instance

If the UUID of the vCenter instance you are licensing by using the VCF Operations UI is upper case, the operation fails with an error such as: `This license could not be assigned to the selected vCenter System. Check the network connection from the selected vCenter system to the license server and try again. Please refer to KB article 424533 for more information.`

The fix makes sure that the vCenter UUID is always lower case.

vCenter vpxd service might intermittently fail during backup operations due to a missing InstanceUUID in a virtual machine

A missing `InstanceUUID` parameter in a virtual machine during VM backup operations with a 3-rd party tool might cause the vpxd service to fail with a `core.vpxd-worker` dump and `Program terminated with signal SIGABRT, Aborted` error.

You do not see service accounts in the Global Permissions page in the vSphere Client

Since service account permissions are not customer-managed, service accounts are filtered out from the **Global Permissions** page in the vSphere Client. The page also excludes VCF reserved groups. You can retrieve all accounts for auditing or any other purpose by using CLI/API.

Applying password expiry and lockout policies for the vCenter Single Sign-On (SSO) administrator account might affect existing automation and integrations

The vCenter SSO administrator account enforces no password expiration or lockout policies by default. Applying these security policies globally might affect existing automation, integrations, and day-to-day operations. vCenter 9.1.1.0 introduces an opt-in/opt-out mechanism for the SSO administrator account password policy through a vCenter API endpoint. By default, the account remains opted out, preserving the existing behavior where no expiration or lockout is

enforced. If you require strict compliance, you can opt in to apply expiry and lockout policies to the account. The VCF Operations UI does not expose this setting in 9.1.1.0. You can use only the vCenter API.

This issue is resolved in this release. If you opt in for password expiry and lockout policies for the vCenter SSO administrator account, you can use the following example:

curl -sk -X PATCH \

"https://10.161.46.164/api/identity/admin/administrator/password-policy" \

-H "vmware-api-session-id: ${session}" \

-H "Content-Type: application/json" \

-d '{"enable_expiry_policy": true, "enable_lockout_policy": true}'

After a VCF certificate refresh, you see stale data for removed hosts in vSphere Configuration Profiles (VCP) cluster configurations

Following a VCF certificate refresh, the VCP inventory monitoring service loses its cached host association information. If a host removal event occurs before the cache is rebuilt, the system fails to identify the host association and skips the necessary configuration cleanup. As a result, stale host-specific and host-override sections remain in the cluster configuration.

The vSphere Statistics (vstats) service repeatedly logs a false-positive ERROR-level message about a missing discovery configuration for host-based metrics

The vstats provider orchestrator might incorrectly attempt to register the ESX host metrics provider with the generic discovery manager, even though host providers use a push-based streaming model and do not require generic discovery. As a result, the provider reports an error multiple times per minute, generating roughly 5,000 false-positive error events per day in Log management. The vstats service remains fully functional, only the logging behavior is affected.

Content library synchronization occasionally fails due to a reported missing file, even though the library is fully in sync and the file exists on the publisher

The pagination queries during a content library sync might not use a fully deterministic sort order. As a result, for libraries containing more than 100 items, some file records belonging to the same item might be returned in an inconsistent order across paginated queries. Occasionally, a file that is already present, might be identified as missing and scheduled for deletion during a subscribed library sync.

The pagination queries used during library-item sync now sort deterministically by item, version, and file identifiers, ensuring files are consistently accounted for across paginated results.

A vApp does not retain changes to some settings after a restart of vCenter or the VPXD service

Some settings of vApps such as the start order and the IP allocation are not updated in the vCenter database when they are changed. As a result, they might revert to previous values after a reboot of vCenter or a restart of the VPXD service.

vCenter upgrade from 8.0.x or 9.0.x to 9.1.0 fails during the import of vSphere Lifecycle Manager while attempting database schema upgrade

Orphaned database records in the vSphere Lifecycle Manager database, specifically in the `pm_recommendation_spec` table, might cause vCenter upgrade from 8.0.x or 9.0.x to 9.1.0 to fail. In the Virtual Appliance Management Interface, you see an error such as *`Error attempting Upgrade Database Schema. Please check vcintegrity migration logs for details.`*

vCenter 9.1.0.0 introduces a strict foreign key constraint, `FK_PM_RECOMMENDATION_SPEC`, to harden database integrity and the Postgres engine blocks schema changes because existing orphaned data violates the constraint.

Converging vSphere environments to VCF 9.1 might complete with errors due to duplicate DNS servers

In the vCenter Appliance Management Interface (VAMI), you can set duplicate DNS Server settings, which leads to errors after converging vSphere environments to VCF 9.1.

The fix removes duplicates and prevents error propagation for invalid DNS addresses.

You see an error 'HTTP Error 403: Forbidden' in the vSphere Client while downloading VIBs

Upgrading or remediating ESX hosts might fail with an error `HTTP Error 403: Forbidden` in the vSphere Client while downloading VIBs because of an issue with file permissions.

OpenLDAP login to vCenter fails after upgrade to VCF 9.1 due to a missing attribute

vCenter requires the `serviceAccount` attribute for OpenLDAP providers and if such is missing, OpenLDAP login fail after an upgrade to VCF 9.1.

Some vCenter services or operations might fail due to machine account password mismatch

If the machine account password stored in the VMware Directory Service (VMDIR) database does not match the password used by a given vCenter service, such services fail to start or some vCenter operations fail, but you do not see a notification or informative error message.

The fix adds the error message `Machine Account password mismatch. Refer to KB 316608`, providing a vCenter alarm on the condition and steps for remediation.

You can accidentally remove a node from Enhanced Linked Mode (ELM) topology by running the cmsso-util unregister command on the same vCenter instance

When you run the `cmsso-util unregister` command from a vCenter instance, you might accidentally unregister that same vCenter instead of another node in the topology.

The fix adds a validation that the `cmsso-util unregister` command does not target the vCenter instance from which it is run.

Running the cmsso-util unregister command for a vCenter that is not powered off causes an inconsistent state of the vCenter

If you do not power off or shut down a vCenter instance before running the `cmsso-util unregister` command, as required, the operation fails and the vCenter instance is in an inconsistent state.

The fix adds a pre-check to make sure the vCenter being unregistered is powered off before triggering the `cmsso-util unregister` command for it from another linked vCenter instance.

Miscellaneous Issues

After renewal, you see Solution User certificates with 2-year validity instead of the expected 10 years

When you use the vSphere Certificate Manager Utility to renew or replace a solution user certificate, if you set the option **Do you wish to generate all certificates using configuration file** to `Y`, the new certificates default to a 2-year validity period. If the option is set to `N`, the solution user certificates are generated with a validity period of 10 years, which is the expected and documented behavior.

vSphere High Availability failover fails on virtual machines for appliances such as vCenter and Fleet Manager

SDCC Manager uses the vSphere API call `migrateManagementNetwork` to migrate VMs for appliances such as vCenter and Fleet Manager from a standard switch to a distributed virtual switch (VDS). The API might fail to set the persist path of the dvport used by the VMs. As a result, if the hosting ESX node is rebooted, HA cannot restore the VM on another host: `loadDVPort` fails with `ENOENT / PlatformConfigFault`, HA rolls back the failover, and the VM remains powered off.

Extension authentication by using LoginExtensionBySubjectName API fails after upgrading vCenter to version 9.1.1.0

After upgrading vCenter to version 9.1.1.0, if you use the `LoginExtensionBySubjectName` API for extension authentication, the task fails with an `InvalidLogin SOAP` fault. In the `vpxd.log`, you see a message similar to:`[SessionManagerMo::LoginExtensionBySubjectName] Login failed for extension <extension-key>: certificate not pinned in VCDB. Use SetExtensionCertificate to register the extension certificate.`

Extensions using `LoginExtensionByCertificate` or SSO-based authentication and other vCenter Server management operations are not affected. The failure results from vCenter enforcing certificate pinning on `LoginExtensionBySubjectName`, which causes extensions that have not registered their TLS certificate by `SetExtensionCertificate` to receive `InvalidLogin` faults after a vCenter upgrade.

The fix effectively removes the deprecated `LoginExtensionBySubjectName` API.

Cloning a virtual appliance (vApp) might skip a permission check when the target ESX host is not specified

When cloning a vApp and specifying a target ESX host in the CloneSpec API, vCenter requires the `VApp.Create` permission on that host. But when the target host is not specified, the compute resource is implicitly determined from the owner of the target Resource Pool or vApp. In such cases, the permission check is skipped, allowing a vApp to be cloned onto a host or cluster that lacks the `VApp.Create` permission, as long as the permissions on other objects, like `Resource.AssignVAppToPool` on the target resource pool, are satisfied.

The fix enforces the `VApp.Create` permission. You cannot clone vApps onto compute resources without the `VApp.Create` permission.

If the ESX host selected to create an NFC session during a File Manager backup is entering maintenance mode, the backup might fail

During a File Manager backup, while downloading VMDKs from a datastore browser, an NFC session is created with the selected ESX host. If the host is entering maintenance mode, the NFC session fails and as a result, the backup fails.

The fix prevents the selection of ESX hosts which are entering or exiting maintenance mode when creating an NFC session to download VMDKs during a File Manager backup.

Upgrade Issues

Executing a VCF 9.1 upgrade precheck prematurely enables cgroupv2 in the OS configuration and might cause unpredictable service behavior if the source machine restarts

When performing an upgrade precheck targeting VCF version 9.1 either by Reduced Downtime Upgrade (RDU) or regular upgrade, the OS configuration for cgroupv2 might be altered prematurely on the source node. Restarting the source machine after the precheck might disrupt operational services such as the vc-ws1a-broker service in vCenter.

vCenter CLI upgrade fails with an HTTP 401 Unauthenticated error during the source vCenter version check phase

When performing a vCenter upgrade from a version earlier than 9.0 or from 9.0.x to 9.1 by using the Command Line Interface (CLI), if an Active Directory (AD) domain is configured as the default identity source in the vCenter Single Sign-On (SSO) configuration, the process might fail. The upgrade tool incorrectly attempts to authenticate the local root account against the AD identity provider instead of the local SSO domain (vsphere.local), resulting in an authentication failure.

You see “Exception occurred in postInstallHook for B2B-patching” error during upgrade from vCenter 9.0.2.0 to 9.1

If you follow Broadcom knowledge base article 414489 to modify the `/usr/lib/vmware-trustmanagement/config/trustmanagement-vlsi.xml` file during an upgrade to vCenter 9.0.2.0, you might see an error when upgrading to version 9.1. The error occurs because VCF 9.1 contains an updated version of the `trustmanagement-vlsi.xml` file and if the file was modified in 9.0.2.0, the upgrade to 9.1 leaves the old 9.0.2.0 `trustmanagement-vlsi.xml` in place. As a result, the vCenter `vmware-trustmanagement` service cannot start.

For upgrades to VCF 9.1, make sure you revert `/usr/lib/vmware-trustmanagement/config/trustmanagement-vlsi.xml` to the default before the upgrade.

Backup and Restore

SSH keys on remote servers are removed during SFTP backup

When a SFTP backup schedule is created, an SSH key of the vCenter instance is added to `~/.ssh/authorized_keys` on the remote server, but the corresponding SSH key is not removed from the remote server.

The fix removes stale SSH keys from remote servers during the first backup triggered after upgrade to vCenter 9.1.1.0.

File-based backup and restore transfers to external FTPS, HTTPS, or SFTP servers execute without authenticating the target server identity

In vCenter 9.1.1.0, file-based backup and restore enhances target server identity verification and auditing for FTPS, HTTPS, and SFTP protocols. In default mode (`validateCerts: false`), data transfers remain backward-compatible and execute as before, while a background probe checks the server identity and records a non-blocking advisory in:

- vCenter Appliance Management Interface (VAMI) backup activity details

- the restore wizard review page
- audit logs if the server is unverified.

If you enable strict validation (`validateCerts: true`), connections strictly enforce peer identity verification, leveraging custom CA certificates (`br_servercert.crt`), the system CA trust store (`ca-bundle.crt`), or pinned SSH host keys (`br_known_hosts`), and fail the connection if unverified.

For more information on how to prevent unverified target server advisories or to enable strict peer verification, see Broadcom knowledge base article 310399.

Known Issues

vCenter upgrade or patch to version 9.1.1 fails during the prechecks with error message: Unable to run vCenter NTP server check

The NTP precheck fails on vCenter instances configured with a non-UTC time zone.

Workaround: To change the configured time zone to UTC, follow the steps in Broadcom knowledge base article 455439.

Migration Issues

After Cross vCenter vMotion migration, powered-off virtual machines are always placed on the same host

In the vSphere Client, when you navigate to **Home > Hosts and Clusters**, right-click to select a cluster and click **Import VMs**, powered-off VMs are always relocated to the same target host in the selected cluster, even when the migration is split into multiple distinct tasks over time.

Workaround: Manually pick a different target host.

API/CLI Issues

vSphere Automation API does not honor network mappings in DeploySpec

When you specify network mapping entries in a DeploySpec, the API does not honor the mapping and selects a default network instead. In the vpxd logs, you see an error such as `Host did not have any virtual network defined (vim.fault.OvfNoHostNic)`. As a result, the VM does not receive the correct network that you specified.

Workaround: Change the network settings of the VM after it has finished deploying by either the vSphere Client or SDK.

You see a syntax warning message when using the certificate-manager CLI

When you manually run a certificate-manager CLI script, you might see a `SyntaxWarning` message due to internal updates. The warning has no effect on the functionality of the certificate-manager CLI utility.

Workaround: None. Ignore the warning.

Upgrade Issues

A reset of the vSphere Lifecycle Manager database might cause data loss in the Supervisor

If the vSphere Lifecycle Manager database in your environment is reset before upgrading vCenter from versions 8.0 Update 3 and later or 9.0.x to 9.1.0 or 9.1.1, the upgrade might cause data loss in the Supervisor. To avoid data loss, before a vCenter upgrade, you must first check your environment and take mitigation steps, if necessary.

Workaround: See Broadcom knowledge base article 455737 for instructions how to check if your environment is affected and for mitigation steps.

vCenter shows "Virtual Machine UEFI Secure Boot Platform Key is out of date." warning for the license server

After you patch your vCenter from version 9.1.0.x to 9.1.1, in the vSphere Client where the license server is deployed, you see the message `Virtual Machine UEFI Secure Boot Platform Key is out of date.` in the issues and alarms section. The alarm appears when you have license servers in version 9.1.0.x or license servers patched to version 9.1.1. This alert is not critical and has no impact on the boot or the functionalities of your license server.

Workaround: To resolve the alarm, from the vSphere Client, upgrade the compatibility of the license server VM to ESXi 6.7 and later by following the Upgrade the Compatibility of a Virtual Machine Manually procedure.

Upgrade from vCenter 8.0 Update 3j to 9.1.1.0 might fail in environments with Windows 2016 server

In some environments with Windows Server 2016 Datacenter (Build 10.0.14393), when you use the vCenter installer to upgrade from vCenter 8.0 Update 3j to 9.1.1.0, the operation might fail in stage 1 with an error such as `Failed to send file [disk-0.vmdk] to the host [lvnvcfspatn02.lvn.broadcom.net], please check the network connection).`

Workaround: Update the Windows Server version.

vCenter and vSphere Client Issues

In the vSphere Client, you see a License Inventory Monitoring alarm

After you assign an override license to an ESX hosts of version 8.x, the license usage calculation might incorrectly include the usage from the ESXi 8.x hosts to the license assigned to the managing vCenter instance. As a result, in the vSphere Client you see a `License Inventory Monitoring` alarm. The license calculation discrepancy affects only the API responsible for the vCenter alert. The overall core count displayed in the **Licenses** tab in the vSphere Client is correct and matches the license usage metrics in VCF Operations.

Workaround: See Broadcom knowledge base article 456737.

ESX 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Getting to 9.1.1
- Product Support Notes
- Patches Contained in This Release
  - VMware ESX 9.1.1.0
  - Patch Download and Installation
- Resolved Issues
  - ESXi-9.1.1.0-25714478
  - ESXi-9.1.1.0-25714478-standard
  - ESXi-9.1.1.0-25714478-no-tools
- Known Issues
  - CLI and API Issues

Introduction

VMware ESX 9.1.1.0 | 03 SEP 2026 | Build 25714478
Check for additions and updates to these release notes.

What's New

Automated Secure Boot Platform Key (PK) Remediation: To address Microsoft 2011 Secure Boot certificate expirations, as detailed in Broadcom knowledge base article 423893, VCF 9.1.1.0 introduces three new capabilities to simplify Platform Key (PK) remediation:

- **vCenter Alarm:** Proactively warns administrators when Secure Boot-enabled, powered-on virtual machines have an out-of-date NULL PK. This per-VM alarm is triggered once vCenter and the ESX host are upgraded to 9.1.1.0.
- **Silent PK Update in ESX:** Automatically updates the out-of-date NULL PK on Secure Boot-enabled virtual machines that have no virtual Trusted Platform Module (vTPM) during a guest reboot.
- **Capsule PK Update:** Enables a secure mechanism to safely update the out-of-date NULL PK on Secure Boot-enabled, vTPM-enabled Windows virtual machines during a guest reboot without interrupting TPM-based applications. The Capsule PK update driver triggering the PK update is available starting in VMware Tools 13.1.5 for supported Windows versions, except Windows Server 2016, Windows 10 64-bit 22H2, and 1809, which will be supported in a future VMware Tools release. For the Capsule PK update, the July 2026 Windows Cumulative Update or later is

required. You must install this cumulative update before installing or upgrading VMware Tools to version 13.1.5 to allow the installation of the PK update driver, except for Windows Server 2025, Windows 11 25H2, and 24H2.

Getting to 9.1.1

For information about deploying, converging, upgrading or patching your environment to 9.1.1, see Getting to 9.1.1.

Product Support Notes

Replacement of SHA-1 in ESX IPsec required before removal:

In accordance with NIST guidelines, VCF 9.1 and later require using strong ciphers with the `esxcli network ip ipsec` command namespace. To avoid service disruptions, replace SHA-1 before upgrading to a future scheduled maintenance release.

Patches Contained in This Release

VMware ESX 9.1.1.0

Build Details

VMware vSphere Hypervisor (ESX) Offline Bundle

Download Filename:	VMware-ESXi-9.1.1.0.25714478-depot.zip
Build:	25714478
Download Size:	680 MB
SHA256 checksum:	71bdb30387d3f04d66e20369965f54f9cee4ede9ffe0a0ffa7e3d846885f205e
Live Patchable	No
Host Reboot Required:	Yes
Virtual Machine Migration or Shutdown Required:	Yes

VMware vSphere Hypervisor (ESX) ISO image

Download Filename:	VMware-VMvisor-Installer-9.1.1.0.25714478.x86_64.iso
Build:	25714478
Download Size:	700 MB
SHA256 checksum:	712d153f32581d7dc2027403c988fc0159e69619c4486941df69aa0616591c53

ESX Images

Name and Version	Release Date	Live Patchable	Category
ESXi 9.1.1-0.25714478	03 SEP 2026	No	Bugfix and Security

Image Profiles

VMware patch and update releases contain general and critical image profiles. Application of the general release image profile applies to new bug fixes.

Image Profile Name
ESXi-9.1.1.0-25714478-standard
ESXi-9.1.1.0-25714478-no-tools

Patch Download and Installation

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement, VMware vSphere Foundation or VMware Cloud Foundation.

For download instructions, see Download Broadcom products and software.

See these KBs for details on the authenticated online and offline download: 390121, 390098, and 389276.

For details on updates and upgrades by using vSphere Lifecycle Manager, see About vSphere Lifecycle Manager and vSphere Lifecycle Manager Baselines and Images. You can also update ESX hosts without the use of vSphere Lifecycle Manager by using an image profile. To do this, you must manually download the patch offline bundle ZIP file or see the KB How to download ESXi ISO image for all releases including patch updates.

For more information, see Getting Started with ESXCLI and the VMware ESX Upgrade guide.

Resolved Issues

ESXi-9.1.1.0-25714478

Name	ESX
Version	ESXi-9.1.1.0-25714478
Release Date	September 3, 2026
Category	Bugfix
Live Patchable	No

Affected Components	• Broadcom-ELX-lpfc • Broadcom-bnxt-Net-RoCE • Broadcom-lsi-mr3 • Broadcom-lsi-msgpt3 • Broadcom-lsi-msgpt35 • Cisco-nfnic • ESXi • HPE-nhpsa • Intel-Volume-Mgmt-Device • Intel-i40en • Intel-icen • Intel-irdman • Intel-ixgben • MRVL-Atlantic-Driver-Bundle • MRVL-E3-Ethernet-iSCSI-FCoE • MRVL-E4-CNA-Driver-Bundle • MRVL-QLogic-FC • Mellanox-nmlx5 • Mellanox-nmlxbf-gige • Solarflare-NIC • VMware-Cpu-Microcode • VMware-HBR-UW • VMware-Host-Client • VMware-NVMe-PCIe • VMware-NVMeoF-RDMA • VMware-VM-Tools • VMware-ahci • VMware-bfedac • VMware-dwi2c • VMware-iser • VMware-nvme-plugin • VMware-nvmxnet3 • VMware-nvmxnet3-ens • VMware-penedac • VMware-pvscsi • VMware-qat • VMware-rdmahl • VMware-rshim • VMware-vmkusb • esx-update • esxio-update • vsphere-fdm
Related CVE numbers	N/A

This patch resolves the following issues:

ESX host might fail with a purple diagnostic screen after PCI passthrough on a PCI/PCIe device to a Linux or Windows VM

When you use PCI passthrough on a PCI/PCIe device to a Linux or Windows VM, including Nvidia GPUs, the VMs might not program the MSI/MSIx interrupts correctly during device probe. As a result, the ESX host either powers off the VM or fails with a purple diagnostic screen.

You see a "Create and Commit draft check" or "Failed to invoke create and commit" error in VCF Operations

When attempting to patch ESX hosts to version 9.1.1, the workflow fails at step **Desired State**. In the SDDC Manager and VCF Operations UI, you see errors such as `Create and Commit draft check` or `Failed to invoke create`

`and commit`. If you try to set the vSphere Lifecycle Manager cluster image to 9.1.1 in the vSphere Client, you see the following error:

```
The /profile/nsx/fabric/transport_node_profile in configuration is not compatible with the draft image. Remove the incompatible configuration before setting the new desired state.
```

Workaround: Perform the steps in Broadcom knowledge base article 455572.

On the VM Summary page in the VMware Host Client, you see a false warning that the VM network portgroup does not exist

After a VCF deployment, the **VM Summary** page in the VMware Host Client might incorrectly display the warning `This VM is attached to a network portgroup undefined that doesn't exist` for VMs with network adapters connected to a Distributed Virtual Switch (DVS) portgroup. This issue occurs due to an underlying check for only recognized standard virtual switches and not identifying the portgroup for DVS-backed network adapters. As a result, you see a false-positive warning for every affected VM.

Due to vSAN disk failures, you might not see the vSAN File Service UI widget

vSAN File Service determines its supported version by evaluating the on-disk format versions across all disks in the cluster. If a disk in the cluster is in a Permanent Device Loss (PDL) state, such as Absent vSAN Disk, the vSAN File Service query might return an obsolete or inaccurate format version of that disk. As a result, the vSAN File Service might get an incorrect supported version and due to vSAN disk failures, the vSAN File Service UI widget might not display. This issue applies to both vSAN Original Storage Architecture (OSA) and vSAN Express Storage Architecture (ESA).

The fix skips PDL disks when calculating lowest disk format version.

Fault Domain Manager (FDM) might fail when vSphere High Availability (HA) is active in environments with Cisco NFNIC driver

The Cisco NFNIC driver might generate an excessively large volume of stats data and while attempting to retrieve and process such data, FDM might run out of memory and fail with a core dump at `/var/core/fdm-zdump`. In the `/var/run/log/fdm.log` file, you see errors such as `Unable to allocate memory` and under `/var/lib/vmware/hostd/stats dir`, you see large stats files.

Hot-add operation for an independent nonpersistent disk might fail for virtual machines hosted on vSphere Virtual Volumes datastores

When you restore VMs on ESX 8.0 Update 1 and later hosts from earlier ESX versions, hot-add operations for some of the restored disks hosted on vSphere Virtual Volumes datastores might fail due to a mismatch in the virtual volume namespace versions. The issue is specific for independent nonpersistent disks.

Configuring vSAN File Service with Active Directory domain fails with an error for exception caught when running preflight check on the file server

In the vSphere Client, when you create a file service domain with AD and click **Next**, you see an error such as:

```
Failed to check domain configuration: Exception caught when running preflight check on file server.
```

The issue occurs because querying the Active Directory domain for LDAP SRV records returns multiple duplicate entries for the same Domain Controller hostname. As a result, the pre-flight check script causes an exception and fails the file service enablement workflow.

A disk-only Storage vMotion operation might accidentally delete an orphaned virtual disk file on the destination datastore and cause data loss

When you perform a disk-only Storage vMotion, vCenter might not check if an orphaned virtual disk (VMDK) file - for example, one left behind by an earlier disk detach operation - is already present in the destination folder. As a result, the new file might get the same name as the existing VMDK and the migration task fails. The cleanup after such a failure might remove the pre-existing orphaned virtual disk file, and cause loss of that file's data.

Multiple ESX hosts might fail with a purple diagnostic screen due to a rare race condition in the NFSv4.1 client

On ESX hosts using the NFSv4.1 client, if a competing APD starts during an ongoing APD recovery, the file reclaim process creates duplicate insertions and causes pointer corruption. As a result, multiple ESX hosts might fail with a purple diagnostic screen.

VMware Tools Bundling Changes in ESX 9.1.1.0

The following VMware Tools ISO images are bundled with ESX 9.1.1.0:

- **windows.iso**: VMware Tools 13.1.5 supports 64-bit Windows versions - Windows 7 SP1 or Windows Server 2008 R2 SP1 and later.

The following VMware Tools ISO images are available for download:

- VMware Tools 12.5.4:
  - **windows.iso:** VMware Tools 12.5.4 supports 64-bit Windows versions.
  - **windows-x86.iso:** VMware Tools 12.4.9 supports 32-bit Windows versions.
  - **linux.iso**: VMware Tools 10.3.26 ISO image for Linux OS with glibc 2.11 or later.
- VMware Tools 11.0.6:
  - **windows.iso**: for Windows Vista (SP2) and Windows Server 2008 Service Pack 2 (SP2).
- VMware Tools 10.0.12:
  - **winPreVista.iso**: for Windows 2000, Windows XP, and Windows 2003.
  - **linuxPreGLibc25.iso**: supports Linux guest operating systems earlier than Red Hat Enterprise Linux (RHEL) 5, SUSE Linux Enterprise Server (SLES) 11, Ubuntu 7.04, and other distributions with **glibc** version earlier than 2.5.
- **solaris.iso**: VMware Tools image 10.3.10 for Solaris.
- **darwin.iso**: Supports Mac OS X versions 10.11 and later.

Follow the procedures listed in the following documents to download VMware Tools for platforms not bundled with ESX:

- VMware Tools 13.1.5 Release Notes
- VMware Tools for hosts provisioned with Auto Deploy
- Upgrading VMware Tools

ESX hosts might experience CPU utilization at around 100% after a port is quiesced in an Enhanced Network Stack (ENS) environment

When a network port is quiesced, the host network scheduler might fail to correctly update its internal byte counters after clearing pending packets. This mismatch causes the system to continually check for network traffic even when the queue is empty, resulting in the transmit (TX) process getting stuck in a loop and consuming up to 100% of CPU resources.

The fix ensures that internal byte counters are accurately updated when packets are dropped.

When using Link Aggregation Control Protocol (LACP), if a physical NIC is down, defined alarms might not trigger

When you configure an alarm based on Broadcom knowledge base article 378014, the alarm might not trigger in the vSphere Client if a physical NIC is down.

When resuming virtual machines configured with device groups containing DVX devices, the VMs might fail to power on

A power-on failure might occur when resuming a VM configured with a device group containing DVX devices.

Uplink gets reenabled before the time defined by the TeamPolicyUpDelay policy passes

The ESX advanced setting `Net.TeamPolicyUpDelay` sets a time before an uplink is reenabled after the link status changes from `DOWN` to `UP`. During such a wait period, new ports might be enabled for various reasons, such as migration, VM power cycle, or flapping of the network interface inside the guest OS. A newly powered-on vNIC can cause an uplink in `TeamPolicyUpDelay` state to reactivate prematurely for all VMs connected to the switch.

ESX hosts using Emulex Fibre Channel adapters might fail with a purple diagnostic screen after powering on virtual machines when Virtual Machine Identifier (VMID) is enabled

An issue in the Broadcom Emulex lpfc storage driver if VMID is enabled can cause an ESX host to fail with a purple diagnostic screen immediately after powering on virtual machines. The issue occurs due to an invalid memory access during Fibre Channel common transport command processing.

If ESX hosts share a LUN, you might overwrite VMFS volumes

If ESX hosts share a LUN and you create a VMFS volume on one of the hosts by using the VMware Host Client, the new volume might not be immediately visible on the other hosts and another user can create a VMFS volume on the same LUN from another Host Client session. As a result, the first VMFS datastore path might be overwritten.

The fix makes sure that while listing the available LUNs for new VMFS volumes, latest changes on the LUNs are fetched and considered.

A rare race condition in the lpfc driver might cause ESXi hosts to fail with a purple diagnostic screen during reboot or shutdown

On an ESXi host with Emulex LightPulse Fibre Channel adapters, a rare race condition in the lpfc driver can result in an invalid DMA access. This invalid access can lead to silent memory corruption, resulting in unpredictable system instability that might cause the ESX host to fail with a purple diagnostic screen, but since the memory corruption only affects the address range of the lpfc driver, it does not damage user VM data. The race condition only occurs during the device detachment phase, typically triggered during a reboot or when enabling PCI passthrough, and the probability of occurrence is low.

ESXi hosts using the lpfc driver do not provide log visibility for certain faulty small form-factor pluggable (SFP) optics

When an SFP module is present but non-functional, the Emulex Fibre Channel adapter firmware detects the fault and reports an error code. The lpfc driver does not capture or log that specific hardware error code into the vmkernel.log, which makes it difficult to identify and troubleshoot faulty optics.

The fix enhances the driver to properly log SFP hardware errors as they occur.

After an Emulex Fibre Channel adapter firmware upgrade, ESX hosts might fail with a purple diagnostic screen

When updating the firmware on certain Broadcom Emulex Fibre Channel adapters, the inbox lpfc driver might incorrectly handle a change in the internal resource counts during the subsequent host reboot. This mismatch can trigger an improper memory management condition during driver initialization or cleanup, leading to a purple diagnostic screen on the ESX host.

Emulex SAN Manager (ESM) does not display encryption details for certain Host Bus Adapters (HBAs)

An issue within the lpfc driver prevents ESM from properly retrieving data from all encryption-capable Emulex Fibre Channel adapters. This occurs due to a communication mismatch during fabric port initialization and link setup sequences between the ESX host and the switch.

ESX hosts using Emulex Fibre Channel adapters might fail with a purple diagnostic screen during reboot or shutdown due to a race condition

A race condition in the native lpfc driver can occur if a hardware error on an Emulex Host Bus Adapter (HBA) triggers while the driver is unloading. As a result, the ESXi host fails with a a purple diagnostic screen during reboot or shutdown with an error such as #`PF in lpfc_hw_info_setup()`.

ESX hosts with Emulex Fibre Channel HBAs might fail with a purple diagnostic screen during storage array upgrades

During the upgrade of certain Fibre Channel storage arrays, the target node IDs might change. As a result, the lpfc driver interprets the targets as offline and different targets coming online in a short period. Handling such cases might trigger a race condition in the lpfc driver, leading to failure of the ESX host with a purple diagnostic screen displaying an error such as `#PF Exception 14 in world <world_id>:lpfc_path_cl`.

Scheduling delays when high-priority processes are placed on a busy physical CPU might cause packets drop

When high-priority processes, for example in an Enhanced Network Stack (ENS) context, are placed on a busy physical CPU, they rely on the virtual CPU migration algorithm to move them to an idle or less busy CPU as appropriate. An issue with the migration algorithm might cause such processes to stay on the busy CPU for extended periods, causing significant scheduling delays, or high CPU Ready Time. As a result, you might see packets drop.

Log entries in the dfwpktlogs.log for distributed firewall (DFW) packets might occasionally split across two lines

Some log records for DFW packets might be written as two separate lines instead of one. When the split occurs within the record timestamp, the second line shows a system-generated timestamp rather than the original. For example

```
2026-03-11T05:57:28.172Z -NOTICE FIREWALL-PKTLOG 2100407 [nsx@4413] 2026-03-11
```

```
2026-03-11T05:57:28.176Z -NOTICE FIREWALL-PKTLOG 2100407 [nsx@4413] T05:57:28.172Z 4678804c INET6 match PASS
 1007 OUT 76 TCP 2001:db8:abcd:12::1001/23557->2001:db8:abcd:12::1501/80 S Cyperf_L4-rule
```

The issue only affects log formatting, no log data is lost and firewall enforcement is unaffected.You can read the full record by combining the split line with the partial record on the following line.

In the ESX Host Client, you do not see the option to add Sound Controller for virtual machines

In ESX Host Client version 9.1, under **Edit Settings > Virtual Hardware > Add New Device**, you do not see the **Sound Controller** option to configure audio hardware.

Setting the /Scsi/NvmeMaxUnmapBlockDescriptorLbaCount advanced configuration option does not correctly limit the Maximum Unmap LBA Count Per Descriptor for NVMe devices

When the advanced configuration option `/Scsi/NvmeMaxUnmapBlockDescriptorLbaCount` is set to a non-zero value for the Maximum Deallocate Range Size Limit, ESX incorrectly applies the same limit to the Maximum Unmap LBA Count Per Descriptor as for the Maximum Unmap Descriptor Count. As a result, the vSphere API for Array Integration (VAAI) cache reports incorrect UNMAP limits, which might cause UNMAP operations to behave unexpectedly with NVMe storage arrays.

When Intel SGX Flexible Launch Control (FLC) is set to unlocked in the ESX host firmware, VMs using vSGX might fail to power on after a Quick Boot

When SGX FLC is set to unlocked in the ESX host firmware, and a VM is configured to enable SGX with FLC, the hypervisor programs the associated FLC Model-Specific Register (MSRs) with guest-provided values. Such values persist during a Quick Boot, which might cause subsequent MSR uniformity checks to fail during boot. As a result, ESX might disable SGX on the host if it finds non-uniform values in the FLC MSRs during boot. The issue also impacts Pod VMs utilizing vSGX, such as the TDX Quote Pod.

Intel Xeon 6 processors utilizing QAT accelerators might see increased boot times on ESX 9.1

On Intel Xeon 6 processors systems using QAT devices, in some cases, the boot time for ESX hosts might increase.

In the VMware Host Client, you do not see vSAN data migration options while entering maintenance mode

When placing a vSAN host into maintenance mode by using the VMware Host Client in version 9.1, you might not see vSAN data migration options in the dialog box.

In the NSX Manager, you see unknown status for multiple ESX host metrics

In the NSX Manager, when you navigate to **System > Fabric > Hosts**, you see unknown status for multiple ESX host metrics, such as `Controller Connectivity`, `Tunnel Status`, and `PNIC/Bond Status`. The issue occurs because NSX requests high quality entropy for frequent use and consequently the default HWRNG entropy is exhausted and causes timeouts. Affected ESX hosts create an opsAgent core dump file: `/var/core/opsAgent-zdump`. During heavy load, multiple ESX hosts might be affected in batches. In the ESX log, `/var/run/log/nsx-syslog.log`, you see log messages such as:

```
Wa(###) nsx-opsagent[#######]: NSX ######## - [nsx@4413 comp="nsx-esx" subcomp="opsagent"
s2comp="nsx-core" tid="########" level="WARNING"] AsioNsxProvider: (0x##########-2) user
dispatcher blocked since 20 seconds.
```

The ESX agent hostd might intermittently fail or generate a core dump during gathering device statistics or socket disconnections

Under conditions of high-concurrency performance queries or unexpected connection drops, synchronization race conditions can occur. Such timing conflicts might cause internal tracking structures to be cleared prematurely and cause hostd to terminate unexpectedly.

A very rare race condition might cause an encrypted virtual machine to fail with a core dump

A very rare race condition might cause the VMX process on an ESX host to fail and cause an encrypted virtual machine to unexpectedly power off. In the `vmware.log` file you see an error such as: `PANIC: Unexpected signal: 6`.

In the VMkernel logs, you see multiple log messages for failed retrieval of ENS uplink distributed statistics

In environments using the Enhanced Network Stack (ENS), the VMkernel creates logs each time it fails to retrieve distributed statistics for an uplink port, even when the port does not support ENS. The error messages are `Fail to get`

`uplink dist stats for ens port`. Such retrieval attempts can fail transiently under normal operating conditions and do not indicate an actual network problem, but might clutter VMkernel logs and cause unnecessary log noise, CPU overhead, and affect monitoring.

The fix demotes the `Fail to get uplink dist stats for ens port` error messages to debug-level logging and you do not see such in release builds.

Tunneled SSL from vCenter to ESX fails intermittently

In some cases, such as when traffic goes through a tunnel that terminated inside a guest virtual machine, an SSL connection from vCenter to the ESX host might intermittently fail.

In Advanced Settings, you do not see an option to configure a time window for consecutive login failures before locking user accounts

In ESX, user accounts are locked after a configurable number of consecutive login failures without a specific time window and you cannot configure such a window.

The fix updates the Pluggable Authentication Modules and adds the advanced ESX setting `Security.AccountLockFailInterval`, which allows you to set a time window for consecutive login failures before locking user accounts. `Security.AccountLockFailInterval` defaults to 15 min, but you can configure the time window accordingly.

IPFIX traffic might be blocked due to a missing route on a DPU ESX host

On a dual-DPU ESX host with offloading enabled, when you configure sending IPFIX data to a VCF Operations for networks collector but the IP address/netmask of the collector is in a different network that requires a gateway, IPFIX traffic might be blocked due to a missing route. In a non-DPU environment, you can configure a default gateway for VCF Operations, but you cannot create a default gateway in a DPU environment.

In rare cases, ESXi hosts might fail with a purple diagnostic screen during VMFS UNMAP operation

Under rare race conditions, ESXi hosts with VMFS datastores supporting UNMAP operations might fail with a purple diagnostic screen during an UNMAP task.

The esxtop utility reports inflated VMWAIT values

The calculation of VMWAIT, which is the percentage of time a VM waits for a VMkernel activity such as running I/O to complete before it can continue, uses the CPU WAIT and IDLE values. In some cases, the calculation might overestimate the CPU IDLE value and as a result, the VMWAIT value is much higher.

ESX 9.1.1.0 includes the following Intel microcode:

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Sandy Bridge DT	0x206a7 (06/2a/7)	0x12	baseline	0x2f	2/17/2019	Intel Xeon E3-1100 Series; Intel Xeon E3-1200 Series; Intel i7-2655-LE Series; Intel i3-2100 Series
Sandy Bridge EP	0x206d6 (06/2d/6)	0x6d	baseline	0x621	3/4/2020	Intel Pentium 1400 Series; Intel Xeon E5-1400 Series; Intel Xeon E5-1600 Series; Intel Xeon E5-2400 Series; Intel Xeon E5-2600 Series; Intel Xeon E5-4600 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Sandy Bridge EP	0x206d7 (06/2d/7)	0x6d	baseline	0x71a	3/24/2020	Intel Pentium 1400 Series; Intel Xeon E5-1400 Series; Intel Xeon E5-1600 Series; Intel Xeon E5-2400 Series; Intel Xeon E5-2600 Series; Intel Xeon E5-4600 Series
Ivy Bridge DT	0x306a9 (06/3a/9)	0x12	baseline	0x21	2/13/2019	Intel i3-3200 Series; Intel i7-3500-LE/UE; Intel i7-3600-QE; Intel Xeon E3-1200-v2 Series; Intel Xeon E3-1100-C-v2 Series; Intel Pentium B925C
Haswell DT	0x306c3 (06/3c/3)	0x32	baseline	0x28	11/12/2019	Intel Xeon E3-1200-v3 Series; Intel i7-4700-EQ Series; Intel i5-4500-TE Series; Intel i3-4300 Series
Ivy Bridge EP	0x306e4 (06/3e/4)	0xed	baseline	0x42e	3/14/2019	Intel Xeon E5-4600-v2 Series; Intel Xeon E5-2600-v2 Series; Intel Xeon E5-2400-v2 Series; Intel Xeon E5-1600-v2 Series; Intel Xeon E5-1400-v2 Series
Ivy Bridge EX	0x306e7 (06/3e/7)	0xed	baseline	0x715	3/14/2019	Intel Xeon E7-8800/4800/2800-v2 Series
Haswell EP	0x306f2 (06/3f/2)	0x6f	baseline	0x49	8/11/2021	Intel Xeon E5-4600-v3 Series; Intel Xeon E5-2600-v3 Series; Intel Xeon E5-2400-v3 Series; Intel Xeon E5-1600-v3 Series; Intel Xeon E5-1400-v3 Series
Haswell EX	0x306f4 (06/3f/4)	0x80	baseline	0x1a	5/24/2021	Intel Xeon E7-8800/4800-v3 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Broadwell H	0x40671 (06/47/1)	0x22	baseline	0x22	11/12/2019	Intel Core i7-5700EQ; Intel Xeon E3-1200-v4 Series
Avoton	0x406d8 (06/4d/8)	0x01	baseline	0x12d	9/16/2019	Intel Atom C2300 Series; Intel Atom C2500 Series; Intel Atom C2700 Series
Broadwell EP/EX	0x406f1 (06/4f/1)	0xef	baseline	0xb000040	5/19/2021	Intel Xeon E7-8800/4800-v4 Series; Intel Xeon E5-4600-v4 Series; Intel Xeon E5-2600-v4 Series; Intel Xeon E5-1600-v4 Series
Skylake SP	0x50654 (06/55/4)	0xb7	baseline	0x2007006	3/6/2023	Intel Xeon Platinum 8100 Series; Intel Xeon Gold 6100/5100, Silver 4100, Bronze 3100 Series; Intel Xeon D-2100 Series; Intel Xeon D-1600 Series; Intel Xeon W-3100 Series; Intel Xeon W-2100 Series
Cascade Lake B-0	0x50656 (06/55/6)	0xbf	baseline	0x4003901	12/12/2024	Intel Xeon Platinum 9200/8200 Series; Intel Xeon Gold 6200/5200; Intel Xeon Silver 4200/Bronze 3200; Intel Xeon W-3200
Cascade Lake	0x50657 (06/55/7)	0xbf	baseline	0x5003901	12/12/2024	Intel Xeon Platinum 9200/8200 Series; Intel Xeon Gold 6200/5200; Intel Xeon Silver 4200/Bronze 3200; Intel Xeon W-3200
Cooper Lake	0x5065b (06/55/b)	0xbf	baseline	0x7002b01	12/12/2024	Intel Xeon Platinum 8300 Series; Intel Xeon Gold 6300/5300
Broadwell DE	0x50662 (06/56/2)	0x10	baseline	0x1c	6/17/2019	Intel Xeon D-1500 Series
Broadwell DE	0x50663 (06/56/3)	0x10	baseline	0x700001c	6/12/2021	Intel Xeon D-1500 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Broadwell DE	0x50664 (06/56/4)	0x10	baseline	0xf00001a	6/12/2021	Intel Xeon D-1500 Series
Broadwell NS	0x50665 (06/56/5)	0x10	baseline	0xe000015	8/3/2023	Intel Xeon D-1600 Series
Skylake H/S	0x506e3 (06/5e/3)	0x36	baseline	0xf0	11/12/2021	Intel Xeon E3-1500-v5 Series; Intel Xeon E3-1200-v5 Series
Denverton	0x506f1 (06/5f/1)	0x01	baseline	0x3e	10/5/2023	Intel Atom C3000 Series
Ice Lake SP	0x606a6 (06/6a/6)	0x87	baseline	0xd000433	3/9/2026	Intel Xeon Platinum 8300 Series; Intel Xeon Gold 6300/5300 Series; Intel Xeon Silver 4300 Series
Ice Lake D	0x606c1 (06/6c/1)	0x10	baseline	0x1000301	3/9/2026	Intel Xeon D-2700 Series; Intel Xeon D-1700 Series
Snow Ridge	0x80665 (06/86/5)	0x01	baseline	0x4c000026	2/28/2024	Intel Atom P5000 Series
Snow Ridge	0x80667 (06/86/7)	0x01	baseline	0x4c000026	2/28/2024	Intel Atom P5000 Series
Tiger Lake U	0x806c1 (06/8c/1)	0x80	baseline	0xbe	7/24/2025	Intel Core i3/i5/ i7-1100 Series
Tiger Lake U Refresh	0x806c2 (06/8c/2)	0xc2	baseline	0x3e	7/24/2025	Intel Core i3/i5/ i7-1100 Series
Tiger Lake H	0x806d1 (06/8d/1)	0xc2	baseline	0x58	7/24/2025	Intel Xeon W-11000E Series
Sapphire Rapids SP HBM	0x806f8 (06/8f/8)	0x10	baseline	0x2c000435	3/2/2026	Intel Xeon Max 9400 Series
Sapphire Rapids SP	0x806f8 (06/8f/8)	0x87	baseline	0x2b000685	3/2/2026	Intel Xeon Platinum 8400 Series; Intel Xeon Gold 6400/5400 Series; Intel Xeon Silver 4400 Series; Intel Xeon Bronze 3400 Series
Kaby Lake H/S/X	0x906e9 (06/9e/9)	0x2a	baseline	0xf8	9/28/2023	Intel Xeon E3-1200-v6 Series; Intel Xeon E3-1500-v6 Series
Coffee Lake	0x906ea (06/9e/ a)	0x22	baseline	0xfa	7/28/2024	Intel Xeon E-2100 Series; Intel Xeon E-2200 Series (4 or 6 core)
Coffee Lake	0x906eb (06/9e/ b)	0x02	baseline	0xf6	2/1/2024	Intel Xeon E-2100 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Coffee Lake	0x906ec (06/9e/c)	0x22	baseline	0xf8	2/1/2024	Intel Xeon E-2100 Series
Coffee Lake Refresh	0x906ed (06/9e/d)	0x22	baseline	0x104	11/14/2024	Intel Xeon E-2200 Series (8 core)
Rocket Lake S	0xa0671 (06/a7/1)	0x02	baseline	0x66	2/12/2026	Intel Xeon E-2300 Series
Granite Rapids SP R1S	0xa06d1 (06/ad/1)	0x20	baseline	0xa000151	3/24/2026	Intel Xeon 6500P/6700P/6900P Series
Granite Rapids AP/SP	0xa06d1 (06/ad/1)	0x95	baseline	0x1000434	4/27/2026	Intel Xeon 6500P/6700P/6900P Series
Sierra Forest	0xa06f3 (06/af/3)	0x01	baseline	0x30003b2	3/16/2026	Intel Xeon 6700E/6900E Series
Raptor Lake E/HX/S	0xb0671 (06/b7/1)	0x32	baseline	0x133	10/8/2025	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0671 (06/b7/1)	0x36	baseline	0x137	2/18/2026	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0674 (06/b7/4)	0x32	baseline	0x133	10/8/2025	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0674 (06/b7/4)	0x36	baseline	0x137	2/18/2026	Intel Xeon E-2400 Series
Emerald Rapids SP	0xc06f2 (06/cf/2)	0x87	baseline	0x210002f4	3/2/2026	Intel Xeon 8500 Series; Intel Xeon Gold 6500/5500 Series; Intel Xeon Silver 4500 Series; Intel Xeon Bronze 3500 Series

The VF link state in NVIDIA NICs remains at "UP" regardless of the PF link state

For NVIDIA NICs, the VF link state does not follow the PF link state and always remains UP, even if the physical port link state changes to DOWN.

With ESX 9.1.1.0, in the NVIDIA nmlx5 driver you can configure the behavior of the VF link state. You need to download nmlxcli tools, which is an ESXCLI command line extension available on the NVIDIA website, on the ESXi host to configure PFs so that VFs follow the PF link state.

ESXi-9.1.1.0-25714478-standard

Profile Name	ESXi-9.1.1.0-25714478-standard
Build	For build information, see Patches Contained in This Release.
Vendor	Broadcom, Inc.
Release Date	September 3, 2026
Acceptance Level	Partner Supported
Affected Hardware	N/A
Affected Software	N/A

Affected VIBs	VMW_bootbank_atlantic_1.0.3.0-17vmw.911.0.25714478.vib, VMW_bootbank_bfedac-esxio_0.1-2vmw.911.0.25714478.vib, VMware_bootbank_bmcal_9.1.1-0.25714478.vib, VMware_bootbank_bmcal-esxio_9.1.1-0.25714478.vib, VMW_bootbank_bnxtnet_232.0.31.0-70vmw.911.0.25714478.vib, VMW_bootbank_bnxtroce_232.0.31.0-70vmw.911.0.25714478.vib, VMware_bootbank_clusterstore_9.1.1-0.25714478.vib, VMware_bootbank_cpu-microcode_9.1.1-0.25714478.vib, VMware_bootbank_crx_9.1.1-0.25714478.vib, VMware_bootbank_drivervm-gpu-base_9.1.1-0.25714478.vib, VMW_bootbank_dwi2c-esxio_0.1-17vmw.911.0.25714478.vib, VMware_bootbank_esx-base_9.1.1-0.25714478.vib, VMware_bootbank_esx-dvfilter-generic-fastpath_9.1.1-0.25714478.vib, VMware_bootbank_esx-ui_9.1.1-0.25714478.vib, VMware_bootbank_esx-update_9.1.1-0.25714478.vib, VMware_bootbank_esx-xserver_9.1.1-0.25714478.vib, VMware_bootbank_esxio_9.1.1-0.25714478.vib, VMware_bootbank_esxio-base_9.1.1-0.25714478.vib, VMware_bootbank_esxio-combiner_9.1.1-0.25714478.vib, VMware_bootbank_esxio-combiner-esxio_9.1.1-0.25714478.vib, VMware_bootbank_esxio-dvfilter-generic-fastpath_9.1.1-0.25714478.vib, VMware_bootbank_esxio-update_9.1.1-0.25714478.vib, VMware_bootbank_gc_9.1.1-0.25714478.vib, VMware_bootbank_gc-esxio_9.1.1-0.25714478.vib, VMW_bootbank_i40en_2.6.0.46-1vmw.911.0.25714478.vib, VMW_bootbank_iavmd_9.0.0.1100-7vmw.911.0.25714478.vib, VMW_bootbank_icen_1.15.0.5-1vmw.911.0.25714478.vib, VMware_bootbank_infravisor_9.0.0-25593624.vib, VMW_bootbank_irdman_1.5.0.5-1vmw.911.0.25714478.vib, VMW_bootbank_iser_1.1.0.5-1vmw.911.0.25714478.vib, VMW_bootbank_ixgben_1.7.1.50-1vmw.911.0.25714478.vib, VMware_bootbank_loadesx_9.1.1-0.25714478.vib, VMware_bootbank_loadesxio_9.1.1-0.25714478.vib, VMW_bootbank_lpfc_910.14.4.895.25-1vmw.911.0.25714478.vib, VMW_bootbank_lsi-mr3_7.736.02.00-3vmw.911.0.25714478.vib, VMW_bootbank_lsi-msgpt3_17.00.13.00-5vmw.911.0.25714478.vib, VMW_bootbank_lsi-msgpt35_37.00.00.00-2vmw.911.0.25714478.vib, VMware_bootbank_native-misc-drivers_911.0.25714478-dummyvmw.911.0.25714478.vib, VMware_bootbank_native-misc-drivers-esxio_911.0.25714478-dummyvmw.911.0.25714478.vib, VMW_bootbank_nfnic_5.0.0.45-4vmw.911.0.25714478.vib, VMW_bootbank_nhpsa_70.0051.0.100-6vmw.911.0.25714478.vib, VMW_bootbank_nmlx5-cc_4.25.1.2-1vmw.911.0.25714478.vib, VMW_bootbank_nmlx5-cc-esxio_4.25.1.2-1vmw.911.0.25714478.vib, VMW_bootbank_nmlx5-core_4.25.1.2-1vmw.911.0.25714478.vib, VMW_bootbank_nmlx5-core-esxio_4.25.1.2-1vmw.911.0.25714478.vib, VMW_bootbank_nmlx5-rdma_4.25.1.2-1vmw.911.0.25714478.vib, VMW_bootbank_nmlx5-rdma-esxio_4.25.1.2-1vmw.911.0.25714478.vib, VMW_bootbank_nmlxbf-gige-esxio_2.6-1vmw.911.0.25714478.vib, VMware_bootbank_nsx-adf_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-adf-esxio_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-cfgagent_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-cfgagent-esxio_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-context-mux_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-context-mux-esxio_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-cpp-libs_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-cpp-libs-esxio_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-esx-datapath_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-esx-datapath-esxio_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-exporter_9.1.1.0-9.1.25691512.vib, VMware_bootbank_nsx-

Related CVE numbers	N/A

This patch resolves the following issues:

ESX host might fail with a purple diagnostic screen after PCI passthrough on a PCI/PCIe device to a Linux or Windows VM

When you use PCI passthrough on a PCI/PCIe device to a Linux or Windows VM, including Nvidia GPUs, the VMs might not program the MSI/MSIx interrupts correctly during device probe. As a result, the ESX host either powers off the VM or fails with a purple diagnostic screen.

On the VM Summary page in the VMware Host Client, you see a false warning that the VM network portgroup does not exist

After a VCF deployment, the **VM Summary** page in the VMware Host Client might incorrectly display the warning `This VM is attached to a network portgroup undefined that doesn't exist` for VMs with network adapters connected to a Distributed Virtual Switch (DVS) portgroup. This issue occurs due to an underlying check for only recognized standard virtual switches and not identifying the portgroup for DVS-backed network adapters. As a result, you see a false-positive warning for every affected VM.

Due to vSAN disk failures, you might not see the vSAN File Service UI widget

vSAN File Service determines its supported version by evaluating the on-disk format versions across all disks in the cluster. If a disk in the cluster is in a Permanent Device Loss (PDL) state, such as Absent vSAN Disk, the vSAN File Service query might return an obsolete or inaccurate format version of that disk. As a result, the vSAN File Service might get an incorrect supported version and due to vSAN disk failures, the vSAN File Service UI widget might not display. This issue applies to both vSAN Original Storage Architecture (OSA) and vSAN Express Storage Architecture (ESA).

The fix skips PDL disks when calculating lowest disk format version.

Fault Domain Manager (FDM) might fail when vSphere High Availability (HA) is active in environments with Cisco NFNIC driver

The Cisco NFNIC driver might generate an excessively large volume of stats data and while attempting to retrieve and process such data, FDM might run out of memory and fail with a core dump at `/var/core/fdm-zdump`. In the `/var/run/log/fdm.log` file, you see errors such as `Unable to allocate memory` and under `/var/lib/vmware/hostd/stats dir`, you see large stats files.

Hot-add operation for an independent nonpersistent disk might fail for virtual machines hosted on vSphere Virtual Volumes datastores

When you restore VMs on ESX 8.0 Update 1 and later hosts from earlier ESX versions, hot-add operations for some of the restored disks hosted on vSphere Virtual Volumes datastores might fail due to a mismatch in the virtual volume namespace versions. The issue is specific for independent nonpersistent disks.

Configuring vSAN File Service with Active Directory domain fails with an error for exception caught when running preflight check on the file server

In the vSphere Client, when you create a file service domain with AD and click **Next**, you see an error such as:

`Failed to check domain configuration: Exception caught when running preflight check on file server.`

The issue occurs because querying the Active Directory domain for LDAP SRV records returns multiple duplicate entries for the same Domain Controller hostname. As a result, the pre-flight check script causes an exception and fails the file service enablement workflow.

A disk-only Storage vMotion operation might accidentally delete an orphaned virtual disk file on the destination datastore and cause data loss

When you perform a disk-only Storage vMotion, vCenter might not check if an orphaned virtual disk (VMDK) file - for example, one left behind by an earlier disk detach operation - is already present in the destination folder. As a result, the new file might get the same name as the existing VMDK and the migration task fails. The cleanup after such a failure might remove the pre-existing orphaned virtual disk file, and cause loss of that file's data.

Multiple ESX hosts might fail with a purple diagnostic screen due to a rare race condition in the NFSv4.1 client

On ESX hosts using the NFSv4.1 client, if a competing APD starts during an ongoing APD recovery, the file reclaim process creates duplicate insertions and causes pointer corruption. As a result, multiple ESX hosts might fail with a purple diagnostic screen.

VMware Tools Bundling Changes in ESX 9.1.1.0

The following VMware Tools ISO images are bundled with ESX 9.1.1.0:

- **windows.iso**: VMware Tools 13.1.5 supports 64-bit Windows versions - Windows 7 SP1 or Windows Server 2008 R2 SP1 and later.

The following VMware Tools ISO images are available for download:

- VMware Tools 12.5.4:
  - **windows.iso:** VMware Tools 12.5.4 supports 64-bit Windows versions.
  - **windows-x86.iso:** VMware Tools 12.4.9 supports 32-bit Windows versions.
  - **linux.iso**: VMware Tools 10.3.26 ISO image for Linux OS with glibc 2.11 or later.
- VMware Tools 11.0.6:
  - **windows.iso**: for Windows Vista (SP2) and Windows Server 2008 Service Pack 2 (SP2).
- VMware Tools 10.0.12:
  - **winPreVista.iso**: for Windows 2000, Windows XP, and Windows 2003.
  - **linuxPreGLibc25.iso**: supports Linux guest operating systems earlier than Red Hat Enterprise Linux (RHEL) 5, SUSE Linux Enterprise Server (SLES) 11, Ubuntu 7.04, and other distributions with **glibc** version earlier than 2.5.
- **solaris.iso**: VMware Tools image 10.3.10 for Solaris.
- **darwin.iso**: Supports Mac OS X versions 10.11 and later.

Follow the procedures listed in the following documents to download VMware Tools for platforms not bundled with ESX:

- VMware Tools 13.1.5 Release Notes
- VMware Tools for hosts provisioned with Auto Deploy
- Upgrading VMware Tools

ESX hosts might experience CPU utilization at around 100% after a port is quiesced in an Enhanced Network Stack (ENS) environment

When a network port is quiesced, the host network scheduler might fail to correctly update its internal byte counters after clearing pending packets. This mismatch causes the system to continually check for network traffic even when the queue is empty, resulting in the transmit (TX) process getting stuck in a loop and consuming up to 100% of CPU resources.

The fix ensures that internal byte counters are accurately updated when packets are dropped.

When using Link Aggregation Control Protocol (LACP), if a physical NIC is down, defined alarms might not trigger

When you configure an alarm based on Broadcom knowledge base article 378014, the alarm might not trigger in the vSphere Client if a physical NIC is down.

When resuming virtual machines configured with device groups containing DVX devices, the VMs might fail to power on

A power-on failure might occur when resuming a VM configured with a device group containing DVX devices.

Uplink gets reenabled before the time defined by the TeamPolicyUpDelay policy passes

The ESX advanced setting `Net.TeamPolicyUpDelay` sets a time before an uplink is reenabled after the link status changes from `DOWN` to `UP`. During such a wait period, new ports might be enabled for various reasons, such as migration, VM power cycle, or flapping of the network interface inside the guest OS. A newly powered-on vNIC can cause an uplink in `TeamPolicyUpDelay` state to reactivate prematurely for all VMs connected to the switch.

ESX hosts using Emulex Fibre Channel adapters might fail with a purple diagnostic screen after powering on virtual machines when Virtual Machine Identifier (VMID) is enabled

An issue in the Broadcom Emulex lpfc storage driver if VMID is enabled can cause an ESX host to fail with a purple diagnostic screen immediately after powering on virtual machines. The issue occurs due to an invalid memory access during Fibre Channel common transport command processing.

If ESX hosts share a LUN, you might overwrite VMFS volumes

If ESX hosts share a LUN and you create a VMFS volume on one of the hosts by using the VMware Host Client, the new volume might not be immediately visible on the other hosts and another user can create a VMFS volume on the same LUN from another Host Client session. As a result, the first VMFS datastore path might be overwritten.

The fix makes sure that while listing the available LUNs for new VMFS volumes, latest changes on the LUNs are fetched and considered.

A rare race condition in the lpfc driver might cause ESXi hosts to fail with a purple diagnostic screen during reboot or shutdown

On an ESXi host with Emulex LightPulse Fibre Channel adapters, a rare race condition in the lpfc driver can result in an invalid DMA access. This invalid access can lead to silent memory corruption, resulting in unpredictable system instability that might cause the ESX host to fail with a purple diagnostic screen, but since the memory corruption only affects the address range of the lpfc driver, it does not damage user VM data. The race condition only occurs during the device detachment phase, typically triggered during a reboot or when enabling PCI passthrough, and the probability of occurrence is low.

ESXi hosts using the lpfc driver do not provide log visibility for certain faulty small form-factor pluggable (SFP) optics

When an SFP module is present but non-functional, the Emulex Fibre Channel adapter firmware detects the fault and reports an error code. The lpfc driver does not capture or log that specific hardware error code into the vmkernel.log, which makes it difficult to identify and troubleshoot faulty optics.

The fix enhances the driver to properly log SFP hardware errors as they occur.

After an Emulex Fibre Channel adapter firmware upgrade, ESX hosts might fail with a purple diagnostic screen

When updating the firmware on certain Broadcom Emulex Fibre Channel adapters, the inbox lpfc driver might incorrectly handle a change in the internal resource counts during the subsequent host reboot. This mismatch can trigger an improper memory management condition during driver initialization or cleanup, leading to a purple diagnostic screen on the ESX host.

Emulex SAN Manager (ESM) does not display encryption details for certain Host Bus Adapters (HBAs)

An issue within the lpfc driver prevents ESM from properly retrieving data from all encryption-capable Emulex Fibre Channel adapters. This occurs due to a communication mismatch during fabric port initialization and link setup sequences between the ESX host and the switch.

ESX hosts using Emulex Fibre Channel adapters might fail with a purple diagnostic screen during reboot or shutdown due to a race condition

A race condition in the native lpfc driver can occur if a hardware error on an Emulex Host Bus Adapter (HBA) triggers while the driver is unloading. As a result, the ESXi host fails with a a purple diagnostic screen during reboot or shutdown with an error such as #`PF in lpfc_hw_info_setup()`.

ESX hosts with Emulex Fibre Channel HBAs might fail with a purple diagnostic screen during storage array upgrades

During the upgrade of certain Fibre Channel storage arrays, the target node IDs might change. As a result, the lpfc driver interprets the targets as offline and different targets coming online in a short period. Handling such cases might trigger a race condition in the lpfc driver, leading to failure of the ESX host with a purple diagnostic screen displaying an error such as `#PF Exception 14 in world <world_id>:lpfc_path_cl`.

Scheduling delays when high-priority processes are placed on a busy physical CPU might cause packets drop

When high-priority processes, for example in an Enhanced Network Stack (ENS) context, are placed on a busy physical CPU, they rely on the virtual CPU migration algorithm to move them to an idle or less busy CPU as appropriate. An issue with the migration algorithm might cause such processes to stay on the busy CPU for extended periods, causing significant scheduling delays, or high CPU Ready Time. As a result, you might see packets drop.

Log entries in the dfwpktlogs.log for distributed firewall (DFW) packets might occasionally split across two lines

Some log records for DFW packets might be written as two separate lines instead of one. When the split occurs within the record timestamp, the second line shows a system-generated timestamp rather than the original. For example

```
2026-03-11T05:57:28.172Z -NOTICE FIREWALL-PKTLOG 2100407 [nsx@4413] 2026-03-11
2026-03-11T05:57:28.176Z -NOTICE FIREWALL-PKTLOG 2100407 [nsx@4413] T05:57:28.172Z 4678804c INET6 match PASS
 1007 OUT 76 TCP 2001:db8:abcd:12::1001/23557->2001:db8:abcd:12::1501/80 S Cyperf_L4-rule
```

The issue only affects log formatting, no log data is lost and firewall enforcement is unaffected.You can read the full record by combining the split line with the partial record on the following line.

In the ESX Host Client, you do not see the option to add Sound Controller for virtual machines

In ESX Host Client version 9.1, under **Edit Settings > Virtual Hardware > Add New Device**, you do not see the **Sound Controller** option to configure audio hardware.

Setting the /Scsi/NvmeMaxUnmapBlockDescriptorLbaCount advanced configuration option does not correctly limit the Maximum Unmap LBA Count Per Descriptor for NVMe devices

When the advanced configuration option `/Scsi/NvmeMaxUnmapBlockDescriptorLbaCount` is set to a non-zero value for the Maximum Deallocate Range Size Limit, ESX incorrectly applies the same limit to the Maximum Unmap LBA Count Per Descriptor as for the Maximum Unmap Descriptor Count. As a result, the vSphere API for Array Integration (VAAI) cache reports incorrect UNMAP limits, which might cause UNMAP operations to behave unexpectedly with NVMe storage arrays.

When Intel SGX Flexible Launch Control (FLC) is set to unlocked in the ESX host firmware, VMs using vSGX might fail to power on after a Quick Boot

When SGX FLC is set to unlocked in the ESX host firmware, and a VM is configured to enable SGX with FLC, the hypervisor programs the associated FLC Model-Specific Register (MSRs) with guest-provided values. Such values persist during a Quick Boot, which might cause subsequent MSR uniformity checks to fail during boot. As a result, ESX might disable SGX on the host if it finds non-uniform values in the FLC MSRs during boot. The issue also impacts Pod VMs utilizing vSGX, such as the TDX Quote Pod.

Intel Xeon 6 processors utilizing QAT accelerators might see increased boot times on ESX 9.1

On Intel Xeon 6 processors systems using QAT devices, in some cases, the boot time for ESX hosts might increase.

In the VMware Host Client, you do not see vSAN data migration options while entering maintenance mode

When placing a vSAN host into maintenance mode by using the VMware Host Client in version 9.1, you might not see vSAN data migration options in the dialog box.

In the NSX Manager, you see unknown status for multiple ESX host metrics

In the NSX Manager, when you navigate to **System > Fabric > Hosts**, you see unknown status for multiple ESX host metrics, such as `Controller Connectivity`, `Tunnel Status`, and `PNIC/Bond Status`. The issue occurs because NSX requests high quality entropy for frequent use and consequently the default HWRNG entropy is exhausted and causes timeouts. Affected ESX hosts create an opsAgent core dump file: `/var/core/opsAgent-zdump`. During heavy load, multiple ESX hosts might be affected in batches. In the ESX log, `/var/run/log/nsx-syslog.log`, you see log messages such as:

```
Wa(###) nsx-opsagent[#######]: NSX ######## - [nsx@4413 comp="nsx-esx" subcomp="opsagent"
s2comp="nsx-core" tid="########" level="WARNING"] AsioNsxProvider: (0x##########-2) user
dispatcher blocked since 20 seconds.
```

The ESX agent hostd might intermittently fail or generate a core dump during gathering device statistics or socket disconnections

Under conditions of high-concurrency performance queries or unexpected connection drops, synchronization race conditions can occur. Such timing conflicts might cause internal tracking structures to be cleared prematurely and cause hostd to terminate unexpectedly.

A very rare race condition might cause an encrypted virtual machine to fail with a core dump

A very rare race condition might cause the VMX process on an ESX host to fail and cause an encrypted virtual machine to unexpectedly power off. In the `vmware.log` file you see an error such as: `PANIC: Unexpected signal: 6`.

In the VMkernel logs, you see multiple log messages for failed retrieval of ENS uplink distributed statistics

In environments using the Enhanced Network Stack (ENS), the VMkernel creates logs each time it fails to retrieve distributed statistics for an uplink port, even when the port does not support ENS. The error messages are `Fail to get uplink dist stats for ens port`. Such retrieval attempts can fail transiently under normal operating conditions and do not indicate an actual network problem, but might clutter VMkernel logs and cause unnecessary log noise, CPU overhead, and affect monitoring.

The fix demotes the `Fail to get uplink dist stats for ens port` error messages to debug-level logging and you do not see such in release builds.

Tunneled SSL from vCenter to ESX fails intermittently

In some cases, such as when traffic goes through a tunnel that terminated inside a guest virtual machine, an SSL connection from vCenter to the ESX host might intermittently fail.

In Advanced Settings, you do not see an option to configure a time window for consecutive login failures before locking user accounts

In ESX, user accounts are locked after a configurable number of consecutive login failures without a specific time window and you cannot configure such a window.

The fix updates the Pluggable Authentication Modules and adds the advanced ESX setting `Security.AccountLockFailInterval`, which allows you to set a time window for consecutive login failures before locking user accounts. `Security.AccountLockFailInterval` defaults to 15 min, but you can configure the time window accordingly.

IPFIX traffic might be blocked due to a missing route on a DPU ESX host

On a dual-DPU ESX host with offloading enabled, when you configure sending IPFIX data to a VCF Operations for networks collector but the IP address/netmask of the collector is in a different network that requires a gateway, IPFIX traffic might be blocked due to a missing route. In a non-DPU environment, you can configure a default gateway for VCF Operations, but you cannot create a default gateway in a DPU environment.

In rare cases, ESXi hosts might fail with a purple diagnostic screen during VMFS UNMAP operation

Under rare race conditions, ESXi hosts with VMFS datastores supporting UNMAP operations might fail with a purple diagnostic screen during an UNMAP task.

The esxtop utility reports inflated VMWAIT values

The calculation of VMWAIT, which is the percentage of time a VM waits for a VMkernel activity such as running I/O to complete before it can continue, uses the CPU WAIT and IDLE values. In some cases, the calculation might overestimate the CPU IDLE value and as a result, the VMWAIT value is much higher.

ESX 9.1.1.0 includes the following Intel microcode:

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Sandy Bridge DT	0x206a7 (06/2a/7)	0x12	baseline	0x2f	2/17/2019	Intel Xeon E3-1100 Series; Intel Xeon E3-1200 Series; Intel i7-2655-LE Series; Intel i3-2100 Series
Sandy Bridge EP	0x206d6 (06/2d/6)	0x6d	baseline	0x621	3/4/2020	Intel Pentium 1400 Series; Intel Xeon E5-1400 Series; Intel Xeon E5-1600 Series; Intel Xeon E5-2400 Series; Intel Xeon E5-2600 Series; Intel Xeon E5-4600 Series
Sandy Bridge EP	0x206d7 (06/2d/7)	0x6d	baseline	0x71a	3/24/2020	Intel Pentium 1400 Series; Intel Xeon E5-1400 Series; Intel Xeon E5-1600 Series; Intel Xeon E5-2400 Series; Intel Xeon E5-2600 Series; Intel Xeon E5-4600 Series
Ivy Bridge DT	0x306a9 (06/3a/9)	0x12	baseline	0x21	2/13/2019	Intel i3-3200 Series; Intel i7-3500-LE/UE; Intel i7-3600-QE; Intel Xeon E3-1200-v2 Series; Intel Xeon E3-1100-C-v2 Series; Intel Pentium B925C
Haswell DT	0x306c3 (06/3c/3)	0x32	baseline	0x28	11/12/2019	Intel Xeon E3-1200-v3 Series; Intel i7-4700-EQ Series; Intel i5-4500-TE Series; Intel i3-4300 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Ivy Bridge EP	0x306e4 (06/3e/4)	0xed	baseline	0x42e	3/14/2019	Intel Xeon E5-4600-v2 Series; Intel Xeon E5-2600-v2 Series; Intel Xeon E5-2400-v2 Series; Intel Xeon E5-1600-v2 Series; Intel Xeon E5-1400-v2 Series
Ivy Bridge EX	0x306e7 (06/3e/7)	0xed	baseline	0x715	3/14/2019	Intel Xeon E7-8800/4800/2800-v2 Series
Haswell EP	0x306f2 (06/3f/2)	0x6f	baseline	0x49	8/11/2021	Intel Xeon E5-4600-v3 Series; Intel Xeon E5-2600-v3 Series; Intel Xeon E5-2400-v3 Series; Intel Xeon E5-1600-v3 Series; Intel Xeon E5-1400-v3 Series
Haswell EX	0x306f4 (06/3f/4)	0x80	baseline	0x1a	5/24/2021	Intel Xeon E7-8800/4800-v3 Series
Broadwell H	0x40671 (06/47/1)	0x22	baseline	0x22	11/12/2019	Intel Core i7-5700EQ; Intel Xeon E3-1200-v4 Series
Avoton	0x406d8 (06/4d/8)	0x01	baseline	0x12d	9/16/2019	Intel Atom C2300 Series; Intel Atom C2500 Series; Intel Atom C2700 Series
Broadwell EP/EX	0x406f1 (06/4f/1)	0xef	baseline	0xb000040	5/19/2021	Intel Xeon E7-8800/4800-v4 Series; Intel Xeon E5-4600-v4 Series; Intel Xeon E5-2600-v4 Series; Intel Xeon E5-1600-v4 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Skylake SP	0x50654 (06/55/4)	0xb7	baseline	0x2007006	3/6/2023	Intel Xeon Platinum 8100 Series; Intel Xeon Gold 6100/5100, Silver 4100, Bronze 3100 Series; Intel Xeon D-2100 Series; Intel Xeon D-1600 Series; Intel Xeon W-3100 Series; Intel Xeon W-2100 Series
Cascade Lake B-0	0x50656 (06/55/6)	0xbf	baseline	0x4003901	12/12/2024	Intel Xeon Platinum 9200/8200 Series; Intel Xeon Gold 6200/5200; Intel Xeon Silver 4200/Bronze 3200; Intel Xeon W-3200
Cascade Lake	0x50657 (06/55/7)	0xbf	baseline	0x5003901	12/12/2024	Intel Xeon Platinum 9200/8200 Series; Intel Xeon Gold 6200/5200; Intel Xeon Silver 4200/Bronze 3200; Intel Xeon W-3200
Cooper Lake	0x5065b (06/55/b)	0xbf	baseline	0x7002b01	12/12/2024	Intel Xeon Platinum 8300 Series; Intel Xeon Gold 6300/5300
Broadwell DE	0x50662 (06/56/2)	0x10	baseline	0x1c	6/17/2019	Intel Xeon D-1500 Series
Broadwell DE	0x50663 (06/56/3)	0x10	baseline	0x700001c	6/12/2021	Intel Xeon D-1500 Series
Broadwell DE	0x50664 (06/56/4)	0x10	baseline	0xf00001a	6/12/2021	Intel Xeon D-1500 Series
Broadwell NS	0x50665 (06/56/5)	0x10	baseline	0xe000015	8/3/2023	Intel Xeon D-1600 Series
Skylake H/S	0x506e3 (06/5e/3)	0x36	baseline	0xf0	11/12/2021	Intel Xeon E3-1500-v5 Series; Intel Xeon E3-1200-v5 Series
Denverton	0x506f1 (06/5f/1)	0x01	baseline	0x3e	10/5/2023	Intel Atom C3000 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Ice Lake SP	0x606a6 (06/6a/6)	0x87	baseline	0xd000433	3/9/2026	Intel Xeon Platinum 8300 Series; Intel Xeon Gold 6300/5300 Series; Intel Xeon Silver 4300 Series
Ice Lake D	0x606c1 (06/6c/1)	0x10	baseline	0x1000301	3/9/2026	Intel Xeon D-2700 Series; Intel Xeon D-1700 Series
Snow Ridge	0x80665 (06/86/5)	0x01	baseline	0x4c000026	2/28/2024	Intel Atom P5000 Series
Snow Ridge	0x80667 (06/86/7)	0x01	baseline	0x4c000026	2/28/2024	Intel Atom P5000 Series
Tiger Lake U	0x806c1 (06/8c/1)	0x80	baseline	0xbe	7/24/2025	Intel Core i3/i5/ i7-1100 Series
Tiger Lake U Refresh	0x806c2 (06/8c/2)	0xc2	baseline	0x3e	7/24/2025	Intel Core i3/i5/ i7-1100 Series
Tiger Lake H	0x806d1 (06/8d/1)	0xc2	baseline	0x58	7/24/2025	Intel Xeon W-11000E Series
Sapphire Rapids SP HBM	0x806f8 (06/8f/8)	0x10	baseline	0x2c000435	3/2/2026	Intel Xeon Max 9400 Series
Sapphire Rapids SP	0x806f8 (06/8f/8)	0x87	baseline	0x2b000685	3/2/2026	Intel Xeon Platinum 8400 Series; Intel Xeon Gold 6400/5400 Series; Intel Xeon Silver 4400 Series; Intel Xeon Bronze 3400 Series
Kaby Lake H/S/X	0x906e9 (06/9e/9)	0x2a	baseline	0xf8	9/28/2023	Intel Xeon E3-1200-v6 Series; Intel Xeon E3-1500-v6 Series
Coffee Lake	0x906ea (06/9e/ a)	0x22	baseline	0xfa	7/28/2024	Intel Xeon E-2100 Series; Intel Xeon E-2200 Series (4 or 6 core)
Coffee Lake	0x906eb (06/9e/ b)	0x02	baseline	0xf6	2/1/2024	Intel Xeon E-2100 Series
Coffee Lake	0x906ec (06/9e/c)	0x22	baseline	0xf8	2/1/2024	Intel Xeon E-2100 Series
Coffee Lake Refresh	0x906ed (06/9e/ d)	0x22	baseline	0x104	11/14/2024	Intel Xeon E-2200 Series (8 core)
Rocket Lake S	0xa0671 (06/ a7/1)	0x02	baseline	0x66	2/12/2026	Intel Xeon E-2300 Series
Granite Rapids SP R1S	0xa06d1 (06/ ad/1)	0x20	baseline	0xa000151	3/24/2026	Intel Xeon 6500P/6700P/6900P Series
Granite Rapids AP/SP	0xa06d1 (06/ ad/1)	0x95	baseline	0x1000434	4/27/2026	Intel Xeon 6500P/6700P/6900P Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Sierra Forest	0xa06f3 (06/af/3)	0x01	baseline	0x30003b2	3/16/2026	Intel Xeon 6700E/6900E Series
Raptor Lake E/HX/S	0xb0671 (06/b7/1)	0x32	baseline	0x133	10/8/2025	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0671 (06/b7/1)	0x36	baseline	0x137	2/18/2026	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0674 (06/b7/4)	0x32	baseline	0x133	10/8/2025	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0674 (06/b7/4)	0x36	baseline	0x137	2/18/2026	Intel Xeon E-2400 Series
Emerald Rapids SP	0xc06f2 (06/cf/2)	0x87	baseline	0x210002f4	3/2/2026	Intel Xeon 8500 Series; Intel Xeon Gold 6500/5500 Series; Intel Xeon Silver 4500 Series; Intel Xeon Bronze 3500 Series

The VF link state in NVIDIA NICs remains at "UP" regardless of the PF link state

For NVIDIA NICs, the VF link state does not follow the PF link state and always remains UP, even if the physical port link state changes to DOWN.

With ESX 9.1.1.0, in the NVIDIA nmlx5 driver you can configure the behavior of the VF link state. You need to download nmlxcli tools, which is an ESXCLI command line extension available on the NVIDIA website, on the ESXi host to configure PFs so that VFs follow the PF link state.

ESXi-9.1.1.0-25714478-no-tools

Profile Name	ESXi-9.1.1.0-25714478-no-tools
Build	For build information, see Patches Contained in This Release.
Vendor	Broadcom, Inc.
Release Date	September 3, 2026
Acceptance Level	Partner Supported
Affected Hardware	N/A
Affected Software	N/A
Affected VIBs	Same list as in the ESXi-9.1.1.0-25714478-standard image profile except the VMware_locker_tools-light_13.1.5-0.25714478.vib
Related CVE numbers	N/A

This patch resolves the following issues:

ESX host might fail with a purple diagnostic screen after PCI passthrough on a PCI/PCIe device to a Linux or Windows VM

When you use PCI passthrough on a PCI/PCIe device to a Linux or Windows VM, including Nvidia GPUs, the VMs might not program the MSI/MSIx interrupts correctly during device probe. As a result, the ESX host either powers off the VM or fails with a purple diagnostic screen.

On the VM Summary page in the VMware Host Client, you see a false warning that the VM network portgroup does not exist

After a VCF deployment, the **VM Summary** page in the VMware Host Client might incorrectly display the warning `This VM is attached to a network portgroup undefined that doesn't exist` for VMs with network

adapters connected to a Distributed Virtual Switch (DVS) portgroup. This issue occurs due to an underlying check for only recognized standard virtual switches and not identifying the portgroup for DVS-backed network adapters. As a result, you see a false-positive warning for every affected VM.

Due to vSAN disk failures, you might not see the vSAN File Service UI widget

vSAN File Service determines its supported version by evaluating the on-disk format versions across all disks in the cluster. If a disk in the cluster is in a Permanent Device Loss (PDL) state, such as Absent vSAN Disk, the vSAN File Service query might return an obsolete or inaccurate format version of that disk. As a result, the vSAN File Service might get an incorrect supported version and due to vSAN disk failures, the vSAN File Service UI widget might not display. This issue applies to both vSAN Original Storage Architecture (OSA) and vSAN Express Storage Architecture (ESA).

The fix skips PDL disks when calculating lowest disk format version.

Fault Domain Manager (FDM) might fail when vSphere High Availability (HA) is active in environments with Cisco NFNIC driver

The Cisco NFNIC driver might generate an excessively large volume of stats data and while attempting to retrieve and process such data, FDM might run out of memory and fail with a core dump at `/var/core/fdm-zdump`. In the `/var/run/log/fdm.log` file, you see errors such as `Unable to allocate memory` and under `/var/lib/vmware/hostd/stats dir`, you see large stats files.

Hot-add operation for an independent nonpersistent disk might fail for virtual machines hosted on vSphere Virtual Volumes datastores

When you restore VMs on ESX 8.0 Update 1 and later hosts from earlier ESX versions, hot-add operations for some of the restored disks hosted on vSphere Virtual Volumes datastores might fail due to a mismatch in the virtual volume namespace versions. The issue is specific for independent nonpersistent disks.

Configuring vSAN File Service with Active Directory domain fails with an error for exception caught when running preflight check on the file server

In the vSphere Client, when you create a file service domain with AD and click **Next**, you see an error such as:

`Failed to check domain configuration: Exception caught when running preflight check on file server.`

The issue occurs because querying the Active Directory domain for LDAP SRV records returns multiple duplicate entries for the same Domain Controller hostname. As a result, the pre-flight check script causes an exception and fails the file service enablement workflow.

A disk-only Storage vMotion operation might accidentally delete an orphaned virtual disk file on the destination datastore and cause data loss

When you perform a disk-only Storage vMotion, vCenter might not check if an orphaned virtual disk (VMDK) file - for example, one left behind by an earlier disk detach operation - is already present in the destination folder. As a result, the new file might get the same name as the existing VMDK and the migration task fails. The cleanup after such a failure might remove the pre-existing orphaned virtual disk file, and cause loss of that file's data.

Multiple ESX hosts might fail with a purple diagnostic screen due to a rare race condition in the NFSv4.1 client

On ESX hosts using the NFSv4.1 client, if a competing APD starts during an ongoing APD recovery, the file reclaim process creates duplicate insertions and causes pointer corruption. As a result, multiple ESX hosts might fail with a purple diagnostic screen.

ESX hosts might experience CPU utilization at around 100% after a port is quiesced in an Enhanced Network Stack (ENS) environment

When a network port is quiesced, the host network scheduler might fail to correctly update its internal byte counters after clearing pending packets. This mismatch causes the system to continually check for network traffic even when the queue is empty, resulting in the transmit (TX) process getting stuck in a loop and consuming up to 100% of CPU resources.

The fix ensures that internal byte counters are accurately updated when packets are dropped.

When using Link Aggregation Control Protocol (LACP), if a physical NIC is down, defined alarms might not trigger

When you configure an alarm based on Broadcom knowledge base article 378014, the alarm might not trigger in the vSphere Client if a physical NIC is down.

When resuming virtual machines configured with device groups containing DVX devices, the VMs might fail to power on

A power-on failure might occur when resuming a VM configured with a device group containing DVX devices.

Uplink gets reenabled before the time defined by the TeamPolicyUpDelay policy passes

The ESX advanced setting `Net.TeamPolicyUpDelay` sets a time before an uplink is reenabled after the link status changes from `DOWN` to `UP`. During such a wait period, new ports might be enabled for various reasons, such as migration, VM power cycle, or flapping of the network interface inside the guest OS. A newly powered-on vNIC can cause an uplink in `TeamPolicyUpDelay` state to reactivate prematurely for all VMs connected to the switch.

ESX hosts using Emulex Fibre Channel adapters might fail with a purple diagnostic screen after powering on virtual machines when Virtual Machine Identifier (VMID) is enabled

An issue in the Broadcom Emulex lpfc storage driver if VMID is enabled can cause an ESX host to fail with a purple diagnostic screen immediately after powering on virtual machines. The issue occurs due to an invalid memory access during Fibre Channel common transport command processing.

If ESX hosts share a LUN, you might overwrite VMFS volumes

If ESX hosts share a LUN and you create a VMFS volume on one of the hosts by using the VMware Host Client, the new volume might not be immediately visible on the other hosts and another user can create a VMFS volume on the same LUN from another Host Client session. As a result, the first VMFS datastore path might be overwritten.

The fix makes sure that while listing the available LUNs for new VMFS volumes, latest changes on the LUNs are fetched and considered.

A rare race condition in the lpfc driver might cause ESXi hosts to fail with a purple diagnostic screen during reboot or shutdown

On an ESXi host with Emulex LightPulse Fibre Channel adapters, a rare race condition in the lpfc driver can result in an invalid DMA access. This invalid access can lead to silent memory corruption, resulting in unpredictable system instability that might cause the ESX host to fail with a purple diagnostic screen, but since the memory corruption only affects the address range of the lpfc driver, it does not damage user VM data. The race condition only occurs during the device detachment phase, typically triggered during a reboot or when enabling PCI passthrough, and the probability of occurrence is low.

ESXi hosts using the lpfc driver do not provide log visibility for certain faulty small form-factor pluggable (SFP) optics

When an SFP module is present but non-functional, the Emulex Fibre Channel adapter firmware detects the fault and reports an error code. The lpfc driver does not capture or log that specific hardware error code into the vmkernel.log, which makes it difficult to identify and troubleshoot faulty optics.

The fix enhances the driver to properly log SFP hardware errors as they occur.

After an Emulex Fibre Channel adapter firmware upgrade, ESX hosts might fail with a purple diagnostic screen

When updating the firmware on certain Broadcom Emulex Fibre Channel adapters, the inbox lpfc driver might incorrectly handle a change in the internal resource counts during the subsequent host reboot. This mismatch can trigger an improper memory management condition during driver initialization or cleanup, leading to a purple diagnostic screen on the ESX host.

Emulex SAN Manager (ESM) does not display encryption details for certain Host Bus Adapters (HBAs)

An issue within the lpfc driver prevents ESM from properly retrieving data from all encryption-capable Emulex Fibre Channel adapters. This occurs due to a communication mismatch during fabric port initialization and link setup sequences between the ESX host and the switch.

ESX hosts using Emulex Fibre Channel adapters might fail with a purple diagnostic screen during reboot or shutdown due to a race condition

A race condition in the native lpfc driver can occur if a hardware error on an Emulex Host Bus Adapter (HBA) triggers while the driver is unloading. As a result, the ESXi host fails with a a purple diagnostic screen during reboot or shutdown with an error such as #PF in lpfc_hw_info_setup().

ESX hosts with Emulex Fibre Channel HBAs might fail with a purple diagnostic screen during storage array upgrades

During the upgrade of certain Fibre Channel storage arrays, the target node IDs might change. As a result, the lpfc driver interprets the targets as offline and different targets coming online in a short period. Handling such cases might trigger a race condition in the lpfc driver, leading to failure of the ESX host with a purple diagnostic screen displaying an error such as #PF Exception 14 in world <world_id>:lpfc_path_cl.

Scheduling delays when high-priority processes are placed on a busy physical CPU might cause packets drop

When high-priority processes, for example in an Enhanced Network Stack (ENS) context, are placed on a busy physical CPU, they rely on the virtual CPU migration algorithm to move them to an idle or less busy CPU as appropriate. An issue with the migration algorithm might cause such processes to stay on the busy CPU for extended periods, causing significant scheduling delays, or high CPU Ready Time. As a result, you might see packets drop.

Log entries in the dfwpktlogs.log for distributed firewall (DFW) packets might occasionally split across two lines

Some log records for DFW packets might be written as two separate lines instead of one. When the split occurs within the record timestamp, the second line shows a system-generated timestamp rather than the original. For example

```
2026-03-11T05:57:28.172Z -NOTICE FIREWALL-PKTLOG 2100407 [nsx@4413] 2026-03-11
2026-03-11T05:57:28.176Z -NOTICE FIREWALL-PKTLOG 2100407 [nsx@4413] T05:57:28.172Z 4678804c INET6 match PASS
 1007 OUT 76 TCP 2001:db8:abcd:12::1001/23557->2001:db8:abcd:12::1501/80 S Cyperf_L4-rule
```

The issue only affects log formatting, no log data is lost and firewall enforcement is unaffected.You can read the full record by combining the split line with the partial record on the following line.

In the ESX Host Client, you do not see the option to add Sound Controller for virtual machines

In ESX Host Client version 9.1, under **Edit Settings > Virtual Hardware > Add New Device**, you do not see the **Sound Controller** option to configure audio hardware.

Setting the /Scsi/NvmeMaxUnmapBlockDescriptorLbaCount advanced configuration option does not correctly limit the Maximum Unmap LBA Count Per Descriptor for NVMe devices

When the advanced configuration option /Scsi/NvmeMaxUnmapBlockDescriptorLbaCount is set to a non-zero value for the Maximum Deallocate Range Size Limit, ESX incorrectly applies the same limit to the Maximum Unmap LBA Count Per Descriptor as for the Maximum Unmap Descriptor Count. As a result, the vSphere API for Array Integration (VAAI) cache reports incorrect UNMAP limits, which might cause UNMAP operations to behave unexpectedly with NVMe storage arrays.

When Intel SGX Flexible Launch Control (FLC) is set to unlocked in the ESX host firmware, VMs using vSGX might fail to power on after a Quick Boot

When SGX FLC is set to unlocked in the ESX host firmware, and a VM is configured to enable SGX with FLC, the hypervisor programs the associated FLC Model-Specific Register (MSRs) with guest-provided values. Such values persist during a Quick Boot, which might cause subsequent MSR uniformity checks to fail during boot. As a result, ESX might disable SGX on the host if it finds non-uniform values in the FLC MSRs during boot. The issue also impacts Pod VMs utilizing vSGX, such as the TDX Quote Pod.

Intel Xeon 6 processors utilizing QAT accelerators might see increased boot times on ESX 9.1

On Intel Xeon 6 processors systems using QAT devices, in some cases, the boot time for ESX hosts might increase.

In the VMware Host Client, you do not see vSAN data migration options while entering maintenance mode

When placing a vSAN host into maintenance mode by using the VMware Host Client in version 9.1, you might not see vSAN data migration options in the dialog box.

In the NSX Manager, you see unknown status for multiple ESX host metrics

In the NSX Manager, when you navigate to **System > Fabric > Hosts**, you see unknown status for multiple ESX host metrics, such as Controller Connectivity, Tunnel Status, and PNIC/Bond Status. The issue occurs because

NSX requests high quality entropy for frequent use and consequently the default HWRNG entropy is exhausted and causes timeouts. Affected ESX hosts create an opsAgent core dump file: `/var/core/opsAgent-zdump`. During heavy load, multiple ESX hosts might be affected in batches. In the ESX log, `/var/run/log/nsx-syslog.log`, you see log messages such as:

```
Wa(###) nsx-opsagent[#######]: NSX ######## - [nsx@4413 comp="nsx-esx" subcomp="opsagent"
s2comp="nsx-core" tid="########" level="WARNING"] AsioNsxProvider: (0x##########-2) user
dispatcher blocked since 20 seconds.
```

The ESX agent hostd might intermittently fail or generate a core dump during gathering device statistics or socket disconnections

Under conditions of high-concurrency performance queries or unexpected connection drops, synchronization race conditions can occur. Such timing conflicts might cause internal tracking structures to be cleared prematurely and cause hostd to terminate unexpectedly.

A very rare race condition might cause an encrypted virtual machine to fail with a core dump

A very rare race condition might cause the VMX process on an ESX host to fail and cause an encrypted virtual machine to unexpectedly power off. In the `vmware.log` file you see an error such as: `PANIC: Unexpected signal: 6`.

In the VMkernel logs, you see multiple log messages for failed retrieval of ENS uplink distributed statistics

In environments using the Enhanced Network Stack (ENS), the VMkernel creates logs each time it fails to retrieve distributed statistics for an uplink port, even when the port does not support ENS. The error messages are `Fail to get uplink dist stats for ens port`. Such retrieval attempts can fail transiently under normal operating conditions and do not indicate an actual network problem, but might clutter VMkernel logs and cause unnecessary log noise, CPU overhead, and affect monitoring.

The fix demotes the `Fail to get uplink dist stats for ens port` error messages to debug-level logging and you do not see such in release builds.

Tunneled SSL from vCenter to ESX fails intermittently

In some cases, such as when traffic goes through a tunnel that terminated inside a guest virtual machine, an SSL connection from vCenter to the ESX host might intermittently fail.

In Advanced Settings, you do not see an option to configure a time window for consecutive login failures before locking user accounts

In ESX, user accounts are locked after a configurable number of consecutive login failures without a specific time window and you cannot configure such a window.

The fix updates the Pluggable Authentication Modules and adds the advanced ESX setting `Security.AccountLockFailInterval`, which allows you to set a time window for consecutive login failures before locking user accounts. `Security.AccountLockFailInterval` defaults to 15 min, but you can configure the time window accordingly.

IPFIX traffic might be blocked due to a missing route on a DPU ESX host

On a dual-DPU ESX host with offloading enabled, when you configure sending IPFIX data to a VCF Operations for networks collector but the IP address/netmask of the collector is in a different network that requires a gateway, IPFIX traffic might be blocked due to a missing route. In a non-DPU environment, you can configure a default gateway for VCF Operations, but you cannot create a default gateway in a DPU environment.

In rare cases, ESXi hosts might fail with a purple diagnostic screen during VMFS UNMAP operation

Under rare race conditions, ESXi hosts with VMFS datastores supporting UNMAP operations might fail with a purple diagnostic screen during an UNMAP task.

The esxtop utility reports inflated VMWAIT values

The calculation of VMWAIT, which is the percentage of time a VM waits for a VMkernel activity such as running I/O to complete before it can continue, uses the CPU WAIT and IDLE values. In some cases, the calculation might overestimate the CPU IDLE value and as a result, the VMWAIT value is much higher.

ESX 9.1.1.0 includes the following Intel microcode:

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Sandy Bridge DT	0x206a7 (06/2a/7)	0x12	baseline	0x2f	2/17/2019	Intel Xeon E3-1100 Series; Intel Xeon E3-1200 Series; Intel i7-2655-LE Series; Intel i3-2100 Series
Sandy Bridge EP	0x206d6 (06/2d/6)	0x6d	baseline	0x621	3/4/2020	Intel Pentium 1400 Series; Intel Xeon E5-1400 Series; Intel Xeon E5-1600 Series; Intel Xeon E5-2400 Series; Intel Xeon E5-2600 Series; Intel Xeon E5-4600 Series
Sandy Bridge EP	0x206d7 (06/2d/7)	0x6d	baseline	0x71a	3/24/2020	Intel Pentium 1400 Series; Intel Xeon E5-1400 Series; Intel Xeon E5-1600 Series; Intel Xeon E5-2400 Series; Intel Xeon E5-2600 Series; Intel Xeon E5-4600 Series
Ivy Bridge DT	0x306a9 (06/3a/9)	0x12	baseline	0x21	2/13/2019	Intel i3-3200 Series; Intel i7-3500-LE/UE; Intel i7-3600-QE; Intel Xeon E3-1200-v2 Series; Intel Xeon E3-1100-C-v2 Series; Intel Pentium B925C
Haswell DT	0x306c3 (06/3c/3)	0x32	baseline	0x28	11/12/2019	Intel Xeon E3-1200-v3 Series; Intel i7-4700-EQ Series; Intel i5-4500-TE Series; Intel i3-4300 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Ivy Bridge EP	0x306e4 (06/3e/4)	0xed	baseline	0x42e	3/14/2019	Intel Xeon E5-4600-v2 Series; Intel Xeon E5-2600-v2 Series; Intel Xeon E5-2400-v2 Series; Intel Xeon E5-1600-v2 Series; Intel Xeon E5-1400-v2 Series
Ivy Bridge EX	0x306e7 (06/3e/7)	0xed	baseline	0x715	3/14/2019	Intel Xeon E7-8800/4800/2800-v2 Series
Haswell EP	0x306f2 (06/3f/2)	0x6f	baseline	0x49	8/11/2021	Intel Xeon E5-4600-v3 Series; Intel Xeon E5-2600-v3 Series; Intel Xeon E5-2400-v3 Series; Intel Xeon E5-1600-v3 Series; Intel Xeon E5-1400-v3 Series
Haswell EX	0x306f4 (06/3f/4)	0x80	baseline	0x1a	5/24/2021	Intel Xeon E7-8800/4800-v3 Series
Broadwell H	0x40671 (06/47/1)	0x22	baseline	0x22	11/12/2019	Intel Core i7-5700EQ; Intel Xeon E3-1200-v4 Series
Avoton	0x406d8 (06/4d/8)	0x01	baseline	0x12d	9/16/2019	Intel Atom C2300 Series; Intel Atom C2500 Series; Intel Atom C2700 Series
Broadwell EP/EX	0x406f1 (06/4f/1)	0xef	baseline	0xb000040	5/19/2021	Intel Xeon E7-8800/4800-v4 Series; Intel Xeon E5-4600-v4 Series; Intel Xeon E5-2600-v4 Series; Intel Xeon E5-1600-v4 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Skylake SP	0x50654 (06/55/4)	0xb7	baseline	0x2007006	3/6/2023	Intel Xeon Platinum 8100 Series; Intel Xeon Gold 6100/5100, Silver 4100, Bronze 3100 Series; Intel Xeon D-2100 Series; Intel Xeon D-1600 Series; Intel Xeon W-3100 Series; Intel Xeon W-2100 Series
Cascade Lake B-0	0x50656 (06/55/6)	0xbf	baseline	0x4003901	12/12/2024	Intel Xeon Platinum 9200/8200 Series; Intel Xeon Gold 6200/5200; Intel Xeon Silver 4200/Bronze 3200; Intel Xeon W-3200
Cascade Lake	0x50657 (06/55/7)	0xbf	baseline	0x5003901	12/12/2024	Intel Xeon Platinum 9200/8200 Series; Intel Xeon Gold 6200/5200; Intel Xeon Silver 4200/Bronze 3200; Intel Xeon W-3200
Cooper Lake	0x5065b (06/55/b)	0xbf	baseline	0x7002b01	12/12/2024	Intel Xeon Platinum 8300 Series; Intel Xeon Gold 6300/5300
Broadwell DE	0x50662 (06/56/2)	0x10	baseline	0x1c	6/17/2019	Intel Xeon D-1500 Series
Broadwell DE	0x50663 (06/56/3)	0x10	baseline	0x700001c	6/12/2021	Intel Xeon D-1500 Series
Broadwell DE	0x50664 (06/56/4)	0x10	baseline	0xf00001a	6/12/2021	Intel Xeon D-1500 Series
Broadwell NS	0x50665 (06/56/5)	0x10	baseline	0xe000015	8/3/2023	Intel Xeon D-1600 Series
Skylake H/S	0x506e3 (06/5e/3)	0x36	baseline	0xf0	11/12/2021	Intel Xeon E3-1500-v5 Series; Intel Xeon E3-1200-v5 Series
Denverton	0x506f1 (06/5f/1)	0x01	baseline	0x3e	10/5/2023	Intel Atom C3000 Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Ice Lake SP	0x606a6 (06/6a/6)	0x87	baseline	0xd000433	3/9/2026	Intel Xeon Platinum 8300 Series; Intel Xeon Gold 6300/5300 Series; Intel Xeon Silver 4300 Series
Ice Lake D	0x606c1 (06/6c/1)	0x10	baseline	0x1000301	3/9/2026	Intel Xeon D-2700 Series; Intel Xeon D-1700 Series
Snow Ridge	0x80665 (06/86/5)	0x01	baseline	0x4c000026	2/28/2024	Intel Atom P5000 Series
Snow Ridge	0x80667 (06/86/7)	0x01	baseline	0x4c000026	2/28/2024	Intel Atom P5000 Series
Tiger Lake U	0x806c1 (06/8c/1)	0x80	baseline	0xbe	7/24/2025	Intel Core i3/i5/ i7-1100 Series
Tiger Lake U Refresh	0x806c2 (06/8c/2)	0xc2	baseline	0x3e	7/24/2025	Intel Core i3/i5/ i7-1100 Series
Tiger Lake H	0x806d1 (06/8d/1)	0xc2	baseline	0x58	7/24/2025	Intel Xeon W-11000E Series
Sapphire Rapids SP HBM	0x806f8 (06/8f/8)	0x10	baseline	0x2c000435	3/2/2026	Intel Xeon Max 9400 Series
Sapphire Rapids SP	0x806f8 (06/8f/8)	0x87	baseline	0x2b000685	3/2/2026	Intel Xeon Platinum 8400 Series; Intel Xeon Gold 6400/5400 Series; Intel Xeon Silver 4400 Series; Intel Xeon Bronze 3400 Series
Kaby Lake H/S/X	0x906e9 (06/9e/9)	0x2a	baseline	0xf8	9/28/2023	Intel Xeon E3-1200-v6 Series; Intel Xeon E3-1500-v6 Series
Coffee Lake	0x906ea (06/9e/ a)	0x22	baseline	0xfa	7/28/2024	Intel Xeon E-2100 Series; Intel Xeon E-2200 Series (4 or 6 core)
Coffee Lake	0x906eb (06/9e/ b)	0x02	baseline	0xf6	2/1/2024	Intel Xeon E-2100 Series
Coffee Lake	0x906ec (06/9e/c)	0x22	baseline	0xf8	2/1/2024	Intel Xeon E-2100 Series
Coffee Lake Refresh	0x906ed (06/9e/ d)	0x22	baseline	0x104	11/14/2024	Intel Xeon E-2200 Series (8 core)
Rocket Lake S	0xa0671 (06/ a7/1)	0x02	baseline	0x66	2/12/2026	Intel Xeon E-2300 Series
Granite Rapids SP R1S	0xa06d1 (06/ ad/1)	0x20	baseline	0xa000151	3/24/2026	Intel Xeon 6500P/6700P/6900P Series
Granite Rapids AP/SP	0xa06d1 (06/ ad/1)	0x95	baseline	0x1000434	4/27/2026	Intel Xeon 6500P/6700P/6900P Series

Code Name	FMS	Plat ID	Servicing	MCU Rev	MCU Date	Brand Names
Sierra Forest	0xa06f3 (06/af/3)	0x01	baseline	0x30003b2	3/16/2026	Intel Xeon 6700E/6900E Series
Raptor Lake E/HX/S	0xb0671 (06/b7/1)	0x32	baseline	0x133	10/8/2025	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0671 (06/b7/1)	0x36	baseline	0x137	2/18/2026	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0674 (06/b7/4)	0x32	baseline	0x133	10/8/2025	Intel Xeon E-2400 Series
Raptor Lake E/HX/S	0xb0674 (06/b7/4)	0x36	baseline	0x137	2/18/2026	Intel Xeon E-2400 Series
Emerald Rapids SP	0xc06f2 (06/cf/2)	0x87	baseline	0x210002f4	3/2/2026	Intel Xeon 8500 Series; Intel Xeon Gold 6500/5500 Series; Intel Xeon Silver 4500 Series; Intel Xeon Bronze 3500 Series

The VF link state in NVIDIA NICs remains at "UP" regardless of the PF link state

For NVIDIA NICs, the VF link state does not follow the PF link state and always remains UP, even if the physical port link state changes to DOWN.

With ESX 9.1.1.0, in the NVIDIA nmlx5 driver you can configure the behavior of the VF link state. You need to download nmlxcli tools, which is an ESXCLI command line extension available on the NVIDIA website, on the ESXi host to configure PFs so that VFs follow the PF link state.

Known Issues

CLI and API Issues

The AcquireTicket API returns a ticket containing empty sslThumbprint and third-party solutions might fail to open a VM console

As part of security hardening in VCF 9.1.1.0, ESX no longer supports SHA1 and the `sslThumbprint` field that contains the SHA1 thumbprint of the SSL certificate of the ESX host issuing the ticket is empty by default. Setting the advanced option `Config.HostAgent.ticketing.thumbprintTypes` to include SHA1 as a thumbprint type is also not supported. As a result, third-party VM console solutions that are not updated to support SHA256 might fail to open a VM console. The changes does not affect opening a VM console by using the ESX Host Client, the vSphere Client, or the VMware Remote Console (VMRC). You can also use PowerCLI after updating your environment to 9.1.1.0.

Workaround: None. Instead of the `sslThumbprint` field, use the `sslCertificate` field, which contains the full PEM-encoded SSL certificate. If a thumbprint is required, the `certThumbprintList` field contains at least one entry representing the SHA256 thumbprint of the SSL certificate of the host issuing the ticket.

vSAN 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Getting to 9.1.1
- Resolved Issues
- Known Issues

Introduction

VMware vSAN 9.1.1.0 | 03 SEP 2026 |
VMware vSAN ESA Witness 9.1.1.0 | 03 SEP 2026 | Build 25714474
VMware vSAN OSA Witness 9.1.0.0 | 03 SEP 2026 | Build 25714473
VMware vSAN File Services 9.1.0.0 | 03 SEP 2026 | Build 25714478
Check for additions and updates to these release notes.

What's New

vSAN Topologies support in CNS - Qualification/Validation

In VCF 9.1.1, VMware Cloud Foundation Automation makes cloud management simple for both administrators and developers by providing fully validated core services across various vSAN storage topologies, allowing users to seamlessly run traditional and cloud-native applications.

VCF Native Object Store - 9.1.1 Tech Preview

VCF 9.1.1 introduces a Tech Preview of native, S3-compatible object storage built directly into vSAN. By eliminating the need for third-party add-ons, native object storage provides a unified, scalable, and multi-tenant object storage platform for modern workloads.

Getting to 9.1.1

For information about deploying, converging, upgrading or patching your environment to 9.1.1, see Getting to 9.1.1.

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

UpdateDatastoreSource API fails for Cross vCenter service account password reset

In a Cross-vCenter environment, attempting to reset the service account password for a server vCenter by invoking the UpdateDatastoreSource API on the client vCenter would fail.

This issue occured when a client cluster mounted a remote vSAN datastore managed by a separate vCenter instance, and that remote datastore's owner vCenter was running version 9.1.0.0 EP2.

This has been fixed.

The vSAN File Service with vSAN RDMA enabled went to an unhealthy state after upgrading from vSAN 7.x to vSAN 8.x

After upgrading vSAN environment to 8.x, the vSAN File Service was in an unhealthy state, with vSAN RDMA enabled.

This issue no longer occurs after upgrading to VCF 9.1.1.

The vSAN File Service temporarily returned incorrect file-size in metadata over NFS.

The vSAN File Service was temporarily returning incorrect file-sizes in metadata over NFS. This issue occurred rarely when multiple writes were being sent from an NFS client, with the writes causing the file size to increase. After the metadata cache expires or was correctly updated, however, the NFS server started returning correct metadata.

This issue has been fixed.

Known Issues

Applying Host Profiles containing vSAN OSA or ESA configuration deltas to ESXi hosts fails with a generic 'vim.fault.HostConfigFailed' or 'ClusterUUID MethodFault' error.

When remediating a host profile with vSAN configuration differences across hosts in a cluster, the batch remediation task fails on all target hosts. This issue applies to both vSAN ESA and vSAN OSA.

The vSphere Client UI reports a non-descriptive error summary displaying Error: 'ClusterUUID'. Individual per-host applyHostConfig tasks fail with an error status, while log entries indicate access denials to vSAN VSI nodes.

This issue prevents users from being able to standardize vSAN cluster configurations or apply host profiles when vSAN configuration differences exist between the profile and target hosts.

Non-vSAN settings can only be remediated if vSAN configuration deltas are completely eliminated prior to profile application.

Workaround:

To apply non-vSAN configuration changes via host profiles, ensure there is no delta in the vSAN configuration by disabling or aligning the vSAN sub-profile settings prior to remediation. While applying the non-vSAN configuration through host profile, de-select the vSAN configuration.

For managing and standardizing vSAN cluster settings, use vSphere Configuration Profiles (VCP) or the vSAN Cluster QuickStart -> Configuration wizard.

vSAN File Service — upgrade order requirement for 172.17.x.x subnet users

If you use IP addresses in the 172.17.x.x subnet for vSAN File Service domains or shares, upgrade the ESX host to version 9.1.1 before upgrading the FSVM. Upgrading the FSVM ahead of the ESX host can cause the FSVM's internal Docker bridge network to reclaim the 172.17.0.0/16 range, conflicting with File Service domain/share IPs in that subnet.

NSX 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Getting to 9.1.1
- Known Issues
- Resolved Issues

Introduction

NSX 9.1.1.0 | 03 SEP 2026 | Build 25691509

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and the following new features.

- Introduces an Active/Active (A/A) deployment option for EVPN Route Controllers in Distributed Transit Gateway (DTGW) topologies. All active Route Controller nodes establish independent BGP sessions directly to external EVPN gateways (BGWs), which increases resiliency and availability during failure and maintenance scenarios.
- Starting with this release, the Distributed VXLAN Connectivity model supports EVPN-VXLAN Direct Prefix Routing. This feature optimizes traffic forwarding and reduces packet processing overhead on the EVPN gateway by establishing a direct VXLAN tunnel between the ESXi VTEP and the physical VXLAN leaf switch VTEP. The feature is configurable per external connection on the Distributed VXLAN connection and creates a hybrid forwarding mode by letting the designated latency-sensitive storage traffic (such as NFS and S3/object storage) bypass the EVPN gateway and letting other traffic continue using the standard EVPN Gateway path.
- Administrators can now reallocate CPU cores on NSX Edge nodes from services to the packet data path for greater performance and improved tuning. This feature provides optimized throughput during peak demand while maintaining flexibility in resource allocation. Predefined CPU allocation profiles are available for both VM and bare metal NSX Edge nodes.
- This release extends advanced networking services (such as NAT, load balancing, and DHCP relay) to support EVPN-VXLAN distributed connectivity in VMware Cloud Foundation, enabling critical multi-tenant and external connectivity capabilities at the VPC and transit gateway levels for key customer deployments. To enable support for this feature follow the procedure in Enable Advanced Networking Services for Distributed VXLAN Connections.
- Multi-tenant EVPN-VXLAN distributed external connectivity is supported for VCF Automation and vSphere Supervisor. Provider admins can create VXLAN external connections and allocate them to target organizations, allowing org admins to seamlessly attach them to their Transit Gateways.
- Introduces vSphere Distributed Switch sharing across multiple clusters in a VCF domain, reducing switch provisioning overhead and ensuring consistent network configuration and policies across clusters.

- This release introduces support for DHCP Relay in distributed VPC environments with EVPN-VXLAN and VLAN external connectivity. This feature simplifies IP address management by allowing workloads across VPCs to obtain IP addresses from external for NSX DHCP servers while leveraging distributed external connectivity. DHCP Relay is supported for VPC public subnets only; private subnets are not supported.
- Introduces a new predefined role, Cloud Partner Auditor, for Microsoft Azure VMware Solution (AVS). This role is specifically designed for cloud partners that require less access than Cloud Partner Admin to networking and security services.
- Administrators can use the NSX API to change the host_switch_mode of host transport nodes between Legacy and Standard without having to place the ESX host in maintenance mode.
- This release introduces support for a VLAN-backed VPC (networking model without TEPs) under the Distributed Transit Gateway. In a VLAN-backed VPC model, all traffic flows directly on physical VLANs without the overlay encapsulation. It does not support private subnets as the IP scheme is limited to the CIDRs backed by physical VLANs. This is the default model during a VCF import.

Getting to 9.1.1

For information about deploying, converging, upgrading or patching your environment to 9.1.1, see Getting to 9.1.1.

Known Issues

ESX host goes to the Install Failed state immediately after upgrade to version 9.1.1.0 if DFW is enabled globally.

DFW services on host might not function correctly. This issue is applicable to only the standalone hosts.

Workaround:

After the upgrade completes, go to **System > Fabric > Cluster** or **Other Nodes** and resolve the `Install Failed` issue.

The ESX host should now show `Install Success`.

While upgrade is in progress, the system is in "pinned mode" in which it continues to behave as before the upgrade. The login page to mimic 4.2.x is called the legacy login page, which contains errors. Also, the "redirect URI" used twice during SSO processing through VIDM is changed, which means that VIDM log in will not work properly.

Users can't use the UI to complete the upgrade process.

Workaround:

Backups cannot be taken when NSX Manager is stuck in a terminal state.

Impact is low because there is a workaround, which is to restart proton on each Manager.

Workaround:

Restart Proton on each NSX Manager.

CM-inventory error is seen in cm-inventory.log: Failed to import the trusted root certificate for compute manager XXX. Try again". Proton error is seen in nsxapi.log: Certificate cannot be deleted because it is used by 3 MP node(s).

NSX unusable because it cannot be re-registered with vCenter.

Workaround:

1. On the LM where the error is seen, remove all "REMOTE" site certificates by using the following steps:
   a. Find all site IDs for REMOTE site certificates:
      curl -s http://127.0.0.1:7440/nsxapi/api/v1/trust-management/site-certificates | grep -B 3 'site_type\" : \"REMOTE' | grep site_id | sort | uniq
   b. For each site ID, delete the REMOTE site certificates as seen on the LM:
      curl -i -H 'X-NSX-Username:admin' -X DELETE http://127.0.0.1:7440/nsxapi/api/v1/trust-management/site-certificates/$SITE_ID
   c. Check that all REMOTE site certificates have been removed by repeating Step a. The output should be empty.
2. Repeat the registration of NSX with vCenter.

3. On the other sites, specifically the GM and the other LM, refresh the site certificates (this is a push operation that pushes the site certificates to all sites including the LM where the site certificates were deleted):
   curl -i -X POST -H "Content-Type: application/json" -H 'X-NSX-Username:admin' http://127.0.0.1:7441/api/v1/sites?action=refresh

On NSX Edges with dynamic BGP neighbors configured, customers might observe NSX Edge CLI commands such as ‘get route’ hanging or timing out, and routing/FIB convergence failures logged as repeated EDG0100012 ("Waiting for RT stack flush start... ignore FIB update") errors in the edge logs. The edge's routing state stops updating, new and withdrawn routes are not reflected in the forwarding table, and any new configuration pushed to the affected edge from NSX Manager (for example, new BGP neighbors, route-maps, static routes, VRF changes) is also not realized until the affected process is manually restarted.

Edges using only statically configured BGP neighbors are not exposed to this issue.

On edges with dynamic BGP neighbors configured, once the RCPM deadlock is triggered, the affected tier-0 Service Router's routing control plane stops converging and routes learned or withdrawn after the deadlock begins are not propagated to the dataplane. This causes stale forwarding behavior for prefixes that change after the onset. In addition, configuration changes made from NSX Manager after the deadlock begins will not take effect on the affected edge. The condition does not self-recover; it persists until RCPM (and in some cases nsxa) is restarted during which time routing updates for the affected edge are not processed. Edge CLI-based troubleshooting (such as get route) might also be unresponsive during the affected window.

Workaround:

Restart the RCPM service (and nsxa, if it has also stopped processing updates) on the affected edge to clear the deadlocked state and restore routing convergence. As a preventive measure, edges that do not require dynamic BGP neighbors can avoid exposure to this issue by using static BGP neighbor configuration only.

Resolved Issues

On a DFW enabled host that is in INSTALL_SUCCESSFUL state, the nsx-scx service is in stopped state.

DFW enforcement, which requires nsx-scx will not be active on affected hosts despite the NSX UI displaying a healthy fabric status, creates a false impression of full DFW configuration. Management plane connectivity and other host services remain completely unaffected.

When a tier-1 gateway has a static route configured with NULL next hop (:: for IPv6, 0.0.0.0 for IPv4), cfgAgent correctly sets nhType = VDR_ROUTE_NEXTHOP_INTERFACE for both the address families. The IPv6 Route update processing does not handle host Route with VDR_ROUTE_NEXTHOP_INTERFACE.

RPF failure drops count 931287+ at interface 971c5440-ab99-4e7f-96d4-58e0317f629c.

During uninstalling NSX, NSX Manager shows transport nodes in orphaned state and the hosts lose connectivity. Logging into the host through console and checking net-dvs -l shows that the 'com.vmware.vswitch.disabled' property on the host switch is set 'false'.

Hosts lose connectivity and transport nodes go into the orphaned state in NSX. To recover the host connectivity, users have to log in to the host through the console and set 'com.vmware.vswitch.disabled' to 'true'. Afterwards, users will need to delete and cleanup any leftover NSX transport node configuration.

The customer's issue is cosmetic. False negative status is reported.

The bug blocks customers from seeing the actual status as it always shows an error, but it does not block setting the configuration.

LDAP sessions are revalidated by default every 5 minutes. Because of this bug, revalidation will always fail, the session will be terminated, and the UI user will be logged out.

LDAP UI user will be logged out after 5 minutes.

Group memberships may take long time, sometimes more than 24 hours, to reflect the correct members. nsx-ccp logs will show frequent "TX Abort merge" errors such as nsx$DynamicGroupMemberComputationResult org.corfudb.runtime.exceptions.StaleRevisionUpdateException: Update on stale revision. LSPs churn is causing re-evaluation of impacted groups very frequently leading to the same groups being updated in DB frequently.

Sometimes these frequent DB updates lead to the stale revision exception which triggers CCP retry logic which is not efficient leading to delay in group membership evaluation.

Since the groups are not updating quickly, Distributed Firewall (DFW) rules end up using outdated information. This can cause traffic to be incorrectly allowed or blocked, which disrupts a customer's security policies.

Customers see consistent warnings and intermittent "Discovery Failed" errors when running Security Intelligence policy recommendations.

Automated policy generation is halted that stalls micro-segmentation projects. Applications intended to be protected by these policies remain exposed to security risks until the issue is manually worked around.

Following a floating IP or EgressIP failover event, network traffic continues to route to the former IP owner causing a data path disruption. Checking the logical switch ARP table reveals stale MAC addresses mapped to the active IP address. These invalid records persist indefinitely in the host's NestDB and cannot be cleared by restarting the host-side cfgagent or opsagent services.

This issue results in a production platform outage, which misroutes application traffic and disrupts end-user access to impacted cluster services. The communication failure affects all ESX hosts shared to the specific controller node holding the stale record.

Host live upgrades fail with a traceback RunCommandError: Output from command ... exceeds 1048576 bytes. Memory usage in net-vdl2 increases linearly during the backup loop, and BFD multipliers may reset to 0, causing session flapping.

Lifecycle upgrades fail completely in scale environments with over 1,000 BFD sessions requiring manual host reboots or recovery steps. This extends maintenance windows and increases administrative overhead.

The original code checked only the most recent 1024-byte PTY read chunk against the prompt regex; if the kernel delivered "sftp> " split across two or more reads, the prompt was never matched. This left the sftp subprocess waiting for input that never came. Because support bundle generation internally invoked the Backup List API (which lists all backup files over SFTP), the hang/slowness surfaced as support bundle generation taking excessively long or appearing stuck, especially with many existing backups.

Support bundle collection could hang or take a very long time to complete on NSX Manager nodes with SFTP-based backup configured delaying troubleshooting/case data collection. No data loss or corruption occurs. This is an availability and a latency impact on the backup and support-bundle workflows only.

The BgpNeighborState runbook does not collect any stats if the BGP peer is in the ESTABLISHED state.

No functional impact, but customers want to check their setup health in general by running the ODS runbook diagnostics like ping test, packet captures and traceroute.

During a brief IPsec/IKE session flap (for example, triggered by a missed IKE rekey and hard-lifetime expiry), the tunnel is torn down and re-established within the same second with no real data-plane impact. However, the L2VPN_session_DOWN alarm raised at the moment of the flap does not clear immediately. It persists for roughly two minutes before the alarm-resolution logic finally catches up, because the retry timer needed to detect the recovered/UP state was not being (re)armed in all conditions.

Monitoring and alerting systems report a false L2VPN outage of around two minutes even though the tunnel actually recovered instantly with no observed traffic loss.

Workload VMs experience packet drops when co-located on the same ESX host as the edge node. The issue persists when i) the Edge Uplink Profile transport VLAN is unset or set to 0. ii) The Edge VTEP fastpath (fp-ethx) interface is connected to a non-trunk Distributed Virtual Port Group (DVPG). iii) Both the Edge VTEP and management/VLAN Host Switch interfaces are connected to VLAN-tagged DVPGs.

Customers using the specific configuration described above will experience datapath traffic interruptions due to packet drops for workload VMs residing on the same host as the edge node.

Edge Services DHCP opened port 1167 for DHCP leases sync. It used four ciphers for handshake in which two non-AEAD ciphers are identified as weak, but are not excluded.

Customers are exposed to cryptographic vulnerabilities (specifically non-AEAD cipher risks) on the DHCP HA sync port that potentially compromises the security of Edge Services.

Improve DLB upgrade precheck message and add KB number 440901 in the precheck message to make it more clear for users.

Users could see the precheck warnings and errors, but were not aware on how to proceed as it was not documented.

The traffic of L4 virtual server in the Load Balancer (LB) might fail after failover even when the LB connection mirror is enabled.

The system faces LB traffic interruption.

Allocation for a tier-1 shows member index as -1. Relocate and remove operation will not succeed and may end up allocating the context to one of the DOWN edge nodes, or upon the same source edge node.

Tier-1 gateway ends with erroneous allocation on an ineligible edge member index.

After removing edge transport nodes from a cluster, the nodes still appear as selectable options for consumption in the UI.

Stale edge transport nodes are displayed as cluster members in the NSX UI as available for consumption, which causes failure if a user selects them.

An unconditional write in the ArpTableConfig table caused a Corfu compactor out-of-memory (OOM) error, which resulted in continuous Proton restarts and overall system instability.

Proton experienced out-of-memory errors leading to overall system instability and multiple restarts.

Users configuring static routes on a tier-1 with connected service interface (CSP) or the service interface as a next hop do not see the route on the tier-1 DR or ESX hosts. Forwarding on DR to this network relies on the default route on DR and then the route gets resolved on SR on the edge. If a user has an overlapping or bigger prefix on the tier-1 DR, the default route path for the static route will not be taken.

Users are not able to get forwarding through a tier-1 static route with the service interface next hop in case of overlapping network routes on the concerned tier-1 gateway.

On a transit gateway and tier-0 gateway, users can see the stale advertised prefix from a deleted VPC static route for AVI. The prefix used in deleted AVI VPC static route is reused for a different service like NAT, but the traffic doesn't work for the new service.

User traffic can be affected for a new service like NAT when a deleted VPC static route for AVIs public IP/prefix is reused in the new service.

On the NSX UI, selecting edges for tier-0 uplinks or setting preferred edges for tier-1 lists the same edge node twice.

Edge cluster member replacement leads to old edge still hosting logical entities.

When a tier-1 gateway with "All NAT IPs" route advertisement and an SNAT rule (translated IP from tier-0 external subnet) is deleted, the ARP proxy entries on tier-0 gateway's external interface are not removed.

Invalid ARP proxy entries remain in the system and cannot be removed.

Host PSOD.

Intermittent display of PSOD by a host if the host switch mode is EDP Standard, vNIC is e1000, and the guest VM enables TSO and sends a large TCP packet.

VCF Installer / SDDC Manager 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Getting to 9.1.1
- Resolved Issues
- Known Issues

Introduction

VCF Installer / SDDC Manager 9.1.1.0 | 03 SEP 2026 | Build 25713928

Check for additions and updates to these release notes.

What's New

Reduced resource footprint for VCF management services

VCF management services now require less compute and memory resources for all deployment sizes. For sizing details, see the VCF 9.1.1 Planning and Preparation Workbook. To reduce the footprint on environments patched to version 9.1.1, see Broadcom knowledge base article 455842.

New default deployment size selection

When you deploy a new VCF fleet or VCF Instance, the VCF Installer UI defaults to a starting deployment size of **small**, replacing the previous default of **medium**. The small deployment size provides full capability and is optimized for production environments that require High Availability. To match your scale size, during deployment, you can change the default setting.

VCF Operations must now reside in the management domain of the first VCF Instance

Starting with VCF 9.1.1, it is required that VCF Operations resides in the management domain of the first VCF Instance in the VCF fleet. This is mandated by all VCF Installer workflows.

Getting to 9.1.1

For information about deploying, converging, upgrading or patching your environment to 9.1.1, see Getting to 9.1.1.

Resolved Issues

Initiating SDDC Manager upgrade pre-checks from the instance in Lifecycle tab in VCF Operations or from the Available Upgrades tab in SDDC Manager Lifecycle Management UI fails with a Triggering SDDC Manager upgrade bundle failed

When you initiate upgrade pre-checks for SDDC Manager in VCF Operations (**Build > Lifecycle > VCF Instances > instance > SDDC Manager Upgrades** tab) or SDDC Manager UI (**Lifecycle Management > SDDC Manager > Available Upgrades** tab), the operation fails with a `Triggering SDDC Manager upgrade bundle failed. A problem has occurred on the server. Please retry or contact the service provider and provide the reference token` error.

Known Issues

When upgrading SDDC Manager from 9.0.x , the upgrade fails with error `Timed out or the process exited without updating status while waiting for upgrade to finish.`

On SDDC Manager 9.0.x appliances, a Photon OS background job periodically refreshes package update information and holds the package manager lock while it attempts to contact the package repository. On networks that silently drop outbound traffic to the repository, the job holds the the package manager lock for approximately 48 minutes. The upgrade needs the same the package manager lock to install packages, waits for it to become available, and times out after 25 minutes.

Before starting the upgrade, stop the background job on the SDDC Manager appliance as **root**:

```
systemctl stop tdnf-cache-updateinfo.timer tdnf-cache-updateinfo.service
```

Verify that both units report inactive:

```
systemctl is-active tdnf-cache-updateinfo.timer tdnf-cache-updateinfo.service
```

This stops the update-check job until the next reboot. Run the command again if the appliance is rebooted before the upgrade starts.

If an upgrade attempt has already failed, check for a leftover script:

```
pgrep -af cap_platform_setup
```

Run the stop command so the leftover script can finish, wait until `pgrep` shows no output, then retry the upgrade.

Submitting a component-scoped patch plan causes previously patched components to incorrectly display a `VERSION_DRIFT` status.

After upgrading to a major release and patching a component, submitting a new component-scoped patch plan, such as patching only VC or NSX, causes other already patched components to fall back to the base BoM version in the release manifest rather than their current version. This leads to an incorrect `VERSION_DRIFT` report on the **Component Version** page. The issue compounds across sequential single-component patches, because each new plan save discards the prior plan's per-component targets. The display issue is cosmetic only and does not affect the actual component versions or patch operations.

Delete the current patch plan or successfully complete its application. Either action clears the incorrect `VERSION_DRIFT` status display on the **Component Version** page.

When invalid vCenter Single Sign-On credentials are provided, VCF Installer fails on the Validate & Deploy page

During the **Deployment Specification** validation phase, the exception handler in the validator catches an authentication failure `vim.fault.InvalidLogin` and misattributes it to a missing DVS network configuration. Since this validator encounters the error first, the validation process halts before the dedicated credential check runs and displays the correct authentication error message. As a result, even when the vCenter VM is already attached to a Distributed Virtual Switch, VCF Installer displays the following error message: `vCenter VM must be connected to a Distributed Virtual Switch.`

Workaround: In the deployment specification, enter the correct vCenter Single Sign-On administrator credentials and retry the deployment.

After upgrading SDDC Manager to version 9.1.1, in the offline depot settings, the VCF Operations UI displays Hostname, Port, and Username instead of the Depot URL.

An offline depot that you configured before the upgrade stores its address as separate hostname and port values in the backend record. The upgrade does not migrate this legacy record to the new URL field format, which stores the depot address as a single URL. As a result, the read-only depot settings continue to show the legacy fields.

Workaround: Perform one of the following tasks.

- Disconnect the offline depot and reconnect it by using the URL format.
- In the offline depot settings, click **Edit -> Save.**

When deploying a new workload domain and selecting **VLAN-backed VPC** on the NSX Manager step, subsequent wizard steps display NSX-Overlay traffic type and overlay Transport Zone labels, even though the deployment is TEP-less.

When you select **VLAN backed VPC** on the NSX Manager step, the Distributed Switch selection screen lists `NSX-Overlay` in the **Supported Traffic Type** column, and the Review screen displays `NSX-Overlay Traffic`, `Overlay Networking`, and a transport zone. The **IP Assignment (TEP)** field correctly shows `None`. The overlay transport zone is created internally as part of the VLAN-backed VPC configuration and is required by NSX. The overlay labels are graphical artifacts, non-functional, and do not indicate that the deployment uses overlay networking or TEPs. The VLAN-backed VPC configuration is operational and there is no functional impact.

None. The overlay transport zone labels do not affect the TEP-less VLAN-backed VPC configuration.

Deploying a VCF Instance with a VLAN-backed VPC displays an incorrect VLAN count on the VLAN requirements page

When you deploy a new VCF Instance by using the VCF Installer UI and select VLAN-backed VPC, the VLAN requirements summary page displays an incorrect number of VLANs that you must prepare for the deployment.

Workaround: In the VCF Installer UI, select **View Details** in the VLAN requirements dialog box and see the actual number of required VLANs.

When selecting a port group in VCF Installer, the Select port group dialog lists multiple entries with the same name and without distinguishing information, as a result you might select a wrong port group

The port group picker lists all port groups from the specified vCenter Server instance, without filtering or additional context. Selecting an incorrect port group can cause operation failure or completing an operation with the management networks attached to the wrong network backing.

Workaround: Perform the following tasks.

1. In the vSphere Client, locate the cluster on which the vCenter appliance VM runs and note its data center. The port group you must select is the one attached to a Distributed Switch in that data center and attached to that cluster.
2. Rename that port group so that its name is unique across all data centers and Distributed Switches in the vCenter instance.
3. Return to VCF Installer, open the **Select port group** dialog, and select the port group by its new, unique name.

Adding a new cluster to a VLAN-backed virtual private cloud (VPC) workload domain has no network span or transit gateway associated with it, resulting in an incomplete network configuration. Adding a new cluster to a tepless Workload Domain results in a tepless cluster with no network span defined.

When you add a new cluster to a workload domain that uses a VLAN-backed VPC configuration, SDDC Manager creates the cluster in TEP-less mode but does not associate a network span or configure a transit gateway. The workflow neither inherits the parent domain's network span. For existing vSphere clusters imported to or synced with SDDC Manager, the import and sync workflows associate all VLAN-backed VPC clusters under a vCenter with the same network span and transit gateway, but if the VLAN configuration differs or the vSphere Distributed Switch is not shared, the clusters experience connectivity issues.

Workaround: See Broadcom knowledge base article 454415.

When performing parallel upgrade of VCF components, VCF Operations upgrade fails

When you upgrade VCF components to version 9.1.1 and upgrade VCF Operations in parallel, the upgrade fails due to race conditions.

Workaround: Upgrade VCF Operations separately from other VCF components. Before proceeding with upgrading other VCF components, verify that the upgrade is completed successfully.

SDDC Manager allows upgrades of VCF core components before VCF Operations is upgraded to or above the target version

SDDC Manager permits core components upgrades, such as vCenter, ESX, and SDDC Manager itself, while VCF Operations still runs on an earlier version. Upgrading the core components before upgrading VCF Operations can cause environmental issues.

Workaround: Before proceeding with any VCF core component upgrades, verify that VCF Operations is at or above the target version.

Inventory sync for an out-of-band workload domain fails at the `Update or create with given network span` step

Inventory sync for an out-of-band workload domain fails at the **Update or create with given network span** step with the error `Invalid Configuration: Transit Gateway path=[/orgs/default/projects/default/transit-gateways/default] network stack cannot be changed from FULL_STACK_VPC to VLAN_BACKED_VPC`. This issue occurs when you add a cluster to a workload domain that shares an automatically deployed NSX instance in a converged environment and then trigger an inventory sync. SDDC Manager attempts to reuse the NSX default transit gateway (TGW) for the new cluster, which uses VLAN-backed configuration. If the default TGW already serves virtual private clouds (VPCs) that use the full stack VPC configuration, NSX rejects the reconfiguration because a TGW network stack cannot change from a full stack VPC to VLAN-backed VPC while VPCs are attached.

See Broadcom knowledge base article 452453.

When importing a vCenter instance in a scaled setup requires more than 60 seconds, the import validation operation fails or timeout with HTTP 504 error

When importing an existing vCenter instance in a scaled setup, if API validations response acknowledgment has not returned in 60 seconds, the VCF Operations UI closes or times out the connection and UI displays HTTP 504 error that indicates the operation has failed or was interrupted. Validation process continues to run in the background.

Workaround: Use the SDDC Manager API to import the instance. You can run the APIs from the SDDC API explorer or from the command prompt.

1. By using the import vCenter payload, initiate a validation.
   `POST /v1/sddcs/imports/validations`

2. To check the validation progress, poll the task ID received from the previous request.
   `GET /v1/sddcs/imports/{taskId}`
3. After the validation succeeds, perform the import.
   `POST /v1/sddcs/imports`

When upgrading to VCF 9.1.1 by using the Optimized upgrade sequence, the NSX pre-check or upgrade fails

After the vCenter preparation phase ends, initiating the NSX Manager upgrade or pre-check immediately from the **Upgrades** tab, results in the following UI error message: `Invalid upgrade spec, nsxtld passed as null.`

Workaround: Refresh the browser page and retry the upgrade.

When configuring upgrades in an environment with vLCM and VUM clusters, an error occurs

In an environment that contains both vLCM and VUM clusters, configuring an upgrade for one cluster type and then configuring an upgrade for the other cluster type may cause the Configure Upgrade wizard to retain stale cluster selection state. As a result, the wizard may display stale clusters, leading to an incorrect upgrade specification being submitted and the upgrade request failing.

Workaround: Refresh the browser page and configure the upgrade.

VCF Operations 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
  - Operate
  - Manage
  - Supported Browsers
- Getting to 9.1.1
- Product Support Notes
  - Deprecation Notes
  - Other Notes
- Security Fixes
- Resolved Issues
  - Operate
  - Manage
  - VCF Services Runtime
- Known Issues
  - Build
  - Operate
  - Manage
  - VCF Services Runtime

Introduction

Build numbers for VCF Operations and its components.

VCF Operations Component	Date	Version	Build Number
VCF Operations	03 SEP 2026	9.1.1.0	25679751
VCF Operations (Upgrade)	03 SEP 2026	9.1.1.0	25679887
License server	03 SEP 2026	9.1.1.0	25679819
Cloud proxy	03 SEP 2026	9.1.1.0	25679891
Fleet lifecycle	03 SEP 2026	9.1.1.0	25713934
SDDC lifecycle	03 SEP 2026	9.1.1.0	25713940

VCF Operations Component	Date	Version	Build Number
Log management	03 SEP 2026	9.1.1.0	25679624
Identity broker	03 SEP 2026	9.1.1.0	25679886
VCF Operations for networks	03 SEP 2026	9.1.1.0	25682214
Real-time metrics	03 SEP 2026	9.1.1.0	25679622
Real-time metrics store	03 SEP 2026	9.1.1.0	25714471
Salt RaaS	03 SEP 2026	9.1.1.0	25679895
Salt master	03 SEP 2026	9.1.1.0	25679895
VCF Operations HCX	03 SEP 2026	9.1.1.0	25690219
VCF Operations orchestrator	03 SEP 2026	9.1.1.0	25679883

Check for additions and updates to these release notes.

What's New

Operate

Changes to the SDDC Manager Log Configuration

Log collection across all VCF components is now fully managed within VCF Operations. This update extends automated log configuration to SDDC Manager, eliminating manual setup. Users can now enable, disable, filter, and control log volume to suit their environment. For more information, see Managing Collection from Log Sources.

Outbound Network Proxy Settings for cloud proxy deployment

Starting with VCF 9.1.1.0, when you deploy a new cloud proxy using the cloud proxy OVA, you can set up Outbound Network Proxy Settings to route external traffic (for example: Broadcom Portal) through a dedicated proxy. For more information, see Configuring Cloud Proxies in VCF Operations.

VMware Salt for VCF Components API

The VMware Salt for VCF Components API is now available. Based on VMware Salt, this new API lets you programmatically manage designated configuration settings across the VCF stack. Using native Salt constructs, you can implement and maintain desired state consistently across VCF Components.

Manage

On-demand lookup

You can now search AD users and groups on-demand using identity broker, with real-time authentication based on group membership and privileges at login. For more information, see Configure Active Directory as an Identity Provider Using AD/LDAP, (Optional) Assign VCF Roles to Groups and Users using On-Demand Lookup, and Managing VCF Single Sign-On.

VCF Roles

Starting from vCenter 9.1.1.0, the VCF admin role and any custom VCF role that includes the vCenter admin role are automatically mapped to the local vCenter Administrators group. For more information, see Managing VCF Roles.

Improved user experience with licensing

Error messages now provide more extensive information about the issue and remediation guidance.

License Server IPv6 Support

Starting with version 9.1.1.0, the license server supports IPv6 networking that uses static addressing, or DHCPv6/SLAAC. For more information, see License Server Networking.

Password Management

- VCF Operations now manages additional OS and application accounts, including the vCenter `administrator@vsphere.local` account, SDDC Manager `root`, `admin@local`, and `vcf` accounts.

- VCF Automation, VCF Operations for networks and cloud proxy now support password policy management through VCF Operations.
- VCF Operations now displays the last password update date for all managed accounts.
- You can now remove password policy from selected VCF Instances. When you remove a password policy from a VCF instance the instance falls back to the fleet policy, if one is configured, or to the component's own password requirements.
- All local account-related operations are audited, including account creation, successful and failed logins, password updates, password policy updates, and account lockouts.
- You can update the password for a locked or expired account from VCF Operations. Password update does not change the lockout state of the account.

For more information, see Managing Passwords for VCF Components.

Certificate Management

- VCF Operations now manages certificates for additional components, including NSX (all appliances), cloud proxy, license server, VCF Operations for networks collector node, Security Token Service (STS), vSphere Supervisor certificates, vSAN storage certificates, and VCF Automation.
- You can replace certificates that are signed by a configured or a non-configured CA with VMCA-signed certificates before they expire.
- VCF Operations generates expiry alarms for all certificates across VCF components, including certificates that are not managed by VCF Operations.
- VCF Operations detects and displays self-signed CA certificates as self-signed in the VCF Operations UI.

For more information, see Managing Certificates in VCF.

VCF Operations APIs for Tag Management

VCF Operations now exposes APIs through which administrators can manage VCF tags across a VCF Fleet.

Service Provider Metadata Re-Import Recommended for SAML Customers

Starting with identity broker 9.1.1.0, the service provider (SP) metadata published by the identity broker includes a new EncryptionMethod hint that signals enterprise identity providers to use RSA-OAEP with SHA-256 for SAML assertion encryption. This replaces the previous behavior where no algorithm hint was provided, and which caused some identity providers to default to SHA-1 OAEP.

If you have SAML federation configured with an enterprise identity provider such as Okta, Microsoft Entra ID, PingFederate, or ADFS, it is recommended that you re-import the identity broker service provider metadata into your identity provider after you upgrade to 9.1.1.0. Re-importing ensures your identity provider reads the new encryption hint and switches to SHA-256 OAEP for all subsequent SAML assertion encryption.

SAML login continues to work without re-importing since the identity broker retains a SHA-1 OAEP fallback in 9.1.1.0 while telemetry data is collected to confirm broad fleet adoption. The fallback will be removed in a future release and at that point, SP metadata re-import will become mandatory.

For more information, see Configure Okta as an Identity Provider using SAML, Configure Ping Identity as an Identity Provider Using SAML, Configure Microsoft Entra ID as an Identity Provider Using SAML, Configure Microsoft ADFS as an Identity Provider Using SAML, Configure an Identity Provider using Generic SAML 2.0.

Non-vIDM Authentication Support for Shared Sessions for the VCF Operations Orchestrator Plug-in for VCF Automation for VM apps

VCF Operations Orchestrator Plug-in for VCF Automation for VM apps supports use API token authentication, which allows use of the plug-in in environments that configured without VMware Identity Manager when using a shared session.

Supported Browsers

This VCF Operations release supports all current Web browsers, although only the following browsers were tested with this release:

- Google Chrome: Versions 152 and 151

- Mozilla Firefox: Versions 154.0.1 and 153
- Microsoft Edge: Versions 152 and 151
- Safari: Versions 26.6 and 26.5

Getting to 9.1.1

For information about deploying, converging, upgrading or patching your environment to 9.1.1, see Getting to 9.1.1.

Product Support Notes

Deprecation Notes

Deprecation announcement for Windows Server 2008 SP2 in VCF Operations HCX OS Assisted Migration (OSAM)

Removed support for Windows Server 2008 SP2 in VCF Operations HCX OS Assisted Migration (OSAM).

Deprecation announcement for support of VMware Cloud Director (VCD) as a destination in VCF Operations HCX 9.1.1.0

VMware Cloud Director (VCD) is no longer available as a destination in VCF Operations HCX 9.1.1.0.

Data collection results and Topology Graph widgets are marked as deprecated

Deprecation of low-usage widgets based on telemetry analysis. A deprecated warning icon appears on the corresponding widget card.

Other Notes

Removal of AWS and Azure data source support in VCF Operations for networks

Starting with VCF 9.1.1.0, VCF Operations for networks removes support for AWS and Azure as data sources. In new deployments, you cannot add AWS or Azure public clouds as data sources. If you upgrade an existing deployment that has AWS or Azure public cloud data sources to VCF 9.1.1.0, VCF Operations for networks disables those data sources and ceases data collection. However, you can continue to view and query data collected from AWS and Azure data sources before the VCF 9.1.1.0 upgrade until you remove the data sources. For more information, see Adding a Data Source in VCF Operations for networks.

Removal of the geo map within the VCF Operations UI

To ensure adherence to local laws, the geo map has been removed from the following areas within the VCF Operations UI:

- **Overview section of the Home page:** The Inventory card no longer includes a map.
- **Widget removal:** The Geo widget is no longer available in the widget list during dashboard creation.
- **Existing Dashboards:** Existing dashboards containing a Geo widget (such as those that were imported or upgraded) now show a 'Map view is no longer supported' message in the widget preview.
- **Inventory Management (Manage Tags):** The wrench control for managing geo locations on the map has been removed.
- **Sustainability:** For Physical Data Centers, the map view has been removed, leaving only the list view available.
- **Adding a Physical Data Center:** The map, coordinates, and map-based location selection flow are no longer part of the Physical Data Center addition process.
- **Physical Data Center Details/Selection:**The map has been removed from the selection screen, leaving only the associated accounts visible.

Removal of the Additional Storage Required metric and its associated symptoms, alerts, and dashboards.

In previous releases, the **Additional Storage Required** metric within the Log Management Health dashboard could erroneously report a storage shortfall on clusters where log partitions were left at their default settings (without a user-defined retention period). This non-zero value appeared even when ingestion rates were low and ample disk space was available, inadvertently misleading users into believing they needed to provision more storage. Because this metric does not accurately reflect a true storage deficit in the absence of a defined retention contract, the metric, along with any symptoms, alerts, and dashboards that depend on it, has been removed in version 9.1.1.0.

Server Side Encryption field removed from the Add New Storage UI

The `serverSideEncryption` setting has been removed from the **Add New Storage** configuration UI. For AWS S3 destinations, this option is no longer required because AWS now enforces AES-256 encryption on all buckets by default.

For non-AWS S3-compatible storage solutions, such as MinIO or Ceph, you must now enable default bucket-level auto-encryption directly on their storage servers. If you previously relied on this UI setting to manage encryption, you must now ensure that encryption policies are configured natively on your destination storage server.

Security Fixes

For a list of fixed CVEs, see VCF Operations 9.1.1.0 - Fixed CVEs.

Resolved Issues

Operate

SMTP outbound email plugin instances fail to authenticate with the mail server after upgrading to VCF Operations 9.1.0.0

In VCF Operations 9.1.0.0, the internal metadata key **IS_REQUIRES_AUTHETICATION** was renamed to `IS_REQUIRES_AUTHENTICATION` for email plugins. As a result, email plugin instances created before the upgrade did not recognize that authentication was required and did not send credentials to the SMTP server. Depending on the mail server and plugin, notifications were rejected with errors such as `530-5.7.0 Authentication Required`, or the connection test on the SMTP outbound Standard Email plugin failed with Email test error: `Invalid Addresses`.

Creating a vCenter cloud account using the default collector group fails with an unhandled error message when a collector in the group is offline.

If a collector within the default collector group is offline or unavailable, the system fails to create a vCenter cloud account. The operation fails because the assigned collector cannot process tasks. The user interface surfaces an unhandled internal log message instead of a standard failure warning, providing no actionable information.

Updating an existing application monitoring service via the SuiteAPI PUT endpoint fails with a "Configuration already used." error.

When using the SuiteAPI PUT endpoint /api/applications/agents/{id}/services to modify an existing application monitoring service — such as setting isActivated to false to disable the service — the request returns HTTP 422 with API error code 1508. The error incorrectly reports a conflict between the service name and an existing configuration on the same VM, even when no actual conflict exists. This failure affects all service update operations on existing application resources.

The content upgrade status for product-managed Telegraf agents intermittently displays as "Failed" despite the agent upgrading successfully

When a content upgrade also upgrades the Salt minion, a separate synchronous Salt call used to verify/restore the agent's running status could be issued while the minion was briefly offline during the minion swap, causing it to fail with "Minion did not return" and incorrectly marking the whole content upgrade as failed — most noticeable on Application Monitoring HA-enabled collector groups.

On Windows VMs running a non-English (localized) system language, the Telegraf agent status incorrectly reports as unhealthy

The agent queries Windows services via `sc.exe` using `subprocess.Popen with shell=True`, which routes output through `cmd.exe` and its OEM code page. On localized Windows builds, for example, Polish, service display names containing non-ASCII characters cannot be decoded as UTF-8/ANSI, causing a `UnicodeDecodeError` that crashes the service-status check and marks the agent unhealthy.

The agent status on Windows machines intermittently appears as unhealthy

The UCP minion's service monitor periodically collects per-process CPU statistics to assess health. If a target process exits between the time its PID is sampled and the time `psutil` attempts to read its stats, `psutil` raises a `NoSuchProcess/ProcessLookupError` originating from the underlying OpenProcess Windows API call. Because this exception is unhandled, the health and statistics collection fails, causing the agent's status to flip to unhealthy despite no actual issue. This is a race condition triggered by short-lived or recently exited processes on Windows.

If a report contains text with a symbol that has no corresponding glyph in the font that is used, an exception is thrown that breaks report generation

An exception is thrown when a report contains the U+202F (narrow no-break space) Unicode character, which has no corresponding glyph in the WenQuanYiMicroHei font.

When exporting a report to PDF, configured metric colorization does not render in the generated file

You encounter this issue in VCF 9.1.x when generating a PDF report from a view that has "Ranges for metric coloring" configured. Although the metric colors display correctly within the user interface, they fail to pass through to the exported PDF report.

When attempting to navigate from Inventory to another IP using Global Search, the page fails to redirect and continues to display the current view

While viewing an object on the Inventory page, a user may need to navigate to another object that is not visible in the current view or is difficult to access. To work around this, the user enters the target object's IP address in Global Search to navigate to it directly. However, this does not work as expected and the page remains on the current view.

Webhook notification templates fail to render dynamic placeholders when the payload root is defined as a JSON array

When a webhook notification template uses a JSON array as the root payload format, dynamic placeholders such as `${...}` are not evaluated and are sent unchanged to the receiving endpoint.

Double-clicking a metric or resource name in Metric Search inserts duplicate text into the search bar and triggers a syntax error.

When a user opens Global Search, selects the Metric Search category, and double-clicks a metric or resource name to select or insert it, the application appends duplicate text to the existing search bar content. The resulting malformed query immediately triggers a syntax error banner in the search bar.

The UI does not load and some services fail to start if NTP is not in-sync.

The UI fails to load if NTP is not synchronized. When running the standard synchronization command ntp sync fails, set the NTP server manually by using the following command: ntp set --ip-fqdn <ntp-server>.

Setting the system access URL such as the `BASE_URL`, using the Global Settings API failed regardless of how the value was entered. A URL containing `https://` returned a 404 error, and a URL without the scheme returned a 422 Invalid value error, making it impossible to configure `BASE_URL` through the API

Calling `PUT /api/deployment/config/globalsettings/{key}/{value}` with a raw URL in `{value}` broke path-based request routing. The `://` in `https://` caused the API framework to misparse the path and return a 404 error, while omitting the scheme caused the value to fail Global Setting validation (422 error).

Sticky bit not set for temporary directories created by the 'yarn' user.

Files created by the 'yarn' user in a temporary directory could be deleted by any user. This behavior was flagged as a security issue. The issue has been fixed by setting the sticky bit for the directory created by the yarn user, which restricts file deletion to the file owner, the directory owner, or the root user.

Git sync, check-in, or check-out operations fail for Configuration templates after a service restart.

Git-based Configuration templates operations fail consistently after a service restart when a source control endpoint is configured.

The VMware Cloud (VMC) SDDC group dashboard does not display route tables and SDDC information, and network flows are not enriched with VMware Managed Transit Gateway (VMTG) details.

When viewing a VMC SDDC group in VCF Operations for networks, the SDDC group dashboard page does not display the expected VTGW route table and SDDC information. In addition, network flows are not enriched with VTGW details, so the VTGW context that should accompany each flow is absent from the flow records.

Manage

API calls allowed VCF single-sign configuration on component vCenter and NSX instances even when VCF single sign-on for that VCF Instance was already managed (at least one vCenter or NSX instance already had VCF single sign-on configured) by a different VCF Operations

API calls did not perform eligibility checks on component vCenter and NSX instances when the VCF single sign-on of those components was managed by a different VCF Operations instance. As a result, users could configure VCF single sign-on using API.

When a vCenter instance has multiple v8 license keys of the same product family, host, socket, and core counts are doubled in Cost Driver > License, resulting in doubled host costs.

During v8 license discovery, discovered OS types are accumulated in a list instead of a set. When a vCenter instance has more than one VCF License of the same product family (such as two VCF or two VVF keys), the same OS type is appended multiple times. Each server is then registered against that license once per duplicate entry, causing vmCount, socketCount, and coreCount totals to be multiplied by the number of duplicate license keys.

A**fter removing all user-assigned license mappings from Custom License Assignment for a host, the Monthly Host OS License Total Cost metric continues to include the cost of all the removed license mappings.**

When all user-assigned host licenses are unmapped from Custom License Assignment, leaving the User Assigned column empty, the expected result is the reduction of OS license cost for that host. However, the cost calculation engine continues to factor in all previously assigned license costs in the Monthly Host OS License Total Cost metric even after the mappings are cleared.

When the License cost driver is configured with an Enterprise License Agreement (ELA) fixed cost, running a cost calculation does not apply the ELA costs to hosts. The Host License Cost metric remains unchanged.

When a user selects the ELA cost option in the License cost driver, saves an amount, and runs a cost calculation, the Host License Cost metric does not update with the new ELA costs across applicable hosts. This issue occurs only when the License cost driver is the sole cost driver with a fixed cost enabled. If any other cost driver also has a fixed cost configured, the issue does not manifest.

When exporting the Server Hardware: Hyperconverged cost driver data from the cost driver summary page, the exported Excel file contains traditional server data instead of hyperconverged server data.

Steps to Reproduce

When a user navigates to the cost driver summary page and exports the Server Hardware: Hyperconverged data as an Excel file, the export incorrectly populates with a list of traditional servers instead of hyperconverged servers.

When the allocation cost model is enabled and "Cluster Usable Capacity after HA and Buffer" calculation model is selected, the Cluster CPU Base Rate is computed using Total Capacity (cores) instead of Usable Capacity (cores), causing VM cost metrics to be lower than expected.

When a cluster has vSphere HA enabled, the allocation cost model is configured and Cluster Usable Capacity after HA and Buffer calculation model selected, the Cluster CPU Base Rate should be derived from the usable CPU core count after HA fail over reservations are subtracted. However, the cost engine uses the total physical core count of the cluster, ignoring HA-reserved capacity. This results in a lower-than-expected CPU Base Rate and cost metrics that do not reflect the configured allocation model.

Cost calculation fails for one or more data centers in a multi-data center Standard Topology (ST) deployment, if any data center is in "None" state with no new metrics being published.

In a Standard Topology deployment with multiple data centers, the cost engine fails with a java.lang.IllegalArgumentException: Invalid UUID string error when a data center's vCenter UUID (VC property Summary|VirtualCenter ID)is not populated in the system. During ESXi v9.x license cost assignment, the cost engine attempts to parse the empty vCenter UUID without first validating it, causing cost calculation to abort for the affected data center. Other data centers in the same deployment with valid vCenter UUIDs are unaffected.

The Potential Savings widget displays $0 for reclaimable hosts, and the Reclaimable Host metric is unavailable when inspecting cluster metrics.

vCenter instances integrated through the VCF Management Pack are classified as "Hybrid Cloud" environments. The cost engine does not calculate or expose the Reclaimable Host metric for these clusters due to this classification.

Windows Server 2025 VMs are incorrectly categorized under "Others" in the Windows license cost assignment instead of "Windows 2016 or later".

When Windows Server 2025 VMs are present in the environment, the Windows licensing cost driver does not recognize Windows Server 2025 as a "Windows 2016 or later" operating system. These VMs are grouped under the "Others" category, resulting in incorrect license cost allocation for Windows Server 2025 workloads.

VCF adapter instance creation fails due to CERTIFICATE_AUTHORITY type certificates imported in VCF Operations

When a certificate from vCenter or SDDC Manager is imported into VCF Operations with the type CERTIFICATE_AUTHORITY from the Control Panel > Trusted Certificates page, the VCF adapter instance fails to be created. This issue occurs in two scenarios:

- On the VCF Operations Integration page, when a user attempts to save a VCF adapter instance, an error notification appears with the message starting with "Unable to connect to VC: Duplicate Key: XXX". The message also references the CertificateConfig class.
- In the VCF installer workflow, the converge process fails, and the failure is visible in VCF Operations under Control Panel > Management Tasks > Update Component configurations, where the task fails at Stage 3 while configuring an adapter.

vCenter instance reported as unusable in the VCF Operations orchestrator plug-in for vCenter

If the connection to a vCenter instance is interrupted, the vCenter instance might be reported as unusable in the VCF Operations orchestrator inventory and you cannot run workflow against it.

Local VCF Operations orchestrator roles are sometimes ignored if VCF Operations orchestrator is configured with VCF SSO

VCF Operations orchestrator fails to parse the correct organization during login for users using VCF SSO configured with UPN. Login works for VCF SSO configured with sAMAccountName. As a result, local roles assigned in VCF Operations orchestrator are ignored during login.

Workflow variables missing from the field configuration drop-down menu in the Form Designer in VCF Operations orchestrator

When configuring field properties in the Form Designer in VCF Operations orchestrator, for example, mapping action inputs on the Values tab, the dropdown menu for selecting a field does not display the correct workflow variables. Under the Variables section of the dropdown, default request variables like `Catalog item reference`, `Tenant reference`, and `Provider binding` are incorrectly displayed.

Scheduled workflow runs in VCF Operations orchestrator fail

Scheduled workflows and long-running workflows in VCF Operations orchestrator fail if they are requested by a user who has more than one assigned role in VCF Automation.

The context.getToken() function breaks after token refresh in Python runtimes in VCF Operations orchestrator

In Python environments, the `context.getToken()` function does not work when VCF Operations orchestrator uses VCF Automation as an authentication provider.

VCF Services Runtime

During identity broker upgrade from 9.0 to 9.1, the upgrade process might stop responding at the backup stage for up to 120 minutes and display only a generic timeout error

This behavior affects administrators performing the upgrade and can cause uncertainty about whether the upgrade is progressing or has failed. This issue is fixed in this release and upgrade fails fast on a backup failure and displays a clear error.

Entering a hostname or FQDN in mixed case caused failures in install, upgrade, import, and other operations of VCF management services or VCF Automation

Issue occurs due to case-sensitive Domain Name System (DNS) and certificate matching. This issue is fixed in this release and all FQDNs can use mixed case.

When you power on a VCF management services or VCF Automation cluster, some services might fail to resume

After a shutdown or a power-cycle of the cluster, one or more services could fail to start automatically and required manual recovery. This issue is fixed in this release and services recover automatically after power-on.

VCF services runtime can accumulate log buffers, which results in the logger disk to fill up and health-check failures

Fluentd log buffers and retained backup chunks can accumulate on the logging disk until available disk space is exhausted. When the logging disk reaches capacity, platform health checks fail and block platform operations. This issue is fixed in this release and logging buffer is improved.

Known Issues

Build

Duplicate error messages appear on failed fleet lifecycle tasks

Some fleet lifecycle tasks automatically retry upon failure to improve overall task reliability. However, this change causes duplicate error messages to appear when a task fails and is retried. Users may observe repeated error entries for a single failed task, which can make troubleshooting more difficult.

Workaround: None

Component installation can fail during VCF service runtime node rotation

Fleet lifecycle services run on a single node. During a VCF services runtime platform node rotation operation, an in-progress component installation can fail. Fleet lifecycle automatically retries the installation of the component. In the worst case, the retry does not succeed and the installation task fails, requiring you to retry the task manually.

Workaround: If the component installation task fails, retry the task.

Scaling a VCF services runtime component can fail with a misleading task status after a transient network interruption

When you scale a VCF services runtime component, such as `vsp-platform` from Small to Large, a transient network or infrastructure interruption can cause the orchestrator to lose track of the task status polling loop in `sddc-build-service`. The underlying scale operation completes successfully on the component, but the orchestrator times out while waiting for a status update and retries the scaling request. The retry request is rejected by a guard validation that prevents no-op configuration updates, so the workflow task is marked FAILED even though the component reached the requested scale size. If you retry the same operation from the UI or from the API client, you will encounter the same no-op guard because the internal VSP task is already scaled to Large.

Workaround: This issue causes no functional impact, data loss, or service downtime. To verify that the component has been scaled to the target size, check the component size displayed in the fleet lifecycle UI. If the component reflects the updated target size, such as Large, no further action or retry is necessary and the failed task notification can be disregarded.

Successful tasks show failing sub-tasks

When an internal workflow contains sub-workflows that fail initially, the VCF Operation UI displays the failed attempts as errors, even though subsequent retries succeed and the task completes successfully. This behavior is expected and is caused by detailed task progress tracking, which now records failed sub-task attempts.

Workaround: None.

Scaling VCF Management Services runtime from Small to Small (High Availability) fails with the error "An error occurred while updating config for component with ID:xxxx" and the SDDC Lifecycle log shows the error message "Unexpected value 'small_ha'."

VCF Management Services runtime scaling from Small to Small (High Availability) fails when Fleet Lifecycle is upgraded to 9.1.1 but SDDC Lifecycle remains on 9.1.0. The Small (High Availability) functionality is introduced in both Fleet Lifecycle and SDDC Lifecycle 9.1.1, so you can use the functionality only after both components are upgraded to 9.1.1.

Workaround: Use one of the following workarounds:

- Upgrade SDDC Lifecycle to 9.1.1 along with the Fleet Lifecycle upgrade, and then perform the scale operation from Small to Small (High Availability).
- Scale to another size, such as Medium or Large, based on the available resources.

When creating or updating the backup configuration for a VCF management services, the operation fails and the UI displays a generic error message

When creating or configuring a backup for VCF management services in the VCF Operations UI, the backup configuration task can fail for either of the following reasons.

- SFTP connectivity failure. VCF services runtime cannot reach or authenticate against the configured SFTP server.
- Multi-cluster inconsistency. In an environment with VCF Automation deployed, the backup configuration can succeed on one VCF services runtime cluster and fail on another.

Workaround: Perform the following tasks.

1. Verify network connectivity, host key trust, and credentials between VCF services runtime cluster and the SFTP server.
2. If the failure persists, file a Support Request (SR) with Broadcom Support and attach the VCF Services Runtime support bundle.

When you install Real-time metrics, Log Management, and VCF Operations for networks in parallel, the Real-time metrics installation fails and the VCF Operations for networks installation appears stuck for more than three hours before eventually failing.

When you trigger the installation of Real-time metrics, Log Management, and VCF Operations for networks in parallel, a simultaneous platform node replacement can transiently disrupt platform health. The Real-time metrics installation detects the disruption and fails immediately with a platform health-check error. The VCF Operations for networks installation does not detect the disruption, so it continues to run without progress or error until the installation workflow times out after three hours.

Workaround: Avoid installing VCF Operations for Networks in parallel with components that can trigger VCF Services Runtime platform node scaling, such as Log Management. Install these components sequentially instead. If the installation is stuck, you must wait for the installation workflow's three-hour timeout to fail the task, after which you can retry the installation.

Onboarding and deploy steps on extra-large scale vCenter instances may time out with a 504 Gateway Timeout error.

On extra-large scale vCenter environments, for example 2,000 or more hosts and 30,000 or more virtual machines, validation and cluster selection steps during VVVF or VCF onboarding in the installer, converge, or import workflow may take over an hour to complete. Clicking **Deploy** may trigger a transient 504 Gateway Timeout error before the deployment starts.

Workaround: Retry the **Deploy** operation. The 504 Gateway Timeout error is transient, and the deployment proceeds on retry. If the problem persists, use the APIs in the VMware Cloud Foundation® Operations fleet management developer center. Run the Validation API followed by the Import API. For more information, see the VCF Operations fleet management API reference.

The VCF Operations upgrade precheck shows raw, unresolved resource-bundle keys and JSON instead of human-readable text for the Management Pack compatibility check

When you run the VCF Operations 9.1 to 9.1.1.0 upgrade precheck from the VCF Operations fleet management UI, the "Validating Management Pack Compatibility with VMware Cloud Foundation Operations 9.1.1" precheck correctly detects and reports incompatible Management Packs, but the Message and Resolution fields display raw, unresolved resource-bundle keys and JSON instead of human-readable text. The separately downloaded APUAT support bundle HTML report renders the same result correctly.

Workaround: Download the APUAT support bundle HTML report from the same precheck run. The report renders the Management Pack compatibility check results correctly, including the full message and recommendation text.

The Small deployment size is missing for the High Availability deployment model in the Deploy deferred components workflow.

When you deploy VCF Operations and VCF Automation using a custom network through the **Deploy deferred components** option in the VCF Installer, the deployment size selector for the High Availability model shows only Medium and Large. Small is not available, so you cannot select it for a high availability deployment in this workflow.

Workaround: Use one of the following workarounds:

- Use the existing high availability deployment sizes, Medium or Large.
- Use the JSON input option and pass the VCF Operations master and replica node details with appliance size set to Small.
- Use the simple deployment model with Small size, complete the deployment, and then deploy the replica node for the VCF Operations component in the VCF Operations fleet management UI and enable high availability.

A joined VCF Instance does not appear on the Integration/Registrations page in VCF Operations after the join task reports success.

A transient disruption affects a service that VCF Operations depends on internally (for example VCF Operations for networks), while VCF Operations registers the newly joined VCF Instance. If the disruption lasts longer than the automatic retry window, the registration does not complete on the VCF Operations side, but the join task in VCF Operations fleet management still reports success. No error or failure appears in the VCF Operations fleet management UI or task history, so the issue can go unnoticed unless you check the Integration/Registrations page after the join operation.

Workaround: If a VCF Instance does not appear on the Integration/Registrations page in VCF Operations after a join operation reports success, manually add the VCF Instance from the UI.

Deploying to a VSP cluster by using the VCF Operations load balancer FQDN fails with an error that the hostname does not match the address of any of the VCF cluster nodes

When deploying to a VSP cluster, the deployment workflow prompts for either the VCF Operations load balancer FQDN or the master node hostname. If you provide the VCF Operations load balancer FQDN, the workflow reports that the hostname does not match the address of any of the VCF cluster nodes, and the installation cannot start. This issue occurs only when the load balancer FQDN is provided as the target hostname.

Workaround: Provide the hostname of the VCF Operations master node instead of the VCF Operations load balancer FQDN, and restart the installation process.

Management packs created with the Management Pack Builder break after VCF Operations is upgraded to version 9.1.1

Upgrading VCF Operations to version 9.1.1 also upgrades the Management Pack Builder, causing custom management packs built with a previous version of the Management Pack Builder to stop functioning correctly after the upgrade.

Workaround: Recreate the affected management packs using the updated Management Pack Builder after VCF Operations has been upgraded to version 9.1.1. For more information, see KB 454434.

Operate

When you deploy a secondary VCF Instance at a newer version than the existing VCF Operations instance, the SDDC Manager of the secondary VCF Instance does not appear as a VCF Adapter on the Administration -> Integrations tab in VCF Operations UI

The cloud proxy deployed for a secondary VCF Instance must match the exact version of the VCF Operations cluster that it connects to. If the secondary instance runs a newer version, its cloud proxy fails to register, and the secondary instance never appears on the Integration tab, even when the rest of the deployment completes without error. When you add an instance to an existing fleet, VCF Installer validates only `major.minor` version compatibility between cloud proxy and VCF Operations instead of the exact version match that cloud proxy requires.

Workaround: Upgrade VCF Operations to the same version as the secondary VCF Instance and perform one of the following tasks, that matches the current state of the VCF Adapter.

- If cloud proxy is already registered and the VCF Adapter instance exists in an error state and cannot start because of the version mismatch, the VCF Adapter instance recovers after the VCF Operations upgrade.
- If the VCF Adapter instance was not created, add the secondary VCF Instance after the upgrade.

Note: To avoid this issue, before you deploy a secondary VCF Instance, upgrade VCF Operations to the desired target version or deploy the secondary VCF Instance at a version that matches the current VCF Operations version.

Operations for Logs Agent 8.18.x installation fails on Linux systems after a failed 9.1.0.0 installation attempt

On Linux operating systems with OpenSSL versions earlier than 3.0 (for example, Ubuntu 18.04), installing Operations for Logs Agent 9.1.0.0 fails because the OpenSSL version does not meet the minimum requirement. If you then attempt

to install an earlier agent version, such as 8.18.5 or 8.18.6, which does not depend on OpenSSL 3.0, the installation fails with a package conflict error similar to:

```
dpkg: regarding VMware-Log-Insight-Agent-8.18.5-24965621.deb containing vmware-log-insight-agent:
 operations-logs-agent conflicts with vmware-log-insight-agent
dpkg: error processing archive VMware-Log-Insight-Agent-8.18.5-24965621.deb (--install):
 conflicting packages - not installing vmware-log-insight-agent
```

This occurs because remnants of the failed 9.1.0.0 `operations-logs-agent` package remain on the system and conflict with the earlier `vmware-log-insight-agent` package.

Workaround:

Before installing the earlier agent version, remove the leftover 9.1.0.0 agent package by running:

```
sudo dpkg -P operations-logs-agent
```

Then proceed with installing the desired earlier agent version (for example, 8.18.5 or 8.18.6).

Log Management Disaster Recovery displays an error after restoration

Log Management Disaster Recovery (DR) requires manual intervention to be fully functional. The Operations UI in the Log Analysis page currently displays the following error, after restoration, which prevents it from being fully operational:

`Unable to access logs due to user permissions.`

Workaround: If you encounter this issue, perform a service restart of the log management service via Fleet LCM using the component Stop / Start action.

After a new service instance is added to a product managed Telegraf agent, the service instance cannot be reliably edited or deleted

Impact:

- Avoid adding new service instances on a product-managed Telegraf agent in VCF Operations 9.1.1.0, because they cannot be reliably edited or deleted afterward.
- Data collection for existing and newly added service instances continues to work normally.

Workaround: If you have already added a new service instance in 9.1.1.0 and need to edit or delete it, the only remediation is to reinstall the Telegraf agent without retaining the existing Telegraf configuration, then re-add all service instances from scratch. Manually editing the `.conf` file does not work.

After a Machine SSL certificate rotation on vCenter Server, the associated vSphere Supervisor adapter instance may stop collecting data and move to a Not Existing state, even though the Supervisor Cluster itself is healthy.

The Supervisor adapter depends on connection/trust information from the associated vCenter adapter instance rather than connecting independently. This trust information is not always refreshed promptly after a certificate rotation, causing collection failures that can eventually cause the resource to be marked `Not Existing`.

This can occur even if the certificate rotation happens on only one domain (for example, the management domain). The resulting collection failure can affect Supervisor adapter instances across all domains, not just the domain where the rotation occurred.

- Before rotating vCenter Server certificates
  - Navigate to **Operate > Administration > Configurations > Inventory Management > Adapter Instances > vSphere Supervisor**, and select the Supervisor adapter instance.
  - Stop the Supervisor adapter instance before rotating the certificate.
  - Rotate the certificate on vCenter Server.
  - Confirm the vCenter adapter instance is collecting successfully with the new certificate.
  - Start the Supervisor adapter instance again.
- Post-Recovery - If already impacted, but not yet **Not Existing**
  - If the Supervisor adapter instance shows `No Data Receiving`, confirm that the vCenter adapter instance is collecting successfully post-rotation.
  - Restart the Supervisor adapter instance (stop, then start) via the navigation path above.
- Post-Recovery - If the adapter instance has already gone to **Not Existing** (resources/history removed by the platform)

- Once the resource is `Not Existing`, its objects and history are already removed, so a simple stop/start no longer recovers it.
- Retrieve the adapter instance ID to be deleted:
  a. Navigate to **Operate > Administration > Configurations > Inventory Management > Adapter Instances > vSphere Supervisor**, and locate the non-existing Supervisor adapter instance.
  b. Copy the value in the `ID` column for that adapter instance.
- Delete the Supervisor adapter instance using the suite-api: `DELETE /api/adapters/{id}`, using the ID retrieved above.
- Once the vCenter adapter instance is confirmed healthy, no further action is needed. The vCenter adapter will automatically recreate the Supervisor adapter instance as part of its regular collection interval.

Workload domain accounts remain in Stopped state after configuring a VCF account in VCF Operations 9.1 or later

When a VCF 5.2.1 account is configured, or an existing VCF cloud account is upgraded to VCF Operations 9.1 or later, workload domain sub-accounts (vCenter and NSX) may remain in a Stopped status and fail to collect data. When you attempt to edit an affected workload domain account, the following UI issues are observed:

- The vCenter hostname field does not pre-populate in the Edit wizard.
- Clicking Validate Connection returns a generic Error trying to establish connection failure with no diagnostic detail.
- The NSX tab within the Edit wizard renders as a blank form with no input fields.

These accounts appear assigned to the default legacy collector instead of the configured cloud proxy, causing collection to never start.

Workaround: Manually re-save each workload domain account to rebind it to the correct cloud proxy and activate collection. For more information, see Configuring a Standalone VCF Account in VCF Operations.

Platform nodes in a VCF Operations for networks cluster do not appear simultaneously on the agent listing page. Instead, their entries toggle or overwrite one another

When deploying or running a multi-node VCF Operations for networks cluster, the VCF Operations for logs agent instances on each platform node generate identical cached ID configurations. This shared ID conflict causes the agent listing page to constantly overwrite node entries rather than displaying all active cluster nodes at the same time.

Workaround:

To resolve the ID collision across the cluster:

1. SSH into Platform 1 of the VCF Operations for networks clustered deployment (or the single-node deployment) using the **support** user.
2. Switch to the ubuntu user: `ub`
3. Stop the VCF Operations for logs agent service across all nodes: `./run_all.sh sudo service liagentd stop`
4. Remove the cached ID configuration files to force a reset: `./run_all.sh sudo rm -r /var/lib/loginsight-agent/storage`
5. Restart the VCF Operations for logs agent service to generate a new, unique ID for each node: `./run_all.sh sudo service liagentd start`

Manage

After you upgrade a vCenter instance to version 9.1.0.0300, the vCenter instance does not appear on the Licensing page in VCF Operations

After you upgrade a vCenter instance from version 9.0.x to version 9.1.0.0300, the vCenter instance does not appear in the VCF Operations UI under **Manage** > **Licensing**, so you cannot assign a license to the vCenter instance. In the vSphere Client, no licenses are displayed on the **Administration** page. There is no banner to indicate that there are unlicensed assets.

A stale or orphaned vSphere+ subscription license in the vCenter LDAP database prevents the vCenter instance from appearing in the VCF Operations UI.

Identify the stale vSphere+ license and manually delete the license from the vCenter LDAP database. For more details, see Broadcom knowledge base article 455886.

Duplicate completion markers displayed in the Add Plug-in wizard in VCF Operations orchestrator

When a user adds a new plug-in to VCF Operations orchestrator, the Add Plug-in wizard incorrectly displays two overlapping or duplicate completion markers per step, like incomplete circles or green checkmarks, instead of displaying a single completion marker.

Workaround: No workaround.

Missing selection column prevents removal of packages and dependencies in the VCF Operations orchestrator Environment Editor

In VCF Operations orchestrator 9.1.1, users might experience an issue where they cannot select and delete existing packages, dependencies, or key:value pairs within the Environment Editor.

Workaround: If you need to remove a package or dependency, use the corresponding REST API endpoint or command-line tool to update the environment's configuration. Alternatively, you can create a fresh environment configuration from scratch containing only your desired dependencies.

After you patch the license server to version 9.1.1, used license capacity might appear higher than the actual used capacity

After you patch the license server to version 9.1.1, the VCF Operations UI might incorrectly show the used license capacity as higher than the actual used capacity. A warning message about license overuse might appear, and the system might prevent license assignment. The issue affects only the information that the VCF Operations shows. Your assigned licenses, used capacity, and reported usage remain correct on the VCF Business Services console.

Workaround: Perform the following steps to restart the VCF Operations cluster.

1. Ensure that all vCenter instances are running and connected to the license server.
2. Log in to the VCF Operations administration UI at `https://<vcf_operations_fqdn>/admin` as the admin local user.
   a. Take the VCF Operations cluster offline.
   b. On the **System status** page, click **Take cluster offline**.
3. In the **Take cluster offline** dialog box, provide the reason for the shutdown and click **OK**. This operation might take about an hour to complete.
4. To take the VCF Operations cluster online, on the **System status** page, click **Bring cluster online** and wait for the operation to complete.

vCenter shows "Virtual Machine UEFI Secure Boot Platform Key is out of date." warning for the license server.

After you patch your vCenter from version 9.1.0.x to 9.1.1, you see this message in the issues and alarms section in the vSphere Client where the license server is deployed. The alarm appears when you have license servers in version 9.1.0.x or license servers patched to version 9.1.1. This alert is not critical and has no impact on the boot or the functionalities of your license server.

Workaround: To resolve the alarm, from the vSphere Client, upgrade the compatibility of the license server VM to **ESXi 6.7 and later** by following the Upgrade the Compatibility of a Virtual Machine Manually procedure.

An update password task is marked as failed in VCF Operations, even though the password update on the target component succeeds.

When you update the password for an account in VCF Operations, the password is updated on the target component. If that account is also used by a configured integration, VCF Operations additionally attempts to propagate the updated password to the credential object associated with that integration. If the credential object is orphaned (no owner assigned in VCF Operations), this secondary propagation step fails with `Operation is not allowed for credential`. The primary password rotation is not affected. The new password is valid on the target component. Only the propagation to the orphaned integration credential fails, but the entire update password task is marked as failed.

Configure integrations to use service accounts rather than user-managed credential accounts (avoids the issue entirely). If an integration's credential is already orphaned, assign it an owner in VCF Operations to restore normal propagation. Alternatively, manually update the integration's credential with the new password as a one-time step.

While executing the 'Update Password' operation in VCF Operations for a `vmware-system-user`, task timeout triggers an error

An incorrect INVALID_CREDENTIALS error occurs ('the current password provided is incorrect') when the underlying password-update task times out, despite the password being accurate.

Workaround: None

The password policy page is available in the VCF Operations UI before upgrade of the remaining VCF component completes

After you upgrade VCF Operations to 9.1.1.0 from Aria Operations 8.18 or VCF Operations 9.0, but before you complete the upgrade of the remaining VCF components, the password policy page is available in the VCF Operations UI. The password policy page is introduced in VCF 9.1 and should not be available before all VCF components are upgraded to version 9.1 and later.

Workaround: None

The VCF Operations UI incorrectly displays "No Expiry" for the vCenter root account even when it has expired. This issue occurs only when the vCenter version is 9.1 or earlier and VCF Operations is at version 9.1.1.0

For vCenter 9.1 and earlier, the last password change date for an expired root account is incorrectly reset to 0, resulting in an invalid expiry status.

Workaround: None

The `Replace with VMware Certificate Authority (VMCA)` operation fails with the error `Failed to generate certificate from CSR` when the certificate signing request (CSR) contains wildcard entries in the Subject Alternative Name (SAN) DNS field

VMCA does not support signing certificates with wildcard fully qualified domain name (FQDN) entries in the SAN field.

Workaround: Use wildcard SAN entries to replace the certificate using OpenSSL, Microsoft CA, or an external CA with an imported certificate instead of VMCA. To use VMCA as the signing CA, provide all SAN FQDNs explicitly in the CSR without wildcards.

Certificate replacement tasks fail after 2 hours when multiple certificate tasks run concurrently

VCF Operations does not support concurrent certificate rotation. Running multiple rotation operations at the same time causes instability. When one task briefly restarts a service to apply its certificate, any other task running in parallel may lose its connection, stall, and eventually time out. The VCF Operation UI already warns against running certificate operations concurrently.

Workaround: Perform certificate replacements one at a time, and always wait for the active task to finish before starting the next.

Bulk certificate replacement for NSX fails with the `Unable to obtain CSR ID from NSX for replace certificate operation, Certificate mismatch detected when connecting to endpoint error`

After upgrade to VCF 9.1.1.0, in NSX multi-node cluster environments upgraded from versions earlier than 9.0, bulk certificate replacement can fail if the VIP certificate is replaced before the cluster node certificate. The updated certificate may take time to become available, and if the next replacement attempt falls within the same collection window, a certificate mismatch error occurs.

Workaround: Retry the certificate replacement for the failed component.

Certificate operations fail with `Unable to find end point` after a collector changes due to load balancing or a user-initiated operation

If you perform certificate operations on an endpoint and the collector assigned to that endpoint changes before the next VMware Infrastructure Management (VIM) adapter collection cycle (every 6 hours), the operations fail with `ENDPOINT_NOT_FOUND`.

Workaround:

1. Log in to VCF Operations.
2. In the left pane, navigate to **Administration > Configurations**.
3. On the **Configurations** page, click the **Inventory Management** card.
4. In the left pane, navigate to **Adapter Instances > VMware Infrastructure Management Adapter Instance**.
5. For each adapter instance, click **Start Maintenance**, wait for ten seconds, and click **End Maintenance**.

After replacing the SSL certificate on an 8.x vCenter instance, attempts to establish or re-establish trust in VCF Operations fail. Authentication using valid vSphere single sign-on credentials for an existing account is rejected, and the SDDC Manager UI is inaccessible

The certificate replacement task in VCF Operations fails with the error: Certificate task REPLACE_CERTIFICATE for vcenter-xxx has failed. Error message: Failed to retrust VCF Ops truststore. Additionally, SDDC Manager fails with the error: Authorization Error : unauthorized access. As a result, the truststores of both SDDC Manager and VCF Operations are affected, rendering the SDDC Manager UI inaccessible and disrupting VCF Operations.

Workaround: To resolve the SDDC Manager truststore issue, refer to KB 316056. After SDDC Manager is restored, delete the VCF integration in VCF Operations and re-add it using the same credentials.

After a certificate is replaced on a VCF management component, VCF Operations might not re-establish trust with that component until the next inventory synchronization, causing dependent tasks and inventory views to fail

This issue occurs when the periodic inventory synchronization between fleet lifecycle and VCF Operations runs after a certificate is replaced on a component but before fleet lifecycle retrieves the new certificate. The synchronization workflow republishes the fleet lifecycle cached certificates for every managed component to VCF Operations. Any component with a replaced certificate within that interval might have its old certificate replace the new certificate in the VCF Operations inventory. This prevents VCF Operations from establishing a trusted connection to the component.

Affected tasks fail with a certificate trust error such as `Error occurred while pushing capabilities to VCF Operations for Logs`. VCF components might not appear in the lifecycle and certificate management views, or an integration might report a connection failure. The condition persists until the next inventory synchronization publishes the current certificate and does not affect running workloads or certificates that were already replaced successfully. The inventory synchronization is scheduled by default to run every 24 hours.

Workaround: Change the synchronization schedule by temporarily setting the `ops.platform.sync.cron` property to `0 0 * * * *` in the fleet build service to run hourly. After the synchronization runs successfully, revert the `ops.platform.sync.cron` property to `@daily`.

vMotion fails if vCenter Server certificate changes before relocate starts and during initiation of vMotion

vMotion fails if the vCenter Server certificate changes before relocate starts and during initiation of vMotion. For example, storage refresh of vMotion.

The vCenter interface reports a template drift, but selecting the drift view shows no actual drift or discrepancies

This rare issue occurs when duplicate global permission entries exist in the system. Although the vCenter UI typically prevents duplicate permissions from being created, edge cases can allow a duplicate entry to bypass validation. This redundant entry triggers false-positive drift alerts while failing to render any visible differences in the comparison view.

Workaround: None

Restoring SDDC Lifecycle task incorrectly reports as failed

The SDDC Lifecycle restore operation in the VCF Operations UI might appear stuck "in progress" and eventually report a failure, however this is strictly a reporting error. Standalone SDDC Lifecycle and multiple components that include the SDDC Lifecycle component all restore properly. The underlying back-end process completes successfully, and the target component boots and functions as expected.

Workaround: No corrective action or secondary restore is required. Administrators should manually verify that the target component is active and functioning, then proceed with standard operations.

Content items cannot be selected in the VCF Operations orchestrator tree view datagrid

Users cannot select one or multiple content items in the VCF Operations orchestrator tree view datagrid. Clicking on rows fails to highlight them or register a selection, preventing users from performing bulk actions on those items, like moving or deleting them. Additionally, hovering over item names does not change the cursor to a pointer or show standard hyperlink styling.

Workaround: To continue managing your content, use the following methods.

- Click the item name directly. While your mouse cursor will not change to a pointer when hovering over the text, clicking the item will register the action.

- Avoid bulk UI actions.
- For urgent bulk management tasks, like moving multiple workflows to a new category, use the VCF Operations orchestrator API or CLI.

After upgrading a clustered VCF Operations orchestrator deployment, the salt minion config service might not start on some of the nodes

After upgrading to a clustered VCF Operations orchestrator 9.1.1 deployment, the salt minion config service on port 8061 might not be available on all of the nodes. You can check if the service is active by running the `systemctl status nginx.service` command on each node.

Workaround: If the service is inactive, run the `systemctl start nginx.service` command.

VCF Operations orchestrator SSO login breaks after vIDB certificate replacement

When a vIDB certificate is replaced with a certificate from a different certificate authority, VCF Operations orchestrator single sign-on (SSO) breaks and requires re-registration. The VCF Operations orchestrator NDC certificate-replace endpoint uses a hardcoded URL path that only works with embedded (vCenter-hosted PSC) vIDB deployments. External (standalone VSP appliance) vIDB deployments return a 404 error which prevents the self-healing certificate rotation from completing.

Workaround: Reconfigure the authentication for VCF Operations orchestrator. See Configure VCF Operations Orchestrator for vSphere by Using VCF SSO.

The autocomplete functionality for the script editor in VCF Operations orchestrator does not work

Typing in the script editor in VCF Operations orchestrator does not trigger the completion pop-up which provides a list of suggestions that match the typed string.

Workaround: No workaround.

Some scripts appear as a hex-encoded string in the workflow script element in VCF Operations orchestrator

In VCF Operations orchestrator, scripts that contain Unicode characters like emojis are encoded upon package export. When a package with such scripts is imported into a VCF Operations orchestrator instance, the script remains encoded when viewed in the UI, preventing further edits.

Workaround: Remove characters like emojis from workflow scripts or actions before exporting them in a package.

The workflow selector field in a VCF Operations orchestrator workflow element appears empty

The workflow selector field in a VCF Operations orchestrator workflow element appears empty even when the workflow is populated.

Workaround: No workaround.

The All Runs button is missing from the workflow editor in VCF Operations orchestrator

In VCF Operations orchestrator 9.1.1, users cannot navigate to the historical execution runs of a workflow directly from the Workflow Editor page because the All Runs button is missing from the action menu.

Workaround: To view your workflow runs, use the following procedure.

1. Copy and save the workflow ID from the URL or editor details of your specific workflow.
2. Navigate to the main **Runs** page.
3. On the **Runs** page, enter `workflowId:<your_workflow_id>` in the search to isolate the runs for your workflow.

Conditions in the Decision and Switch fields in the VCF Operations orchestrator workflow schema might clear unexpectedly while the user is typing

In VCF Operations orchestrator 9.1.1, when a user adds a Decision or a Switch element to a workflow's schema and populates the conditions for these elements, the information the user entered might suddenly disappear or reset. While the user is typing, the page occasionally refreshes in the background which might accidentally clear out any new, unsaved text.

Workaround: To prevent losing your work, use one of the following methods.

- Save your work immediately after filling out the Decision or Switch field before clicking elsewhere on the page.

- Do not move to other tasks in the VCF Operations orchestrator UI before you are done writing a condition.
- For long or complex conditions, write them in an external application, like Notepad, first. You can then copy and paste the content in VCF Operations orchestrator and save it immediately.

VCF Operations orchestrator script editor gets stuck when the browser is set to a non-English locale

In VCF Operations orchestrator 9.1.1, the script editor fails to load if the user's browser language or locale is set to anything other than English. The application remains permanently stuck on a loading spinner, preventing users from viewing or editing scripts.

Workaround: To regain access to the script editor, use one of the following methods.

- Temporarily change the primary browser language or preferred language settings to English.
- If you need to keep your primary browser in a different language for other tasks, create a secondary browser profile or using an alternative browser specifically configured with an English locale to manage your scripts.
- After updating the language settings, you might need to clear your cache or fully refresh the application page.

After upgrading a clustered VCF Operations orchestrator deployment, the salt-minion-config TLS endpoint is unavailable

After upgrading a clustered VCF Operations orchestrator deployment to 9.1.1, the `salt-minion-config` TLS endpoint on port 8061 is unavailable on one or more nodes.

Workaround:

1. Run `systemctl is-active nginx.service` on every node.
2. If any reports failed, run the following command on that node.
   ```
   systemctl reset-failed nginx.service
   systemctl start nginx.service
   ```
3. Verify that the service is active by running `systemctl is-active nginx.service`.

If your environment has a VCF Operations HCX manager, the password policy page does not display the VCF management components row, and applying a password policy fails with a null pointer error

An incorrectly configured VCF Operations HCX adapter prevents VCF Operations from retrieving the VCF Management components list, so the VCF management components row is missing from the password policy page. Applying a password policy fails with a null pointer exception in `VcfPasswordPolicyManager.getVCFManagementComponentsFromvRops()`. The adapter collection status shows as green, so the misconfiguration is not apparent until you attempt to apply a password policy. The error message does not indicate the adapter configuration as the cause.

Workaround: The user account that VCF Operations uses for the integration with VCF Operations HCX management pack must exist in vCenter and be a member of the **Migration Appliance Administrators** and **Migration Users** user groups. Remove the misconfigured HCX integration and reconfigure it in VCF Operations. See Management Pack for HCX.

OSAM migrations fail if HCX Manager is upgraded to 9.1.1 during an active migration

Upgrading the HCX Manager to version 9.1.1.0 while OS Assisted Migrations (OSAM) are in progress may cause those migrations to fail during the switchover/fixup phase with authentication errors.

Preventative: Ensure all in-progress OSAM migrations are fully completed before upgrading the HCX Manager to 9.1.1.0. For new migrations, ensure the entire ecosystem (Manager, Interconnect appliances, and Sentinel agents) is running 9.1.1.0.

Recovery for Windows VMs: If a migration fails with authentication errors, upgrade the Sentinel agent on the source VM to 9.1.1.0 and re-invoke the migration.

Recovery for Linux VMs: If a migration fails, upgrade the OSAM data-plane appliances like SRG/SGW/SDR to 9.1.1.0 to ensure the correct fixup disk is used, then retry the migrationUpgrading the HCX Manager to version 9.1.1.0 while OS Assisted Migrations (OSAM) are in progress may cause those migrations to fail during the switchover/fixup phase with authentication errors.

Resolution: Retry the migration after upgrading the OSAM data-plane appliance and sentinel on the VM.

Post HCX upgrade to 9.1.1.0+, data plane appliances need to be redeployed/updated to send logs to the syslog server

Post HCX upgrade to 9.1.1.0+, data plane appliances stop sending logs to the syslog server.

Workaround: Redeploy or update the data plane appliances to stream the relevant logs to the syslog server.

Unable to modify the "Force Power Off" setting for an active migration if the migration was initiated without a defined switchover schedule

Unable to modify the "Force Power Off" setting for an active migration if the migration was initiated without a defined switchover schedule.

Workaround: Temporarily assign a switchover schedule to the migration to force a value update.

The PowerCLI module for HCX Manager (VMware.VimAutomation.Hcx) included in all versions of VCF.PowerCLI is not compatible with VMware Operations HCX version 9

The PowerCLI module for HCX Manager (VMware.VimAutomation.Hcx) included in all versions of VCF.PowerCLI is compatible with HCX version 4.11 and no later.

After upgrading HCX Manager to version 9.1.1.0, pending switchovers or newly initiated Bulk and RAV migrations may fail due to a certificate validation mismatch

Following an upgrade of HCX Manager to version 9.1.1.0, pending switchovers or newly initiated Bulk and RAV migrations may fail due to a certificate validation mismatch.app logs will display an error similar to:

```
Caused by: com.vmware.vchs.hybridity.adapters.https.PeerNotVerifiedException: Host
name '172.16.64.204' does not match the certificate subject provided by the peer
(OID.1.2.840.113549.1.9.2="...", CN=VMware vSphere Replication Server, ...)
```

Workaround: To prevent or resolve this issue, complete all ongoing Bulk and RAV migrations prior to starting the upgrade process and immediately upgrade or redeploy the photon-based service mesh after upgrading HCX Manager.

After upgrading the HCX Manager to 9.1.1.0, OSAM migrations may fail during the fix-up operation with an authentication failure if the service meshes which have SGW/SDR/SRG appliances are not upgraded to version 9.1.1.0

OSAM migration fails during the fix-up operation on the migrated VM with the error "Failed to perform fix-up operation on migrated VM.

Workaround: Upgrade all service meshes with OSAM Interconnect appliances (not just the HCX Manager) to 9.1.1 before triggering OSAM migrations.

VCF Services Runtime

On stretched clusters, VCF management services platform nodes deployed as Day-N operation are not automatically added to the AZ1 DRS host-affinity rules

New or scaled-out VCF management services and VCF Automation VMs are not automatically assigned to AZ1 DRS affinity rules on stretched clusters. Consequently, the nodes might run on hosts outside AZ1, which can affect the expected placement and availability of VCF management services.

Workaround: Manually move the Day-N-deployed node VMs to the AZ1 DRS affinity rule after deployment.

After VCF management services node VMs are relocated by vMotion to a new resource pool, Day-N deployment and scale-out operations fail

VCF management services node VMs are created within a pre-specified resource pool. If the VMs are moved directly in vCenter, the VCF service runtime configuration becomes out-of-sync, which results in issues for subsequent Day-N component deployment or scale-out operations.

Workaround: Do not move the VCF management services VMs to a different resource pool or folder. If VMs have already been moved, contact Broadcom Support to reconcile placement.

VCF Automation 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Getting to 9.1.1
- Product Support Notes
- Resolved Issues
  - Provider Management
  - Organization Management
  - VCF Services Runtime
- Known Issues
  - Provider Management
  - Organization Management
  - Upgrade
  - VCF Services Runtime

Introduction

VCF Automation 9.1.1.0 | 03 SEP 2026 | Build 25714559
Check for additions and updates to these release notes.

What's New

Argo CD as VCF Service

Until VMware Cloud Foundation 9.1, Argo CD was available only as a Supervisor Service. With VCF 9.1.1, Argo CD is available in the following two forms:

- **Argo CD Supervisor Service**
  Deploy and manage the Argo CD Supervisor Service in vCenter. After you deploy the Supervisor Service, use the CLI to create an Argo CD instance in a vSphere Namespace. An Argo CD instance manages workloads in vSphere Namespaces and VKS clusters. This capability is available with VCF 9.1.With VCF 9.1.1, Argo CD Supervisor Service reduces the manual toil and introduced a policy to automatically discover and attach VKS clusters to the ArgoCD instances enabling quick start managing workloads in VKS clusters. For more information, see Installing and Configuring Argo CD. The Argo CD version that is currently release is 1.2.0, check the release notes.
- **Argo CD as a VCF Service**
  VCF 9.1.1 introduces installation of the Argo CD service through the **Service Management** option in the VCF Automation Provider Management UI. The VCF Automation organization UI enables organization admin to deploy Argo CD instances to their vSphere Namespaces and then log in to the deployed Argo CD instance by using thier VCF Automation credentials to quickly start managing workloads in vSphere Namespaces and VKS clusters. See Installing and Configuring Argo CD.

  Note:

  In the VCF Automation organization UI, as an organization admin you can use the GitOps Service to deploy Argo CD instances. You can manage up to 30 vSphere Namespace across all deployed Argo CD instances in the VCF Automation. For VCF 9.1.1, Argo CD as VCF Service is release as a tech preview.

VKr Support for Argo CD

Argo CD Service support for new Kubernetes minor versions lags VKS by 2–4 months**.** Based on current upstream schedules, a June VKr receives Argo CD support in October, an October VKr receives Argo CD support in January, and a February VKr receives Argo CD support in April.

Support for VLAN-backed VPC

VCF 9.1.1.0 introduces support for VLAN-backed VPCs that are consumed via VCF Automation. In this model, all traffic flows directly on physical VLANs without overlay encapsulation. It does not support Private networks as the IP scheme is limited to the CIDRs backed by physical VLANs.

Getting to 9.1.1

For information about deploying, converging, upgrading or patching your environment to 9.1.1, see Getting to 9.1.1.

Product Support Notes

Deprecation of native management capabilities for public cloud resources

Starting with VCF Automation 9.1.1, native management capabilities for public cloud resources, including Amazon Web Services (AWS), Microsoft Azure, and Google Cloud Platform (GCP), are deprecated and disabled by default in VM Apps organizations.

This deprecation impacts new VCF Automation 9.1.1 installations and environments that were upgraded from earlier versions. Administrators with the Service Broker Administrator or Assembler Administrator role can restore full public cloud management functionality using the procedure described in Broadcom knowledge base article 448993.

- If upgrading from VCF Automation 9.0 or 9.1 to version 9.1.1, the procedure to enable full public cloud management capabilities can be applied before or after upgrade.
- If upgrading from VMware Aria Automation 8.18.x to VCF Automation 9.1.1, the reenablement procedure can only be applied after upgrade.

After native management capabilities for public cloud resources are enabled in VCF Automation 9.1.1, customers do not need to reenable the functionality for future VCF releases.

Review the affected functionality and the recommended steps for managing existing deployments.

- **Infrastructure management.** Create, read, update, and delete (CRUD) operations for the following resources are restricted: cloud accounts, cloud zones, projects, profiles (image, flavor, network, storage), networks, security groups.
- **Deployments and resources.**
  - Create, update, and delete operations are blocked for deployments that contain public cloud resources.
  - Existing deployments are marked as **Stale** except for deployments that use Terraform configurations.

    Note:

    The transition of resources to a **Stale** status after disabling NPC support and the subsequent synchronization after reenabling NPC support is not immediate. Allow time for these transitions to complete before verifying resource state.
  - All Day 2 actions on deployments are disabled, except for Lease management.

    Note:

    If a deployment lease expires when NPC support is disabled, VCF Automation attempts to enforce the lease expiration. After five automatic retry attempts, the system stops retrying. The deployment remains active with an expired lease and is not deleted. To resume system management of the lease, manually trigger a **Change Lease** action.
- **Blueprints.**
  - New blueprints that contain public cloud resources are flagged as **Invalid** and cannot be versioned or released to the catalog.
  - Existing blueprints display a warning when a user interacts with or modifies them.

    Note:

    Blueprints that use custom Terraform providers, which execute code in the user's Kubernetes environment, are not affected by this deprecation.
- **Catalog and content sources.** Existing catalog items remain visible, but deployment requests that use public cloud resources fail.
- **Onboarding.** Onboarding plans that use public cloud resources are blocked during execution.

Deprecation of BYO Velero Package Installation:

Support for bring-your-own (BYO) Velero package installation has been deprecated and will be ended in the next VCF release. If you use BYO Velero packages, remove the existing packages and enable VKS to deploy the Velero package that Broadcom supports. For more information, see the Broadcom knowledge base article 428948.

Resolved Issues

Provider Management

Storage classes with datastore clusters display incorrect total capacity in regions

When you create a storage class that includes a datastore cluster, the total capacity of the storage class does not include the datastore cluster capacity. This problem occurs because the vCenter listener ignores storage pod events. As a result, the datastore table is not populated with the storage pod, and the storage capacity calculations exclude the storage pods.

Region quota update tasks fail with a generic exception when a stale VCF Automation content library is detected

When you modify a region quota for an organization, if the system encounters a stale or missing VCF Automation content library, the update task fails with an exception. The error log provides only a generic message that does not identify the specific content library that caused the failure.

Organization Management

Custom forms with drop-down fields populated with VCF Operations orchestrator actions fail validation

After upgrading from VCF Automation 9.0.2 to VCF Automation 9.1.x, submitting custom forms that contain a drop-down field with a value list populated by VCF Operations orchestrator actions fails to validate. For VCF Operations orchestrator actions that return Properties objects in a key:value pair format, the backend validation compares the submitted values against an expected value list that contains null values. In VCF Automation 9.0, action results used the format `[\{"id": "<key>", "name": "<value>"}]`. In VCF Automation 9.1, however, the format changed to `[\{"key": "<key>", "value": "<value>"}]` so the validation fails when a user submits a form with incorrectly formatted data.

Saving a VCF cloud account associated with a deleted NSX cloud account fails

When deleting a VCF cloud account that uses a NSX cloud account, which is shared between multiple VCF cloud accounts, the NSX cloud account gets deleted despite still being used by other VCF accounts. When updating another VCF cloud account associated with the deleted NSX cloud account, saving the updates fails with the error `com.vmware.admiral.vcf.exception.VcfException: Failed to find associated internal NSX account for VCF`. This causes data corruption for the NSX account that gets deleted and subsequent loss of data.

VCF Services Runtime

During upgrade of VCF Automation from 9.0 to 9.1, the process might stop responding at the backup stage for up to 120 minutes and display only a generic timeout error

This behavior affects administrators performing the upgrade and can cause uncertainty about whether the upgrade is progressing or has failed. This issue is fixed in this release and upgrade fails fast on a backup failure and displays a clear error.

Entering a hostname or FQDN in mixed case caused failures in install, upgrade, import, and other operations of VCF Automation

Issue occurs due to case-sensitive Domain Name System (DNS) and certificate matching. This issue is fixed in this release and all FQDNs can use mixed case.

When you power on a VCF Automation cluster, some services might fail to resume

After a shutdown or a power-cycle of the cluster, one or more services could fail to start automatically and required manual recovery. This issue is fixed in this release and services recover automatically after power-on.

VCF Automation can accumulate log buffers, which results in the logger disk to fill up and health-check failures

Fluentd log buffers and retained backup chunks can accumulate on the logging disk until available disk space is exhausted. When the logging disk reaches capacity, platform health checks fail and block platform operations. This issue is fixed in this release and logging buffer is improved.

Known Issues

Provider Management

Synchronization of a subscribed content library fails with an HTTP 401 error

In the VCF Automation Provider Management UI, when you subscribe a content library to a password-protected vCenter content library, the subscription and metadata synchronization succeed. However, newly added content library items, which trigger a fresh file download, are stuck downloading. An HTTP 401 error is thrown when the item's file content is downloaded. Synchronizing to an unchanged vCenter library or one without password protections is not affected.

Workaround: None.

Creating a subscribed content library fails with an HTTP 401 error

In the VCF Automation Provider Management UI, when you create a subscribed content library by using a subscription link to a vCenter content library that is protected by a password, the creation fails wit a 401 error.

Workaround: Remove the password from the vCenter content library.

vCenter is wrongly listed as Licensed while in evaluation mode

If a vCenter instance is still in evaluation mode, the main VCF Automation banner displays correct information about the licensing evaluation period and prompts you to add a licensed instance vCenter 9.0 or later. However, on the **Connections** page in the VCF Automation Provider Management UI, the vCenter instance is wrongly listed as `Licensed`.

Workaround: Use the warning banner in the VCF Automation Provider Management UI to monitor your evaluation period and ensure that you license your vCenter instances before the evaluation expires.

A field validation error incorrectly appears in the New Volume dialog box

When you publish a VM image and you try to add a new volume, a **New Volume** dialog box opens and immediately shows a warning about a missing size, even though you have not entered a value for the size of the new volume. Also, if you enter an invalid name in the respective field, no validation warning appears, but the **Create** button is deactivated. The dialog box operates correctly despite the incorrect warnings.

Workaround: None.

A newly created VM class in the vSphere Supervisor is not visible in the VCF Automation Provider Management UI

Newly created VM classes for a Supervisor might not be visible when you click a region from the **Regions** panel in the VCF Automation Provider Management UI, even if you manually refresh the connection to the vCenter instance. The issue occurs when the vCenter instance supports organizations for VM apps and the **Mixed Tenancy Mode** feature flag is deactivated in Provider Manager. In such cases, new custom VM classes are not detected and displayed in the VCF Automation Provider Management UI.

Workaround:

1. Log in to the VCF Automation Provider Management UI.
2. Navigate to **Feature Flags** and enable **Mixed Tenancy Mode.**

Deleting a region quota fails with an error and the region quota remains visible and in a Ready state

When you upgrade VCF Automation from 9.0.x to 9.1.1 and try to delete a region quota that is created before the upgrade, the delete request is accepted but the operation fails with an error. Region quotas that are created after the VCF Automation upgrade are not affected.

This issue occurs because during a VCF Automation upgrade, the storage class configuration data that belongs to existing region quotas is migrated to a new internal format that is introduced in version 9.1.0.0. During the upgrade, the data is copied, but the old copy is not deleted. As a result, when you attempt to delete region quotas created before the VCF Automation upgrade, the system encounters the leftover configuration data and the deletion fails.

Workaround: See Broadcom knowledge base article 453765.

The vksm service installation fails after a VCF Automation upgrade

After a VCF Automation upgrade, the vksm service installation fails with an installation error. The error occurs when the service upgrade starts on top of a previous version that never completed installation properly, or on a previous installation that is stuck in uninstallation while still retaining some of its resource custom resources. The new version creates its own resources instead of transferring the existing ones, and these resources overlap with those from the previous version. The overlap triggers an `already exists` validation error, and the installation fails.

Workaround: Clean up the old version of the service, then reinstall the new version.

1. Log in to the VCF Automation Provider Management UI.
2. In the left navigation pane, click **Service Management**.
3. Click **VCF Services**.
4. On the card of the previous vksm service, click **Uninstall**.
5. After uninstallation completes, on the card of the service, click **Delete**.
6. Install the new version of the vksm service.

Partner services does not display resolving status after uploading the `argocd` service tar file

When you upload the `argocd` service tar file in the **Partner services** section to install the `argocd` service, the UI does not display the resolving status with a loading indicator. Instead, the status remains in an unresolved state. Only the status indicator is affected; the underlying installation behavior is unchanged. The service resolves after 3-4 minutes and moves to the **VCF Services** tab in the `Not Installed` state, ready for further user actions.

Workaround: None.

Region creation fails with the `Following zones of the specified supervisors do not have a network stack configured` error

In VCF Automation 9.1.1, provider administrators must select a network stack when creating a region. The network stack is fetched from NSX. When creating a region with a VLAN-backed network stack, the region creation might fail with the error `Following zones of the specified supervisors don't have a network stack configured`. This is caused by an intermittent issue where network stacks for zones are not populated from NSX.

Workaround:

1. Using the VCF Automation Provider Management UI:
   a. In the VCF Automation Provider Management UI, select Administration select **Connections**.
   b. Under **vCenter**, identify the vCenter instances whose supervisors are included in the region.
   c. Click the three dots next to the vCenter instance and click **Refresh**.
      Once the refresh finishes, the network stack details for every zone are obtained from NSX.
   d. Attempt to create the region again.
2. Using the VCF Automation Provider Management API
   a. Invoke the refresh VC endpoint.
      ```
      POST https://<vcfa-endpoint>/api/admin/extension/vimServer/<vc-id>/action/refresh
      ```
      Payload is empty. After a successful refresh, the network stack details for zone are populated and the region is successfully created.

Organization Management

Pod details not displayed in the VCF Automation organization portal

In the VCF Automation organization, when you navigate to **Manage&Govern** > **Kubernetes Managment** > **Clusters**, you click a cluster and navigate to the **Nodes** tab for the cluster, and you click a pod name to see pod details, a blank page is displayed instead of a pod details page.

Workaround: Append a `/` symbol and the namespace name of the pod to URL of the blank page.

Example:

Blank page URL: `https://vcfa-host/tenant/:id/automation/#/manage-and-govern/km/workloads/kubernetes-cluster-0875/kube-system/pods/antrea-agent-rcbvb`

Pod details URL: `https://vcfa-host/tenant/:id/automation/#/manage-and-govern/km/workloads/kubernetes-cluster-0875/kube-system/pods/antrea-agent-rcbvb/vc01-ns-19-4n464`

When saving a network profile or a cloud zone, the user is presented with a Discard Changes dialog In

When creating a network profile or a cloud zone in a VCF Automation organization for VM Apps, filling out the creation form so that it is valid, and then saving the form, the user is presented with a Discard Changes dialog.

Workaround: In the dialog, click **Discard** and navigate to the main Network Profile or Cloud Zone page. Confirm that the network profile or the cloud zone is available.

Upgrade

VCF Operations orchestrator logs fill disk space on VCF Automation appliances upgraded from VMware Aria Automation 8.18.x

In environments upgraded from VMware Aria Automation 8.18.x to VCF Automation 9.x, the log deletion policy is missing so VCF Operations orchestrator logs accumulate and fill the disk space on the VCF Automation appliance nodes. When disk usage reaches 100%, VCF Automation stops working. When the user runs the kubectl get pods -A command, they observe a large number of orphaned pods.

Workaround: Follow the procedure described in Broadcom knowledge base article 458715.

Patching the migration service engine component to version 9.1.1 fails and times out after several hours

This problem occurs when you patch migration service engine to version 9.1.1 before you upgrade VCF Automation to version 9.1.1. Migration service engine 9.1.1 requires updated database capabilities that are only delivered with VCF Automation 9.1.1. Patching the migration service engine on an earlier VCF Automation platform causes the component to hang during deployment and ultimately fail with an "Step vmsp_upgrade failed. Reference Code: 85616483." error.

Workaround: Upgrade VCF Automation to version 9.1.1 before you patch the migration service engine component. See Broadcom knowledge base article 455559.

VCF Automation and migration service engine patches fail with a com.vmware.vcfms.system.precheck.backup.PackageDeploymentsCompleteWaitTimeout error

If you tried to patch the migration service engine to 9.1.1 before the VCF Automation is patched to 9.1.1, the patching of both components becomes blocked.

Workaround: To unblock the patch of VCF Automation to 9.1.1, follow the instructions in Broadcom knowledge base article 455559.

Custom Day-2 actions intermittently disappear and are unavailable from the deployment actions menu in VCF Automation for VM Apps

In VM Apps organizations in VCF Automation 9.1.1, custom day 2 resource actions, like a custom Deployment Delete action bound to deployment resources, might intermittently fail to render or populate in the Actions drop-down menu. This issue occurs when day 2 policy entitlement evaluations or custom resource action bindings temporarily fail to refresh or synchronize for active deployments. The issue impacts environments that were upgraded from VMware Aria Automation 8.18.1 to VCF Automation 9.1.1.

Workaround: Follow the procedure described in Broadcom knowledge base article 454245.

Upgrading VCF Automation 9.0.1, 9.0.2.X, or 9.1.0.X to VCF Automation 9.1.1 fails

During upgrade, any custom profiles applied on VCF Automation 9.0.1, 9.0.2.X, or 9.1.0.X cause the upgrade to VCF Automation 9.1.1 to fail. Custom profiles are drop-in configuration overlays applied to VCF Automation services. During an upgrade to a version earlier than 9.1.1, the profile artifacts from the source release are not compatible and cause the upgrade to fail.

Workaround: Follow the steps in Broadcom knowledge base article 451147.

Upgrading VMware Aria Automation 8.18.x to VCF Automation 9.1.1 fails with an internal error

When upgrading VMware Aria Automation 8.18.x to VCF Automation 9.1.1, the system uses name resolution to convert user-friendly names to IP addresses. Whenever the connection to your DNS server experiences connectivity issues or resolution does not work as expected, VCF Automation might produce the wrong output when resolving names. Using the incorrect output further in the upgrade can cause the upgrade to fail with the following error:

```
ERROR (CC26CB94) com.vmware.vcfms.virtualmachine.VirtualMachineNotFound [VCFMS-VM-002]:
  Internal error occurred. Failed to locate virtual machine
  ;; communications error to <DNS IP address>#53: timed out.
  Please retry the operation or contact support if the issue persists. (<VM IP address>)
```

Workaround:

1. Restart the VMware Aria Automation 8.18.x services. See Starting and stopping VMware Aria Automation.
2. Ensure that DNS resolution in the reported DNS works and is stable.
3. Run the upgrade again.

   Note:

   If the upgrade still fails, use the procedure described in Broadcom knowledge base article 441333 and then run the upgrade again.

VCF Services Runtime

On stretched clusters, VCF Automation platform nodes deployed as Day-N operation are not automatically added to the AZ1 DRS host-affinity rules

New or scaled-out VCF Automation VMs are not automatically assigned to AZ1 DRS affinity rules on stretched clusters. Consequently, the nodes might run on hosts outside AZ1, which can affect the expected placement and availability of VCF Automation.

Workaround: Manually move the Day-N-deployed node VMs to the AZ1 DRS affinity rule after deployment.

After VCF Automation node VMs are relocated by vMotion to a new resource pool, Day-N deployment and scale-out operations fail

VCF Automation node VMs are created within a pre-specified resource pool. If the VMs are moved directly in vCenter, the VCF Automation configuration becomes out-of-sync, which results in issues for subsequent Day-N component deployment or scale-out operations.

Workaround: Do not move the VCF Automation VMs to a different resource pool or folder. If VMs have already been moved, contact Broadcom Support to reconcile placement.

VCF SDKs, APIs, and CLIs

This document provides a consolidated summary of all changes made to the API layer across various VCF components. It highlights newly introduced APIs, removed APIs, deprecated APIs, updated APIs, and structural modifications. For in-depth information on each change, click the hyperlink associated with the corresponding API specification. This will take you to a dedicated page on the Broadcom Developer Portal with comprehensive details about the specific modifications.

VMware Cloud Foundation SDKs 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Product Support Notes
- Resolved Issues

Introduction

VMware Cloud Foundation SDKs 9.1.1.0 | 03 SEP 2026 | Build 25714914 Check for additions and updates to these release notes.

What's New

VCF SDK 9.1.1 is a security-focused maintenance release. This release does not introduce any new VCF components, and no VCF component samples are added or removed.

Security Enhancements

VCF SDK 9.1.1 addresses potential vulnerabilities and strengthens the security of VCF SDKs. Several dependent libraries are upgraded to make VCF SDK more secure and reduce exposure to known security risks.

What's New in This Release

- No new VCF components are added in VCF 9.1.1.
- No new VCF component samples are added or removed in VCF 9.1.1.

Product Support Notes

VMware Cloud Foundation Java SDK

Java Version Requirements

Java 17 is the minimum requirement for the VCF Java SDK in the 9.1.1.0 release. The SDK is compatible with the following Java LTS versions: 17, 21, and 25. It is strongly recommended to use one of those versions when integrating the SDK into custom applications and when running the samples.

Apache CXF Upgrade

The VCF Java SDK modules for the SOAP APIs of vSphere and vSAN — namely vim25, pbm, sms, ssoclient, vslm, and eam — now use Apache CXF 4.1.7 to provide patches for CVEs and strong security postures for the SDK and the applications consuming it. This version of Apache CXF requires Java 17 and is compatible with modern, well-supported APIs and implementations such as Jakarta EE 10, Spring 6, and Spring Boot 3.

VMware Cloud Foundation Python SDK

Python Version Compatibility

All modules of the VCF Python SDK are compatible with and verified against the supported versions of Python at the time of their release. Once a Python version reaches End-Of-Life (EOL), it no longer receives security patches. VCF Python SDK releases that occur after this moment do not provide compatibility guarantees for the EOL-ed Python version. As a general best practice and for the strongest security posture, use the VCF Python SDK with an actively maintained version of Python and keep your environment on the latest patch provided by the Python Software Foundation (PSF).

For the VCF 9.1.1.0 release, the supported Python versions are 3.10, 3.11, 3.12, 3.13, and 3.14.

Resolved Issues

pyVmomi Type Hints

The following type hint issues are resolved in this release:

- **Fixed name collisions in type hint stubs**.
  Resolved collisions where multiple packages defined classes with the same short name (for example, `ConfigInfo`). Cross-package and `stdlib` references are now fully qualified, ensuring correct type resolution across all packages.
- **Fixed `vmodl.MethodFault` stub.**
  The stub now correctly inherits from both `Exception` and `DynamicData`. Previously, the emitted `__init__.pyi` declared `MethodFault(Exception)` only, which caused type checkers to reject assignments and attribute access that relied on its `DynamicData` lineage.
- **Removed `vmodl.DataObject` and `vmodl.ManagedObject`**.
  These were empty type hint classes that erroneously overrode the actual class definitions from `VmomiSupport.py`. Removing them restores correct type resolution.

VMware Cloud Foundation PowerCLI 9.1.1.0 Release Notes

This document contains the following sections

- Introduction
- What's New
- Product Support Notes
- Resolved Issues

Introduction

VMware Cloud Foundation PowerCLI 9.1.1.0 | 14 SEP 2026 | Build 25718932
Check for additions and updates to these release notes.

VMware Cloud Foundation PowerCLI 9.1.1.0 focuses on delivering a more secure and resilient automation platform designed to address evolving threat landscapes, including emerging vulnerability risks linked to Mythos frameworks and modern AI agent environments. This release prioritizes hardened certificate validation, upgraded core dependencies, and clearer diagnostics for mission-critical automation pipelines.

What's New

Image Builder and lifecycle security

Python 3.14 Support: The Image Builder module now officially supports Python 3.14, enabling customers with strict compliance rules to continue patching and updating safely.

> **Important:**
>
> In alignment with Python lifecycle policies, support for Python 3.7, 3.8, and 3.9 has been removed. Users must run Python 3.10 or higher to maintain product support and compatibility.

Product Support Notes

VMware.VimAutomation.Common

- **PowerShell Core Minimum Requirement**
  Raised the minimum supported PowerShell Core version to **7.0.13** to maintain compliance with baseline security and stability standards.

Resolved Issues

- **`Open-VMConsoleWindow`**
  Resolved connection failures with modern servers utilizing updated certificate checksum algorithms, ensuring secure console access.
- **`New-NetworkAdapter`**
  Fixed a `NullReferenceException` triggered when providing an invalid MAC address, improving execution resilience.
- **Content Library Cmdlets**
  Updated error handling to surface exact server-side failure messages instead of generic errors.
- **Content Library Subscriptions**
  Improved diagnostic accuracy when handling SSL certificate thumbprint mismatches during subscription synchronization.

Changelog for VCF 9.1.1.0

This document provides a consolidated summary of all changes made to the API layer across various VCF components. It highlights newly introduced APIs, removed APIs, deprecated APIs, updated APIs, and structural modifications. For in-depth information on each change, click the hyperlink associated with the corresponding API specification. This will take you to a dedicated page on the Broadcom Developer Portal with comprehensive details about the specific modifications.

vSphere

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
Virtual Infrastructure JSON API	0	0	0
vSphere Automation API	6	0	0

NSX

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
NSX Autonomous Edge API	0	0	0
NSX Global Policy API	0	0	0
NSX Manager API	2	2	0
NSX Policy API	11	0	0

VCF Operations

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
Log Management API	0	0	0
VCF Operations API	31	0	0
VCF Operations for Networks API	0	0	0

SDDC Manager

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
SDDC Manager API	6	0	0

VMware Identity Broker

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
VMware Identity Broker - vCenter Server API	2	0	0

VCF Installer

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
VCF Installer API	1	0	0

HCX Management Platform

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
HCX Manager Appliance Management APIs	5	0	0

LCM

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
VCF Fleet LCM Service APIs	2	0	0
VCF SDDC LCM Service APIs	1	0	0

Org Management - All Apps Org

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
All Apps Org - Access Control	8	0	3
All Apps Org - Custom Resource Types And Actions	0	0	0

Org Management - VM Apps Org

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
VM Apps Org - Access Control	8	0	2
VM Apps Org - Custom Forms	0	0	0

Private AI Services

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
VMware Private AI Service API	0	4	0

Provider Infrastructure APIs

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
Provider Infrastructure APIs	15	0	4

Realtime Metrics

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
Realtime Metrics API	0	0	0

VMware Data Service Manager

SPECIFICATION	NEW OPERATIONS	DEPRECATED OPERATIONS	DELETED OPERATIONS
VMware Data Services Manager REST API	0	0	0

Changelog for NSX NSX Policy API

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	11	3	0	0
Structures	7	21	0	1

Total changes: 54

Operation Changes

New Operations

VERB	PATH
GET	/infra/settings/firewall/security/malware-prevention-service/exclusions
GET	/infra/settings/firewall/security/malware-prevention-service/exclusions/{exclusion-id}
PUT	/infra/settings/firewall/security/malware-prevention-service/exclusions/{exclusion-id}
PATCH	/infra/settings/firewall/security/malware-prevention-service/exclusions/{exclusion-id}
DELETE	/infra/settings/firewall/security/malware-prevention-service/exclusions/{exclusion-id}
GET	/infra/settings/scrx/cluster-configs/{cluster-id}/status
GET	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/feature-opt-in
PUT	/infra/sites/{site-id}/enforcement-points/{enforcementpoint-id}/host-transport-nodes/feature-opt-in
GET	/infra/tier-0s/{tier-0-id}/tls-inspection-state
GET	/infra/tier-0s/{tier-0-id}/tls-inspection-state/fqdns
GET	/infra/tier-0s/{tier-0-id}/tls-inspection-state/fqdns/{fqdn-id}

Updated Operations

GET /infra/tier-0s/{tier-0-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Parameter added: `backward_compatible`

GET /infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Parameter added: `backward_compatible`

GET /orgs/{org-id}/projects/{project-id}/infra/tier-1s/{tier-1-id}/l2vpn-services/{service-id}/sessions/{session-id}/peer-config

- Parameter added: `backward_compatible`

Deprecated Operations

No changes.

Deleted Operations

No changes.

Data Structure Changes

New Structures

Structure Name
ChildMpsExclusion
FeatureOptIn
HostScrxResizeStatus

Structure Name
IdsProfileSignature
MpsExclusion
MpsExclusionListResult
ScrxResizeStatus

Updated Structures

ConfigurationStateElement

- New Property: `core_allocation_profile`

DistributedVxlanConnection

- New Property: `direct_path`

FeatureUsages

- New Property: `NETWORK_TRAFFIC_ANALYSIS`

IdsProfileSignatures

- Updated Property: `signatures` From `array` to `IdsProfileSignature`

MalwarePreventionProfile

- New Property: `fileless_enabled`
- New Property: `local_exclusions`
- New Property: `file_size`

PolicyEdgeCluster

- New Property: `core_allocation_profile`

PolicyEdgeClusterMemberState

- New Property: `core_allocation_profile`

PolicyTransportZone

- New Property: `is_security`

PolicyVmApplianceConfig

- New Property: `core_allocation_profile`

ScrxClusterConfig

- New Property: `available_mem_size`
- New Property: `force_reconfiguration`
- New Property: `num_vcpus`
- New Property: `reserved_mem_size`
- New Property: `size`

ScrxSizeInfo

- New Property: `available_mem_size`
- New Property: `num_vcpus`
- New Property: `reserved_mem_size`
- New Property: `size`

SecurityLicenseUsageCSVRecord

- New Property: `licensed_host_core_count_nta`
- New Property: `raw_host_core_count_nta`

StaticMimeContent

- New Property: `html_template`
- New Property: `html_template_with_message`

SubjectAltNames

- New Property: `emails`

TraceflowObservationDelivered

- New Property: `reason`

TraceflowObservationDropped

- New Property: `uplink_name`

TransportNodeState

- New Property: `core_allocation_profile`

VirtualNetworkApplianceClusterMemberState

- New Property: `core_allocation_profile`

VirtualNetworkApplianceDeploymentConfig

- New Property: `host_affinity_config`

VmApplianceState

- New Property: `core_allocation_profile`

VpcServiceInstanceStatus

- New Property: `periodic_garp_interval`

Deprecated Structures

No changes.

Deleted Structures

Structure Name
DirectoryAdGroup

Changelog for NSX NSX Manager API

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	2	0	2	0
Structures	1	13	0	1

Total changes: 26

Operation Changes

New Operations

VERB	PATH
POST	/systemhealth/container-cluster/ncp/status/advanced
POST	/trust-management/certificates/action/replace-host-certificate-generated/{host-id}/{certificate-id}

Updated Operations

No changes

Deprecated Operations

VERB	PATH
GET	/fabric/compute-managers/thumbprint-hashing-algorithm
PUT	/fabric/compute-managers/thumbprint-hashing-algorithm

Deleted Operations

No changes.

Data Structure Changes

New Structures

Structure Name
ContainerClusterStatusFilter

Updated Structures

ComputeManagerStatus

- New Property: `machine_ssl_cert_id`
- New Property: `certificates`

ConfigurationStateElement

- New Property: `core_allocation_profile`

DiscoveredNode

- New Property: `patch_level`

EdgeCluster

- New Property: `core_allocation_profile`

EdgeNodeSettings

- New Property: `core_allocation_profile`

FeatureUsages

- New Property: `NETWORK_TRAFFIC_ANALYSIS`

NodeUserProperties

- New Property: `password_expires`
- New Property: `last_password_change_epoch`
- New Property: `password_expires_epoch`
- New Property: `locked`
- New Property: `account_expires`

PasswordComplexityProperties

- New Property: `invalid_password_chars`
- New Property: `invalid_password_patterns`

SecurityLicenseUsageCSVRecord

- New Property: `raw_host_core_count_nta`

- New Property: `licensed_host_core_count_nta`

SubjectAltNames

- New Property: `emails`

TraceflowObservationDelivered

- New Property: `reason`

TraceflowObservationDropped

- New Property: `uplink_name`

TransportNodeState

- New Property: `core_allocation_profile`

Deprecated Structures

No changes.

Deleted Structures

Structure Name
DirectoryAdGroup

Changelog for NSX NSX Global Policy API

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	0	0	0	0
Structures	3	12	0	0

Total changes: 19

Operation Changes

New Operations

No changes.

Updated Operations

No changes

Deprecated Operations

No changes.

Deleted Operations

No changes.

Data Structure Changes

New Structures

Structure Name
ChildMpsExclusion
IdsProfileSignature

Structure Name
MpsExclusion

Updated Structures

ConfigurationStateElement

- New Property: `core_allocation_profile`

DistributedVxlanConnection

- New Property: `direct_path`

FeatureUsages

- New Property: `NETWORK_TRAFFIC_ANALYSIS`

IdsProfileSignatures

- Updated Property: `signatures` From `array` to `IdsProfileSignature`

MalwarePreventionProfile

- New Property: `local_exclusions`
- New Property: `file_size`
- New Property: `fileless_enabled`

PolicyEdgeCluster

- New Property: `core_allocation_profile`

PolicyTransportZone

- New Property: `is_security`

SecurityLicenseUsageCSVRecord

- New Property: `raw_host_core_count_nta`
- New Property: `licensed_host_core_count_nta`

StaticMimeContent

- New Property: `html_template`
- New Property: `html_template_with_message`

SubjectAltNames

- New Property: `emails`

TraceflowObservationDelivered

- New Property: `reason`

TraceflowObservationDropped

- New Property: `uplink_name`

Deprecated Structures

No changes.

Deleted Structures

No changes.

Changelog for NSX NSX Autonomous Edge API

These are all the changes between the previous version and the current version.

	NEW	UPDATED	DEPRECATED	DELETED
Operations	0	0	0	0
Structures	0	2	0	0

Total changes: 7

Operation Changes

New Operations

No changes.

Updated Operations

No changes

Deprecated Operations

No changes.

Deleted Operations

No changes.

Data Structure Changes

New Structures

No changes.

Updated Structures

NodeUserProperties

- New Property: `password_expires_epoch`
- New Property: `locked`
- New Property: `account_expires`
- New Property: `password_expires`
- New Property: `last_password_change_epoch`

PasswordComplexityProperties

- New Property: `invalid_password_patterns`
- New Property: `invalid_password_chars`

Deprecated Structures

No changes.

Deleted Structures

No changes.

Patch Releases 9.1.0.x

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch release notes cover only newly identified known issues for each release. All known issues documented in earlier releases remain valid until a subsequent release resolves them. VCF releases are cumulative, so each release includes all fixes from earlier releases.

For more information, see Lifecycle Management in VMware Cloud Foundation.

To see an AI-generated list of all available patch releases, grouped by release date, click here.

You can use a similar sample search to get details on the content and builds for any of the VCF Components.

- vSphere
- vSAN
- NSX
- SDDC Manager
- VCF Operations
- VCF Automation

vSphere

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for vSphere 9.1.0.x:

- ESX
- vCenter

ESX

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for ESX 9.1.0.x:

- VMware ESX 9.1.0.0100 Release Notes
- VMware ESX 9.1.0.0200 Release Notes

VMware ESX 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Build Details
  - VMware ESX 9.1.0.0100
  - Applying the Patch
- Known Issues

Introduction

VMware ESX 9.1.0.0100 | 05 JUN 2026 | Build 25433460 Check for additions and updates to these release notes.

What's New

- This live-patchable release contains various security enhancements. The patch includes updates to the NSX kernel modules.

Build Details

VMware ESX 9.1.0.0100

Build Details

VMware vSphere Hypervisor (ESX) Offline Bundle

Download Filename:	VMware-ESXi-9.1.0.0100.25433460-depot.zip
Build:	25433460
Download Size:	692 MB
SHA256 checksum:	a55b746cb959b502c12cfb7dfd5b54653f136fb6ea90857b56754340a4478644
Live Patchable	Yes
Host Reboot Required:	No
Virtual Machine Migration or Shutdown Required:	No

VMware vSphere Hypervisor (ESX) ISO image

Download Filename:	VMware-VMvisor-Installer-9.1.0.0100.25433460.x86_64.iso
Build:	25433460
Download Size:	711.19 MB
SHA256 checksum:	98a8bd08e6b35acc59795640fa240b027a6d28f253d37d902c80a2a22afc7597

ESX Images

Name and Version	Release Date	Category	Live Patchable	Detail
ESXi-9.1.0.0100-25433460	05 June 2026	Security	Yes	Security only image

Image Profiles

VMware patch and update releases contain general and critical image profiles. Application of the general release image profile applies to new bug fixes.

Image Profile Name
ESXi-9.1.0.0100-25433460-standard
ESXi-9.1.0.0100-25433460-no-tools

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement, VMware vSphere Foundation or VMware Cloud Foundation.

For download instructions, see Download Broadcom products and software.

See these KBs for details on the authenticated online and offline download: 390121, 390098, and 389276.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, for details on updates and upgrades by using vSphere Lifecycle Manager, see What is vSphere Lifecycle Manager and vSphere Lifecycle Manager Images and Baselines. You can also update ESX hosts without the use of vSphere Lifecycle Manager by using an image profile. To do this, you must manually download the patch offline bundle ZIP file or see the Broadcom knowledge base article How to download ESXi ISO image for all releases including patch updates.

For more information, see Using ESXCLI for Host Management and the VMware ESX Upgrade guide.

Known Issues

Live patch pre-check fails on vSAN compute clusters causing ESX upgrades to fail

When initiating a live patch ESX upgrade on a vSAN compute cluster, the pre-remediation health check shown in the vSphere Client fails with the following error:

```
The health check failed to complete.
```

This precheck failure blocks the upgrade process for the ESX hosts in the vSAN compute cluster.

This issue only affects vSAN compute clusters that do not have any local vSAN storage like in vSAN HCI or vSAN Storage cluster.

Workaround: Disabling the live patch vSAN health checks on vSAN compute clusters allows the process to continue. See Broadcom knowledge base article 442180.

VMware ESX 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Build Details
  - VMware ESX 9.1.0.0200
- Applying the Patch

Introduction

VMware ESX 9.1.0.0200 | 13 JUL 2026 | Build 25557999 Check for additions and updates to these release notes.

What's New

- This release contains various security enhancements.

Build Details

VMware ESX 9.1.0.0200

Build Details

VMware vSphere Hypervisor (ESX) Offline Bundle

Download Filename:	VMware-ESXi-9.1.0.0200.25557999-depot.zip
Build:	25557999
Download Size:	673 MB
SHA256 checksum:	d3e21e885f59282598f1ba5b7a550741037f67f048fb28a439cd6b8b8c139272
Live Patchable	No
Host Reboot Required:	Yes
Virtual Machine Migration or Shutdown Required:	Yes

VMware vSphere Hypervisor (ESX) ISO image

Download Filename:	VMware-VMvisor-Installer-9.1.0.0200.25557999.x86_64.iso
Build:	25557999
Download Size:	693 MB
SHA256 checksum:	a4e2b45c9438d6134ba7226b978cbabda0b75670c623c805ad60c81392f35e3f

ESX Images

Name and Version	Release Date	Category	Live Patchable	Detail
ESXi-9.1.0.0200-25557999	13 July 2026	Security	No	Security only image

Image Profiles

VMware patch and update releases contain general and critical image profiles. Application of the general release image profile applies to new bug fixes.

Image Profile Name
ESXi-9.1.0.0200-25557999-standard
ESXi-9.1.0.0200-25557999-no-tools

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement, VMware vSphere Foundation or VMware Cloud Foundation.

For download instructions, see Download Broadcom products and software.

See these KBs for details on the authenticated online and offline download: 390121, 390098, and 389276.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, for details on updates and upgrades by using vSphere Lifecycle Manager, see What is vSphere Lifecycle Manager and vSphere Lifecycle Manager Images and Baselines. You can also update ESX hosts without the use of vSphere Lifecycle Manager by using an image profile. To do this, you must manually download the patch offline bundle ZIP file or see the Broadcom knowledge base article How to download ESXi ISO image for all releases including patch updates.

For more information, see Using ESXCLI for Host Management and the VMware ESX Upgrade guide.

vCenter

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for vCenter 9.1.0.x:

- VMware vCenter 9.1.0.0100 Release Notes
- VMware vCenter 9.1.0.0200 Release Notes
- VMware vCenter 9.1.0.0300 Release Notes

VMware vCenter 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Build Details
  - VMware vCenter 9.1.0.0100
  - Applying the Patch
- Known Issues

Introduction

VMware vCenter 9.1.0.0100 | 05 JUN 2026| Build 25417926 Check for additions and updates to these release notes.

What's New

- This release contains various security enhancements.

Build Details

VMware vCenter 9.1.0.0100

Build Details

Download Filename:	VMware-vCenter-Server-Appliance-9.1.0.0100.25417926-patch-FP.iso
Build:	25417926
Download Size:	8628.3 MB
SHA256 checksum:	962b6a6442bee9ae5d0988ca2b1ef9b1c7cba5aeb2c8fe9a69df696a44409a3f

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement.

For download instructions, see Download Broadcom products and software.

For more information on using the vCenter shells, see Broadcom knowledge base article 2100508.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, see Upgrading the vCenter Appliance.

Known Issues

A reset of the vSphere Lifecycle Manager database might cause data loss in the Supervisor

If the vSphere Lifecycle Manager database in your environment is reset before upgrading vCenter from versions 8.0 Update 3 and later or 9.0.x to 9.1.0 or 9.1.1, the upgrade might cause data loss in the Supervisor. To avoid data loss, before a vCenter upgrade, you must first check your environment and take mitigation steps, if necessary.

Workaround: See Broadcom knowledge base article 455737 for instructions how to check if your environment is affected and for mitigation steps.

VMware vCenter 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction

- What's New
- Product Support Notes
- Build Details
  - VMware vCenter 9.1.0.0200
- Applying the Patch
- Known Issues

Introduction

VMware vCenter 9.1.0.0200 | 13 JUL 2026 | Build 25573614
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

For vSphere Supervisor updates, see the vSphere Supervisor Release Notes.

Product Support Notes

Ruby vSphere Console (RVC) is no longer available in the Appliance Shell:

With vCenter 9.1.0.0200, the interactive CLI for managing and monitoring vCenter environments especially for vSAN operations, RVC, is no longer available in the the restricted Appliance Shell, used for system commands and API tasks. RVC is deprecated and will be removed in a future vCenter release. You can still use RVC in the standard BASH shell.

Build Details

VMware vCenter 9.1.0.0200

Build Details

Download Filename:	VMware-vCenter-Server-Appliance-9.1.0.0200.25573614-patch-FP.iso
Build:	25573614
Download Size:	8625.2 MB
SHA256 checksum:	17bda708f1e58baf5c127f4f4caf31fe4d17b7d43ec8ad84bd89ef9bafe06e9b

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement.

For download instructions, see Download Broadcom products and software.

For more information on using the vCenter shells, see Broadcom knowledge base article 2100508.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, see Upgrading the vCenter Appliance.

Known Issues

A reset of the vSphere Lifecycle Manager database might cause data loss in the Supervisor

If the vSphere Lifecycle Manager database in your environment is reset before upgrading vCenter from versions 8.0 Update 3 and later or 9.0.x to 9.1.0 or 9.1.1, the upgrade might cause data loss in the Supervisor. To avoid data loss, before a vCenter upgrade, you must first check your environment and take mitigation steps, if necessary.

Workaround: See Broadcom knowledge base article 455737 for instructions how to check if your environment is affected and for mitigation steps.

vCenter backup taken in Ehanced Linked Mode (ELM) cannot be restored after breaking ELM

When a vCenter is in ELM, its Single Sign-On (SSO) domain maintains replication agreements with all partner vCenters. Backups taken in ELM environments capture such replication agreements. After breaking ELM, linked vCenter instances are removed from the topology, but the restored backup tries to re-establish SSO sync with them. As a result, the backup fails to restore with a message such as `Error Failed to synchronize SSO data with partners.`

Workaround: After breaking ELM, take new backups to use for vCenter restore.

During vCenter Reduced Downtime Upgrade (RDU), you see a warning that does not correctly display the version of VCF Operations and the target vCenter version

During RDU from VCF version 9.0.x to 9.1, in the vSphere Client, you might see a precheck warning such as `Registered VCF Ops's version '%(0)s' is lower than the target vCenter's '%(1)s`, in which versions are not correctly displayed.

Workaround: Ensure that VCF Operations is upgraded before vCenter to a version matching the new desired vCenter version, for example 9.1. You can ignore the error message.

VMware vCenter 9.1.0.0300 Release Notes

This document contains the following sections

- Introduction
- What's New
- Build Details
  - VMware vCenter 9.1.0.0300
- Applying the Patch
- Known Issues

Introduction

VMware vCenter 9.1.0.0300 | 29 JUL 2026 | Build 25629530 Check for additions and updates to these release notes.

What's New

- This release resolves CVE-2026-59310. For more information on this vulnerability and its impact on Broadcom products, see VMSA-2026-0006.

Build Details

VMware vCenter 9.1.0.0300

Build Details

Download Filename:	VMware-vCenter-Server-Appliance-9.1.0.0300.25629530-patch-FP.iso
Build:	25629530
Download Size:	8629.3 MB
SHA256 checksum:	759a55bd4c0029503c61814bf5f61f73e54fa07339915d6f0107150f868b5f2f
Quick Patch	No
CVEs	CVE-2026-59310

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement.

For download instructions, see Download Broadcom products and software.

For more information on using the vCenter shells, see Broadcom knowledge base article 2100508.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, see Upgrading the vCenter Appliance.

Known Issues

A reset of the vSphere Lifecycle Manager database might cause data loss in the Supervisor

If the vSphere Lifecycle Manager database in your environment is reset before upgrading vCenter from versions 8.0 Update 3 and later or 9.0.x to 9.1.0 or 9.1.1, the upgrade might cause data loss in the Supervisor. To avoid data loss, before a vCenter upgrade, you must first check your environment and take mitigation steps, if necessary.

Workaround: See Broadcom knowledge base article 455737 for instructions how to check if your environment is affected and for mitigation steps.

vSAN

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for vSAN 9.1.0.x:

- VMware vSAN 9.1.0.0100 Release Notes
- VMware vSAN 9.1.0.0200 Release Notes

VMware vSAN 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Known Issues

Introduction

Build numbers for VMware vSAN components.

VMware vSAN ESA Witness 9.1.0.0100 | 05 JUN 2026 | Build 25434574
VMware vSAN OSA Witness 9.1.0.0100 | 05 JUN 2026 | Build 25434573

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Known Issues

Live patch pre-check fails on vSAN compute clusters causing ESX upgrades to fail

When initiating a live patch ESX upgrade on a vSAN compute cluster, the pre-remediation health check shown in the vSphere Client fails with the following error:

```
The health check failed to complete.
```

This precheck failure blocks the upgrade process for the ESX hosts in the vSAN compute cluster.

This issue only affects vSAN compute clusters that do not have any local vSAN storage like in vSAN HCI or vSAN Storage cluster.

Workaround: Disabling the quick patch vSAN health checks on vSAN compute clusters allows the process to continue. See Broadcom knowledge base article 442180.

VMware vSAN 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VMware vSAN 9.1.0.0200 | 13 JUL 2026 | Build 25557999

VMware vSAN ESA Witness 9.1.0.0200 | 13 JUL 2026 | Build 25558001

VMware vSAN OSA Witness 9.1.0.0200 | 13 JUL 2026 | Build 25558000

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

NSX

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for NSX 9.1.0.x:

- NSX 9.1.0.0100 Release Notes
- NSX 9.1.0.0200 Release Notes

NSX 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

NSX 9.1.0.0100 | 05 JUN 2026| Build 25470810
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

NSX 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

NSX 9.1.0.0200 | 13 JUL 2026 | Build 25524170

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

SDDC Manager

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for SDDC Manager 9.1.0.x:

- SDDC Manager 9.1.0.0100 Release Notes
- SDDC Manager 9.1.0.0200 Release Notes
- SDDC Manager 9.1.0.0300 Release Notes
- SDDC Manager 9.1.0.0400 Release Notes

SDDC Manager 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Known Issues
- Applying the Patch

Introduction

VMware Cloud Foundation SDDC Manager 9.1.0.0100 | 05 JUN 2026 | Build 25428926
Check for additions and updates to these release notes.

What's New

- This release contains various security enhancements.

IMPORTANT: For upgrading your environment from VCF 5.2.1 to 9.1.0.0100, you must first upgrade from 5.2.1 to 5.2.2 or 5.2.3 and then to 9.1.0.0100.

Known Issues

Initiating SDDC Manager upgrade pre-checks from the instance in Lifecycle tab in VCF Operations or from the Available Upgrades tab in SDDC Manager Lifecycle Management UI fails with a `Triggering SDDC Manager upgrade bundle failed`

When you initiate upgrade pre-checks for SDDC Manager in VCF Operations (**Build > Lifecycle > VCF Instances > instance > SDDC Manager Upgrades** tab) or SDDC Manager UI (**Lifecycle Management > SDDC Manager > Available Upgrades** tab), the operation fails with a `Triggering SDDC Manager upgrade bundle failed. A problem has occurred on the server. Please retry or contact the service provider and provide the reference token` error.

Workaround: Initiate the upgrade pre-checks either from the **Build > Lifecycle > VCF Instances > instance > domain > Upgrades** tab in the VCF Operations UI or the **Inventory > Workload Domains > domain > Upgrades** tab in the SDDC Manager UI.

Version 9.1.0.0100 is not listed under Available Upgrades

In the SDDC Manager UI, under **Lifecycle Management > SDDC Manager**, you might not see version 9.1.0.0100 for the SDDC Manager, even though the patch bundle is successfully downloaded or uploaded to your environment. The same issue occurs in VCF Operations, under **Build > Lifecycle > VCF Instances > {specific VCF instance} > SDDC Manager Upgrades**.

Workaround: Apply the SDDC Manager patch by using the standard Plan Upgrade or Plan Patch workflows.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

SDDC Manager 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Known Issues
- Applying the Patch
- Resolved Issues

Introduction

SDDC Manager 9.1.0.0200 | 25 JUN 2026 | Build 25496021

Check for additions and updates to these release notes.

For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release delivers a fix as described in the Resolved Issues section.

Known Issues

Initiating SDDC Manager upgrade pre-checks from the instance in Lifecycle tab in VCF Operations or from the Available Upgrades tab in SDDC Manager Lifecycle Management UI fails with a `Triggering SDDC Manager upgrade bundle failed`

When you initiate upgrade pre-checks for SDDC Manager in VCF Operations (**Build > Lifecycle > VCF Instances > instance > SDDC Manager Upgrades** tab) or SDDC Manager UI (**Lifecycle Management > SDDC Manager > Available Upgrades** tab), the operation fails with a `Triggering SDDC Manager upgrade bundle failed. A problem has occurred on the server. Please retry or contact the service provider and provide the reference token` error.

Workaround: Initiate the upgrade pre-checks either from the **Build > Lifecycle > VCF Instances > instance > domain > Upgrades** tab in the VCF Operations UI or the **Inventory > Workload Domains > domain > Upgrades** tab in the SDDC Manager UI.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

In VMware vSphere Foundation environments, installing the Log management component fails with an error "Unexpected vSphere client error has occurred"

In VMware vSphere Foundation environments, due to an issue with the persistence of vCenter administrator credentials in Fleet lifecycle components when the admin credentials are updated directly on vCenter, certain component installation and upgrade workflows might fail to complete. For example, installing the log management component might fail with an error `Unexpected vSphere client error has occurred`.

SDDC Manager 9.1.0.0300 Release Notes

This document contains the following sections

- Introduction
- What's New
- Known Issues
- Applying the Patch

Introduction

SDDC Manager 9.1.0.0300 | 30 JUN 2026 | Build 25536191

Check for additions and updates to these release notes.

What's New

During an upgrade from VCF 9.0.x to 9.1, after you deploy VCF management services, your existing management components are automatically added to the lifecycle inventory. If you have stale certificates, passwords, or FQDN data for a component, the automatic add might fail. Starting with version 9.1.0.0300, in the VCF Operations UI, you can see error notifications and messages that identify the components that cannot be added. In the Tasks panel, you can see warnings for all components that failed to be added and remediation guidance. For the remediation steps and instructions to add the components, see Broadcom knowledge base article 441858.

Known Issues

Initiating SDDC Manager upgrade pre-checks from the instance in Lifecycle tab in VCF Operations or from the Available Upgrades tab in SDDC Manager Lifecycle Management UI fails with a `Triggering SDDC Manager upgrade bundle failed`

When you initiate upgrade pre-checks for SDDC Manager in VCF Operations (**Build > Lifecycle > VCF Instances > instance > SDDC Manager Upgrades** tab) or SDDC Manager UI (**Lifecycle Management > SDDC Manager > Available Upgrades** tab), the operation fails with a `Triggering SDDC Manager upgrade bundle failed.`

`A problem has occurred on the server. Please retry or contact the service provider and provide the reference token` error.

Workaround: Initiate the upgrade pre-checks either from the **Build > Lifecycle > VCF Instances > instance > domain > Upgrades** tab in the VCF Operations UI or the **Inventory > Workload Domains > domain > Upgrades** tab in the SDDC Manager UI.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

SDDC Manager 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Known Issues
- Applying the Patch

Introduction

SDDC Manager 9.1.0.0400 | 13 JUL 2026 | Build 25570100

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Known Issues

Initiating SDDC Manager upgrade pre-checks from the instance in Lifecycle tab in VCF Operations or from the Available Upgrades tab in SDDC Manager Lifecycle Management UI fails with a `Triggering SDDC Manager upgrade bundle failed`

When you initiate upgrade pre-checks for SDDC Manager in VCF Operations (**Build > Lifecycle > VCF Instances > instance > SDDC Manager Upgrades** tab) or SDDC Manager UI (**Lifecycle Management > SDDC Manager > Available Upgrades** tab), the operation fails with a `Triggering SDDC Manager upgrade bundle failed. A problem has occurred on the server. Please retry or contact the service provider and provide the reference token` error.

Workaround: Initiate the upgrade pre-checks either from the **Build > Lifecycle > VCF Instances > instance > domain > Upgrades** tab in the VCF Operations UI or the **Inventory > Workload Domains > domain > Upgrades** tab in the SDDC Manager UI.

During a deferred components deployment, the VCF Installer UI requests 6 IP addresses instead of the 5 IP addresses that the VCF Automation deployment requires

VCF Installer UI prompts for one more IP address than the VCF Automation deployment uses. The additional IP address that the UI requests is not consumed and does not affect the deployment.

Workaround: Perform one of the following tasks.

- Provide 6 IP addresses in the VCF Installer UI. See Deploying Deferred Components on Custom Networking.
- Provide 5 IP addresses in the JSON specification file. See Use a JSON Specification File to Deploy VMware Cloud Foundation or vSphere Foundation.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Operations

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for VCF Operations 9.1.0.x:

- 9.1.0.0100
- 9.1.0.0200
- 9.1.0.0300
- 9.1.0.0400

9.1.0.0100

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

VCF Operations

- VCF Operations 9.1.0.0100 Release Notes (includes the cloud proxy and license server components)
- VCF Operations HCX 9.1.0.0100 Release Notes
- VCF Operations for Networks 9.1.0.0100 Release Notes
- VCF Operations Orchestrator 9.1.0.0100 Release Notes

VCF Management Services

- Fleet Lifecycle 9.1.0.0100 Release Notes
- SDDC Lifecycle 9.1.0.0100 Release Notes
- Log Management 9.1.0.0100 Release Notes
- Real-Time Metrics 9.1.0.0100 Release Notes
- Salt Master 9.1.0.0100 Release Notes
- Salt RaaS 9.1.0.0100 Release Notes
- Identity Broker 9.1.0.0100 Release Notes

VCF Operations 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Build numbers for VCF Operations and its components.

VCF Operations 9.1.0.0100 | 05 JUN 2026 | Build 25435105 VCF Operations Upgrade 9.1.0.0100 | 05 JUN 2026 | Build 25435107 Cloud Proxy 9.1.0.0100 | 05 JUN 2026 | Build 25434833 License Server 9.1.0.0100 | 05 JUN 2026 | Build 25434835 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

When you apply the VCF Operations patch, the cloud proxy and license server components are patched automatically.

VCF Operations for Networks 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Known Issues

Introduction

VCF Operations for Networks 9.1.0.0100 | 05 JUN 2026 | Build 25427421 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Known Issues

Shutting down VCF Operations for networks during upgrade or other maintenance activities.

Shutting down VCF Operations for Networks cluster appliances via Fleet Lifecycle Manager may cause services to go unhealthy and introduce database inconsistencies. The Fleet Lifecycle Manager doesn't follow the prescribed procedure to shutdown VCF Operations for Networks cluster.

Do not use Fleet Lifecycle Manager to shut down the appliances for snapshots or maintenance. Instead, follow the manual procedure to safely power down the cluster and take snapshots. For detailed guidance, see the Broadcom Knowledge Base article 314428.

VCF Operations HCX 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VCF Operations HCX 9.1.0.0100 | 05 JUN 2026 | Build 25426672 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Operations Orchestrator 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VCF Operations Orchestrator 9.1.0.0100 | 05 JUN 2026 | Build 25434839 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Fleet Lifecycle 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Fleet Lifecycle 9.1.0.0100 | 05 JUN 2026 | Build 25423358 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

SDDC Lifecycle 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

SDDC Lifecycle 9.1.0.0100| 05 JUN 2026 | Build 25423352
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Log Management 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Log Management 9.1.0.0100 | 05 JUN 2026 | Build 25435121
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Real-Time Metrics 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Real-Time Metrics 9.1.0.0100 | 05 JUN 2026 | Build 25435036
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Salt Master 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Salt Master 9.1.0.0100 | 05 JUN 2026 | Build 25434834
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Salt RaaS 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Salt RaaS 9.1.0.0100 | 05 JUN 2026 | Build 25434834
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Identity Broker 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Related Resolved Issues

Introduction

Identity Broker 9.1.0.0100 | 13 JUL 2026 | Build 25522734
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This patch includes no changes other than the alignment of build details and does not introduce any resolved or known issues.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Related Resolved Issues

VCF Services Runtime 9.1.0.0200 resolves the following issues related to Identity Broker:

- **Upgrade of VCF Identity Broker and VCF Automation might fail with error VCFMS-BACKUP-COMPONENT-006**
  During an upgrade of VCF identity broker or VCF Automation, the process might fail with a generic backup timeout error **VCFMS-BACKUP-COMPONENT-006**. The error does not identify the actual cause: the configured SFTP backup destination server has insufficient free disk space to accommodate the pre-upgrade backup.
  A pre-upgrade validation check now verifies that the SFTP backup server has sufficient free disk space before the upgrade begins, and returns a descriptive error message if the condition is not met.
- **VCF Identity Broker and VCF Automation upgrade from VCF 9.0 to 9.1 fails if the 9.0 appliance VMs are not in the original vCenter folder**
  When upgrading VCF identity broker or VCF Automation from VCF 9.0 to 9.1, the upgrade might fail if the VMs for the 9.0 appliances are moved out of their original vCenter inventory folder.
  VM operations during upgrade now look up VMs by their unique ID rather than by folder path, so the upgrade succeeds regardless of where appliance VMs are located on the vCenter instance.
- **Scheduled backups silently fail after VCF Automation or VCF Identity Broker upgrade from VCF 9.0 to 9.1 on clusters older than 60 days**
  Following an upgrade of VCF Automation or VCF identity broker from VCF 9.0 to 9.1, scheduled backups complete without error messages but produce no valid backup data. An SSL certificate hostname mismatch causes the failure: the upgrade process incorrectly restores stale internal certificate request objects from the pre-upgrade cluster, preventing the new cluster from generating a valid certificate for internal communication. Backups that depend on this internal certificate path fail silently. This condition affects only clusters that were in operation for more than 60 days before the upgrade.
  Stale internal certificate request objects from the previous cluster version are no longer restored during upgrade, allowing the upgraded cluster to generate valid internal certificates and complete scheduled backups successfully.

9.1.0.0200

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

VCF Operations

- VCF Operations 9.1.0.0200 Release Notes (includes the cloud proxy and license server components)
- VCF Operations for Networks 9.1.0.0200 Release Notes
- VCF Operations HCX 9.1.0.0200 Release Notes

VCF Management Services

- VCF Services Runtime 9.1.0.0200 Release Notes
- SDDC Lifecycle 9.1.0.0200 Release Notes
- Real-Time Metrics Store 9.1.0.0200 Release Notes

VCF Operations 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction

- What's New
- Applying the Patch
- Resolved Issues

Introduction

Build numbers for VCF Operations and its components.

VCF Operations 9.1.0.0200 | 25 JUNE 2026 | Build 25500350 VCF Operations Upgrade 9.1.0.0200 | 25 JUNE 2026 | Build 25500347 Cloud Proxy 9.1.0.0200 | 25 JUNE 2026 | Build 25500351 License Server 9.1.0.0200 | 25 JUNE 2026 | Build 25499768 Check for additions and updates to these release notes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

When you apply the VCF Operations patch, the cloud proxy and license server components are patched automatically.

Resolved Issues

VCF Operations upgrade from 9.0, 9.0.1, and 9.0.2 to 9.1 fails during the post-upgrade script execution phase

This issue occurs while upgrading an environment where a previously imported license has since been deleted. The deleted license leaves behind a stale record in the database which later violates a new foreign key constraint introduced during the upgrade process. This constraint violation causes the Postgres database update to fail.

The license server does not work properly and after the appliance boots, in the console you see a black screen

The license server uses the `172.16.0.0/12` and `172.17.0.0/16` IP address ranges for internal communications. If you deploy the license server on the `172.16.0.0/12` network or configure the license server to use a gateway that advertises a routable path of `172.17.0.0/16`, a network conflict occurs. As a result, you see only a black screen in the license server console after booting.

Microsoft CA certificates are displayed as external CA signed certificates instead of Microsoft CA signed certificates

This issue can occur when the root certificate in the Microsoft CA configuration is updated.

After you upgrade from VCF 9.0 to 9.1, Microsoft CA certificates appear as EXTERNAL_CA signed certificates

This happens because in VCF 9.0, VCF Fleet Lifecycle Manager appliances stored locker-related information in their local database. In VCF 9.1, VCF Fleet Lifecycle Manager is deprecated, and all locker contents are migrated to the VCF Operations locker database.

Certificate replacement with Microsoft CA fails

This issue occurs when the Microsoft CA configuration includes intermediate certificates. In such cases, any certificate replacement operation triggered with the Microsoft CA fails.

VCF Operations for Networks 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

- Resolved Issues

Introduction

VCF Operations for Networks 9.1.0.0200 | 13 JUL 2026 | Build 25517220
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

The certificate rotation and update API enforces strict Subject Alternative Name (SAN) validation on custom SSL/TLS certificates after upgrading to VMware Cloud Foundation (VCF) 9.1.0.0200.

Starting with VCF 9.1.0.0200, the API actively checks that the Subject Alternative Name (SAN) field is present and correctly populated with the IP addresses of all platform cluster nodes. Certificates missing a SAN, or containing incomplete cluster IPs, are rejected by the API with an error.

Environments upgraded to VCF 9.1.0.0200 with an active custom certificate that lacks a valid SAN will not experience disruption to existing session traffic. However, SAN compliance is required for all future certificate updates. Administrators must audit existing custom certificates and reissue them with the complete list of platform node IPs to maintain compliance.

Infrastructure nodes experience disk space exhaustion or trigger storage capacity alerts due to retained legacy Python binaries.

Following system updates, legacy Python versions (such as 3.5, 3.6, and 3.8) remain in the /usr/local/lib directory. These obsolete binaries consume excessive disk space and are not automatically removed by standard package managers. Administrators encounter storage capacity warnings when the partition hosting the library directory reaches maximum utilization.

Antrea flows for VMware vSphere Kubernetes Service 1.35.0 and later clusters are now visible in VMware Cloud Foundation Operations for networks.

VMware Cloud Foundation Operations for networks now successfully discovers VMware vSphere Kubernetes Service 1.35.0 and later clusters. Previously, a discovery failure prevented these clusters and their associated Antrea flows from appearing in VMware Cloud Foundation Operations for networks, as well as in the Operate > Flows section of VMware Cloud Foundation Operations.

VCF Operations HCX 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VCF Operations HCX 9.1.0.0200 | 13 JUL 2026 | Build 25535720
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Services Runtime 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues
- Known Issues

Introduction

VCF Services Runtime 9.1.0.0200 | 13 JULY 2026 | Build 25555874
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

See the Resolved Issues and Known Issues sections for fixes and current operational issues.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

VCF Services Runtime 9.1.0.0200 resolves the following issues:

- **VCF Services Runtime upgrade fails due to vCenter permission error**
  During an upgrade of VCF services runtime, the service might fail to apply the updated vCenter roles and permissions required for VCF 9.1. As a result, the upgrade process either ends with an error or completes in a degraded state, leaving the cluster with insufficient privileges to perform post-upgrade operations.
  VCF services runtime now accepts administrator credentials from the Fleet Lifecycle Manager during upgrade and applies the required vCenter roles and permissions before the upgrade proceeds.
- **VCF upgrade from 9.0 to 9.1 fails due to a DNS check**
  When upgrading from VCF 9.0 to 9.1, the pre-upgrade health check validates DNS resolution for the VCF Operations hostname. If that host is no longer in the DNS configuration, the health check reports an error and blocks the upgrade.
  The health check now skips the VCF Operations hostname DNS check during upgrade, preventing such errors.
- **VCF Automation services fail to recover after cluster restart**
  A full restart of the VCF Automation cluster might cause one or more VCF Automation services to remain in a non-running state, requiring manual intervention to restore functionality.
  A housekeeping task that was blocking successful restarts is now configured to stop any previously running instances before starting a new one, and has a maximum allowed runtime so a stuck instance cannot block the system indefinitely.
- **Upgrade of VCF Identity Broker and VCF Automation might fail with error VCFMS-BACKUP-COMPONENT-006**

During an upgrade of VCF identity broker or VCF Automation, the process might fail with a generic backup timeout error `VCFMS-BACKUP-COMPONENT-006`. The error does not identify the actual cause: the configured SFTP backup destination server has insufficient free disk space to accommodate the pre-upgrade backup.

A pre-upgrade validation check now verifies that the SFTP backup server has sufficient free disk space before the upgrade begins, and returns a descriptive error message if the condition is not met.

- **VCF Identity Broker and VCF Automation upgrade from VCF 9.0 to 9.1 fails if the 9.0 appliance VMs are not in the original vCenter folder**

  When upgrading VCF identity broker or VCF Automation from VCF 9.0 to 9.1, the upgrade might fail if the VMs for the 9.0 appliances are moved out of their original vCenter inventory folder.

  VM operations during upgrade now look up VMs by their unique ID rather than by folder path, so the upgrade succeeds regardless of where appliance VMs are located on the vCenter instance.
- **You see reports for failed VCF Management Services installation even though the cluster is healthy**

  After completing a VCF management services installation, due to invalid vCenter authentication performed by internal services, the final status incorrectly reports a failure even though the cluster is fully operational and all services are running.

  Health checks now authenticate correctly against vCenter and succeed on a healthy cluster, fixing the invalid vCenter authentication by internal services.
- **Scheduled backups silently fail after VCF Automation or VCF Identity Broker upgrade from VCF 9.0 to 9.1 on clusters older than 60 days**

  Following an upgrade of VCF Automation or VCF identity broker from VCF 9.0 to 9.1, scheduled backups complete without error messages but produce no valid backup data. An SSL certificate hostname mismatch causes the failure: the upgrade process incorrectly restores stale internal certificate request objects from the pre-upgrade cluster, preventing the new cluster from generating a valid certificate for internal communication. Backups that depend on this internal certificate path fail silently. This condition affects only clusters that were in operation for more than 60 days before the upgrade.

  Stale internal certificate request objects from the previous cluster version are no longer restored during upgrade, allowing the upgraded cluster to generate valid internal certificates and complete scheduled backups successfully.
- **VCF Management Services install fails with "unexpected EOF" error when vSphere password contains special characters**

  When the vSphere administrator password includes special characters — such as single quotes (') or double quotes (") — the VCF management services installation might fail. The error message reports an unexpected EOF condition, which does not identify the special character encoding as the root cause.

  Password values are now written using shell-safe encoding.
- **VCF Management Services installation might fail due to duplicate vCenter port group names**

  When two or more vCenter port groups share the same display name across different distributed switches, the VCF management services provisioning process might fail with an error that the path resolves to multiple networks.

  Network lookup now uses the unique network ID directly instead of resolving port groups by name.
- **Storage DRS live migration of VCF Services Runtime VMs causes storage failures**

  When you enable Storage DRS (SDRS) on the datastore cluster that hosts VCF services runtime nodes, vCenter might automatically migrate VCF services runtime virtual machines to different datastores as part of the storage load balancing and cause storage failures on the affected nodes.

  VCF services runtime now automatically excludes its VMs from Storage DRS, preventing vSphere from migrating them. Manually migrating VCF services runtime virtual machines is not recommended.
- **Overlapping IP pool and Kubernetes internal network ranges cause silent networking failures in VCF Services Runtime deployment**

  Deploying a VCF services runtime cluster with an IP pool that overlaps with Kubernetes internal network ranges might cause silent networking failures and connection issues after deployment.

  VCF services runtime now validates IP ranges during deployment and rejects requests with an error message if the provided IP pool conflicts with internal network ranges. For more information, see Deploy VCF Management Services and License Server as Part of VCF Upgrade to 9.1.
- **Mixed-case hostname or FQDN names cause failures across VCF install, upgrade, and import workflows**

  When you provide a hostname or fully qualified domain name (FQDN) using mixed-case characters — for example, MyHost.Example.com — install, upgrade, import, and other operations across the VCF environment might fail, because DNS resolution and SSL certificate matching are case-sensitive.

FQDNs are now automatically normalized to lowercase at all entry points, preventing case-sensitivity issues across all workflows.

Known Issues

- **You cannot power down or shut down a VCF Services Runtime cluster by using the UI**
  VCF services runtime does not provide a UI control for powering down or shutting down a cluster. The cluster shutdown operation is only available through CLI or API.
  Workaround: For more information, see Starting Up VMware Cloud Foundation and Shutting Down VMware Cloud Foundation.
- **VCF Management Services or VCF Automation services fail to resume after power-on**
  When you power on a previously shut-down VCF management services or VCF Automation cluster, some services might fail to resume. Affected components remain unavailable after power-on and require manual intervention to restore full service operation.
  Workaround: For more information, see Broadcom knowledge base article 440862.
- **You cannot change the FQDN for VCF Management Services or VCF Automation after deployment**
  You cannot change the fully qualified domain name (FQDN) for VCF management services or VCF Automation components after initial deployment. To change the FQDN, you must remove the existing deployment entirely and redeploy.
  Workaround: For more information, see Broadcom knowledge base article 441333.
- **You cannot retry a failed VCF Automation upgrade**
  When a VCF Automation upgrade workflow fails, you cannot retry the operation. Instead, you must delete the component and restart the upgrade.
  Workaround: For more information, see Broadcom knowledge base article 441333.
- **VCF Automation upgrade precheck from VCF 9.0 to 9.1 fails when source and target datastores do not match**
  The VCF Automation upgrade precheck from VCF 9.0 to 9.1 fails when the target datastore does not match the source datastore configuration. The upgrade process stops until you align the datastore configuration between the source and target environments.
  Workaround: For more information, see Broadcom knowledge base article 440045.
- **VCF Identity Broker upgrade precheck from VCF 9.0 to 9.1 fails when target network or datastore configuration does not match**
  The VCF identity broker upgrade precheck from VCF 9.0 to 9.1 fails when the target network or datastore configuration does not match the source. The upgrade stops until you align both the network and datastore configuration between the source and target.
  Workaround: For more information, see Broadcom knowledge base article 444734.
- **If the management domain vCenter certificate rotates twice within 30 minutes, VCF Management Services loses connection to vCenter**
  If the management domain vCenter certificate rotates twice within a 30-minute window, VCF management services might lose connectivity to the vCenter instance. As a result, VM rollout, scaling, and disk resize operations fail and VMs remain unavailable until you manually restore vCenter connectivity.
  Workaround: For more information, see Broadcom knowledge base article 424402.
- **After a component disk or volume is resized, the UI might show an incorrect size of 0**
  After a component disk or volume is resized, the UI might display an incorrect size of 0 instead of the actual disk size. This error blocks any subsequent resize operations through the UI.
  Workaround: For more information, see Broadcom knowledge base article 442600.

SDDC Lifecycle 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

SDDC Lifecycle 9.1.0.0200 | 25 JUN 2026 | Build 25495903
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release delivers a fix as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

VCF Automation upgrade might fail if SDDC lifecycle cannot communicate with SDDC Manager

SDDC lifecycle uses a Service Account to communicate with SDDC Manager APIs. During the periodic Service Account rotation, such an account might be corrupted when it is close to expiration, approximately 30 days from installation. As a result, if you do not deploy VCF Automation within 50 days after upgrading to or deploying VCF 9.1, the VCF Automation upgrade fails.

Real-Time Metrics Store 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Real-Time Metrics Store 9.1.0.0200 | 13 JUL 2026 | Build 25555874

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

9.1.0.0300

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

VCF Operations

- VCF Operations 9.1.0.0300 Release Notes

VCF Management Services

- Fleet Lifecycle 9.1.0.0300 Release Notes
- SDDC Lifecycle 9.1.0.0300 Release Notes

VCF Operations 9.1.0.0300 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Build numbers for VCF Operations and its components.

VCF Operations 9.1.0.0300 | 30 JUN 2026 | Build 25531073 VCF Operations Upgrade 9.1.0.0300 | 30 JUN 2026 | Build 25531064 Cloud Proxy 9.1.0.0300 | 30 JUN 2026 | Build 25531074 License Server 9.1.0.0300 | 30 JUN 2026 | Build 25531069 The cloud proxy and license server components do not carry any changes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

During an upgrade from VCF 9.0.x to 9.1, after you deploy VCF management services, your existing management components are automatically added to the lifecycle inventory. If you have stale certificates, passwords, or FQDN data for a component, the automatic add might fail. Starting with version 9.1.0.0300, in the VCF Operations UI, you can see error notifications and messages that identify the components that cannot be added. In the Tasks panel, you can see warnings for all components that failed to be added and remediation guidance. For the remediation steps and instructions to add the components, see Broadcom knowledge base article 441858.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

When you apply the VCF Operations patch, the cloud proxy and license server components are patched automatically.

Fleet Lifecycle 9.1.0.0300 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Fleet Lifecycle 9.1.0.0300 | 30 JUN 2026 | Build 25536195 Check for additions and updates to these release notes.

What's New

During an upgrade from VCF 9.0.x to 9.1, after you deploy VCF management services, your existing management components are automatically added to the lifecycle inventory. If you have stale certificates, passwords, or FQDN data for a component, the automatic add might fail. Starting with version 9.1.0.0300, in the VCF Operations UI, you can see error notifications and messages that identify the components that cannot be added. In the Tasks panel, you can see warnings for all components that failed to be added and remediation guidance. For the remediation steps and instructions to add the components, see Broadcom knowledge base article 441858.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

SDDC Lifecycle 9.1.0.0300 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

SDDC Lifecycle 9.1.0.0300 | 30 JUN 2026 | Build 25536191 Check for additions and updates to these release notes.

What's New

During an upgrade from VCF 9.0.x to 9.1, after you deploy VCF management services, your existing management components are automatically added to the lifecycle inventory. If you have stale certificates, passwords, or FQDN data for a component, the automatic add might fail. Starting with version 9.1.0.0300, in the VCF Operations UI, you can see error notifications and messages that identify the components that cannot be added. In the Tasks panel, you can see warnings for all components that failed to be added and remediation guidance. For the remediation steps and instructions to add the components, see Broadcom knowledge base article 441858.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

9.1.0.0400

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Some components might skip a release version if no issues meet the release criteria. As a result, not all components follow a strict sequence in versions. For example, the first patch might be 9.1.0.0100 and the next patch for that component might be 9.1.0.0300. For information about release types and dependencies, see Lifecycle Management documentation.

VCF Operations

- VCF Operations 9.1.0.0400 Release Notes (includes the cloud proxy and license server components)
- Fleet Lifecycle 9.1.0.0400 Release Notes
- VCF Operations Orchestrator 9.1.0.0400 Release Notes

VCF Management Services

- Salt Master 9.1.0.0400 Release Notes
- Salt RaaS 9.1.0.0400 Release Notes
- Log Management 9.1.0.0400 Release Notes
- Fleet Lifecycle 9.1.0.0400 Release Notes
- SDDC Lifecycle 9.1.0.0400 Release Notes
- Real-Time Metrics 9.1.0.0400 Release Notes
- Software Depot 9.1.0.0400 Release Notes

VCF Operations 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues
  - Upgrade
  - Fleet Management
  - Licensing

Introduction

Build numbers for VCF Operations and its components.

VCF Operations 9.1.0.0400 | 13 JUL 2026 | Build 25541561 VCF Operations Upgrade 9.1.0.0400 | 13 JUL 2026 | Build 25541550 Cloud Proxy 9.1.0.0400 | 13 JUL 2026 | Build 25541562 License Server 9.1.0.0400 | 13 JUL 2026 | Build 25541557 Check for additions and updates to these release notes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

When you apply the VCF Operations patch, the cloud proxy and license server components are patched automatically.

Resolved Issues

Upgrade

VCF Operations upgrade from 9.0, 9.0.1, and 9.0.2 to 9.1 fails during the post-upgrade script execution phase

This issue occurs while upgrading an environment where a previously imported license has since been deleted. The deleted license leaves behind a stale record in the database which later violates a new foreign key constraint introduced during the upgrade process. This constraint violation causes the Postgres database update to fail.

Fleet Management

Replacing vCenter certificates fails when the new certificate includes intermediate certificates in its chain

Replacing vCenter certificates with a new certificate that contains intermediate certificates in its chain fails with the message: *"Certificate replacement operation completed successfully on VCENTER component with FQDN XXXX. However, automated post-update trust failed with errors."* After a certificate replacement operation completes successfully on a vCenter component, the automated post-update retrust step targeting VCF Automation fails in VCF Operations 9.1 and displays errors.

Certificate Replacement with a Configured CA (Microsoft) operation fails when Microsoft CA is configured as an Intermediate CA

When Microsoft CA is configured as an intermediate CA, the Certificate Replacement with a Configured CA operation fails because VCF Certificate Management does not build the full certificate chain which includes intermediate and root certificates.

After upgrading a multi VCF Instance from 9.0 to 9.1, the 'Choose Deployment Type' step on the SSO Configuration Overview page remains in an 'In Progress' state, while all other steps displayed as completed

During VCF Operations upgrade from 9.0 to 9.1, the configuration sync converts pre-existing 9.0 single sign-on data into 9.1 single sign-on domain-specific data. During this process, when no identity provider is found, the `vcfInstanceId` is incorrectly retrieved from the component's authsource configuration instead of from the identity broker. Since this does not always guarantee that the discovered component belongs to the correct VCF Instance, the single sign-on domain was created with an incorrect VCF Instance ID.

Licensing

VCF Operations 9.1.0.0400 resolves the following issues related to Licensing:

- **You do not see informative messages for license assignment failures in VCF Operations**
  When a license assignment to a vCenter instance fails due to a connectivity failure from VCF Operations to the vCenter instance or from the vCenter instance to the license server, the message in the task results pane does not provide sufficient information.
  The fix adds informative messages that include the specific reason for failure. You can use the reason details to diagnose issues such as invalid API keys, DNS failures, or NTP synchronization problems.
- **You see only generic alerts when VCF Operations cannot reach a vCenter instance**
  In VCF Operations, you see generic alerts when VCF Operations cannot reach a vCenter instance, without details about the failure type.
  The fix adds specific alerts and remediation guidance. VCF Operations now displays dedicated alerts with remediation guidance depending on the failure type, and you can identify whether the root cause is a DNS issue, a network timeout, a refused connection on port 443, or insufficient permissions.
- **No support for Internet Control Message Protocol (ICMP) requests for license servers**
  License servers prior to VCF Operations 9.1.0.0400 do not respond to ICMP requests.
  Starting with VCF Operations 9.1.0.0400, network administrators can use standard ping diagnostics to verify license server reachability, which simplifies network monitoring and connectivity troubleshooting for license server deployments.
- **You do not see a warning when the vCenter version is later than the VCF Operations version**
  You must upgrade VCF Operations before vCenter in any upgrade sequence. When the upgrade order is reversed and one or more vCenter instances are of version later than the current VCF Operations version, the affected vCenter instances are not flagged.
  The fix adds comparison based on major and minor version numbers. Patch-level differences do not trigger the warning.
- **License assignment fails if the vCenter UUID contains uppercase letters**
  When the vCenter UUID contains uppercase characters, license assignment fails. The authorization request that VCF Operations sends to the license server embeds the vCenter UUID directly, and the license server rejects requests where the UUID casing does not match the expected lowercase format.
  VCF Operations now changes the vCenter UUID to lowercase before it builds the authorization request, and license assignment succeeds regardless of the casing that the source vCenter system uses.
- **License server attempts to connect to external Network Time Protocol (NTP) servers for time synchronization**
  The license server incorrectly attempts to connect to an external NTP server to update its internal clock.
  Starting with VCF Operations 9.1.0.0400, time synchronization for the license server is restricted exclusively to the host system on which the license server virtual machine runs.

VCF Operations Orchestrator 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues
- Known Issues

Introduction

VCF Operations Orchestrator 9.1.0.0400 | 13 JUL 2026 | Build 25545173
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

The Mail plug-in for VCF Operations orchestrator does not work after upgrade

After upgrade, the Mail plug-in for VCF Operations orchestrator cannot send or receive messages. When the **Send notification** workflow is run, the UI shows the `unable to create object : EmailMessage : null` error.

Known Issues

The Mail plug-in for VCF Operations orchestrator cannot send emails that contain attachments

VCF Operations orchestrator cannot send emails with the Mail plug-in if the email contains an attachment.

Workaround: Download and install the VCF Operations orchestrator Mail plug-in 9.1.0.0401 hotpatch.

Log Management 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

Log Management 9.1.0.0400 | 13 JUL 2026 | Build 25544947
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

Fixed an error when configuring the Integrated Load Balancer VIP after updating the storage size.

The error **The VMSP operation (Create or Delete) failed** no longer occurs when you add a Virtual IP (VIP) under **Operate > Administration > Configurations > Log Collection > Integrated Load Balancer** after modifying the storage size. This occurred with any input in GB which was not divisible by 256.

Real-Time Metrics 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Real-Time Metrics 9.1.0.0400 | 13 JUL 2026 | Build 25544944

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Fleet Lifecycle 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

Fleet Lifecycle 9.1.0.0400 | 13 JUL 2026 | Build 25570104
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

IP address input for add component or upgrade flows only accept a single IP range or CIDR block

During add component or upgrade flows, IP address input for VCF management services, VCF services runtime, and VCF Automation components is limited to a single IP range or CIDR block, requiring allocation of a contiguous address block regardless of actual availability.

SDDC Lifecycle 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

- Known Issues

Introduction

SDDC Lifecycle 9.1.0.0400 | 13 JUL 2026 | Build 25570103
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Known Issues

Batch precheck of upgrade plan for all VCF management components fails with the validation error `VCF_LCM_FLEET_UPGRADE_400_COMPONENT_NOT_NEEDED_USER_INPUT_SPEC_PROVIDED`

This issue occurs when a component's user input specification remains configured after the component has already been upgraded to its target version. If you then click **Run Prechecks (ALL)**, or use **Select All** on the **VCF Management** > **Upgrade** page without selecting individual components, the precheck runs against the full upgrade plan. Because the plan includes a user input spec for a component that no longer requires one, the validation fails and returns the error above.

Workaround: Do not use the **Run Prechecks (ALL)** option. Instead, select the checkbox for each component you want to precheck individually, and then run the prechecks.

Salt Master 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Salt master 9.1.0.0400 | 13 JUL 2026 | Build 25544946
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Salt RaaS 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Salt RaaS 9.1.0.0400 | 13 JUL 2026 | Build 25544946
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Software Depot 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Known Issues

Introduction

Software Depot 9.1.0.0400 | 13 JUL 2026 | Build 25570105

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Known Issues

Concurrent software depot component patching causes other component patch operations to fail

Patching software depot takes it temporarily offline. If another component patch from fleet lifecycle runs concurrently, that patch operation cannot access the required binaries and fails. This issue affects environments where administrators initiate multiple component patches in parallel.

Workaround: Do not initiate other component patches while the software depot component is being patched. If concurrent patching already caused failures, wait for the software depot patching process to complete successfully. After software depot is patched, retry the failed component patches.

VCF Automation

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for VCF Automation 9.1.0.x:

- VCF Automation 9.1.0.0100 Release Notes
- VCF Automation 9.1.0.0200 Release Notes

VCF Automation 9.1.0.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VMware Cloud Foundation Automation 9.1.0.0100 | 05 JUN 2026 | Build 25429499
Check for additions and updates to these release notes.

What's New

- This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Automation 9.1.0.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

VCF Automation 9.1.0.0200 | 13 JUL 2026 | Build 25556825

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

- **Creating a Canonical content library fails with an OVF validation error**
  This issue is caused by the addition of an SBOM in Ubuntu OS images. The following files are present in both the OVA and the manifest (`.mf`) file but are not actually downloaded because they are not referenced by the OVF:
  - `ubuntu-resolute-26.04-cloudimg.manifest`
  - `ubuntu-resolute-26.04-cloudimg.sbom.spdx`
  - `ubuntu-resolute-26.04-cloudimg.filelist`
- **Users who are added to projects as part of a user group cannot access project resources**
  This issue occurs in VM Apps and All Apps organizations and includes catalog items, deployments, and, in All Apps organizations, errors with supervisor resources. The issue is caused by the incorrect use of a filter in the Project Service when associating users with groups and assigning group project principals' access to namespaces. Instead of

fetching the desired group from VCF Automation Provider Management, the Project Service fetches a page of groups. When there are more groups than the page size, which is 25, the groups that are left out cannot be handled.

- **VCF Operations orchestrator is missing auto token refresh mechanism in HTTP interceptor**
  If a VCF Automation user stays on the **Orchestrator**tab for longer than the access token lifetime, which is one hour by default, the user might get a forced logout due to the access token expiring and not being refreshed.
- **VCF Automation services fail to recover after cluster restart**
  A full restart of the VCF Automation cluster might cause one or more VCF Automation services to remain in a non-running state, requiring manual intervention to restore functionality.
  A housekeeping task that was blocking successful restarts is now configured to stop any previously running instances before starting a new one, and has a maximum allowed runtime so a stuck instance cannot block the system indefinitely.
- **Upgrade of VCF Identity Broker and VCF Automation might fail with error VCFMS-BACKUP-COMPONENT-006**
  During an upgrade of VCF identity broker or VCF Automation, the process might fail with a generic backup timeout error `VCFMS-BACKUP-COMPONENT-006`. The error does not identify the actual cause: the configured SFTP backup destination server has insufficient free disk space to accommodate the pre-upgrade backup.
  A pre-upgrade validation check now verifies that the SFTP backup server has sufficient free disk space before the upgrade begins, and returns a descriptive error message if the condition is not met.
- **VCF Identity Broker and VCF Automation upgrade from VCF 9.0 to 9.1 fails if the 9.0 appliance VMs are not in the original vCenter folder**
  When upgrading VCF identity broker or VCF Automation from VCF 9.0 to 9.1, the upgrade might fail if the VMs for the 9.0 appliances are moved out of their original vCenter inventory folder.
  VM operations during upgrade now look up VMs by their unique ID rather than by folder path, so the upgrade succeeds regardless of where appliance VMs are located on the vCenter instance.
- **Scheduled backups silently fail after VCF Automation or VCF Identity Broker upgrade from VCF 9.0 to 9.1 on clusters older than 60 days**
  Following an upgrade of VCF Automation or VCF identity broker from VCF 9.0 to 9.1, scheduled backups complete without error messages but produce no valid backup data. An SSL certificate hostname mismatch causes the failure: the upgrade process incorrectly restores stale internal certificate request objects from the pre-upgrade cluster, preventing the new cluster from generating a valid certificate for internal communication. Backups that depend on this internal certificate path fail silently. This condition affects only clusters that were in operation for more than 60 days before the upgrade.
  Stale internal certificate request objects from the previous cluster version are no longer restored during upgrade, allowing the upgraded cluster to generate valid internal certificates and complete scheduled backups successfully.

VCF Download Tool

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for VCF Download Tool 9.1.0.x:

- VCF Download Tool 9.1.0.0400 Release Notes

VCF Download Tool 9.1.0.0400 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VCF Download Tool 9.1.0.0400 | 13 JUL 2026 | Build 25550178

Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Patch Releases 9.1.1.x

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch release notes cover only newly identified known issues for each release. All known issues documented in earlier releases remain valid until a subsequent release resolves them. VCF releases are cumulative, so each release includes all fixes from earlier releases.

For more information, see Lifecycle Management in VMware Cloud Foundation.

To see an AI-generated list of all available patch releases, grouped by release date, click here.

You can use a similar sample search to get details on the content and builds for any of the VCF Components:

- vSphere
- vSAN
- NSX
- SDDC Manager
- VCF Operations
- VCF Automation
- VCF Download Tool

vSphere

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for vSphere 9.1.1.x:

- ESX
- vCenter

ESX

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for ESX 9.1.1.x:

- ESX 9.1.1.0100 Release Notes

ESX 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Build Details
- Applying the Patch

Introduction

VMware ESX 9.1.1.0100 | 12 OCT 2026 | Build 25782009
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

- This live-patchable release contains various security enhancements. The patch includes updates to the NSX kernel modules.

Build Details

VMware ESX 9.1.1.0100

VMware vSphere Hypervisor (ESX) Offline Bundle

Download Filename:	VMware-ESXi-9.1.1.0100.25782009-depot.zip
Build:	25782009
Download Size:	700 MB
SHA256 checksum:	ee2e159b8713dc022cbe57e8096aac97b2f3b05c0bd5030eec190395b7b93d91
Live Patchable	Yes
Host Reboot Required:	No
Virtual Machine Migration or Shutdown Required:	No

VMware vSphere Hypervisor (ESX) ISO image

Download Filename:	VMware-VMvisor-Installer-9.1.1.0100.25782009.x86_64.iso
Build:	25782009
Download Size:	719 MB
SHA256 checksum:	8f6a3598207f20e1918694bd1f10c312c49a7c169c8bc2515e774fa685ffd384

ESX Images

Name and Version	Release Date	Category	Live Patchable	Detail
ESXi-9.1.1.0100-25782009	12 October 2026	Security	Yes	Security only image

Image Profiles

VMware patch and update releases contain general and critical image profiles. Application of the general release image profile applies to new bug fixes.

Image Profile Name
ESXi-9.1.1.0100-25782009-standard
ESXi-9.1.1.0100-25782009-no-tools

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement, VMware vSphere Foundation or VMware Cloud Foundation.

For download instructions, see Download Broadcom products and software.See these KBs for details on the authenticated online and offline download: 390121, 390098, and 389276.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, for details on updates and upgrades by using vSphere Lifecycle Manager, see What is vSphere Lifecycle Manager and vSphere Lifecycle Manager Images and Baselines. You can also update ESX hosts without the use of vSphere Lifecycle Manager by using an image profile. To do this, you must manually download the patch offline bundle ZIP file or see the Broadcom knowledge base article How to download ESXi ISO image for all releases including patch updates.

For more information, see Using ESXCLI for Host Management and the VMware ESX Upgrade guide.

vCenter

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for vCenter 9.1.1.x:

- vCenter 9.1.1.0100 Release Notes

vCenter 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Build Details
- Applying the Patch
- Resolved Issues
  - Upgrade Issues

Introduction

VMware vCenter 9.1.1.0100 | 12 OCT 2026| Build 25784172 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Build Details

VMware vCenter 9.1.1.0100

Download Filename:	VMware-vCenter-Server-Appliance-9.1.1.0100.25784172-patch-FP.iso
Build:	25784172
Download Size:	8068.7 MB
SHA256 checksum:	65b0b7b77f8f72b414584af57fd1251f6b7e34948c0f6f09c3a893ef2e9929ca

Applying the Patch

Log in to the Broadcom Support Portal to download this patch, depending on your entitlement.

For download instructions, see Download Broadcom products and software.

For more information on using the vCenter shells, see Broadcom knowledge base article 2100508.

For VCF environments, you apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

For VMware vSphere Foundation environments, see Upgrading the vCenter Appliance.

Resolved Issues

Upgrade Issues

A reset of the vSphere Lifecycle Manager database might cause data loss in the vSphere Supervisor

If the vSphere Lifecycle Manager database in your environment is reset before upgrading vCenter from versions 8.0 Update 3 and later or 9.0.x to 9.1.0 or 9.1.1, the upgrade might cause data loss in the vSphere Supervisor. To avoid data loss, before a vCenter upgrade, you must first check your environment and take mitigation steps.

vCenter upgrade or patch to version 9.1.1 fails during the prechecks with error message: Unable to run vCenter NTP server check

The NTP precheck fails on vCenter instances configured with a non-UTC time zone.

vSAN

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for vSAN 9.1.1.x:

- vSAN 9.1.1.0100 Release Notes

vSAN 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VMware vSAN 9.1.1.0100 | 12 OCT 2026 |
VMware vSAN ESA Witness 9.1.1.0100 | 12 OCT 2026 | Build 25784021
VMware vSAN OSA Witness 9.1.1.0100 | 12 OCT 2026 | Build 25783993
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

NSX

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for NSX 9.1.1.x:

- NSX 9.1.1.0100 Release Notes

NSX 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

NSX 9.1.1.0100 | 12 OCT 2026 | 25762940
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

SDDC Manager

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for SDDC Manager 9.1.1.x:

- VCF Installer / SDDC Manager 9.1.1.0200 Release Notes

VCF Installer / SDDC Manager 9.1.1.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues
- Known Issues

Introduction

VCF Installer / SDDC Manager 9.1.1.0200 | 12 OCT 2026 | Build 25801071
Check for additions and updates to these release notes.

What's New

This release delivers fixes as described in the Resolved Issues section.

IMPORTANT: For upgrading your environment from VCF 5.2.1 to 9.1.1.0200, you must first upgrade from 5.2.1 to 5.2.2 or 5.2.3 and then to 9.1.1.0200.

Applying the Patch

Use the latest available binaries for components when you deploy, upgrade, or patch.

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

When configuring DNS or NTP servers with link-local IP addresses during VCF deployment, the VCF Installer validation rejects the addresses and blocks the deployment from proceeding.

The VCF Installer validation rejects link-local IP addresses, such as those in the `169.254.0.0/16` range, across all IP input fields. This validation is necessary for fields where link-local addresses should not be permitted, such as NSX tunnel endpoint IPs, vMotion, and management network specifications. However, the same validation also applies to DNS and NTP server fields, where link-local addresses are valid and sometimes required. In cloud environments, DNS and NTP services are reachable only through link-local addresses, and the blanket rejection prevents provisioning using native hyperscaler infrastructure services.

SDDC Manager fails to connect to the online depot through a proxy server with configured SSL/TLS interception

When SDDC Manager validates the online depot FQDN during depot configuration, it does not route the request through the configured proxy with SSL/TLS interception. In network environments where the depot FQDN is resolvable only through the proxy, the validation fails because the direct DNS lookup cannot resolve the address. Additionally, the certificate retrieval step that follows bypasses the proxy entirely, fetching the depot certificate directly instead of through the proxy connection. The issue occurs even when all required online depot URLs are allowed on the proxy and the proxy's root CA certificate is imported in the SDDC Manager trust store. This issue prevents SDDC Manager from retrieving depot certificates, which blocks online depot operations such as patch downloads and bundle retrieval.

When deploying a new VCF or vSphere Foundation instance by using VCF Installer, on the General Information page, the version drop-down menu is empty and does not pre-load the target version, requiring manual selection of the version before proceeding

The VCF Installer UI performs an exact version match against the versions returned by the releases API. A mismatch between the version string sent by the UI and the version string returned by the API prevents the drop-down menu from automatically populating with the default version.

After SDDC Manager completes an upgrade of the VCF Operations HCX component, the upgrade overview in the SDDC Manager UI continues to show zero steps completed for 15 minutes or longer, and the component remains listed as ready to upgrade, even though the upgrade task has succeeded

The VCF Operations HCX upgrade does not update the target version in the SDDC Manager lifecycle management cache after the upgrade completes. As a result, SDDC Manager relies on the scheduled LCM cache refresh to detect the completed upgrade, which can delay the status update.

If SDDC Manager cluster creation fails before vCenter creates the cluster object, you cannot remove the cluster

If the cluster creation operation fails before vCenter creates the cluster object, the cluster does not exist in vCenter. When you attempt to remove the failed cluster from SDDC Manager, the removal operation cannot locate the cluster object in vCenter and hangs indefinitely.

Upgrading an NSX Manager cluster by using SDDC Manager fails with a error message

During retention evaluation, the automated backup cleanup script skips NSX backups stored under the NSX Manager Virtual IP (VIP) directory structure. As a result expired backups accumulate indefinitely on the SFTP server. When the upgrade retrieves the backup history, the accumulated files cause the NSX API to time out, returning the following error: `Read timed out.`

After importing a workload domain whose cluster hosts have individually configured NSX transport nodes, domain synchronization fails with an error message

If the hosts in an imported workload domain have individually configured transport nodes rather than a Transport Node Profile, the domain synchronization workflow detects the host-level NSX configuration and attempts to record a warning for the cluster. An error while recording the warning stops the synchronization and returns the following error message: `NSX_TNC_CONFIG_ERROR_GENERICError in configuring transport node collections.`

Importing an existing vCenter instance deploys NSX Manager on the wrong vCenter and the wrong distributed virtual port group

If a stale powered-off VM with the same hostname as the vCenter VM exists on the target cluster, SDDC Manager detects the stale VM instead of the actual vCenter instance. As a result, SDDC Manager deploys NSX Manager to the wrong vCenter and port group. If there is no connectivity between the NSX Manager VMs and vCenter, the import fails during **Compute Manager** registration.

Importing a new workload domain or converging a vCenter with a shared NSX fail with a misleading compatibility error when the NSX install image bundles are deleted from the SDDC Manager bundle repository, even though the existing NSX instance is compatible with the target vCenter

When importing a new workload domain or converging a vCenter with a shared NSX instance, the workflow may fail with an error stating that the existing NSX instance is not compatible with the vCenter, even though the versions are compatible. This occurs when NSX installation bundles have been removed from the SDDC Manager bundle repository.

After SDDC Manager completes a Quick Patch of the management domain vCenter, the vCenter version displayed in VCF Operations shows a false version drift, and the vCenter upgrade bundle remains listed as available in SDDC Manager, even though the upgrade succeeded

SDDC Manager caches the vCenter version per session with no expiry. The cache is removed only if SDDC Manager disconnects from vCenter or the connection throws an error. A quick patch workflow does not restart vCenter services and as a result SDDC Manager holds the pre-patch vCenter version persists in the inventory indefinitely. This also corrupts SDDC Manager upgrade-readiness state, because the vCenter bundle remains listed as available, which can affect upgrade sequencing and checks for subsequent operations.

After a failed or aborted upgrade attempt, upgrading vCenter to version 9.1 by using the Reduced Downtime Upgrade workflow fails

When you run pre-checks or upgrade vCenter by using the Reduced Downtime Upgrade workflow, the upgrade fails at the **VCENTER_UPGRADE_PRECHECK** stage with the following error message: `vCenter upgrade failed at the VCENTER_UPGRADE_PRECHECK stage. vCenter set target version - vCenter set target version - <target_version> failed. Non retriable exception while retrying operation failed.`

This issue occurs when the source vCenter version is below 9.1, target vCenter version is 9.1 or later, but after a failed or aborted upgrade attempt, vCenter Lifecycle Manager is already version 9.1 or later. As a result, SDDC Manager tries to upgrade vCenter Lifecycle Manager by using a method, that requires vCenter version 9.1 or later. Since the vCenter version is below 9.1, the pre-check fails.

Upgrading SDDC Manager to version 9.1.1 fails at the SDDC Manager Deployment Drift step

If the password for any SDDC Manager appliance account (such as `root`, `vcf`, `backup`, or `audit`) was changed more than 90 days ago and the default password policy configuration has been modified, during the SDDC Manager upgrade procedure, the configuration restore task incorrectly expires the respective accounts and as a result, the upgrade to version 9.1.1 fails.

Known Issues

When the Binary Management page lists 90 or more bundles, error banners or missing download statuses are displayed

When the **Binary Management** page lists 90 or more bundles, the page sends all bundle status requests at once and the gateway rejects the excess requests with a HTTP 503 error. This issue affects mostly installation binaries on upgraded setups with large software depot instances, and does not affect bundle downloading, scheduling, or deleting operations.

Workaround: Perform the following tasks.

1. Ignore and close the error banners.
2. If a bundle shows no status, reload the page or switch the binary type and switch back.

3. If a bundle you no longer need is listed, such as a bundle for version you have already upgraded to, delete the bundle.
4. For bulk download, schedule, or delete actions, select less than 90 bundles per action, and verify that the system created a task for each bundle.

VCF Operations

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for VCF Operations 9.1.1.x:

- 9.1.1.0100
- 9.1.1.0200

9.1.1.0100

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

VCF Operations:

- VCF Operations 9.1.1.0100 Release Notes
- VCF Operations for Networks 9.1.1.0100 Release Notes
- VCF Operations HCX 9.1.1.0100 Release Notes
- VCF Operations Orchestrator 9.1.1.0100 Release Notes

VCF Management Services:

- VCF Services Runtime 9.1.1.0100 Release Notes
- Fleet Lifecycle 9.1.1.0100 Release Notes
- SDDC Lifecycle 9.1.1.0100 Release Notes
- Log Management 9.1.1.0100 Release Notes
- Real-Time Metrics 9.1.1.0100 Release Notes
- Salt Master 9.1.1.0100 Release Notes
- Salt RaaS 9.1.1.0100 Release Notes
- Telemetry 9.1.1.0100 Release Notes
- Identity Broker 9.1.1.0100 Release Notes

VCF Operations 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

VCF Operations 9.1.1.0100 | 12 OCT 2026 | Build 25795063
VCF Operations Upgrade 9.1.1.0100 | 12 OCT 2026 | Build 25795060
Cloud Proxy 9.1.1.0100 | 12 OCT 2026 | Build 25795064
License Server 9.1.1.0100 | 12 OCT 2026 | Build 25795080
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

When you apply the VCF Operations patch, the cloud proxy and license server components are patched automatically.

Resolved Issues

The vCenter Task Console displays recurring plug-in tasks and vCenter license assignment fails from VCF Operations.

When a vCenter instance is managed by VCF Operations, the VCF Operations plug-in registers and unregisters cyclically. As a result, the vCenter Task Console becomes populated with recurring plug-in download, deployment, and undeployment tasks. Additionally, license assignment to vCenter instances from VCF Operations fails.

An error is displayed on the Build > Lifecycle > VCF Instance page when accessing it with a user scope restricted only to a specific workload domain

When a user with restricted access to a specific workload domain navigates to the Build > Lifecycle > VCF Instance page, the page fails to load and displays an error. This issue is triggered by dependency in the scope permissions, and the page only functions correctly if the assigned scope also explicitly includes access to the management vCenter object. This dependency limits the ability to effectively restrict per-domain access for users and groups.

Witness and data nodes with a mismatched build version can join the cluster without a compatibility check

In VCF Operations 9.1, the endpoints that enroll witness and data nodes into the cluster do not perform a build-version compatibility check. As a result, a witness or data node running a newer or older build can be enrolled into the cluster without being rejected, leaving the cluster in a mixed-build state.

A replica node running a newer or older build can join the cluster without a version compatibility check

In VCF Operations 9.1, the replica node enrollment flow does not perform a build-version compatibility check. As a result, a replica node deployed on a newer or older build than the primary node can join the cluster without being rejected, leaving the cluster in a mixed-build state. The inconsistency surfaces later when any subsequent data-node addition is rejected with HTTP 412, blocking further scale-out and requiring a manual workaround.

vCenter integration settings are not saved when vSAN is not enabled for the cluster.

In VCF Operations 9.1, when vSAN is not enabled for the cluster, the product does not save updates to vCenter integration settings made from the **Integrations** page. This blocks routine administrative tasks such as updating the vCenter password or activating Log Collection.

Upgrading to 9.1.1 causes Telegraf plugin deletion and updates to fail, resulting in orphan configuration blocks and continued data collection

When updating or deleting Telegraf plugins in version 9.1.1, a status update task unexpectedly bakes a dynamic job ID (jobId) into the plugin's configuration file marker on the cloud proxy. Because subsequent operations attempt to match the original marker format (without the job ID), the system fails to locate the marker and cannot remove or edit the plugin block.

A missing role or authentication failure during Content Management export/import results in a silent failure with no error message displayed

Single sign-on users without an assigned role experience a silent failure during Content Management export/import operations, with no error message displayed indicating the failure.

Local user accounts in VCF Operations are locked for an incorrect duration after exceeding the maximum failed login attempts, conflicting with the configured lockout policy

When a local user account was locked due to exceeding maximum failed login attempts, the lockout expiry duration was incorrectly calculated using the password expiration setting (in days) directly as seconds, rather than using the configured lockout duration policy setting.

Note: The 'admin' user account was not affected by this issue.

VCF Operations HCX 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VCF Operations HCX 9.1.1.0100 | 12 OCT 2026 | Build 25768312 Check for additions and updates to these release notes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Operations for Networks 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Known Issues

Introduction

VCF Operations for Networks 9.1.1.0100 | 12 OCT 2026 | Build 25774578 Check for additions and updates to these release notes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Known Issues

The collector hostname appears as "localhost" in the log collection UI.

In VCF Operations, the log collection UI displays the collector hostname as "localhost" instead of the actual hostname or IP address. This cosmetic display issue occurs under Administration > Configurations > Log Collection > Agent and does not affect log collection

Workaround: None

VCF Operations Orchestrator 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

VCF Operations orchestrator 9.1.1.0100 | 12 OCT 2026 | Build 25795101 Check for additions and updates to these release notes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

The Ochestrate tab in the Provider Consumption organization is not available after restarting the embedded VCF Operations orchestrator

After restarting the VCF Operations orchestrator instance that is embedded in VCF Automation, for example, after a plug-in update, and launching the Provider Consumption Organization, the Orchestrate tab is not available in the organization. In addition, workflows that were previously visible in the Provider Consumption organization are no longer accessible.

Running a VCF Operations orchestrator workflow output that holds a managed object fails with an error

Running any VCF Operations orchestrator workflow that binds an output of type `Any` which holds a VMODL data object that references a managed object fails at the output-binding step with the error `java.lang.NullPointerException: Cannot invoke "java.lang.Class.getName()" because the return value of "java.lang.reflect.Method.getDeclaringClass()" is null`.

Long-running workflows in VCF Operations orchestrator fail intermittently with an error

Long-running workflows in VCF Operations orchestrator fail intermittently with one of two errors, `ch.dunes.util.NotAuthorizedException: No active session with id *******` or `delegating token is not service token`. Logs also show the error `Failed to retrieve permissions using service account.org.springframework.web.client.HttpClientErrorException$BadRequest: 400 Bad Request` some time prior to the first error. This issue is caused by service token rotation that is enabled by default in VCF Automation. When two VCF Operations orchestrator instances or two threads try to renew the service tokens at the same time, the token for the second instance is no longer valid.

Running local system commans in VCF Operations orchestrator fails with the error "This method is disabled for security reasons. 'Command' is deprecated and will be removed in future release"

When running local system commands in VCF Operation orchestrator using workflows that use the JS script engine, the operation fails with the error `This method is disabled for security reasons. 'Command' is deprecated and will be removed in future release.` Approvals for operations using the command method are also marked with a red exclamation mark even if the approvals were granted correctly.

VCF Operations orchestrator script editor gets stuck when the browser is set to a non-English locale

The script editor in VCF Operations orchestrator 9.1.1 fails to load if the user's browser language or locale is set to anything other than English. The application remains permanently stuck on a loading spinner, preventing users from viewing or editing scripts.

Fleet Lifecycle 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

Fleet Lifecycle 9.1.1.0100 | 21 SEP 2026 | Build 25761871 Check for additions and updates to these release notes.

What's New

This release delivers fixes as described in the Resolved Issues section.

Resolved issues in this patch also depend on other components. When deploying new 9.1.1.x environments or patching existing 9.1.0.x environments, ensure you use:

- Fleet lifecycle 9.1.1.0100 binaries
- SDDC lifecycle 9.1.1.0100 binaries
- Migration service engine 9.1.1.0100 binaries

Applying the Patch

Use the latest available binaries for components when you deploy, upgrade, or patch.

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

Fleet lifecycle sync tasks remain in pending state indefinitely

Manually initiating a lifecycle metadata sync operation from the Lifecycle view under VCF Management in VCF Operations can cause the task to stall in a pending state and prevent the page from loading.

Post-patch inventory sync fails during VCF Operations registration for VCF services runtime clusters with more than 20 nodes

During post-patch inventory synchronization, registering a VCF services runtime cluster with more than 20 nodes with VCF Operations fails with a `DuplicateKeyError`. This occurs because the inventory synchronization process creates duplicate node records for clusters of this size, preventing registration from completing.

When you patch components to 9.1.1 you might see an error task message in the VCF Operations UI on the Register a component with VCF Operations step

When you patch VCF components from version 9.1.0.x to 9.1.1, if the SDDC Manager certificate of the VCF Instance has 15 or less days of validity, this certificate prevents the new version of a successfully patched component to register with VCF Operations.

SDDC Lifecycle 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

SDDC Lifecycle 9.1.1.0100 | 21 SEP 2026 | Build 25761870
Check for additions and updates to these release notes.

What's New

This release delivers fixes as described in the Resolved Issues section.

Resolved issues in this patch also depend on other components. When deploying new 9.1.1.x environments or patching existing 9.1.0.x environments, ensure you use:

- Fleet lifecycle 9.1.1.0100 binaries
- SDDC lifecycle 9.1.1.0100 binaries
- Migration service engine 9.1.1.0100 binaries

Applying the Patch

Use the latest available binaries for components when you deploy, upgrade, or patch.

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

Registering a VCF services runtime cluster with more than 20 nodes with VCF Operations fails

When registering a VCF Services runtime cluster with more than 20 nodes with VCF Operations, the registration fails with a `duplicate key error`. This occurs because the inventory synchronization process creates duplicate node records for large clusters, preventing registration from completing.

During patching of a subsequent SDDC lifecycle instance to 9.1.1.0, operation fails in VCF fleets with more than one VCF Instance

In a VCF fleet managing multiple instances, patching the SDDC lifecycle component to version 9.1.1.0 succeeds on the first instance but might fail on subsequent instances. The failure occurs during the fleet lifecycle refresh step with error reference code 63377924, preventing the patch from completing on the affected instances.

When you click the Sync button to sync lifecycle metadata in VCF Operations, the software depot to staging task might remain stuck

When patching from version 9.1.0.x to 9.1.1, the software depot metadata synchronization step remains in progress indefinitely, preventing the synchronization from completing.

VCF Services Runtime 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

VCF Services Runtime 9.1.1.0100 | 12 OCT 2026| Build 25801571
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

VCF services runtime exposes ports 30005 and 30006 over an insecure TLS port

The VCF services runtime exposes ports **30005** and **30006** over a TLS configuration that does not meet security hardening requirements.

VCF Log Management installation stalls during setup or has authentication issues post-intallation

During installation, the VCF Log Management install process may stop responding and fail to complete. Issues can cause VCF Log Management installation to either stall, take 30 more minutes than necessary, or cause authentication issues when certain operations are performed post-installation.

Log Management 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Log Management 9.1.1.0100 | 12 OCT 2026 | Build 25795095
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Real-Time Metrics 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Real-Time Metrics 9.1.1.0100 | 12 OCT 2026 | Build 25801571
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Salt Master 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Salt Master 9.1.1.0100 | 12 OCT 2026 | Build 25795075
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Salt RaaS 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Salt RaaS 9.1.1.0100 | 12 OCT 2026 | Build 25795075
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Telemetry 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Telemetry 9.1.1.0100 | 12 OCT 2026| Build 25741214 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

Use the latest available binaries for components when you deploy, upgrade, or patch.

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Identity Broker 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Identity Broker 9.1.1.0100 | 12 OCT 2026 | Build 25796677 Check for additions and updates to these release notes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This patch includes no changes other than the alignment of build details and does not introduce any resolved or known issues.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

9.1.1.0200

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

VCF Management Services:

- Fleet Lifecycle 9.1.1.0200 Release Notes
- SDDC Lifecycle 9.1.1.0200 Release Notes
- Software Depot 9.1.1.0200 Release Notes

Fleet Lifecycle 9.1.1.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues
- Known Issues

Introduction

Fleet Lifecycle 9.1.1.0200 | 12 OCT 2026 | Build 25801070 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

Domain Lifecycle content fails to load in VCF Operations

After navigating to **Build > Lifecycle** and selecting a domain or refreshing the page, the Lifecycle content might fail to load and the loading indicator might continue to spin. As a result, users cannot access the Upgrades page for the domain.

Deployment spec validation now rejects non-native Single Sign-On domains for the administrator username

When you submit a deployment spec, the system now validates that the `adminUserSsoUsername` value belongs to the vCenter native or local Single Sign-On (SSO) domain, as reported by the vCenter SSO configuration API. If the username belongs to a federated or external domain, the system rejects the submission and displays a validation error that instructs you to provide a native SSO account. This change prevents misconfigurations that could occur when a federated domain account was previously accepted for the administrator username.

Missing VSP services runtime binaries cause VCF Automation deployment or upgrade to fail

When you deploy or upgrade VCF Automation on an existing SDDC, the operation fails with a generic, unactionable error if the requested VCF services runtime installation binaries are not downloaded in SDDC Manager. The failure occurs after the bootstrap task has started.

Incorrect IP pool size is not reported as an error in the UI when a fleet task runs

When an IP pool has an incorrect size, the VCF services runtime task detects and reports the error, but the fleet task does not show this error in the UI. As a result, users may not be aware that the IP pool size is invalid, and the operation may appear to succeed or fail without a clear error message.

Fleet lifecycle component installation or patch fails in multi-VCF deployments because of an invalid SDDC Manager certificate

In a multi-VCF deployment, upgrading SDDC lifecycle on a secondary VCF instance after upgrading fleet lifecycle on a primary VCF instance can fail. The fleet lifecycle refresh step `refresh_fleet_lcm_component_task_ref` encounters an unexpected error, and the subsequent `post_upgrade_inventory_sync` step also fails. The root cause is that an invalid SDDC Manager certificate is sent during component install or patch operations. This failure affects both component patching and component install workflows.

Upgrading to VCF Automation 9.1.x requires the source and target clusters to reside on the management datastore

When you upgrade to VCF Automation 9.1.x from 8.x or 9.0.x, both the source cluster and the target cluster must reside on the same datastore, and that datastore must be the management datastore. An arbitrary non-management datastore that is visible to the management cluster does not satisfy this requirement. If the source and target clusters do not both reside on the management datastore, the upgrade to 9.1.x is not supported.

Fleet lifecycle installs dependency components at base version instead of latest express patch

Fleet lifecycle 9.1.1.0 and 9.1.1.0100 always install dependency components at version 9.1.1.0, regardless of the latest available express patch release. This behavior prevents customers from installing the latest express patch for migration service engine and VCF services runtime when deploying VCF Automation, and for real-time metrics store when deploying real-time metrics.

Deployment validation does not detect an invalid identity broker IP address until late in the process

During deployment, the validation checks do not detect when the identity broker IP address is not part of the VCF services runtime network. Because the misconfiguration goes unchecked, the deployment proceeds for approximately three hours before it fails with an error. This delays detection of the invalid network configuration and wastes deployment time.

Deployment wizard forces vCenter selection when using an existing VCF Operations instance

When deploying VCF 9.1.1, customers who select the option to use an existing VCF Operations 9.1 instance find that the wizard automatically selects the option to use an existing vCenter instance. Customers cannot clear this selection. This affects customers who want to reuse their existing VCF Operations instance but do not want to reuse an existing vCenter instance.

Known Issues

VCF services runtime component upgrade task fails during database failover

During a VCF services runtime upgrade, the Conductor task that upgrades the VCF services runtime component can fail if a PostgreSQL database failover or database read timeout occurs while Conductor is updating the task state.

Because the task state update fails in the database, the task is not returned to the queue and is lost. When the Conductor sweeper thread finds that the component upgrade task is stuck in progress, has not received any new task updates, and hits `responseTimeout`, it marks the task as failed. Conductor has a repair mechanism to fix a lost task, but this mechanism is only invoked once during startup in VCF 9.1 and 9.1.1, not periodically. As a result, a lost task is not automatically recovered.

The underlying VCF services runtime task that upgrades the VCF services runtime cluster continues to make progress without interruption. Only the Conductor task tracking fails. Retrying the failed fleet lifecycle task completes quickly.

Workaround: Retry the failed task.

Transport Node Collection creation fails during Brownfield Import for VCP clusters

When you perform a Brownfield Import of a VMware vCenter® instance running version 8.0.3Ue or later that contains VCP clusters with hosts running version 8.0.3 or later, joining an existing NSX Manager cluster in pinned mode during upgrade from 4.2.x to 9.x causes Transport Node Collection creation to fail for those VCP clusters. The operation returns the following error:

```
vLCM Config Manager is enabled on this cluster. Applying Transport Node Profile is not allowed. (error code
 26219)
```

Workaround:

1. Complete the NSX Manager upgrade finalize process.
2. Retry the Brownfield Import.

Certificate replacement fails when a component certificate's Common Name contains special characters

After a component certificate is replaced outside SDDC Manager, the Non-Disruptive Certificate (NDC) replacement workflow fails. The error is `CS_APPLIANCE_CERT_ALIAS_INVALID`. SDDC Manager can then no longer connect to the affected component, because the new certificate is not added to its trust store.

When a component certificate is replaced directly in the product (out of band) and the new certificate's Common Name (CN) contains special characters, SDDC Manager builds a trust-store alias from that CN. The alias is rejected if it contains anything other than:

- letters (A–Z, a–z) and digits (0–9);
- period (`.`), underscore (_), hyphen (-) and colon (`:`).

The alias is also rejected if it contains consecutive periods (`..`) or exceeds 255 characters. A common example is a space, as in `CN=Root CA`.

Workaround: Re-issue the component certificate with a CN that uses only letters, digits, periods, underscores, hyphens and colons, and has no consecutive periods. Then re-run the NDC workflow.

SDDC Lifecycle 9.1.1.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

SDDC Lifecycle 9.1.1.0200 | 12 OCT 2026 | Build 25801981
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Software Depot 9.1.1.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Software Depot 9.1.1.0200 | 12 OCT 2026 | Build 25801072
Check for additions and updates to these release notes.
For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Automation

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply

based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for VCF Automation 9.1.1.x:

- VCF Automation 9.1.1.0100 Release Notes
- VCF Automation 9.1.1.0200 Release Notes
- Migration Service Engine 9.1.1.0100 Release Notes
- Migration Service Engine 9.1.1.0200 Release Notes

VCF Automation 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

VCF Automation 9.1.1.0100 | 21 SEP 2026 | Build 25757808
Check for additions and updates to these release notes.

What's New

This release allows for the migration service engine 9.1.1.0100 release that fixes a critical issue during patching VCF Automation to version 9.1.1. If your VCF Automation is already at version 9.1.1.0, you can skip the VCF Automation patch to 9.1.1.0100.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Automation 9.1.1.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

VCF Automation 9.1.1.0200 | 12 OCT 2026 | Build 25801570
Check for additions and updates to these release notes.

What's New

This release contains various security enhancements and delivers fixes as described in the Resolved Issues section.

This patch includes new versions with various bug fixes of the following VCF Services:

- VKSM Extensions
- VKS Cluster Management Auto-Attach

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

Upgrade to VCF Automation 9.1.1 fails after the Migration Service Engine step fails with an error such as `Step vmsp_upgrade failed`, and the upgrade precheck reports a failed backup precheck or package-deployment wait timeout.

During VCF Automation upgrade to 9.1.1, the VCD Migrator backup completes successfully, but the subsequent step that deploys the new VCD Migrator Helm release times out indefinitely while waiting on the underlying Helm chart pods and Postgres instance to reach `Ready`. When the workflow deadline is exceeded, the step is marked as failed, leaving the deployment stuck in a `Progressing` state. The Migration Service Engine upgrade must be performed after the VCF Automation upgrade completes; attempting the Migration Service Engine upgrade first creates a deadlock that blocks both upgrades.

After upgrading Aria Automation 8.18.x to VCF Automation 9.x, the configured upstream proxy is not migrated, and outbound calls that depend on the proxy, such as validating cloud accounts, fail.

When migrating the existing proxy configuration during upgrade, the workflow uses a malformed payload with mismatched field names to an internal API and the proxy migration fails. The migration completes with an `Upstream proxy migration completed successfully` message. As a result, the previously configured proxy settings are silently discarded. When you access the cloud account page after the upgrade, the page displays the following error:

```
java.lang.RuntimeException: java.net.ProtocolException: unexpected end of stream
```

When you attempt to validate a cloud account, the validation displays the following error:

```
Unable to validate the provided access credentials
```

Upgrading VCF Automation from 9.0.x to 9.1.1 can fail or time out during the database migration steps.

The `user_session` and `session_role` database tables can accumulate a large number of expired rows if the session-cleanup job stops running, causing the upgrade workflow's row-by-row **DELETE** operation to exceed the database's 30-second statement timeout. The upgrade workflow now uses **TRUNCATE** on the session tables in the database instead of row-by-row **DELETE**.

Pod details not displayed in the VCF Automation organization portal

In the VCF Automation organization, when you navigate to **Manage&Govern** > **Kubernetes Managment** > **Clusters**, you click a cluster and navigate to the **Nodes** tab for the cluster, and you click a pod name to see pod details, a blank page is displayed instead of a pod details page.

When upgrading to VCF Automation 9.1.x from 9.0.x or from Aria Automation 8.18.x, the pre-upgrade validation fails if the datastore hosting the source appliance differs from the datastore used by the target cluster.

When upgrading to VCF Automation 9.1.x from 9.0.x or from Aria Automation 8.18.x, the upgrade workflows requires that the appliance is deployed on the primary datastore of the primary cluster and automatically uses that datastore for the target deployment. Environments where the appliance is deployed on a separate datastore fail the pre-upgrade validation because the storage migration process requires the source and target clusters to use the same datastore.

With VCF Automation 9.1.1.0200 and later, you can upgrade your 8.x or 9.x Automation instance that is not deployed on the primary datastore of the management domain primary cluster, if your fleet lifecycle, SDDC lifecycle, and SDDC Manager components are on version 9.1.1.0200 or later.

When upgrading Aria Automation 8.18.1.x to VCF Automation 9.1.0.x or 9.1.1.0, the pre-upgrade source-validation fails with the following error: `ERROR: Custom profiles detected: proxy-service The precheck com.broadcom.vcfa.upgrade.80.source.check.test-source-04-custom-profiles is reported as failed.`

The precheck script `vra8x-check-custom-profiles.sh` treats any profile directory under `/etc/vmware-prelude/profiles` that is not owned by an RPM package as a customer-added custom profile and fails the upgrade if any are found. The `proxy-service` profile directory is a known leftover from an earlier manual KB-based workaround for an IP Address Management (IPAM)/Infoblox DNS resolution issue. Because this directory is not owned by an RPM package, the precheck flags it as a manually added custom profile and blocks the upgrade.

The precheck script now recognizes and skips the known `proxy-service` profile directory, so the upgrade precheck no longer fails for this specific case.

Retiring a 1.32.x VMware Kubernetes Service cluster and then upgrading it to 1.33.x fails with an `admission webhook` error and requires manually editing the cluster object

After retiring a Tanzu Kubernetes Cluster (TKC) running a vSphere Kubernetes release (VKr) 1.32.x cluster, attempting to upgrade the cluster to VKr 1.33.x fails. The admission webhook denies the upgrade with the following error:

```
admission webhook "capi.validating.tanzukubernetescluster.run.tanzu.vmware.com" denied the request: Cluster's Kubernetes version v1.33.x+vmware.1-fips does not meet the version requirements of ClusterClass vmware-system-vks-public/builtin-generic-v3.1.0 set by annotations: kubernetes.vmware.com/min-version-supported and kubernetes.vmware.com/max-version-supported.
```

This issue occurs because the `kubernetes.vmware.com/skip-auto-cc-rebase` annotation is not removed automatically when a TKC is retired. The presence of this annotation prevents the cluster from rebasing to a newer `ClusterClass` that supports VKr 1.33.x, so the version validation fails.

The notification in the Notifications dashboard widget states an approval request will be automatically approved, even though the request will actually be rejected

When a pending approval request is governed by a policy set to auto-reject after a timeout, the notification in the Notifications dashboard widget states that the request will be automatically approved, even though it will actually be automatically rejected when the timer expires. VCF Automation enforces the auto-reject policy correctly and the email notification and the Inbox Details page both correctly state that the request will be rejected.

VCF Automation displays the licensing evaluation period banner after a fully licensed vCenter 9.x is attached

VCF Automation continues to display the licensing evaluation period banner after a fully licensed vCenter 9.x is attached and is healthy, and the remaining days counter freezes instead of clearing.

After migrating from vIDM to vIDB, some users cannot log in to VCF Automation or lose their group membership permissions

After the VCF Automation identity source is migrated from VMware Identity Manager to VMware Identity Broker, some users who previously had access to VCF Automation can no longer log in or lose the roles and permissions granted by their group membership, even though these users are still listed on the Access Management page with their expected roles.

The Ochestrate tab in the Provider Consumption organization is not available after restarting the embedded VCF Operations orchestrator

After restarting the VCF Operations orchestrator instance that is embedded in VCF Automation, for example, after a plug-in update, and launching the Provider Consumption Organization, the Orchestrate tab is not available in the organization. In addition, workflows that were previously visible in the Provider Consumption organization are no longer accessible.

Running VCF CLI commands fails with an error indicating the plugin-inventory OCI image could not be found in new VCF Automation with a regional Harbor registry

After deploying VCF Automation with a regional Harbor registry and running any VCF CLI command, CLI initialization fails with an error indicating the plug-in inventory OCI image could not be found, which blocks the installation or synchronization of recommended CLI plug-ins.

Custom resource actions disappear from the action list

In VCF Automation, custom resource actions for a deployment or a deployment resource like Cloud.vSphere.Machine disappear from the UI action list. Calling the deployment actions REST API omits the custom action from the JSON response array while standard built-in actions remain present. Navigating to **Design** > **Resource Actions** and saving the action temporarily restores visibility in the UI, but the action disappears again later.

The Servers dropdown menu in the API Help Center or Swagger UI shows an internal address

When an organization administrator opens the VCF Automation API Help Center or Swagger UI for a service, for example, Organization for VM Apps, the Servers dropdown shows `localhost:8600` or a similar internal address instead of the actual VCF Automation URL. The Swagger/OpenAPI specification files for several VCF Automation components, including Blueprints, Catalog, Deployments, Policies, and Organizations for VM Apps, are generated and hosted statically with a hardcoded localhost server entry, which is carried forward into published documentation regardless of the deployment environment. This is a display issue only. The underlying APIs work correctly when called directly.

Migration Service Engine 9.1.1.0100 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

Migration Service Engine 9.1.1.0100 | 21 SEP 2026| Build 25757808 Check for additions and updates to these release notes.

What's New

This release delivers fixes as described in the Resolved Issues section.

Applying the Patch

Use the latest available binaries for components when you deploy, upgrade, or patch.

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

Patching the Migration service engine component to version 9.1.1 fails, times out after several hours, and blocks the VCF Automation patch to 9.1.1

If you start the patch of the migration service engine to 9.1.1 before you patch the VCF Automation instance to 9.1.1, the patch fails with an `Step vmsp_upgrade failed. Reference Code: 85616483.` error. As a result the failed patch blocks both the VCF Automation and the migration service engine patches to version 9.1.1.

Migration Service Engine 9.1.1.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch

Introduction

Migration Service Engine 9.1.1.0200 | 12 OCT 2026| Build 25801570 Check for additions and updates to these release notes.

What's New

This release contains various security enhancements.

Applying the Patch

Use the latest available binaries for components when you deploy, upgrade, or patch.

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

VCF Download Tool

Patch releases provide time-sensitive fixes to security and catastrophic issues, impacting business operations, that need to be released between major, minor, and maintenance releases. You can pick and choose which components to apply based on the impact on your environment and operational costs. Patch releases are not synchronized among all VCF components and do not require a new implementation of a Bill Of Materials.

Patch Releases for VCF Download Tool 9.1.1.x:

- VCF Download Tool 9.1.1.0200 Release Notes

VCF Download Tool 9.1.1.0200 Release Notes

This document contains the following sections

- Introduction
- What's New
- Applying the Patch
- Resolved Issues

Introduction

VCF Download Tool 9.1.1.0200 | 12 OCT 2026 | Build 25801073 Check for additions and updates to these release notes. For information about release types and dependencies, see the Lifecycle Management documentation.

What's New

This release contains various security enhancements.

Applying the Patch

You apply this patch by using VCF Operations. See Upgrade or Patch an Individual VCF Component.

Resolved Issues

When downloading OCI image components through a proxy server by using the artifacts option, the download operation fails

For components with OCI images, the artifacts extension does not pass the proxy arguments to the `imgpkg` commands that pull the images. Without the proxy configuration, `imgpkg` cannot reach the OCI registry through the proxy server.

Async Releases

Introduction

Async releases relate to Express Patches of components released without a corresponding VCF release or third-party deliverables that are released async by other companies in the VCF ecosystem, such as Kubernetes software distributions, or the Async Patch Tool, which allows you to apply critical patches to certain VCF components outside of VCF releases.

vSphere

- VMware Tools Release Notes
- VMware Remote Console Release Notes
- VMware vSphere Container Storage Plug-in Release Notes

VCF Operations

- VMware Cloud Foundation Operations for Integrations 9.1 Release Notes
- VMware Cloud Foundation Operations for Integrations 9.1.1 Release Notes

VCF Automation

- VMware vSphere Kubernetes Service Release Notes
- VMware VKr Release Notes
- VKS Add-ons Release Notes

VMware Cloud Foundation Operations for Integrations 9.1 Release Notes

This document contains the following sections

- Introduction
- What's New

Introduction

VMware Cloud Foundation Operations for Integrations 9.1 Check for additions and updates to these release notes.

What's New

1. OOTB Monitoring Of Databases Provisioned From DSM
   a. Automated monitoring for DSM databases requires zero manual configuration.
   b. Centralized "Data Services" view supports PostgreSQL and MySQL.
   c. Filter and view health at Org, Region, Namespace, or Project levels.
2. Extending VCF Ops Management Packs To Include Logs Based Content
   a. vRLI log management is natively converged into VCF Operations.
   b. Management Packs deliver out-of-the-box log-based dashboards and alerts.
   c. Convert legacy content packs for unified operational visibility.

VMware Cloud Foundation Operations for Integrations 9.1.1 Release Notes

This document contains the following sections

- Introduction
- Known Issues

Introduction

VMware Cloud Foundation Operations for Integrations 9.1.1 Check for additions and updates to these release notes.

This release includes the following known issue:

Known Issues

Mandatory Non-Native Management Pack Upgrades in 9.1.1

- Starting with VCF Operations 9.1.1, several management packs require an updated, compatible version to continue collecting data correctly.

- If the environment has one or more adapter instances configured for any of the impacted management packs, **data collection for those adapter instances will break immediately after you upgrade VCF Operations to 9.1.1**, unless the management pack is also upgraded.
- VCF Operations 9.1.1 includes a pre-upgrade check that will flag affected adapter instances and notifies if any of these management packs are detected in the environment.
- KB 454432 explains which management packs are affected and what action to take.