Building Cloud Applications

Use **VCF Automation** to provision VMs, Kubernetes workloads, and other Cloud Services by using self-service UI, API, and CLI, as DevOps or an application developer.

Table 1847: Provisioning Workloads in VCF and vSphere Foundation

Workload Provisioning Method	UI or Utility	Documentation
UI-based workload provisioning	VCF Automation catalog in the namespace allocated to you by your organization administrator.	Getting Started with the Self-Service Catalog in VCF Automation in the *VMware Cloud Foundation Consumption* documentation.
	Services console in VCF Automation in VCF or Local Consumption Interface invSphere Foundation.	Access the IaaS Services Console or Local Consumption Interface in the *VMware Cloud Foundation Consumption* documentation.
Automated workload provisioning	`kubectl` command in the namespace allocated to you in VCF Automation by your organization administrator, accessing the namespace and Kubernetes resources in it by using the VCF Consumption CLI (also called VCF CLI).	Installing and Using VCF CLI v9.1

Available Workload Types

You can provision the following workload types by using the out-of-the-box VCF deployment:

- Kubernetes clusters
- Virtual machines
- Containers as vSphere Pods
- Secrets
- Persistent volumes
- GPU-enabled private AI workloads or Kubernetes clusters
- Databases using Data Services Manager