

an der Fakultät für Informatik

Plant Detection and State Classification with Machine Learning

DIPLOMARBEIT

zur Erlangung des akademischen Grades

Diplom-Ingenieur

im Rahmen des Studiums

Software Engineering & Internet Computing

eingereicht von

Tobias Eidelpes, BSc

Matrikelnummer 01527193

der Technischen Universität Wien		
Betreuung: Ao.UnivProf. Dr. Hors	st Eidenberger	
Wien, 20. Februar 2023		
	Tobias Eidelpes	Horst Eidenberger



Plant Detection and State Classification with Machine Learning

DIPLOMA THESIS

submitted in partial fulfillment of the requirements for the degree of

Diplom-Ingenieur

in

Software Engineering & Internet Computing

by

Tobias Eidelpes, BSc

Registration Number 01527193

to the Faculty of Informatics		
at the TU Wien		
Advisor: Ao.UnivProf. Dr. Horst I	Eidenberger	
Vienna, 20 th February, 2023	Tobias Eidelpes	Horst Eidenberger
	iobias Lidelpes	riorst Eidenberger

Erklärung zur Verfassung der Arbeit

Hiermit erkläre ich, dass ich diese Arbeit selbständig verfasst habe, dass ich die verwen-
deten Quellen und Hilfsmittel vollständig angegeben habe und dass ich die Stellen der
Arbeit – einschließlich Tabellen, Karten und Abbildungen –, die anderen Werken oder
dem Internet im Wortlaut oder dem Sinn nach entnommen sind, auf jeden Fall unter
Angabe der Quelle als Entlehnung kenntlich gemacht habe.

Tobias Eidelpes, BSc

Wien, 20. Februar 2023	
	Tobias Eidelpes

Danksagung

Ihr Text hier.

Acknowledgements

Enter your text here.

Kurzfassung

Ihr Text hier.

Abstract

Enter your text here.

Contents

K	urzfa	ssung	xi
A	bstra	ct	xiii
\mathbf{C}	onter	nts	xv
1		roduction	1
	1.1	Motivation and Problem Statement	1
	1.2	Methodological Approach	3
	1.3	Thesis Structure	4
2	The	oretical Background	5
	2.1	Object Detection	5
	2.2	Classification	6
	2.3	Transfer Learning	6
	2.4	Hyperparameter Optimization	6
	2.5	Related Work	7
3	Pro	totype Development	11
	3.1	Requirements	11
	3.2	Design	12
	3.3	Object Detection	12
	3.4	Classification	15
	3.5	Deployment	15
4	Eva	luation	17
•	4.1	Methodology	17
	4.2	Results	17
	7.2	4.2.1 Object Detection	17
		Test Phase	18
		Hyperparameter Optimization	18
		4.2.2 Classification	21
		Hyperparameter Optimization	$\frac{21}{22}$
		Class Activation Maps	$\frac{22}{24}$
			∠1

		4.2.3	Aggregate Model	27					
		4.2.4	Non-optimized Model	28					
		4.2.5	Optimized Model	29					
	4.3	Discus	sion	30					
5	Conclusion								
	5.1	Future	e Work	31					
List of Figures									
List of Tables									
List of Algorithms									
Acronyms									
Bi	bliog	raphy		41					

CHAPTER 1

Introduction

Machine learning has seen an unprecedented rise in various research fields during the last few years. Large-scale distributed computing and advances in hardware manufacturing have allowed machine learning models to become more sophisticated and complex. Multi-billion parameter deep learning models show best-in-class performance in Natural Language Processing (NLP) [BMR⁺20], fast object detection [BWL20] and various classification tasks [ZHT22; AH22]. Agriculture is one of the areas which profits substantially from the automation possible with machine learning.

Large-scale as well as small local farmers are able to survey their fields and gardens with drones or stationary cameras to determine soil and plant condition as well as when to water or fertilize [RRL⁺20]. Machine learning models play an important role in that process because they allow automated decision-making in real time. While machine learning has been used in large-scale agriculture, it is also a valuable tool for household plants and gardens. By using machine learning to monitor and analyze plant conditions, homeowners can optimize their plant care and ensure their plants are healthy and thriving.

1.1 Motivation and Problem Statement

The challenges to implement an automated system for plant surveying are numerous. First, gathering data in the field requires a network of sensors which are linked to a central server for processing. Since communication between sensors is difficult without proper infrastructure, there is a high demand for processing the data on the sensor itself [MWL22]. Second, differences in local soil, plant and weather conditions require models to be optimized for these diverse inputs. Centrally trained models often lose the nuances present in the data because they have to provide actionable information for a larger area [Awa19]. Third, specialized methods such as hyper- or multispectral imaging in the field provide fine-grained information about the object of interest but come with substantial upfront costs and are of limited interest for gardeners.

To address all of the aforementioned problems, there is a need for an installation which is deployable by homeowners, gathers data using readily available hardware and performs computation on the device without a connection to a central server. The device should be able to visually determine whether the plants in its field of view need water or not and output its recommendation.

The aim of this work is to develop a prototype which can be deployed by gardeners to survey plants and recommend watering or not. To this end, a machine learning model will be trained to first identify the plants in the field of view and then to determine if the plants need water or not. The model should be suitable for edge devices equipped with a TPU or GPU but with otherwise limited processing capabilities. Examples of such systems include Google's Coral development board and the Nvidia Jetson series of single-board computers (SBCs). The model should make use of state-of-the-art algorithms from either classical machine learning or deep learning. The literature review will yield an appropriate machine learning method. Furthermore, the adaption of existing models (transfer learning) for object detection to the domain of plant recognition may provide higher performance than would otherwise be achievable within the time constraints.

The model will be deployed to the single-board computer and evaluated using established and well-known metrics from the field of machine learning. The evaluation will seek to answer the following questions:

1. How well does the model work in theory and how well in practice?

We will measure the performance of our model with common metrics such as accuracy, F-score, Receiver Operating Characteristic (ROC) curve, Area Under the Curve (AUC), Intersection over Union (IOU) and various mean Average Precision (mAP) measures. These measurements will allow comparisons between our model and existing models. We expect the plant detection part of the model to achieve high scores on the test dataset. However, the classification of plants into stressed and non-stressed will likely prove to be more difficult. The model is limited to physiological markers of water stress and thus will have difficulties with plants which do not overtly display such features.

Even though models may work well in theory, some do not easily transfer to practical applications. It is, therefore, important to examine if the model is suited for productive use in the field. The evaluation will contain a discussion about the model's transferability because theoretical performance does not automatically guarantee real-world performance due to different environmental conditions.

2. What are possible reasons for it to work/not work?

Even if a model scores high on performance metrics, there might be a mismatch between how researchers think it achieves its goal and how it actually achieves its goal. The results have to be plausible and explainable with its inputs. Otherwise, there can be no confidence in the model's outputs. Conversely, if the model does not work, there must be a reason. We estimate that the curation of the dataset for the training and test phases will play a significant role. Explanations for model out- or underperformance are likely to be found in the structure and composition of the model's inputs.

3. What are possible improvements to the system in the future?

The previous two questions will yield the data for possible improvements to the model and/or our approach. With the decision to include a plant detection step at the start, we hope to create consistent conditions for the stress classification. A downside to this approach is that errors during detection can be propagated through the system and result in adverse effects to overall performance. Although we estimate this problem to be negligible, additional feedback regarding our approach in this way might offer insight into potential improvements. If the model does not work as well as expected, which changes to the approach will yield a better result? Similarly to the previous question, the answer will likely lie in the dataset. A heavy focus on dataset construction and curation will ensure satisfactory model performance.

1.2 Methodological Approach

The methodological approach consists of the following steps:

- **Literature Review** The literature review informs the type of machine learning methods which are later applied during the implementation of the prototype.
- **Object Detection** Flowers present in the image will be detected using object detection methods. These methods will draw bounding boxes around the objects of interest. The output is fed into the next stage.
- **State Classification** The bounded images will be fed to a classifier which will determine whether the plant needs water or not.
- **Deployment to SBC** The software prototype will be deployed to the single-board computer.
- **Evaluation** The prototype will be evaluated to determine its feasibility and performance. During evaluation the author seeks to provide a basis for answering the research questions.

Additionally, go into detail about how the literature was selected to be relevant for the decisions underlying the choice of models/algorithms. Mention how literature in general was found (search terms, platforms, etc.).

1.3 Thesis Structure

The first part of the thesis (chapter 2) contains the theoretical basis of the models which we use for the prototype. Chapter 3 goes into detail about the design of the prototype, the construction of the training/test sets and how the prototype reports its results via its REST API. Chapter 4 shows the results of the testing phases as well as the performance of the aggregate model. Futhermore, the results are compared with the expectations and it is discussed whether they are explainable in the context of the task at hand as well as benchmark results from other datasets (COCO). Chapter 5 concludes the thesis with an outlook on further research questions and possible improvements.

CHAPTER 2

Theoretical Background

Describe the contents of this chapter.

- Introduction to Object Detection, short "history" of methods, region-based vs. single-shot, YOLOv7 structure and successive improvements of previous versions. (8 pages)
- Introduction to Image Classification, short "history" of methods, CNNs, problems with deeper network structures (vanishing gradients, computational cost), methods to alleviate these problems (alternative activation functions, normalization, residual connections, different kernel sizes). (10 pages)
- Introduction into transfer learning, why do it and how can one do it? Compare fine-tuning just the last layers vs. fine-tuning all of them. What are the advantages/disadvantages of transfer learning? (2 pages)
- Introduction to hyperparameter optimization. Which methods exist and what are their advantages/disadvantages? Discuss the ones used in this thesis in detail (random search and evolutionary optimization). (3 pages)
- Related Work. Add more approaches and cross-reference the used networks with the theoretical sections on object detection and image classification. (6 pages)

Estimated 29 pages for this chapter.

2.1 Object Detection

Give a definition of object detection and contrast it with instance segmentation/other detection tasks. Briefly mention how object detection was done before deep neural

networks (feature-based methods (HOG, SIFT) and sliding window methods (Viola-Jones)). Go over the different approaches to object detection, namely region-based methods (Mask R-CNN and Faster R-CNN) and single-shot detection. Illustrate the approach region-based methods take and discuss problems arising from said approach (e.g. Dual-Priorities, multiple image passes and slow selective search algorithms for region proposals). Contrast the previous region-based methods with newer single-shot detectors such as YOLO and SSDnet. Describe the inner workings of the YOLOv7 model structure and contrast it with previous versions. What has changed and how did these improvements manifest themselves? Reference the original paper [WBL22] and papers of previous versions of the same model (YOLOv5 [JCS+22], YOLOv4 [BWL20]).

Estimated 10 pages for this section.

2.2 Classification

Give a definition of image classification and briefly mention the way in which classification was done before the advent of CNNs. Introduce CNNs, their overall design, and why a kernel-based approach allows two-dimensional data such as images to be efficiently processed. Give an introduction to SOTA classifiers before ResNet (AlexNet, VGGnet Inception/GoogLeNet), the prevailing opinion of going deeper (stacking more layers) and the limit of said approach (Degradation Problem) due to Vanishing Gradients. Explain ways to deal with the vanishing gradients problem by using different activation functions other than Sigmoid (ReLU and leaky ReLU) as well as normalization techniques and residual connections. Introduce the approach of the ResNet networks which implement residual connections to allow deeper layers. Describe the inner workings of the ResNet model structure. Reference the original paper [HZR⁺16].

Estimated 10 pages for this section.

2.3 Transfer Learning

Give a definition of transfer learning and explain how it is done. Compare fine-tuning just the last layers vs. propagating changes through the whole network. What are advantages to transfer learning? Are there any disadvantages?

Estimated 2 pages for this section.

2.4 Hyperparameter Optimization

Give a definition of hyperparameter optimization, why it is done and which improvements can be expected. Mention the possible approaches (grid search, random search, bayesian optimization, gradient-based optimization, evolutionary optimization) and discuss the used ones (random search (classifier) and evolutionary optimization (object detector) in detail.

Estimated 3 pages for this section.

2.5 Related Work

The literature on machine learning in agriculture is broadly divided into four main areas: livestock management, soil management, water management, and crop management [BTD⁺21]. Of those four, water management only makes up about 10% of all surveyed papers during the years 2018–2020. This highlights the potential for research in this area to have a high real-world impact.

Su et al. [SCL⁺20] used traditional feature extraction and pre-processing techniques to train various machine learning models for classifying water stress for a wheat field. They took top-down images of the field using an unmanned aerial vehicle (UAV), segmented wheat pixels from background pixels and constructed features based on spectral intensities and color indices. The features are fed into a support vector machine (SVM) with a Gaussian kernel and optimized using Bayesian optimization. Their results of 92.8% accuracy show that classical machine learning approaches can offer high classification scores if meaningful features are chosen. One disadvantage is that feature extraction is often a tedious task involving trial and error. Advantages are the small dataset and the short training time (3s) required to obtain a good result.

Similarly, López-García et al. [LIM+22] investigated the potential for UAVs to determine water stress for vineyards using RGB and multispectral imaging. The measurements of the UAV were taken at 80 m with a common off-the-shelf APS-C sensor. At the same time, stem water measurements were taken with a pressure chamber to be able to evaluate the performance of an artificial neural network (ANN) against the ground truth. The RGB images were used to calculate the green canopy cover (GCC) which was also fed to the model as input. The model achieves a high determination coefficient R^2 of 0.98 for the 2018 season on RGB data with a relative error of RE = 10.84%. However, their results do not transfer well to the other seasons under survey (2019 and 2020).

Zhuang et al. [ZWJ $^+17$] showed that water stress in maize can be detected early on and, therefore, still provide actionable information before the plants succumb to drought. They installed a camera which took 640×480 pixel RGB images every two hours. A simple linear classifier (SVM) segmented the image into foreground and background using the green color channel. The authors constructed a fourteen-dimensional feature space consisting of color and texture features. A gradient boosted decision tree (GBDT) model classified the images into water stressed and non-stressed and achieved an accuracy of 90.39 %. Remarkably, the classification was not significantly impacted by illumination changes throughout the day.

An et al. [ALL⁺19] used the ResNet50 model as a basis for transfer learning and achieved high classification scores (ca. 95%) on maize. Their model was fed with 640×480 pixel images of maize from three different viewpoints and across three different growth phases. The images were converted to grayscale which turned out to slightly lower

classification accuracy. Their results also highlight the superiority of deep convolutional neural networks (DCNNs) compared to manual feature extraction and gradient boosted decision trees (GBDTs).

Chandel et al. [CCR+21] investigated deep learning models in depth by comparing three well-known CNNs. The models under scrutiny were AlexNet, GoogLeNet, and Inception V3. Each model was trained with a dataset containing images of maize, okra, and soybean at different stages of growth and under stress and no stress. The researchers did not include an object detection step before image classification and compiled a fairly small dataset of 1200 images. Of the three models, GoogLeNet beat the other two with a sizable lead at a classification accuracy of >94% for all three types of crop. The authors attribute its success to its inherently deeper structure and application of multiple convolutional layers at different stages. Unfortunately, all of the images were taken at the same $45^{\circ} \pm 5^{\circ}$ angle and it stands to reason that the models would perform significantly worse on images taken under different conditions.

Ramos-Giraldo et al. [RRL⁺20] detected water stress in soybean and corn crops with a pretrained model based on DenseNet-121. Low-cost cameras deployed in the field provided the training data over a 70-day period. They achieved a classification accuracy for the degree of wilting of 88%.

In a later study, the same authors [RRM⁺20] deployed their machine learning model in the field to test it for production use. They installed multiple Raspberry Pis with attached Raspberry Pi Cameras which took images in 30 min intervals. The authors had difficulties with cameras not working and power supply issues. Furthermore, running the model on the resource-constrained RPis proved difficult and they had to port their TensorFlow model to a TensorFlow Lite model. This conversion lowered their classification scores slightly since it was sometimes off by one water stress level. Nevertheless, their architecture allowed for reasonably high classification scores on corn and soybean with a low-cost setup.

Azimi, Kaur, and Gandhi [AKG20] demonstrate the efficacy of deep learning models versus classical machine learning models on chickpea plants. The authors created their own dataset in a laboratory setting for stressed and non-stressed plants. They acquired 8000 images at eight different angles in total. For the classical machine learning models, they extracted feature vectors using scale-invariant feature transform (SIFT) and histogram of oriented gradients (HOG). The features are fed into three classical machine learning models: support vector machine (SVM), k-nearest neighbors (KNN), and a decision tree (DT) using the classification and regression (CART) algorithm. On the deep learning side, they used their own CNN architecture and the pre-trained ResNet-18 model. The accuracy scores for the classical models was in the range of 60 % to 73 % with the SVM outperforming the two others. The CNN achieved higher scores at 72 % to 78 % and ResNet-18 achieved the highest scores at 82 % to 86 %. The results clearly show the superiority of deep learning over classical machine learning. A downside of their approach lies in the collection of the images. The background in all images was uniformly white and the plants were prominently placed in the center. It should, therefore, not be assumed

that the same classification scores can be achieved on plants in the field with messy and noisy backgrounds as well as illumination changes and so forth.

A significant problem in the detection of water stress is posed by the evolution of indicators across time. Since physiological features such as leaf wilting progress as time passes, the additional time domain has to be taken into account. To make use of these spatiotemporal patterns, Azimi, Wadhawan, and Gandhi [AWG21] propose the application of a CNN-long short-term memory (CNN-LSTM) architecture. The model was trained on chickpea plants and achieves a robust classification accuracy of >97%.

All of the previously mentioned studies solely focus on either one specific type of plant or on a small number of them. Furthermore, the researchers construct their datasets in homogeneous environments which often do not mimic real-world conditions. Finally, there exist no studies on common household or garden plants. This fact may be attributed to the propensity for funding to come from the agricultural sector. It is thus desirable to explore how plants other than crops show water stress and if there is additional information to be gained from them.

Prototype Development

- 1. Expand on the requirements of the prototype from what is stated in the motivation and problem statement. (Two-stage approach, small device, camera attached, outputs via REST API)
- 2. Describe the architecture of the prototype (two-stage approach and how it is implemented with an object detector and classifier). How the individual stages are connected (object detector generates cutouts which are passed to classifier). Periodic image capture and inference on the Jetson Nano.

Estimated 8 pages for this chapter.

3.1 Requirements

Briefly mention the requirements for the prototype:

- 1. Detect household potted plants and outdoor plants.
- 2. Classify plants into stressed and healthy.
- 3. Camera attached to device.
- 4. Deploy models to device and perform inference on it.

Estimated 1 page for this section.




Figure 3.1: Methodological approach for the prototype. The prototype will run in a loop which starts at the top left corner. First, the camera attached to the prototype takes images of plants. These images are passed to the models running on the prototype. The first model generates bounding boxes for all detected plants. The bounding boxes are used to cut out the individual plants and pass them to the state classifier in sequence. The classifier outputs a probability score indicating the amount of stress the plant is experiencing. After a set amount of time, the camera takes a picture again and the process continues indefinitely.

3.2 Design

Reference methods section (1.2) to explain two-stage structure of the approach. Reference the description of the processing loop on the prototype in Figure 3.1.

Estimated 1 page for this section.

3.3 Object Detection

Describe how the object detection model was trained and what the training set looks like. Include a section on hyperparameter optimization and go into detail about how the detector was optimized.

The object detection model was trained for 300 epochs on 79204 images with 284130 ground truth labels. The weights from the best-performing epoch were saved. The model's fitness for each epoch is calculated as the weighted average of mAP@0.5 and mAP@0.5:0.95:




Figure 3.2: Object detection model fitness for each epoch calculated as in equation 3.1. The vertical gray line at 133 marks the epoch with the highest fitness.

$$f_{epoch} = 0.1 \cdot \text{mAP}@0.5 + 0.9 \cdot \text{mAP}@0.5:0.95$$
 (3.1)

Figure 3.2 shows the model's fitness over the training period of 300 epochs. The gray vertical line indicates the maximum fitness of 0.61 at epoch 133. The weights of that epoch were frozen to be the final model parameters. Since the fitness metric assigns the mAP at the higher range the overwhelming weight, the mAP@0.5 starts to decrease after epoch 30, but the mAP@0.5:0.95 picks up the slack until the maximum fitness at epoch 133. This is an indication that the model achieves good performance early on and continues to gain higher confidence values until performance deteriorates due to overfitting.

Overall precision and recall per epoch are shown in figure 3.3. The values indicate that neither precision nor recall change materially during training. In fact, precision starts to decrease from the beginning, while recall experiences a barely noticeable increase. Taken together with the box and object loss from figure 3.4, we speculate that the pre-trained model already generalizes well to plant detection because one of the categories in the COCO [LMB⁺15] dataset is *potted plant*. Any further training solely impacts the confidence of detection, but does not lead to higher detection rates. This conclusion is supported by the increasing mAP@0.5:0.95 until epoch 133.

Further culprits for the flat precision and recall values may be found in bad ground truth data. The labels from the Open Images Dataset (OID) are sometimes not fine-grained




Figure 3.3: Overall precision and recall during training for each epoch. The vertical gray line at 133 marks the epoch with the highest fitness.

enough. Images which contain multiple individual—often overlapping—plants are labeled with one large bounding box instead of multiple smaller ones. The model recognizes the individual plants and returns tighter bounding boxes even if that is not what is specified in the ground truth. Therefore, it is prudent to limit the training phase to relatively few epochs in order to not penalize the more accurate detections of the model. The smaller bounding boxes make more sense considering the fact that the cutout is passed to the classifier in a later stage. Smaller bounding boxes help the classifier to only focus on one plant at a time and to not get distracted by multiple plants in potentially different stages of wilting.

The box loss decreases slightly during training which indicates that the bounding boxes become tighter around objects of interest. With increasing training time, however, the object loss increases, indicating that less and less plants are present in the predicted bounding boxes. It is likely that overfitting is a cause for the increasing object loss from epoch 40 onward. Since the best weights as measured by fitness are found at epoch 133 and the object loss accelerates from that point, epoch 133 is probably the correct cutoff before overfitting occurs.

Estimated 2 pages for this section.




Figure 3.4: Box and object loss measured against the validation set of 3091 images and 4092 ground truth labels. The class loss is omitted because there is only one class in the dataset and the loss is therefore always zero.

3.4 Classification

Describe how the classification model was trained and what the training set looks like. Include a subsection hyperparameter optimization and go into detail about how the classifier was optimized.

The dataset was split 85/15 into training and validation sets. The images in the training set were augmented with a random crop to arrive at the expected image dimensions of 224 pixels. Additionally, the training images were modified with a random horizontal flip to increase the variation in the set and to train a rotation invariant classifier. All images, regardless of their membership in the training or validation set, were normalized with the mean and standard deviation of the ImageNet [DDS⁺09] dataset, which the original Residual Neural Network (ResNet) model was pre-trained with. Training was done for 50 epochs and the best-performing model as measured by validation accuracy was selected as the final version.

Figure 3.5 shows accuracy and loss on the training and validation sets. There is a clear upwards trend until epoch 20 when validation accuracy and loss stabilize at around 0.84 and 0.3, respectively. The quick convergence and resistance to overfitting can be attributed to the model already having robust feature extraction capabilities.

Estimated 2 pages for this section.

3.5 Deployment

Describe the Jetson Nano, how the model is deployed to the device and how it reports its results (REST API).

Estimated 2 pages for this section.




Figure 3.5: Accuracy and loss during training of the classifier. The model converges quickly, but additional epochs do not cause validation loss to increase, which would indicate overfitting. The maximum validation accuracy of 0.9118 is achieved at epoch 27.

Evaluation

The following sections contain a detailed evaluation of the model in various scenarios. First, we present metrics from the training phases of the constituent models. Second, we employ methods from the field of Explainable Artificial Intelligence (XAI) such as Gradient-weighted Class Activation Mapping (Grad-CAM) to get a better understanding of the models' abstractions. Finally, we turn to the models' aggregate performance on the test set.

4.1 Methodology

Go over the evaluation methodology by explaining the test datasets, where they come from, and how they're structured. Explain how the testing phase was done and which metrics are employed to compare the models to the SOTA.

Estimated 2 pages for this section.

4.2 Results

Systematically go over the results from the testing phase(s), show the plots and metrics, and explain what they contain.

Estimated 4 pages for this section.

4.2.1 Object Detection

The following parapraph should probably go into section 3.3.

The object detection model was pre-trained on the COCO [LMB⁺15] dataset and finetuned with data from the OID [KRA⁺20] in its sixth version. Since the full OID dataset contains considerably more classes and samples than would be feasibly trainable on a small cluster of GPUs, only images from the two classes Plant and Houseplant have been downloaded. The samples from the Houseplant class are merged into the Plant class because the distinction between the two is not necessary for our model. Furthermore, the OID contains not only bounding box annotations for object detection tasks, but also instance segmentations, classification labels and more. These are not needed for our purposes and are omitted as well. In total, the dataset consists of 91479 images with a roughly 85/5/10 split for training, validation and testing, respectively.

Test Phase

Of the 91479 images around 10% were used for the test phase. These images contain a total of 12238 ground truth labels. Table 4.1 shows precision, recall and the harmonic mean of both (F1-score). The results indicate that the model errs on the side of sensitivity because recall is higher than precision. Although some detections are not labeled as plants in the dataset, if there is a labeled plant in the ground truth data, the chance is high that it will be detected. This behavior is in line with how the model's detections are handled in practice. The detections are drawn on the original image and the user is able to check the bounding boxes visually. If there are wrong detections, the user can ignore them and focus on the relevant ones instead. A higher recall will thus serve the user's needs better than a high precision.

	Precision	Recall	F1-score	Support
Plant	0.547571	0.737866	0.628633	12238.0

Table 4.1: Precision, recall and F1-score for the object detection model.

Figure 4.1 shows the Average Precision (AP) for the IOU thresholds of 0.5 and 0.95. Predicted bounding boxes with an IOU of less than 0.5 are not taken into account for the precision and recall values of table 4.1. The lower the detection threshold, the more plants are detected. Conversely, a higher detection threshold leaves potential plants undetected. The precision-recall curves confirm this behavior because the area under the curve for the threshold of 0.5 is higher than for the threshold of 0.95 (0.66 versus 0.41). These values are combined in COCO's [LMB⁺15] main evaluation metric which is the AP averaged across the IOU thresholds from 0.5 to 0.95 in 0.05 steps. This value is then averaged across all classes and called mAP. The object detection model achieves a state-of-the-art mAP of 0.5727 for the *Plant* class.

Hyperparameter Optimization

This section should be moved to the hyperparameter optimization section in the development chapter (section 3.3).

To further improve the object detection performance, we perform hyper-parameter optimization using a genetic algorithm. Evolution of the hyper-parameters starts from




Figure 4.1: Precision-recall curves for IOU thresholds of 0.5 and 0.95. The AP of a specific threshold is defined as the area under the precision-recall curve of that threshold. The mAP across IOU thresholds from 0.5 to 0.95 in 0.05 steps mAP@0.5:0.95 is 0.5727.

the initial 30 default values provided by the authors of YOLO. Of those 30 values, 26 are allowed to mutate. During each generation, there is an 80% chance that a mutation occurs with a variance of 0.04. To determine which generation should be the parent of the new mutation, all previous generations are ordered by fitness in decreasing order. At most five top generations are selected and one of them is chosen at random. Better generations have a higher chance of being selected as the selection is weighted by fitness. The parameters of that chosen generation are then mutated with the aforementioned probability and variance. Each generation is trained for three epochs and the fitness of the best epoch is recorded.

In total, we ran 87 iterations of which the 34th generation provides the best fitness of 0.6076. Due to time constraints, it was not possible to train each generation for more epochs or to run more iterations in total. We assume that the performance of the first few epochs is a reasonable proxy for model performance overall. The optimized version of the object detection model is then trained for 70 epochs using the parameters of the 34th generation.

Figure 4.2 shows the model's fitness during training for each epoch. After the highest fitness of 0.6172 at epoch 27, the performance quickly declines and shows that further training would likely not yield improved results. The model converges to its highest fitness much earlier than the non-optimized version, which indicates that the adjusted parameters provide a better starting point in general. Furthermore, the maximum fitness is 0.74% higher than in the non-optimized version.

Figure 4.3 shows precision and recall for the optimized model during training. Similarly to the non-optimized model from figure 3.3, both metrics do not change materially during training. Precision is slightly higher than in the non-optimized version and recall hovers at the same levels.

The box and object loss during training is pictured in figure 4.4. Both losses start from a lower level which suggests that the initial optimized parameters allow the model to converge quicker. The object loss exhibits a similar slope to the non-optimized model in




Figure 4.2: Object detection model fitness for each epoch calculated as in equation 3.1. The vertical gray line at 27 marks the epoch with the highest fitness of 0.6172.




Figure 4.3: Overall precision and recall during training for each epoch of the optimized model. The vertical gray line at 27 marks the epoch with the highest fitness.




Figure 4.4: Box and object loss measured against the validation set of 3091 images and 4092 ground truth labels. The class loss is omitted because there is only one class in the dataset and the loss is therefore always zero.

figure 3.4. The vertical gray line again marks epoch 27 with the highest fitness. The box loss reaches its lower limit at that point and the object loss starts to increase again after epoch 27.

	Precision	Recall	F1-score	Support
Plant	0.633358	0.702811	0.666279	12238.0

Table 4.2: Precision, recall and F1-score for the optimized object detection model.

Turning to the evaluation of the optimized model on the test dataset, table 4.2 shows precision, recall and the F1-score for the optimized model. Comparing these metrics with the non-optimized version from table 4.1, precision is significantly higher by more than 8.5%. Recall, however, is 3.5% lower. The F1-score is higher by more than 3.7% which indicates that the optimized model is better overall despite the lower recall. We feel that the lower recall value is a suitable trade off for the substantially higher precision considering that the non-optimized model's precision is quite low at 0.55.

The precision-recall curves in figure 4.5 for the optimized model show that the model draws looser bounding boxes than the optimized model. The AP for both IOU thresholds of 0.5 and 0.95 is lower indicating worse performance. It is likely that more iterations during evolution would help increase the AP values as well. Even though the precision and recall values from table 4.2 are better, the mAP@0.5:0.95 is lower by 1.8%.

4.2.2 Classification

The classifier receives cutouts from the object detection model and determines whether the image shows a stressed plant or not. To achieve this goal, we trained a ResNet [HZR⁺16] on a dataset of 452 images of healthy and 452 stressed plants. We chose the ResNet architecture due to its popularity and ease of implementation as well as its consistently high performance on various classification tasks. While its classification speed




Figure 4.5: Precision-recall curves for IOU thresholds of 0.5 and 0.95. The AP of a specific threshold is defined as the area under the precision-recall curve of that threshold. The mAP across IOU thresholds from 0.5 to 0.95 in 0.05 steps mAP@0.5:0.95 is 0.5546.

in comparison with networks optimized for mobile and edge devices (e.g. MobileNet) is significantly lower, the deeper structure and the additional parameters are necessary for the fairly complex task at hand. Furthermore, the generous time budget for object detection and classification allows for more accurate results at the expense of speed. The architecture allows for multiple different structures, depending on the amount of layers. The smallest one has 18 and the largest 152 layers with 34, 50 and 101 in-between. The larger networks have better accuracy in general, but come with trade-offs regarding training and inference time as well as required space. The 50 layer architecture (ResNet50) is adequate for our use case.

Hyperparameter Optimization

This section should be moved to the hyperparameter optimization section in the development chapter (section 3.4).

In order to improve the aforementioned accuracy values, we perform hyper-parameter optimization across a wide range of parameters. Table 4.3 lists the hyper-parameters and their possible values. Since the number of all combinations of values is 11520 and each combination is trained for 10 epochs with a training time of approximately six minutes per combination, exhausting the search space would take 48 days. Due to time limitations, we have chosen to not search exhaustively but to pick random combinations instead. Random search works surprisingly well—especially compared to grid search—in a number of domains, one of which is hyper-parameter optimization [BB12].

The random search was run for 138 iterations which equates to a 75% probability that the best solution lies within 1% of the theoretical maximum (4.1). Figure 4.6 shows three of the eight parameters and their impact on a high F1-score. Stochastic Gradient Descent (SGD) has less variation in its results than Adam [KB17] and manages to provide eight out of the ten best results. The number of epochs to train for was chosen based on the observation that almost all configurations converge well before reaching the tenth epoch. The assumption that a training run with ten epochs provides a good proxy for final

Parameter	Values
optimizer	adam, sgd
batch size	4, 8, 16, 32, 64
learning rate	0.0001, 0.0003, 0.001, 0.003, 0.01, 0.1
step size	2, 3, 5, 7
gamma	0.1, 0.5
beta one	0.9, 0.99
beta two	0.5, 0.9, 0.99, 0.999
eps	0.00000001,0.1,1

Table 4.3: Hyper-parameters and their possible values during optimization.

Optimizer	Batch Size	Learning Rate	Step Size
SGD	64	0.01	5

Table 4.4: Chosen hyper-parameters for the final, improved model. The difference to the parameters listed in Table 4.3 comes as a result of choosing SGD over Adam. The missing four parameters are only required for Adam and not SGD.

performance is supported by the quick convergence of validation accuracy and loss in figure 3.5.

$$1 - (1 - 0.01)^{138} \approx 0.75 \tag{4.1}$$

Table 4.4 lists the final hyper-parameters which were chosen to train the improved model. In order to confirm that the model does not suffer from overfitting or is a product of chance due to a coincidentally advantageous train/test split, we perform stratified 10-fold cross validation on the dataset. Each fold contains 90% training and 10% test data and was trained for 25 epochs. Figure 4.7 shows the performance of the epoch with the highest F1-score of each fold as measured against the test split. The mean ROC curve provides a robust metric for a classifier's performance because it averages out the variability of the evaluation. Each fold manages to achieve at least an AUC of 0.94, while the best fold reaches 0.98. The mean ROC has an AUC of 0.96 with a standard deviation of 0.02. These results indicate that the model is accurately predicting the correct class and is robust against variations in the training set.

The classifier shows good performance so far, but care has to be taken to not overfit the model to the training set. Comparing the F1-score during training with the F1-score during testing gives insight into when the model tries to increase its performance during training at the expense of generalizability. Figure 4.8 shows the F1-scores of each epoch and fold. The classifier converges quickly to 1 for the training set at which point it experiences a slight drop in generalizability. Training the model for at most five epochs is




Figure 4.6: This figure shows three of the eight hyper-parameters and their performance measured by the F1-score during 138 trials. Differently colored markers show the batch size with darker colors representing a larger batch size. The type of marker (circle or cross) shows which optimizer was used. The x-axis shows the learning rate on a logarithmic scale. In general, a learning rate between 0.003 and 0.01 results in more robust and better F1-scores. Larger batch sizes more often lead to better performance as well. As for the type of optimizer, SGD produced the best iteration with an F1-score of 0.9783. Adam tends to require more customization of its parameters than SGD to achieve good results.

sufficient because there are generally no improvements afterwards. The best-performing epoch for each fold is between the second and fourth epoch which is just before the model achieves an F1-score of 1 on the training set.

Class Activation Maps

Neural networks are notorious for their black-box behavior, where it is possible to observe the inputs and the corresponding outputs, but the stage in-between stays hidden from view. Models are continuously developed and deployed to aid in human decision-making and sometimes supplant it. It is, therefore, crucial to obtain some amount of interpretability of what the model does *inside* to be able to explain why a decision was made in a certain way. The research field of XAI gained significance during the last few years because of the development of new methods to peek inside these black boxes.

One such method, Class Activation Mapping (CAM) [ZKL⁺15], is a popular tool to produce visual explanations for decisions made by Convolutional Neural Networks (CNNs).




Figure 4.7: This plot shows the ROC curve for the epoch with the highest F1-score of each fold as well as the AUC. To get a less variable performance metric of the classifier, the mean ROC curve is shown as a thick line and the variability is shown in gray. The overall mean AUC is 0.96 with a standard deviation of 0.02. The best-performing fold reaches an AUC of 0.99 and the worst an AUC of 0.94. The black dashed line indicates the performance of a classifier which picks classes at random (AUC = 0.5). The shapes of the ROC curves show that the classifier performs well and is robust against variations in the training set.




Figure 4.8: These plots show the F1-score during training as well as testing for each of the folds. The classifier converges to 1 by the third epoch during the training phase, which might indicate overfitting. However, the performance during testing increases until epoch three in most cases and then stabilizes at approximately 2-3% lower than the best epoch. We believe that the third, or in some cases fourth, epoch is detrimental to performance and results in overfitting, because the model achieves an F1-score of 1 for the training set, but that gain does not transfer to the test set. Early stopping during training alleviates this problem.

Convolutional layers essentially function as object detectors as long as no fully-connected layers perform the classification. This ability to localize regions of interest, which play a significant role in the type of class the model predicts, can be retained until the last layer and used to generate activation maps for the predictions.

A more recent approach to generating a CAM via gradients is proposed by Selvaraju et al. [SCD⁺20]. Their Grad-CAM approach works by computing the gradient of the feature maps of the last convolutional layer with respect to the specified class. The last layer is chosen because the authors find that "[...] Grad-CAM maps become progressively worse as we move to earlier convolutional layers as they have smaller receptive fields and only focus on less semantic local features." [SCD⁺20, p.5]

Turning to our classifier, figure 4.9 shows the CAMs for healthy and stressed. While the regions of interest for the healthy class lie on the healthy plant, the stressed plant is barely considered and mostly rendered as background information (blue). Conversely, when asked to explain the inputs to the stressed classification, the regions of interest predominantly stay on the thirsty as opposed to the healthy plant. In fact, the large hanging leaves play a significant role in determining the class the image belongs to. This is an additional data point confirming that the model focuses on the semantically meaningful parts of the image during classification.

4.2.3 Aggregate Model

In this section we turn to the evaluation of the aggregate model. We have confirmed the performance of the constituent models: the object detection and the classification model. It remains to evaluate the complete pipeline from gathering detections of potential plants in an image and forwarding them to the classifier to obtaining the results as either healthy or stressed with their associated confidence scores.

The test set contains 640 images which were obtained from a google search using the terms thirsty plant, wilted plant and stressed plant. Images which clearly show one or multiple plants with some amount of visible stress were added to the dataset. Care was taken to include plants with various degrees of stress and in various locations and lighting conditions. The search not only provided images of stressed plants, but also of healthy plants due to articles, which describe how to care for plants, having a banner image of healthy plants. The dataset is biased towards potted plants which are commonly put on display in western households. Furthermore, many plants, such as succulents, are sought after for home environments because of their ease of maintenance. Due to their inclusion in the dataset and how they exhibit water stress, the test set nevertheless contains a wide variety of scenarios.

After collecting the images, the aggregate model was run on them to obtain initial bounding boxes and classifications for ground truth labeling. Letting the model do the work beforehand and then correcting the labels allowed to include more images in the test set because they could be labeled more easily. Additionally, going over the detections and classifications provided a comprehensive view on how the models work and what




Figure 4.9: The top left image shows the original image of the same plant in a stressed (left) and healthy (right) state. In the top right image, the CAM for the class *healthy* is laid over the original image. The classifier draws its conclusion mainly from the healthy plant, which is indicated by the red hot spots around the tips of the plant. The bottom right image shows the CAM for the *stressed* class. The classifier focuses on the hanging leaves of the thirsty plant. The image was classified as *stressed* with a confidence of 70%.

	precision	recall	f1-score	support
Healthy	0.665	0.554	0.604	766
Stressed	0.639	0.502	0.562	494
micro avg	0.655	0.533	0.588	1260
macro avg	0.652	0.528	0.583	1260
weighted avg	0.655	0.533	0.588	1260

Table 4.5: Precision, recall and F1-score for the aggregate model.

their weaknesses and strengths are. After the labels have been corrected, the ground truth of the test set contains 766 bounding boxes of healthy plants and 494 of stressed plants.

4.2.4 Non-optimized Model

Table 4.5 shows precision, recall and the F1-score for both classes *Healthy* and *Stressed*. Precision is higher than recall for both classes and the F1-score is at 0.59. Unfortunately,




Figure 4.10: Precision-recall curves for IOU thresholds of 0.5 and 0.95. The AP of a specific threshold is defined as the area under the precision-recall curve of that threshold. The mAP across IOU thresholds from 0.5 to 0.95 in 0.05 steps mAP@0.5:0.95 is 0.3581.

	precision	recall	f1-score	support
Healthy	0.711	0.555	0.623	766
Stressed	0.570	0.623	0.596	494
micro avg	0.644	0.582	0.611	1260
macro avg	0.641	0.589	0.609	1260
weighted avg	0.656	0.582	0.612	1260

Table 4.6: Precision, recall and F1-score for the optimized aggregate model.

these values do not take the accuracy of bounding boxes into account and thus have only limited expressive power.

Figure 4.10 shows the precision and recall curves for both classes at different IOU thresholds. The left plot shows the AP for each class at the threshold of 0.5 and the right one at 0.95. The mAP is 0.3581 and calculated across all classes as the median of the IOU thresholds from 0.5 to 0.95 in 0.05 steps. The cliffs at around 0.6 (left) and 0.3 (right) happen at a detection threshold of 0.5. The classifier's last layer is a softmax layer which necessarily transforms the input into a probability of showing either a healthy or stressed plant. If the probability of an image showing a healthy plant is below 0.5, it is no longer classified as healthy but as stressed. The threshold for discriminating the two classes lies at the 0.5 value and is therefore the cutoff for either class.

4.2.5 Optimized Model

So far the metrics shown in table 4.5 are obtained with the non-optimized versions of both the object detection and classification model. Hyper-parameter optimization of the classifier led to significant model improvements, while the object detector has improved precision but lower recall and slightly lower mAP values. To evaluate the final aggregate model which consists of the individual optimized models, we run the same test described in section 4.2.3.




Figure 4.11: Precision-recall curves for IOU thresholds of 0.5 and 0.95. The AP of a specific threshold is defined as the area under the precision-recall curve of that threshold. The mAP across IOU thresholds from 0.5 to 0.95 in 0.05 steps mAP@0.5:0.95 is 0.3838.

Table 4.6 shows precision, recall and F1-score for the optimized model on the same test dataset of 640 images. All of the metrics are better for the optimized model. In particular, precision for the healthy class could be improved significantly while recall remains at the same level. This results in a better F1-score for the healthy class. Precision for the stressed class is lower with the optimized model, but recall is significantly higher (0.502 vs. 0.623). The higher recall results in a 3% gain for the F1-score in the stressed class. Overall, precision is the same but recall has improved significantly, which also results in a noticeable improvement for the average F1-score across both classes.

Figure 4.11 confirms the performance increase of the optimized model established in table 4.6. The mAP@0.5 is higher for both classes, indicating that the model better detects plants in general. The mAP@0.95 is slightly lower for the healthy class, which means that the confidence for the healthy class is slightly lower compared to the non-optimized model. The result is that more plants are correctly detected and classified overall, but the confidence scores tend to be lower with the optimized model. The mAP@0.5:0.95 could be improved by about 0.025.

4.3 Discussion

Pull out discussion parts from current results chapter (4.2) and add a section about achievement of the aim of the work discussed in motivation and problem statement section (1.2).

Estimated 2 pages for this chapter.

Conclusion

Conclude the thesis with a short recap of the results and the discussion. Establish whether the research questions from section 1.2 can be answered successfully.

Estimated 2 pages for this chapter.

5.1 Future Work

Suggest further research directions regarding the approach. Give an outlook on further possibilities in this research field with respect to object detection and plant classification.

Estimated 1 page for this section

List of Figures

3.1	Methodological approach for the prototype. The prototype will run in a loop	
	which starts at the top left corner. First, the camera attached to the prototype	
	takes images of plants. These images are passed to the models running on	
	the prototype. The first model generates bounding boxes for all detected	
	plants. The bounding boxes are used to cut out the individual plants and pass	
	them to the state classifier in sequence. The classifier outputs a probability	
	score indicating the amount of stress the plant is experiencing. After a set	
	amount of time, the camera takes a picture again and the process continues	
	indefinitely.	12
3.2	Object detection fitness per epoch	13
3.3	Object detection precision and recall during training	14
3.4	Object detection box and object loss	15
3.5	Classifier accuracy and loss during training	16
4.1	Object detection AP@0.5 and AP@0.95	19
4.2	Optimized object detection fitness per epoch	20
4.3	Hyper-parameter optimized object detection precision and recall during train-	
	ing	20
4.4	Hyper-parameter optimized object detection box and object loss	21
4.5	Hyper-parameter optimized object detection AP@0.5 and AP@0.95	22
4.6	Classifier hyper-parameter optimization results	24
4.7	Mean ROC and variability of hyper-parameter-optimized model	25
4.8	F1-score of stratified 10-fold cross validation	26
4.9	Classifier CAMs	28
4.10	Aggregate model AP@0.5 and AP@0.95	29
4.11	Optimized aggregate model AP@0.5 and AP@0.95	30

List of Tables

4.1	Precision, recall and F1-score for the object detection model	18
4.2	Precision, recall and F1-score for the optimized object detection model	21
4.3	Hyper-parameters and their possible values during optimization	23
4.4	Hyper-parameters for the optimized classifier	23
4.5	Precision, recall and F1-score for the aggregate model	28
4.6	Precision, recall and F1-score for the optimized aggregate model	29

List of Algorithms

Acronyms

 ${\bf AP}\,$ Average Precision. 4, 5, 8

CAM Class Activation Mapping. 6, 9

 ${f CNN}$ Convolutional Neural Network. 6

 ${\bf Grad\text{-}CAM}$ Gradient-weighted Class Activation Mapping. 1, 6

IOU Intersection over Union. 4, 5, 8

mAP mean Average Precision. 4, 5, 8

 $\mathbf{OID}\$ Open Images Dataset. 1, 2

ResNet Residual Neural Network. 4, 5

XAI Explainable Artificial Intelligence. 1, 6

Bibliography

- [AH22] Omar El Ariss and Kaoning Hu. ResNet-based Parkinson's Disease Classification. *IEEE Transactions on Artificial Intelligence*:1–11, 2022. DOI: 10.1109/TAI.2022.3193651.
- [AKG20] Shiva Azimi, Taranjit Kaur, and Tapan K Gandhi. Water Stress Identification in Chickpea Plant Shoot Images Using Deep Learning. In 2020 IEEE 17th India Council International Conference (INDICON). 2020 IEEE 17th India Council International Conference (INDICON), pages 1–7, December 2020. DOI: 10.1109/INDICON49873.2020.9342388.
- [ALL⁺19] Jiangyong An, Wanyi Li, Maosong Li, Sanrong Cui, and Huanran Yue. Identification and Classification of Maize Drought Stress Using Deep Convolutional Neural Network. *Symmetry*, 11(2):256, February 2019. DOI: 10.3390/sym11020256.
- [Awa19] Mohamad M. Awad. Toward Precision in Crop Yield Estimation Using Remote Sensing and Optimization Techniques. *Agriculture*, 9(3):54, March 2019. DOI: 10.3390/agriculture9030054.
- [AWG21] Shiva Azimi, Rohan Wadhawan, and Tapan K. Gandhi. Intelligent Monitoring of Stress Induced by Water Deficiency in Plants Using Deep Learning. *IEEE Transactions on Instrumentation and Measurement*, 70:1–13, 2021. DOI: 10.1109/TIM.2021.3111994.
- [BB12] James Bergstra and Yoshua Bengio. Random Search for Hyper-Parameter Optimization. *The Journal of Machine Learning Research*, 13:281–305, null, February 1, 2012.
- [BMR⁺20] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language Models Are Few-Shot Learners. July 22, 2020. DOI: 10.48550/arXiv.2005.14165.

- [BTD⁺21] Lefteris Benos, Aristotelis C. Tagarakis, Georgios Dolias, Remigio Berruto, Dimitrios Kateris, and Dionysis Bochtis. Machine Learning in Agriculture: A Comprehensive Updated Review. Sensors, 21(11):3758, January 2021. DOI: 10.3390/s21113758.
- [BWL20] Alexey Bochkovskiy, Chien-Yao Wang, and Hong-Yuan Mark Liao. YOLOv4: Optimal Speed and Accuracy of Object Detection. April 22, 2020. DOI: 10.48550/arXiv.2004.10934.
- [CCR⁺21] Narendra Singh Chandel, Subir Kumar Chakraborty, Yogesh Anand Rajwade, Kumkum Dubey, Mukesh K. Tiwari, and Dilip Jat. Identifying Crop Water Stress Using Deep Learning Models. *Neural Computing and Applications*, 33(10):5353–5367, May 1, 2021. DOI: 10.1007/s00521-020-05325-4.
- [DDS+09] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In 2009 IEEE Conference on Computer Vision and Pattern Recognition. 2009 IEEE Conference on Computer Vision and Pattern Recognition, pages 248–255, June 2009. DOI: 10.1109/CVPR.2009.5206848.
- [HZR⁺16] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. In 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR). 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pages 770–778, June 2016. DOI: 10.1109/CVPR.2016.90.
- [JCS+22] Glenn Jocher, Ayush Chaurasia, Alex Stoken, Jirka Borovec, NanoCode012, Yonghye Kwon, Kalen Michael, TaoXie, Jiacong Fang, imyhxy, Lorna, Zeng Yifu, Colin Wong, Abhiram V, Diego Montes, Zhiqiang Wang, Cristi Fati, Jebastin Nadar, Laughing, UnglvKitDe, Victor Sonck, tkianai, yxNONG, Piotr Skalski, Adam Hogan, Dhruv Nair, Max Strobel, and Mrinal Jain. Ultralytics/Yolov5: V7.0 YOLOv5 SOTA Realtime Instance Segmentation, Zenodo, November 22, 2022. DOI: 10.5281/zenodo.7347926.
- [KB17] Diederik P. Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. January 29, 2017. DOI: 10.48550/arXiv.1412.6980.
- [KRA+20] Alina Kuznetsova, Hassan Rom, Neil Alldrin, Jasper Uijlings, Ivan Krasin, Jordi Pont-Tuset, Shahab Kamali, Stefan Popov, Matteo Malloci, Alexander Kolesnikov, Tom Duerig, and Vittorio Ferrari. The Open Images Dataset V4: Unified Image Classification, Object Detection, and Visual Relationship Detection at Scale. International Journal of Computer Vision, 128(7):1956–1981, July 2020. DOI: 10.1007/s11263-020-01316-z.
- [LIM⁺22] Patricia López-García, Diego Intrigliolo, Miguel A. Moreno, Alejandro Martínez-Moreno, José Fernando Ortega, Eva Pilar Pérez-Álvarez, and Rocío Ballesteros. Machine Learning-Based Processing of Multispectral and RGB UAV Imagery for the Multitemporal Monitoring of Vineyard

- Water Status. *Agronomy*, 12(9):2122, September 2022. DOI: 10.3390/agronomy12092122.
- [LMB+15] Tsung-Yi Lin, Michael Maire, Serge Belongie, Lubomir Bourdev, Ross Girshick, James Hays, Pietro Perona, Deva Ramanan, C. Lawrence Zitnick, and Piotr Dollár. Microsoft COCO: Common Objects in Context. February 20, 2015. DOI: 10.48550/arXiv.1405.0312.
- [MWL22] Patrick McEnroe, Shen Wang, and Madhusanka Liyanage. A Survey on the Convergence of Edge Computing and AI for UAVs: Opportunities and Challenges. *IEEE Internet of Things Journal*, 9(17):15435–15459, September 2022. DOI: 10.1109/JIOT.2022.3176400.
- [RRL+20] Paula Ramos-Giraldo, Chris Reberg-Horton, Anna M. Locke, Steven Mirsky, and Edgar Lobaton. Drought Stress Detection Using Low-Cost Computer Vision Systems and Machine Learning Techniques. IT Professional, 22(3):27–29, May 2020. DOI: 10.1109/MITP.2020.2986103.
- [RRM⁺20] Paula Ramos-Giraldo, S. Chris Reberg-Horton, Steven Mirsky, Edgar Lobaton, Anna M. Locke, Esleyther Henriquez, Ane Zuniga, and Artem Minin. Low-Cost Smart Camera System for Water Stress Detection in Crops. In 2020 IEEE SENSORS. 2020 IEEE SENSORS, pages 1–4, October 2020. DOI: 10.1109/SENSORS47125.2020.9278744.
- [SCD⁺20] Ramprasaath R. Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-CAM: Visual Explanations from Deep Networks via Gradient-based Localization. *International Journal of Computer Vision*, 128(2):336–359, February 2020. DOI: 10.1007/s11263-019-01228-7.
- [SCL⁺20] Jinya Su, Matthew Coombes, Cunjia Liu, Yongchao Zhu, Xingyang Song, Shibo Fang, Lei Guo, and Wen-Hua Chen. Machine Learning-Based Crop Drought Mapping System by UAV Remote Sensing RGB Imagery. *Unmanned Systems*, 08(01):71–83, January 2020. DOI: 10.1142/S2301385020500053.
- [WBL22] Chien-Yao Wang, Alexey Bochkovskiy, and Hong-Yuan Mark Liao. YOLOv7: Trainable Bag-of-Freebies Sets New State-of-the-Art for Real-Time Object Detectors. July 6, 2022. DOI: 10.48550/arXiv.2207.02696.
- [ZHT22] Yiwei Zhong, Baojin Huang, and Chaowei Tang. Classification of Cassava Leaf Disease Based on a Non-Balanced Dataset Using Transformer-Embedded ResNet. *Agriculture*, 12(9):1360, September 2022. DOI: 10.3390/agriculture12091360.
- [ZKL+15] Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning Deep Features for Discriminative Localization. December 13, 2015. DOI: 10.48550/arXiv.1512.04150.

[ZWJ⁺17] Shuo Zhuang, Ping Wang, Boran Jiang, Maosong Li, and Zhihong Gong. Early Detection of Water Stress in Maize Based on Digital Images. *Computers and Electronics in Agriculture*, 140:461–468, August 1, 2017. DOI: 10.1016/j.compag.2017.06.022.