University of Bergen
Department of Informatics

Application of Dynamic Time Warping to Spatially Ordered Weather Data Series Clustering

Author: Eirik Pedersen
Supervisor: Nello Blaser



UNIVERSITETET I BERGEN
Fakultet for naturvitenskap og teknologi

November, 2026

Abstract

Lorem ipsum dolor sit amet, his veri singulis necessitatibus ad. Nec insolens periculis ex. Te pro purto eros error, nec alia graeci placerat cu. Hinc volutpat similique no qui, ad labitur mentitum democritum sea. Sale inimicus te eum.

No eros nemore impedit his, per at salutandi eloquentiam, ea semper euismod meliore sea. Mutat scaevola cotidieque cu mel. Eum an convenire tractatos, ei duo nulla molestie, quis hendrerit et vix. In aliquam intellegam philosophia sea. At quo bonorum adipisci. Eros labitur deleniti ius in, sonet congue ius at, pro suas meis habeo no.

Acknowledgements

Est suavitate gubergren referrentur an, ex mea dolor eloquentiam, novum ludus suscipit in nec. Ea mea essent prompta constituam, has ut novum prodesset vulputate. Ad noster electram pri, nec sint accusamus dissentias at. Est ad laoreet fierent invidunt, ut per assueverit conclusionemque. An electram efficiendi mea.

`Your name`

Tuesday 3rd November, 2026

Contents

1 Introduction **1**

1.0.1 Listings 1

1.0.2 Figures 1

1.0.3 Tables 2

1.0.4 Git 2

2 Background **3**

2.1 Related Work 3

2.2 Clustering 4

Glossary **5**

List of Acronyms and Abbreviations **6**

Bibliography **7**

A Generated code from Protocol buffers **9**

B Statement on the use of AI tool **10**

List of Figures

1.1 Caption for flowchart 2

List of Tables

1.1 Caption of table 2

Listings

1.1 Short caption 1
1.2 Hello world in Golang 1
A.1 Source code of something 9

Chapter 1

Introduction

1.0.1 Listings

You can do listings, like in Listing 1.1

Listing 1.1: Look at this cool listing. Find the rest in Appendix A.1

```
1 $ java -jar myAwesomeCode.jar
```

You can also do language highlighting for instance with Golang: And in line 6 of Listing 1.2 you can see that we can ref to lines in listings.

Listing 1.2: Hello world in Golang

```
1 package main
2
3 import "fmt"
4
5 func main() {
6     fmt.Println("hello world")
7 }
```

1.0.2 Figures

Example of a centred figure




Figure 1.1: Caption for flowchart

Credit: Acme company makes everything `https://acme.com/`

1.0.3 Tables

We can also do tables. Protip: use `https://www.tablesgenerator.com/` for generating tables.

Table 1.1: Caption of table

Title1	Title2	Title3
data1	data2	data3

1.0.4 Git

Git is fun, use it!

Chapter 2

Background

2.1 Related Work

Several studies have investigated applying Dynamic Time Warping (DTW) on spatial domains and weather data separately , and other studies have investigated the decomposition of weather forecast error into spatial and temporal components . The intersection between these topics, however, is largely unexplored.

remove when explained earlier

add citations

add citations

Dynamic Time Warping applied to spatial orderings has been used with proven results in recent litterature on automatic correlation between well-logs for geological analysis[7]. Nilo et al. use the DTW algorithm to correlate features in wells where measurements are ordered by depth, yielding promising results as an aid in research though still requiring some supervision in practical deployments [7]. Le Coz et al. use DTW together with spatial image warping to correct estimates of total rainfall during events such as convective rainstorms in sub-Saharan Africa. By warping satellite-based estimates to fit measurements from local weather station networks, they note significant improvements over pure satellite-based estimates [4]. Other notable applications include using DTW to compare cloud-top temperature and other satellite-based estimation technique time-series in precipitation estimation. [5, 6]

Decomposing forecast errors into spatial and temporal components is generally first accredited to Hoffman et al. in their 1995 paper "Distortion Representation of Forecast Errors" [2, 3]

2.2 Clustering

Clustering is the process of partitioning a set of data objects into groups referred to as clusters, that are similar to each other or dissimilar to objects in other clusters [1]. This is an unsupervised machine learning technique used to explore the dataset, for preprocessing or as a subroutine for further study [8]. The two main advantages of clustering is that since it is unsupervised it can easily be applied to real-world datasets that don't need to be curated or processed first, and that it might let us discover groupings that humans would not intuitively think of.

Glossary

Git Git is a Version Control System (VCS) for tracking changes in computer files and coordinating work on those files among multiple people.

List of Acronyms and Abbreviations

VCS Version Control System.

Bibliography

[1] Jiawei Han, Micheline Kamber, and Jian Pei. 10 - cluster analysis: Basic concepts and methods. In *Data Mining: Concepts and Techniques (Third Edition)*, The Morgan Kaufmann Series in Data Management Systems, pages 443–495. Morgan Kaufmann, Boston, third edition edition, 2012. ISBN 978-0-12-381479-1. doi: https://doi.org/10.1016/B978-0-12-381479-1.00010-1.
URL: https://www.sciencedirect.com/science/article/pii/B9780123814791000101.

[2] Ross N. Hoffman, Zheng Liu, Jean-Francois Louis, and Christopher Grassoti. Distortion representation of forecast errors. *Monthly Weather Review*, 123(9):2758 – 2770, 1995. doi: 10.1175/1520-0493(1995)123⟨2758:DROFE⟩2.0.CO;2.
URL: https://journals.ametsoc.org/view/journals/mwre/123/9/1520-0493_1995_123_2758_drofe_2_0_co_2.xml.

[3] Isidora Jankov, Scott Gregory, Sai Ravela, Zoltan Toth, and Malaquias Peña. Partition of forecast error into positional and structural components. *Advances in Atmospheric Sciences*, 38:1012–1019, 05 2021. doi: 10.1007/s00376-021-0251-7.

[4] Camille Le Coz, Arnold Heemink, Martin Verlaan, and Nick van de Giesen. Spatial and time warping for gauge adjustment of rainfall estimates. *Atmosphere*, 12(11), 2021. ISSN 2073-4433. doi: 10.3390/atmos12111510.
URL: https://www.mdpi.com/2073-4433/12/11/1510.

[5] Sha Lu, Marie-claire ten Veldhuis, Nick van de Giesen, Arnold Heemink, and Martin Verlaan. Precipitation regime classification based on cloud-top temperature time series for spatially-varied parameterization of precipitation models. *Remote Sensing*, 12(2), 2020. ISSN 2072-4292. doi: 10.3390/rs12020289.
URL: https://www.mdpi.com/2072-4292/12/2/289.

[6] V.M. Mantas, Z. Liu, C. Caro, and A.J.S.C. Pereira. Validation of trmm multi-satellite precipitation analysis (tmpa) products in the peruvian andes. *Atmospheric Research*, 163:132–145, 2015. ISSN 0169-8095. doi:

https://doi.org/10.1016/j.atmosres.2014.11.012.
URL: https://www.sciencedirect.com/science/article/pii/S016980951400413X. 6th Workshop of the International Precipitation Working Group.

[7] Matheus Nilo, Alexsandro Cerqueira, Vinicius Carneiro, and Michael Holz. Semi-automatic well-log correlation using the dynamic time warping algorithm. 10 2023.

[8] John Paparrizos and Luis Gravano. k-shape: Efficient and accurate clustering of time series. *ACM SIGMOD Record*, 45:69–76, 06 2016. doi: 10.1145/2949741.2949758.

A

Generated code from Protocol buffers

Listing A.1: Source code of something

```
1 System.out.println("Hello Mars");
```

Appendix B

Statement on the use of AI tool

- Transparency Declare if and how and which AI tools were used, summarized in the Appendix, and if convenient also atappropriate points in the general text.

I am aware that I am responsible for all content of this master's thesis.