Q. N	lo. 1		
Whic	ch of the following protocol will not require a gateway to communicate with lo		
Platf	forms?		
A:	Bluetooth Low Energy (BTLE)		
B:	ZigBee		
C:	Wi-Fi		
D:	RFID		
Q. N	lo. 2		
IETF	is an acronym for and RFC is an acronym for		
A:	Internet Engineering Task force & Request for Communication		
B:	International Engineering Technical Force & Request for Communication		
C:	Internet Engineering Task Force and Request for Comments		
D:	International Engineering Technical Force & Request for Comments		
Q. N	lo. 3		
Whic	ch communication pattern is followed by MQTT?		
A:	Peer to Peer		
B:	Publish-Subscribe		
C:	Request - Response		
D:	Push-Pull		
Q. N	lo. 4		
MQT	T protocol works on which layer of OSI Model?		
A:	Presentation		
B:	Session		
C:	Transport		
D	Application		

PG-DESD Page 1 of 14

Q.	Nc). 5
----	----	------

What are the things that have created perfect storm for building rapid IoT Solutions?

- A: Broadband Internet is become more widely available.
- B: More devices are being created with Wi-Fi capabilities sensors built into them.
- C: Technology costs are going down.
- D: All of the above.

Q. No. 6

Which of the following resources of REST is idempotent as well as safe?

- A: PUT
- B: POST
- C: DELETE
- D: GET

Q. No. 7

Which interaction model CoAP provides for application endpoints?

- A: Request/Response
- B: publish and subscribe
- C: peer to peer
- D Push and Pull.

Q. No. 8

Socket is a combination of ______.

A: IP Address + Port Number

B: MAC Address + Port Number

C: UUID + Port Number

D IP Address + UUID

PG-DESD Page 2 of 14

The minimum header size is _____ whereas maximum header size for TCP protocol is

- A: 20 bytes and 60 bytes
- B: 12 bytes and 40 bytes.
- C: 40 bytes and 20 bytes.
- D 24 bytes and 36 bytes.

Q. No. 10

What is the indicated type specified inside the socket() system call in UNIX based socket programming for UDP based client –server communication?

- A: SOCKET_DGRAM
- B: SOCK_DATAGRAM
- C: SOCK_DGRAM
- D SOCK_STREAM

Q. No. 11

Question:

How many non-overlapping channels are present in Frequency Hoping Spread Spectrum (FHSS) in 2.4 GHZ spectrum?

- A: 49.
- B: 89.
- C: 79.
- D 69.

PG-DESD Page 3 of 14

Question:

Which of the following channel combination should be selected in case Wi-Fi enabled three routers are operating in the same vicinity to avoid interference in ISM band of 2.4 GHZ?

- A. 1.5, 10
- B. **1, 6, 11**
- C. 2, 6, 11
- D. 1, 4, 9

Q. No. 13

Question:

Which of the following performs "fragmentation and recombination" in Bluetooth stack?

Answer Choices

- A. RFCOMM.
- B. L2CAP.
- C. Host Controller Interface (HCI).
- D. Attribute Protocol (ATT).

Q. No. 14

Question:

Which of the following covers the most deployments in mmWave bands?

Answer Choices

A: 24.25-29.5 GHz

B: 900 MHz to 1800 MHz

C: 700 MHz to 900 MHz

D: 6 GHz to 7 GHz

PG-DESD Page 4 of 14

\mathbf{O}	No.	1	5
w.	IWL)_		. 1

Which of the two frequency bands is used by Dual Band Wi- fi Routers?

A: Both 5 GHz Band

B: Both 2.4GHz Band

C: 2.4 GHz, 5GHz Band

D: 868 MHz, 915MHz Band

Q. No. 16

Question:

110NNNNN. NNNNNNNN. NNNNNNNNN. HHHHHHHHH Which class of IP does this belong Where: $N = network\ ID\ bits\ H = host\ ID\ bits$

A: Class A

B: Class B

C: Class C

D: Class D

Q. No. 17

Question:

6LowPAN End Nodes Connects to Internet with the help of intermediate entity known as_____?

A: Border Router

B: Access Point

C: Switch

D: Router

Q. No. 18

Question:

What is Bandwidth allocated for NBIoT?

A: 180 MHz

B: 180 KHz

C: 2.4 GHz

PG-DESD Page 5 of 14

D: 900 MHz

Q. No. 19

Question:

Which generation of cellular communication only supports circuit switching?

A: Second Generation (2G)

B: Third Generation (3G)

C: Fourth Generation (4G)

D: First Generation (1G)

Q. No. 20

Question:

Which of the following feature of CoAP is used to map request and response?

Answer Choices

A: Token Number

B: Message ID

C: Discovery

D: Observe

Difficulty Level: Difficult

Q. No. 21

Question:

Which of the following provides adaption between upper layer frame and baseband layer frame format in Bluetooth?

A: L2CAP

B: LMP

C: SDP

D: RFCOMM

PG-DESD Page 6 of 14

Question:

Which of the following is Low Power Wide Area Network (LPWAN) Solution?

A: Wi-Fi

B: Bluetooth

C: NB-IoT

D: ZigBee

Q. No. 23

Which of the following IEEE standard/technology stack is used by 6LowPAN for transmission and reception of IPV6 packets?

A: IEEE 802.11

B: IEEE 802.3

C: IEEE 802.15.1

D: IEEE 802.15.4

Q. No. 24

Question:

Which of the following virtual career sensing mechanism is used by Wi-Fi (IEEE 802.11) protocol to avoid collisions?

A: Network Allocation Vector (NAV)

B: Request to Send (RTS)

C: Clear to Send (CTS)

D: CSMA/CA

Q. No. 25

Question:

Which of the following encryption method is used by Wi-Fi WPA2 security?

Answer Choices

A: AES

B: RSA

PG-DESD Page 7 of 14

C: DSA
D: SHA
Q. No. 26
Logical Port Addressing is Associated with Which of the following layer of OSI Model?
A: Application Layer
B: Transport Layer
C: Session Layer
D: Data Link Layer
Q. No. 27
Who coined the term IoT?
A: Kevin Ashton
B: Mark Weiser
C: Sundar Pichai
D: Jerry yang
Q. No. 28
Fire and Forget mechanism for data communication in MQTT protocol is practiced in .
A: QOS - 2
B: QOS - 1
C: QOS - 3
D: QOS - 0

PG-DESD Page 8 of 14

Sample MCQS - PGDESD

Q. No. 29

Which of the following feature of MQTT protocol allows last known good value to be received by subscriber; in case subscriber got disconnected from the broker due to poor network connectivity?

A: Retain message

B: Last will and Testament

C: Quality of Service (QoS)

D: Clean Session

Q. No. 30

Which of the following resource of REST/Http1.1 is neither idempotent nor safe?

A: GET

B: PUT

C: POST

D: DELETE

Q. No. 31

Which of the following status code in REST paradigm represents success?

A: 4.X.X

B: 5.X.X

C: 2.X.X

D: 1.X.X

Q. No. 32

Question:

How to identify the acknowledgement of CoAP request using CONFIRMABLE message type?

A: Using Token ID

B: Using Message ID

C: Using Discovery Method

D: Using Observe Method

PG-DESD Page 9 of 14

Which of the following system call is used to fetch pending connection request from the queue in Unix Based Socket Programming using TCP protocol?

A: bind ()

B: listen ()

C: socket ()

D: accept ()

Q. No. 34

Question:

Which of the following technique(s) can be used to develop the concurrent server in Unix Based Socket Programming?

A: Using fork() system call

B: Using multithreading technique(s)

C: Using select () system call

D: All of the above.

Q. No. 35

What is the indicated type specified inside the socket() system call in UNIX based socket programming for TCP based client –server communication?

A: SOCKET_DGRAM

B: SOCK_DATAGRAM

C: SOCK_DGRAM

D: SOCK_STREAM

Q. No. 36

Which of the following feature of CoAP can be used to get notification from server to client whenever there is a change in the resource state?

A: Using DISCOVERY method

B: Registering GET method with OBSERVE

PG-DESD Page 10 of 14

Sample MCQS - PGDESD

- C: Using PUT resource
- D: Using POST resource

Q. No. 37

Which of the following protocol maintains single TCP connection for bi-directional full duplex communication in client-server communication model?

Answer Choices

- A. Http/1.1
- B. MQTT
- C. CoAP
- D. WebSocket

Q. No. 38

Which type of address is not used by IPV6?

A. Broadcast

- B. Multicast
- C. Anycast
- D. Unicast

Q. No. 39

Long Term Evolution (LTE) is which generation cellular technology?

Answer Choices

A: 3rd Generation (3G)

B: 2nd Generation (2G)

C: 1st Generation (1G)

D: 4th Generation (4G)

PG-DESD Page 11 of 14

Q. I	Vο	. 40
------	----	------

Which of the following IEEE 802.11 standard has highest data rates?

A: 802.11b

B: 802.11ac

C: 802.11ax

D: 802.11g

Q. No. 41

Which of the following IPV4 address is used as a loopback address for testing/hosting internal application only on the host machine?

A: 192.168.0.1

B: 127.0.0.1

C: 10.0.17.2

D: 172.17.0.1

Q. No. 42

Question:

6LowPAN is based on _____ addressing scheme?

A: IPV4

B: EPC

C: IPV6

D: UUID

Q. No. 43

Which of the following character is used as a single level wild cards in MQTT?

A: +

B: #

C: \$

D: @

PG-DESD Page 12 of 14

ZigBee protocol takes benefit of Physical and data link layer of ______standard.

A: IEEE 802.11

B: IEEE 802.15.4

C: IEEE 802.3

D: IEEE 802.16

Q. No. 45

Bluetooth Low Energy uses which of the following profile for connection and advertising?

Answer Choices

A: GATT

B: ATT

C: GAP

D: L2CAP

Q. No. 46

Question:

Max how many active devices can be part of piconet?

A: 512

B: 8

C: 16

D: 1024

Q. No. 47

Question:

Which of the following protocol is used by Bluetooth for serial communication and is emulation of RS232 serial ports over the L2CAP protocol?

A: TCS-BIN

B: OBEX

PG-DESD Page 13 of 14

C: SDP

D: RFCOMM

Q. No. 48

Question:

Which of the following link is used for voice traffic in Bluetooth?

A: Synchronous Connection Oriented (SCO)

B: Asynchronous Connection Less (ACL)

C: RFCOMM

D: Host Controller Interface (HCI)

Q. No. 49

Question:

Which of the following IEEE standard is used to add wireless access in vehicular environments (WAVE)?

A: IEEE 801.11ac

B: IEEE 802.11ax

C: IEEE 802.11 a

D: IEEE 802.11p

Q. No. 50

Which of the following wireless technology consumes less power for data communication?

A: Bluetooth

B: Bluetooth Low Energy (BTLE)

C: Wi-Fi

D: ZigBee

PG-DESD Page 14 of 14