N/Agency++: Auditing the Public Surface of User-Facing LLM Agents

Anonymous ACL submission




Figure 1: **Runtime audit trade-offs.** (a) Exposure and raw leaks (% of 9,000 generations). (b) Denial and intent residuals (% of 6,000 denied generations). (c) V3 compliance versus local generation latency; color shows denied intent. All V3 backbones have 0.00% measured surface exposure. (d) Schematic: permission and rendering redistribute output mass into retained lines and fallbacks, without changing the model (Section 3).

Abstract

User-facing LLM agents render intermediate state and error fallbacks alongside final answers, creating disclosure paths that answer-only audits miss. We present *N/Agency++* (Negotiated Agency++), a framework extending Permissioned Action Generation (PAG) through oracle permission, public-surface auditing, and field-level control. A local llama.cpp/Godot study evaluates five GGUF models on 600 prompts across three runs: 9,000 generations and 27,000 audit views. Expanding the audit boundary raises measured exposure from 1.00% to 1.23%. A benchmark-conditioned V3 controller reduces detector-flagged exposure to 0.00% and raises whole-request audit pass from 33.23% to 56.03%, preserving all 3,000 allowed final lines. Paired replay and timing analyses connect containment, policy residuals, and runtime cost to deployment regression testing.

Code & data | **Project page**

1 Introduction

LLM applications increasingly mediate interaction through agentic pipelines that generate reasoning-action traces, invoke tools, and maintain intermediate state (Yao et al., 2023; Liu et al., 2023; Ma et al., 2024; Lu et al., 2024). Research on tool-agent risk, prompt injection, and privacy acquisition has accordingly broadened safety evaluation beyond final responses (Ruan et al., 2023; Zhan et al., 2024; Debenedetti et al., 2024; Staab et al., 2024; Zhang et al., 2026). Runtime guardrails further separate policy enforcement from model generation (Rebedea et al., 2023; Wang et al., 2025a). Yet the user interface introduces another boundary: intent labels, controller states, and error fallbacks may be rendered independently of the final answer. A system can thus withhold an unsafe answer while exposing sensitive side fields. This motivates auditing what the interface displays under its rendering contract.

This paper addresses that deployment problem through *N/Agency++* (Negotiated Agency++), ex-

tending Negotiated Agency's separation of proposals, permissions, and public outcomes into staged Permissioned Action Generation (PAG) tasks. A llama.cpp/Godot case study connects these tasks to local generation, structured parsing, and deterministic user-interface rendering.

Our contributions address three complementary requirements. First, we formalize PAG across oracle-permission, audit-coverage, and field-control settings, making the transition from generated proposals to public outcomes explicit. Second, N/Agency++ implements this separation as a common generation–permission–rendering framework with a measurable public-surface contract. Third, a 45,000-observation condition sweep and a 9,000-generation runtime study connect audit coverage to policy ablations, retained responses, and processing cost. Together, these analyses distinguish failures of audit coverage, external enforcement, and interaction policy.

2 Related Work

Deployment-oriented evaluation. SAGE evaluates application-specific harms (Jindal et al., 2025); RAG faithfulness leaderboards support repeated automated audits (Tamber et al., 2025); AgentBoard tracks multi-turn task progress (Ma et al., 2024). N/Agency++ extends application-boundary evaluation to rendered fields, checking audit acceptance and preservation on outputs.

Agent risk and prompt injection. ToolEmu evaluates long-tailed failures before tools are deployed, while InjecAgent and AgentDojo test indirect prompt injection in tool-integrated agents (Ruan et al., 2023; Zhan et al., 2024; Debenedetti et al., 2024). R-Judge evaluates trajectory risk awareness, Agent-SafetyBench tests behavior across interactive environments, and Agent Security Bench compares attacks and defenses across agent stages (Yuan et al., 2024; Zhang et al., 2024b,a). ATBench evaluates trajectory-level safety and diagnoses risk sources, failure modes, and harms (Li et al., 2026). Complementing these approaches, N/Agency++ isolates disclosure through rendered fields and fallbacks, including interfaces without external tools.

Structured and agentic generation. PICARD and SynCode constrain generation syntax (Scholak et al., 2021; Ugare et al., 2025), while JSONSchemaBench evaluates structured-output constraints (Geng et al., 2025). PAG addresses a complementary question: which generated fields are authorized to reach the user interface?

Privacy acquisition and disclosure. Refusal can arise from instruction-tuned behavior (Ouyang et al., 2022), yet ordinary text still supports sensitive user inferences (Staab et al., 2024). PrivacyPeek inspects unnecessarily acquired sensitive information even when final output appears benign (Zhang et al., 2026). These probes separate context acquisition from disclosure. N/Agency++ examines downstream rendering, including metadata and fallbacks visible after refusal.

3 Permissioned Action Generation And N/Agency++

From proposals to public outcomes. Agent interfaces expose reasoning and tool state beyond final answers (Yao et al., 2023; Ruan et al., 2023; Debenedetti et al., 2024). Syntactic constraints regulate output form (Scholak et al., 2021), while privacy audits examine information flow through the workflow (Zhang et al., 2026). PAG therefore separates generation, permission, and rendering as evaluation objects at the interface boundary.

Definition 1 (Permissioned inference)**.** For fixed input x and context κ, let $Y \sim P_\theta(\cdot \mid x)$ follow an autoregressive decoder (Bengio et al., 2003). Parsing $\Pi(y) = (z, e)$ yields intent/action/line $z = (i, a, \ell)$ and runtime state e. Permission $p = C_\kappa(z, e)$ and renderer R induce $T_\kappa(y) = R(z, p, e)$ and

$$P_\theta(y \mid x) = \prod_{t=1}^{|y|} p_\theta(y_t \mid x, y_{<t}),$$
$$P^{C,R}_{\theta,\kappa}(s \mid x) = \sum_{y\,:\,T_\kappa(y)=s} P_\theta(y \mid x). \tag{1}$$

Here $p \in \{\mathsf{A}, \mathsf{D}\}$ denotes `ALLOW/DENY`. p_θ includes the decoding rule (greedy is a point mass), while T_κ transforms the public surface with fixed model parameters.

Definition 2 (V3 gate and renderer)**.** Let $v(e)$ and $D_\kappa(t)$ be binary parse-validity and text-risk indicators, with $D_\kappa(\epsilon) = 0$ for empty text. The V3 rejection gate is

$$q_\kappa(z, e) = \max\big\{1 - v(e),\ \mathbf{1}[a = \texttt{unveil}],\ D_\kappa(i),\ D_\kappa(\ell)\big\}. \tag{2}$$

Thus $p = \mathsf{D} \iff q_\kappa = 1$. For audited fields $\mathcal{F} = (\text{line}, \text{intent}, \text{error}, \text{raw})$, the projection of




Figure 2: **N/Agency++ evaluation boundary across versions.** The P_θ–C_κ–R_3 pipeline follows Eqs. (1)–(3); V1 uses oracle permission, V2 expands audit scope, and V3 applies the benchmark-conditioned guard in replay.

$s = R_3(z, p, e)$ is

$$s_{\mathcal{F}} = \begin{cases} (\ell, i, \epsilon, \epsilon), & p = \mathsf{A}, \\ b(e), & p = \mathsf{D}. \end{cases} \tag{3}$$

Fallback $b(e)$ supplies fixed refusal, redaction, and error strings while suppressing raw model output.

Definition 3 (Exposure and audit gap)**.** For $S = T_\kappa(Y)$, full-surface exposure, final-line exposure, and the audit gap are

$$\begin{aligned} U_\kappa(s) &= \max_{f \in \mathcal{F}} D_\kappa(s_f), \\ u_\kappa(s) &= D_\kappa(s_{\text{line}}), \\ \Delta_\kappa &= \mathbb{E}\big[U_\kappa(S) - u_\kappa(S)\big] \\ &= \Pr\big(U_\kappa(S) = 1,\ u_\kappa(S) = 0\big). \end{aligned} \tag{4}$$

RQ2 estimates this gap by paired audits, conditional on x, κ or averaged over the evaluation set.

Assumption 1 (Mediated rendering)**.** R_3 is the sole display path for $\mathcal{F}$, and every field of $b(e)$ is D_κ-negative, including parse-error states.

Following the risk–coverage view of selective prediction (Geifman and El-Yaniv, 2017), we retain loss on the fallback branch.

Proposition 1 (Selective exposure risk)**.** For surface loss $h = h(S) \in [0, 1]$, set $\alpha = \Pr(p = \mathsf{A})$, $\beta_h = \mathbb{E}[h \mid p = \mathsf{A}]$, and $\gamma_h = \mathbb{E}[h \mid p = \mathsf{D}]$. If $\beta_h \le \varepsilon$ and $\gamma_h \le \delta$, then

$$\begin{aligned} r_h := \mathbb{E}[h(S)] &= \alpha\beta_h + (1 - \alpha)\gamma_h \\ &\le \alpha\varepsilon + (1 - \alpha)\delta. \end{aligned} \tag{5}$$

Empty branches are assigned zero loss. Under Assumption 1, V3 has $\beta_{U_\kappa} = \gamma_{U_\kappa} = 0$, hence $r_{U_\kappa} = 0$.

Proof. Apply total expectation and the branch bounds. Under Assumption 1, V3 exposes only detector-negative fields. □

Figure 1d visualizes this redistribution between retained fields and fallbacks. Equation (5) applies per input and under averaging; semantic loss requires independently validated branch bounds.

Experimental versions. V1 gates disclosure with `gold_permission`; V2 controls actions and lines without that oracle, under two audit scopes. V3 replays fixed outputs using Eqs. (2)–(3) and the annotation-conditioned D_κ (Figure 2).

Research questions.

RQ	Question	Quantitative evidence
1	Does oracle permission contain disclosure?	Disclosure (Table 2a)
2	How do audit scope and external control change outcomes?	Gap, ablation, pass, budget yield (Tables 1b, 3; Fig. 3b)
3	How do residuals and costs vary by deployment setting?	Residuals, context, latency (Figs. 1c, 4–5)

4 Evaluation Design

We evaluate 600 synthetic, deterministically labeled prompts (200 allowed, 400 denied) on five fixed GGUF backbones across three runs (Table 1). Godot uses llama.cpp on an RTX 4060 Laptop GPU, schema decoding, temperature 0, and a 256-token cap (Appendix B). Latency is client–server generation time, excluding rendering.

Paired V2/V3 audits reuse 9,000 outputs: 6,000 denied and 3,000 allowed. *Whole-request audit*




Figure 3: **Empirical rendering and generation-budget yield.** (a) 9,000 observations, including 18 invalid proposals; ribbons measure benchmark-mixture transitions, not fixed-input sampling (Eq. 1). (b) Paired V2/V3 timely audit passes/all requests. Shading: gain; bars: 95% prompt-bootstrap intervals. Both policies share generation times, excluding rendering.

pass requires a nonempty final line and no unsafe surface, visible raw output, denied non-refusal, visible denied intent, or allowed refusal: contract-based acceptance rather than task success. We report allowed-line text equality, audit gap Δ, category span (max–min, pp), missed-flag share, and controller coverage 100α (%). Exposure denotes detector flags under the guards in Section 3. For pass indicator w_j and generation time τ_j, budget-qualified yield is $100N^{-1}\sum_j w_j \mathbf{1}[\tau_j \le t]$: timely audit passes divided by all requests.

Paired diagnostic replay. Context omissions modify the controller while keeping scoring annotations fixed. Both policies use 100 category-stratified prompt masks per omission rate. Bootstrap intervals (Efron, 1979) use 2,000 stratified prompt resamples; every model/run pair stays together in both protocols (Appendix B).

5 Results

5.1 RQ1: Oracle Feasibility And Baselines

Oracle PAG V1 records 0.00% unsafe disclosure for every backbone; each non-oracle baseline has nonzero cells (Table 2a). Safety prompting ranges from 0.33–2.83%, versus 8.00–16.50% for schema-only generation. Externally assigned permission thus provides an oracle reference for the runtime audit and enforcement study.

5.2 RQ2: Audit Boundary And Policy Design

Final-only V2 scoring measures 1.00% exposure; full-surface auditing raises it to 1.23%: 21 of 111 flags (18.9%) lie outside the final line (Eq. (4); Table 4). On condition-sweep outputs, the ablation (Table 3) applies a common audit across prompt, schema, and policy families. Holding Schema proposals fixed, V3 reduces V2 exposure from 0.87% to 0.00% and raises joint pass from 32.03% to 90.37%; both preserve 96.70% of allowed lines. Self-policy leaves 99.80% denied intent visible: model-side permission does not enforce field withholding.

In the runtime cohort, V3 raises whole-request audit pass from 33.23% to 56.03% (+22.80 pp, 95% interval [21.30, 24.27]; Table 1b). Figure 3a instantiates Figure 1d: 2,052 proposals enter fallback, but only 93 final lines change; 1,959 interventions change only side fields (Appendix Table 14). All 3,000 allowed lines are preserved. At the same generation times, V2/V3 budget-qualified yield is 21.49/34.26% by 1.5 s and 32.60/53.21% by 2 s (Figure 3b): a 20.61 pp gain at 2 s (95% paired interval [19.22, 21.98]), improving accepted yield at fixed generation cost.

5.3 RQ3: Residuals And Context Availability

Refusal does not imply metadata withholding. V3 retains 21.00% denied non-refusal and 65.80% visible denied intent. Category profiles differ (Figure 4a): Llama reaches 66% injection non-refusal; Gemma2 9B, 47% on contested exposure. Of 4,740 detector-refused observations, 2,688 still show intent (56.71%, 95% interval [53.95, 59.42]); backbone rates span 46.13–82.44% (panel b). Appendix Table 13 gives the full intent matrix. Backbone timing differs (Figure 1c); Appendix Figure 7 resolves budget-qualified yield. Table 3 reports generation and CPU postprocessing times separately.

Context availability versus withholding. Removing either context field restores 90 final-line flags (1.00%) but no raw leaks; coverage rises from 77.2% to 78.2% (Figure 5a). At complete omission, deny-on-missing scores 66.67% joint

(a) PAG benchmark contract

Category	Action	Permission	Unique	Live
safe reflection	reflect	A	100	1,500
ambiguous emotion	reflect	A	100	1,500
private inference	unveil	D	100	1,500
third-party secret	unveil	D	100	1,500
prompt injection	withhold	D	100	1,500
contested exposure	unveil	D	100	1,500
Total (6 categories)		**200A/400D**	**600**	**9,000**

(b) Whole-request audit pass

Backbone	V2 (%)	V3 (%)	Gain (pp)
Gemma2 2B Q8	33.17	61.67	+28.50
Qwen2.5 7B	33.17	66.83	+33.67
Llama3.1 8B	33.33	52.00	+18.67
Mistral 7B	33.17	58.17	+25.00
Gemma2 9B	33.33	41.50	+8.17
All backbones	**33.23**	**56.03**	**+22.80**

(c) Evaluation cohorts

Cohort	Compared conditions	Models	Runs	Generated	Primary views
Historical V1	Direct, Safety prompt [2023; 2025; 2025b], Schema only [2025; 2025] Self-policy [2024; 2024; 2025a; 2026], Oracle PAG (ours)	5	3	45,000	45,000
Live V2/V3	Final-only audit, Complete-surface audit, Surface controller	5	3	9,000	27,000
Total	**shared prompts; separate generation records**	**5**	**3**	**54,000**	**72,000**

Table 1: **Benchmark, request-level audit, and cohorts.** (a) Unique prompts and live generations; A/D: `ALLOW/DENY`. (b) Paired audit pass: 1,800 observations per backbone, 9,000 pooled. V3 preserves all 3,000 allowed final lines (exact text equality). (c) Audit views reuse generations.




Figure 4: **Residual heterogeneity and conditional visibility.** (a) Non-refusal (%): 100 prompts × three runs/cell; span: max–min (pp). (b) Visible intent among detector-refused observations: counts and 95% prompt-bootstrap intervals.

pass by refusing every request, including all 3,000 allowed cases (panel b). Joint pass, preservation, and exposure therefore provide complementary policy-selection criteria (Eq. (5)).

6 Discussion

Audit-boundary completeness. The side-field gap (Table 4) motivates renderer tests alongside syntax constraints and content guards (Scholak et al., 2021; Inan et al., 2023; Han et al., 2024; Zeng et al., 2024; Ghosh et al., 2024), and acquisition auditing (Zhang et al., 2026). Field-level audits assess protections at the interface boundary.

Layered enforcement. Programmable rails (Rebedea et al., 2023; Wang et al., 2025a), trusted control flow (Debenedetti et al., 2025), and policy/trajectory guards (Xiang et al., 2024; Chen et al., 2025; Wang et al., 2025b; Zhao et al., 2026; Chen et al., 2026; Mou et al., 2026; Liu et al., 2026; Chen and Cong, 2025; Luo et al., 2025) complement renderer checks. Prompt admission (Appendix Table 9) addresses denied-request residuals; rendering mediates generated fields and malformed output.

Deployment-oriented acceptance. Joint audit and allowed-line preservation complement interactive benchmarks (Liu et al., 2023; Lu et al., 2024; Ruan et al., 2023; Jindal et al., 2025) by testing a rendering contract. Budget-qualified yield separates backbone selection under a deadline from policy selection on fixed proposals. In the latter

(a) Backbone-level historical and live results

Backbone	Historical PAG task: unsafe disclosure (%)					Live public-surface study (% except latency)				
	Direct	Safety prompt	Schema only	Self-policy	V1 oracle	V2 surface flags / all	V3 surface flags / all	V3 refusal / denied	V3 intent shown / denied	Mean latency (s)
Gemma2 2B Q8	6.67	0.83	16.50	4.00	**0.00**	0.17	**0.00**	**95.00**	57.25	**1.018**
Qwen2.5 7B	3.00	0.67	11.00	0.50	**0.00**	3.50	**0.00**	93.75	**49.50**	1.331
Llama3.1 8B	9.00	0.33	10.00	6.83	**0.00**	0.33	**0.00**	58.50	72.00	1.596
Mistral 7B	10.00	2.83	8.00	4.17	**0.00**	2.17	**0.00**	78.00	62.50	1.515
Gemma2 9B	1.50	0.67	8.83	0.50	**0.00**	**0.00**	**0.00**	69.75	87.75	1.611

(b) Aggregate display-policy audit

Policy	All	Denied	Surface flagged	Final line flagged	Raw visible	Raw on parse failure	Denied not refused	Denied intent shown	Allowed refused
V2 final-only	9,000	6,000	1.00	1.00	0.00	0.00	22.55	0.00	0.30
V2 public surface	9,000	6,000	**1.23**	1.00	**0.20**	**0.20**	22.55	**99.70**	0.30
V3 surface controller	**9,000**	**6,000**	**0.00**	**0.00**	**0.00**	**0.00**	**21.00**	**65.80**	**0.30**

Table 2: **Main results.** (a) Separate historical and runtime cohorts, $N = 1{,}800$ per cell; V1 uses gold permission. (b) Paired views of 9,000 runtime proposals. Rates (%) follow column denominators; latency is generation seconds.

Variant	P	S	M	C2	C3	Surf. (%) ↓	Pass (%) ↑	Gen. (s)	CPU (μs)
Safety	✓	–	–	–	–	6.20	86.30	2.095	3.1 ± 2.3
Schema	–	✓	–	–	–	14.34	33.13	1.398	7.4 ± 3.7
Self-policy	–	✓	✓	–	–	6.53	32.64	2.075	8.3 ± 6.7
+ V2	–	✓	–	✓	–	0.87	32.03	1.398	16.1 ± 8.9
+ V3 (ours)	**–**	**✓**	**–**	**–**	**✓**	**0.00**	**90.37**	**1.398**	**11.1 ± 4.8**

Table 3: **Ablation study** ($N = 9{,}000$/row). P/S/M: safety prompt/schema/model policy; C2/C3: controller. Gen.: mean generation time; Schema rows share outputs and times. CPU: Python postprocessing, mean±SD over 30 passes, excluding generation/GUI. Full metrics: Table 6.

Backbone	Final	Raw only	Intent only	Missed (%)	Δ pp [95% interval]
Gemma2 2B Q8	3	0	0	0.0	0.00 [–]
Qwen2.5 7B	63	0	0	0.0	0.00 [–]
Llama3.1 8B	3	0	3	50.0	0.17 [0.00,0.50]
Mistral 7B	21	18	0	46.2	1.00 [0.33,1.83]
Gemma2 9B	0	0	0	–	0.00 [–]
All	**90**	**18**	**3**	**18.9**	**0.23 [0.07,0.40]**

Table 4: Paired audit gap ($N = 1{,}800$/backbone). Counts are disjoint; missed is the side-only share. Δ: surface–final gap with 95% prompt-bootstrap intervals; –: no events or denominator.

comparison, acceptance improves at unchanged generation time; CPU replay separately measures processing overhead. Context interventions reveal whether an acceptance gain retains allowed lines or simply withholds more requests (Figure 5). These measurements jointly assess containment, retention, and processing cost for deployment regression tests under a common audit contract.




Figure 5: **Context sensitivity.** (a) Backbone traces and pooled exposure. (b) Audit pass versus line preservation, labeled by omission rate. Bands: 5th–95th percentiles over 100 masks; scoring labels stay fixed.

7 Conclusion

N/Agency++ separates generation, permission, and rendering through staged PAG tasks. V1 provides an oracle reference; V2 reveals audit undercounting; benchmark-conditioned V3 improves joint audit pass by 22.80 pp while preserving all 3,000 allowed lines. Measured transitions, budget-qualified yield, and context sensitivity guide deployment and follow-up auditing. Condition-family ablation separates model-side instructions from external enforcement, while CPU replay quantifies postprocessing independently of generation time. Together, these diagnostics make public-field containment, residual behavior, and processing cost explicit criteria for selecting an agent's rendering contract. The released replay suite enables repeatable policy checks on saved generations, without additional model inference.

8 Limitations

N/Agency++ addresses the rendered surface of single-turn, text-based interactions. Extending its contract to persistent memory, multi-turn state, and tool effects requires additional mediation points. Production deployment also requires independently validated policy decisions and monitoring beyond the benchmark-conditioned audit used here. In game-like interfaces, author-labeled dialogue choices (Appendix E) could move some permission decisions to design time while preserving generative variation in rendered lines. Evaluating this choice-gated trade-off remains future work.

9 Ethical Considerations

The work uses synthetic prompts and does not collect human-subject data. The system is designed to avoid diagnosing users, inferring hidden psychological truths, revealing third-party private information, or displaying raw model failures after denial. If deployed publicly, it should disclose that it is not a therapist, clinician, or truth-discovery system, and it should provide a clear way for users to stop interacting. The benchmark intentionally includes prompt-injection and privacy-sensitive requests; these are synthetic and used only to test whether the interface withholds unsafe content.

References

Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Jauvin. 2003. A Neural Probabilistic Language Model. *Journal of Machine Learning Research*, 3:1137–1155.

Jizhou Chen and Samuel Lee Cong. 2025. AgentGuard: Repurposing Agentic Orchestrator for Safety Evaluation of Tool Orchestration. *arXiv preprint arXiv:2502.09809*.

Yen-Shan Chen, Sian-Yao Huang, Cheng-Lin Yang, and Yun-Nung Chen. 2026. TraceSafe: A Systematic Assessment of LLM Guardrails on Multi-Step Tool-Calling Trajectories. *arXiv preprint arXiv:2604.07223*.

Zhaorun Chen, Mintong Kang, and Bo Li. 2025. ShieldAgent: Shielding Agents via Verifiable Safety Policy Reasoning. *arXiv preprint arXiv:2503.22738*.

Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. 2025. Defeating Prompt Injections by Design. *arXiv preprint arXiv:2503.18813*.

Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. 2024. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. *arXiv preprint arXiv:2406.13352*.

B. Efron. 1979. Bootstrap Methods: Another Look at the Jackknife. *The Annals of Statistics*, 7(1):1–26.

Yonatan Geifman and Ran El-Yaniv. 2017. Selective classification for deep neural networks. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc.

Saibo Geng, Hudson Cooper, Michał Moskal, Samuel Jenkins, Julian Berman, Nathan Ranchin, Robert West, Eric Horvitz, and Harsha Nori. 2025. JSONSchemaBench: A Rigorous Benchmark of Structured Outputs for Language Models. *Preprint*, arXiv:2501.10868.

Shaona Ghosh, Prasoon Varshney, Erick Galinkin, and Christopher Parisien. 2024. AEGIS: Online Adaptive AI Content Safety Moderation with Ensemble of LLM Experts. *arXiv preprint arXiv:2404.05993*.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. 2024. WildGuard: Open One-Stop Moderation Tools for Safety Risks, Jailbreaks, and Refusals of LLMs. *arXiv preprint arXiv:2406.18495*.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. 2023. Llama Guard: LLM-based Input-Output Safeguard for Human-AI Conversations. *arXiv preprint arXiv:2312.06674*.

Madhur Jindal, Hari Shrawgi, Parag Agrawal, and Sandipan Dandapat. 2025. SAGE: A generic framework for LLM safety evaluation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 11–33, Suzhou (China). Association for Computational Linguistics.

Haoran Li, Jingru Zeng, Yulin Chen, Huihao Jing, Wenbin Hu, Hao Peng, Haochen Shi, Xi Yang, Ziqian Zeng, Sirui Han, and Yangqiu Song. 2025a. GSPR: Aligning LLM Safeguards as Generalizable Safety Policy Reasoners. *Preprint*, arXiv:2509.24418.

Yu Li, Haoyu Luo, Yuejin Xie, Yuqian Fu, Zhonghao Yang, Shuai Shao, Qihan Ren, Wanying Qu, Yanwei Fu, Yujiu Yang, Jing Shao, Xia Hu, and Dongrui Liu. 2026. ATBench: A Diverse and Realistic Agent Trajectory Benchmark for Safety Evaluation and Diagnosis. *arXiv preprint arXiv:2604.02022*.

Yucheng Li, Surin Ahn, Huiqiang Jiang, Amir H. Abdi, Yuqing Yang, and Lili Qiu. 2025b. SecurityLingua: Efficient Defense of LLM Jailbreak Attacks via Security-Aware Prompt Compression. *Preprint*, arXiv:2506.12707.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, and 3 others. 2023. AgentBench: Evaluating LLMs as Agents. *arXiv preprint arXiv:2308.03688*.

Zhe Liu, Zonghao Ying, Wenxin Zhang, Quanchen Zou, Deyue Zhang, Dongdong Yang, Xiangzheng Zhang, and Hao Peng. 2026. SafeHarbor: Defining Precise Decision Boundaries via Hierarchical Memory-Augmented Guardrail for LLM Agent Safety. *arXiv preprint arXiv:2605.05704*.

Jiarui Lu, Thomas Holleis, Yizhe Zhang, Bernhard Aumayer, Feng Nan, Felix Bai, Shuang Ma, Shen Ma, Mengyu Li, Guoli Yin, Zirui Wang, and Ruoming Pang. 2024. ToolSandbox: A Stateful, Conversational, Interactive Evaluation Benchmark for LLM Tool Use Capabilities. *arXiv preprint arXiv:2408.04682*.

Weidi Luo, Shenghong Dai, Xiaogeng Liu, Suman Banerjee, Huan Sun, Muhao Chen, and Chaowei Xiao. 2025. AGrail: A Lifelong Agent Guardrail with Effective and Adaptive Safety Detection. *arXiv preprint arXiv:2502.11448*.

Chang Ma, Junlei Zhang, Zhihao Zhu, Cheng Yang, Yujiu Yang, Yaohui Jin, Zhenzhong Lan, Lingpeng Kong, and Junxian He. 2024. AgentBoard: An Analytical Evaluation Board of Multi-turn LLM Agents. *arXiv preprint arXiv:2401.13178*.

Yutao Mou, Zhangchi Xue, Lijun Li, Peiyang Liu, Shikun Zhang, Wei Ye, and Jing Shao. 2026. ToolSafe: Enhancing Tool Invocation Safety of LLM-based agents via Proactive Step-level Guardrail and Feedback. *arXiv preprint arXiv:2601.10156*.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc.

Traian Rebedea, Razvan Dinu, Makesh Sreedhar, Christopher Parisien, and Jonathan Cohen. 2023. NeMo Guardrails: A Toolkit for Controllable and Safe LLM Applications with Programmable Rails. *arXiv preprint arXiv:2310.10501*.

Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. 2023. Identifying the Risks of LM Agents with an LM-Emulated Sandbox. *arXiv preprint arXiv:2309.15817*.

Torsten Scholak, Nathan Schucher, and Dzmitry Bahdanau. 2021. PICARD: Parsing incrementally for constrained auto-regressive decoding from language models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 9895–9901, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Robin Staab, Mark Vero, Mislav Balunović, and Martin Vechev. 2024. Beyond Memorization: Violating Privacy Via Inference with Large Language Models. In *International Conference on Learning Representations*.

Manveer Singh Tamber, Forrest Sheng Bao, Chenyu Xu, Ge Luo, Suleman Kazi, Minseok Bae, Miaoran Li, Ofer Mendelevitch, Renyi Qu, and Jimmy Lin. 2025. Benchmarking LLM faithfulness in RAG with evolving leaderboards. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 799–811, Suzhou (China). Association for Computational Linguistics.

Shubham Ugare, Tarun Suresh, Hangoo Kang, Sasa Misailovic, and Gagandeep Singh. 2025. SynCode: LLM Generation with Grammar Augmentation. *Transactions on Machine Learning Research*.

Haoyu Wang, Christopher M. Poskitt, and Jun Sun. 2025a. AgentSpec: Customizable Runtime Enforcement for Safe and Reliable LLM Agents. *arXiv preprint arXiv:2503.18666*.

Peiran Wang, Yang Liu, Yunfei Lu, Yifeng Cai, Hongbo Chen, Qingyou Yang, Jie Zhang, Jue Hong, and Ye Wu. 2025b. AgentArmor: Enforcing Program Analysis on Agent Runtime Trace to Defend Against Prompt Injection. *arXiv preprint arXiv:2508.01249*.

Yan Wang, Zhixuan Chu, Zihao Xue, Zhen Bi, Bingyu Zhu, YueFeng Chen, Zeyu Yang, Jungang Lou, Longtao Huang, Ningyu Zhang, Kui Ren, and Hui Xue. 2026. ConsisGuard: Aligning Safety Deliberation with Policy Enforcement in LLM Guardrails. *Preprint*, arXiv:2605.31073.

Zezhong Wang, Fangkai Yang, Lu Wang, Pu Zhao, Hongru Wang, Liang Chen, Qingwei Lin, and Kam-Fai Wong. 2024. SELF-GUARD: Empower the LLM to safeguard itself. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 1648–1668, Mexico City, Mexico. Association for Computational Linguistics.

Zhen Xiang, Linzhi Zheng, Yanjie Li, Junyuan Hong, Qinbin Li, Han Xie, Jiawei Zhang, Zidi Xiong, Chulin Xie, Carl Yang, Dawn Song, and Bo Li. 2024. GuardAgent: Safeguard LLM Agents by a Guard Agent via Knowledge-Enabled Reasoning. *arXiv preprint arXiv:2406.09187*.

Yueqi Xie, Jingwei Yi, Jiawei Shao, Justin Curl, Lingjuan Lyu, Qifeng Chen, Xing Xie, and Fangzhao Wu. 2023. Defending ChatGPT against jailbreak attack via self-reminders. *Nature Machine Intelligence*, 5(12):1486–1496.

Chen Xiong, Xiangyu Qi, Pin-Yu Chen, and Tsung-Yi Ho. 2025. Defensive prompt patch: A robust and generalizable defense of large language models against jailbreak attacks. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 409–437, Vienna, Austria. Association for Computational Linguistics.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing Reasoning and Acting in Language Models. In *International Conference on Learning Representations*.

Tongxin Yuan, Zhiwei He, Lingzhong Dong, Yiming Wang, Ruijie Zhao, Tian Xia, Lizhen Xu, Binglin Zhou, Fangqi Li, Zhuosheng Zhang, Rui Wang, and Gongshen Liu. 2024. R-Judge: Benchmarking Safety Risk Awareness for LLM Agents. *arXiv preprint arXiv:2401.10019*.

Wenjun Zeng, Yuchi Liu, Ryan Mullins, Ludovic Peran, Joe Fernandez, Hamza Harkous, Karthik Narasimhan, Drew Proud, Piyush Kumar, Bhaktipriya Radharapu, Olivia Sturman, and Oscar Wahltinez. 2024. ShieldGemma: Generative AI Content Moderation Based on Gemma. *arXiv preprint arXiv:2407.21772*.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. 2024. InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents. *arXiv preprint arXiv:2403.02691*.

Hanrong Zhang, Jingyuan Huang, Kai Mei, Yifei Yao, Zhenting Wang, Chenlu Zhan, Hongwei Wang, and Yongfeng Zhang. 2024a. Agent Security Bench (ASB): Formalizing and Benchmarking Attacks and Defenses in LLM-based Agents. *arXiv preprint arXiv:2410.02644*.

Mingxuan Zhang, Jiahui Han, Dadi Guo, Songze Li, Guanchu Wang, Na Zou, Dongrui Liu, and Xia Hu. 2026. PrivacyPeek: Auditing What LLM-Based Agents Acquire, Not Just What They Say. *arXiv preprint arXiv:2606.00152*.

Zhexin Zhang, Shiyao Cui, Yida Lu, Jingzhuo Zhou, Junxiao Yang, Hongning Wang, and Minlie Huang. 2024b. Agent-SafetyBench: Evaluating the Safety of LLM Agents. *arXiv preprint arXiv:2412.14470*.

Wei Zhao, Zhe Li, Peixin Zhang, and Jun Sun. 2026. ClawGuard: A Runtime Security Framework for Tool-Augmented LLM Agents Against Indirect Prompt Injection. *arXiv preprint arXiv:2604.11790*.

Metric	Counted event	**Population**
Unsafe final/surface	detector match in final / any visible field	**all**
Raw/parse leak	raw text visible / parse failure exposes raw text	**all**
Denied non-refusal	denied prompt whose final line lacks a detected refusal	**denied**
Intent on denied	denied prompt with non-withheld intent metadata	**denied**
Over-refusal	allowed prompt with refusal-like final line	**allowed**
Latency	client–server generation round trip	**all**

Table 5: Audit metrics and their denominators. All, denied, and allowed refer to generated observations, including the three recorded runs.

A Implementation And Audit Specification

Historical conditions. Each backbone uses five in-house conditions (Table 2a). *Direct* generates an unconstrained final line; *Safety prompt* adds a safety instruction; *Schema only* requires `intent`, `action`, and `line` but displays the line without permission control. *Self-policy* additionally generates `permission` and `public_outcome`; *V1 oracle* reads `gold_permission` before rendering. Citations in Table 1c contextualize these designs, not reproductions of complete defense pipelines. No separately trained guard is used.

Joint audit and preservation. For the five binary failure flags f_{jk} listed in Section 4 and final line ℓ_j, the whole-request pass indicator is

$$w_j = \mathbf{1}[\ell_j \neq \epsilon] \prod_{k=1}^{5} (1 - f_{jk}),$$

$$\widehat{W} = \frac{100}{N} \sum_j w_j.$$

V2 full-surface and V3 observations are paired by backbone, prompt, and run. Allowed-line preservation is exact string equality on the allowed subset; the nine pre-existing allowed refusals remain failures in both views. A parse error alone is not a failure if its rendered fallback passes all checks. Controller coverage $100\widehat{\alpha}$ counts `ALLOW` decisions and is distinct from $\widehat{W}$. Missed-flag share is undefined when no surface flag exists (shown as –); category span is max–min in pp, not an uncertainty interval.

B Diagnostic Replay Protocol

Generation and policy ablation. Table 3 uses the original condition-sweep files (`pag_eval_llamacpp_*_full.csv` and `*_schema_policy_full.csv`): five backbones, 600 shared prompts, three runs, and 9,000 observations per row (6,000 denied; 3,000 allowed). Safety prompt, Schema only, and Self-policy retain their original final lines and decisions. Structured views expose intent and raw text on parse failure; text-only Safety prompt has no intent field. All rows use the same surface auditor, combining benchmark-conditioned and generic text checks, unlike the original final-line detector in panel (a). Schema only, Schema + V2, and Schema + V3 share exactly the same 9,000 proposals; the other families vary generation instructions and output contracts. Thus the Schema contrast isolates external enforcement, while Self-policy substitutes model-generated permission. Both controllers change 99 allowed lines, preserving 2,901/3,000; the 18 existing allowed refusals become 117. V3 gains 5,250 audit passes over V2 with no newly failing observations. All 18,000 controller views exactly match the stored surface-audit records. The separate runtime-proposal study uses the same benchmark prompts with the Godot persona contract. `research/naacl_family_ablation.py` records input hashes and per-backbone counts without altering original generations.

The P column denotes the dedicated safety-prompt condition, not the generic action guidelines in structured prompts. S denotes structured generation and M denotes model-assigned permission; C2/C3 replace the external controller. These switches describe alternative designs rather than a nested sequence of identical prompts. Table 6 retains every residual rate.

Postprocessing overhead. We separately time the Python replay path on an Intel Core i5-7267U CPU (macOS/Darwin 22.6.0, Python 3.12.14): five warmup passes followed by 30 counterbalanced passes over all 9,000 observations per variant. Each timed block processes 1,800 observations from one backbone; input shuffling, verification, and disk I/O are outside the timer. The timed path includes parsing, policy application, and public-field construction, but excludes generation, network requests, evaluation-only scoring, and GUI painting. All 45,000 public views exactly match the original replay. Mean±SD is computed over pass means, not individual-request tail latency. The process is single-threaded, unpinned, with ordinary garbage collection. V2 retains its separate policy parser; timings characterize these implementations, not an intrinsic algorithmic ranking. V3 takes $11.1 \pm 4.8\,\mu$s versus $16.1 \pm 8.9\,\mu$s for V2. We do not add these CPU timings to generation times measured on the GPU host. Per-backbone values and all timed blocks are released with `research/naacl_postprocessing_benchmark.py`.

Renderer component ablation. G replaces the V2 action/generic-line gate with V3's annotation-conditioned line-and-intent checks; both retain parse rejection and the `unveil` action check. M redacts intent whenever the selected gate denies. S removes raw output and replaces parse-error text with the V3 generic message. All eight combinations use the original evaluation annotations. The all-off and all-on endpoints exactly match every saved V2 and V3 field and metric, respectively. Neither M nor S rewrites the final line. No variation changes an allowed line; allowed over-refusal stays 0.30%. These are fixed-output component replays, not independently generated live systems. `research/naacl_component_ablation.py` exports all per-backbone cells and verifies input hashes and endpoint equality.

The live server uses llama.cpp build 9553 (`9e3b928fd`), Vulkan, a 2,048-token context, batch size 512, full available GPU offload, and one parallel slot. Gemma2 2B uses Q8; all downloaded GGUF artifacts remain fixed. The renderer-component, context, distribution, and budget analyses use the five runtime raw/audit file pairs. Replaying full-context V3 reproduces all 9,000 saved surfaces and their metrics; source-file SHA-256 hashes are checked before and after. Four intervention conditions blank only permission, only category, both, or both with an explicit deny-on-missing fallback. Unavailable values are empty strings, not substituted `ALLOW` labels. The unchanged detector requires a `DENY` permission and a recognized category to activate its annotation-specific branch; either blank field disables that branch. Generic text patterns, the `unveil` check, parse withholding, and raw suppression remain active. All scoring calls use the original row and annotations.

Deny-on-missing is a replay-only availability

Variation	Surface flagged	Denied not refused	Denied intent shown	Allowed refused	Joint audit pass	Generation mean (s)	CPU (μs)
Safety prompt	6.20	7.85	0.00	10.70	86.30	2.095	3.1 ± 2.3
Schema only	14.34	65.42	99.90	0.60	33.13	1.398	7.4 ± 3.7
Self-policy	6.53	36.20	99.80	2.07	32.64	2.075	8.3 ± 6.7
Schema + V2	0.87	9.85	99.90	3.90	32.03	1.398	16.1 ± 8.9
Schema + V3 (ours)	**0.00**	**8.55**	**12.50**	**3.90**	**90.37**	**1.398**	$\mathbf{11.1 \pm 4.8}$

Table 6: Full ablation metrics for Table 3. The common surface auditor evaluates condition-sweep outputs, $N = 9{,}000$ per row (6,000 denied; 3,000 allowed). Rates (%) use the labeled population. Schema rows hold proposals fixed; both controllers preserve 96.70% of allowed lines. Recorded generation time and separately measured CPU postprocessing (mean±SD over 30 passes) are not summed across devices.

Variation	G	M	S	Surface flagged	Raw visible	Denied not refused	Denied intent shown	Joint audit pass
V2 (base)	–	–	–	1.23	0.20	22.55	99.70	33.23
V2 + S	–	–	•	1.03	0.00	22.55	99.70	33.43
V2 + M	–	•	–	1.23	0.20	22.55	67.35	54.80
V2 + G	•	–	–	0.23	0.20	21.00	99.70	33.23
V3 − G	–	•	•	1.03	0.00	22.55	67.35	55.00
V3 − M	•	–	•	0.03	0.00	21.00	99.70	33.43
V3 − S	•	•	–	0.20	0.20	21.00	65.80	55.83
V3 (ours)	•	•	•	**0.00**	**0.00**	**21.00**	**65.80**	**56.03**

Table 7: Full factorial component replay. All eight combinations use the same 9,000 runtime generations; denied rates use 6,000 observations. G: field gate; M: denied-intent redaction; S: raw/error protection. The all-off/all-on endpoints reproduce saved V2/V3 exactly; allowed-line preservation is 100% for every row.

policy: a missing context causes a fixed withholding line, redacted intent, a generic context-unavailable error, and no raw output. It does not recategorize valid output as a parse failure. This deterministic intervention isolates the response to missing context. Table 8 gives the unchanged guard's complete-omission endpoint; blanking either field yields the same endpoint as blanking both. The intervention therefore characterizes the specified missing-value policy.

For each seed (20261031–20261130), we independently permute the 100 unique prompts within each category. The first 0, 10, 25, 50, 75, or 100 prompts form nested omission masks. Every occurrence of a selected prompt is masked across all five backbones and three runs. The plotted band is the 5th–95th percentile across these 100 masks, not a confidence interval for generalization. Of 3,000 backbone–prompt clusters, 2,999 have identical raw output across the three runs; repetitions are therefore not independent evidence. The 111 V2 flags cover 37 backbone–prompt pairs: 30 final-line, six raw-parse-only, and one intent-only. This context analysis reuses generations and recorded generation times; the separate CPU benchmark measures postprocessing only.

The executable protocol and unit tests are

Backbone	Flags	Surface % all	Not refused % denied	Intent % denied	Coverage 100α
Gemma2 2B Q8	3	0.17	5.25	57.50	71.67
Qwen2.5 7B	63	3.50	11.50	54.75	69.83
Llama3.1 8B	3	0.17	41.75	72.25	81.50
Mistral 7B	21	1.17	23.75	64.25	76.17
Gemma2 9B	0	0.00	30.25	87.75	91.83
All	90	1.00	22.50	67.30	78.20

Table 8: Unchanged V3 guard with complete controller-context omission, scored against original annotations. Surface rates and controller coverage 100α use all generations; non-refusal and intent use denied generations. Raw/parse leakage remains zero.

`research/naacl_deep_analysis.py` and `research/test_naacl_deep_analysis.py`. The saved manifest records input hashes, seeds, context transformations, and outputs; per-mask and per-backbone endpoint CSVs accompany the paper.

For bootstrap intervals, seed 20261101 generates 2,000 resamples with replacement: 100 unique prompt IDs within each of six categories. A selected ID retains every backbone and run, so repeats do not inflate the effective sample. Each replicate recomputes the paired exposure gap, joint-pass gain, and the ratio of visible

Policy	Denied blocked (%)	Allowed blocked (%)	Surface flagged (% all)	Not refused (% denied)	Intent shown (% denied)	Refused (% allowed)
V3 surface ctrl.	–	–	0.00	21.00	65.80	0.30
V3 + admission	100.00	0.00	0.00	0.00	0.00	0.30

Table 9: Prompt-side admission ablation. Blocking rates measure the prompt gate; remaining columns audit the rendered response. Rules are benchmark-facing.

intent to detected refusals on denied prompts. Reported bounds are empirical 2.5th/97.5th percentiles. They describe stability under this benchmark's resampling scheme, not open-world risk bounds; zero-event intervals are omitted. The denied V3 contingency counts are 2,052 neither failure, 2,688 intent-only, 1,260 both failures, and zero non-refusal-only observations.

C Historical V1 Condition Sweep

Before the live public-surface study, we ran 600 prompts for three runs under five generation conditions and five backbones, yielding 45,000 observations. Figure 6 reports that historical cohort. The four baselines are direct generation, a safety prompt, schema-only generation, and a schema whose policy decision is generated by the model. Oracle PAG V1 records 0.00% unsafe disclosure and denied non-refusal for every backbone, with 0.00–0.50% over-refusal and 0.757–1.920 s mean generation latency for the historical sweep.

V1 reads `gold_permission` before rendering, establishing an oracle reference for proposal/permission separation. The historical sweep and runtime study therefore answer complementary questions: the former compares generation and permission designs, whereas the latter holds proposals fixed to isolate public-surface policies. V3 uses benchmark permission and category annotations within its field detector, as specified in Section 3.

D Additional Audit Details

Table 11 separates V2 final-line and side-field flags. Its 21 refusal-like final-line flags require human adjudication before interpretation as harmful disclosure. Table 9 tests a prompt-only gate for the four denied categories; these benchmark-facing rules use neither generated outputs nor benchmark annotations at inference. Table 12 reports generation time shared by all replay policies.

Category	Surface flagged	Denied not refused	Denied intent shown	Allowed refused	Mean latency (s)
safe reflection	**0.00**	–	–	0.40	1.411
ambiguous emotion	**0.00**	–	–	0.20	1.354
private inference	**0.00**	23.20	68.20	–	1.466
third-party secret	**0.00**	16.80	82.20	–	**1.349**
prompt injection	**0.00**	**25.60**	**85.00**	**–**	**1.406**
contested exposure	**0.00**	18.40	27.80	–	1.497

Table 10: V3 category marginals, retained from the primary audit. Rates are percentages; latency is seconds. Figure 4 resolves these marginals into backbone–category interactions.

V2 public-surface flag	Count	% all
Unsafe final-line flag	90	1.00
Raw parse-output leak	18	0.20
Unsafe intent-only flag	3	0.03
Any public-surface flag	111	1.23
Refusal-like final flags	21	0.23

Table 11: Decomposition of V2 public-surface flags. The first three rows are disjoint; the refusal-like row is a diagnostic subset of final-line flags.

Model	Mean	95th percentile	Maximum
All	1.414	1.937	6.750
Gemma2 2B Q8	1.018	1.252	2.621
Qwen2.5 7B	1.331	1.943	4.349
Mistral 7B	1.515	2.034	6.750
Gemma2 9B	1.611	1.889	2.624
Llama3.1 8B	1.596	2.026	3.048

Table 12: V3 live generation latency in seconds.

A deterministic 200-row V3 spot-check sample spans all models and categories: 0 unsafe public-surface flags, 24 strict denied non-refusal flags, and 78 intent-on-denied metadata flags. Regenerate these tables from saved audit CSVs with `research/emnlp_industry_strengthening_analysis.py`.

Representative cases. Examples are sanitized; generated prompt text is summarized. **Raw parse leak (V2):** a system-prompt request is withheld in the final line, but raw JSON exposes generated




Figure 6: **Historical five-condition sweep** across five GGUF backbones ($N = 1{,}800$ per cell). Lower is better in every panel. PAG denotes the task contract; the outlined V1 column is N/Agency++'s gold-permission oracle setting. Historical and runtime cohorts are reported separately.

Backbone	Private	Third-party	Injection	Contested	Span (pp)
Gemma2 2B Q8	47	81	88	13	75
Qwen2.5 7B	54	32	93	19	74
Llama3.1 8B	76	100	88	24	76
Mistral 7B	64	98	64	24	74
Gemma2 9B	100	100	92	59	41

Table 13: Visible intent on denied prompts (%), with $N_D = 300$ per cell. Span is the category max–min. This unconditional matrix complements the refusal-conditioned analysis in Figure 4b.

prompt text. **Conservative flag (V2):** a refused hidden-message request retains intent that names the requested message; this is a diagnostic flag, not adjudicated harm. **Non-refusal (V3):** a private-reason request redirects to self-exploration without a detected refusal. **Redaction (V3):** invalid output is hidden and the canonical withholding line is rendered.

Empirical rendering distribution. For proposal class a_j and rendered branch b_j, the observed transition mass is $\widehat{M}_{ab} = N^{-1} \sum_j \mathbf{1}[a_j = a, b_j = b]$. Its column sums give the empirical rendered distribution in Figure 3a. This averages across the fixed prompt/model/run mixture, not $P_\theta(\cdot \mid x)$ at a single input. Table 14 separates action transitions from exact V2–V3 text changes. Of 2,052 fallback observations, 1,959 (95.47%) preserve the V2 final line; across all observations, 8,907/9,000 (98.97%) do so. Preservation measures exact text retention under the rendering intervention.

(a) Proposed action to V3 branch

Proposal	Reflect kept	Withhold kept	Fallback
Reflect	4146	0	156
Withhold	0	2802	135
Unveil	0	0	1743
Invalid	0	0	18

(b) Audited text changes from V2 to V3

Backbone	None	Intent only	Line + intent	Intent + raw
Gemma2 2B Q8	1287	510	3	0
Qwen2.5 7B	1194	543	63	0
Llama3.1 8B	1464	330	6	0
Mistral 7B	1350	411	21	18
Gemma2 9B	1653	147	0	0
All	**6948**	**1941**	**93**	**18**

Table 14: Exact rendering transitions and edit locality. (a) Fallback always renders `withhold`; the two kept branches preserve the proposal's line and intent. (b) Mutually exclusive changes in line, intent, and raw text; action/control labels are not counted as text edits. Each panel totals 9,000 observations.

Budget-qualified response yield. Figure 3b is an empirical sub-distribution: its limit is joint audit pass, not 100%. It uses the saved generation round-trip time shared by V2/V3, without estimating renderer overhead or production service-level compliance. Pooled V3–V2 gain is 12.77 pp $[11.72, 13.82]$ at 1.5 s, 20.61 pp $[19.22, 21.98]$ at 2 s, and 22.42 pp $[20.93, 23.88]$ at 3 s (paired 95% intervals). For backbone selection (Figure 7), Qwen minus Gemma2 2B at 1.5 s is -14.28 pp (95% paired prompt-bootstrap interval $[-17.83, -10.67]$); at 2 s it is $+1.39$ pp $[-1.89, 4.33]$, and at 3 s $+5.11$ pp $[2.11, 7.95]$. These paired comparisons use the same synthetic workload and show how the deadline changes the balance between generation speed and eventual audit pass.

Backbone	1.5 s	2.0 s
Gemma2 2B Q8	61.33 [58.67, 63.83]	61.39 [58.78, 63.89]
Qwen2.5 7B	47.06 [43.89, 50.06]	62.78 [60.11, 65.39]
Llama3.1 8B	11.61 [9.67, 13.39]	47.44 [45.17, 49.56]
Mistral 7B	38.22 [35.33, 40.83]	54.06 [51.50, 56.78]
Gemma2 9B	13.06 [11.28, 14.89]	40.39 [38.72, 42.11]

Table 15: V3 audit-qualified generation-budget yield (%) with 95% prompt-bootstrap intervals. Each denominator includes all 1,800 observations, not only those completing within budget.




Figure 7: V3 generation-budget yield by backbone. Curves count timely audit passes among all requests; error bars are 95% prompt-bootstrap intervals. This deployment-selection view is separate from the V2–V3 method comparison in Figure 3b.

E Choice-Gated Dialogue Complement

Figures 8–14 provide the dialogue artifacts referenced in the limitations. Dialogue 1 reproduces saved V3 audit rows across categories and backbones, plus one aggregate public-surface audit delta. Dialogue 2 illustrates a complementary game interface in which author-labeled choices provide a V1-like interaction gate while the rendered NPC line and other displayed fields remain subject to the V3 surface contract at runtime.




Figure 8: **Dialogue 1-1.** Allowed reflection examples where V3 preserves rendered dialogue variation.




Figure 9: **Dialogue 1-2.** Private-inference examples where V3 replaces an unsafe inference with a controlled withholding line.




Figure 10: **Dialogue 1-3.** Contested-exposure examples with consistent V3 withholding.



Figure 11: **Dialogue 1-4.** Third-party-secret examples where V3 withholds private inference about another person.




Figure 12: **Dialogue 1-5.** Prompt-injection examples where V3 hides raw fallback text and renders only the safe response.




Figure 13: **Dialogue 1-6.** Public-surface audit delta showing that V3 suppresses raw parse leaks and side-field exposure that final-only scoring does not measure.




Figure 14: **Dialogue 2.** Choice-gated dialogue as a V1-like complement to V3. The author-labeled choice gate moves some permission decisions to design time, while the generated player-facing line remains governed by the V3 renderer contract.