Name: Aditya Rajesh Sawant

Subject: CN

Roll No: 46

Division: TE4

Batch: D

Experiment: 7

Aim: Design VPN and Configure RIP/OSPF using Packet tracer

Implementation: Create the following network and set IP Addresses.






Router1
Physical
Config
CLI
Attributes
GLOBAL
Settings
Algorithm Settings
ROUTING
Static
RIP
SWITCHING
VLAN Database
INTERFACE
FastEthernet0/0
FastEthernet0/1
FastEthernet0/0
Port Status
On
Bandwidth
100 Mbps
10 Mbps
Auto
Duplex
Half Duplex
Full Duplex
Auto
MAC Address
00D0.BAC5.7D01
IP Configuration
IPv4 Address
192.168.3.3
Subnet Mask
255.255.255.0
Tx Ring Limit
10
Equivalent IOS Commands
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/0
Router(config-if)#
Top


PC0
Physical
Config
Desktop
Programming
Attributes
IP Configuration
Interface
FastEthernet0
IP Configuration
DHCP
Static
IPv4 Address
192.168.1.100
Subnet Mask
255.255.255.0
Default Gateway
192.168.1.1
DNS Server
0.0.0.0
IPv6 Configuration
Automatic
Static
IPv6 Address
Link Local Address
FE80::230:A3FF:FE21:DB0A
Default Gateway
DNS Server
802.1X
Use 802.1X Security
Authentication
MD5
Username
Top


PC1
Physical
Config
Desktop
Programming
Attributes
IP Configuration
Interface
FastEthernet0
IP Configuration
DHCP
Static
IPv4 Address
192.168.2.100
Subnet Mask
255.255.255.0
Default Gateway
192.168.2.1
DNS Server
0.0.0.0
IPv6 Configuration
Automatic
Static
IPv6 Address
Link Local Address
FE80::260:3EFF:FEE7:6261
Default Gateway
DNS Server
802.1X
Use 802.1X Security
Authentication
MD5
Username
Top


PC2
Physical
Config
Desktop
Programming
Attributes
IP Configuration
Interface
FastEthernet0
IP Configuration
DHCP
Static
IPv4 Address
192.168.2.101
Subnet Mask
255.255.255.0
Default Gateway
192.168.2.1
DNS Server
0.0.0.0
IPv6 Configuration
Automatic
Static
IPv6 Address
Link Local Address
FE80::20D:BDFF:FE61:75E3
Default Gateway
DNS Server
802.1X
Use 802.1X Security
Authentication
MD5
Username
Top

Sending the packet



Creating a VLAN :







Conclusion : Thus we have successfully implemented VLAN and RIP protocol