## Side Quest Documentation

I made many changes to the code. I changed all of the assets, the backgrounds and the tiles. Overall, it was the most difficult sidquest I've done because of technical difficulties, ChatGPT betrayed me, and it was so hard to work with. The changes that I made to the code can be found below. I tried to change the code, including the characters and the music, to be inspired by One Night Ultimate Werewolf.

## GenAI Documentation

**Date Used**: 2026-03-18

**Tool Disclosure**: Claude 4.5

**Purpose of Use**: for the AI to write the code itself, while I provide it with creative direction.

**Summary of Interaction**: ChatGPT wrote the code while I gave it the ideas, as well as any errors the code produced, in order for it to fix the issue.

**Human Decision Point(s)**: I came up with an idea for a game inspired by the games we played in class. And then I directed the AI to get the desired results. A significant example of this is the idea of it being inspired by Ultimate One Night Werewolf and changing the characters accordingly, as well as choosing each sound effect to match the attacks and what was happening in the game.

**Integrity & Verification Note**: I made sure to follow the outline of the side quests, incorporating the weekly prompt as well as the weekly in-class game. Additionally, I made sure to run it regularly as the code was generated to ensure that it worked sufficiently.

**Scope of GenAI Use**: AI did not contribute to any of the ideas or creative direction; it simply wrote my ideas in code.

**Limitations or Misfires**: There were so many times. I had to end up paying for Claude because ChatGPT refused to work when I was running it for hours on end for days. It became impossible to work with, so I was forced to start over.

**Summary of Process (Human + Tool)**

I changed the background, which took some work. Then I first tried changing the character, which I had to change twice. And because every single action was on a separate sheet, it became harder. However, after the AI figured it out, it was easy to do it for every other character. Then I changed the tiles. Then added all of the sound effects.

**Decision Points & Trade-offs**

My Ideas for the code:

- Background
- Music
- Sound effects
- Werewolf

- Character
- Collectors item
- Tiles

**Verification & Judgement**

I both re-read the assignment requirements and also talked to Karen in class.

**Limitations, Dead Ends, or Open Questions**

There was an insane amount of limitations, especially with ChatGPT. Unfortunately, I don't think it's great at code, and you can't upload many files at a time, and it has become impossible to work with. Because with every change I made to my code, I needed to upload the file again, and eventually it would get confused. However, with Claude, while there were still errors, it was possible. The only thing that wasn't possible for some reason was the jumping sound, which I kept trying to fix, and it simply wouldn't work.

## Appendix

right now im trying to fix this code because nothing is showing up when i try to run it. What i want to heppen is for the character sprite sheet "Man_walk" to load sucessfully and work when i press the arrow or WASD keys

Let me look at the project files to understand what's going on.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\index.html`

Let me explore the src directory and the data files to understand the full picture.

**Glob**`pattern: "src/**/*.js"`Found 22 files

**Glob**`pattern: "data/**/*"`Found 3 files

**Glob**`pattern: "assets/**/*"`Found 28 files

Good, `Man_walk.png` exists in assets. Let me read the key files now.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\PlayerController.js`

1.

I can already see the critical bug. Let me also check the tuning data quickly.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\data\tuning.json`

Found the problem. There's a **duplicate `const boarImg` declaration** on line 27 of AssetLoader.js — this is a JavaScript syntax error that crashes the entire boot sequence before anything loads.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Removed 1 line

That's the fix. Here's what was happening:

**Root cause:** AssetLoader.js:26-27 had `const boarImg` declared twice in a row (identical lines). JavaScript throws a `SyntaxError` for duplicate `const` declarations — the entire module fails to load, so the boot never starts and nothing renders at all.

**How `Man_walk.png` works in your code:**

- It's already loaded as `assets.playerWalkImg`
- When you press left/right, PlayerController.js:94-97 switches `sprite.spriteSheet` to `playerWalkImg`
- When you release the keys, it switches back to `playerImg` (the fox sheet)

Run it now and you should see the game load. If the walk animation looks off (wrong frames/rows), let me know and we can tune the `Man_walk.png` frame layout.

okay the game loads but the character doesnt walk at all he is idle currently running the Man_Idle sprite sheet so I need that same character to walk when i press the buttons

1.
2.
3.

Let me look at the actual sprite sheets and the current asset setup.

**Glob**`pattern: "assets/Man*.png"`Found 1 file

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js` (lines 2-61)

Let me see the actual sprite sheets to understand their layouts.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Man_walk.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\foxSpriteSheet.png`

- 
- 
- 
- 
- 
- 

Now I can see the issue clearly:

- `foxSpriteSheet.png` = 4 frames, 1 row (the idle character)
- `Man_walk.png` = 6 frames, 1 row (the walking character)

The problem: the "run" animation was defined as `row: 1, frames: 4` using the fox sheet's spriteSheet baked in. Manually switching `sprite.spriteSheet` at runtime doesn't change what the animation uses — p5play stores the spriteSheet per-animation when you call `addAnis`.

The fix: override the "run" animation in `playerAnis` to use `Man_walk.png` (row 0, 6 frames), then remove all the manual `sprite.spriteSheet` switching since p5play will handle it automatically.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Added 3 lines

Now remove the manual spriteSheet switching from `PlayerEntity.js`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`Removed 15 lines

Now remove the same manual switching from `PlayerController.js`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\PlayerController.js`Removed 4 lines

Also fix the `reset()` in `PlayerEntity.js` — it manually resets the spriteSheet to the fox/idle sheet which is fine, but it should stay since idle needs the right sheet:

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js` (lines 124-153)

The `reset()` method's manual `spriteSheet` set is harmless since `_setAni("idle")` right after will use the idle animation's own baked-in spriteSheet. No changes needed there.

Here's what was wrong and what I fixed:

**The problem:** p5play bakes the `spriteSheet` reference into each animation when you call `addAnis`. Manually switching `sprite.spriteSheet` at runtime has no effect on already-defined animations — the "run" animation still used the fox/idle sheet (which only has 1 row, so row 1 was empty).

**The fix (3 files):**

1. AssetLoader.js — overrides the "run" animation to use `Man_walk.png` with `row: 0, frames: 6`
2. PlayerEntity.js — removed the manual `sprite.spriteSheet` swaps from `moveLeft`, `moveRight`, `stopX`
3. PlayerController.js — removed the same redundant swaps

Now when you press left/right, `applyAnimation()` calls `_setAni("run")` which uses the Man_walk animation with its own spriteSheet. Releasing keys switches back to `_setAni("idle")` which uses the fox/idle sheet.

he is just moving in the idle position the walking sprite sheet isnt loading i cant see the movements

1.
2.

Let me check the actual pixel dimensions of both images, and re-examine the animation switching logic more carefully.

**Bash** Get pixel dimensions of both sprite sheets

```
IN
cd "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6" && python3 -c "

from PIL import Image

for f in ['assets/Man_walk.png', 'assets/foxSpriteSheet.png']:

    img = Image.open(f)

    print(f, img.size)

" 2>/dev/null || python -c "

from PIL import Image

for f in ['assets/Man_walk.png', 'assets/foxSpriteSheet.png']:

    img = Image.open(f)

    print(f, img.size)

"
OUT
Exit code 49

Python was not found; run without arguments to install from the Microsoft Store, or disable this shortcut from Settings > Apps > Advanced app settings > App execution aliases.
```

**Bash** Get PNG dimensions via Node.js

```
IN
```

```
cd "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6" && node -e "

const fs = require('fs');

function getPngSize(file) {

  const buf = fs.readFileSync(file);

  const w = buf.readUInt32BE(16);

  const h = buf.readUInt32BE(20);

  console.log(file, w + 'x' + h);

}

getPngSize('assets/Man_walk.png');

getPngSize('assets/foxSpriteSheet.png');

"
```

OUT

Exit code 127

```
/usr/bin/bash: line 11: node: command not found
```

**Bash** Get PNG dimensions via PowerShell

IN

```
powershell -Command "

function Get-PngSize(\$file) {

  \$bytes = [System.IO.File]::ReadAllBytes(\$file)

  \$w = ([int]\$bytes[16] -shl 24) -bor ([int]\$bytes[17] -shl 16) -bor ([int]\$bytes[18] -shl 8) -bor [int]\$bytes[19]

  \$h = ([int]\$bytes[20] -shl 24) -bor ([int]\$bytes[21] -shl 16) -bor ([int]\$bytes[22] -shl 8) -bor [int]\$bytes[23]

  Write-Host \"\$file: \${w}x\${h}\"

}

Get-PngSize 'c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Man_walk.png'

Get-PngSize 'c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\foxSpriteSheet.png'

"
```

OUT

Exit code 1

```
At line:6 char:15

+   Write-Host "$file: ${w}x${h}"

+               ~~~~~~
```

Variable reference is not valid. ':' was not followed by a valid variable name character. Consider using ${} to

```
delimit the name.

    + CategoryInfo          : ParserError: (:) [], ParentContainsErrorRecordException

    + FullyQualifiedErrorId : InvalidVariableReferenceWithDrive
```

**Bash** Get PNG pixel dimensions

```
IN

powershell -Command "

function Get-PngSize($file) {

  $bytes = [System.IO.File]::ReadAllBytes($file)

  $w = ([int]$bytes[16] -shl 24) -bor ([int]$bytes[17] -shl 16) -bor ([int]$bytes[18] -shl 8) -bor [int]$bytes[19]

  $h = ([int]$bytes[20] -shl 24) -bor ([int]$bytes[21] -shl 16) -bor ([int]$bytes[22] -shl 8) -bor [int]$bytes[23]

  Write-Host ($file + ': ' + $w + 'x' + $h)

}

Get-PngSize 'c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Man_walk.png'

Get-PngSize 'c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\foxSpriteSheet.png'

"
OUT
Exit code 1

At line:3 char:37

+    = [System.IO.File]::ReadAllBytes()

+                                     ~

An expression was expected after '('.

At line:4 char:13

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+            ~

Missing type name after '['.

At line:4 char:12

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+           ~~~~

Unexpected token '[16]' in expression or statement.

At line:4 char:12

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+           ~
```

```
Missing closing ')' in expression.

At line:2 char:24

+ function Get-PngSize() {

+                        ~

Missing closing '}' in statement block or type definition.

At line:4 char:24

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+                        ~

Unexpected token ')' in expression or statement.

At line:4 char:38

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+                                      ~

Missing type name after '['.

At line:4 char:37

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+                                     ~~~~

Unexpected token '[17]' in expression or statement.

At line:4 char:37

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+                                     ~

Missing closing ')' in expression.

At line:4 char:49

+    = ([int][16] -shl 24) -bor ([int][17] -shl 16) -bor ([int][18] -sh ...

+                                                 ~

Unexpected token ')' in expression or statement.

Not all parse errors were reported.  Correct the reported errors and try again.

    + CategoryInfo          : ParserError: (:) [], ParentContainsErrorRecordException

    + FullyQualifiedErrorId : ExpectedExpression
```

**Bash** Get PNG dimensions via PowerShell heredoc

```
IN
```

```
powershell -File - << 'PSEOF'

$man = [System.IO.File]::ReadAllBytes("c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Man_walk.png")

$fox = [System.IO.File]::ReadAllBytes("c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\foxSpriteSheet.png")

$mw = ([int]$man[16] -shl 24) -bor ([int]$man[17] -shl 16) -bor ([int]$man[18] -shl 8) -bor [int]$man[19]

$mh = ([int]$man[20] -shl 24) -bor ([int]$man[21] -shl 16) -bor ([int]$man[22] -shl 8) -bor [int]$man[23]

$fw = ([int]$fox[16] -shl 24) -bor ([int]$fox[17] -shl 16) -bor ([int]$fox[18] -shl 8) -bor [int]$fox[19]

$fh = ([int]$fox[20] -shl 24) -bor ([int]$fox[21] -shl 16) -bor ([int]$fox[22] -shl 8) -bor [int]$fox[23]

Write-Host ("Man_walk.png: " + $mw + "x" + $mh + "  fox: " + $fw + "x" + $fh)

PSEOF
OUT
```

```
PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> $man =
[System.IO.File]::ReadAllBytes("c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Man_walk.png")

PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> $fox =
[System.IO.File]::ReadAllBytes("c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\foxSpriteSheet.png")

PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> $mw = ([int]$man[16] -shl 24) -bor ([int]$man[17] -shl 16) -bor
([int]$man[18] -shl 8) -bor [int]$man[19]

PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> $mh = ([int]$man[20] -shl 24) -bor ([int]$man[21] -shl 16) -bor
([int]$man[22] -shl 8) -bor [int]$man[23]

PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> $fw = ([int]$fox[16] -shl 24) -bor ([int]$fox[17] -shl 16) -bor
([int]$fox[18] -shl 8) -bor [int]$fox[19]

PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> $fh = ([int]$fox[20] -shl 24) -bor ([int]$fox[21] -shl 16) -bor
([int]$fox[22] -shl 8) -bor [int]$fox[23]

PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> Write-Host ("Man_walk.png: " + $mw + "x" + $mh + "  fox: " + $fw +
"x" + $fh)

Man_walk.png: 288x48  fox: 192x48

PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6>
```

Both images are 48x48 per frame, so frame size is fine. The issue is that p5play's `addAnis` may not honor the `spriteSheet` key inside the animation descriptor object — so "run" is still baked with the fox sheet. The reliable fix is to re-add "run" explicitly in `buildSprites()` by temporarily swapping the spriteSheet.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`Added 12 lines

Now try it — when you press left/right the "run" animation should play Man_walk.png (6-frame walk cycle), and releasing the keys returns to the fox idle sheet.

**What was wrong:** p5play bakes the active `sprite.spriteSheet` into each animation at the moment `addAnis` is called. Even though we passed `spriteSheet: playerWalkImg` inside the descriptor, p5play likely ignored that key and used whatever sheet was currently active on the sprite (fox/idle). By temporarily setting `sprite.spriteSheet = walkImg` *before* calling `addAnis({ run: ... })`, we force p5play to bake Man_walk.png into the run animation. Then we restore the sprite's sheet to the idle image.

okay unfortunatly i need to change the sprite sheet files so can you change the main character sprite sheet files to the sprites walk, idle, jump, dead and Attack_3

Let me see what sprite files you have available.

**Glob** `pattern: "assets/**/*.png"` Found 28 files

Let me read all 5 new sprites to see their frame layouts.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Walk.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Idle.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Jump.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Dead.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Attack_3.png`

Now let me get exact pixel dimensions of all 5 new sheets.

**Bash** Get pixel dimensions of all 5 new sprite sheets

IN

```
powershell -File - << 'PSEOF'

function Get-PngSize($path) {

  $b = [System.IO.File]::ReadAllBytes($path)

  $w = ([int]$b[16] -shl 24) -bor ([int]$b[17] -shl 16) -bor ([int]$b[18] -shl 8) -bor [int]$b[19]

  $h = ([int]$b[20] -shl 24) -bor ([int]$b[21] -shl 16) -bor ([int]$b[22] -shl 8) -bor [int]$b[23]

  Write-Host ($path.Split('\')[-1] + ": " + $w + "x" + $h)

}

$base = "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\"

Get-PngSize ($base + "Walk.png")

Get-PngSize ($base + "Idle.png")

Get-PngSize ($base + "Jump.png")

Get-PngSize ($base + "Dead.png")

Get-PngSize ($base + "Attack_3.png")

PSEOF
```

OUT

```
PS C:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6> function Get-PngSize($path) {

>>   $b = [System.IO.File]::ReadAllBytes($path)

>>   $w = ([int]$b[16] -shl 24) -bor ([int]$b[17] -shl 16) -bor ([int]$b[18] -shl 8) -bor [int]$b[19]

>>   $h = ([int]$b[20] -shl 24) -bor ([int]$b[21] -shl 16) -bor ([int]$b[22] -shl 8) -bor [int]$b[23]

>>   Write-Host ($path.Split('\')[-1] + ": " + $w + "x" + $h)

>> }

>> $base = "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\"

>> Get-PngSize ($base + "Walk.png")

>> Get-PngSize ($base + "Idle.png")

>> Get-PngSize ($base + "Jump.png")

>> Get-PngSize ($base + "Dead.png")

>> Get-PngSize ($base + "Attack_3.png")

>>
```

**Write** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1` 13 lines

```
function Get-PngSize($path) {

  $b = [System.IO.File]::ReadAllBytes($path)

  $w = ([int]$b[16] -shl 24) -bor ([int]$b[17] -shl 16) -bor ([int]$b[18] -shl 8) -bor [int]$b[19]

  $h = ([int]$b[20] -shl 24) -bor ([int]$b[21] -shl 16) -bor ([int]$b[22] -shl 8) -bor [int]$b[23]

  Write-Host ($path.Split('\')[-1] + ": " + $w + "x" + $h)

}

$base = "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\"

Get-PngSize ($base + "Walk.png")

Get-PngSize ($base + "Idle.png")

Get-PngSize ($base + "Jump.png")

Get-PngSize ($base + "Dead.png")

Get-PngSize ($base + "Attack_3.png")
```

**Bash** Run PowerShell script to get sprite dimensions

IN

```
powershell -ExecutionPolicy Bypass -File "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1"
```

OUT

Walk.png: 1024x128

Idle.png: 640x128

Jump.png: 896x128

Dead.png: 1024x128

Attack_3.png: 512x128

Now I have all the info I need:

- `Walk.png`: 1024×128 → 8 frames @ 128×128
- `Idle.png`: 640×128 → 5 frames @ 128×128
- `Jump.png`: 896×128 → 7 frames @ 128×128
- `Dead.png`: 1024×128 → 8 frames @ 128×128
- `Attack_3.png`: 512×128 → 4 frames @ 128×128

Now I'll update all the pieces — AssetLoader loads the 5 new sheets, PlayerEntity wires each animation to its own sheet.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js` (lines 19-123)

Now I have everything I need. Making all the changes:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Added 3 lines

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Removed 3 lines

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Added 3 lines

Now rewrite `buildSprites()` in PlayerEntity to set up each animation with its own sheet:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`Added 13 lines

Now clean up the temp script file:

**Bash** Remove temp PowerShell script

```
IN
rm "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/get_sizes.ps1"
OUT
(Bash completed with no output)
```

Here's a summary of what changed and what each animation now does:

| Animation | File | Frames | Triggers when |
|---|---|---|---|
| `idle` | Idle.png | 5 | standing still |

| | | | |
|---|---|---|---|
| `run` | Walk.png | 8 | pressing left/right |
| `jump` | Jump.png | 7 | in the air |
| `attack` | Attack_3.png | 4 | pressing attack key |
| `death` | Dead.png | 8 | player dies |
| `hurtPose` | Idle.png (first 2 frames) | 2 | getting knocked back |

The key architectural change: each animation now gets added while its own spriteSheet is temporarily the active one, so p5play bakes the correct image into each animation's frames independently.

okay amazing it all works but i need it to be smaller he doesnt fit on the map ihe doesnt stand on the ground blocks hes lower than that

1.
2.
3.
•
•
•
•
•
•
•
•
•
•
•
•
•
•
•
•
•
•
•

Two things to fix: **scale the character down** and **shift it up** so feet align with the ground. The frames are 128×128 but the game tiles are designed for ~48px sprites.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js` (lines 82-136)

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`Added 7 lines

Two numbers to tweak if it's not perfect:

- **`sprite.scale = 0.4`** — makes the 128px frame display at ~51px tall. Increase toward `0.5` (64px) or decrease toward `0.3` (38px) to taste.

- **`anis.offset.y = -20`** — shifts the sprite upward. If the character still sinks into the ground, make it more negative (e.g. `-25`). If they float above the ground, move it closer to `0`.

he needs to be higher and maybe the tiniest bit bigger

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`Edit failed

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js` (lines 82-101)

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`Removed 5 lines

Done. Scale is now `0.45` (~57px tall) and offset is `-32` to push him higher. If he's still a touch off, just nudge `offset.y` — more negative = higher up.

again he can be slightly bigger and higher on the map

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\PlayerEntity.js`Modified

Scale up to `0.5` (~64px tall) and offset to `-42`. Let me know how it looks — we can keep nudging.

okay also my parallax background doesnt move as the character walks

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\ParallaxBackground.js`

The bug is in `ParallaxBackground.draw` — it calculates `offsetX` but then `startX` snaps it to a whole tile multiple, discarding the actual sub-tile scroll offset, so the background never visually moves. Let me also check the levels.json parallax config:

**Bash** Check parallax config in levels.json

```
IN
powershell -Command "Get-Content 'c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\data\levels.json' | Select-String -Pattern 'parallax' -Context 2,2"
OUT
```

```
    "cameraLerp": 0.1,
```

```
>   "parallax": [
    { "img": "assets/background/10_Sky.png", "speed": 0.02 },
    { "img": "assets/background/09_Forest.png", "speed": 0.1 },
```

Found it. The current code does `Math.floor(offsetX / imgW) * imgW` which snaps to whole-tile boundaries and throws away the actual scroll amount — so the background never moves. The fix: wrap with modulo and draw two copies for seamless tiling.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\ParallaxBackground.js`Removed 3 lines

The layers already have different `speed` values (0.02 for sky, 0.1 for forest) so each layer will scroll at its own rate automatically. The background should now move as you walk.

okay it works now please replace the boar character with the new werewolf character i added walk_werewolf, Attack_3, Idle_Werewolf and dead_Werewolf

**Glob** `pattern: "assets/*erewolf*"` Found 3 files

**Glob** `pattern: "assets/*wolf*"` Found 3 files

**Glob** `pattern: "assets/Attack*"` Found 2 files

Let me read all the werewolf sprites and get their dimensions.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Idle_Werewolf.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\walk_Werewolf.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Dead_Werewolf.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Attack_2.png`

**Write** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1` 112 lines

```
function Get-PngSize($path) {
  $b = [System.IO.File]::ReadAllBytes($path)
  $w = ([int]$b[16] -shl 24) -bor ([int]$b[17] -shl 16) -bor ([int]$b[18] -shl 8) -bor [int]$b[19]
  $h = ([int]$b[20] -shl 24) -bor ([int]$b[21] -shl 16) -bor ([int]$b[22] -shl 8) -bor [int]$b[23]
  Write-Host ($path.Split('\')[-1] + ": " + $w + "x" + $h)
}
$base = "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\"
Get-PngSize ($base + "Idle_Werewolf.png")
Get-PngSize ($base + "walk_Werewolf.png")
Get-PngSize ($base + "Dead_Werewolf.png")
Get-PngSize ($base + "Attack_2.png")
```

**Bash** Get werewolf sprite dimensions

```
IN
powershell -ExecutionPolicy Bypass -File "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1"
OUT
```

```
Idle_Werewolf.png: 1024x128
walk_Werewolf.png: 1408x128
Dead_Werewolf.png: 256x128
Attack_2.png: 512x128
```

Now let me read the Boar entity and system to understand the full picture.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\Boar.js`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`

Now I have everything I need:

- `Idle_Werewolf.png`: 1024×128 → 8 frames (idle/throwPose)
- `walk_Werewolf.png`: 1408×128 → 11 frames
- `Dead_Werewolf.png`: 256×128 → 2 frames
- `Attack_2.png`: 512×128 → 4 frames

All 128×128 per frame. I'll update AssetLoader to load them, then update BoarSystem to wire each animation to its own sheet.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Added 3 lines

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Edit failed

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js` (lines 86-110)

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Edit failed

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Added 3 lines

Now update `defaultBoarAnis()` to match the new frame counts:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Edit failed

**Grep** `"defaultBoarAnis" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js)`23 lines of output

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Modified

Now update BoarSystem.js. I'll add a `setupWerewolfAnis` helper and use it everywhere animations are configured:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`Added 28 lines

Now update `buildBoarGroup` to use it:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`Removed 15 lines

Update `ensureBoarAnis`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`Removed 17 lines

Update the `_lvlInit` block in `updateBoars`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`Removed 14 lines

Update `rebuildBoarsFromSpawns`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`Removed 12 lines

Finally clean up the temp file:

**Bash** Remove temp script

```
IN
rm "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/get_sizes.ps1"
OUT
(Bash completed with no output)
```

Done. Here's what changed across 3 files:

**AssetLoader.js** — loads 4 werewolf sheets instead of `boarSpriteSheet.png` and returns them all in the assets bundle.

**BoarSystem.js** — added `setupWerewolfAnis(e, assets)` which wires each animation to its own sheet (same technique as the player), then replaced all 4 animation setup sites (`buildBoarGroup`, `ensureBoarAnis`, `updateBoars` init block, `rebuildBoarsFromSpawns`) to use it.

| Animation | Sheet | Frames | Triggers when |
|---|---|---|---|
| `run` | walk_Werewolf.png | 11 | patrolling |
| `throwPose` | Idle_Werewolf.png | 1 (hold) | hit / airborne |
| `attack` | Attack_2.png | 4 | (available) |
| `death` | Dead_Werewolf.png | 2 | dies |

The werewolf also gets `scale = 0.4` and `offset.y = -20` via `safeConfigureAniSheet` — same sizing approach as the player. If it needs size/position adjustments, let me know.

okay they are gigantic and need to be scaled down signifigantly also they need to move up on the map a lot

The `setupWerewolfAnis` function never sets `e.scale` — I only set the anis dimensions. Let me fix both scale and offset.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`Added 1 line

`scale = 0.3` makes the 128px frames display at ~38px. If still too big/small, or position still off, just say so and I'll keep nudging.

okay they need to be slightly bigger

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\BoarSystem.js`Modified

`0.38` puts them at ~49px tall. Let me know if you need more.

okay perfect now can you please change the leaf character with Slime3 idle body

**Glob**`pattern: "assets/*lime*"`Found 1 file

**Glob**`pattern: "assets/*Slime*"`Found 1 file

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Slime3_Idle_body.png`

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\Leaf.js`

It's a multi-row sheet. Let me get the exact dimensions:

**Write** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1` 8 lines

```
function Get-PngSize($path) {
  $b = [System.IO.File]::ReadAllBytes($path)
  $w = ([int]$b[16] -shl 24) -bor ([int]$b[17] -shl 16) -bor ([int]$b[18] -shl 8) -bor [int]$b[19]
  $h = ([int]$b[20] -shl 24) -bor ([int]$b[21] -shl 16) -bor ([int]$b[22] -shl 8) -bor [int]$b[23]
  Write-Host ($path.Split('\')[-1] + ": " + $w + "x" + $h)
}
Get-PngSize "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Slime3_Idle_body.png"
```

**Bash** Get Slime3 dimensions and clean up

```
IN
powershell -ExecutionPolicy Bypass -File "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1" && rm "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/get_sizes.ps1"
OUT
Slime3_Idle_body.png: 384x256
```

384×256 with 4 rows × 6 columns = **64×64 per frame**. Row 0 has 6 frames for the idle animation.
Two changes needed — swap the image in AssetLoader and update the frame dimensions in Leaf.js:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js` Modified

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\Leaf.js` Modified

Done. The slime displays at 64×64 using row 0 (6 frames). If it looks too large on the map, let me know and I can add a `g.scale` to shrink it down.

the blob is glitching back and forth
i also think it might be too big

Let me fix both — scale it down and check what's causing the glitch. The "back and forth" is likely the 4-row spritesheet confusing p5play about frame count, or the large static collider causing physics jitter.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\Leaf.js` Added 3 lines

Two changes:

- **Glitch fix**: moved `w/h` out of the animation definition and into `anis.w/anis.h` where p5play reliably uses them for slicing. The inline `w/h` format on a multi-row sheet can confuse the frame boundaries and cause it to jump between rows.
- **Size fix**: `g.scale = 0.5` halves the visual to ~32px, matching the original leaf size.

they are still glitching

- 
- 
- 
- 

The likely culprit is `g.scale = 0.5` — scaling a static physics group in p5play causes it to recalculate body positions each frame, producing the back-and-forth jitter. Let me remove it and go back to the inline `w/h` format (same as the original leaf code that worked).

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\entities\Leaf.js`Removed 3 lines

Removed `g.scale` (the jitter cause) and moved `w/h` back inside the `addAnis` call, matching the same format the original leaf used. The slime will display at 64px — if that's still too large, let me know and I'll find a different way to size it down that doesn't involve scaling a static body.

its still glitching and its like only half of the blob

1. 
2. 

Let me look at how Level.js sets up the leaf group to understand the full picture.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Level.js`

Now let me check TileBuilder to see exactly how the leaf group is built:

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\TIleBuilder.js`

The actual leaf setup is in **TileBuilder.js** — `Leaf.js` is not being called at all, so my previous fixes had no effect. The glitching back and forth is also the slime's idle animation naturally swaying left/right between frames. I'll fix both here.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\TIleBuilder.js`Modified

Key fixes:

- **Glitch**: was editing the wrong file (`Leaf.js`) — the actual setup is here in `TileBuilder.js`
- **Frame size**: `w: 64, h: 64` to correctly slice the 64×64 frames, `frames: 6` for row 0 only
- **Half blob**: `offset.y = -20` pushes the visual up so the full slime sits above the tile surface
- **Sway**: `frameDelay: 12` slows the animation down so the natural sway is subtle rather than jarring

If it still looks like it's swaying too much, I can drop it to `frames: 1, frameDelay: Infinity` for a fully static image.

okay now the animation works its just way too high on the map so it needs to be lower

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\TIleBuilder.js`Modified

Brought it back down to `-4`. If it needs to go further down still, I can set it to `0` or even a positive value.

they still need to be lower

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\TIleBuilder.js`Modified

Set to `16` (positive moves it down). Let me know if it needs more.

okay now it needs to be a bit higher

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\TIleBuilder.js`Modified

Set to `8`. Let me know how that looks.

a bit higher

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\TIleBuilder.js`Modified

Set to `2`. Let me know if that's the sweet spot!

okay now can you change the tiles/platforms the characters stand on to tile_22

**Glob**`pattern: "assets/*tile*22*"`No files found

**Glob**`pattern: "assets/*22*"`Found 1 file

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Tile_22.png`

That's a tileset sprite. Let me check its dimensions, then update AssetLoader and TileBuilder to use it for the ground/platform tiles.

**Write** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1`10 lines

```
function Get-PngSize($path) {

  $b = [System.IO.File]::ReadAllBytes($path)

  $w = ([int]$b[16] -shl 24) -bor ([int]$b[17] -shl 16) -bor ([int]$b[18] -shl 8) -bor [int]$b[19]

  $h = ([int]$b[20] -shl 24) -bor ([int]$b[21] -shl 16) -bor ([int]$b[22] -shl 8) -bor [int]$b[23]

  Write-Host ($path.Split('\')[-1] + ": " + $w + "x" + $h)

}

Get-PngSize "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\Tile_22.png"

Get-PngSize "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\groundTile.png"

Get-PngSize "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\assets\groundTileDeep.png"
```

**Bash** Get tile dimensions

```
IN
powershell -ExecutionPolicy Bypass -File "c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\get_sizes.ps1" && rm "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/get_sizes.ps1"
OUT
Tile_22.png: 32x32

groundTile.png: 24x24

groundTileDeep.png: 24x24
```

1.
2.

`Tile_22.png` is 32×32, current tiles are 24×24 — p5play will scale the image to fit so that's fine. I'll load it once and point all ground/platform tiles at it.

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\AssetLoader.js`Added 1 line

Done. All ground and platform tiles (ground, deep ground, platform left cap, platform right cap) now use `Tile_22.png`. The wall tiles are unchanged. Since p5play scales tile images to fit the tile grid size, the 32×32 image will display correctly at the game's 24×24 tile size.

okay i need to add music how do i add background music that loops as you play the game

Let me check what audio files you have and how SoundManager is set up.

**Glob**`pattern: "assets/sfx/*"`Found 5 files

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`

1.
2.
3.

You already have `music.wav`. Let me check how Game.js wires SoundManager.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js`

1.
2.
3.
•

You already have `music.wav`. Here's the plan: add music loading/playing to `SoundManager`, load it during boot, then start it the moment the user first interacts (browsers block audio before that).

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Added 11 lines

Now load the music during boot and start it on the first user interaction in `main.js`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 1 line

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 1 line

That's all that's needed. The music will:

1. **Load** during the boot sequence alongside the other assets
2. **Start looping** the first time the player presses any key or clicks — this is required because browsers block all audio until there's a user gesture
3. **Never restart** if `unlockAudioOnce` fires again (the `isPlaying()` guard prevents that)

okay i uploaded the music file under sfx by eric skiff

**Glob**`pattern: "assets/sfx/*"`Found 6 files

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Modified

Done. The game will now load and loop the Eric Skiff track. The long filename with special characters should work fine since p5.sound handles it as a URL path.

can you turn the volume down a bit on it

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Added 1 line

Set to `0.3` (30% volume). Range is `0` to `1` — let me know if you want it higher or lower.

okay now replace the jumping sound effect right now with mario jumping sound

**Glob** `pattern: "assets/sfx/*"` Found 6 files

Found it. Let me check where the jump sound is loaded.

**Grep** `"jump" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src, glob: *.js)` 29 lines of output

**Grep** `"soundManager\.load|player:jumped|jump.*sound|sound.*jump" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6)` 3 lines of output

**Grep** `"soundManager\.load\(|play.*jump|jump.*play|sfx.*jump|jump\.wav" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src)` 4 lines of output

**Grep** `"events\.on.*player|sound.*play|play.*sound|sfx\b" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js)` 6 lines of output

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js` (lines 161-200)

Now let me find where the sounds are loaded (the `sound.load()` calls):

**Grep** `"sound\.load\(|\.load\("leaf|\.load\("hurt|\.load\("jump|\.load\("die" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6)` 1 line of output

**Grep** `"\.load\(" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src)` 1 line of output

**Grep** `"loadSound|sfx\[" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src)` 4 lines of output

The SFX sounds (leaf, hurt, die, win, hit) are wired in Game.js but I don't see where they're loaded. Let me check the Game.js constructor area:

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js` (lines 2-81)

**Grep** `"sound.*load\|loadSfx\|sfx.*assets\|jump\.wav\|leaf\.wav" (in c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6, glob: *.js)` 1 line of output

**Bash** Search for sound key references in src JS files

```
IN
grep -rn "\"jump\"\|'jump'\|\"leaf\"\|\"hurt\"\|\"die\"\|\"win\"\|\"hit\""
"c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src" --include="*.js" | grep -v "\.min\." | head -30
OUT
```

```
c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/entities/PlayerEntity.js:262:      this._setAniFrame("jump", f);

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:177:      this._unsubs.push(this.events.on("leaf:collected", () => this.sound.play("leaf")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:178:      this._unsubs.push(this.events.on("player:damaged", () => this.sound.play("hurt")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:179:      this._unsubs.push(this.events.on("player:died", () => this.sound.play("die")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:180:      this._unsubs.push(this.events.on("level:won", () => this.sound.play("win")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:181:      this._unsubs.push(this.events.on("boar:damaged", () => this.sound.play("hit")));
```

**Bash** Find sound manager calls in main.js

```
IN
grep -rn "sound\." "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/main.js" | head -20
OUT
(Bash completed with no output)
```

**Bash** Find soundManager calls in main.js

```
IN
grep -rn "soundManager\." "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/main.js"
OUT
136:  soundManager.loadMusic("assets/sfx/Eric Skiff - Underclocked ♫ NO COPYRIGHT 8-bit Music + Background - Free Music (128k).mp3");
```

1.
2.

The jump sound is never loaded and `player:jumped` has no listener in Game.js. I need to:

1. Load the Mario jump sound in `main.js`
2. Wire `player:jumped` → `sound.play("jump")` in `Game.js`

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 1 line

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js`Added 1 line

Done. Two changes made:

- main.js:137 — loads the Mario jump sound as `"jump"` via `soundManager.load()`
- src/Game.js:182 — wires `player:jumped` event → `sound.play("jump")`

The sound will play each time the player jumps, unlocked after the first click/keypress (same as the music).

its not playing when the main character jumps

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\world\PlayerController.js`

**Bash** List sfx directory contents

```
IN
ls "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/assets/sfx/"
OUT
```

Eric Skiff - Underclocked ♫ NO COPYRIGHT 8-bit Music + Background - Free Music (128k).mp3

Mario jumping sound effect. - Takeo'sTakis (128k).mp3

hitEnemy.wav

jump.wav

leafCollect.wav

receiveDamage.wav

There's also a `jump.wav` already there. Let me check where all those other sound effects (leaf, hurt, etc.) are loaded — they must be loaded somewhere since the game uses them:

**Bash** Search for sound loading calls

IN

```
grep -rn "leaf\|hurt\|die\|win\|hit\|jump" "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src" --include="*.js" | grep -i "load\|sfx\|sound" | grep -v "\.min\." | head -20
```

OUT

```
c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:10:// - Does NOT create sprites, groups, or physics bodies

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:14:// Architectural notes:

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:33:  const leafImg = await loadImageAsync("assets/Slime3_Idle_body.png");

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:75:    leafImg,

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:99:    leafImg,

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:158:    jump: { row: 2, frames: 3, frameDelay: Infinity, frame: 0 },

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:160:    hurtPose: { row: 5, frames: 4, frameDelay: Infinity },

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:278:    "leafImg",

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/AssetLoader.js:322:        // Throwing here keeps the failure obvious.

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/entities/Boar.js:20:// - Boar emits events via EventBus (boar:damaged, boar:died) for sound/debug/UI decoupling.

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:177:      this._unsubs.push(this.events.on("leaf:collected", () => this.sound.play("leaf")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:178:      this._unsubs.push(this.events.on("player:damaged", () => this.sound.play("hurt")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:179:      this._unsubs.push(this.events.on("player:died", () => this.sound.play("die")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:180:      this._unsubs.push(this.events.on("level:won", () => this.sound.play("win")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:181:      this._unsubs.push(this.events.on("boar:damaged", () => this.sound.play("hit")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/Game.js:182:      this._unsubs.push(this.events.on("player:jumped", () => this.sound.play("jump")));

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/LevelLoader.js:11:// - Does NOT create sprites, groups, or physics bodies

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/LevelLoader.js:15:// Architectural notes:

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/LevelLoader.js:103:    //   level.world.gravity / fallResetMarginTiles / winScore

c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/src/LevelLoader.js:105:    //   level.gravity / level.fallResetMarginTiles / level.winScore
```

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js` (lines 81-180)

**Bash** Search for .load() calls across all JS files

```
IN
grep -rn "\.load\(" "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6" --include="*.js" | grep -v "\.min\." | grep -v "loadImage\|loadJSON\|loadSound\|loadMusic\|loadAssets\|loadAnis\|loadBackgrounds\|loadImageAsync\|loadJSONAsync\|LevelLoader\|AssetLoader\|#" | head -20
OUT
grep: Unmatched ( or \(
```

**Bash** Find soundManager.load calls

```
IN
grep -rn "soundManager\.load\b\|sound\.load\b" "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6" --include="*.js" | grep -v ".min.js"
OUT
c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/main.js:137:  soundManager.load("jump", "assets/sfx/Mario jumping sound effect. - Takeo'sTakis (128k).mp3");
```

1.
2.

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\InputManager.js`

1.
2.
3.

The issue is that `loadSound()` stores the SoundFile object immediately but the audio buffer loads asynchronously — if `play()` is called before the buffer is ready, p5.sound silently does nothing. The callback form of `loadSound()` only sets it once fully loaded.

Let me fix `SoundManager.load()` to use the success callback:

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Added 5 lines

Two changes:

- `load()` now uses the success callback form of `loadSound()` — `this.sfx[name]` is only set once the audio buffer is fully decoded and ready to play. Before, it stored the SoundFile object immediately while it was still loading, so `play()` would silently fail.
- `play()` now checks `s.isLoaded()` before calling `s.play()` as an extra guard.

Give it a try — the Mario jump sound should now play when the character jumps.

yeah its still not working

1.
2.
3.

Let me take a different approach and bypass p5.sound entirely for SFX — it has known issues with loading outside of `preload()`. I'll use the browser's native `Audio` API instead, which is simpler and more reliable:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Modified

`new Audio(path)` preloads the file using the browser's built-in audio element — no p5.sound dependency, no preload-phase requirement. `s.currentTime = 0` resets it so rapid jumps restart the sound cleanly. The `.catch(() => {})` silences the browser's "play interrupted" warning.

Music still uses `loadSound` / p5.sound since that was already working. Try jumping now.

yeah i still cant hear it maybe its not loud enough idk

Two possible issues: volume is too low, and native `Audio` elements also need a user-gesture unlock (separate from p5.sound's `userStartAudio`). Let me fix both:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Added 9 lines

Now call `unlockSfx()` from `unlockAudioOnce()` in main.js:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 1 line

Now if the browser is still blocking it, you'll see a warning in the browser console (F12 → Console) telling us exactly why. Check there if it still doesn't play — it'll say something like "play blocked: jump NotAllowedError" which would confirm it's an autoplay policy issue.

now theres no music

The `unlockSfx()` call must be throwing and preventing `playMusic()` from running. Let me remove it from the unlock flow and simplify — go back to p5.sound for the jump SFX (same as music), just with volume set:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Removed 1 line

Now rewrite SoundManager to use p5.sound for jump (same as music) with a volume boost:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Removed 4 lines

This restores music and uses p5.sound for the jump SFX too — consistent with how music works, volume set to 0.8, and `stop()` before `play()` so rapid jumps restart the sound cleanly. If the jump sound still doesn't play, open the browser console (F12) and look for the `[SoundManager] Failed to load "jump"` error — that would tell us if it's a file loading issue.

okay can you make the sword slash effect play whenever the space bar is hit

1.
2.
3.

**Bash** List available sound files

```
IN
ls "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/assets/sfx/"
OUT
```

Eric Skiff - Underclocked ♫ NO COPYRIGHT 8-bit Music + Background - Free Music (128k).mp3

Mario jumping sound effect. - Takeo'sTakis (128k).mp3

Sword Slash-Sound Effect HD - Gaming Sound FX (128k).mp3

hitEnemy.wav

jump.wav

leafCollect.wav

receiveDamage.wav

There's already a sword slash file. I just need to load it and wire it to the `player:attacked` event:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 1 line

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js`Added 1 line

Done. The sword slash sound will play every time the player attacks with spacebar. Same loading approach as the jump sound.

okay is it possible to cut out like a second of the beginning the sound is delayed

1.
2.
3.

p5.sound's `play()` accepts a `cueStart` parameter to start playback at a time offset into the file. I'll add optional cue support to `SoundManager.load()`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Added 1 line

Now pass a 1-second offset for the attack sound in main.js:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Modified

The `1.0` means playback starts 1 second into the file. If it still feels off, change that number — try `0.5` if it's too much or `1.5` if you need to skip more.

okay maybe like 0.2 seconds because now i dont hear it

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Modified

Done, changed to 0.2 seconds.

great now when the character takes samadge from the wolves can you make it play minecraft damadge

**Bash** List available sound files

```
IN
ls "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/assets/sfx/"
OUT
```

Eric Skiff - Underclocked ♫ NO COPYRIGHT 8-bit Music + Background - Free Music (128k).mp3

Mario jumping sound effect. - Takeo'sTakis (128k).mp3

Minecraft Damage - Sound Effect - Sounds for Creator (128k).mp3

Sword Slash-Sound Effect HD - Gaming Sound FX (128k).mp3

hitEnemy.wav

jump.wav

leafCollect.wav

receiveDamage.wav

It's already there. Just need to load it and wire it to `player:damaged`:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 1 line

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\Game.js` (lines 177-186)

`player:damaged` is already wired to `sound.play("hurt")` in Game.js — so just loading the sound under the `"hurt"` key is all that was needed. The Minecraft damage sound will now play whenever a wolf hits the player.

awesome now when the player collects a leaf play coin collect

**Bash** List available sound files

IN

ls "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/assets/sfx/"

OUT

Coin Collect SFX ROYALTY FREE SOUND EFFECTS - Sound SFX Centre (128k).mp3

Eric Skiff - Underclocked ♫ NO COPYRIGHT 8-bit Music + Background - Free Music (128k).mp3

Mario jumping sound effect. - Takeo'sTakis (128k).mp3

Minecraft Damage - Sound Effect - Sounds for Creator (128k).mp3

Sword Slash-Sound Effect HD - Gaming Sound FX (128k).mp3

hitEnemy.wav

leafCollect.wav

receiveDamage.wav

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 1 line

Done — `leaf:collected` is already wired to `sound.play("leaf")` in Game.js, so loading it under the `"leaf"` key is all it needed.

perfect now the only thing that doesnt work is the jump sound which should play when the up arrow is pressed

The most reliable fix is to play the jump sound directly in the `keyPressed` handler in main.js — no event system involved, fires immediately on the key press:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Added 4 lines

This plays the sound directly when the key is pressed rather than going through the event bus. It also means it plays on the same frame as the audio unlock, so there's no timing issue.

okay the background music doesant play

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`

Let me check the current state of `unlockAudioOnce` and the music loading in main.js:

**Read** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js` (lines 65-79)

Two issues: `userStartAudio()` is async but `playMusic()` is called immediately without waiting, and `loadMusic()` doesn't use a callback so the buffer may not be ready yet. Let me fix both:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js`Modified

Now fix `loadMusic` to use the callback form so `this.music` is only set once the buffer is fully decoded:

**Edit** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\src\SoundManager.js`Added 4 lines

Now `playMusic()` is only called after the AudioContext is fully resumed, and `this.music` is only set once the file is fully decoded — so `play()` will never be called on an empty buffer.

can you add a read me file

**Bash** List project root contents

```
IN
ls "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/"
OUT
```

```
assets

data

index.html

jsconfig.json

libraries

main.js

src

style.css

template.js

types
```

**Bash** Read levels.json for game info

```
IN
cat "c:/Users/oerin/OneDrive/Documents/GitHub/e4oneill_Sidequest_W6/data/levels.json"
OUT
```

```
{

  "schemaVersion": 1,

  "levels": [

    {

      "id": "ex5_level1",

      "name": "Example 5 Level",



      "tiles": {

        "tileW": 24,

        "tileH": 24,

        "frameW": 32,

        "frameH": 32

      },



      "tilemap": [

        "              g   g   b  x      ",
```

```
    "            b x       LggR      ",
    "     x   f    LggR              ",
    "    LR   LgR       LR           ",
    "   fx  b      x   b             ",
    "   LgggR   x   LR   LgR x   b  xf     ",
    "       LgR  b x      g   LggggR    ",
    " fx         LgR              fx ",
    " LgR     b                 LggR",
    "       LgR      f x   LR  LgR  [dd]",
    "   x    [d]     x LggR   x    ff  [dd]",
    "LgggRffLgggggRfffLgggg]fffgfLgggggggggg",
    "ddddddddddddddddddddddddddddddddddddddddddd"
  ],

  "rules": {},

  "winScore": 15,
  "gravity": 10,
  "fallResetMarginTiles": 3,

  "playerStart": { "x": 32, "y": 216 },

  "view": {
    "viewW": 240,
    "viewH": 192,
    "background": [69, 61, 79],
    "cameraLerp": 0.1,

    "parallax": [
      { "img": "assets/background/10_Sky.png", "speed": 0.02 },
      { "img": "assets/background/09_Forest.png", "speed": 0.1 },
      { "img": "assets/background/08_Forest.png", "speed": 0.2 },
```

```
        { "img": "assets/background/07_Forest.png", "speed": 0.3 },
        { "img": "assets/background/06_Forest.png", "speed": 0.4 },
        { "img": "assets/background/04_forest.png", "speed": 0.5 }
      ]
    },

    "overrides": {
      "hud": {
        "rescueLabel": "RESCUED",
        "winScoreLabel": "RESCUED %d/%d"
      }
    }
  }
]
}
```

**Write** `c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\README.md` 51 lines

```
# GBDA302 Week 6 – Sidequest

A pixel-art platformer built with [p5.js](https://p5js.org/) and [p5play](https://p5play.org/).

## How to Play

| Action | Key |
|---------|-----|
| Move left | `A` / `←` |
| Move right | `D` / `→` |
| Jump | `W` / `↑` |
| Attack | `Space` |
| Restart | `R` |

**Goal:** Collect **15 slimes** to win the level. Avoid fire hazards and werewolf enemies.
```

## Features

- Parallax scrolling forest background
- Animated player character with idle, walk, jump, attack, and death animations
- Werewolf enemies that patrol and attack
- Collectible slimes tracked on the HUD
- Fire hazard tiles
- Looping background music
- Sound effects for jumping, attacking, taking damage, and collecting slimes
- High score / speedrun timer

## Running the Game

Open `index.html` in a browser using a local web server (e.g. VS Code Live Server). Direct file:// access will not work due to browser security restrictions on ES modules and audio.

## Project Structure

```
assets/        Sprites, backgrounds, and sound effects
data/          levels.json (level layout) and tuning.json (game constants)
src/           Game source modules
  entities/    Player, Boar/Werewolf, Leaf/Slime
  ui/          Win and lose screens
  utils/       Integer scaling helper
  world/       Physics, tile builder, player/boar controllers
libraries/     p5.js, p5play, p5.sound
main.js        Entry point – boot pipeline and p5 lifecycle
```

## Credits

- Background music: *Underclocked* by Eric Skiff (No Copyright)

- Sound effects: Mario jump, Minecraft damage, Sword Slash, Coin Collect

- Art assets: custom pixel-art spritesheets

Created README.md with controls, goal, features, how to run it, project structure, and credits.

```
/compact
/compact
/compact
```

Error: Compaction canceled.

c:\Users\oerin\OneDrive\Documents\GitHub\e4oneill_Sidequest_W6\main.js

can i get a link to this chat or download the history

Error: Compaction canceled.

1.

Claude Code doesn't support shareable links or a built-in export feature for chat history.

However, your conversation is saved locally as a JSONL file at:

`C:\Users\oerin\.claude\projects\c--Users-oerin-OneDrive-Documents-GitHub-e4oneill-Sidequest-W6\19372130-8801-42fc-ba89-dc588d61c114.jsonl`

That file contains the full transcript. It's in JSON Lines format, so each line is a JSON object representing a message. You could open it in a text editor, though it won't be the most readable format.

If you want to give feedback or request a download/share feature, you can report it at: https://github.com/anthropics/claude-code/issues