

Branch & Bound and Knapsack Lab

Objectives

- Perform the branch and bound algorithm
- Apply branch and bound to the knapsack problem
- Understand the geometry of the branch and bound algorithm

Brief description: In this lab, we will try solving an example of a knapsack problem with the branch-and-bound algorithm. We will also see how adding a cutting plane helps in reducing the computation time and effort of the algorithm. Lastly, we will explore the geometry of the branch and bound algorithm.

```
In [1]: # imports -- don't forget to run this cell
import pandas as pd
import gilp
from gilp.visualize import feasible_integer_pts
from ortools.linear_solver import pywraplp as OR
```

Part 1: Branch and Bound Algorithm

Recall that the branch and bound algorithm (in addition to the simplex method) allows us to solve integer programs. Before applying the branch and bound algorithm to the knapsack problem, we will begin by reviewing some core ideas. Furthermore, we will identify a helpful property that will make branch and bound terminate quicker later in the lab!

Q1: What are the different ways a node can be fathomed during the branch and bound algorithm? Describe each.

A: A node can be fathomed if its value violates a lower or upper bound as set by a previously found optimal value.

Q2: Suppose you have a maximization integer program and you solve its linear program relaxation. What does the LP-relaxation optimal value tell you about the IP optimal value? What if it is a minimization problem?

A: Its linear program relaxation will be an upper bound for the integer problem optimal value. If it is a minimization problem, its linear program relaxation will be a lower bound for the integer problem optimal value.

Q3: Assume you have a maximization integer program with all integral coefficients in the objective function. Now, suppose you are running the branch and bound algorithm and come across a node with an optimal value of 44.5. The current incumbent is 44. Can you fathom this node? Why or why not?

A: You can fathom this node because it is higher than the previous optimum value, which sets an upper bound for the optimal value.

Q4: If the optimal solution to the LP relaxation of the original program is integer, then you have

found an optimal solution to your integer program. Explain why this is true.

A: Continuing the branch-and-bound algorithm can only result in more constraints added to the original problem which restricts the solution even more. If a better solution was not found by solving the linear problem relaxation, then a better integer solution does not exist.

Q5: If the LP is infeasible, then the IP is infeasible. Explain why this is true.

A: Since the LP is a relaxation of the IP, this means that no solution, integer or otherwise, exists for the LP. Since no integer solution exists, no solution to the corresponding LP exists.

The next questions ask about the following branch and bound tree. If the solution was not integral, the fractional x_i that was used to branch is given. If the solution was integral, it is denoted INT . In the current iteration of branch and bound, you are looking at the node with the *.



Q6: Can you determine if the integer program this branch and bound tree is for is a minimization or maximization problem? If so, which is it?

A: It is for a minimization problem because the optimal values are increasing every time.

Hint: For **Q7-8**, you can assume integral coefficients in the objective function.

Q7: Is the current node (marked z^*) fathomed? Why or why not? If not, what additional constraints should be imposed for each of the next two nodes?

A: It is not because it is not breaking the lower bound set by the previous iteration. The constraint that should be added is $x \geq 1$ and $x \leq 0$

Q8: Consider the nodes under the current node (where $z = 16.3$). What do you know about the optimal value of these nodes? Why?

A: The optimal value of these nodes must be greater than or equal to 16.3 since the previous optimal value sets a lower bound on the optimal values of subsequent iterations.

Part 2: The Knapsack Problem

In this lab, you will solve an integer program by branch and bound. The integer program to be solved will be a knapsack problem.

Knapsack Problem: We are given a collection of n items, where each item $i = 1, \dots, n$ has a weight w_i and a value v_i . In addition, there is a given capacity W , and the aim is to select a maximum value subset of items that has a total weight at most W . Note that each item can be brought at most once.

$$\begin{aligned}
 \max \quad & \sum_{i=1}^n v_i x_i \\
 \text{s.t.} \quad & \sum_{i=1}^n w_i x_i \leq W \\
 & 0 \leq x_i \leq 1, \text{ integer}, i = 1, \dots, n
 \end{aligned}$$

Consider the following data which we import from a CSV file:

```
In [2]: data = pd.read_csv('knapsack_data_1.csv', index_col=0)
        data
```

```
Out[2]:
```

	value	weight
item		
1	50	10
2	30	12
3	24	10
4	14	7
5	12	6
6	10	7
7	40	30

and $W = 18$.

Q9: Are there any items we can remove from our input to simplify this problem? Why? If so, replace `index` with the item number that can be removed in the code below. Hint: how many of each item could we possibly take?

A: Item 7 because its weight is greater than the maximum total weight.

```
In [3]: # TODO: replace index
        data = data.drop(7)
```

Q10: If we remove item 7 from the knapsack, it does not change the optimal solution to the integer program. Explain why.

A: Item 7 could have never been in any optimal solution so by removing this item, it does not change any feasible solutions to the problem.

Q11: Consider removing items i such that $w_i > W$ from a knapsack input. How does the LP relaxation's optimal value change?

A: It grows closer the the optimal value of the associated IP.

In **Q10-11**, you should have found that removing these items removes feasible solutions from the linear program but does not change the integer program. This is desirable as the gap between the optimal IP and LP values can become smaller. By adding this step, branch and bound may terminate sooner.

Recall that a branch and bound node can be fathomed if its bound is no better than the value of the best feasible integer solution found thus far. Hence, it helps to have a good feasible integer solution as quickly as possible (so that we stop needless work). To do this, we can first try to construct a good feasible integer solution by a reasonable heuristic algorithm before starting to run the branch and bound procedure.

In designing a heuristic for the knapsack problem, it is helpful to think about the value per unit weight for each item. We compute this value in the table below.

```
In [4]: data['value per unit weight'] = (data['value'] / data['weight']).round(2)
data
```

```
Out[4]:
```

	value	weight	value per unit weight
1	50	10	5.00
2	30	12	2.50
3	24	10	2.40
4	14	7	2.00
5	12	6	2.00
6	10	7	1.43

item			
1	50	10	5.00
2	30	12	2.50
3	24	10	2.40
4	14	7	2.00
5	12	6	2.00
6	10	7	1.43

Q12: Design a reasonable heuristic for the knapsack problem. Note a heuristic aims to find a decent solution to the problem (but is not necessarily optimal).

A: The heuristic will select items in order from highest value per unit weight and continuing adding items until the max weight is reached.

Q13: Run your heuristic on the data above to compute a good feasible integer solution. Your heuristic should generate a feasible solution with a value of 64 or better. If it does not, try a different heuristic (or talk to your TA!)

A: Items 1 and 4

We will now use the branch and bound algorithm to solve this knapsack problem! First, let us define a mathematical model for the linear relaxation of the knapsack problem.

Q14: Complete the model below.

```
In [5]: def Knapsack(table, capacity, integer = False):
        """Model for solving the Knapsack problem.

        Args:
            table (pd.DataFrame): A table indexed by items with a column for value and
            capacity (int): An integer-capacity for the knapsack
            integer (bool): True if the variables should be integer. False otherwise
        """
        ITEMS = list(table.index)          # set of items
        v = table.to_dict()['value']        # value for each item
        w = table.to_dict()['weight']       # weight for each item
        W = capacity                       # capacity of the knapsack
```

```

# define model
m = OR.Solver('knapsack', OR.Solver.CBC_MIXED_INTEGER_PROGRAMMING)

# decision variables
x = {}
for i in ITEMS:
    if integer:
        x[i] = m.IntVar(0, 1, 'x_%d' % (i))
    else:
        x[i] = m.NumVar(0, 1, 'x_%d' % (i))

# define objective function here
m.Maximize(sum(v[i]*x[i] for i in ITEMS))

# TODO: Add a constraint that enforces that weight must not exceed capacity
# recall that we add constraints to the model using m.Add()
m.Add(sum(w[i]*x[i] for i in ITEMS) <= W)

return (m, x) # return the model and the decision variables

```

```

In [6]: # You do not need to do anything with this cell but make sure you run it!
def solve(m):
    """Used to solve a model m."""
    m.Solve()

    print('Objective =', m.Objective().Value())
    print('iterations :', m.iterations())
    print('branch-and-bound nodes :', m.nodes())

    return ({var.name() : var.solution_value() for var in m.variables()})

```

We can now create a linear relaxation of our knapsack problem. Now, `m` represents our model and `x` represents our decision variables.

```
In [7]: m, x = Knapsack(data, 18)
```

We can use the next line to solve the model and output the solution

```
In [8]: solve(m)
```

```

Objective = 70.0
iterations : 0
branch-and-bound nodes : 0

```

```

Out[8]: {'x_1': 1.0,
         'x_2': 0.6666666666666667,
         'x_3': 0.0,
         'x_4': 0.0,
         'x_5': 0.0,
         'x_6': 0.0}

```

Q15: How does this optimal value compare to the value you found using the heuristic integer solution?

A: The optimal value of is higher than the value from the heuristic.

Q16: Should this node be fathomed? If not, what variable should be branched on and what additional constraints should be imposed for each of the next two nodes?


```
In [11]: # Template
m, x = Knapsack(data, 18)
# Add constraints here
m.Add(x[2] <= 0)
m.Add(x[4] >= 1)
m.Add(x[5] <= 0)
solve(m)
# fathomed? no
```

```
Objective = 66.4
iterations : 0
branch-and-bound nodes : 0
```

```
Out[11]: {'x_1': 1.0,
          'x_2': 0.0,
          'x_3': 0.100000000000000009,
          'x_4': 1.0,
          'x_5': 0.0,
          'x_6': 0.0}
```

```
In [12]: # Template
m, x = Knapsack(data, 18)
# Add constraints here
m.Add(x[2] <= 0)
m.Add(x[4] >= 1)
m.Add(x[5] <= 0)
m.Add(x[3] <= 0)
solve(m)
# fathomed? no
```

```
Objective = 65.42857142857143
iterations : 0
branch-and-bound nodes : 0
```

```
Out[12]: {'x_1': 1.0,
          'x_2': 0.0,
          'x_3': 0.0,
          'x_4': 1.0,
          'x_5': 0.0,
          'x_6': 0.14285714285714302}
```

```
In [13]: # Template
m, x = Knapsack(data, 18)
# Add constraints here
m.Add(x[2] <= 0)
m.Add(x[4] >= 1)
m.Add(x[5] <= 0)
m.Add(x[3] <= 0)
m.Add(x[6] <= 0)
solve(m)
# fathomed?
```

```
Objective = 64.0
iterations : 0
branch-and-bound nodes : 0
```

```
Out[13]: {'x_1': 1.0, 'x_2': 0.0, 'x_3': 0.0, 'x_4': 1.0, 'x_5': 0.0, 'x_6': 0.0}
```

A: Items 1 and 4

Q21: How many nodes did you have to explore while running the branch and bound algorithm?

A: 5

In the next section, we will think about additional constraints we can add to make running

branch and bound quicker.

Part 3: Cutting Planes

In general, a cutting plane is an additional constraint we can add to an integer program's linear relaxation that removes feasible linear solutions but does not remove any integer feasible solutions. This is very useful when solving integer programs! Recall many of the problems we have learned in class have something we call the "integrality property". This is useful because it allows us to ignore the integrality constraint since we are guaranteed to reach an integral solution. By cleverly adding cutting planes, we strive to remove feasible linear solutions (without removing any integer feasible solutions) such that the optimal solution to the linear relaxation is integral!


Consider an integer program whose linear program relaxation is


$$\begin{aligned} \max \quad & 2x_1 + x_2 \\ \text{s.t.} \quad & x_1 + x_2 \leq 3 \\ & 2x_1 \leq 5 \\ & -x_1 + 2x_2 \leq 2 \\ & x_1, x_2 \geq 0 \end{aligned}$$

We can define this linear program and then visualize its feasible region. The integer points have been highlighted.

```
In [14]: lp = gilp.LP([[1,1],[2,0],[-1,2]],
                    [3,5,2],
                    [2,1])
fig = gilp.lp_visual(lp)
fig.set_axis_limits([3.5,2])
fig.add_trace(feasible_integer_pts(lp, fig))
fig
```

Geometric Interpretation of LPs





Q22: List every feasible solution to the integer program.

A: (0,0),(1,0),(2,0),(0,1),(1,1),(1,2)


Q23: Is the constraint $x_2 \leq 1$ a cutting plane? Why? (Hint: Would any feasible integer points become infeasible? What about feasible linear points?)

A: Yes because the highest x_2 value that a feasible integer solution can have is 1.

Let's add this cutting plane to the LP relaxation!

```
In [15]: lp = gilp.LP([[1,1],[2,0],[-1,2],[0,1]],
                    [3,5,2,1],
                    [2,1])
fig = gilp.lp_visual(lp)
fig.set_axis_limits([3.5,2])
fig.add_trace(feasible_integer_pts(lp, fig))
fig
```

Geometric Interpretation of LPs



Q24: Is the constraint $x_1 \leq 3$ a cutting plane? Why?

A: No because it does not limit the domain of solutions that we already have.


Q25: Can you provide another cutting plane? If so, what is it?

A: $x_1 \leq 2$

Let's look at the feasible region after adding the cutting plane from **Q23** and one of the possible answers from **Q25**. Notice the optimal solution to the LP relaxation is now integral!

```
In [16]: lp = gilp.LP([[1,1],[2,0],[-1,2],[0,1],[1,0]],
                    [3,5,2,1,2],
                    [2,1])
fig = gilp.lp_visual(lp)
fig.set_axis_limits([3.5,2])
fig.add_trace(feasible_integer_pts(lp, fig))
fig
```

Geometric Interpretation of LPs



Let's try applying what we know about cutting planes to the knapsack problem! Again, recall our input was $W = 18$ and:

```
In [17]: data
```

```
Out[17]:
```

	value	weight	value per unit weight
item			

	value	weight	value per unit weight
item			
1	50	10	5.00
2	30	12	2.50
3	24	10	2.40
4	14	7	2.00
5	12	6	2.00
6	10	7	1.43

Q26: Look at items 1, 2, and 3. How many of these items can we take simultaneously? Can you write a new constraint to capture this? If so, please provide it.

A: $x_1 + x_2 + x_3 \leq 1$

Q27: Is the constraint you found in **Q26** a cutting plane? If so, provide a feasible solution to the linear program relaxation that is no longer feasible (i.e. a point the constraint *cuts off*).

A: Yes. (1,0.6667,0,0,0,0)

Q28: Provide another cutting plane involving items 4,5 and 6 for this integer program. Explain how you derived it.

A: $x_4 + x_5 + x_6 \leq 2$. Only 2 of these items are able to be taken before it goes over the weight limit.

Q29: Add the cutting planes from **Q26** and **Q28** to the model and solve it. You should get a solution in which we take items 1 and 4 and $\frac{1}{6}$ of item 5 with an objective value of 66.

```
In [18]: m, x = Knapsack(data, 18)
# TODO: Add cutting planes here
m.Add(x[1] + x[2] + x[3] <= 1)
m.Add(x[4] + x[5] + x[6] <= 2)
solve(m)
```

```
Objective = 66.0
iterations : 0
branch-and-bound nodes : 0
```

```
Out[18]: {'x_1': 1.0,
          'x_2': 0.0,
          'x_3': 0.0,
          'x_4': 1.0,
          'x_5': 0.16666666666666666,
          'x_6': 0.0}
```

Let's take a moment to pause and reflect on what we are doing. Recall from **Q9-11** that we dropped item 7 because its weight was greater than the capacity of the knapsack. Essentially we added the constraint $x_7 \leq 0$. This constraint was a cutting plane! It eliminated some linear feasible solutions but no integer ones. By adding these two new cutting planes, we can get branch and bound to terminate earlier yet again! So far, we have generated cutting planes by inspection. However, there are more algorithmic ways to identify them (which we will ignore for now).

If we continue running the branch and bound algorithm, we will eventually reach the branch and bound tree below where the z^* indicates the current node we are looking at.



NOTE: Do not forget about the feasible integer solution our heuristic gave us with value 64.

Q30 Finish running branch and bound to find the optimal integer solution. Use a separate cell for each node you solve and indicate if the node was fathomed with a comment. Hint: Don't forget the cutting plane constraints should be included in every node of the branch and bound tree.

```
In [19]: # Template
m, x = Knapsack(data, 18)
# Add constraints here
m.Add(x[1] + x[2] + x[3] <= 1)
m.Add(x[4] + x[5] + x[6] <= 2)
m.Add(x[5] >= 1)
m.Add(x[4] <= 0)
solve(m)
# fathomed? no
```

```
Objective = 64.85714285714286
iterations : 0
branch-and-bound nodes : 0
```

```
Out[19]: {'x_1': 1.0,
          'x_2': 0.0,
          'x_3': 0.0,
          'x_4': 0.0,
          'x_5': 1.0,
          'x_6': 0.28571428571428586}
```

```
In [20]: # Template
m, x = Knapsack(data, 18)
# Add constraints here
m.Add(x[1] + x[2] + x[3] <= 1)
m.Add(x[4] + x[5] + x[6] <= 2)
m.Add(x[5] >= 1)
m.Add(x[4] <= 0)
m.Add(x[6] <= 0)
solve(m)
# fathomed? no
```

```
Objective = 62.0
iterations : 0
branch-and-bound nodes : 0
```

```
Out[20]: {'x_1': 1.0, 'x_2': 0.0, 'x_3': 0.0, 'x_4': 0.0, 'x_5': 1.0, 'x_6': 0.0}
```

```
In [ ]:
```

A: Items 1 and 5

Q31: Did you find the same optimal solution? How many nodes did you explore? How did this compare to the number you explored previously?

A: No. 3 nodes. This value is less than the value found previously

Part 4: Geometry of Branch and Bound


Previously, we used the `gilp` package to visualize the simplex algorithm but it also has the functionality to visualize branch and bound. We will give a quick overview of the tool. Similar to `lp_visual` and `simplex_visual`, the function `bnb_visual` takes an LP and returns a visualization. It is assumed that every decision variable is constrained to be integer. Unlike previous visualizations, `bnb_visual` returns a series of figures for each node of the branch and bound tree. Let's look at a small 2D example:

$$\begin{aligned} \max \quad & 5x_1 + 8x_2 \\ \text{s.t.} \quad & x_1 + x_2 \leq 6 \\ & 5x_1 + 9x_2 \leq 45 \\ & x_1, x_2 \geq 0, \quad \text{integral} \end{aligned}$$

```
In [21]: nodes = gilp.bnb_visual(gilp.examples.STANDARD_2D_IP)
```

```
In [22]: nodes[0].show()
```

Geometric Interpretation of LPs



Run the cells above to generate a figure for each node and view the first node. At first, you will see the LP relaxation on the left and the root of the branch and bound tree on the right. The simplex path and isoprofit slider are also present.

Q32: Recall the root of a branch and bound tree is the unaltered LP relaxation. What is the optimal solution? (Hint: Use the objective slider and hover over extreme points).

A: (2.25,3.75)

Q33: Assume that we always choose the variable with the minimum index to branch on if there are multiple options. Write down (in full) each of the LPs we get after branching off the root node.

A: Written in image in Q34

Q34: Draw the feasible region to each of the LPs from **Q33** on the same picture.

A:

Branch-and-Bound Lab

$$\max S_{x_1} + 8x_2$$

$$\text{s.t. } x_1 + x_2 \leq 6$$

$$5x_1 + 9x_2 \leq 45$$

$$x_1 \leq 2$$

$$x_1, x_2 \geq 0, \text{ integer}$$


$$\max S_{x_1} + 8x_2$$

$$\text{s.t. } x_1 + x_2 \leq 6$$

$$5x_1 + 9x_2 \leq 45$$

$$x_1 \geq 3$$


$$x_1, x_2 \geq 0, \text{ integer}$$



Run the following cell to see if the picture you drew in **Q34** was correct.

In [23]: `nodes[1].show()`

Geometric Interpretation of LPs



The outline of the original LP relaxation is still shown on the left. Now that we have eliminated some of the fractional feasible solutions, we now have 2 feasible regions to consider. The darker one is the feasible region associated with the current node which is also shaded darker in the branch and bound tree. The unexplored nodes in the branch and bound tree are not shaded in.

Q35: Which feasible solutions to the LP relaxation are removed by this branch?


A: Solutions where $2 < x_1 < 3$


Q36: At the current (dark) node, what constraints will we add? How many feasible regions will the original LP relaxation be broken into?

A: $x_2 \geq 4$, $x_2 \leq 3$. It will be broken up into 3 feasible solutions.

In [24]: `nodes[2].show()`

Geometric Interpretation of LPs





Q37: What is the optimal solution at the current (dark) node? Do we have to further explore this branch? Explain.

A: (2,3). No because this is a feasible integer solutions.

Q38: Recall shaded nodes have been explored and the node shaded darker (and feasible region shaded darker) correspond to the current node and its feasible region. Nodes not shaded have not been explored. How many nodes have not yet been explored?


A: 2


Q39: How many nodes have a degree of one in the branch and bound tree? (That is, they are only connected to one edge). These nodes are called leaf nodes. What is the relationship between the leaf nodes and the remaining feasible region?

A: 3. The leaf nodes are the nodes and regions that have not yet been explored and the nodes and regions that have most recently been explored.

```
In [25]: # Show the next two iterations of the branch and bound algorithm
nodes[3].show()
nodes[4].show()
```

Geometric Interpretation of LPs






$x_2 \leq 3$
34
 $x^* = (2, 3)$

Objective
0.0 1

Geometric Interpretation of LPs



Constraint(s)
--- $x_1 \leq 1$
--- $x_1 \geq 2$

$x_1 \leq 2$
41.111
 $x^* = (2, 3.88)$

$x_2 \leq 3$
34
 $x^* = (2, 3)$

$x_1 \leq 1$
40.556
 $x^* = (1, 4.4)$

Objective
0.0

Q40: At the current (dark) node, we added the constraint $x_1 \leq 1$. Why were the fractional solutions $1 < x_1 < 2$ not eliminated for $x_2 \leq 3$?


A: That constraint is redundant so it is not necessary to show this constraint.

```
In [26]: # Show the next three iterations of the branch and bound algorithm
nodes[5].show()
nodes[6].show()
nodes[7].show()
```


Geometric Interpretation of LPs




Constraint(s)
--- $x_2 \leq 4$



Geometric Interpretation of LPs



Geometric Interpretation of LPs





Q41: What constraints are enforced at the current (dark) node? Why are there no feasible solutions at this node?

A: $x_1 \leq 2$, $x_2 \geq 4$, $x_1 \geq 2$. There are no feasible solutions here because x_1 must equal 2 with the constraints. The corresponding x_2 value to this value of x_1 is less than 4, so there is no feasible solution.

In [27]: `nodes[8].show()`

Geometric Interpretation of LPs





Q42: Are we done? If so, what nodes are fathomed and what is the optimal solution? Explain.


A: We are done because the nodes that are left are either fathomed or feasible integer solutions. We have fathomed $x_2 \leq 3$ and $x_1 \geq 2$. The optimal solution is $(0, 5)$.

Let's look at branch and bound visualization for an integer program with 3 decision variables!

```
In [28]: nodes = gilp.bnb_visual(gilp.examples.VARIED_BRANCHING_3D_IP)
```

```
In [29]: # Look at the first 3 iterations
nodes[0].show()
nodes[1].show()
nodes[2].show()
```

Geometric Interpretation of LPs




Geometric Interpretation of LPs


Constraint(s)

$x_1 < 2$

$x_2 \leq 2$
 $x_2 \geq 3$




$x_2 \leq 2$
12.8
 $x^* = (1.2, 2, 2.4)$



Geometric Interpretation of LPs


Constraint(s)

$x_1 \leq 1$
 $x_1 \geq 2$



$x_2 \leq 2$
12.8
 $x^* = (1.2, 2, 2.4)$


$x_1 \leq 1$
12.5
 $x^* = (1, 2, 2.5)$



Let's fast-forward to the final iteration of the branch and bound algorithm.

```
In [30]: nodes[-1].show()
```

Geometric Interpretation of LPs



Q43: Consider the feasible region that looks like a rectangular box with one corner point at the origin. What node does it correspond to in the tree? What is the optimal solution at that node?

A: $x_3 \leq 2$, (1,2,2)

Q44: How many branch and bound nodes did we explore? What was the optimal solution? How many branch and bound nodes would we have explored if we knew the value of the optimal solution before starting branch and bound?

A: We explored 13 nodes. The optimal solution is (0,3,1). We would have only have to explore 2 nodes if we knew the optimal solution before starting branch and bound.

Bonus: Branch and Bound for Knapsack

Consider the following example:

item	value	weight
1	2	1
2	9	3
3	6	2

The linear program formulation will be:


$$\begin{aligned} \max \quad & 2x_1 + 9x_2 + 6x_3 \\ \text{s.t.} \quad & 1x_1 + 3x_2 + 2x_3 \leq 10 \\ & x_1, x_2, x_3 \geq 0, \quad \text{integer} \end{aligned}$$

In gilp, we can define this lp as follows:

```
In [31]: lp = gilp.LP([[1,3,2]],
                     [10],
                     [2,9,6])

for fig in gilp.bnb_visual(lp):
    fig.show()
```

Geometric Interpretation of LPs



Objective V


0.0 13.0


Geometric Interpretation of LPs

Constraint(s)


$$x_2 \leq 3$$

$$x_2 \geq 4$$






$x_2 \leq 3$
30
 $x^* = (0, 3, 0.5)$



Geometric Interpretation of LPs


Constraint(s)

- $x_3 \leq 0$
- $x_3 \geq 1$



$x_2 \leq 3$
30
 $x^* = (0, 3, 0.5)$


$x_3 \leq 0$
29
 $x^* = (1, 3, 0)$





Geometric Interpretation of LPs

Constraint(s)

- $x_3 \leq 0$
- $x_3 \geq 1$







Geometric Interpretation of LPs

Constraint(s)


- $x_2 \leq 2$
- $x_2 \geq 3$




Geometric Interpretation of LPs


Constraint(s)

- $x_2 \leq 2$
- $x_2 \geq 3$







Geometric Interpretation of LPs



Constraint(s)

- $x_2 \leq 3$
- $x_2 \geq 4$



In []: