

Cincinnati Fire Department Fire Training Supplement DRILL BOOK

SECTION #8 Minimum Company Standards

Date: January 2006

TOPIC TITLE:

Reverse Lead to Fire Department Connection

Total # of Pages: 2
Topic #: 9

Title:

Sprinkler / Standpipe Supply and Operations

Task Level:

Section #: 8

Company (4 personnel)

Equipment Needed:

Engine Company, 5" Supply Line, 2-1/2" supply hose, Hydrant

Safe location without traffic safety hazards

Recommended Time:

3 minutes and 30 seconds

Reference:

NFPA 1410, 2000 Edition, Training for Initial Scene Operations

Instruction:

• Stage Engine Company and assigned personnel away from fire area. When personnel are ready, give signal and proceed to the area.

• TIME STARTS WHEN ENGINE STOPS AT FIRE AREA.

 Remove 5" supply, 3-way wye, necessary adapters and 2-1/2" hose

• Reverse Lay 5" supply line a distance of 300 feet.

• FAO hooks into hydrant upon arrival at hydrant.

• Supply FDC with 2-1/2" supply line (2 LINES)

• Officer calls for water when the line is advanced

• Flow 500 GPM from the initial hose line into the FDC

• FAO transfers from the tank to the hydrant

• Stop the time when all lines are supplied and flowing properly

Evaluation: Pass or Fail

Re-Testing: If companies fail to meet the required time limit or are stopped due to unsafe

acts they will be given an additional opportunity to pass the evolution in one

month.

<u>Critical Criteria:</u> Failure to meet time limit

Failure to wear full PPE

Failure to advance proper length of hose

Failure to supply proper GPM

Failure to transfer from tank to hydrant supply properly. Up to 10 second interruption in water supply deliver is acceptable, more than 10 seconds is

unacceptable

Unsafe acts as interpreted by the evaluator



Cincinnati Fire Department Fire Training Supplement DRILL BOOK

SECTION #8 Minimum Company Standards

Date: January 2006

Section #: 8

TOPIC TITLE:Reverse Lead to Fire Department Connection

Total # of Pages: 2
Topic #: 9

Topic Number 9 Description

