


|   |   |   |
|---|---|---|
|  | <b>Cincinnati Fire Department<br/>Fire Training Supplement<br/>DRILL BOOK</b> | <b>SECTION #8<br/>Minimum<br/>Company<br/>Standards</b> |
| Date: January 2006  | <b>TOPIC TITLE:</b>   | Total # of Pages: 2                                     |
| Section #: 8  | Ground Ladder Deployment – Parallel Raise                                     | Topic #: 11   |

**Title:** Ground Ladder Deployment – Parallel Raise

**Task Level:** Company (4 personnel)

**Equipment Needed:** Ladder Company with 28' Ladder and 35' Ladder  
Safe location without traffic safety hazards

**Recommended Time:** 4 minutes

**Instruction:**


- Stage Ladder Company and assigned personnel at fire area. When personnel are ready, give signal and personnel are to exit apparatus.
- TIME STARTS WHEN PERSONNEL EXIT THE APPARATUS.
- Remove a 28 foot ladder and place at second story window to be used for RAT.
- Remove a 35 foot ladder and place at Roof level to be used to move onto and off the roof
- Stop the time when all ladders are raised in their designated location

**Evaluation:** Pass or Fail

**Re-Testing:** If companies fail to meet the required time limit or are stopped due to unsafe acts they will be given an additional opportunity to pass the evolution in one month.

**Critical Criteria:**

Failure to meet time limit  
Failure to wear full PPE  
Failure to properly set the ladder (improper climbing angle)  
Dropping the ladder  
Operating within 10 feet of overhead power lines  
Unsafe acts as interpreted by the evaluator

|   |   |  |
|---|---|--|
|  | <b>Cincinnati Fire Department<br/>Fire Training Supplement<br/>DRILL BOOK</b> | <b>SECTION #8</b><br>Minimum<br>Company<br>Standards |
| Date: January 2006  | <b>TOPIC TITLE:</b>   | Total # of Pages: 2                                  |
| Section #: 8  | Ground Ladder Deployment – Parallel Raise                                     | Topic #: 11  |

### Topic #11 Description

