

structs and classes

structs and classes

Way to design a reusable data model

Create the model once and generate copies of it

Define a set of characteristics and actions

Define a set of **variables** and **functions**

class

struct


Model and instance

Model > define characteristics and actions


Instance > copy what was defined by the model

Any update on the Model affect its instances

Instances represent elements from the same "domain"



Model and instance




Model and instance




Model and instance



Model and instance



Model and instance




Model and instance




Model and instance



Model and instance



Model and instanc



struct

```
// Declaring the data model  
struct Person {
```

```
}
```

```
// Declaring the data model
```

```
struct Person {
```

```
}
```

```
// Declaring the data model
```

```
struct Person {
```

```
    var name: String
```

```
    var talkText: String
```

```
}
```



```
// Declaring the data model
```

```
struct Person {
```

```
    var name: String
```

```
    var talkText: String
```

```
}
```

```
// Declaring the data model
```

```
struct Person {
```

```
    var name: String
```

```
    var talkText: String
```

```
    func talk(){
```

```
        print(talkText)
```

```
}
```

```
}
```

```
// Declaring the data model
```

```
struct Person {
```

```
    var name: String
```

```
    var talkText: String
```

```
    func talk(){
```

```
        print(talkText)
```

```
    }
```

```
}
```

```
// Declaring the data model
struct Person {
    var name: String
    var talkText: String

    func talk(){
        print(talkText)
    }
    // Declaring the initializer
    init(name: String, talkText: String = "Olá") {
        self.name = name
        self.talkText = talkText
    }
}
```

```
// Declaring the data model
```

```
struct Person {
```

```
    var name: String
```

```
    var talkText: String
```

```
    func talk(){
```

```
        print(talkText)
```

```
    }
```

```
// Declaring the initializer
```

```
init(name: String, talkText: String = "Olá") {
```

```
    self.name = name
```

```
    self.talkText = talkText
```

```
}
```

```
}
```

```
// Declaring the data model
struct Person {
    var name: String
    var talkText: String

    func talk(){
        print(talkText)
    }
    // Declaring the initializer
    init(name: String, talkText: String = "Olá") {
        self.name = name
        self.talkText = talkText
    }
}
```

```
// Declaring the data model
struct Person {
    var name: String
    var talkText: String

    func talk(){
        print(talkText)
    }
    // Declaring the initializer
    init(name: String, talkText: String = "Olá") {
        self.name = name
        self.talkText = talkText
    }
}

// Creating an instance of the data model
var eu: Person = Person(name: "Danilo")
```

```
// Declaring the data model
struct Person {
    var name: String
    var talkText: String

    func talk(){
        print(talkText)
    }
    // Declaring the initializer
    init(name: String, talkText: String = "Olá") {
        self.name = name
        self.talkText = talkText
    }
}
```

```
// Creating an instance of the data model
var eu: Person = Person(name: "Danilo")
```



```
// Declaring the data model
struct Person {
    var name: String
    var talkText: String

    func talk(){
        print(talkText)
    }
    // Declaring the initializer
    init(name: String, talkText: String = "Olá") {
        self.name = name
        self.talkText = talkText
    }
}

// Creating an instance of the data model
var eu: Person = Person(name: "Danilo")
```

```
// Declaring the data model
struct Person {
    var name: String
    var talkText: String

    func talk(){
        print(talkText)
    }
    // Declaring the initializer
    init(name: String, talkText: String = "Olá") {
        self.name = name
        self.talkText = talkText
    }
}

// Creating an instance of the data model
var eu: Person = Person(name: "Danilo")
```

```
// Declaring the data model
struct Person {
    var name: String
    var talkText: String

    func talk(){
        print(talkText)
    }
    // Declaring the initializer
    init(name: String, talkText: String = "Olá") {
        self.name = name
        self.talkText = talkText
    }
}

// Creating an instance of the data model
var eu: Person = Person(name: "Danilo")
```

```
struct Person {  
    var name: String  
    var talkText: String  
    func talk(){ print(talkText) }  
  
    init(name: String, talkText: String = "Olá") {  
        self.name = name  
        self.talkText = talkText  
    }  
}  
  
var eu: Person = Person(name: "Danilo")  
eu.talk()  
  
var tu: Person = Person(name: "Mark", talkText: "Hello")  
tu.talk()
```

```
struct Person {  
    var name: String  
    var talkText: String  
    func talk(){ print(talkText) }  
  
    init(name: String, talkText: String = "Olá") {  
        self.name = name  
        self.talkText = talkText  
    }  
}
```

```
var eu: Person = Person(name: "Danilo")  
eu.talk()
```

```
var tu: Person = Person(name: "Mark", talkText: "Hello")  
tu.talk()
```

```
struct Person {  
    var name: String  
    var talkText: String  
    func talk(){ print(talkText) }  
  
    init(name: String, talkText: String = "Olá") {  
        self.name = name  
        self.talkText = talkText  
    }  
}  
  
var eu: Person = Person(name: "Danilo")  
eu.talk()                                Olá  
  
var tu: Person = Person(name: "Mark", talkText: "Hello")  
tu.talk()
```

```
struct Person {  
    var name: String  
    var talkText: String  
    func talk(){ print(talkText) }  
  
    init(name: String, talkText: String = "Olá") {  
        self.name = name  
        self.talkText = talkText  
    }  
}
```

```
var eu: Person = Person(name: "Danilo")  
eu.talk()                                Olá
```

```
var tu: Person = Person(name: "Mark", talkText: "Hello")  
tu.talk()
```

```
struct Person {  
    var name: String  
    var talkText: String  
    func talk(){ print(talkText) }  
  
    init(name: String, talkText: String = "Olá") {  
        self.name = name  
        self.talkText = talkText  
    }  
}
```

```
var eu: Person = Person(name: "Danilo")  
eu.talk()                                Olá
```

```
var tu: Person = Person(name: "Mark", talkText: "Hello")  
tu.talk()                                Hello
```


Hands on

class

Differentiating classes from structs

Classes have inheritance

Classes allow type casting

Classes can have deinitializers

Classes are **reference** type **structs** are **value** type

class

reference
type

struct

value
type

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)
```

```
var rex: Dog = toto
```



```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

Xuxa

Sete

VALUE TYPE

```
struct Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

Xuxa

Sete


```
class Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

Xuxa

Xuxa

```
class Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

Xuxa

Xuxa

```
class Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete

Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

Xuxa

Xuxa

REFERENCE TYPE

```
class Dog {  
    var name: String  
    var isNice: Bool  
}
```

```
var toto: Dog = Dog(name: "Sete", isNice: true)  
var rex: Dog = toto
```

```
print(toto.name)  
print(rex.name)
```

Sete
Sete

```
toto.name = "Xuxa"
```

```
print(toto)  
print(rex)
```

Xuxa
Xuxa

VALUE TYPE

REFERENCE TYPE

VALUE TYPE

REFERENCE TYPE

Instance 1

var toto = "Sete"

VALUE TYPE

REFERENCE TYPE

Instance 1

var toto = "Sete"

Instance 2

VALUE TYPE

REFERENCE TYPE

Instance 1

var toto = "Sete"

Instance 2

var rex = toto

Create

a copy

VALUE TYPE

Instance 1

```
var toto = "Sete"
```

Instance 2

```
var rex = toto
```

Create
a copy

REFERENCE TYPE

```
var toto = "Sete"
```

VALUE TYPE

Instance 1

```
var toto = "Sete"
```

Instance 2

```
var rex = toto
```

Create
a copy

REFERENCE TYPE

```
var toto = "Sete"
```

```
var rex = toto
```

VALUE TYPE

Instance 1

```
var toto = "Sete"
```

Instance 2

```
var rex = toto
```

Create
a copy

REFERENCE TYPE

```
var toto = "Sete"
```

```
var rex = toto
```



Point to
the original

VALUE TYPE

Instance 1

```
var toto = "Sete"
```

Xuxa

Instance 2

```
var rex = toto
```

Sete

Create
a copy

REFERENCE TYPE

```
var toto = "Sete"
```

```
var rex = toto
```

Point to
the original

VALUE TYPE

Instance 1

```
var toto = "Sete"
```

Xuxa

Instance 2

```
var rex = toto
```

Sete

Create
a copy

REFERENCE TYPE

```
var toto = "Sete"
```

Xuxa

```
var rex = toto
```

Xuxa

Point to
the original

Hands on

