

Binary Session Types

Hernán Melgratti

ICC University of Buenos Aires-Conicet

Terminology

We say P is *well-typed* if there exists Γ s.t $\Gamma \vdash P$

Example

Is P well-typed?

- ▶ $P = x^+?(y:\text{int}).x^+!\text{true}.0$
- ▶ **Yes!** take $\Gamma = x^+ : ?\text{int}.!\text{bool}.\text{end}$

$$\frac{\frac{\frac{\emptyset \vdash \text{true} : \text{bool} \quad \frac{x^+ : \text{end}, y : \text{int} \text{ completed}}{x^+ : \text{end}, y : \text{int} \vdash 0} [\text{T-Nil}]}{x^+ : !\text{bool}.\text{end}, y : \text{int} \vdash x^+!\text{true}.0} [\text{T-Out}]}{x^+ : ?\text{int}.!\text{bool}.\text{end} \vdash x^+?(y:\text{int}).x^+!\text{true}.0} [\text{T-In}]$$

Example

Is P well-typed?

► $P = x^+?(y:!bool.end).y!true.0$

► **Yes!** take $\Gamma = x^+ : ?(!bool.end).end$

$$\begin{array}{c} \emptyset \vdash true : bool \qquad \frac{x^+ : end, y : end \text{ completed}}{\qquad\qquad\qquad} [T\text{-Nil}] \\ \hline \qquad\qquad\qquad x^+ : end, y : end \vdash 0 \qquad\qquad\qquad [T\text{-Out}] \\ \hline \qquad\qquad\qquad x^+ : end, y : !bool.end \vdash y!true.0 \\ \hline x^+ : ?(!bool.end).end \vdash x^+?(y:!bool.end).y!true.0 \qquad\qquad\qquad [T\text{-In}] \end{array}$$

Example

Is P well-typed?

► $P = x^+?(y:!int.end).y!true.0$

No!

Try with $\Gamma = x^+ : ?(!int.end).end$

$$\frac{\frac{\frac{\emptyset \not\vdash true : int}{x^+ : end, y : !int.end \vdash y!true.0} [T-In]}{x^+ : end, y : end \vdash 0} [T-Out]}{x^+ : ?(!int.end).end \vdash x^+?(y:!int.end).y!true.0} [T-Nil]$$

Example

Is P well-typed?

► $P = x^+?(y:?\text{int.end}).y!1.0$

No! Try with $\Gamma = x^+ : ?(? \text{int.end}).\text{end}$

There is a mismatch: $y : ? \text{int.end}$ and $y!1.0$

$$\frac{\frac{x^+ : \text{end}, y : ? \text{int.end} \vdash y!1.0}{x^+ : ?(? \text{int.end}).\text{end} \vdash x^+?(y:?\text{int.end}).y!1.0} [\text{T-In}]}{\text{[T-Out]}}$$

Rethinking $(\text{int} \rightarrow \text{bool}) \rightarrow \text{bool}$

$?(?\text{int}.\text{!bool.end}).\text{!bool.end}$ is not $(\text{int} \rightarrow \text{bool}) \rightarrow \text{bool}$

$g : (\text{int} \rightarrow \text{bool}) \rightarrow \text{bool}$
 $g\ f = f\ 1$

We may implement g as

$$P_g = x^+?(y:\textcolor{violet}{t_f}).y!\textcolor{blue}{1}.y?(z:\textcolor{blue}{bool}).x^+!z.\textcolor{blue}{0}$$

where $t_f = ?\text{int}.\text{!bool.end}$

But

$$x^+ : ?t_f.\text{!bool.end} \not\vdash P_g$$

However

$$x^+ : ?\overline{t_f}.\text{!bool.end} \vdash P_g$$

What about $?(!\text{int}.\text{?bool}.\text{end}).!\text{bool}.\text{end}?$

$g : (\text{int} \rightarrow \text{bool}) \rightarrow \text{bool}$
 $g\ y = (y\ 1) \ \&\ (y\ 2)$

We may implement g as

$$P_g = x^+?(y:\overline{t_f}).y!1.y?(z_1:\text{bool}).y!2.y?(z_2:\text{bool}).x^+!z_1\&z_2.0$$

where $t_f = ?\text{int}.\text{!bool}.\text{end}$

However

$$x^+ : ?\overline{t_f}.\text{!bool}.\text{end} \not\models P_g$$

The parameter y **must** be used just for **one** application

On linearity

- ▶ Consider $P = x^+ ! y^+ . y^+ ! 1 . 0$.
- ▶ Does the following hold?

$$\Gamma, x^+ : !(int.end).end, y^+ : !int.end \vdash P$$

$$\frac{\Gamma_1 \vdash v : t \quad \Gamma_2, x^p : S \vdash P}{\Gamma_1 + (\Gamma_2, x^p : !t.S) \vdash x^p ! v . P} \text{[T-Out]}$$

- ▶ No. Why does [T-Out] ban P ?
- ▶ Take

$$Q = (\nu y : !int.end)(\nu x : !(int.end).end)(P \mid x^-?(z:int.end).z!2.0 \mid y^-?(z:int).0)$$

- ▶ $Q \xrightarrow{\tau, \neg} Q'$ where

$$Q' = (\nu y : !int.end)(\nu x : end)(y^+ ! 1.0 \mid y^+ ! 2.0 \mid y^-?(z:int).0)$$

where two processes concurrently send on y^+

- ▶ A process does not use a session endpoint after *delegating* it (i.e., sending it over a different session endpoint)

Theorem (Type Preservation)

- ▶ If $\Gamma \vdash P$ and $P \xrightarrow{\tau, \bar{\tau}} Q$ then $\Gamma \vdash Q$.
- ▶ If $\Gamma, x^p : S, x^{\bar{p}} : \bar{S} \vdash P$ and $P \xrightarrow{x, \bar{l}} Q$ then $S \xrightarrow{l} T$ and $\Gamma, x^p : T, x^{\bar{p}} : \bar{T} \vdash Q$.

Theorem (Type Safety)

Let $\Gamma \vdash P$ where Γ balanced ²

- ▶ If $P \equiv (\nu \tilde{z} : \tilde{S})(x^p ! v . P_1 \mid x^{\bar{p}}?(y : \tilde{t}) . P_2 \mid Q)$ with $p \in \{+, -\}$ then $x, x^+, x^- \notin \text{fn}(Q)$ and $\Gamma, \tilde{z} : \tilde{S} \vdash v : t$
- ▶ If $P \equiv (\nu \tilde{z} : \tilde{S})(x^p \triangleleft \mathfrak{l}_j . R \mid x^{\bar{p}} \triangleright [\mathfrak{l}_i : P_i]_{i \in I} \mid Q)$ with $p \in \{+, -\}$ then $x, x^+, x^- \notin \text{fn}(Q)$ and $j \in I$.

² Γ is balanced if $x^p : S$ and $x^{\bar{p}} : T$ implies $S = \bar{T}$

Properties

Does the following hold?

$$\vdash (\nu x:?\text{int}.\text{end})(x^+?(z:\text{int}).x^-!z.0)$$

Yes!

- ▶ The process is well-typed and deadlocked

The type system ensures

- ▶ *Type Safety* in communication (e.g., received values are of the expected type)
- ▶ *Session Fidelity* (e.g., communication follows the flow described by the session type)
- ▶ The type system does not ensure deadlock-freedom

Deadlock

Deadlocked Process

$$P = x^+?(z:\text{int}).y^-!1.0 \quad | \quad y^+?(z:\text{int}).x^-!1.0$$

Is P well-typed?

$$\vdash (\nu x:?\text{int}.\text{end})(\nu y:?\text{int}.\text{end})P$$

Yes!

- ▶ The process is well-typed and deadlocked
- ▶ The type system does not check the dependencies between different sessions

Deadlock-freedom by design (linear logic approaches)

- ▶ Connection drawn between linear logic and session-typed pi-calculus gave rise to type systems that guarantee deadlock-freedom
 - ▶ Luís Caires, Frank Pfenning: Session Types as Intuitionistic Linear Propositions. CONCUR 2010.
 - ▶ Philip Wadler: Propositions as sessions. ICFP 2012.
- ▶ The type system imposes some structural constraint on programs
 - ▶ two processes share at most one channel
 - ▶ Hence, there are no circular dependencies