DGJL Motor Technology CO., LTD
Dongguan Jiali Motor Co., Ltd.

Date: 27-Oct-22

Add: Room 188, NO.137, Guanzhang road, Zhangmutou Town, Dongguan, Guangdong, China 523000
Moblie:86-13712020146; Fax:86-769-87791953
From: Joron Huang E-mail: joron.huang@sumotor.com; meriel@sumotor.com

mini DC Brush Worm Gear Motor











Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·cm)	Rated Current (A)	Stall Torque (N·cm)	Stall Current (A)	Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW12N20-3-15	3V	15	11	2	0.08			35x12x10mm	Single	Φ3*8	12g
GW12N20-3-30		30	22		0.1						
GW12N20-3-45		45	34		0.12						
GW12N20-6-30	6V	30	22	3	0.1						
GW12N20-6-60		60	45		0.15						
GW12N20-6-90		90	65		0.2						
GW12N20-12-60	12V	60	45	3	0.25						
GW12N20-12-120		120	90		0.3						
GW12GA-2	DC 3V	2	1.5	4.5	0.04	6.8	0.075	36x17x10 mm 1.42x0.67x0.39 inch	Single D shaft	Φ3*10	15 g 0.53 Oz
GW12GA-5		5	3.5	2.5	0.045	3.5	0.077				
GW12GA-3-10		10	7.5	0.7	0.03	1.9	0.08				
GW12GA-3-20		20	15	1.7	0.115	4.3	0.33				
GW12GA-32		32	24	1.7	0.17	5.7	0.67				
GW12GA-4	DC 6V	4	3	7	0.005	15	0.145				
GW12GA-10		10	8	3.5	0.055	7.8	0.135				
GW12GA-20		20	16	1.5	0.05	4	0.16				
GW12GA-40		40	30	3	0.19	6.7	0.6				
GW12GA-65		65	48	3.7	0.33	8.8	2.3				
GW12GA-9	DC 12V	9	7	8.5	0.065	27.3	0.28				
GW12GA-22		22	17	5	0.08	13.3	0.3				
GW12GA-42		42	32	3	0.07	7.5	0.3				
GW12GA-80		80	60	4	0.25	12.5	1.1				
GW180-4	DC 6V	4	3	54	0.3	90	0.8A	87x32x16 mm 3.43x1.26x0.63 inch	Single D shaft	Φ6*21.5	0.1 Kg 0.22 lb
GW180-6		6	4.5	35		70					
GW180-9		9	6.8	25		50					
GW180-12		12	9	16		30					
GW180-25		25	19	8		20					
GW180-8.5	DC 12V	8.5	6.5	75		208	1.2A				
GW180-13		13	10	50		180					
GW180-18		18	14	34		138					
GW180-26		26	20	24		100					
GW180-52		52	40	12		52					
GW2650-6-3	DC 6V	3	2.4	40	0.2	180	0.8A	86x26x16 mm 3.43x1.02x0.63 inch	Single/ Double D shaft / hall encoder	Φ6*21.5	0.1 Kg 0.22 lb
GW2650-6-6		6	4.5	30		150					
GW2650-6-8		8	6	20		80					
GW2650-6-13		13	10	11		50					
GW2650-6-16		16	12	10		40					
GW2650-6-26		26	20	7		25					
GW2650-6-34		34	27	4		16					
GW2650-6-75		75	57	2		8					
GW2650-12-3	DC 12V	3	2.4	40	0.4	180	2A				
GW2650-12-6		6	4.8	100		400					
GW2650-12-13		13	10	80		300					
GW2650-12-18		18	14	35		140					
GW2650-12-26		26	20	24		100					
GW2650-12-34		34	27	22		90					
GW2650-12-52		52	40	18		70					
GW2650-12-75		75	57	10		40					
GW2650-12-150		150	114	7		30					
GW2650-24-6	DC 24V	6	4.8	100	0.2	400	1A				
GW2650-24-13		13	10	80		300					
GW2650-24-18		18	14	35		140					
GW2650-24-26		26	20	24		100					
GW2650-24-34		34	27	22		90					
GW2650-24-52		52	40	18		70					
GW2650-24-75		75	57	10		40					
GW2650-24-150		150	114	7		30					
GW370-3-3	DC 3V	3	2	35	0.3	Unable to stall		82x32x27 mm 3.23x1.26x1.06 inch	Single D shaft	Φ6*14	0.18 Kg 0.397 lb
GW370-3-5.2		5.2	4	20		Unable to stall					
GW370-3-14		14	11	8		Unable to stall					
GW370-3-26		26	20	4		Unable to stall					
GW370-3-48		48	38	3		Unable to stall					
GW370-3-70		70	53	2		Unable to stall					
GW370-6-1	DC 6V	1	0.8	70	0.1	Unable to stall					
GW370-6-2.2		2.2	1.7	110	0.15	Unable to stall					
GW370-6-4		4	3	70	0.18	Unable to stall					
GW370-6-6		6	4.5	60		Unable to stall					
GW370-6-10		10	7.6	36		Unable to stall					
GW370-6-22		22	16	13		Unable to stall					
GW370-6-30		30	21	12		Unable to stall					
GW370-6-50		50	40	6		Unable to stall					
GW370-6-100		100	76	4	0.3	Unable to stall					



GW370-6-140		140	106	3		Unable to stall					
GW370-12-0.6	DC 12V	0.6	0.45	250	0.15	Unable to stall		82x32x27 mm 3.23x1.26x1.06 inch	Single D shaft	Φ6*14	0.18 Kg 0.397 lb
GW370-12-2		2	1.6	150		300	0.5				
GW370-12-5		5	3.8	200	0.5	650	2				
GW370-12-8		8	7	120		400					
GW370-12-14		14	10	70		240					
GW370-12-25		25	18	50		140					
GW370-12-45		45	34	25		80					
GW370-12-65		65	50	15		60					
GW370-12-80		80	60	13		50					
GW370-12-120		120	92	8		40					
GW370-12-180		180	135	6		27					
GW370-12-360		360	270	4		14					
GW370-24-1.2	DC 24V	1.2	0.9	250	0.2	Unable to stall					
GW370-24-5		5	3	200		650	0.4				
GW370-24-8		8	6	120	0.3	400	1				
GW370-24-14		14	10	70		240					
GW370-24-25		25	19	50		140					
GW370-24-45		45	34	25		80					
GW370-24-65		65	50	18		60					
GW370-24-120		120	90	12		40					
GW370-24-180		180	135	8		27					
GW370-24-360		360	270	4		14					
GW395-12	DC 6V	12	9	80	0.9			100x32x27 mm 3.94x1.26x1.06 inch	Single D shaft	Φ6*13.5	0.22 Kg 0.485 lb
GW395-20		20	15	30							
GW395-58		58	44	15							
GW395-25	DC 12V	25	19	90	0.8						
GW395-42		42	32	50							
GW395-120		120	92	20							







small DC Brush Worm Gear Motor

Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·cm)	Rated Current (A)	Stall Torque (N·cm)	Stall Current (A)	Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW31CT-2.2	DC 12V	2.2	1.8	400	0.8			118x42x32 mm 4.65x1.65x1.26 inch	Double /Single D shaft	Double Φ8*15 Single	0.38 Kg 0.838 lb
GW31CT-5		5	4	500	1.5						
GW31CT-5.2	DC 24V	5.2	4	500	1						
GW31ZY-12-3	DC 12V	3	2.2	500	1.5A	1100	2A	118x40x40 mm 4.65x2.76x2.76 inch	Single 15mm D shaft / Double 15mm D shaft / Single 30mm D shaft / tail shaft / We also customize hall encoder /brushless	Φ8*15	0.38 Kg 0.838 lb
GW31ZY-12-5		5	3.8	700	1.5A	1600	4.5A				
GW31ZY-12-7		7	5.5	400	0.7A	800	2A				
GW31ZY-12-10		10	7.5	500	1.5A	1400	4.5A				
GW31ZY-12-15		15	10.5	400	1.7A	1200	6A				
GW31ZY-12-25		25	19	220		650					
GW31ZY-12-40		40	30	120		440					
GW31ZY-12-80		80	50	60		210					
GW31ZY-12-100		100	80	50		150					
GW31ZY-12-160		160	120	35		100					
GW31ZY-12-248		248	188	22		80					
GW31ZY-12-468		468	348	12		40					
GW31ZY-24-3	DC 24V	3	2.2	500	0.4A	1100	1A				
GW31ZY-24-5		5	3.8	700	0.8A	1600	3A				
GW31ZY-24-7		7	5.5	400	0.4A	800	1A				
GW31ZY-24-10		10	7.5	700	0.8A	1600	3A				
GW31ZY-24-15		15	11	600	1.1A	1400	4A				
GW31ZY-24-25		25	19	350		800					
GW31ZY-24-40		40	30	150		500					
GW31ZY-24-80		80	60	70		260					
GW31ZY-24-110		110	83	50		200					
GW31ZY-24-160		160	120	40		140					
GW31ZY-24-250		250	190	28		100					
GW31ZY-24-470		470	350	15		50					


Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·cm)	Rated Current (A)	Stall Torque (N·cm)	Stall Current (A)	Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW4058-6-2	DC 6V	2	1.6	700	1.5A	1800	2.5A	120x40x40 mm 4.72x1.57x1.57 inch	Single 15mm D shaft/ Double 15mm D shaft/ Single 30mm D shaft/ tail shaft / customize hall encoder /brushless	Φ8*15	0.38 Kg 0.838 lb
GW4058-6-5		5	3.8	700		1400					
GW4058-6-10		10	7.5	400		800					
GW4058-6-15		15	11	250		520					
GW4058-6-30		30	22	140		260					
GW4058-6-40		40	30	100		190					
GW4058-6-60		60	47	60		120					
GW4058-12-2	DC 12V	2	1.6	650	1.3A	1600	2A				
GW4058-12-5		5	3.8	600		1200					
GW4058-12-10		10	7.5	700	2.2A	1800	6A				
GW4058-12-20		20	15	420		900					
GW4058-12-30		30	22.5	250		600					
GW4058-12-60		60	45	140		300					
GW4058-12-80		80	60	100		240					
GW4058-12-125		125	96	65		160					
GW4058-24-2	DC 24V	2	1.6	650	0.5A	1600	1A				
GW4058-24-5		5	3.8	600		1200					
GW4058-24-10		10	7.5	700		1800					
GW4058-24-20		20	15	420		900					

GW4058-24-30	DC 24V	30	22.5	250	1.1A	600	3A				
GW4058-24-60		60	45	140		300					
GW4058-24-80		80	60	100		240					
GW4058-24-125		125	96	65		160					
GW38ZY-6	DC 12V	6	4.5	320	1.50			150x50x45 mm 59x19.69x17.72 inch	Double /Single D shaft	Φ10*20	0.7 Kg 1.543 lb
GW38ZY-18		18	14	220	1.90						
GW38ZY-56		56	42	90							
GW38ZY-14	DC 24V	14	10.5	400	1.20						
GW38ZY-40		40	30	200	1.80						
GW38ZY-120		120	91	100							



small DC Brush Worm Gear Motor

Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·cm)	Rated Current (A)	Stall Torque (N·cm)	Stall Current (A)	Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW4468-70	DC 12V	70	52	110	1.2			128x60x44 mm 5.04x2.36x1.73 inch	Single D shaft (Some with Double shaft)	Φ8*20	0.63 Kg 1.39 lb
GW4468-4.5		4.5	3.3	600	1			152x93x44 mm 5.98x3.66x1.73 inch			1.2 Kg 2.647 lb
GW4468-12		12	9	400	2						
GW4468-26		26	19.5	250							
GW4468-48		48	36	220	2.2						
GW4468-140	DC 24V	140	105	100	1.5			128x60x44 mm 5.04x2.36x1.73 inch			0.63 Kg 1.389 lb
GW4468-175		175	131	80	1.8						
GW4468-9		9	7	1000	1.2			152x93x44 mm 5.98x3.66x1.73 inch			1.2 Kg 2.647 lb
GW4468-24		24	18	600	2.2						
GW4468-52		52	39	300							
GW4468-100		100	75	280	3.2						
GW600-12-2	DC12V	2	1.7	3000	1.8A	6000	4A	152x58x52 mm 5.98x2.28x2.05 inch	Single 20mm D shaft / Double 20mm D shaft / Single 35mm D shaft / Single 20mm shaft with keyway / tail shaft / hall encoder	Φ10*20	1 Kg 2.205 lb
GW600-12-3		3	2.4	2800		6000					
GW600-12-5		5	3.5	2200	3A	6000	11A				
GW600-12-9		9	7	1600		6000					
GW600-12-14		14	10	1100		4600					
GW600-12-20		20	15	660		2800					
GW600-12-30		30	23	500		2200					
GW600-12-45		45	34	350		1400					
GW600-12-60		60	45	270		1000					
GW600-12-100		98	75	170		600					
GW600-12-200		200	160	70		270					
GW600-24-3	DC24V	3	2.4	3000	2.5A	6000	4A				
GW600-24-5		5	3.5	2800		6000					
GW600-24-9		9	7	2500		6000	8A				
GW600-24-14		14	10	1750		5000					
GW600-24-20		20	15	1100		3300					
GW600-24-30		30	22	700		2100					
GW600-24-45		45	34	580		1700					
GW600-24-60		60	45	450		1200					
GW600-24-80		80	60	370		1100					
GW600-24-100		100	76	280		850					
GW600-24-140		140	106	200		700					
GW600-24-200		200	160	110		330					
GW600-24-300		300	240	110	3A	330	9A				
GW5882-R775-12-2	DC 12V	2	1.5	2500	2A	6000	4A	162x58x52 mm 6.38x2.28x2.05 inch	Single 20mm D shaft / Double 20mm D shaft / Single 35mm D shaft / Single 20mm shaft with keyway /hall encoder	Φ10*20	1 Kg 2.205 lb
GW5882-R775-12-6		6	4.5	2200	3.5A	6000	11A				
GW5882-R775-12-9		9	6.8	1700		5800					
GW5882-R775-12-13		13	10	1200		4000					
GW5882-R775-12-20		20	15	720		2400					
GW5882-R775-12-30		30	23	560		1800					
GW5882-R775-12-40		40	30	360		1200					
GW5882-R775-12-60		60	45	270		900					
GW5882-R775-12-100		100	76	170		500					
GW5882-R775-12-200		200	160	70		200					
GW5882-R775-24-6	DC 24V	6	4.5	2800	2.5A	6000	8A				
GW5882-R775-24-9		9	6.8	2500		6000					
GW5882-R775-24-13		13	10	1750		5000					
GW5882-R775-24-20		20	15	1100		3300					
GW5882-R775-24-30		30	23	700		2100					
GW5882-R775-24-40		40	30	580		1700					
GW5882-R775-24-60		60	45	450		1200					
GW5882-R775-24-100		100	75	280		850					
GW5882-R775-24-200		200	160	110		330					
GW5882-12-100	DC12V	100	76	200	3	600	12	162x58x52 mm 6.38x2.28x2.05 inch	Double/ Single D shaft	Φ10*20	1.2Kg 2.65 lb
GW5882-24-10	DC24V	10	7.6	2000	2.6	3000	8				
GW5882-24-30		30	23	800		1900					
GW5882-24-100		100	76	300		700					
GW5882-24-140		140	106	200		500					
GW5882-24-280		280	212	100		250					
GW5882-24-480		480	364	80	3	200	16				
GW63ZYA-12-5	DC 12V	5	4	3000	5			255x86x70 mm	Single shaft with key-way	Φ15	3.4 Kg
GW63ZYA-24-5	DC 24V	5	4	6000	3.8						
GW63ZYA-24-10		10	8	5000	8						
GW63ZY-24-20	DC 24V	20	15	2000	6.5			243x75x90 mm 9.57x2.95x3.54 inch	Double D shaft	Φ12*24	2.9 Kg 6.4 lb
GW63ZY-24-60		60	45	680							















GW3865	**DC 12V**	**100**	**75**	**150**	**2.5**		170x115x31 mm for car windows	D shaft	**Φ10*20**	0.5 Kg 1.1 lb
								Gear	**Mod 2.0 8 teeth**	0.5 Kg 1.1 lb
GW520	**DC 24V**	**12**	**10**	**441 N 15mm/**	**1**		197x47x34 mm 7.76x1.85x1.34 inch	08A 6T sprocket for windows open		0.55 Kg 1.213 lb
GW45100	**DC 24V**	**130**	**100**	**250**	**3**		168x70.5x40mm for table raise/down	Hexagon hole	8mm	0.8 Kg

small DC Brush Worm Gear Motor (volute type)



Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·cm)	Rated Current (A)	Stall Torque (N·cm)	Stall Current (A)	Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW7085L-42S	DC 12V	42	35	600	6			180x100x80 mm 7.09x3.94x3.15 inch	Screw Shaft	M8x12	1.5 Kg 3.307 lb
GW7085R-40S		40									
GW7085L-42		42							D shaft	Φ12X36	
GW7085R-40		40									
GW63100-250	DC 24V	250	190	250	3.5			190x62x95 mm 7.48x2.44x3.74 inch	D shaft	Φ10x48	1.5 Kg 3.307 lb
GW63100-220		220	165	400	4.5			204x62x95 mm 8.03x2.44x3.74 inch		Φ10x26	2.0 Kg 4.41 lb
GW6280L-30	DC 24V	30	22	480	3.2			180x100x70 mm 7.09x3.94x2.76 inch	D shaft	Φ10x36	1.3 Kg 2.866 lb
GW6280R-30											
GW6280L-52		52	40	500	4						
GW6280R-50		50									
GW6280L-100		100	76	350	4						
GW6280R-100											
GW70105L-25	DC 12V	25	20	550	5.5			200x100x80 mm 7.87x3.94x3.15 inch	D shaft	Φ12X36	1.8 Kg 3.97 lb
GW70105L-100		100	76	300	6.5						
GW70105L-52	DC 24V	52	45	800	6.5			200x100x80 mm 7.87x3.94x3.15 inch	D shaft	Φ12X36	1.8 Kg 3.968 lb
GW70105L-52S									Screw Shaft	M8x12	
GW70105R-50S		50									
GW70105-100	DC 24V	100	75	450	6.5			200x100x80 mm	D shaft	Φ10x41	1.8 Kg
GW82120L-38S	DC 24V	38	30	1200	8			227x128x85 mm 8.94x5.04x3.35 inch	Screw Shaft	M8x12	3 Kg 6.614 lb
GW82120R-38S											

medium DC Brush Worm Gear Motor



Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·m)	Rated Current (A)		Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW80170-040 100:1	DC 12V	12	9	39	15A		280x96x135 mm 11.02x3.78x5.32inch	Double /Single/ Tail shaft / encoder / Brake	Φ18 output bore	4.9 Kg 10.8 lb
GW80170-040 80:1		15	11	39						
GW80170-040 60:1		20	15	34						
GW80170-040 50:1		24	18	26						
GW80170-040 40:1		30	22	23						
GW80170-040 30:1		40	30	18						
GW80170-040 25:1		48	36	14.5						
GW80170-040 20:1		60	45	11.5						
GW80170-040 15:1		90	67	9						
GW80170-040 10:1		120	90	5.9						
GW80170-040 7.5:1		160	120	4.5						
GW80170-040 5:1		240	180	2.9						
GW80170-040 100:1	DC 24V	16	13	39	8A					
GW80170-040 80:1		20	15	39						
GW80170-040 60:1		27	21	38						
GW80170-040 50:1		33	25	28						
GW80170-040 40:1		41	31	23						
GW80170-040 30:1		55	42	20						
GW80170-040 25:1		65	49	16.5						
GW80170-040 20:1		82	62	13						
GW80170-040 15:1		110	83	10						
GW80170-040 10:1		165	125	6.5						
GW80170-040 7.5:1		220	167	5						
GW80170-040 5:1		330	250	3.2						
GW80170-030 80:1	DC 12V	15	11	15	15A		255x96x115 mm 10.04x3.78x5.22inch	Double /Single/ Tail shaft / encoder / Brake	Φ14 output bore	3.9 Kg 8.6 lb
GW80170-030 60:1		20	15	19						
GW80170-030 50:1		24	18	23						
GW80170-030 40:1		30	22	23						
GW80170-030 30:1		40	30	18						
GW80170-030 25:1		48	36	14.5						
GW80170-030 20:1		60	45	11.5						
GW80170-030 15:1		90	67	9						
GW80170-030 10:1		120	90	5.9						
GW80170-030 7.5:1		160	120	4.5						
GW80170-030 5:1		240	180	2.9						
GW80170-030 80:1	DC 24V	20	15	15	8A					
GW80170-030 60:1		27	21	19						
GW80170-030 50:1		33	25	23						
GW80170-030 40:1		41	31	23						
GW80170-030 30:1		55	42	20						

GW80170-030 25:1	DC 24V	65	49	16.5	8A					
GW80170-030 20:1		82	62	13						
GW80170-030 15:1		110	83	10						
GW80170-030 10:1		165	125	6.5						
GW80170-030 7.5:1		220	167	5						
GW80170-030 5:1		330	250	3.2						
GW97140 100:1	DC 24V	18	14	32	11.5A		260x97x136 mm 10.24x3.82x5.35Inch	Double /Single shaft / encoder / Brake	Φ18 output bore	5.2 Kg 11.46 lb
GW97140 80:1		22	17	34						
GW97140 60:1		30	23	43						
GW97140 50:1		36	27	40						
GW97140 40:1		45	34	30						
GW97140 30:1		60	45	24.5						
GW97140 20:1		90	68	16.5						
GW97140 15:1		120	91	12						
GW97140 10:1		180	137	8						
GW97140 7.5:1		240	182	6						
GW97140 5:1		360	270	4						
GW114165 100:1	DC 12V / DC 24V	17	13	70	50A (12V) / 25A (24V)		360x114x167 mm 14.17x4.49x6.57inch	Double /Single shaft / encoder / Brake	Φ25 output bore	9.2 Kg 20.3 lb
GW114165 80:1		21	16	75						
GW114165 60:1		28	21	80						
GW114165 50:1		34	26	85						
GW114165 40:1		42	31	85						
GW114165 30:1		56	42	60						
GW114165 20:1		84	63	40						
GW114165 15:1		112	85	30						
GW114165 10:1		170	126	20						
GW114165 7.5:1		227	168	16						
GW114165 5:1		340	252	11						
GW650 100:1	DC 24V	6	5	120	34A		396x197x144 mm 15.59x7.76x5.67inch	Double /Single/ / encoder / Brake	Φ25 output bore	15 Kg 33.07 lb
GW650 80:1		7.5	6.2	130						
GW650 60:1		10	8.3	140						
GW650 50:1		12	10	160						
GW650 40:1		15	12.5	160						
GW650 30:1		20	16.6	160						
GW650 20:1		30	25	160						
GW650 15:1		40	33	120						
GW650 10:1		60	50	80						
GW650 7.5:1		80	66	60						
GW650 5:1		120	100	40						

ultra-low speed medium DC Brush Worm Gear Motor

Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·m)	Rated Current (A)		Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW6097-030										
GW31ZY030050 1200:1	DC 12V / DC 24V	0.008	0.006	60	0.7A (12V) / 0.4A (24V)		227x170x136mm	Double /Single/ Tail shaft / encoder / Brake	Φ25 output bore	6.4 Kg
GW31ZY030050 900:1		0.011	0.008	60						
GW31ZY030050 600:1		0.016	0.012	60						
GW31ZY030050 300:1		0.033	0.022	60						
GW600040 80:1	DC 12V / DC 24V	0.1	0.08	40	4A (12V) / 2A (24V)		177x174x90mm 6.97x6.85x3.54 inch	Double /Single/ Tail shaft / encoder /Brake	Φ18 output bore	3.1 Kg 6.834 lb
GW600040 60:1		0.15	0.12	50						
GW600040 30:1		0.3	0.24	60						
GW600040 15:1		0.6	0.5	60						
GW600040 10:1		0.9	0.7	60						
GW600040 7.5:1		1.3	1	50						
GW600040 5:1		1.8	1.4	40						
GW030050 900:1	DC 12V / DC 24V	2	1.5	89	15A (12V) / 8A (24V)		237x255x121 mm 9.33x10.04x4.76inch	Double /Single/ Tail shaft / encoder / Brake	Φ25 output bore	7.2 Kg 15.9 lb
GW030050 600:1		3	2.2	89						
GW030050 500:1		3.6	2.4	82						
GW030050 400:1		4.5	3.4	65						
GW030050 300:1		6	4	50						
GW030063 1500:1	DC 12V / DC 24V	1.2	0.8	160	15A (12V)/ 8A (24V)		262x255x131 mm 10.3x10.04x5.16inch	Double /Single/ Tail shaft / encoder / Brake	Φ25 output bore	9.8 Kg 20.6 lb
GW030063 1200:1		1.5	1.1	160						
GW030063 900:1		2	1.5	160						
GW030063 600:1		3	2.2	140						
GW040075 1200:1	DC 12V / DC 24V	1.3	1	300	50A (12V) / 25A (24V)		290x300x167 mm 11.4x11.8x6.57inch	Double /Single shaft / encoder / Brake	Φ28 output bore	20Kg 44.09 lb
GW040075 900:1		1.8	1.4	300						
GW040075 600:1		2.7	2.1	300						
GW040075 400:1		4.1	3.1	300						
GW040075 300:1		5.5	4.2	230						
GW040075 200:1		8.2	6.2	160						
GW040075 150:1		12	9	150						
GW040090 1200:1	DC 12V / DC 24V	1.3	1	450	50A (12V) / 25A (24V)		290x345x167 mm 12x78.74x5.51inch	Double /Single shaft / encoder / Brake	Φ35 output bore	24 Kg 52.91 lb
GW040090 900:1		1.8	1.4	450						
GW040090 600:1		2.7	2.1	400						
GW040090 400:1		4.1	3.1	300						
GW040090 300:1		5.5	4.2	230						
GW040090 200:1		8.2	6.2	160						



GW040090 150:1		12	9	150						
GW650130 1200:1	DC 24V	0.5	0.4	2700	34A		465x420x200mm	Double /Single shaft / encoder	Φ45 output bore	65 Kg
GW650130 900:1		0.67	0.5	2700						
GW650130 600:1		1	0.75	2400						
GW650130 400:1		1.5	1.25	1900						
GW650130 300:1		2	1.5	1600						
GW650130 200:1		3	2.25	1200						
GW650130 150:1		4	3	900						
Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·m)	Rated Current (A)		Dimension (exclude shaft)	Shaft (mm)		Net Weight

Remarks: 1)Besides this models, costomized inquiry is welcomed. Some items also have longer shaft in stock.
2)Dimensions and weight of list may be a little different from real products.
3)Electric motor loading should not exceed the rated torque, or it's will be damaged



DC Brushless Worm Gear Motor (>10,000 hours)

Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·cm)	Rated Current (A)	Stall Torque (N·cm)	Stall Current (A)	Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW370BL											
GW4058BL-6-2	DC 6V	2	1.6	**600**	1.5A	1300	2.5A	120x40x40 mm 4.72x1.57x1.57 inch	Single 15mm D shaft / Double 15mm D shaft / Single 30mm D shaft	Φ8*15	0.38 Kg 0.838 lb
GW4058BL-6-5		5	3.8	**600**		1200					
GW4058BL-6-10		10	7.5	**350**		700					
GW4058BL-6-15		15	11	200		500					
GW4058BL-6-30		30	22	120		260					
GW4058BL-6-40		40	30	90		190					
GW4058BL-6-60		60	45	60		120					
GW4058BL-12-2	DC 12V	2	1.6	**800**	0.9A	1500	1.8A				
GW4058BL-12-5		5	3.8	**800**		1500					
GW4058BL-12-10		10	7.5	**700**	1.5A	1500	2.5A				
GW4058BL-12-20		20	15	**380**		800					
GW4058BL-12-30		30	22	200		520					
GW4058BL-12-60		60	45	120		260					
GW4058BL-12-80		80	60	90		190					
GW4058BL-12-125		125	95	60		120					
GW4058BL-24-2	DC 24V	2	1.6	**700**	0.5A	1500	0.8A				
GW4058BL-24-5		5	3.8	**700**		1500					
GW4058BL-24-10		10	7.5	**800**	0.9A	1500	2A				
GW4058BL-24-20		20	15	**450**		900					
GW4058BL-24-30		30	22	280		600					
GW4058BL-24-60		60	45	150		300					
GW4058BL-24-80		80	60	110		250					
GW4058BL-24-125		125	95	70		160					
Item	Voltage (V)	No Load Speed	Loading Speed	Rated Torque (N·m)	Rated Current (A)			Dimension (exclude shaft)	Shaft (mm)		Net Weight
GW62-42BL-12	DC 24V	12	9.6	21.5	2			190x62x46 mm 7.48x2.44x1.81 inch	Φ15x30		1.8 Kg 3.97 lb
GW62-42BL-18		18	14.4	15							
GW62-42BL-52		52	41.6	5							

