Affected products covered by this PCN:

101025501	Z-Laser Modell LP-HFD2-7-520F-T-60
101065600	Z-Laser Modell LP-HFD2-7-520F-S-60
101025301	Z-Laser Modell LP-HFD2-7-520F-S-80
101025701	Z-Laser Modell LP-HFD2-7-520F-S-60F
101063100	Z-Laser Modell LP-HFD2-14-520F-S-80
101069100	Z-Laser Modell LP-HFD2-14-520F-T-60

The affected Z-Laser products “LP-HFD2” will be specified for an enhanced temperature range:

Old range of operating temperature	New range of operating temperature
0°C…**+40**°C (ambient temperature)	0°C …**+50°**C (ambient temperature)

A warning will be issued (LED blinking) when the laser projector passes 45°C. The projector will stop projecting when it passes 50°C.

This is regardless of what maximum operating temperature was stated in the user’s manual. The documentation will be updated accordingly.

Note-1:
The product change will take effect for LP-HFD2 products shipped either along with this PCN or along with an updated user’s documentation (printed or on digital media)

Note-2:
The new temperature limits do not lead to a product change. These limits are parameters that are written into the modules’ configuration memory (LPC.INI) during the calibration process. Neither the firmware nor the hardware base of the laser modules is changed.

Z-Laser service personnel can modify this parameter for the respective products.

This document is valid without signature