


SESNOR OUT SIGNALS




SENSOR OUT SIGNALS




SENSOR OUT SIGNALS



SOLDER BRIDGE




For Single-supply, solder SB3, SB5, SB6
For Double-supply, solder SB1, SB2, SB4



eSpark Consulting Group

Title: Connector-Sheet.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11


INSTRUMENTAL AMPLIFIER



VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component


DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC

SHORT WHILE DUAL SUPPLY
ELSE OPEN




TEST PADS




4 Pin SMD Wire Connector

sEMG SENSOR




For Dual-supply, short VREF_GND SB


LED




Voltage Divider



Solder Bridges








eSpark Consulting Group


Title: Electrode_Sheet1.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11

INSTRUMENTAL AMPLIFIER




VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component




DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC




TEST PADS




4 Pin SMD Wire Connector

sEMG SENSOR




For Dual-supply, short VREF_GND SB


LED




Voltage Divider



Solder Bridges








eSpark Consulting Group

Title: Electrode_Sheet2.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11


INSTRUMENTAL AMPLIFIER



VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component


DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC

SHORT WHILE DUAL SUPPLY
ELSE OPEN




TEST PADS




4 Pin SMD Wire Connector

sEMG SENSOR




For Dual-supply, short VREF_GND SB


LED




Voltage Divider



Solder Bridges








eSpark Consulting Group

Title: Electrode_Sheet3.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11


INSTRUMENTAL AMPLIFIER



VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component


DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC

SHORT WHILE DUAL SUPPLY
ELSE OPEN




TEST PADS




4 Pin SMD Wire Connector

LED




sEMG SENSOR





For Dual-supply, short VREF_GND SB

Voltage Divider



Solder Bridges








eSpark Consulting Group

Title: Electrode_Sheet4.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11

INSTRUMENTAL AMPLIFIER




VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component




DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC




TEST PADS




4 Pin SMD Wire Connector


LED




sEMG SENSOR




Voltage Divider



Solder Bridges








eSpark Consulting Group

Title: Electrode_Sheet5.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11

INSTRUMENTAL AMPLIFIER




VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component




DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC

SHORT WHILE DUAL SUPPLY
ELSE OPEN




TEST PADS




4 Pin SMD Wire Connector

sEMG SENSOR




For Dual-supply, short VREF_GND SB


LED




Voltage Divider



Solder Bridges








eSpark Consulting Group

Title: Electrode_Sheet6.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11


INSTRUMENTAL AMPLIFIER



VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component


DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC

SHORT WHILE DUAL SUPPLY
ELSE OPEN




TEST PADS




4 Pin SMD Wire Connector

sEMG SENSOR




For Dual-supply, short VREF_GND SB


LED




Voltage Divider



Solder Bridges








eSpark Consulting Group

Title: Electrode_Sheet7.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11

INSTRUMENTAL AMPLIFIER




VREF input requires almost 50uA current. This would make the total current of 8 opamps equal to 400uA.

Supporting Component




DECOUPLING CAPS




Place these near AD8221ARZ-R7

DUAL SUPPLY IC

SHORT WHILE DUAL SUPPLY
ELSE OPEN




TEST PADS




4 Pin SMD Wire Connector

sEMG SENSOR




For Dual-supply, short VREF_GND SB


LED




Voltage Divider



Solder Bridges









eSpark Consulting Group

Title: Electrode_Sheet8.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11


DECOUPLING CAPS




NEGATIVE RAIL




OPAMP FOR IMPEDANCE MATCHING




RESISTIVE NETWORK FOR 1.65V




SOLDER BRIDGE





UNITY GAIN AMPLIFIER FOR IMPEDANCE MATCHING






SESNOR OUT SIGNALS






eSpark Consulting Group

Title: Opamp_Sheet.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 09/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11



eSpark Consulting Group

Title: Top-Sheet.SchDoc		
File: EMG-Arm-ELEC-V2.0.PrjPcb		
Date: 08/02/2025	Page	Num: *
Drawn By: Huzaifa Ali	Page	Total: 11


ELECTRODE # 8
ELECTRODE # 7
ELECTRODE # 6
V-REF
ELECTRODE # 5
ELECTRODE # 4
ELECTRODE # 3
ELECTRODE # 2
ELECTRODE # 1
210.92 (mm)
171.29 (mm)