TO MAIN BOARD

230V BIG MAINS

230V to 12V PSU

Isolated 230V OUT PORT x1 - x3

EXTERNAL SOURCE CHARGING UNIT

12V Nomial Input

DC / DC Charging PSU

To System Battery

ALERT OUT (OPTIONAL)

STANDALONE UNIT

SMART CONNECT

UART

RS-485 TO UART **SP3485EIM**

TO ULTRASONIC SENSOR **RS-485**

SPI

NFC **PN532**

WBUS INTERFACE HEATER CONTROL

Main Heater

Aux Heater

UART LEVEL-SHIF TXB0102DCUT

A7672E (FASE) GSM-GPRS MODEM

RF ANT / **U.FL-R-SMT-1(80)**

MODEM UPDATE INTERFACE

GNSS ANT / **U.FL-R-SMT-1(80)**

NANO SIM

BIG BRAIN PRODUCTION

SPI UART **WK2124-ISSG**

RS-485 TDS & TEMP **SP3485EIM/TR**

AUTO FLUSH **SOLINOID OUT**

RESIN SAVER (Waste) **SOLINOID OUT**

RESIN SAVER (Pure) **SOLINOID OUT**

RO INLET PRESSURE **ANALOG IN**

OPTO-ISO **PS2801C-1-F3-A**

WASTE FLOW **PULSE IN**

OPTO-ISO **PS2801C-1-F3-A**

DI OUT FLOW **PULSE IN**

OPTO-ISO **PS2801C-1-F3-A**

INCOMING FLOW **PULSE IN**