Humanization API Documentation

This document outlines the WebSocket API endpoints for the text humanization system. The humanization system allows users to transform AI-generated text to appear more natural and human-written, helping to avoid AI detection.

Table of Contents

1. Connection
2. Message Format
3. API Endpoints
    - Humanize Message
    - Re-humanize Previously Humanized Text
    - Humanize Raw Text
    - Get Humanized Messages
4. Response Types
5. Error Handling
6. Re-humanization Flow

Connection

Connect to the WebSocket server with a valid authentication token:

```
ws://your-server-url/ws?token=your-refresh-auth-token
```

The server will validate your token against active subscriptions before allowing connection.

Message Format

All messages sent to and received from the server follow a JSON format with a `type` field that determines the action to be performed:

```
{
  "type": "message_type",
  "...other_fields": "based on message type"
}
```

API Endpoints

Humanize Message

Humanizes text content from an existing message in the chat history.

Request:

```
{
  "type": "humanize",
  "message_id": "uuid-of-message-to-humanize",
  "request_id": "client-generated-request-id-for-tracking"
}
```

Fields:

- `message_id`: (Required) UUID of the message to humanize
- `request_id`: (Optional) Client-generated ID to track this specific request

Re-humanize Previously Humanized Text

Takes previously humanized text and runs it through the humanization algorithm again for improved results. This is particularly useful for achieving lower AI detection scores.

Request:

```
{
  "type": "humanize",
  "message_id": "uuid-of-original-message",
  "re_humanize": true,
  "request_id": "client-generated-request-id-for-tracking"
}
```

Fields:

- `message_id`: (Required) UUID of the original message
- `re_humanize`: (Required) Set to `true` to activate re-humanization. This will take the most recently humanized version of the text and run it through the humanization process again.
- `request_id`: (Optional) Client-generated ID to track this specific request

Note: The system keeps track of the re-humanization history to prevent circular references. Each re-humanized text is stored as a new record in the database with a reference to its parent.

Humanize Raw Text

Humanizes arbitrary text that is not associated with an existing message.

Request:

```
{
  "type": "humanize",
  "text": "Raw text content to be humanized",
  "re_humanize": false,
  "request_id": "client-generated-request-id-for-tracking"
}
```

Fields:

- `text`: (Required) Raw text content to humanize
- `re_humanize`: (Optional) Set to `true` to re-humanize previously humanized raw text. The system will use the most recent raw text humanization.
- `request_id`: (Optional) Client-generated ID to track this specific request

Note: Even for raw text without a message_id, the system stores the humanization history, allowing for re-humanization of direct text inputs.

Get Humanized Messages

Retrieves previously humanized messages with pagination support.

Request:

```
{
  "type": "get_humanized_messages",
  "limit": 20,
  "offset": 0,
  "message_id": "uuid-of-specific-message"
}
```

Fields:

- `limit` : (Optional) Maximum number of records to return (default: 20)
- `offset` : (Optional) Number of records to skip (default: 0)
- `message_id` : (Optional) If provided, returns only humanized versions of this specific message

Response Types

Humanize Status

Sent immediately after a humanization request is received:

```
{
  "type": "humanize_status",
  "status": "processing",
  "request_id": "your-request-id-if-provided"
}
```

Humanize Complete

Sent when humanization is complete:

```
{
  "type": "humanize_complete",
  "original_text": "The original text that was humanized",
  "humanized_text": "The humanized version of the text",
  "request_id": "your-request-id-if-provided",
  "message_id": "uuid-of-original-message-if-applicable"
}
```

Humanized Messages List

Response to a get_humanized_messages request:

```
{
  "type": "get_humanized_messages",
  "messageId": "uuid-of-filtered-message-or-null",
  "messages": [
    {
      "id": "uuid-of-humanized-message",
      "humanized_text": "Humanized content",
      "created_at": "2023-01-01T12:00:00Z",
```

```
      "re_humanized": true
    },
    // ... more messages
  ]
}
```

The `re_humanized` flag indicates whether this text is a result of re-humanizing a previously humanized text. When `true`, it means this humanized message was derived from another humanized text rather than directly from the original message.

Error Handling

Error responses follow this format:

```
{
  "type": "error",
  "error": "Error message description",
  "request_id": "your-request-id-if-provided"
}
```

Common error scenarios:

- Unauthorized access to messages
- Message not found
- Text exceeds maximum allowed length
- Failed API calls to the humanization service
- Rate limiting errors

Re-humanization Flow

The re-humanization feature allows users to iteratively improve the humanization quality of their text by running it through the algorithm multiple times.

How it works:

1. **Initial Humanization**: Text is first humanized using either a message_id reference or direct text input.
2. **Re-humanization Request**: To re-humanize, send a request with:
    - Original `message_id`
    - `re_humanize` parameter set to `true`
3. **Processing**: The system retrieves the most recent humanized version of that message and processes it again through the humanization algorithm.
4. **Storage**: Each re-humanization creates a new record in the database with:
    - The new humanized text
    - A reference to the previous humanization via `re_humanized_id`
    - The original message ID remains the same
5. **Retrieval**: When retrieving humanized messages, the `re_humanized` flag indicates whether a text has been re-humanized.

Example Flow:

1. Original message with ID `abc-123` contains AI text
2. First humanization creates record with ID `hum-456` referencing `abc-123`
3. Re-humanization creates record with ID `hum-789` referencing `abc-123` and setting `re_humanized_id` to `hum-456`
4. When listing humanized messages, `hum-789` will show `re_humanized: true`