




Title		
Size: A	Number	Revision
Date: 7/23/2024		Sheet of
File: C:\Users\..\Top-Sheet.SchDoc		Drawn By:

BATTERY CHARGER


100mA Charging Current




ON/OFF CONTROLLER




MODE/POWER BUTTON




BATTERY FUEL GAUGE



3V3 LDO







eSpark Consulting Group

Title: Power-Sheet.SchDoc	
File: Button-Board.PrjPcb	
Date: 21/07/2024	Page Num: 2
Drawn By: Huzaifa Ali	Page Total: 5


ATTINY1616




PROGRAMMING




BATTERY LEVEL



MODE SELECTION







eSpark Consulting Group


Title: Controller-Sheet.SchDoc	
File: Button-Board.PrjPcb	
Date: 23/07/2024	Page Num: 3
Drawn By: Huzaifa Ali	Page Total: 5

LED DRIVER



RED LED CONTROL







eSpark Consulting Group

Title: LED-Driver-Sheet.SchDoc	
File: Button-Board.PrjPcb	
Date: 23/07/2024	Page Num: 4
Drawn By: Huzaifa Ali	Page Total: 5


LED INTERFACE CONNECTOR




BATTERY INPUT



USB INTERFACE CONNECTOR







eSpark Consulting Group

Title: Connector-Sheet.SchDoc	
File: Button-Board.PrjPcb	
Date: 21/07/2024	Page Num: 5
Drawn By: Huzaifa Ali	Page Total: 5

Layer	Name	Material	Thickness	Constant	Board Layer Stack
	Top Overlay				
	Top Solder	Solder Resist	0.010mm	3.5	
1	Top Layer		0.035mm		
	Dielectric 1	FR-4	1.500mm	4.8	
2	Bottom Layer		0.035mm		
	Bottom Solder	Solder Resist	0.010mm	3.5	
	Bottom Overlay				
Total board thickness:			1.590mm		

