



U_Power_Section
Power_Section.SchDoc
S_REG
A_REG
S_REG
A_REG
U_Audio_Section
Audio_Section.SchDoc
#12-P
#13-P
#14-P
#15-P
#12-P
#13-P
#14-P
#15-P
#O_MIC
#O_MIC
U_Battery management Section
Battery management Section.SchDoc
CHG
B_ADC
CHG
B_ADC
U_Sensor_Section
Sensor_Section.SchDoc
SDA_
SCL_
LED#
CLED
SDA_
SCL_
LED#
CLED
U_SourceSelector_Section
SourceSelector_Section.SchDoc
S_SENS
S_SENS
U_Connector_Section
Connector_Section.SchDoc
RX
TX
RTS
DTR
RX
TX
RTS
DTR
AC_LINE
AC_Neutral
AC_LINE
AC_Neutral
U_Controller_Section
Controller_Section.SchDoc
#12-P
#13-P
#14-P
#15-P
#12-P
#13-P
#14-P
#15-P
CHG
B_ADC
#O_MIC
CHG
B_ADC
#O_MIC
RX
TX
RTS
DTR
RX
TX
RTS
DTR
SDA_
SCL_
SDA_
SCL_
LED#
CLED
S_REG
A_REG
S_SENS
LED#
CLED
S_REG
A_REG
S_SENS
U_Supply_Section
Supply_Section.SchDoc
AC_LINE
AC_Neutral
AC_LINE
AC_Neutral




Power Section











Place Decoupling Capacitor with there respective pins.


ISET Resistor Value is changed in Parameters, please be careful.


As per Datasheet, the value should not exceed 675 Ohm.














Battery Charging Section





External Enable wouldn't be used as Development board already had circuit.


SW2 is being used for Software Reset.















Controller Section





Audio Section














Sensor Section





Mentioned Capacitors will be placed with Battery Connector and with USB Main Connector.


No Need to place Decoupling Capacitors with Switch as this is just path.













Connector Section



Title		
Size: A	Number	Revision
Date: 3/18/2021	Sheet of	
File: E:\GitHub\..\SourceSelector_Section.SchDoc	Drawn By:	





Title		
Size: A	Number	Revision
Date: 3/18/2021		Sheet of
File: E:\GitHub\..\Supply_Section.SchDoc		Drawn By: