## Breakout - Code Documentation

By Umang Deshpande and Akshay Hegde

June 2017

## 1 Program Code

The git repository for the complete code can be found here. It contains the complete project folder used in CCS.

- The console support libraries (including the font libraries) are present in the Console folder.
- The game objects are present in the Objects folder.
- The game screens are present in the Screens folder.
- game.c is the main file. This contains the two basic tasks part of RTOS, with their internal state machines. Additional functions are used from above libraries.

## 2 Main Code

Firstly, following headers are included:

```
/* XDC module Headers */
#include <xdc/std.h>
#include <xdc/runtime/System.h>

#include <xdc/runtime/Log.h>
//needed for any Log_info() call
#include <xdc/cfg/global.h>
//header file for statically defined objects/handles
#include <xdc/runtime/Log.h>
//needed for any Log_info() call

/* BIOS module Headers */
#include <ti/sysbios/BIOS.h>
```

```
#include <ti/sysbios/knl/Clock.h>
#include <ti/sysbios/knl/Task.h>
#include <ti/sysbios/knl/Semaphore.h>
/* Standard C Libraries */
#include <stdint.h>
#include <stdlib.h>
#include <stdbool.h>
/* Include header files for ADC, Timer
and Interrupt functions */
#include "inc/hw_types.h"
#include "inc/hw_memmap.h"
#include "driverlib/gpio.h"
#include "inc/tm4c123gh6pm.h"
#include "driverlib/debug.h"
#include "driverlib/pin_map.h"
#include "driverlib/adc.h"
#include "driverlib/interrupt.h"
#include "driverlib/timer.h"
#include <time.h>
#define TARGET_IS_BLIZZARD_RB1
#include "driverlib/rom.h"
#include "Console/consoleInit.h"
#include "Console/glcd.h"
#include "Console/gameDisplay.h"
#include "Console/tones.h"
#include "Objects/gameObjects.h"
#include "Screens/gameScreens.h"
```

- XDC Headers handle XDCTools as part of RTOS, which aid in debugging.
- BIOS module headers allow use of Tasks and Semaphore definitions.
- stdint.h Headers allow use of uint32 variables, stdbool allows use of stdbool.h variables, stdlib.h allows randomization function rand() to be called.
- For the timer, timer interrupt and ADC functions used in Timer2\_ISR(Task Scheduler) and in ADC Input code, the different libraries for Tiva C are included
- rom.h Allows the use of ROM functions for the given board.
- The Console headers provide developer level functions to the console, so that initialization can be performed using a single function \_init\_().

- GLCD functions for basic GLCD refresh, sending commands and sending data are obtained from glcd.h header.
- Various game objects(Like a graphic of a particular dimension) can be displayed on screen using certain specific functions in gameDisplay.h.
- Different beeps and music can be played through the functions defined in tones.h.
- The different game objects are designed and their hex arrays are stored in gameObjects.h.
- The game screens are designed using Paint, converted to Hex from BMP format, and then preloaded in the form of hex arrays in gameScreens.h.

Following this, define all global variables are defined as follows:

```
/* Global Variables
 */
uint32_t ui32ADC0Value,latency, tickCount;
uint32_t specialTimeCount, pinName, baseName;
uint8_t ui8XAxisAvg, ui8XAxisPrev = 64;
signed char hit [64];
signed int paddleXPos, paddleXPrev;
unsigned char victoryCheck, ballXPos,ballYPos;
unsigned char ballXPrev, ballYPrev;
unsigned int ballXMapInt, scoreInt, lifeCount = 3;
unsigned int ballMovSpeed = 325, paddleSpeed = 2;
unsigned int lifeCountTemp;
char score_str [4];
```

- ui32ADCOValue is used for ADC Input Buffer.
- latency defines game screen refresh latency.
- tickCount is used for Task Scheduling in Timer\_ISR.
- specialTimeCount is used to count 10 seconds in the SPECIAL mode of the paddle in Timer1\_ISR.
- pinName,baseName and flag are used for Switch selection. baseName is the port to which the switch belongs to. pinName is the actual pin to which the switch is connected.
- ui8XAxisAvg is used to read ADC value. And ui8XAxisPrev holds the previous sampled value of the ADC, for clearing purposes.
- hit [64] holds the value of the hit for each block that can be displayed on screen.

- paddleXPos is used to hold the sticky position of the paddle with response to the Thumbstick ADC. The previous paddle position is stored in paddleXPrev.
- victoryCheck flag is used to check for victory condition(whether all blocks are cleared).
- ballXPos, ballYPos, ballXPrev and ballYPrev is used to monitor the present and previous positions of the ball.
- ballXMapInt is used to map ball position to corresponding block position.
- scoreInt is used to monitor score where score\_str[4] stores the score in string format to be displayed on GLCD.
- lifeCount is the total number of lives available to the player at the start of game, where lifeCountTemp is the live monitoring of pending lives during gameplay.
- ballMovSpeed controls the delay between subsequent ball display. Smaller the value, faster is the ball.
- paddleSpeed is used to control the speed of the paddle. Larger the value, greater the speed.

All the different states for the various state machines used are enlisted as follows:

```
/*
  * Enumeration of States for State Machines
  */
enum modes
{
    // Different game states(Classified
    // because of different I/O behaviour in each state)
    MENU,
    INSTRUCTIONS,
    SETTINGS,
    GAMEPLAY,
    VICTORY,
    GAMEOVER
};
// Initialization
enum modes mode = MENU;
```

mode enumerated variable is thus initially in MENU state.

```
enum menuModes menuMode = ENTRY;
// Different Paddle States(Different paddle sizes
// upon hit of BLOCK_MAGIC2)
enum gameplayChanges
{
    NORMAL,
```

```
SPECIAL
};
// Initialization
enum gameplayChanges gameplayChange;
```

gameplayChange enumerated variable is thus initialized.

```
// Different Gameplay Internal States
// (Different I/O behaviour in different states)
enum gameplayModes
{
    ENTER,
    DEATH,
    REENTER,
    ALWAYS
};
// Initialization
enum gameplayModes gameplayMode = ENTER;
```

gameplayMode enumerated variable is thus initialized to ENTER.

```
// Different Menu Internal States
// (Certain functions are called upon
// entry, rest are performed throughout)
enum menuModes
{
    ENTRY,
    THROUGHOUT
};
// Initialization
enum menuModes menuMode = ENTRY;
```

menuMode enumerated variable is thus initialized to ENTRY.

```
// Cursor States
enum cursorPositions
{
    ONE,
    TWO,
    THREE
};
// Initialization
enum cursorPositions cursorPos;
```

cursorPos enumerated variable is thus initialized.

```
// Enumeration of Difficulties
// (Different brick composition and
// number of lives on game start)
enum difficulties
{
```

```
EASY, // More Easy Bricks, 3 Lives
MEDIUM, // More Medium Bricks, 2 Lives
HARD // More Hard Bricks, 1 Lifes
};
// Initialization
enum difficulties difficulty;
```

difficulty enumerated variable is thus initialized.

```
// Enumeration of different ballspeed states
enum ballSpeeds
{
    SLOW,
    FAST,
    FASTER
};
// Initialization
enum ballSpeeds ballSpeed = FAST;
```

ballSpeed enumerated variable is thus initialized to FAST.

```
// Different Ball States(Directions)
enum directions
{
    INIT,
    // For Initial Ball Position
    // at centre on gameplay entry/ re entry
    UP.LEFT,
    UP.RIGHT,
    DOWN.RIGHT,
    DOWN.LEFT,
};
// Initialization
enum directions direction = INIT;
```

direction enumerated variable is thus initialized to INIT.

```
// Different Block Type(States for Blocks)
enum blocks
{
    NONE, // No Block
    BLOCK.HARD, // Takes 3 hits to disappear
    BLOCK.MED, // Takes 2 hits to disappear
    BLOCK.EASY, // Takes 1 hit to disappear
    BLOCK.MAGIC1,
    // Delivers 1 hit to all surrounding blocks
    // and itself disappears
    BLOCK.MAGIC2 // Increases Paddle Size for 10 Seconds
};
// Initialization of blocks(Maximum
// of 64 blocks can be accommodated on screen)
```

```
enum blocks block [64];
```

block enumerated variable is thus initialized.

Following this, various functions are defined as follows:

ballMovement(). This function has the ball direction state machine, which continuously controls ball motion. Ball is reflected off the left,right, top walls and also off the paddle. It also checks for brick collision at all times, and is reflected off of the brick if it is present and also delivers 1 hit to the brick. Initially, it also checks whether all bricks are cleared(for victory condition).

```
void ballMovement(void)
    volatile unsigned char arrayCount = 0;
    victoryCheck = 1;
    for(arrayCount = 0; arrayCount < 32; arrayCount++)</pre>
        if(block[arrayCount] != NONE)
            victoryCheck = 0;
            break;
    switch(direction){
    case INIT:
        ballDisplay(ballInit);
        direction = UP_LEFT;
        break;
    case UPLEFT:
        if(ballXPos > 0)
            ballXPos --;
        if (ballYPos > 0)
            ballYPos --;
        ballXMapInt = (ballXPos/2);
        if(block[ballXMapInt + (8*(ballYPos+1))] != NONE)
```

```
blockClear(ballXMapInt, (ballYPos+1));
        direction = UP_RIGHT;
        ballXPos++;
        ballYPos++;
        break;
    // Check whether there is a brick to the top, if so,
   else if(block[ballXMapInt + (8*ballYPos)] != NONE)
        blockClear(ballXMapInt, ballYPos);
        direction = DOWNLEFT;
        ballXPos++;
        ballYPos++;
        break;
   else
        /* Display the ball as per UP_LEFT coordinates
        8x8 frames using GLCD. There are two ball displays
        ballDisplay(ball3);
        millis (ballMovSpeed / 2);
        ballDisplay(ball1);
        millis (ballMovSpeed / 2);
        if(ballXPos == 0)
            direction = UP_RIGHT;
            if(ballYPos == 0)
                direction = DOWN_RIGHT;
                break;
            break;
        if(ballYPos == 0)
            direction = DOWNLEFT;
        break;
case UP_RIGHT:
```

```
if(ballXPos < 15)</pre>
    ballXPos++;
if (ballYPos > 0)
    ballYPos --;
ballXMapInt = (ballXPos/2);
if(block[ballXMapInt + (8*(ballYPos+1))] != NONE)
    blockClear(ballXMapInt, (ballYPos+1));
    direction = UP_LEFT;
    ballXPos --;
    ballYPos++;
    break;
// Check whether there is a brick to the top, if so,
else if(block[ballXMapInt + (8*ballYPos)] != NONE)
    blockClear(ballXMapInt, ballYPos);
    direction = DOWN.RIGHT;
    ballXPos --;
    ballYPos++;
    break;
else
{
    /* Display the ball as per UP_RIGHT co ordinates
    in different quadrants for fluider ball motion) */
    ballDisplay(ball3);
    millis (ballMovSpeed / 2);
    ballDisplay(ball0);
    millis (ballMovSpeed / 2);
    if (ballXPos == 15)
    {
        direction = UP_LEFT;
        if(ballYPos == 0)
```

```
direction = DOWNLEFT;
                break;
        if(ballYPos == 0)
            direction = DOWN_RIGHT;
        break;
case DOWNRIGHT:
    if(ballXPos < 15)</pre>
        ballXPos++;
    if (ballYPos < 7)
        ballYPos++;
    /* Maps ball position to correspond to brick position,
    hence divided by 2. */
    ballXMapInt = (ballXPos/2);
    if(block[ballXMapInt + (8*(ballYPos -1))] != NONE)
        blockClear(ballXMapInt, (ballYPos - 1));
        direction = DOWNLEFT;
        ballXPos --;
        ballYPos --;
        break;
    else if(block[ballXMapInt + (8*ballYPos)] != NONE)
        blockClear(ballXMapInt, ballYPos);
        direction = UP_RIGHT;
        ballXPos --;
        ballYPos --;
        break;
    else
        ballDisplay(ball0);
        millis (ballMovSpeed / 2);
```

```
if (ballXPos == 15)
    direction = DOWNLEFT;
if(ballYPos == 7)
    switch(gameplayChange){
    case NORMAL:
        if((ballXPos >= ((paddleXPos - 6)/8))
        && (ballXPos \leq ((paddleXPos + 6)/8)))
            direction = UP_RIGHT;
            paddleBeep();
            break;
        else
            // then a life is lost
            gameplayMode = DEATH;
            break;
    case SPECIAL:
        if((ballXPos >= ((paddleXPos-12)/8))
        && (ballXPos \leq ((paddleXPos + 12)/8)))
            direction = UP_RIGHT;
            paddleBeep();
            break;
        else
        {
            gameplayMode = DEATH;
```

```
break;
        ballDisplay(ball3);
        millis (ballMovSpeed / 2);
        break;
case DOWNLEFT:
   if(ballXPos > 0)
        ballXPos --;
   if (ballYPos < 7)
        ballYPos++;
   /* Maps ball position to correspond to brick
   and 8 Brick Positions, hence divided by 2 */
   ballXMapInt = (ballXPos/2);
   /* Check whether there is a brick to the left,
   if(block[ballXMapInt + (8*(ballYPos -1))] != NONE)
        blockClear(ballXMapInt, (ballYPos - 1));
        direction = DOWN.RIGHT;
        ballXPos++;
        ballYPos --;
        break;
    // Check whether there is a brick down,
   else if(block[ballXMapInt + (8*ballYPos)] != NONE)
        blockClear(ballXMapInt, ballYPos);
        direction = UP_LEFT;
        ballXPos++;
        ballYPos --;
        break;
   else
        ballDisplay(ball3);
```

```
millis (ballMovSpeed / 2);
if(ballXPos == 0)
    direction = DOWN_RIGHT;
if(ballYPos == 7)
    /* Based on size of
    the paddle */
    switch(gameplayChange){
    case NORMAL:
        // Normal sized paddle,
        if((ballXPos >= ((paddleXPos - 6)/8))
        && (ballXPos \leq ((paddleXPos + 6)/8)))
            direction = UP_LEFT;
            paddleBeep();
            break;
        else
            gameplayMode = DEATH;
            break;
    case SPECIAL:
        if((ballXPos >= ((paddleXPos - 12)/8))
        && (ballXPos \leq ((paddleXPos + 12)/8)))
            // If special paddle is present,
            direction = UP\_LEFT;
            paddleBeep();
            break;
        else
```

readInput(). This function switches input behaviour based on the overall state of the game. It includes initial menu navigation using a cursor, which switches between settings, instructions and menu screen using on board switch presses alone. Once in gameplay mode, input is through the ADC Joystick, and Joystick ADC is mapped as per paddle size. Is implemented as a task in RTOS, initialized with readInputSem Semaphore.

```
mode = GAMEPLAY;
        gameplayMode = ENTER;
        entryBeep();
        glcd_clearDisplay();
    else if(detectKeyPress(2) == 1)
        cursorPos = TWO;
        blockBeep();
    break;
case TWO:
    if(detectKeyPress(1) == 1)
    {
        // Once RIGHT SWITCH is pressed,
        mode = INSTRUCTIONS;
        entryBeep();
        glcd_clearDisplay();
    else if (\text{detectKeyPress}(0) = 1)
        cursorPos = ONE;
        blockBeep();
    else if (\text{detectKeyPress}(2) == 1)
        cursorPos = THREE;
        blockBeep();
    break;
case THREE:
    if(detectKeyPress(1) == 1)
        mode = SETTINGS;
        entryBeep();
```

```
glcd_clearDisplay();
        glcd_write(settingsScreen);
        cursorPos = ONE;
    else if (\text{detectKeyPress}(0) = 1)
        cursorPos = TWO;
        blockBeep();
    break;
break;
case INSTRUCTIONS:
    if(detectKeyPress(3) == 1)
        menuMode = ENTRY;
        mode = MENU;
        glcd_clearDisplay();
    break;
case SETTINGS:
    switch(cursorPos){
    case ONE:
        if(detectKeyPress(1) == 1)
             difficulty = HARD;
            lifeCount = 1; // Only One Life
        else if (detectKeyPress(3) == 1)
            difficulty = EASY;
            lifeCount = 3; // Three Lives
        else if (\text{detectKeyPress}(4) == 1)
```

```
difficulty = MEDIUM;
        lifeCount = 2; // Two Lives
    else if (\text{detectKeyPress}(0) == 1)
        mode = MENU;
        menuMode = ENTRY;
    else if(detectKeyPress(2) == 1)
        cursorPos = TWO;
    break;
case TWO:
    if(detectKeyPress(1) == 1)
        // fastest option. Also correspondingly
        // paddle movement is set to a
        faster speed for a balanced gameplay
        ballSpeed = FASTER;
        ballMovSpeed = 175;
        paddleSpeed = 4;
    else if (\text{detectKeyPress}(3) == 1)
        // slowest option. Also correspondingly
        ballSpeed = SLOW;
        ballMovSpeed = 325;
        paddleSpeed = 2;
    else if (detectKeyPress(4) == 1)
        // Also correspondingly paddle movement
        ballSpeed = FAST;
```

```
ballMovSpeed = 250;
        paddleSpeed = 3;
    else if (\text{detectKeyPress}(0) == 1)
        cursorPos = ONE;
    else if(detectKeyPress(2) == 1)
        // If DOWN SWITCH is pressed, move back
        mode = MENU;
        menuMode = ENTRY;
    break;
break;
case GAMEPLAY:
    if(gameplayMode == ALWAYS)
        ADCIntClear(ADC1_BASE, 3);
        ADCProcessorTrigger(ADC1_BASE, 3);
        /* Wait till conversion is complete */
        while (! ADCIntStatus (ADC1_BASE, 3,
        false))
        /* Clear the ADC interrupt flag
        and get the conversion result */
        ADCIntClear (ADC1_BASE, 3);
        ADCSequenceDataGet (ADC1_BASE,
        3,&ui32ADC0Value);
        / given by ADC Joystick
        ui8XAxisAvg = 128 - (ui32ADC0Value/32);
        switch(gameplayChange){
        case NORMAL:
            if (ui8XAxisAvg > 100)
```

```
// If paddle is moved to
        if(paddleXPos >= 120)
            paddleXPos = 120;
            /* Limit Maximum
            screen */
        else
            paddleXPos += paddleSpeed;
            /* Move paddle to
            a sticky manner
            zero)*/
    else if(ui8XAxisAvg <= 28)</pre>
    {
        if(paddleXPos <= 8)</pre>
            paddleXPos = 8;
            // does not move off screen
            paddleXPos -= paddleSpeed;
            /* Move paddle to
            does not revert to zero) */
    // Display paddle at the determined
    paddleDisplay();
    break;
case SPECIAL:
    if(ui8XAxisAvg > 100)
    {
        if(paddleXPos >= 110)
```

```
paddleXPos = 110;
                                  // position so that special
                              else
                                  paddleXPos += paddleSpeed;
                                  // Move paddle to the right
                                  // in a sticky manner(paddle
                          else if(ui8XAxisAvg <= 28)</pre>
                          {
                              if(paddleXPos <= 18)</pre>
                                  paddleXPos = 18;
                              else
                                  paddleXPos -= paddleSpeed;
                                  /* Move paddle
                                  to zero) */
                          paddleSpecialDisplay();
                          break;
}
```

displayOutput(). This function switches output behaviour based on the overall state of the game. It provides control over buzzer, GLCD and LEDs. Different screens are displayed in different states accordingly with appropriate animations wherever applicable. Is implemented as a task in RTOS, initialized with

displayOutputSem Semaphore.

```
void displayOutput(void)
   while(1)
   {
        /* Semaphore_pend(*sem, wait/timeout)
        * decrements the semaphore by 1.
        * Until semaphore value is zero task is
        * blocked.
       Semaphore_pend(displayOutputSem, BIOS_WAIT_FOREVER);
       // Once Semaphore is posted, Switching State Machine
       switch(mode){
        case MENU:
           switch (menuMode) {
            case ENTRY:
                cursorPos = ONE;
                glcd_write(menuScreen);
                mode = MENU;
                displaySmallText("PLAY", 3, 6);
                displaySmallText("INSTRUCTIONS", 5, 2);
                displaySmallText("SETTINGS", 7, 4);
                menuMode = THROUGHOUT;
                startBeep();
                break;
            case THROUGHOUT:
                cursorDisplay();
                break;
            break;
            case INSTRUCTIONS:
                displaySmallText("USE THUMB STICK
                TO MOVE PADDLE", 0, 0;
                displaySmallText("YOU HAVE THREE LIVES", 3, 0);
                displaySmallText("CLEAR ALL BRICKS", 6, 0);
                displaySmallText("ALL THE BEST!", 7, 0);
                break:
            case SETTINGS:
```

```
// In the Settings State
displaySmallText("DIFFICULTY",\ 3,\ 2);
// display different difficulty modes as selected,
switch(difficulty){
case EASY:
    displaySmallText("EASY", 4, 9);
    break:
case MEDIUM:
    displaySmallText("HARD", 4, 9);
    break;
case HARD:
    displaySmallText("INSANE", 4, 9);
    break;
displaySmallText("BALL SPEED", 5, 2);
switch(ballSpeed){
case SLOW:
    displaySmallText("SLOW", 6, 9);
    break;
case FAST:
    displaySmallText("FAST ", 6, 9);
    break;
case FASTER:
    displaySmallText("EXTREME", 6, 9);
    break;
cursorDisplay();
break;
case GAMEPLAY:
    switch(gameplayMode){
    case ENTER:
        lifeCountTemp = lifeCount;
        score_str[0] = "0";
        score_str[1] = "0";
        score_str[2] = "0";
        paddleXPos = 64;
        paddleXPrev = paddleXPos;
        gameplayChange ⇒NORMAL;
```

```
// Paddle size
appropriate number of lives screen
switch(difficulty){
case EASY:
    screenFlash(threeLivesScreen);
    break;
case MEDIUM:
    screenFlash(twoLivesScreen);
    break;
case HARD:
    screenFlash(oneLifeScreen);
    break;
gameScreen();
ballXPos = 7;
ballXPrev = 7;
ballYPos = 7;
ballYPrev = 7;
gameplayMode = ALWAYS;
break;
case DEATH:
    motorON();
    lifeCountTemp --;
    if(lifeCountTemp == 2)
    {
        screenFlash(twoLivesScreen);
        gameplayMode = REENTER;
    else if(lifeCountTemp == 1)
        screenFlash(oneLifeScreen);
        gameplayMode = REENTER;
    else if(lifeCountTemp == 0)
        mode = GAMEOVER;
```

```
// mode when player runs
        break;
    case REENTER:
        gameScreenRefresh();
        ballXPos = 7;
        ballXPrev = 7;
        ballYPos = 7;
        ballYPrev = 7;
        motorOFF();
        direction = INIT;
        gameplayMode = ALWAYS;
        break;
    case ALWAYS:
        ballMovement();
        {\tt satisfaction}
        if(victoryCheck == 1)
            mode = VICTORY;
        ledOFF(1);
        ledOFF(2);
        ledOFF(3);
        ledOFF(4);
        break;
break;
case VICTORY:
    motorOFF();
    victoryAnimationDisplay();
    // Display a firework themed victory
    animation
    play_GOT();
    glcd_write(creditsScreen);
    millis (5000);
    mode = MENU; // Return to Menu
```

```
menuMode = ENTRY;
                     break;
                 case GAMEOVER:
                     motorOFF();
                     direction = INIT;
                     glcd_write(gameOverScreen);
                     displaySmallText(score_str, 5, 9);
                     gameOverMusic();
                     millis (2000);
                     glcd_write(creditsScreen);
                     millis (5000);
                     scoreInt = 0;
                     menuMode = ENTRY; // Return to Menuu
                     mode = MENU;
                     break;
}
```

main() function serves to initialize and start the BIOS. The BIOS handles
program execution. Now, the main() function is defined as follows:

```
int main(void) {
    latency = 5;

    // Initialization of peripherals
    // using functions in Console Directory
    _init_();
    glcd_init();
    glcd_clearDisplay();
    srand(time(NULL));
    // For Randomization of Blocks

    glcd_write(titleScreen);
    // Display Cutscene
    play_MarioBros();
    // Play Mario Brothers Theme
    using Tones Library

BIOS_start(); // Start BIOS

return(0);
}
```

The Timer2\_ISR() is defined, which is used to count to 10 seconds for the SPECIAL mode of the paddle when it hits BLOCK\_MAGIC2. Started on hit, and turned off on countdown.

```
void Timer1_ISR(void)
{
    ROM_TimerIntClear(TIMER1_BASE, TIMER_TIMA_TIMEOUT);
    specialTimeCount++;
    if(specialTimeCount > 10000)
    {
        specialTimeCount = 0;
        gameplayChange = NORMAL;
        glcd_clearRow(7);
        // Clear residual larger paddle
        // (will remain displayed otherwise)
        specialExitBeep();
        // Disable Timer
        ROM_TimerDisable(TIMER1_BASE, TIMER_A);
        ROM_IntDisable(INT_TIMER1A);
        ROM_TimerIntDisable(TIMER1_BASE, TIMER_TIMA_TIMEOUT);
    }
}
```

Finally, the Timer2\_ISR() is defined, which implements the task scheduling as shown:

```
void Timer2_ISR(void)
{
    // Clear Interrupt
    ROM_TimerIntClear(TIMER2_BASE, TIMER_TIMA_TIMEOUT);
    tickCount++;
    switch(tickCount){
        case 10:
            Semaphore_post(displayOutputSem);
            // Post Output Display Semaphore
            break;
        case 40:
            Semaphore_post(readInputSem);
            // Post Input Read Semaphore
            tickCount=0;
            break;
    }
}
```

This is the complete code for the Breakout Game, with a complete statechart implementation.