


# Circulations

**Circulation**  
Demands  
Lower bounds

**Examples**  
Survey design  
Arrodoniment amb  
restrictions  
Image segmentation



# 1 Circulation

## Circulation

Demands

Lower bounds

## Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation

# 2 Examples

# Circulation with demands

- We introduce another flow problem, to deal with supply and demand inside a network.
- Instead of having a pair source/sink the new setting consider a producer/consumer scenario.

Circulation

Demands

Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions


Image segmentation

# Circulation with demands

- We introduce another flow problem, to deal with supply and demand inside a network.
- Instead of having a pair source/sink the new setting consider a producer/consumer scenario.
- Some nodes are able to produce a certain amount of flow.
- Some nodes are willing to consume flow.
- The question is whether it is possible to route “all” the produced flow to the consumers. When possible the flow assignment is called a **circulation**

# Network with demands

A **network with demands**  $\mathcal{N}$  is a tuple  $(V, E, c, d)$  where  $c$  assigns a positive capacity to each edge, and  $d$  is a function associating a demand  $d(v)$ , to  $v \in V$ .



Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrondissement amb  
restrictions

Image segmentation

# Network with demands

Circulation  
Demands  
Lower bounds


Examples

Survey design

Arrondissement amb  
restrictions

Image segmentation

A **network with demands**  $\mathcal{N}$  is a tuple  $(V, E, c, d)$  where  $c$  assigns a positive capacity to each edge, and  $d$  is a function associating a demand  $d(v)$ , to  $v \in V$ .



- When  $d(v) > 0$ ,  $v$  can receive  $d(v)$  units of flow more than it sends,  $v$  is a **sink**.
- If  $d(v) < 0$ ,  $v$  can send  $d(v)$  units of flow more than it receives,  $v$  is a **source**.
- If  $d(v) = 0$ ,  $v$  is neither a source or a sink.

# Network with demands

Circulation  
Demands  
Lower bounds


Examples

Survey design

Arrondissement amb  
restrictions

Image segmentation

A **network with demands**  $\mathcal{N}$  is a tuple  $(V, E, c, d)$  where  $c$  assigns a positive capacity to each edge, and  $d$  is a function associating a demand  $d(v)$ , to  $v \in V$ .




- When  $d(v) > 0$ ,  $v$  can receive  $d(v)$  units of flow more than it sends,  $v$  is a **sink**.
- If  $d(v) < 0$ ,  $v$  can send  $d(v)$  units of flow more than it receives,  $v$  is a **source**.
- If  $d(v) = 0$ ,  $v$  is neither a source or a sink.
- Define  $S$  to be the set of sources and  $T$  the set of sinks.

# Network with demands: circulation

Given a network  $\mathcal{N} = (V, E, c, d)$ , a **circulation** is a flow assignment  $f : E \rightarrow \mathbb{R}^+$  s.t.

- 1 capacity:** For each  $e \in E$ ,  $0 \leq f(e) \leq c(e)$ ,
- 2 conservation:** For each  $v \in V$ ,

$$\sum_{(u,v) \in E} f(u,v) - \sum_{(v,z) \in E} f(v,z) = d(v).$$



# Network with demands: circulation


Given a network  $\mathcal{N} = (V, E, c, d)$ , a **circulation** is a flow assignment  $f : E \rightarrow \mathbb{R}^+$  s.t.

**1 capacity:** For each

$$e \in E, 0 \leq f(e) \leq c(e),$$

**2 conservation:** For each  $v \in V$ ,

$$\sum_{(u,v) \in E} f(u,v) - \sum_{(v,z) \in E} f(v,z) = d(v).$$




Take into account that a circulation might not exist.

# Network with demands: circulation problem

**Circulation problem:** Given  $\mathcal{N} = (V, E, c, d)$  with  $c > 0$ , obtain a circulation provided it does exists.

Circulation  
Demands  
Lower bounds  
  
Examples  
Survey design  
Arrodoniment amb restrictions  
Image segmentation



# A first conditions for a circulation to exists

If  $f$  is a circulation for  $\mathcal{N} = (V, E, c, d)$ ,

$$\sum_{v \in V} d(v) = \sum_{v \in V} \left( \underbrace{\sum_{(u,v) \in E} f(u,v)}_{\text{edges to } v} - \underbrace{\sum_{(v,z) \in E} f(v,z)}_{\text{edges out of } v} \right).$$

Circulation  
Demands  
Lower bounds

Examples  
Survey design  
Arrodoniment amb  
restrictions  
Image segmentation

# A first conditions for a circulation to exists

If  $f$  is a circulation for  $\mathcal{N} = (V, E, c, d)$ ,

$$\sum_{v \in V} d(v) = \sum_{v \in V} \left( \underbrace{\sum_{(u,v) \in E} f(u,v)}_{\text{edges to } v} - \underbrace{\sum_{(v,z) \in E} f(v,z)}_{\text{edges out of } v} \right).$$

For  $e = (u, v) \in E$ ,  $f(e)$  appears in the sum of edges to  $v$  and in the sum of edges out of  $u$ . Both terms cancel!

# A first conditions for a circulation to exists

If  $f$  is a circulation for  $\mathcal{N} = (V, E, c, d)$ ,

$$\sum_{v \in V} d(v) = \sum_{v \in V} \left( \underbrace{\sum_{(u,v) \in E} f(u,v)}_{\text{edges to } v} - \underbrace{\sum_{(v,z) \in E} f(v,z)}_{\text{edges out of } v} \right).$$

For  $e = (u, v) \in E$ ,  $f(e)$  appears in the sum of edges to  $v$  and in the sum of edges out of  $u$ . Both terms cancel!

Then,  $\sum_{v \in V} d(v) = 0$ .

# A first conditions for a circulation to exists

If there is a circulation, then  $\sum_{v \in V} d(v) = 0$ .

Recall that

$$S = \{v \in V | d(v) < 0\} \text{ and}$$

$$T = \{v \in V | d(v) > 0\}.$$

Define  $D = -\sum_{v \in S} d(v) = \sum_{v \in T} d(v)$ .

# A first conditions for a circulation to exists

If there is a circulation, then  $\sum_{v \in V} d(v) = 0$ .


Recall that

$$S = \{v \in V | d(v) < 0\} \text{ and}$$

$$T = \{v \in V | d(v) > 0\}.$$

Define  $D = -\sum_{v \in S} d(v) = \sum_{v \in T} d(v)$ .


$D$  is the total amount of extra flow that has to be transported from the sources to the sinks.



# Circulation problem: reduction to Max-flow

From  $\mathcal{N} = (V, E, c, d)$ , define a flow network  
 $\mathcal{N}' = (V', E', c', s, t)$ :

- $V' = V \cup \{s, t\}$ , we add a source  $s$  and a sink  $t$ .
- For  $v \in S$  ( $d(v) < 0$ ), add  $(s, v)$  with capacity  $-d(v)$ .
- For  $v \in T$  ( $d(v) > 0$ ), add  $(v, t)$  with capacity  $d(v)$ .
- Keep  $E$  and, for  $e \in E$ ,  $c'(e) = c(e)$ .




# Circulation problem: reduction to Max-flow

Circulation  
Demands  
Lower bounds  
  
Examples  
Survey design  
Arrondissement amb  
restrictions  
Image segmentation

From  $\mathcal{N} = (V, E, c, d)$ , define a flow network  
 $\mathcal{N}' = (V', E', c', s, t)$ :

- $V' = V \cup \{s, t\}$ , we add a source  $s$  and a sink  $t$ .
- For  $v \in S$  ( $d(v) < 0$ ), add  $(s, v)$  with capacity  $-d(v)$ .
- For  $v \in T$  ( $d(v) > 0$ ), add  $(v, t)$  with capacity  $d(v)$ .
- Keep  $E$  and, for  $e \in E$ ,  $c'(e) = c(e)$ .



# Circulation problem: reduction to Max-flow

1.- Every flow  $f'$  in  $\mathcal{N}'$  verifies  $|f'| \leq D$

Circulation

Demands

Lower bounds

Examples

Survey design


Arrodoniment amb  
restrictions

Image segmentation

# Circulation problem: reduction to Max-flow

1.- Every flow  $f'$  in  $\mathcal{N}'$  verifies  $|f'| \leq D$

The capacity  $c'(\{s\}, V) = D$ , by the capacity restriction on flows,  $|f'| \leq D$ .



# Circulation problem: reduction to Max-flow

2.- If there is a circulation  $f$  in  $\mathcal{N}$ , we have a max-flow  $f'$  in  $\mathcal{N}'$  with  $|f'| = D$ .

Extend  $f$  to a flow  $f'$ , assigning  $f'(s, v) = -d(v)$ , for  $v \in S$ , and  $f'(u, t) = d(u)$ , for  $u \in T$ .

Circulation

Demands

Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation


# Circulation problem: reduction to Max-flow

Circulation  
Demands  
Lower bounds  
Examples  
Survey design  
Arrondissement amb  
restrictions  
Image segmentation

2.- If there is a circulation  $f$  in  $\mathcal{N}$ , we have a max-flow  $f'$  in  $\mathcal{N}'$  with  $|f'| = D$ .

Extend  $f$  to a flow  $f'$ , assigning  $f'(s, v) = -d(v)$ , for  $v \in S$ , and  $f'(u, t) = d(u)$ , for  $u \in T$ .

By the circulation condition,  $f'$  is a flow in  $\mathcal{N}'$ . Furthermore,  $|f'| = D$ .




# Analysis

3.- If there is a flow  $f'$  in  $\mathcal{N}'$  with  $|f'| = D$ ,  $\mathcal{N}$  has a circulation

For  $e \in E$ , define  $f(e) = f'(e)$ .

- As  $|f'| = D$ , all edges  $(s, v) \in E'$  and  $(u, t) \in E'$  are saturated by  $f'$ .
- By flow conservation,  $f$  satisfies  $d(v) = \sum_{(u,v) \in E} f(u, v) - \sum_{(v,z) \in E} f(v, z)$ .
- So,  $f$  is a circulation for  $\mathcal{N}$ .



# Circulation: main results

From the previous discussion, we can conclude:

**Theorem (Necessary and sufficient condition)**

*There is a circulation for  $\mathcal{N} = (V, E, c, d)$  iff the maxflow in  $\mathcal{N}'$  has value  $D$ .*

Circulation

Demands

Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation

# Circulation: main results

From the previous discussion, we can conclude:

Theorem (**Necessary and sufficient condition**)

*There is a circulation for  $\mathcal{N} = (V, E, c, d)$  iff the maxflow in  $\mathcal{N}'$  has value  $D$ .*

Theorem (**Circulation integrality theorem**)

*If all capacities and demands are integers, and there exists a circulation, then there exists an integer valued circulation.*

Sketch Proof Max-flow formulation + integrality theorem for max-flow



# Circulation: main results

## Theorem

*There is a polynomial time algorithm to solve the circulation problem.*

The cost of the algorithm is the same as the cost of the algorithm used for the MaxFlow computation.

Circulation  
Demands  
Lower bounds

Examples  
Survey design  
Arrodoniment amb restriccions  
Image segmentation

# Circulation: main results

## Theorem

*There is a polynomial time algorithm to solve the circulation problem.*

The cost of the algorithm is the same as the cost of the algorithm used for the MaxFlow computation.

## Theorem

*If all capacities and demands are integers, and there exists a circulation, then we can obtain an integer valued circulation in time  $O(Dm)$ .*

# Networks with demands and lower bounds

Generalization of the previous problem: besides satisfy demands at nodes, we want to force the flow to use certain edges.

Circulation

Demands

Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation

# Networks with demands and lower bounds

Generalization of the previous problem: besides satisfy demands at nodes, we want to force the flow to use certain edges.

Introduce a new constrain  $\ell(e)$  on each  $e \in E$ , indicating the min-value the flow must be on  $e$ .

Circulation  
Demands  
Lower bounds


Examples  
Survey design  
Arrodoniment amb restrictions  
Image segmentation

# Networks with demands and lower bounds

Generalization of the previous problem: besides satisfy demands at nodes, we want to force the flow to use certain edges.

Introduce a new constraint  $\ell(e)$  on each  $e \in E$ , indicating the min-value the flow must be on  $e$ .

A network  $\mathcal{N}$  with **demands and lower bounds** is a tuple  $(V, E, c, \ell, d)$  with  $c(e) \geq \ell(e) \geq 0$ , for each  $e \in E$ ,




# Networks with demands and lower bounds: circulation

Given a network  $\mathcal{N} = (V, E, c, \ell, d)$  a **circulation** as a flow assignment  $f : E \rightarrow \mathbb{R}^+$  s.t.

- 1 capacity: For each  $e \in E$ ,  
 $\ell(e) \leq f(e) \leq c(e)$ ,

- 2 conservation: For each  $v \in V$ ,

$$\sum_{(u,v) \in E} f(u, v) - \sum_{(v,z) \in E} f(v, z) = d(v).$$



A circulation might not exist.

# Circulations with demands and lower bounds problem

Circulation with demands and lower bounds problem: Given  $\mathcal{N} = (V, E, c, \ell, d)$ , obtain a circulation for  $\mathcal{N}$ , provided it does exists


Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrondissement amb  
restrictions

Image segmentation



# Circulations with demands and lower bounds problem

Circulation with demands and lower bounds problem: Given  $\mathcal{N} = (V, E, c, \ell, d)$ , obtain a circulation for  $\mathcal{N}$ , provided it does exists


Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrodoniment amb restriccions

Image segmentation



We devise an algorithm to the problem by a reduction to a circulation with demands problem.


# Circulations with demands and lower bounds: the reduction

Let  $\mathcal{N} = (V, E, c, \ell, d)$ , construct a network  $\mathcal{N}' = (V, E, c', d')$  with only demands as follows:

Initially set  $c' = c$  and  $d' = d$ .

For each  $e = (u, v) \in E$ , with  $\ell(e) > 0$ :

- $c'(e) = c(e) - \ell(e)$ .
- Update the demands on both ends of  $e$ :  
 $d'(u) = d(u) + \ell(e)$  and  $d'(v) = d(v) - \ell(e)$



# Circulations with demands and lower bounds: the reduction

1.- If  $f$  is a circulation in  $\mathcal{N}$ ,  $f'(e) = f(e) - \ell(e)$ , for  $e \in E$ , is a circulation in  $\mathcal{N}'$ .

Circulation  
Demands  
Lower bounds

Examples  
Survey design  
Arrodoniment amb restrictions  
Image segmentation


# Circulations with demands and lower bounds: the reduction

1.- If  $f$  is a circulation in  $\mathcal{N}$ ,  $f'(e) = f(e) - \ell(e)$ , for  $e \in E$ , is a circulation in  $\mathcal{N}'$ .

By construction of  $\mathcal{N}'$ ,  $f'$  verifies the capacity constraint.

Besides, for  $(u, v)$  with  $\ell(u, v) > 0$ , the flow out of  $u$  and the flow in  $v$  is decreased by  $\ell(u, v)$ .

$f$  is a circulation in  $\mathcal{N}$  so, the flow imbalance of  $f'$  matches the demand  $d'$  at each node.



# Circulations with demands and lower bounds: the reduction

2.- If  $f'$  is a circulation in  $\mathcal{N}'$ ,  $f(e) = f'(e) + \ell(e)$ , for  $e \in E$ , is a circulation in  $\mathcal{N}$ .

Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation


# Circulations with demands and lower bounds: the reduction

2.- If  $f'$  is a circulation in  $\mathcal{N}'$ ,  $f(e) = f'(e) + \ell(e)$ , for  $e \in E$ , is a circulation in  $\mathcal{N}$ .

$f'$  verifies the capacity constraint  $f'(e) \geq 0$ , so  $f'(e) \geq \ell(e)$ .

$f'$  is a circulation, the  $f'$  imbalance at  $u$  is  $d'(u)$ .

Therefore, for  $(u, v)$  with  $\ell(u, v) > 0$ , the increase of flow in  $(u, v)$  balances  $\ell(u, v)$  units of flow out of  $u$  with  $\ell(u, v)$  units of flow entering  $v$ . Thus the  $f$  imbalance at  $u$  is  $d(u)$ .



# Main result

## Theorem

*There exists a circulation in  $\mathcal{N}$  iff there exists a circulation in  $\mathcal{N}'$ . Moreover, if all demands, capacities and lower bounds in  $\mathcal{N}$  are integers, and  $\mathcal{N}$  admits a circulation, there is a circulation in  $\mathcal{N}$  that is integer-valued.*

The integer-valued circulation part is a consequence of the integer-value circulation Theorem for  $f'$  in  $G'$ .

# Circulation with demands and lower bounds: main results

## Theorem

*There is a polynomial time algorithm to solve the circulation with demands and lower bounds problem.*

The cost of the algorithm is the same as the cost of the algorithm used for the circulation with demands computation.

Circulation  
Demands  
Lower bounds

Examples  
Survey design  
Arrondissement amb  
restrictions  
Image segmentation

# Circulation with demands and lower bounds: main results

## Theorem

*There is a polynomial time algorithm to solve the circulation with demands and lower bounds problem.*

The cost of the algorithm is the same as the cost of the algorithm used for the circulation with demands computation.

## Theorem

*If all capacities, lower bounds, and demands are integers, and there exists a circulation, then we can obtain an integer valued circulation in time  $O((D + L)m)$  where  $L$  is the sum of all lower bounds.*

## **1** Circulation

Circulation

Demands

Lower bounds

**Examples**

Survey design

Arrodoniment amb  
restrictions

Image segmentation

## **2** Examples

# SURVEY DESIGN problem

Problem: Design a survey among customers of products  
(KT-7.8)

- Customer  $i$  can only be asked about a bought product and must receive a questionnaire for at least  $c_i$  such products, those values are determined as function of the purchased products.
- For each product  $j$ , we want to collect data from a minimum of  $p_j$  customers.
- The  $c$  and  $p$  values cannot

© Original Artist  
Reproduction rights obtainable from  
[www.CartoonStock.com](http://www.CartoonStock.com)



search ID: cwhn1240

# SURVEY DESIGN problem

Circulation  
Demands  
Lower bounds  
  
Examples  
Survey design  
Arrodoniment amb  
restrictions  
Image segmentation

The input to the problem is:

A set  $C$  of  $n$  customers and a set  $P$  of  $m$  products.

- For each customer  $i \in C$ , a list of purchased products and the two values  $c_i \leq c'_i$ .
- For each product  $j \in P$ , two values  $p_j$  and  $p'_j$ .

Alternatively,

- The information about purchases can be represented as a bipartite graph  $G = (C \cup P, E)$ , where  $C$  is the set of customers and  $P$  is the set of products.
- $(i, j) \in E$  means  $i \in C$  has purchased product  $j \in P$ .

# SURVEY DESIGN: Input

Circulation  
Demands  
Lower bounds


Examples  
Survey design

Arrondissement amb  
restrictions  
Image segmentation

Customers  $C = \{a, b, c, d\}$   
Products  $P = \{1, 2, 3, 4, 5, 6\}$

Customer	Bought	c
a	1,2	1
b	1,2,4	1
c	3,6	1
d	3,4,5,6	2

Prod.	1	2	3	4	5	6
d	1	1	1	1	0	1



# SURVEY DESIGN: Circulation with lower bounds formulation

We construct a network  $\mathcal{N} = (V', E', c, \ell)$  from  $G$  as follows:

- Nodes:  $V' = V \cup \{s, t\}$
- Edges:  $E'$  contains  $E$  and edges  $s \rightarrow \{C\}$ ,  $\{P\} \rightarrow t$ , and  $(t, s)$ .
- Capacities and lower bounds:
  - $c(t, s) = \infty$  and  $\ell(t, s) = 0$
  - For  $i \in C$ ,  $\ell(s, i) = c_i$  and  $c(s, i) =$  the number of purchased products.
  - For  $j \in P$ ,  $\ell(j, t) = p_j$  and  $c(j, t) =$  number of customers that purchased  $j$ .
  - For  $(i, j) \in E$ ,  $c(i, j) = 1$ , and  $\ell(i, j) = 0$ .

Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation

# SURVEY DESIGN: Circulation with lower bounds formulation

Circulation  
Demands  
Lower bounds


Examples  
Survey design

Arrondissement amb  
restrictions  
Image segmentation

Customers  $C = \{a, b, c, d\}$   
Products  $P = \{1, 2, 3, 4, 5, 6\}$

Customer	Bought	c
a	1,2	1
b	1,2,4	1
c	3,6	1
d	3,4,5,6	2

Prod.	1	2	3	4	5	6
d	1	1	1	1	0	1




# SURVEY DESIGN: Circulation interpretation

Circulation  
Demands  
Lower bounds  
  
Examples  
Survey design  
Arrodoniment amb restriccions  
Image segmentation

If  $f$  is a circulation in  $\mathcal{N}$ :

- one unit of flow circulates  
 $s \rightarrow i \rightarrow j \rightarrow t \rightarrow s$ .
- $f(i, j) = 1$  means ask  $i$  about  $j$ ,
- $f(s, i)$  # products to ask  $i$  for opinion,
- $f(j, t)$  # customers to be asked to review  $j$ ,
- $f(t, s)$  is the total number of questionnaires.




# SURVEY DESIGN: Circulation vs solutions

Circulation  
Demands  
Lower bounds  
  
Examples  
Survey design  
Arrodoniment amb  
restrictions  
Image segmentation

## A solution

- Ask *a* about 1, 2.
- Ask *b* about 1, 2, 4.
- Ask *c* about 3, 6.
- Ask *d* about 3, 4, 5.



# Main result

Circulation  
Demands  
Lower bounds

Examples  
Survey design

Arrondissement amb  
restrictions  
Image segmentation

**Theorem**  $\mathcal{N}$  has a circulation iff there is a feasible way to design the survey.

**Proof** if there is a feasible way to design the survey:

- if  $i$  is asked about  $j$  then  $f(i, j) = 1$ ,
- $f(s, i) = \text{number questions asked to } i (\geq c_i)$ .
- $f(j, t) = \text{number of customers who were asked about } j (\geq d_j)$ ,
- $f(t, s) = \text{total number of questions}$ .
- easy to verify that  $f$  is a circulation in  $\mathcal{N}$

If there is an integral circulation in  $\mathcal{N}$ :

- if  $f(i, j) = 1$  then  $i$  will be asked about  $j$ ,
- the constraints will be satisfied by the capacity rule.

# Cost of the algorithm

- $\mathcal{N}$  has  $N = n + m + 2$  vertices and  $E = n + m + nm$  edges
- $L = \sum_e \ell(e) \leq nm$ .
- Obtain  $\mathcal{N}$  and extract the information from the circulation has cost  $O(nm)$ .
- FF analysis, the cost of obtaining a circulation  $O(L(N + M)) = O(n^2m^2)$ .
- EK analysis, the cost of obtaining a circulation  $O(NM(N + M)) = O((n + m)n^2m^2)$ .
- The algorithm has cost  $O(n^2m^2)$ .

# Arrodoniment amb restriccions

Considerem una matriu  $A = (a_{ij})$  amb dimensions  $n \times n$ , on cada  $a_{ij} \in \mathbb{R}^+ \cup \{0\}$  i on la suma de cada fila i columna de  $A$  és un enter. Volem arrodonir cada valor  $a_{ij}$  per  $\lfloor a_{ij} \rfloor$  o  $\lceil a_{ij} \rceil$  sense modificar la suma de les files/columnes.

Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrodoniment amb  
restriccions

Image segmentation

# Arrodoniment amb restriccions

Considerem una matriu  $A = (a_{ij})$  amb dimensions  $n \times n$ , on cada  $a_{ij} \in \mathbb{R}^+ \cup \{0\}$  i on la suma de cada fila i columna de  $A$  és un enter. Volem arrodonir cada valor  $a_{ij}$  per  $\lfloor a_{ij} \rfloor$  o  $\lceil a_{ij} \rceil$  sense modificar la suma de les files/columnes.

$$\begin{pmatrix} 10.9 & 2.5 & 1.3 & 9.3 \\ 3.8 & 9.2 & 2.2 & 11.8 \\ 7.9 & 5.2 & 7.3 & 0.6 \\ 3.4 & 13.1 & 1.2 & 6.3 \end{pmatrix} F \rightarrow \begin{pmatrix} 11 & 3 & 1 & 9 \\ 4 & 9 & 2 & 12 \\ 7 & 5 & 8 & 1 \\ 4 & 13 & 2 & 6 \end{pmatrix}$$

# Arrodoniment amb restriccions

El problema consisteix en donada una matriu  $A$ , produir un algorisme eficient per a determinar si es possible arrodonir  $A$  i, si es possible, produir la matriu arrodonida.

Demostreu la correctesa del vostre algorisme. Quina es la complexitat del vostre algorisme?.

## Notem que

- Els elements d' $A$  que són enters no s'han de modificar.
- Sigui  $r_i = \sum_{j=1}^n (a_{ij} - \lfloor a_{ij} \rfloor)$  i  $c_j = \sum_{i=1}^n (a_{ij} - \lfloor a_{ij} \rfloor)$
- si les files i columnes d' $A$  sumen un enter, aleshores  $r_i$  i  $c_j$  son enters.
- A més  $\sum_i r_i = \sum_j c_j$ .

Per a resoldre el problema farem una reducció d'aquest problema a un problema de circulació.

Una unitat de flux la podem interpretar com una part decimal que s'arrodoneix a 1.

Construir una xarxa amb demandes  $\mathcal{N} = (V, E, c, d)$  on:

- **Vertexs:**  $V = \{x_i, y_j | 1 \leq i \leq n\}$ . Els vèrtexs  $x$  representen les files i els  $y$  les columnes.
- **Arestes:**  $E = \{(x_i, y_j) | 1 \leq i, j \leq n \text{ i } a_{i,j} \notin \mathbb{Z}\}$
- **Capacitats:**  $c(x_i, y_j) = 1$ .
- **Demandes:**  $d(x_i) = -r_i$ ,  $1 \leq i \leq n$ , i  $d(y_j) = c_j$ ,  $1 \leq j \leq n$ .

$\mathcal{N}$  té  $O(n)$  vèrtexs i  $O(n^2)$  arestes.

Si existeix un arrodoniment d' $A$ ,  $\mathcal{N}$  té una circulació amb valors enters (0,1).

- Sigi  $B$  un arrodoniment d' $A$ , definim una nova matriu  $D$  on

$$d_{ij} = \begin{cases} 1 & \text{si } b_{ij} > a_{ij} \\ 0 & \text{altrament} \end{cases}$$

- Com  $B$  es un arrodoniment,  $\sum_j d_{ij} = r_i$  i  $\sum_i d_{ij} = c_i$ .
- Llavors, el flux  $f(i,j) = d_{ij}$  és una circulació a  $\mathcal{N}$ .

Si  $\mathcal{N}$  té una circulació amb valors enters  $(0,1)$ , existeix un arrodoniment d' $A$ .

- Sigi  $f$  una circulació a  $\mathcal{N}$ ,
- definim la matriu  $B$  com

$$b_{i,j} = \begin{cases} a_{ij} & \text{si } a_{ij} \in \mathbb{Z} \\ \lceil a_{ij} \rceil & \text{si } a_{ij} \notin \mathbb{Z} \text{ i } f(i,j) = 1 \\ \lfloor a_{ij} \rfloor & \text{altrament} \end{cases}$$

- Com  $f$  es una circulació,  $\sum_j b_{ij} = \sum_j a_{ij}$  i  $\sum_i b_{ij} = \sum_i a_{ij}$ .
- Llavors,  $B$  és un arrodoniment vàlid d' $A$ .

La construcció de  $\mathcal{N}$  té una complexitat de  $O(n^2)$ .

Ford-Fulkerson funciona en  $O(D|E|)$ , on  $D$  és la suma de les demandes positives, i.e.  $D = \sum r_i = O(n^2)$  i com que  $|E| = O(n^2)$ , el nombre total de passos és  $O(n^4)$ .

Circulation  
Demands  
Lower bounds

Examples



Survey design

Arrodoniment amb  
restriccions

Image segmentation

# Pixels and digital image

- In digital imaging, a **pixel** is the smallest controllable element of a picture represented on the screen.
- Digital images are represented by a **raster graphics image**, a dot matrix data structure representing rectangular grid of pixels, or points of color
- The address of a pixel corresponds to its physical coordinates.



# Image segmentation

Given a set of pixels classify each pixel as part of the main object or as part of the background.

Important problem in different techniques for image processing.



Circulation  
Demands  
Lower bounds

Examples

Survey design


Arrondissement amb  
restrictions

Image segmentation



# Foreground/background segmentation

- We aim to **label each pixel as belonging to the foreground or the background**
- Picture pixels as a grid of dots.
- Define the undirected graph  $G = (V, E)$ , where,  $V$  = set pixels in image,  $E$  = pairs of neighbors of pixels (in the grid)



# Foreground/background segmentation

Given information:

- For each pixel  $i$ ,  $a_i \geq 0$  is likelihood that  $i$  is in the foreground and  $b_i \geq 0$  is likelihood that  $i$  is in the background.
- For each  $(i, j)$  of neighboring pixels, there is a separation penalty  $p_{ij} \geq 0$  for placing one in the foreground and the other in the background.

# Foreground/background segmentation

## Goals:

- For  $i$  isolated, if  $a_i > b_i$  we prefer to label  $i$  as foreground (otherwise we label  $i$  as background)
- If many neighbors of  $i$  are labeled foreground we prefer to label  $i$  as foreground. This makes the labeling **smoother** by minimizing the amount of foreground/background

Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrondissement amb  
restrictions

Image segmentation

# Foreground/background segmentation

## Goals:

- For  $i$  isolated, if  $a_i > b_i$  we prefer to label  $i$  as foreground (otherwise we label  $i$  as background)
- If many neighbors of  $i$  are labeled foreground we prefer to label  $i$  as foreground. This makes the labeling **smoother** by minimizing the amount of foreground/background

We want to partition  $V$  into  $A$  (set of foreground pixels) and  $B$  (set of background pixels), such that we maximize the objective function:

$$\sum_{i \in A} a_i + \sum_{j \in B} b_j - \sum_{\{(i,j) \in E, i \in A, j \in B\}} p_{ij}$$

# Formulate as a min-cut problem

Segmentation has the flavor of a cut problem, but

- it is a **maximization** different than the min-cut,
- $G$  is undirected,
- it does not have sink  $s$  and source  $t$  (but we can add them).

Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation

# From maximization to minimization

Recall we want to maximize

$$\underbrace{\sum_{i \in A} a_i + \sum_{j \in B} b_j - \sum_{\{(i,j) \in E, i \in A, j \in B\}} p_{ij}}_{(*)}$$

- Let  $Q = \sum_{i \in V} (a_i + b_i)$ , then

$$\sum_{i \in A} a_i + \sum_{j \in B} b_j = Q - (\sum_{i \in A} b_i + \sum_{j \in B} a_j)$$

$$(*) = Q - (\sum_{i \in A} b_i - \sum_{j \in B} a_j) - \sum_{\{(i,j) \in E, i \in A, j \in B\}} p_{ij}$$

- Therefore, maximizing  $(*)$  is equivalent to minimize

$$\sum_{i \in A} b_i + \sum_{j \in B} a_j + \sum_{\{(i,j) \in E, i \in A, j \in B\}} p_{ij}.$$


# Transforming $G$ into a network $\mathcal{N}$

We transform  $G = (V, E)$  to  $\mathcal{N} = (V', E', c, s, t)$  by

- Add a node  $s$  representing the foreground
- Add a node  $t$  representing the background
- $V' = V \cup \{s, t\}$
- For each  $(v, u) \in E$  create antiparallel directed edges  $(u, v)$  and  $(v, u)$  in  $E'$
- For each pixel  $i$  create directed edges  $(s, i)$  and  $(i, t)$
- $E' = \{(s, v) \cup (v, t)\}_{v \in E} \cup \{(u, v) \cup (v, u)\}_{(u, v) \in E}$

# The pixel graph $G$ and the graf $G' = (V', E')$


Circulation  
Demands  
Lower bounds  
  
Examples  
Survey design  
Arrondissement amb  
restrictions  
  
Image segmentation



$G$




$G'$



# Adding capacities to the edges of $\mathcal{N}$

- For each  $i \in V$ ,  $c(s, i) = a_i$ ,  $c(i, t) = b_i$
- For each  $(i, j) \in E$ ,  $c(i, j) = c(j, i) = p_{ij}$




# $(s, t)$ -cuts in $\mathcal{N}$

A  $(s, t)$ -cut  $(A', B')$  corresponds to a partition of the pixels into  $(A, B)$ , for  $A = A' - \{s\}$ , and  $B = B' - \{t\}\right).$

Circulation  
Demands  
Lower bounds  
**Examples**  
Survey design  
Arrondissement amb  
restrictions  
Image segmentation

- An edge  $(s, j)$  with  $j \in B$  contributes with  $a_j$  to  $c(A', B')$ ,
- An edge  $(i, t)$  where  $i \in A$  contributes with  $b_i$  to  $c(A', B')$ ,
- An edge  $(i, j)$  where  $i \in A$  and  $j \in B$  contributes with  $p_{ij}$  to  $c(A', B')$




# $(s, t)$ -cuts in $\mathcal{N}$

Therefore,

$$c(A', B') = \sum_{i \in A} b_i + \sum_{j \in B} a_j + \sum_{\{(i, j) \in E, i \in A, j \in B\}} p_{ij}$$

We want to find a cut with the min value of the above quantity, which is equivalent to solve the min-cut problem in  $\mathcal{N}$



# Cost

The cost of the algorithm is determined by the cost of finding a min cut in the associated network, i.e., as both vertices and edges are  $O(nm)$ , the cost of the algorithm is  $O((nm)^3)$ .

Circulation  
Demands  
Lower bounds

Examples

Survey design

Arrodoniment amb  
restrictions

Image segmentation