

# Emotion Analysis from Texts (Tutorial Proposal)

**Sanja Štajner**  
Karlsruhe, Germany  
stajner.sanja@gmail.com

**Roman Klinger**  
Institut für Maschinelle Sprachverarbeitung  
University of Stuttgart, Germany  
roman.klinger@ims.uni-stuttgart.de

## Abstract

Emotion analysis in text is an area of research that encompasses a set of various NLP tasks, including classification and regression settings, as well as structured prediction tasks like role labeling or stimulus detection. It is well-grounded in emotion psychology, which also influences the methodological NLP work. In this tutorial, we provide an overview on emotion psychology, relevant existing resources for emotion analysis, and classification methods. We further discuss appraisal theories and how events can be interpreted regarding their presumably caused emotion and further briefly introduce emotion role labeling. In addition to these technical topics, we discuss the societal impact, provide ethical considerations, and give an overview on open topics in the field.

## 1 Description and Relevance

Automatic emotion detection in texts has been gaining popularity since 2010's (Acheampong et al., 2020). The systems for automatic emotion detection are often used for social media and public opinion analysis, e.g., with respect to climate change (Loureiro and Alló, 2020), or elections (Anstead and O'Loughlin, 2014). Automatic emotion detection systems are also envisioned to have an important role in building empathetic chatbots and virtual agents (Paiva et al., 2017; Rashkin et al., 2019; Lin et al., 2019b; Shin et al., 2019; Lin et al., 2019a; Ma et al., 2020). More importantly, emotion analysis could be used to aid suicide prevention (Pestian et al., 2012; Desmet and Hoste, 2013), and early depression detection (Deshpande and Rao, 2017).

In the computational linguistics (CL) research community, the most commonly used emotion models are Ekman's model (Ekman and Friesen, 1981) consisting of six basic emotions (*anger*, *disgust*, *fear*, *joy*, *sadness*, and *surprise*), and Plutchik's model (Plutchik, 1982), which is commonly used focusing on eight primary emotions (*anger*, *anticipation*, *disgust*, *fear*, *joy*, *sadness*, *surprise*,

and *trust*). However, some studies use only certain subsets of those emotions (e.g., Brynielsson et al., 2014), some use different emotion frameworks (Demszky et al., 2020), a customized emotion set (e.g., Mohammad et al., 2015; Bostan et al., 2020; Huguet Cabot et al., 2021), attitudes (Neviarouskaya et al., 2010), or appraisals (Troiano et al., 2023). Since 2005, over 15 datasets manually annotated for emotions has been compiled and made freely available. The majority of datasets is in English, but they cover a variety of domains and text types: Twitter data (Schuff et al., 2017; Mohammad et al., 2015); personal reports on emotional events (Scherer and Wallbott, 1994; Troiano et al., 2019); sentences from fairy tales (Alm et al., 2005); daily dialogs from websites for English language learners (Li et al., 2017); dialog utterances from the television sitcom Friends (Hsu et al., 2018); movie subtitles (Öhman et al., 2020); news headlines (Bostan et al., 2020; Strapparava and Mihalcea, 2007); and Reddit comments (Demszky et al., 2020; Huguet Cabot et al., 2021). The XED dataset (Öhman et al., 2020), a manually annotated dataset of movies subtitles in English and Finish has been extended to 35 further languages by annotation projection to the parallel sentences in those languages.

From the computational perspective, the research community has used a wide range of approaches for emotion detection and classification, e.g., traditional machine learning approaches that use emotion dictionaries (Mohammad et al., 2015), linear classifiers with various lexical, syntactic, semantic, and structural features (Alm et al., 2005), maximum entropy classifiers with bag-of-words as features (Bostan and Klinger, 2018), support vector machines and naïve Bayes classifiers with various lexical, syntactic, and semantic features (Brynielsson et al., 2014), CNN-based classifiers (Hsu et al., 2018), BERT-based classifiers (Demszky et al., 2020; Öhman et al., 2020), multi-

task learning (Huguet Cabot et al., 2021), zero-shot learning (Plaza-del Arco et al., 2022; Gebremichael Tesfagergish et al., 2022), and few-shot learning (Guibon et al., 2021). Given that different architectures were tested on different domains, text types, and class types and distributions, it is not clear which models should be considered state of the art. Commercial emotion analysis models commonly use either dictionary-based approaches (due to their domain customisation capabilities which do not require large amounts of labelled training data) or BERT-based models (due to their domain-agnostic adaptation capabilities in the case of sufficient amounts of labelled training data).

Since 2010's, CL research community has been exponentially increasing the effort in building models for recognising and discerning among Ekman's or Plutchik's basic emotions in texts (Acheampong et al., 2020), and building manually annotated datasets, despite of studies in emotion psychology which suggested that detecting emotions in text is difficult and unreliable (Plutchik, 2001; Lang, 2010). The CL studies have pointed out several challenges in emotion annotation in texts: missing context in short utterances (Öhman et al., 2020; Mohammad, 2012), non-literal meaning (Mohammad, 2012), different perspectives one may take, i.e., the reader's, writer's, or text's (Buechel and Hahn, 2017; Alm et al., 2005), and high subjectivity of the task (low inter-annotator agreements were found even among trained annotators (Alm et al., 2005; Schuff et al., 2017; Štajner, 2021)).

Despite the challenges noted in CL and psychological literature, many tools for emotion analysis are available without a thorough description of challenges and failure modes, e.g., Text2emotion<sup>1</sup> and NRCLex<sup>2</sup> Python libraries. A large number of for-profit companies offer emotion analysis from texts, either using pre-trained models, or customised models trained on clients' data, e.g., BytesView<sup>3</sup>, Komprehend<sup>4</sup>, IBM Watson Natural Language Understanding.<sup>5</sup> When using the paid emotion analysis APIs, the identification of failure modes on specific datasets or in specific applica-

tions, the risk of unintended harms and other ethical considerations are usually shifted to the company or the user of APIs. Those tasks then become extremely difficult given that companies that offer paid APIs do sometimes not disclose the model specifications and datasets the models were trained on.

This tutorial has several goals. First, it provides an overview of most commonly used emotion models and the background in psychology, their limitation and challenges from a psychological perspective as well as from computational linguistics/natural language processing perspective. Second, it provides an extensive overview of freely available emotion analysis datasets, their annotation strategies and limitations. Third, it provides an extensive overview and critical comparison of NLP models used for emotion analysis from texts, ranging from traditional machine learning classifiers based on emotion dictionaries to transformer-based classification systems and zero-shot and few-shot learning models. Finally, this tutorial aims at raising awareness about various ethical issues concerning emotion analysis and the still present challenges in emotion analysis of texts (the absence of standardized annotation and evaluation procedures, common failure modes, etc.) which need to be taken into account when using emotion analysis models in real-world applications to avoid unintended harms.

To provide the tutorial participants with a better understanding of the challenges in emotion analysis and help them get started with developing novel models for emotion analysis, we will implement (at the end of the second part of the tutorial) a small annotation exercise.

## 2 Type: cutting-edge

The first part of the tutorial is an introduction to emotion psychology and the use cases of emotion analysis. The second and third part of the tutorial, however, cover cutting-edge NLP research on emotion analysis.

## 3 Target Audience

This tutorial is well-suited for various audiences: junior and senior researches working on emotion annotation and evaluation of emotion detection models; junior and senior researches working on novel models for emotion analysis, especially those using deep-learning paradigms; industry practition-

<sup>1</sup><https://pypi.org/project/text2emotion/>

<sup>2</sup><https://pypi.org/project/NRCLex/>

<sup>3</sup><https://www.bytesview.com/emotion-analysis>

<sup>4</sup><https://komprehend.io/emotion-analysis>

<sup>5</sup><https://www.ibm.com/cloud/watson-natural-language-understanding>

ers who wish to better understand limitations of publicly available emotion analysis tools and models. There are no prerequisites for attending, although to support a complete understanding of the discussion about strengths and limitations of different computational models, a basic knowledge of commonly used non-neural and neural classifiers is recommended.

## 4 Tutorial Structure

This tutorial contains three thematic parts, each to be covered in a one-hour time slot. The first part introduces emotion models, findings of relevant psychological studies, and use cases. The second part focuses on existing datasets, identified annotations challenges, and strengths and weaknesses of the computational models which have been proposed so far for emotion classification. The third part covers the tasks of emotion role labeling and stimulus detection as well as the interpretation of events with appraisal theories. Further, it discusses some less commonly discussed but still relevant topics, open questions in emotion analysis from texts, relatedness to other NLP tasks, and ethical considerations for emotion analysis.

### Part 1: Foundations

- Emotion theories in psychology
- Emotion recognition reliability in vision and language and what we can expect in NLP
- Use cases and social impact

### Part 2: Coarse-grained Emotion Analysis

- Emotion classification resources
- Emotion intensity prediction resources
- Non-neural models
- Multi-task and transfer-based models
- Zero-shot and few-shot learning for emotion classification
- Interactive annotation exercise with data by participants

### Part 3: Fine-grained Emotion Analysis and Further Topics

- Event evaluation-based approaches (OCC model and appraisals)

- Emotion role labeling and stimulus/cause detection
- Open challenges in emotion analysis
- Relation to other NLP tasks (including personality profiling and hate speech detection)
- Ethical Considerations

## 5 Other People's Work

More than 90% of the work cited is not our work.

## 6 Diversity Considerations

**Data.** We will emphasize multilingual datasets and approaches wherever possible, e.g., the work of [Öhman et al. \(2020\)](#) who extended the manually annotated datasets to 35 other languages by annotation projection to the parallel sentences in those languages and showed that such projections lead to comparable classification results. We will cover a wide range of domains as mentioned in Section 1.

**Instructors.** The instructors come from different demographic groups. The tutorial is structured in a way that it is relevant for both junior and senior researches, as well as for researches from both academia and industry.

## 7 Reading List

Although no particular prior knowledge is necessary for attending the tutorial, we recommend the attendees which are new to the emotion analysis to read the following works from the references section:

- Peter J. Lang. 2010. Emotion and motivation: Toward consensus definitions and a common research purpose. *Emotion review* 2, 3:229–233.
- Robert Plutchik. 2001. The nature of emotions: Human emotions have deep evolutionary roots, a fact that may explain their complexity and provide tools for clinical practice. *American scientist* 89, 4:344–350.
- Laura Ana Maria Bostan and Roman Klinger. 2018. An analysis of annotated corpora for emotion classification in text. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 2104–2119.
- Emily Öhman, Marc Pàmies, Kaisla Kajava, and Jörg Tiedemann. 2020. XED: A multilingual dataset for sentiment analysis and

emotion detection. In Proceedings of the 28th International Conference on Computational Linguistics, pages 6542–6552.

## 8 Instructors' Research Interests and Areas of Expertise

**Sanja Štajner** has over 13 years of research experience across academia and industry on various psycholinguistic topics in NLP. The last four years, she has led and participated in industry-oriented projects that combined psychology and NLP focusing on sentiment analysis, emotion detection, personality modelling, and mental health assessment. Sanja served as a COLING 2018 area chair for psycholinguistics and cognitive modelling track, and an ACL 2022 demo chair. She has experience as tutorial presenter (COLING 2018, AIST 2018, RANLP 2017) for international audiences and as a lecturer at Masters and PhD levels.

**Roman Klinger** is senior lecturer at Stuttgart University, where he teaches courses on Emotion Analysis since 2016 (see <https://www.emotionanalysis.de/>). He has been principal investigator on several externally funded projects with focus on emotion analysis. Roman served as senior area chair for sentiment analysis and argumentation mining at ACL 2022 and EACL 2021, and is senior area chair for language resources and evaluation at EACL 2023. He is also action editor of ACL Rolling Review 2021–2022. He was organizer of the WASSA workshop (on Computational Approaches to Subjectivity, Sentiment and Social Media Analysis) in 2018, 2019, and 2022.

## 9 Audience Size

Due to the increased interest in emotion analysis in recent years, we expect 50-80 attendees.

## 10 Venues

If held online, any of the venues is suitable. If held in person, due to the travel costs, the preferred venue is EACL. Thematically, EACL and ACL are better suited than EMNLP. The tutorial aligns with the special theme of the ACL conference.

## 11 Special Requirements: none

## 12 Tutorial Materials

All tutorial materials will be made publicly available and can be shared.

## 13 Ethics Statement

One of the main goals of the tutorial is to raise awareness about open challenges in emotion analysis which can lead to possible unintended harms and ethical issues with models commonly used for emotion analysis in real-world applications.

## Acknowledgements

Roman Klinger's work is partially funded by the German Research Council (DFG), project "Computational Event Analysis based on Appraisal Theories for Emotion Analysis" (CEAT, project number KL 2869/1-2).

## References

- Francisca Adoma Acheampong, Chen Wenyu, and Henry Nunoo-Mensah. 2020. [Text-based emotion detection: Advances, challenges, and opportunities](#). *Engineering Reports*.
- Cecilia Ovesdotter Alm, Dan Roth, and Richard Sproat. 2005. [Emotions from text: Machine learning for text-based emotion prediction](#). In *Proceedings of Human Language Technology Conference and Conference on Empirical Methods in Natural Language Processing*, pages 579–586, Vancouver, British Columbia, Canada. Association for Computational Linguistics.
- Nick Anstead and Ben O'Loughlin. 2014. [Social Media Analysis and Public Opinion: The 2010 UK General Election](#). *Journal of Computer-Mediated Communication*, 20(2):204–220.
- Laura Ana Maria Bostan, Evgeny Kim, and Roman Klinger. 2020. [GoodNewsEveryone: A corpus of news headlines annotated with emotions, semantic roles, and reader perception](#). In *Proceedings of the 12th Language Resources and Evaluation Conference*, pages 1554–1566, Marseille, France.
- Laura Ana Maria Bostan and Roman Klinger. 2018. [An analysis of annotated corpora for emotion classification in text](#). In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 2104–2119, Santa Fe, New Mexico, USA.
- Joel Brynielsson, Fredrik Johansson, Carl Jonsson, and Anders Westling. 2014. [Emotion classification of social media posts for estimating people's reactions to communicated alert messages during crises](#). *Secur. Informatics*, 3(1):7.
- Sven Buechel and Udo Hahn. 2017. [Readers vs. writers vs. texts: Coping with different perspectives of text understanding in emotion annotation](#). In *Proceedings of the 11th Linguistic Annotation Workshop*, pages 1–12, Valencia, Spain. Association for Computational Linguistics.



- Dorottya Demszy, Dana Movshovitz-Attias, Jeongwoo Ko, Alan Cowen, Gaurav Nemade, and Sujith Ravi. 2020. *GoEmotions: A dataset of fine-grained emotions*. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4040–4054, Online. Association for Computational Linguistics.
- Mandar Deshpande and Vignesh Rao. 2017. *Depression detection using emotion artificial intelligence*. In *2017 International Conference on Intelligent Sustainable Systems (ICISS)*, pages 858–862.
- Bart Desmet and Véronique Hoste. 2013. *Emotion detection in suicide notes*. *Expert Systems with Applications*, 40(16):6351–6358.
- Paul Ekman and Wallace V. Friesen. 1981. *The Repertoire of Nonverbal Behavior: Categories, Origins, Usage, and Coding*, pages 57–106. De Gruyter Mouton, Berlin, Boston.
- Senait Gebremichael Tesfagergish, Jurgita Kapočiūtė-Dzikiene, and Robertas Damaševičius. 2022. *Zero-shot emotion detection for semi-supervised sentiment analysis using sentence transformers and ensemble learning*. *Applied Sciences*, 12:8662.
- Gaël Guibon, Matthieu Labeau, Hélène Flamein, Luce Lefevre, and Chloé Clavel. 2021. *Few-shot emotion recognition in conversation with sequential prototypical networks*. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6858–6870, Online and Punta Cana, Dominican Republic.
- Chao-Chun Hsu, Sheng-Yeh Chen, Chuan-Chun Kuo, Ting-Hao Huang, and Lun-Wei Ku. 2018. *Emotion-Lines: An emotion corpus of multi-party conversations*. In *Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018)*, Miyazaki, Japan.
- Pere-Lluís Huguet Cabot, David Abadi, Agneta Fischer, and Ekaterina Shutova. 2021. *Us vs. them: A dataset of populist attitudes, news bias and emotions*. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 1921–1945, Online.
- Peter J. Lang. 2010. Emotion and motivation: Toward consensus definitions and a common research purpose. *Emotion review* 2, 3:229–233.
- Yanran Li, Hui Su, Xiaoyu Shen, Wenjie Li, Ziqiang Cao, and Shuzi Niu. 2017. *DailyDialog: A manually labelled multi-turn dialogue dataset*. In *Proceedings of the Eighth International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 986–995, Taipei, Taiwan. Asian Federation of Natural Language Processing.
- Zhaojiang Lin, Andrea Madotto, Jamin Shin, Peng Xu, and Pascale Fung. 2019a. *Moel: Mixture of empathetic listeners*. *CoRR*, abs/1908.07687.
- Zhaojiang Lin, Peng Xu, Genta Indra Winata, Zihan Liu, and Pascale Fung. 2019b. *Caire: An end-to-end empathetic chatbot*. *CoRR*, abs/1907.12108.
- Maria L. Loureiro and Maria Alló. 2020. *Sensing climate change and energy issues: Sentiment and emotion analysis with social media in the u.k. and spain*. *Energy Policy*, 143:111490.
- Yukun Ma, Khanh Linh Nguyen, Frank Z. Xing, and Erik Cambria. 2020. *A survey on empathetic dialogue systems*. *Information Fusion*, 64:50–70.
- Saif Mohammad. 2012. *#emotional tweets*. In *\*SEM 2012: The First Joint Conference on Lexical and Computational Semantics – Volume 1: Proceedings of the main conference and the shared task, and Volume 2: Proceedings of the Sixth International Workshop on Semantic Evaluation (SemEval 2012)*, pages 246–255, Montréal, Canada. Association for Computational Linguistics.
- Saif M. Mohammad, Xiao-Dan Zhu, Svetlana Kiritchenko, and Joel D. Martin. 2015. Sentiment, emotion, purpose, and style in electoral tweets. *Information Processing and Management*, 51:480–499.
- Alena Neviarouskaya, Helmut Prendinger, and Mitsuru Ishizuka. 2010. *@AM: Textual attitude analysis model*. In *Proceedings of the NAACL HLT 2010 Workshop on Computational Approaches to Analysis and Generation of Emotion in Text*, pages 80–88, Los Angeles, CA.
- Emily Öhman, Marc Pàmies, Kaisla Kajava, and Jörg Tiedemann. 2020. *XED: A multilingual dataset for sentiment analysis and emotion detection*. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 6542–6552, Barcelona, Spain (Online). International Committee on Computational Linguistics.
- Ana Paiva, Iolanda Leite, Hana Boukricha, and Ipke Wachsmuth. 2017. *Empathy in virtual agents and robots: A survey*. *ACM Transactions on Interactive Intelligent Systems*, 7(3).
- John P. Pestian, Pawel Matykiewicz, Michelle Linngust, Brett South, Ozlem Uzuner, Jan Wiebe, Kevin Bretonnel Cohen, John Hurdle, and Christopher Brew. 2012. Sentiment analysis of suicide notes: A shared task. *Biomedical Informatics Insights*, 5:3–16.
- Flor Miriam Plaza-del Arco, María-Teresa Martín-Valdivia, and Roman Klinger. 2022. *Natural language inference prompts for zero-shot emotion classification in text across corpora*. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 6805–6817, Gyeongju, Republic of Korea.
- Robert Plutchik. 1982. A psychoevolutionary theory of emotions. *Social Science Information* 21, pages 529–553.

- Robert Plutchik. 2001. The nature of emotions: Human emotions have deep evolutionary roots, a fact that may explain their complexity and provide tools for clinical practice. *American scientist* 89, 4:344–350.
- Hannah Rashkin, Eric Michael Smith, Margaret Li, and Y-Lan Boureau. 2019. [Towards empathetic open-domain conversation models: A new benchmark and dataset](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5370–5381, Florence, Italy. Association for Computational Linguistics.
- K. Scherer and H. G. Wallbott. 1994. Evidence for universality and cultural variation of differential emotion response patterning. *Journal of personality and social psychology*, 66 2:310–28.
- Hendrik Schuff, Jeremy Barnes, Julian Mohme, Sebastian Padó, and Roman Klinger. 2017. [Annotation, modelling and analysis of fine-grained emotions on a stance and sentiment detection corpus](#). In *Proceedings of the 8th Workshop on Computational Approaches to Subjectivity, Sentiment and Social Media Analysis*, pages 13–23, Copenhagen, Denmark. Association for Computational Linguistics.
- Jamin Shin, Peng Xu, Andrea Madotto, and Pascale Fung. 2019. [Happybot: Generating empathetic dialogue responses by improving user experience look-ahead](#). *CoRR*, abs/1906.08487.
- Carlo Strapparava and Rada Mihalcea. 2007. [SemEval-2007 task 14: Affective text](#). In *Proceedings of the Fourth International Workshop on Semantic Evaluations (SemEval-2007)*, pages 70–74, Prague, Czech Republic.
- Enrica Troiano, Laura Oberländer, and Roman Klinger. 2023. [Dimensional modeling of emotions in text with appraisal theories: Corpus creation, annotation reliability, and prediction](#). *Computational Linguistics*, 49(1).
- Enrica Troiano, Sebastian Padó, and Roman Klinger. 2019. [Crowdsourcing and validating event-focused emotion corpora for German and English](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4005–4011, Florence, Italy. Association for Computational Linguistics.
- Sanja Štajner. 2021. Exploring Reliability of Gold Labels for Emotion Detection in Twitter. In *Proceedings of the 13th international conference on Recent Advances in Natural Language Processing (RANLP)*, pages 1350–1359.