



## Submittal Data Sheet

2.0T Cased Upflow/Downflow R-32 Coil with EEV

CAPEA2418B3

### STANDARD FEATURES

- All-Aluminum evaporator coil
- Optimized for use with R-32 refrigerant including circuits and manifolds
- R-32 sensor designed for the life span of the coil
- Factory-installed electronic expansion valve (EEV) for precise refrigerant control - Compatibility with Daikin One+ smart thermostat and other Daikin communicating equipment - Cooling and heat pump applications - Fault recall of six most recent faults
- Standardized copper suction tube stub length
- 21" depth for easier attic access
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Rust resistant, thermoplastic drain pans featuring a low water-retention design
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- Drain pan rails designed to remove and reposition coils with ease without compromising structural integrity
- UV-resistant drain pan
- AHRI certified; ETL listed



### CABINET FEATURES

- Single front access panel Foil-faced insulation covers the internal casing to reduce cabinet condensation Galvanized, leather grain-embossed finish



**Submittal Data Sheet**  
2.0T Cased Upflow/Downflow R-32 Coil with EEV  
CAPEA2418B3

PERFORMANCE

|                   |             |                                      |                                               |
|-------------------|-------------|--------------------------------------|-----------------------------------------------|
| Product Model No. | CAPEA2418B3 | Product Model Name:                  | 2.0T Cased Upflow/Downflow R-32 Coil with EEV |
| Type:             | Coil        | Cooling Capacity (Nominal) (Btu/hr): | 24,000                                        |

PRODUCT DETAILS

|                          |                |                                       |     |
|--------------------------|----------------|---------------------------------------|-----|
| Dimensions (HxWxD) (in): | 18 x 17.5 x 21 | Suction Valve Connection Size (inch): | 3/4 |
| Net Weight (lb):         | 43             | Liquid Valve Connection Size (inch):  | 3/8 |
| Gross Weight (lb):       | 45             | Condensate Connection (inch):         | 3/4 |



**Submittal Data Sheet**  
2.0T Cased Upflow/Downflow R-32 Coil with EEV  
CAPEA2418B3

**DIMENSIONAL DRAWING**





**Submittal Data Sheet**  
2.0T Cased Upflow/Downflow R-32 Coil with EEV  
CAPEA2418B3

ACCESSORIES

| PART<br>NUMBER            | DESCRIPTION | INCLUDED |
|---------------------------|-------------|----------|
| No Accessories specified. |             |          |