



Submittal Data Sheet

3.0T Cased Upflow/Downflow R-32 Coil with EEV

CAPEA3626B3

STANDARD FEATURES

- All-Aluminum evaporator coil
- Optimized for use with R-32 refrigerant including circuits and manifolds
- R-32 sensor designed for the life span of the coil
- Factory-installed electronic expansion valve (EEV) for precise refrigerant control - Compatibility with Daikin One+ smart thermostat and other Daikin communicating equipment - Cooling and heat pump applications - Fault recall of six most recent faults
- Standardized copper suction tube stub length
- 21" depth for easier attic access
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Rust resistant, thermoplastic drain pans featuring a low water-retention design
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- Drain pan rails designed to remove and reposition coils with ease without compromising structural integrity
- UV-resistant drain pan
- AHRI certified; ETL listed



CABINET FEATURES

- Single front access panel Foil-faced insulation covers the internal casing to reduce cabinet condensation Galvanized, leather grain-embossed finish



Submittal Data Sheet
3.0T Cased Upflow/Downflow R-32 Coil with EEV
CAPEA3626B3

PERFORMANCE

Product Model No.	CAPEA3626B3	Product Model Name:	3.0T Cased Upflow/Downflow R-32 Coil with EEV
Type:	Coil	Cooling Capacity (Nominal) (Btu/hr):	36,000

PRODUCT DETAILS

Dimensions (HxWxD) (in):	26 x 20 x 21	Suction Valve Connection Size (inch):	7/8
Net Weight (lb):	55	Liquid Valve Connection Size (inch):	3/8
Gross Weight (lb):	57	Condensate Connection (inch):	3/4



Submittal Data Sheet
3.0T Cased Upflow/Downflow R-32 Coil with EEV
CAPEA3626B3

DIMENSIONAL DRAWING





Submittal Data Sheet
3.0T Cased Upflow/Downflow R-32 Coil with EEV
CAPEA3626B3

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
No Accessories specified.		