



Submittal Data Sheet

Two-Stage, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h
DD96TC1205DN

STANDARD FEATURES

- Compatible with the Daikin One+ smart thermostat and other Daikin communicating equipment
- Heavy-duty stainless-steel tubular heat exchanger
- Stainless-steel secondary heat exchanger
- Two-stage gas valve provides quiet, economical heating
- Durable Silicon Nitride igniter
- Quiet two-speed induced draft blower
- Self-diagnostic control board with constant memory fault code history output to dual 7-segment display
- Color-coded low-voltage terminals with provisions for electronic cleaner and humidifier
- Efficient and quiet variable-speed airflow system gently ramps up or down according to heating or cooling demand
- Multiple continuous fan speed options offer quiet circulation
- Auto-Comfort and enhanced dehumidification modes available
- All models comply with California 40 ng/J Low NOx emissions standard



CABINET FEATURES

- Designed for multi-position installation: Downflow, horizontal left or right
- Certified for direct vent (2-pipe) or non-direct vent (1-pipe)
- Convenient left or right connection for gas and electrical service
- Cabinet leakage (QLeak) less than 2%
- Heavy-gauge steel cabinet with durable finish
- Fully insulated heat exchanger and blower section
- Airtight solid bottom or side return with easy-cut tabs for effortless removal in bottom or inlet applications

NOTES

- Complete warranty details available from your local dealer or www.daikincomfort.com. To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), the 12-Year Unit Replacement Limited Warranty and the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Quebec.



Submittal Data Sheet

Two-Stage, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h
DD96TC1205DN

PERFORMANCE

Product Model No.	DD96TC1205DN	Product Model Name:	Two-Stage, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h
AFUE % Rating:	96%	Rated Heating Capacity (Btu/hr):	120,000
Temperature Rise Range (°F) (Low/High):	/	Furnace Input Capacity (Btu/hr):	120,000
Rated External Static Pressure - inWG:	0.5	Furnace Output Capacity (Btu/hr):	115,320
Blower Speed (RPM):	1,075	Blower Motor Rating (HP):	1
Blower Input Power (kW):	1.58	Blower Available AC Tonnage (L/H):	/

PRODUCT DETAILS

Power Supply (V/Hz/Ph):	115 / 60 / 1	Airflow Rate (High) (CFM):	2000
Min. Circuit Amps MCA (A):	13.8	Motor Type:	Variable Speed
Max Overcurrent Protection (MOP) (A):	20	Gas Valve Type:	Two Stage
Dimensions (HxWxD) (in):	34-1/2 x 24-1/2 x 28-7/8	Installation Configuration:	Downflow/Horizontal
Number of Burners:	6	Blower Size Diameter (inch):	11
Heating Vent Diameter in. (Min/Max):	/	Blower Size Width (inch):	11
Net Weight (lb):	158	Condensate Connection (inch):	
Gross Weight (lb):	160	Sound Pressure () (dBA):	



Submittal Data Sheet

Two-Stage, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h
DD96TC1205DN

DIMENSIONAL DRAWING





Submittal Data Sheet

Two-Stage, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h
DD96TC1205DN

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
No Accessories specified.		