



Submittal Data Sheet

Two-Stage, 9-Speed ECM Gas Furnace up to 96%FUE, 60k BTU/h, Upflow/Horizontal
DR96TN0603AN

STANDARD FEATURES

- Heavy-duty stainless-steel tubular heat exchanger
- Stainless-steel secondary heat exchanger
- Two-stage gas valve provides quiet, economical heating
- Durable Silicon Nitride igniter
- Quiet two-speed induced draft blower
- Self-diagnostic control board with constant memory fault history output to 3-digit 7 segment LED display and push buttons
- Color-coded low-voltage terminals with provisions for electronic air cleaner and humidifier
- Multi-speed (9-speed tap) ECM blower motor
- Multiple continuous fan speed options offer quiet air circulation
- Can no longer be installed in California's South Coast Air Quality Management District (SCAQMD) on or after October 1, 2019
- AHRI Certified
- ETL Listed



CABINET FEATURES

- Designed for multi-position installation: Upflow, horizontal left or right
- Certified for direct vent (2-pipe) or non-direct vent (1-pipe)
- Easy-to-install top venting with optional side venting
- Convenient left or right connection for gas and electrical service
- Cabinet air leakage (QLeak) = 2%
- Heavy-gauge steel cabinet with durable finish
- Fully insulated heat exchanger and blower section
- Airtight solid bottom or side return with easy-cut tabs for effortless removal in bottom or inlet applications

NOTES

- Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), the 6-Year Unit Replacement Limited Warranty and the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Quebec.



Submittal Data Sheet

Two-Stage, 9-Speed ECM Gas Furnace up to 96%FUE, 60k BTU/h, Upflow/Horizontal
DR96TN0603AN

PERFORMANCE

Product Model No.	DR96TN0603AN	Product Model Name:	Two-Stage, 9-Speed ECM Gas Furnace up to 96%FUE, 60k BTU/h, Upflow/Horizontal
AFUE % Rating:	96%	Rated Heating Capacity (Btu/hr):	
Temperature Rise Range (°F) (Low/High):	/	Furnace Input Capacity (Btu/hr):	60,000
Rated External Static Pressure - inWG:		Furnace Output Capacity (Btu/hr):	57,660
Blower Speed (RPM):		Blower Motor Rating (HP):	0.5
Blower Input Power (kW):		Blower Available AC Tonnage (L/H):	/

PRODUCT DETAILS

Power Supply (V/Hz/Ph):	115 / 60 / 1	Airflow Rate (High / Low) (CFM):	1,272 / 867
Min. Circuit Amps MCA (A):	7.8	Motor Type:	Multi-Speed
Max Overcurrent Protection (MOP) (A):	15	Gas Valve Type:	Two Stage
Dimensions (HxWxD) (in):	34-1/2 x 14 x 28-7/8	Installation Configuration:	Upflow/Horizontal
Number of Burners:		Blower Size Diameter (inch):	11
Heating Vent Diameter in. (Min/Max):	/	Blower Size Width (inch):	6
Net Weight (lb):	110	Condensate Connection (inch):	
Gross Weight (lb):	111	Sound Pressure () (dBA):	



Submittal Data Sheet

Two-Stage, 9-Speed ECM Gas Furnace up to 96%FUE, 60k BTU/h, Upflow/Horizontal
DR96TN0603AN

DIMENSIONAL DRAWING





Submittal Data Sheet

Two-Stage, 9-Speed ECM Gas Furnace up to 96%FUE, 60k BTU/h, Upflow/Horizontal
DR96TN0603AN

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
No Accessories specified.		