



## Submittal Data Sheet

Modulating, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h  
DR97MC1205DN

### STANDARD FEATURES

- Compatible with the Daikin One+ smart thermostat and other Daikin communicating equipment
- Heavy-duty stainless-steel tubular heat exchanger
- Stainless-steel secondary heat exchanger
- Self-calibrating modulating gas valve to configure for each installation
- Durable Silicon Nitride igniter
- Quiet variable-speed induced draft blower
- Self-diagnostic control board with constant memory fault code history output to dual 7-segment display
- Color-coded low-voltage terminals with provisions for electronic cleaner and humidifier
- Efficient and quiet variable-speed airflow system gently ramps up or down according to heating or cooling demand
- Multiple continuous fan speed options offer quiet circulation
- Auto-Comfort and enhanced dehumidification modes available
- All models comply with California 40 ng/J Low NOx emissions standard



### CABINET FEATURES

- Designed for multi-position installation. DR97MC: upflow, horizontal left or right
- Certified for direct vent (2-pipe) or non-direct vent (1-pipe)
- Easy-to-install top venting with optional side venting
- Convenient left or right connection for gas and electrical service
- Cabinet leakage (QLeak) less than 2%
- Heavy-gauge steel cabinet with durable finish
- Fully insulated heat exchanger and blower section
- Airtight solid bottom or side return with easy-cut tabs for effortless removal in bottom or inlet applications

### NOTES

- Complete warranty details available from your local dealer or [www.daikincomfort.com](http://www.daikincomfort.com). To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), the 12-Year Unit Replacement Limited Warranty and the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Quebec.



Submittal Data Sheet

Modulating, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h  
DR97MC1205DN

PERFORMANCE

|                                         |              |                                    |                                                                       |
|-----------------------------------------|--------------|------------------------------------|-----------------------------------------------------------------------|
| Product Model No.                       | DR97MC1205DN | Product Model Name:                | Modulating, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h |
| AFUE % Rating:                          | 97%          | Rated Heating Capacity (Btu/hr):   | 120,000                                                               |
| Temperature Rise Range (°F) (Low/High): | /            | Furnace Input Capacity (Btu/hr):   | 120,000                                                               |
| Rated External Static Pressure - inWG:  | 0.5          | Furnace Output Capacity (Btu/hr):  | 116,400                                                               |
| Blower Speed (RPM):                     | 1,075        | Blower Motor Rating (HP):          | 1                                                                     |
| Blower Input Power (kW):                | 1.69         | Blower Available AC Tonnage (L/H): | /                                                                     |

PRODUCT DETAILS

|                                       |                          |                               |                   |
|---------------------------------------|--------------------------|-------------------------------|-------------------|
| Power Supply (V/Hz/Ph):               | 115 / 60 / 1             | Airflow Rate (High) (CFM):    | 2000              |
| Min. Circuit Amps MCA (A):            | 14.4                     | Motor Type:                   | Variable Speed    |
| Max Overcurrent Protection (MOP) (A): | 25                       | Gas Valve Type:               | Modulating        |
| Dimensions (HxWxD) (in):              | 34-1/2 x 24-1/2 x 28-7/8 | Installation Configuration:   | Upflow/Horizontal |
| Number of Burners:                    | 6                        | Blower Size Diameter (inch):  | 11                |
| Heating Vent Diameter in. (Min/Max):  | /                        | Blower Size Width (inch):     | 11                |
| Net Weight (lb):                      | 157                      | Condensate Connection (inch): |                   |
| Gross Weight (lb):                    | 160                      | Sound Pressure () (dBA):      |                   |



**Submittal Data Sheet**

Modulating, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h  
DR97MC1205DN

**DIMENSIONAL DRAWING**





**Submittal Data Sheet**

Modulating, Variable-Speed ECM, communicating Gas Furnace, 120k BTU/h  
DR97MC1205DN

ACCESSORIES

| PART<br>NUMBER            | DESCRIPTION | INCLUDED |
|---------------------------|-------------|----------|
| No Accessories specified. |             |          |