



Submittal Data Sheet

15.2 SEER2 R-32 AC, 3 ton

DC5SEA3610

STANDARD FEATURES

- High efficiency scroll compressor
- High-density foam compressor sound blanket
- Advanced Copeland® CoreSense™ Technology
- Fully charged for 15' of tubing length
- Copper tube/ enhanced aluminum fin coil 5mm diameter
- Factory-installed filter drier
- Sweat connection service valves with easy access to gauge ports
- Enclosed contactor
- High-pressure switch
- Ground lug connection
- Capacitors with extended life
- AHRI Certified
- ETL Listed

CABINET FEATURES

- Removable grille-style top design compliant with UL 60335-2-40
- Venturi for increased velocity of airflow
- Custom Nickel Gray powder-paint finish
- 500-hour salt-spray tested
- Wire fan discharge grille
- Steel louver coil guard
- Rust-resistant coated screws
- Top and side maintenance access
- Single-panel access to controls with space provided for field-installed accessories
- When properly anchored, meets the 2023 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)





Submittal Data Sheet
15.2 SEER2 R-32 AC, 3 ton
DC5SEA3610

PERFORMANCE COMBINATION (HSVTC)		* VALUES SHOWN ARE FOR AHRI RATED HIGH SALES VOLUME TESTED	
Outdoor Unit Model No.	DC5SEA3610	Outdoor Unit Name:	15.2 SEER2 R-32 AC, 3 ton
Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 72	Rated Heating Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): /
* EER:		* EER2:	
* SEER:		* SEER2:	
* Rated Cooling Capacity (Btu/hr):			

OUTDOOR UNIT DETAILS			
Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Compressor Stage:	Single Stage
Min. Circuit Amps MCA (A):	17.8	Suction Valve Connection Size (inch):	7/8
Max Overcurrent Protection (MOP) (A):	30	Liquid Valve Connection Size (inch):	3/8
Running Load:	13.4	Sound Power (High) (dBA):	69
Refrigerant Type:	R-32	Cooling Operation Range (°F DB):	55 - 115
Holding Refrigerant Charge (ozs):	88	Heating Operation Range (°F DB):	-
Additional Charge (ounces/ft):		Max. Pipe Length (Vertical) (ft):	50
Pre-charge Piping (Length) (ft):	15	Min. Cooling Range w/Baffle (°F DB):	
Max. Pipe Length (Total) (ft):	79	Min. Heating Range w/Baffle (°F DB):	
Net Weight (lb):		Gross Weight (lb):	226
Dimensions (HxWxD) (in):	39.5 x 35-1/2 x 35.5		



Submittal Data Sheet
15.2 SEER2 R-32 AC, 3 ton
DC5SEA3610

DIMENSIONAL DRAWING





Submittal Data Sheet
15.2 SEER2 R-32 AC, 3 ton
DC5SEA3610

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
0130M00106	Disc Thermostat Crnkcs Htr Sw	No
0130R00000S	PRESSURE SWITCH KIT	No
0161R00128	Cap, Spiral Grill	No
0163R00006	Heater, Crankcase 230V, 40W	No
ABK-20	ANCHOR BRACKET KIT	No
ASC01A	ANTI-SHORT CYCLE KIT	No
CSR-U-1	Compressor Saver - Hard Start Kit - 1 TO 3 Ton	No
FSK01A	Freeze-Stat Kit	No
LAKT01	Low Ambient Kit	No
LSK02A	SOLENOID KIT FOR REM	No