



Submittal Data Sheet

15.2 SEER2 R-32 AC, 5 ton

DC5SEA6010

STANDARD FEATURES

- High efficiency scroll compressor
- High-density foam compressor sound blanket
- Advanced Copeland® CoreSense™ Technology
- Fully charged for 15' of tubing length
- Copper tube/ enhanced aluminum fin coil 5mm diameter
- Factory-installed filter drier
- Sweat connection service valves with easy access to gauge ports
- Enclosed contactor
- High-pressure switch
- Ground lug connection
- Capacitors with extended life
- AHRI Certified
- ETL Listed

CABINET FEATURES

- Removable grille-style top design compliant with UL 60335-2-40
- Venturi for increased velocity of airflow
- Custom Nickel Gray powder-paint finish
- 500-hour salt-spray tested
- Wire fan discharge grille
- Steel louver coil guard
- Rust-resistant coated screws
- Top and side maintenance access
- Single-panel access to controls with space provided for field-installed accessories
- When properly anchored, meets the 2023 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)





Submittal Data Sheet
15.2 SEER2 R-32 AC, 5 ton
DC5SEA6010

PERFORMANCE COMBINATION (HSVTC)		* VALUES SHOWN ARE FOR AHRI RATED HIGH SALES VOLUME TESTED	
Outdoor Unit Model No.	DC5SEA6010	Outdoor Unit Name:	15.2 SEER2 R-32 AC, 5 ton
Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 72	Rated Heating Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): /
* EER:		* EER2:	
* SEER:		* SEER2:	
* Rated Cooling Capacity (Btu/hr):			

OUTDOOR UNIT DETAILS			
Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Compressor Stage:	Two Stage
Min. Circuit Amps MCA (A):	36.4	Suction Valve Connection Size (inch):	7/8
Max Overcurrent Protection (MOP) (A):	60	Liquid Valve Connection Size (inch):	3/8
Running Load:	27.1	Sound Power (High) (dBA):	74
Refrigerant Type:	R-32	Cooling Operation Range (°F DB):	55 - 115
Holding Refrigerant Charge (ozs):	167	Heating Operation Range (°F DB):	-
Additional Charge (ounces/ft):		Max. Pipe Length (Vertical) (ft):	50
Pre-charge Piping (Length) (ft):	15	Min. Cooling Range w/Baffle (°F DB):	
Max. Pipe Length (Total) (ft):	79	Min. Heating Range w/Baffle (°F DB):	
Net Weight (lb):		Gross Weight (lb):	300
Dimensions (HxWxD) (in):	41.625 x 35-1/2 x 35.5		



Submittal Data Sheet
15.2 SEER2 R-32 AC, 5 ton
DC5SEA6010

DIMENSIONAL DRAWING





Submittal Data Sheet
15.2 SEER2 R-32 AC, 5 ton
DC5SEA6010

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
0130R00000S	PRESSURE SWITCH KIT	No
ABK-20	ANCHOR BRACKET KIT	No
ASC01A	ANTI-SHORT CYCLE KIT	No
CSR-U-1	Compressor Saver - Hard Start Kit - 1 TO 3 Ton	No
FSK01A	Freeze-Stat Kit	No
LSK02A	SOLENOID KIT FOR REM	No