



Submittal Data Sheet

fit 16.2 s2 r32 inv-4t ac

DC6VSS4810

STANDARD FEATURES

- Daikin variable-speed swing compressors
- Quiet digitally commutated fan motor
- High-density compressor sound blanket
- Compatible with Daikin One+ smart thermostat and other Daikin communicating equipment
- Daikin control algorithmic logic
- In communicating mode, only two low-voltage wires to outdoor unit required
- Diagnostic indicator lights, seven-segment LED display, and fault code storage
- Daikin Inside intelligence for diagnostics
- Field-selectable boost mode increases compressor speed during unusually high loads
- Field-installed bi-flow filter drier
- Coil and ambient temperature sensors
- Suction pressure transducer
- Sweat connection service valves with easy access to gauge ports
- AHRI Certified; ETL Listed

CABINET FEATURES

- Heavy-gauge galvanized steel cabinet with grille-style sound control side design
- Custom Ivory white powder-paint finish
- High corrosion-resistant (ZAM®), unpainted steel bottom frame and legs
- 500-hour salt-spray tested
- Wire fan discharge grille
- Top and side maintenance access
- When properly anchored, meets the 2023 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)





Submittal Data Sheet

fit 16.2 s2 r32 inv-4t ac
DC6VSS4810

PERFORMANCE COMBINATION (HSVTC) * VALUES SHOWN ARE FOR AHRI RATED HIGH SALES VOLUME TESTED

Outdoor Unit Model No.	DC6VSS4810	Outdoor Unit Name:	fit 16.2 s2 r32 inv-4t ac
Rated Cooling Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): 95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): /
* EER:		* EER2:	9.00
* SEER:		* SEER2:	17.00
* Rated Cooling Capacity (Btu/hr):	45,500		


OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Compressor Stage:	Inverter
Min. Circuit Amps MCA (A):	31.8	Suction Valve Connection Size (inch):	7/8
Max Overcurrent Protection (MOP) (A):	35	Liquid Valve Connection Size (inch):	3/8
Fan/Compressor Drive Input:	25.4	Sound Power (High) (dBA):	72
Refrigerant Type:	R-32	Cooling Operation Range (°F DB):	0 - 115
Holding Refrigerant Charge (ozs):	100	Heating Operation Range (°F DB):	-
Additional Charge (ounces/ft):		Max. Pipe Length (Vertical) (ft):	90
Pre-charge Piping (Length) (ft):	15	Min. Cooling Range w/Baffle (°F DB):	
Max. Pipe Length (Total) (ft):	100	Min. Heating Range w/Baffle (°F DB):	
Net Weight (lb):	163	Gross Weight (lb):	194
Dimensions (HxWxD) (in):	39 x 37 x 12.625		

Submittal Data Sheet fit 16.2 s2 r32 inv-4t ac DC6VSS4810

DIMENSIONAL DRAWING

MODEL	DIMENSIONS		
	W"	D"	H"
DC6VSS4210A*	37	12 $\frac{1}{2}$	39
DC6VSS4810A*	37	12 $\frac{1}{2}$	39
DC6VSS6010A*	37	12 $\frac{1}{2}$	39



UNIT : inch (mm)



Submittal Data Sheet
fit 16.2 s2 r32 inv-4t ac
DC6VSS4810

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
130-DK-008	Hail Guard	No
DACA-WB-3	Powder-Coated Wall-Mounted Bracket	No
DSEN-HAQA	Daikin One Home Air Monitor	No
KPW5G112	Air Adjustment Grille/ Wind Baffle	No