



Submittal Data Sheet
R-32 Daikin 1.25 Ton Floor Mounted System
FVXV15AVJUT9- RXP15AVJU9

INDOOR UNIT



OUTDOOR UNIT





Submittal Data Sheet

R-32 Daikin 1.25 Ton Floor Mounted System

FVXV15AVJUT9- RXP15AVJU9

SYSTEM PERFORMANCE

Indoor Unit Model No.	FVXV15AVJUT9	Indoor Unit Name:	R-32 1.25 Ton Floor Mounted Indoor Unit
Outdoor Unit Model No.	RXP15AVJU9	Outdoor Unit Name:	Daikin Aurora R-32 1.25 Ton Heat Pump Outdoor unit
Rated Cooling Capacity (Btu/hr):	15,000	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Sensible Capacity (Btu/hr):		Rated Piping Length(ft):	66
Max/Min Cooling Capacity (Btu/hr):	19,100 / 6,100	Rated Height Difference (ft):	0.00
Cooling Input Power (kW):	1.350	Heating Input Power (kW):	1.85
SEER2 (Non-Ducted/Ducted):	19.50 /	HSPF2 (Non-Ducted/Ducted):	9.6 /
EER2 (Non-Ducted/Ducted):	12.00 /	Heating COP (Non-Ducted/Ducted):	1.8 /
Rated Heating Capacity (Btu/hr):	18,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Max/Min Heating Capacity (Btu/hr):	20,400 / 7,300		

SYSTEM DETAILS

Refrigerant Type:	R-32	Cooling Operation Range (°F DB):	50 - 115
Holding Refrigerant Charge (lbs):	3.04	Heating Operation Range (°F WB):	-14 - 64
Additional Charge (oz/ft):	0.22	Max. Pipe Length (Vertical) (ft):	66
Pre-charge Piping (Length) (ft):	49	Cooling Range w/Baffle (°F DB):	-
Max. Pipe Length (Total) (ft):	99		
Max Height Separation (Ind to Ind ft):	0		
Fan/Compressor Drive Input:	12.7		



Submittal Data Sheet
R-32 Daikin 1.25 Ton Floor Mounted System
FVXV15AVJUT9- RXP15AVJU9

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 3	Airflow Rate (H/M/L/SL) (CFM):	392/311/254/201
Power Supply Connections:		Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	23-5/8 x 29-1/2 x 9-3/8	Condensate Connection (inch):	
Ext. Static Pressure (Rated/Max) (inWg):	/	Sound Pressure (H/M/L/SL) (dBA):	46/40/36/30
Net Weight (lb):	40	Sound Power Level (dBA):	

DIMENSIONAL DRAWING - INDOOR UNIT



Submittal Data Sheet


R-32 Daikin 1.25 Ton Floor Mounted System
FVXV15AVJUT9- RXP15AVJU9

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Compressor Stage:	Inverter
Power Supply Connections:		Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	16.1	Airflow Rate (H/M) (CFM):	/2,383
Max Overcurrent Protection (MOP) (A):	20	Gas Pipe Connection (inch):	1/2
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):		Sound Pressure (H) (dBA):	55
Dimensions (HxWxD) (in):	29-1/2 x 34-1/4 x 12-5/8	Sound Power Level (dBA):	
Net Weight (lb):	127		

DIMENSIONAL DRAWING - OUTDOOR UNIT

RXP15/18AVJU9



3D150942



Submittal Data Sheet
R-32 Daikin 1.25 Ton Floor Mounted System
FVXV15AVJUT9- RXP15AVJU9

INDOOR ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
BRC073A6	Wired Remote Controller (Requires Additional Wire Harness)	No
DCS302C71	Centralized Controller	No
DST301BA61	Schedule Timer	No
KAF970A46	Titanium apatite photocatalytic air-purifying filter WITHOUT frame	No
KER087A41	S21 conversion connector	No
KRP928BB2S	RA Interface Adaptor for DIII-Net -	No

OUTDOOR ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
KEH064A41	Drain Pan Heater	No
KKG063A44	Back Protection Wire Net	No
KKP937A4	Drain Plug for OD Unit	Yes
KPS063A41	Snow hood (intake side plate) (15, 18 & 24)	No
KPS063A44	Snow hood (intake rear plate) (15,18 & 24)	No
KPS063A47	Snow hood (outlet) (15, 18 & 24)	No
KPW063B4	Air direction adjustment grille	No